

U.S. Navy PARTY NO. 195 PROSPECT ZONE-A-DET-4 COUNTY NOR-SLP STATE ALASKA COUNTRY U.S.A LEFT STORAGE 7:00 ARRIVED FIELD 8:00 LEFT FIELD 8:00 ARRIVED STORAGE 9:00 DATE 2-APR 74 OBSERVER Scott PAGE 1

LINE	SP PROFILE	REEL NUMBER	FILE NUMBER	SHOT	PLAY BACK	TIME	SHOT			SPREAD				TAPE			GAIN						FILTERS			REMARKS								
							SIZE	TOP	NO CAPS	DE CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CWP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH
																	1-4/24	5-8	9-12	13-16	17-20	21-24				FREQ.		SLOPE	IN	OUT				
10	1	F2	148	1	DPB		50	75	2	A	165	EM	A	10'	0	99/96	1	X	55sec	AGC	66	66	66	66	66	66	90	100	100	124	8	36	OUT	INSTS @ 80-10 set up
	2		149	2			50	75	2	A						99/96	1	X			66	66	66	66	60	54		FIRST	768			54-48-42-40-48-54		
	3		150	3			50	75	2							99/96	1	X			66	66	66	60	54	48			768			48-42-42-48-54-60		
	4		151	4			50	75	2							99/96	1		Normal shot		66	66	60	54	48	42			768			40-42-48-54-60-66		
	5		152	5			50	75	2							45/42	1		Normal shot													42-48-54-60-66-66		
	6		153	6			50	75	2							41/88	1																	
	7		154	7			50	75	2							37/84	1																	
	8		155	8			50	75	2							33/80	1																	
	9		156	9			50	75	2							29/76	1																	
	10		157	10			50	75	2							25/72	1																	
	11		158	11			50	70	2							21/68	1																	
	12		159	12			50	75	2							17/64	1																	
	13		160	13			50	75	2							15/62	2																	moved INSTS TO SP. 18
	14		161	14			50	75	2							11/88	2		hole blow															
	15		162	15			50	75	2							37/84	2																	
	16		163	16			50	55	2							33/80	2																	
	17		164	17			50	75	2							29/76	2																	
	18		165	18			50	75	2							25/72	2																	
	19		166	19			50	75	2							21/68	2																	

SEISMOMETER AND SPREAD INFORMATION				
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN
A	modified	9	152'	1st LINE
				GP. INT. 330
				SPREAD PATTERN 1st LINE SPLITS

SHOT CONFIGURATION
S. Hole Notes include

DFS III SYSTEM PARAMETERS:
GAIN CONSTANT 30 DB
UPPER SET LIMIT 75 %
LOWER SET LIMIT 75 %
FORMAT TYPE:
 9 TRACK 21 TRACK
GALVO LEVEL:
1-24 15 DB AUX 15 DB
OTHER:

MISCELLANEOUS INFORMATION:
Had windy cable problems today, client was present!!

RECORDER FIELD DATA TI-13289-A

10-171-0-195

CLIENT: U.S. NAVY PARTY NO: 195 PROSPECT: Zond-A-Pat-4 COUNTY: North Shore STATE: ALASKA COUNTRY: U.S.A. LEFT STORAGE: 7:00 ARRIVED FIELD: 8:00 LEFT FIELD: 1:00 ARRIVED STORAGE: 6:30 DATE: 3-AA-74 OBSERVER: Scott PAGE: 1

LINE	IDENTIFICATION				PLAY BACK	TIME	SHOT				SPREAD				TAPE			GAIN						FILTERS			REMARKS								
	SP PROFILE	REEL NUMBER	FILE NUMBER	SHOT			SIZE	TOP	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.EIS. OFFSET	S.EIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH	
																						1-4/24	5-8	9-12	13-16/17-20/21-24	FREQ.						SLOPE	IN		OUT
10	20	FZ	176	1	DPB		50	75	2	A	165	East	10'	0	49/96	1	X	5 Sec	NGC	66.66	60.54	48.42	42	70	Fast 768	124	8	36	out	Not B. could not Reload					
	21		177	2			50	75	2						49/92	1					60	60.10	50.48	48		Tested before	5407???			Not B. " " "					
	22		178	3			50	75	2						41/88	1																			
	23		179	4			50	75	2						37/84	1																			
	24		180	5			50	75	2						37/80	1																			
	25		181	6			50	75	2						29/76	1																			
	26		182	7			50	75	2						24/72	1																			
	27		183	8			50	75	2						21/68	1																			
	28		184	9			50	75	2						17/64	1																			
	28		185	10			50	75	2						9/56	1																			
	28		186	11			50	75	2						8/88	2																Moved Int 575 - To Sp 36			

FZ 5/1/217

Initial Gain 1-24 all 42dB

Moved Int 575 - To Sp 36

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

SHOT NO.	SPREAD	DEPTH	CDP	SETUP

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 70 DB
 UPPER SET LIMIT 75 %
 LOWER SET LIMIT 25 %
 FORMAT TYPE:
 TRACK 21 TRACK
 GALVO LEVEL:
 1-24 15 DB AUX 15 DB
 OTHER:

MISCELLANEOUS INFORMATION:

SP. 29 STARS ICG. Coords
 are very noisy on the FEG.

CLIENT
US NAVY

PARTY NO. 195 PROSPECT ZONE-A-PET-4 COUNTY North Slope STATE Alaska COUNTRY U.S.A. LEFT STORAGE 7:00 ARRIVED FIELD 8:00 LEFT FIELD 4:30 ARRIVED STORAGE 5:00 DATE 5-11-74 OBSERVER SCOTT PAGE 1

LINE	IDENTIFICATION				PLAY BACK	TIME	SHOT				SPREAD				TAPE				GAIN				FILTERS		REMARKS								
	SP. PROFILE	REEL NUMBER	FILE NUMBER	SHOT			SIZE	TOP	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S. THIS OFFSET	NO. OF DEPT.	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)				FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT	NOTCH		
10	50	72	227	1	DOB		50	75	2	A	16S	East	A	10'	0	49/96	1	X	5500	AGC	66	60	54	45	42	90	Fast	760	124	8	36	OUT	56/44 Air Plane at Record
	51		228	2			50	75	2							45/92	1															57/45	
	52		229	3			50	75	2							41/88	1															58/46 WEAK SHOT??	
	53		230	4			50	75	2							37/84	1															59/47	
	54		231	5			50	75	2							33/80	1															60/48	
	55		232	6			50	75	2							29/76	1															61/49	
	56		233	7			50	75	2							25/72	1															62/50	
	57		234	8			50	75	2							21/68	1															63/51	
	58		235	9			50	75	2							17/64	1															64/52	
	59		236	10			50	75	2							13/60	1															65/53 1-8 dead, cable w/100k	
Tape	60	75	237	11			50	75	2							9/96	2															66/54 moved cts to 70 sp. 66	
	61		238	12			50	65	2							49/92	2															67/55	
	62		239	13			50	75	2							41/88	2															68/56	
	63		240	14			50	75	2							37/84	2															69/57	
	64		241	15			50	75	2							33/80	2															70/58	

Changed Tape

Z-514219 Z-SAR-879

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN
A	Standard	9	15M	in line	330	in line

SHOT CONFIGURATION

Sixty Shots in Line

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB
 UPPER SET LIMIT 75 %
 LOWER SET LIMIT 25 %
 FORMAT TYPE:
 TRACK 21 TRACK
 GALVO LEVEL:
 1-24 13 DB AUX 15 DB
 OTHER:

MISCELLANEOUS INFORMATION:

10-74-C-195

CIMENTY U.S. NAVY PARTY NO. 195 PROSPECT ZONG-A-PET-4 COUNTY STATE ALASKA COUNTRY LEFT STORAGE ARRIVED FIELD LEFT FIELD ARRIVED STORAGE DATE 7-APR-74 OBSERVER SCOTT PAGE 1

LINE	PROFILE	IDENTIFICATION		SHOT CAL	PLAY BACK	TIME	SHOT		SPREAD										TAPE		GAIN						FILTERS		REMARKS								
		REEL NUMBER	FILE NUMBER				SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S. P. SEIS. OFFSET	SEIS. DEPT.	CDP SWITCH	SETUP	SAMPLE RATE MS			RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	AUTO TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH IN/OUT	
																		1	2	4				1-4/24	5-8	9-12	13-16	17-20						21-24	FREQ.		SLOPE
10	87	13	282	1	RAR		50	75	2	A	165	East	A	10'	0	476	1	X	1600		AGC	42						42	40	Fast	768	124	8	36	81/93	SET UP TO ST 93 SHORT NOISE STOP 615	
	88		283	2			50	75	2							472	1		5500			48							768				82/94	Screwed up and did not connect Reset length switches! Wind blowing "BASK"			
	89		284	3			50	75	2							475	1												768				83/95				
	90		285	4			50	75	2							3784	1																84/96	Blowing HARD			
	91		286	5			50	75	2							3780	1																85/97				
	92		287	6			50	75	2							3776	1																86/98				
	93		288	7			50	75	2							3772	1																87/99				
<p>25/4219 25/4219</p> <p>Wind got TO BAD, UNABLE FOR MEN TO WORK OUTSIDE!!</p>																																					

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION						DFS III SYSTEM PARAMETERS:						MISCELLANEOUS INFORMATION:						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN							GAIN CONSTANT _____ DB UPPER SET LIMIT _____ % LOWER SET LIMIT _____ % FORMAT TYPE: <input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK GALVO LEVEL: 1-24 _____ DB AUX _____ DB OTHER:											

