

CLIENT		PARTY NO.		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE											
TETROTECH		195		BARROW		ALASKA		US		7:00		9:00		22/NOV/74		B. WEIR		1		REMARKS		File # 053 to 057		used for tests.											
LINE	PROFILE	IDENTIFICATION		SHOT CAL.	PLAY BACK	TIME	SIZE	SHOT		NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SPREAD		SEIS. DEPT.	CDP SWITCH	SETUP	TAPE				MODE	GAIN					RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FILTERS		NOTCH IN/OUT
		REEL NUMBER	FILE NUMBER					TOP	BOT.						SEIS. OFFSET	SEIS. DEPT.				SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	1-4/24		5-8	9-12	13-16	17-20	21-24				FINAL GAIN DB	LOW CUT FREQ.	
2X	101	672521	061	1A	MON DPB		25	50/60	2			NW	A	10'	-	11	1	✓	5500	AGL	42	36	30	24	18	12	90	FAST	AUTO 350	124	18	12	out.		
	102		062	2A	R.A.W		25	50/60	2							119																			
	103		063	3A			25	50/60	2							117																			
	104		064	4A			25	50/60	2		100'S			50'		125																			
	105		065	5A			25	50/60	2		100'S					133																			
	106		066	6A			25	50/60	2		100'S					141																			
	107		067	7A			25	50/60	2							149																			
	108		*100	8A			25	50/60	2							119		2																	
	109		101	9A	DPB		25	50/60	2							117																			
	110		102	10A	R.A.W		25	50/60	2							125																			
	111		103	11A			25	50/60	2							133																			
	112		104	12A			25	50/60	2							141																			
	113		105	13A			25	50/60	2							149																			
	114		106	14A			25	50/60	2							119		3																	
	115		107	15A			25	50/60	2							117																			
	116		110	16A			25	50/60	2							149																			
	117		111	17A			25	50/60	2							133																			
	118		112	18A			25	50/60	2							141																			
	119		113	19A			25	50/60	2							149																			

REMARKS File # 053 to 057 used for tests. File # 060 Test. T.B.

5 HOLE PATTERN

\* RECORD COUNT SKIPPED @ 10'S COUNT

CDP IN WRONG POSITION - FORGOT AFTER CHECKING SPREAD

END OF TAPE - 672521

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN
A	H2S 8N	9	15'	9 INLINE	110'	48 INLINE

SHOT CONFIGURATION

Code "B" 300% Roll Along Splits  
NW Progressing SE

No. 1 END      No. 24      No. 25

22 groups ← x 10' x 55' x 55' x 110' → 22 groups

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB  
UPPER SET LIMIT 25 %  
LOWER SET LIMIT 25 %  
FORMAT TYPE:  
 9 TRACK  1 TRACK  
GALVO LEVEL:  
148 15 DB AUX 15 DB  
OTHER:

MISCELLANEOUS INFORMATION:

CLIENT		PARTY NO.		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE													
TETROTELH		195		Barrow		Barrow		ALASKA		U.S.		9:00		9:00						23/11/74		R. W. Gier		1													
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN								FILTERS		REMARKS											
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	TOP BOT	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS. OFFSET	SEIS. DEPTH	COP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)								FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH	
																						1-4/24	5-8	9-12	13-16	17-20	21-24	FREQ.	SLOPE					IN	OUT		
LX	120	672522	120	1A	DPB		25	50/60	2													ACC	30	30	20	18	12	12	84	FAST	120	18	8	OUT	REMARKS FILE # 114 to 116 TESTS. FILE 117 TEST 10		
	121		121	2A	DPB		25	50/60	2																												
	122		122	3A	RAW		25	50/60	2																												
	123		123	4A			25	50/60	2																												
	124		124	5A			25	50/60	2																												
	125		125	6A			25	50/60	2																												
	126		126	7A	DPB		25	50/60	2																												
	127		127	8A	RAW		25	50/60	2																												
	128		130	9A			25	50/60	2																												
	129		131	10A			25	50/60	2																												
	130		132	11A			25	50/60	2																												
	131		134	12A			25	50/60	2																												
	132		135	13A			25	50/60	2																												
	133		136	14A			25	50/60	2																												
	134		137	15A	DPB		25	50/60	2																												
	135		140	16A	RAW		25	50/60	2																												
	136		141	17A			25	50/60	2																												
	137		142	18A			25	50/60	2																												

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN
						DAPME

SHOT CONFIGURATION

SAME
------

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB  
 UPPER SET LIMIT 62.5 %  
 LOWER SET LIMIT 25 %  
 FORMAT TYPE:  
 9 TRACK  21 TRACK  
 GALVO LEVEL:  
 148.15 DB AUX 15 DB  
 OTHER:

MISCELLANEOUS INFORMATION:

RECORDER FIELD DATA TI-13238-A

CLIENT: TETRA-TECH PARTY NO: 195 PROSPECT: BARROW COUNTY: BARROW STATE: ALASKA COUNTRY: US LEFT STORAGE: 7:00 ARRIVED FIELD: 8:30 LEFT FIELD: DATE: 25/NOV/88 OBSERVER: R. W. WICK

10R

Main data table with columns: IDENTIFICATION (LINE, PROFILE, REEL NUMBER, FILE NUMBER, SHOT CAL), SHOT (PLAY BACK, TIME, SIZE, TOP BOT), SPREAD (NO CAPS, CODE, SP. OFFSET, NO. 1 DIR., CODE, SEIS. OFFSET, SEIS. DEPTH), TAPE (CDP SWITCH, SETUP, SAMPLE RATE, RECORD LENGTH, PARITY ERRORS, MODE), GAIN (INITIAL GAIN, FINAL GAIN, RELEASE RATE, TRIP DELAY, HIGH CUT FREQ.), FILTERS (LOW CUT, SLOPE, NOTCH), and REMARKS.

WRITE ALL ONES TO FOOT

COMPLETE PICKUP

# 42 DEAD

# 3 REVERSED # 47 DEAD

SEISMOMETER AND SPREAD INFORMATION

CODE SEIS. TYPE NO./GP. INT. GROUP PATTERN GP. INT. SPREAD PATTERN

JAME

SHOT CONFIGURATION

SAME

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB UPPER SET LIMIT 62.5 % LOWER SET LIMIT 35 % FORMAT TYPE: [ ] 9 TRACK [x] 21 TRACK GALVO LEVEL: 148 15 DB AUX 15 DB OTHER:

MISCELLANEOUS INFORMATION:

WEATHER - COLD & WINDY