

RECORDER FIELD DATA TI-13238-A

CLIENT: U.S. NAVY PARTY NO: 195 PROSPECT: Pt BARROW COUNTY: STATE: Alaska COUNTRY: LEFT STORAGE: ARRIVED FIELD: LEFT FIELD: ARRIVED STORAGE: DATE: 4 MARCH 74 OBSERVER: B. Grand PAGE: 1 of 1

IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS		REMARKS																																	
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S. WEST OF	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE		INITIAL GAIN (DB)					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH																					
																							1-4/24	5-8	9-12	13-16	17-20					21-24	FREQ	SLOPE	IN	OUT																			
Amplifier had power supply go out & then regulator transistor went out down all day, parts had to be flown to field.																																																							

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

--

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT _____ DB
 UPPER SET LIMIT _____ %
 LOWER SET LIMIT _____ %
 FORMAT TYPE:
 9 TRACK 21 TRACK
 GALVO LEVEL:
 1-24 _____ DB AUX _____ DB
 OTHER:

MISCELLANEOUS INFORMATION:

U.S. NAVY

PARTY NO. 195 PROSPECT PT BARRROW

COUNTY

STATE ALASKA

COUNTRY U.S.A

LEFT STORAGE 700

ARRIVED FIELD 930

LEFT FIELD

ARRIVED STORAGE

DATE 12 MARCH 74

OBSERVER B. Orand


LINE	IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS			REMARKS							
	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	TOP BOT	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)				FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT	NOTCH IN/OUT
T	1	214	214	SHOT	DPB	1800	25	5/-	2	0	NE				1/49		X	5	OPERATE	42	→		70	FAST	256	124	8	18	-	START OF LINE	
	2	215				1805		53/60							1/49																
	3	216				1815									1/49																
	4	217				1825									1/49																
	5	218				1835									1/41																
	6	219				1845		2/-							1/33																
	7	220	221	222	No Record Caps Bad										1/25																
	8	223				1915									1/17																
	9	224				1925									1/9																
	10	225				1930									1/1																

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN
HSJ	12	20'	INLINE		110'	SP INT 880
14						INLINE

SHOT CONFIGURATION

55' from group center 24 & 25 to sp center
direction of travel NE



DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB
UPPER SET LIMIT 62.5 %
LOWER SET LIMIT 25 %
FORMAT TYPE:
 9 TRACK 21 TRACK
GALVO LEVEL:
1-24 15 DB AUX 15 DB
OTHER:

MISCELLANEOUS INFORMATION:

213 pulse

T-74-B-175

CLIENT: U.S. NAVY PARTY NO: 195 PROSPECT: PT BARROW COUNTY: ALASKA STATE: ALASKA LEFT STORAGE: 700 ARRIVED FIELD: 900 LEFT FIELD: ARRIVED STORAGE: DATE: 13 MARCH OBSERVER: B. Ornd PAGE: 1012

LINE	IDENTIFICATION				SHOT CAL	PLAY BACK	TIME	SIZE	SHOT			SPREAD				TAPE				GAIN					FILTERS			REMARKS							
	PROFILE	REEL NUMBER	FILE NUMBER	TOP					NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	D SEIS OFFSET	SOUTH DIR	CDP SWITCH	SETUP	SAMPLE RATE MS			RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)					RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH	
																		1	2	4				1-4	5-8	9-12	13-16					17-20	21-24		FREQ.
T	11	6	236		DPB	945	25	53/60	2		0	NE			1/41	X	S	OPERATE	42						90	FAST	ZSC AUTO ZSC	124	B	B	B				
	12		237			955								1/33																					
	13		238			1000								1/25																					
	14	3	239			1010								1/17																					
	15	3	240			1020								1/9																					
	16	3	241			1025								1/1																					
	17	3	242			1230								1/41																					
	18	3	243			1240								1/33																					
	19	3	244			1250								1/25																					
	20	3	245			1300								1/18																					
	21	3	246			1305								1/9																					
	22	3	247			1315								1/9																					
	23	3	248			1320								1/9																					
	24	3	249			1330								1/9																					

END OF LINE

SP24 end of line

SEISMOMETER AND SPREAD INFORMATION					
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.
HSJ		12	20	INLINE	110

SHOT CONFIGURATION
 55' from Sp to group centers 24 & 25
 SP 1
 SP 24

DFS III SYSTEM PARAMETERS:
 GAIN CONSTANT 30 DB
 UPPER SET LIMIT 62.5 %
 LOWER SET LIMIT 25 %
 FORMAT TYPE:
 9 TRACK 21 TRACK
 GALVO LEVEL:
 1-24 15 DB AUX 15 DB
 OTHER:

MISCELLANEOUS INFORMATION:
 226 -> 234 drd
 235 AGC up