RECORDED FIELD DATA TI-13238-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
TETRA TECH	195	BARROW	BARROW	ALASKA	U.S.	7:00	8:00			26 Nov 74	R. WEIR	1

IDENTIFICATION							SHOT					SPREAD						TAPE				GAIN						FILTERS				REMARKS
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL.	PLAY BACK	TIME	SIZE	TOP / BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	LOW CUT SLOPE	NOTCH IN / OUT	
"Z"	19	672523	200	1A	MON DPB		25 No.	50/60	2	B	—	SE	A	10'	—	1/1	1		✓		S3R	—	AGL	42	36	30	24	18	12	84	FAST	AUTO 256	124	18	18	OUT	FOR TESTS.
	18		201	2A	RAW		25	50/60	2							1/9						—		48	42	36	30	18	12								FILE # 177 TEST T.B.
	17		202	3A			25	50/60	2							1/17						—		54	48	36	30	18	12								
	16		203	4A			25	50/60	2							1/25						—		60	54	42	30	18	12								
	15		204	5A			25	50/60	2							1/33						—															
	14		205	6A			25	50/60	2							1/41						—															
	13		206	7A			25	50/60	2							1/49						—															
	12		207	8A			25	50/60	2							1/9	2					—	*	FILE COUNTER ERROR - ALSO HIGH PARITY - NO EOD													
	11		210	9A			25	50/60	2							1/17						—	—	HIGH PARITY - NO END of DATA —													
			211				WROTE "ALL ONES" FOR 5 SECONDS - DROPPING LOW ORDER BIT. - BAD WRITE AMP CARD.																														
	10		212	10A			25	50/60	2							1/25																						
	9		213	11A			25	50/60	2							1/33																						
	8		214	12A			25	50/60	2							1/41																						
					TAPE CHANGE																																		
	7	672524	215	13A			25	50/60	2							1/1	3																					# 16 DEAD
	6		216	14A			25	50/60	2							1/9								54	42	36	24	18	12								# 8 "
	5		~~217~~	~~15A~~	N.R.		~~25~~	~~50/60~~	~~2~~							1/17					NO RECORD			RADIO - INTERFERENCE & FIRED SHOT PREMATURELY													
	4		220	16A			25	50/60	2							1/25																						
	3		221	17A			25	50/60	2							1/33																						
	2		222	18A			25	50/60	2							1/41																						
	1		223	19A			25	50/60	2							1/49																						
				—			COMPLETED LINE "Z"																																	

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN
A	HSJ 8N ?	9	15'	9 INLINE	110'	48 INLINE

SHOT CONFIGURATION

CODE "B"

300% ROLL ALONG SPLITS

SE PROGRESSING NW



24 group TAIL SPREAD

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB

UPPER SET LIMIT ~~62.5~~ 55 %

LOWER SET LIMIT ~~35~~ 25 %

FORMAT TYPE:

☐ 9 TRACK ☑ 21 TRACK

GALVO LEVEL:

1-~~48~~ 15 DB AUX 18 DB

OTHER:

MISCELLANEOUS INFORMATION:

WEATHER - COLD