

CLIENT **U.S. NAVY** PARTY NO. **184** PROSPECT **N.P.R.-4** COUNTY **ALASKA** COUNTRY **U.S.A.** LEFT STORAGE **700** ARRIVED FIELD **900** LEFT FIELD **700** ARRIVED STORAGE **8:30** DATE **3-6-75** OBSERVER **F. Carlsenius** PAGE **10F**

IDENTIFICATION					SHOT					SPREAD					TAPE			GAIN					FILTERS			REMARKS										
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S. SEIS. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	SLOPE	NOTCH IN	NOTCH OUT		
40	1	523246	012	1	R/W		50	57/75	2			W	10		1/9	1		✓	5		OK	54	54	54	48	48	30	30	Fast	Auto	124	B	36	out	long drive to line - layout complete spread.	
	2		013	2			50	57/75	2			"	"		1/13			✓	"		"	30	48	48	54	54	"	"	"	"	"	"	"	"		
	3		014	3			50	57/75	2			"	"		1/17			✓	"		"					"	"	"	"	"	"	"	"	"		
	4		015	4			50	57/75	2			"	"		1/21			✓	"		"					"	"	"	"	"	"	"	"	"		
	5		016	5			50	57/75	2			"	"		1/25			✓	"		"					"	"	"	"	"	"	"	"	"		
	6		017	6			50	57/75	2			"	"		1/29			✓	"		"					"	"	"	"	"	"	"	"	"		
	7		020	7			50	57/75	2			"	"		1/33			✓	"		"					"	"	"	"	"	"	"	"	"		
	8		021	8			50	57/75	2			"	"		1/37			✓	"		"					"	"	"	"	"	"	"	"	"		
	9		022	9			50	57/75	2			"	"		1/41			✓	"		"					"	"	"	"	"	"	"	"	"		
	10		023	10			50	57/75	2			"	"		1/45			✓	"		"					"	"	"	"	"	"	"	"	"		
	11		024	11			50	57/75	2			"	"		1/49			✓	"		"					"	"	"	"	"	"	"	"	"		
	12		025	12			50	57/75	2			"	"		1/5	2		✓	"		"					"	"	"	"	"	"	"	"	"		Moved up.
	13		26	13			50	57/75	2			"	"		1/9	2		✓	"		"					"	"	"	"	"	"	"	"	"		"
	14		27	14			50	57/75	2			"	"		1/13			✓	"		"					"	"	"	"	"	"	"	"	"		"
	15		30	15			50	57/75	2	660E		"	50'		1/17			✓	"		"					"	"	"	"	"	"	"	"	"		offset 660' East. 44' 50'
	16		31	16			50	57/75	2			"	10'		1/21			✓	"		"					"	"	"	"	"	"	"	"	"		"
	17		32	17			50	57/75	2			"	"		1/25			✓	"		"					"	"	"	"	"	"	"	"	"		"
	18		33	18			50	57/75	2			"	"		1/29			✓	"		"					"	"	"	"	"	"	"	"	"		"
	19		34	19			50	57/75	2			"	"		1/33			✓	"		"					"	"	"	"	"	"	"	"	"		"
	20		35	20			50	57/75	2			"	"		1/37			✓	"		"					"	"	"	"	"	"	"	"	"		"
	21		36	21			50	57/75	2			"	"		1/41			✓	"		"					"	"	"	"	"	"	"	"	"		"
	22		37	22			50	57/75	2			"	"		1/45			✓	"		"					"	"	"	"	"	"	"	"	"		"
	23		040	23			50	57/75	2			"	"		1/49			✓	"		"					"	"	"	"	"	"	"	"	"		"

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION	

DPS III SYSTEM PARAMETERS:  
 GAIN CONSTANT 30 DB  
 UPPER SET LIMIT 62.5 %  
 LOWER SET LIMIT 18 %  
 FORMAT TYPE:  
 9 TRACK  21 TRACK  
 GALVO LEVEL:  
 1-24 18 DB AUX 15 DB  
 OTHER:

MISCELLANEOUS INFORMATION:  
 File #001-010 = D.R.D.  
 Test Module not working properly - Meter function switch gets hung up.  
 File #011 = Test T.S.  
 Continued trouble with timing lines in camera



CLIENT **U.S. NAVY** PARTY NO **184** PROSPECT **N.P.R.-4** COUNTY \_\_\_\_\_ STATE **ALASKA** COUNTRY **U.S.A.** LEFT STORAGE **700** ARRIVED FIELD **800** LEFT FIELD **630** ARRIVED STORAGE **730** DATE **3-7-75** OBSERVER **F. Carlsen** PAGE **1 of 1**

LINE	IDENTIFICATION				SHOT CAL.	PLAY BACK	TIME	SHOT				SPREAD				TAPE				GAIN										FILTERS		REMARKS					
	PROFILE	REEL NUMBER	FILE NUMBER	NO. CAPS				CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S. SEIS. OFFSET	S. DIR. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)										FINAL GAIN DB	RELEASE RATE		TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH IN/OUT
																				1-4/24	3-8	8-12	19-187	20-21	24	29	30	34	38						42	46	
40	24	523207	42	1	R/W		50	57	75	2		10		1	✓	5	OVER	54	54	54	48	48	30	90	East Amb	24	8	36	out	in 1/2 should be in 1/8 CDP in wrong position							
	25		43	2			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	26		44	3			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	27		45	4			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	28		46	5			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	29		47	6			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	30		50	7			50	57	75	2	175W	"	"		✓	"	"							"	"	"	"	"	"	"							
	31		51	8			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	32		52	9			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	33		53	10			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	34		54	11			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	35		55	12			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	36		56	13			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	37		57	14			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	38		60	15			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	39		61	16			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	40		62	17			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	41		63	18			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	42		64	19			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	43		65	20			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	44		66	21			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	45		67	22			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	46		70	23			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	47		71	24			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
*	48	523207	72	25			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	49		73	26			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	50		74	27			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							
	51		76	28			50	57	75	2		"	"		✓	"	"							"	"	"	"	"	"	"							

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

SP#23  
 21 22 23 24  
 130' 130' 130' 175'  
 SP#24  
 25 26 27 28  
 330' 330' 330' 175'  
 SP#25

Progressing East →

#1 group to the West.

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB  
 UPPER SET LIMIT 62.5 %  
 LOWER SET LIMIT 18 %  
 FORMAT TYPE:  
 9 TRACK  21 TRACK  
 GALVO LEVEL:  
 1-24 18 DB AUX 15 DB  
 OTHER:

MISCELLANEOUS INFORMATION:

File # 041 - Test T.B.  
 Did not record D.R.D.  
 on tape as Test Module  
 giving troubles either  
 Osc or Function Switch.

CLIENT **U.S. NAVY** PARTY NO. **184** PROSPECT **N.P.R.-4** COUNTY STATE **ALASKA** COUNTRY **U.S.A.** LEFT STORAGE **7<sup>30</sup>** ARRIVED FIELD **7<sup>50</sup>** LEFT FIELD ARRIVED STORAGE DATE **3-8-75** OBSERVER **F. Carlsenius** PAGE **10 of 2**

IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN						FILTERS			REMARKS													
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. DIR.	CODE	S.P. OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS				RECORD LENGTH	PARITY ERRORS	MODE		INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH IN/OUT
																		1	2	4	1-4/24					8-8	9-12	13-16	17-20	21-24	FREQ.					SLOPE		
40	59	52307	116	1	R/W		50	57.75	2			W	10'		1/5	1	✓	5					OVER.	54	54	54	48	48	30	90	65T	124	8	36	OUT.			
	60		117	2			50	57.75	2			"	"		1/9		✓	"					"	30	48	48	54	54	54	"	"	"	"	"	"	"	CDP switch 1/4 off 1/8	
	61		120	3			50	57.75	2			"	"		1/13		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
	62		121	4			50	57.75	2			"	"		1/17		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	63		122	5			50	57.75	2			"	"		1/21		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	64		123	6			50	57.75	2			"	"		1/25		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	65		124	7			50	57.75	2			"	"		1/29		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	66		125	8			50	57.75	2			"	"		1/33		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	67		126	9			50	57.75	2			"	"		1/37		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	68		127	10			50	57.75	2			"	"		1/41		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	69		130	11			50	57.75	2			"	"		1/45		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	70		131	12			50	57.75	2			"	"		1/49		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	71		132	13			50	57.75	2			"	"		1/5	2	✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	closed up long distance
	72		133	14			50	57.75	2			"	"		1/9		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	73		134	15			50	57.75	2			"	"		1/13		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	74		135	16			50	57.75	2			"	"		1/17		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	75		136	17			50	57.75	2			"	"		1/21		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	76		137	18			50	57.68	2			"	"		1/25		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	Creek Bottom.
	77		140	19			50	57.75	2			"	"		1/29		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	78		141	20			50	57.75	2			"	"		1/33		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	79		142	21			50	57.75	2			"	"		1/37		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	80		143	22			50	57.75	2			"	"		1/41		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	81		144	23			50	57.75	2			"	"		1/45		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	82		145	24			50	57.75	2			"	"		1/5	3	✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	Moved up. Damaged.
	83		146	25			50	57.75	2			"	"		1/9		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	84		147	26			50	57.75	2			"	"		1/13		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	85		150748	27			50	57.75	2			"	"		1/17		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
	86		151	28			50	57.75	2			"	"		1/21		✓	"					"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"

SEISMOMETER AND SPREAD INFORMATION					
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:  
 GAIN CONSTANT 30 DB  
 UPPER SET LIMIT 625 %  
 LOWER SET LIMIT 18 %  
 FORMAT TYPE:  
 9 TRACK  21 TRACK  
 GALVO LEVEL:  
 1-24 18 DB AUX 15 DB  
 OTHER:

MISCELLANEOUS INFORMATION:  
 File # 105-114 = D.R.D.  
 File # 115 = Test T.B.

CLIENT **U.S. NAVY** PARTY NO. **184** PROSPECT **N.P.R.-4** COUNTY STATE COUNTRY LEFT STORAGE ARRIVED FIELD LEFT FIELD ARRIVED STORAGE DATE **5-8-75** OBSERVER **F. Carlsenius** PAGE **2092**

LINE	IDENTIFICATION				PLAY BACK	TIME	SHOT				S.P. OFFSET	SPREAD				TAPE				GAIN						FILTERS			REMARKS								
	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL			SIZE	TOP	NO CAPS	CODE		NO. 1 DIR.	R. S. SURF. OFFSET	I. OF SURF. D.	CDP SWITCH	SETUP	SAMPLE RATE MS				RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH		
																	1	2	4	1-24				5-8	9-12	13-16	17-20	21-24					FINAL GAIN DB	FREQ.	SLOPE	IN	OUT
409	87	52307	152	29	R/W	50	57.75	2			W	10'	1.25	3	✓	5	OVER.	54	54	54	48	48	30	90	Fast	Auto	124	8	36	OUT							
	88		153	30		50	57.75	2			"	"	1.29		✓	"	"							"	"	"	"	"	"	"							
	89		154	31		50	57.75	2			"	"	1.33		✓	"	"							"	"	"	"	"	"	"							
	90		155	32		50	57.75	2			"	"	1.37		✓	"	"							"	"	"	"	"	"	"							
	91		156	33		50	57.75	2			"	"	1.41		✓	"	"							"	"	"	"	"	"	"							
	92		157	34		50	57.75	2			"	"	1.45		✓	"	"							"	"	"	"	"	"	"							
	93		160	35		50	57.75	2			"	"	1.49		✓	"	"							"	"	"	"	"	"	"							
*	94	52308	161	36		50	57.75	2			"	"	1.5	4	✓	"	4							"	"	"	"	"	"	"	Missing tape change (52308)						
	95		162	37		50	57.75	2			"	"	1.9		✓	"	"							"	"	"	"	"	"	"							
	96		163	38		50	57.75	2			"	"	1.13		✓	"	"							"	"	"	"	"	"	"							
	97		164	39		50	57.75	2			"	"	1.17		✓	"	"							"	"	"	"	"	"	"							
	98		165	40		50	57.75	2			"	"	1.21		✓	"	"							"	"	"	"	"	"	"							
	99		166	41		50	57.75	2			265W	"	1.25		✓	"	"							"	"	"	"	"	"	"	Offset 265' West.						
	100		167	42		50	57.75	2			"	"	1.29		✓	"	"							"	"	"	"	"	"	"							

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION		DFS III SYSTEM PARAMETERS:		MISCELLANEOUS INFORMATION:		
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN			GAIN CONSTANT	DB		
									UPPER SET LIMIT	%		
									LOWER SET LIMIT	%		
									FORMAT TYPE:			
									<input type="checkbox"/> 9 TRACK	<input type="checkbox"/> 21 TRACK		
									GALVO LEVEL:			
									1-24	DB	AUX	DB
									OTHER:			



CLIENT **U.S. NAVY** PARTY NO. **189** PROSPECT **N.P.R.-4** COUNTY \_\_\_\_\_ STATE **ALASKA** COUNTRY **U.S.A.** LEFT STORAGE **7<sup>30</sup>** ARRIVED FIELD **7<sup>30</sup>** LEFT FIELD **4<sup>30</sup>** ARRIVED STORAGE **600** DATE **3-9-75** OBSERVER **F. G. Iversenius** PAGE **109**

IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN						FILTERS			REMARKS												
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	TOP BOT	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.E. IS. OFFSET	S.E. IS. DIST.	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH			
																		1 2 4					1-4 24	3-8		9-12	13-16	17-20	21-24				FREQ.	SLOPE	IN OUT		
40 <sup>W</sup>	101	523208	201	1	R/W		50	57/75	2			N	10'			1/5	1	✓	5			DBR.	54	54	54	48	48	30	90	Fast	Auto	124	8	36	OUT		
	102		202	2			50	57/75	2			"	"			1/9		✓	"			"	30	78	48	54	54	54	"	"	"	"	"	"	"		
	103		203	3			50	57/75	2			"	"			1/13		✓	"			"							"	"	"	"	"	"	"		
	104		204	4			50	57/75	2			"	"			1/17		✓	"			"							"	"	"	"	"	"	"		
	105		205	5			50	57/75	2		660'E	"	"			1/21		✓	"			"							"	"	"	"	"	"	"	Offset 660' East.	
	106		206	6			50	57/75	2			"	"			1/25		✓	"			"							"	"	"	"	"	"	"	"	
	107		207	7			50	57/75	2			"	"			1/29		✓	"			"							"	"	"	"	"	"	"	"	
	108		210	8			50	57/75	2			"	"			1/33		✓	"			"							"	"	"	"	"	"	"	"	ICE HOLE!
	109		211	9			50	57/75	2			"	"			1/37		✓	"			"							"	"	"	"	"	"	"	"	ICE HOLE!
	110		212	10			50	57/75	2			"	"			1/41		✓	"			"							"	"	"	"	"	"	"	"	ICE HOLE!
	111		213	11			50	57/75	2		165'E	"	"			1/45		✓	"			"							"	"	"	"	"	"	"	"	Offset 165' East.
	112		214	12			50	57/75	2			"	"			1/49		✓	"			"							"	"	"	"	"	"	"	"	"
	113		215	13			50	57/75	2			"	"			1/5	2	✓	"			"							"	"	"	"	"	"	"	"	"
	114		216	14			50	57/75	2			"	"			1/9		✓	"			"							"	"	"	"	"	"	"	"	"
	115		217	15			50	57/75	2			"	"			1/13		✓	"			"							"	"	"	"	"	"	"	"	"
	116		220	16			50	57/75	2			"	"			1/17		✓	"			"							"	"	"	"	"	"	"	"	"
	117		221	17			50	57/75	2			"	"			1/21		✓	"			"							"	"	"	"	"	"	"	"	"
	118		222	18			50	57/75	2			"	"			1/25		✓	"			"							"	"	"	"	"	"	"	"	"
	119		223	19			50	57/75	2			"	"			1/29		✓	"			"							"	"	"	"	"	"	"	"	"
	120		224	20			50	57/75	2			"	"			1/33		✓	"			"							"	"	"	"	"	"	"	"	"
	121		225	21			50	57/75	2			"	"			1/37		✓	"			"							"	"	"	"	"	"	"	"	"
	122		226	22			50	57/75	2			"	"			1/41		✓	"			"							"	"	"	"	"	"	"	"	"
	123		227	23			50	57/75	2			"	"			1/45		✓	"			"							"	"	"	"	"	"	"	"	"
	124		230	24			50	57/75	2			"	"			1/49		✓	"			"							"	"	"	"	"	"	"	"	"
	125		231	25			50	57/75	2			"	"			1/49	3	✓	"			"							"	"	"	"	"	"	"	"	Moved up 1 shot point. END OF LINE - 21 Group tail - Spread.

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN	

DFS III SYSTEM PARAMETERS:  
 GAIN CONSTANT 30 DB  
 UPPER SET LIMIT 62.5 %  
 LOWER SET LIMIT 18 %  
 FORMAT TYPE:  
 9 TRACK  21 TRACK  
 GALVO LEVEL:  
 1-24 18 DB AUX 15 DB  
 OTHER:

MISCELLANEOUS INFORMATION:  
 File # 170-177 = D.R.D.  
 File # 200 = Test T.B.  
~~File # 200 = Test T.B.~~