

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																	
NAVY		195	NPR-4	BARROW	ALASKA	U.S.	2:00	11:00	9:00	9:00	9/3/75	R. WEIR	1																	
LINE	PROFILE	IDENTIFICATION		SHOT CAL	PLAY BACK	TIME	SIZE	SHOT		SPREAD				TAPE				GAIN					FILTERS		REMARKS					
		REEL NUMBER	FILE NUMBER					NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT

SEISMOMETER AND SPREAD INFORMATION				
CODE	SEIS. TYPE	NO./GP.	INT.	SPREAD PATTERN
				SAME

SHOT CONFIGURATION

SOUTH Progressing NORTH
#1 to the SOUTH

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB
 UPPER SET LIMIT 62.5%
 LOWER SET LIMIT 25%
 FORMAT TYPE:
 9 TRACK 21 TRACK
 GALVO LEVEL:
 1.48 21 DB AUX 15 DB
 OTHER:

MISCELLANEOUS INFORMATION:

PROBLEMS LAYING CABLE THROUGH RIVERS. 3 CROSSINGS IN A.M. PROBLEMS GETTING SHOOTING TRUCK GOING IN A.M.

REMARKS FROM #001 to 012 USED FOR TESTS 1

QUITE WINDY

REPLANTED #39

* NO FILE # 030 FILE # COUNTER SKIPPED

#48 DEAD

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																							
NAVY		195	NPR-4	BARROW	ALASKA	U.S.	7:00	7:30	8:00	8:30	6/19/65	R. WEIR	2 of 2																							
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS				REMARKS												
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH			
51	79	672565	147	29A	RAW	2:30	100	75/105	2			5		10'	1/5		4	✓	6000			AGC	42	42	42	42	36	15	90	MED	320	124	18	36	out	
	80		150	30A		2:40	100	75/105	2						1/9																					
	81		151	31A		2:50	100	75/105	2						1/13																					
	82		152	32A		3:05	100	75/105	2						1/21																					
	83		153	33A		3:15	100	75/105	2		165'N				1/21																					
	84		154	34A		3:25	100	75/105	2						1/25																					
	85		155	35A		3:25	100	75/105	2		200'N				1/29																					
	86		156	36A		3:45	100	75/105	2						1/33																					WAITING ON DRILLS
	87		157	37A		4:20	100	75/105	2						1/5		5						42	"	"	"	"	12	92							
	88		160	38A		4:40	100	75/105	2		170'S				1/9																					
	89		161	39A		4:50	100	75/105	2						1/13																					
	90		162	40A		6:00	100	75/105	2						1/17																					WAITING ON DRILLS
	91		163	41A		7:00	100	75/105	2						1/21																					

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:	
GAIN CONSTANT	_____ DB
UPPER SET LIMIT	_____ %
LOWER SET LIMIT	_____ %
FORMAT TYPE:	
<input type="checkbox"/> 9 TRACK	<input type="checkbox"/> 21 TRACK
GALVO LEVEL:	
1-24 _____ DB	AUX _____ DB
OTHER:	

MISCELLANEOUS INFORMATION:	

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																							
NAVY		195	NPR-4	BARROW	ALASKA	U.S.	7:00	7:30	8:00	8:30	6/20/65	R. W. Wier	1																							
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS		REMARKS														
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S. SEIS. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE		INITIAL GAIN (DB)					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH IN/OUT		
																			1 2 4				1-4/24	5-8	9-12	13-16	17-20	21-24		FREQ.	SLOPE					
51	51	62553	112	1A	MON 700	8:00	100	75/105	2			5	10'			1/5	1		✓	6 SEC	AW		12.42	12.42	12.42	12.42	12.42	12.42	90	MED	.512	129	8	36	out	
	52		113	2A	RAW	8:10	100	75/105	2							1/9																				
	53		114	3A		8:20	100	75/105	2							1/13																				
	54		115	4A		8:30	100	75/105	2							1/17																				
	55		116	5A		8:40	100	75/105	2							1/21																				
	56		117	6A		8:45	100	75/105	2							1/25																				
	57		120	7A		9:00	100	75/105	2							1/29																				
	58		121	8A		9:15	100	75/105	2							1/33																				
	59		123	9A		9:25	100	75/105	2							1/37																				
	60		124	10A		9:30	100	75/105	2							1/41																				
	61		125	11A		9:40	100	75/105	2							1/45																				
	62		126	12A		9:45	100	75/105	2							1/49																				
	63		127	13A		10:30	100	75/105	2							1/5	2																			
	64		130	14A		10:35	100	75/105	2							1/9																				
	65		131	15A		11:00	100	75/105	2							1/13																				
	66		132	16A		11:10	100	75/105	2							1/17																				
	67		133	17A		11:20	100	75/105	2							1/21																				
	68		134	18A		11:30	100	75/105	2							1/25																				
	69		135	19A		11:40	100	75/105	2							1/29																				
	70		138	20A		11:45	100	75/105	2							1/33																				
	71		137	21A		12:30	100	75/105	2							1/5	3																			
	72		140	22A		12:40	100	75/105	2							1/9																				
	73		141	23A		12:50	100	75/105	2							1/13																				
	74		142	24A		1:00	100	75/105	2							1/17																				
	75		143	25A		1:10	100	75/105	2							1/21																				
	76		144	26A		1:20	100	75/105	2							1/25																				
	77		145	27A		1:30	100	75/105	2							1/29																				
	78		146	28A		1:40	100	75/105	2							1/33																				

* No File # 120 (COUNTER SKIPPED)

* DIDN'T SEEM LIKE 100lbs.

* 47 DEAD

(CDP WRONG)

CAMP MOVING DOWN SPREAD

SEISMOMETER AND SPREAD INFORMATION					SHOT CONFIGURATION	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN
						SAME

DFS III SYSTEM PARAMETERS:
 GAIN CONSTANT _____ DB
 UPPER SET LIMIT _____ %
 LOWER SET LIMIT _____ %
 FORMER TYPE _____
 9 TRACK 21 TRACK
 GALVO LEVEL:
 1-24 _____ DB AUX _____ DB
 OTHER:

MISCELLANEOUS INFORMATION:

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																								
NAVY		1195	NPR-4	BARROW	ALASKA	U.S.	7:00	8:00	7:00	8:00	4-5-75	K. WEIR	10/1																								
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	SHOT		NO CAPS	CODE	S.P. OFFSET	SPREAD			NO. 1 DIR.	S.P. SEIS. OFFSET	S.P. DEPTH	CDP SWITCH	SETUP	TAPE				MODE	GAIN					RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FILTERS		NOTCH IN/OUT	REMARKS
								TOP	BOT.				RECORD LENGTH	PARITY ERRORS	INITIAL GAIN (DB)						FINAL GAIN DB	1-4/24	5-8	9-12		13-16	17-20	21-24	FREQ.	SLOPE							

SEISMO METER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN
41			077	29N	6:35	100
50			100	30N	6:45	100

SHOT CONFIGURATION	
1/29	1/35

DFS III SYSTEM PARAMETERS:
 GAIN CONSTANT _____ DB
 UPPER SET LIMIT _____ %
 LOWER SET LIMIT _____ %
 FORMAT TYPE:
 9 TRACK 21 TRACK
 GALVO LEVEL:
 1-24 _____ DB AUX _____ DB
 OTHER:

MISCELLANEOUS INFORMATION:

10
330
445

REMARKS
 File # 040 to 042
 used Full Tests.

47 DEAD
 # 42 "

46 DEAD
 # 42 "
 # 38 + # 47 DEAD
 # 34 DEAD (C HANLING BAD PHONES)

47 DEAD
 #

19 DEAD

Tape Channel

CLIENT		PARTY NO		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE												
NAVY		195		NPR-4		Barrow		ALASKA		U.S.A.		7:00		7:30		7:30		9:00		7/10/65		R. WEIR		1												
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS				REMARKS												
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	P. SEIS. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH		
																						1-24	3-6	9-12	13-16	17-20	21-24					FREQ.	SLOPE	IN	OUT	
51	92	622566	175	1A	MAN 206	8:40	150	75/105	2		5	10					1	✓	6sec	AGL	12	42	42	42	42	36	12	90	MED.	.320	129	8	36	ant.		
	93		176	2A	RAW	8:45	100	75/105	2																											
	94		177	3A		9:00	100	75/105	2																											
	95		200	4A		9:10	100	45/105	2																											
	96		201	5A		9:45	100	75/105	2																											
	97		202	6A		9:55	100	75/105	2																											
	98		203	7A		10:00	100	75/105	2																											
	99		204	8A		10:10	100	75/105	2																											
	100		205	9A		10:15	100	75/105	2																											
	101		206	10A		10:25	100	75/105	2																											
	102		207	11A		10:55	100	75/105	2																											
	103		210	12A		11:00	100	75/105	2																											
	104		211	13A		12:00	100	75/105	2																											
	105		212	14A		12:10	100	75/105	2																											
	106		213	15A		12:20	100	75/105	2																											
	107		214	16A		12:30	100	75/105	2																											
	108		215	17A		12:45	100	75/105	2																											
	109		216	18A		1:00	100	75/105	2																											
	110		217	19A		1:15	100	75/105	2																											
	111		220	20A		1:20	100	75/105	2																											
	112		221	21A		1:30	100	75/105	2																											
	113		222	22A		2:15	100	75/105	2																											
	114		223	23A		2:25	100	45/105	2																											
	115		224	24A		2:30	100	75/105	2																											
	116		225	25A		4:00	100	75/105	2																											
	117		226	26A		4:10	100	75/105	2																											
	118		227	27A		4:15	100	75/105	2																											
	119		230	28A		4:25	100	75/105	2																											

CHANGING GOOD TIMES

4 DEAD

45 DEAD

SHOOTING TENSE BECAUSE DEAD 1 1/2 hrs

SEISMOMETER AND SPREAD INFORMATION

SHOT CONFIGURATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SAME

DFS III SYSTEM PARAMETERS:
 GAIN CONSTANT 30 DB
 UPPER SET LIMIT 62.5 %
 LOWER SET LIMIT 25 %
 FORMAT TYPE:
 9 TRACK 21 TRACK
 GALVO LEVEL:
 148 21 DB AUX 15 DB
 OTHER:

MISCELLANEOUS INFORMATION:

CLIENT **NAVY** PARTY NO. PROSPECT **195 NPR-4** COUNTY **BARROW** STATE **ALASKA** COUNTRY **U.S.A.** LEFT STORAGE **7:00** ARRIVED FIELD **7:30** LEFT FIELD **7:30** ARRIVED STORAGE **9:00** DATE **7/10/75** OBSERVER **R. WEIR** PAGE **2 of 2**

LINE	PROFILE	IDENTIFICATION		SHOT	PLAY BACK	TIME	SIZE	SPREAD		NO. CAPS	CODE	S.P. OFFSET	NO. DIR.	CODE	S.P. SEIS. OFFSET	SEIS. DEPTH	COP SWITCH	SETUP	TAPE			GAIN						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FILTERS		REMARKS
		REEL NUMBER	FILE NUMBER					TOP	BOT.										SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)									LOW CUT	NOTCH	
		1	2	4	1-4/24	5-8	9-12	13-16	17-20	21-24	FREQ.	SLOPE	IN	OUT																				
51	120	62254	228	29"	RAW	4:30	500	65'	10'	2		5'	10'			1/41	4	✓	6502	AGL	42	42	42	42	36	12	90	AGC	.320/24	8	36	and		
	121		232	30"		4:40	100	75'		2						1/45																		
	122		233	31"		5:35	100	75'		2						1/48	5																	
	123		234	32"		5:45	100	75'		2						1/5																		
	124		255	33"		5:55	100	75'		2						1/9																		
	125		286	34"		6:05	100	75'		2						1/13																		
	126		257	35"		6:15	100	75'		2						1/17																		
	127		260	36"		6:25	100	75'		2						1/21																		
	128		261	37"		6:35	100	75'		2						1/25																		
	129		262	38"		6:45	100	75'		2						1/29																		
	130		263	39"		6:55	100	75'		2						1/33																		
	131		264	40"		7:00	100	75'		2						1/37																		

41 DEAD
* FILE COUNTER SKIPPED TWO DIGITS IN TENS COLUMN

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

SPREAD	DEPTH	NO. CAPS	CODE	S.P. OFFSET	NO. DIR.	CODE	S.P. SEIS. OFFSET	SEIS. DEPTH	COP SWITCH	SETUP

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT _____ DB

UPPER SET LIMIT _____ %

LOWER SET LIMIT _____ %

FORMAT TYPE:

9 TRACK 21 TRACK

GALVO LEVEL:

1-24 _____ DB AUX _____ DB

OTHER:

MISCELLANEOUS INFORMATION:

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																						
NAVY		155	NPR-4	BORROW	ALASKA	USA	7:00	8:00	9:00	10:00	8/10/75	R. UELER	1																						
IDENTIFICATION				SHOT				SPREAD				TAPES				GAIN				FILTERS				REMARKS											
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS. OFFSET	SEIS. DEPTH	COP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH IN/OUT	REMARKS
																						1-4/24	5-8	9-12	13-16	17-20	21-24	FREQ.		SLOPE					
51	132	61260	200	1A	M.W. B.A.S.	8:45	100	75/105	2			S			10'	//	1	✓	6sec	REC	57	57	98	98	42	42	90	100	3.20	124	8	36	out	FILE # 265 to 267 USED FOR TESTS TRACE # 41 & 42 LAYED ACROSS VERY DEEP SUBW DRIFTS. # 47 DEAD # 48 " CHANGED BAD FUGS. # 45 DEAD CHANGED BAD FUGS	
	133		271	2A	R.A.W.	8:55	100	75/105	2							//						12	42	48	48	57	57								
	134		272	3A		9:00	100	75/105	2							//						48	48												
	135		273	4A		9:05	100	75/105	2							//																			
	136		274	5A		9:15	100	75/105	2							//																			
	137	61280	275	6A		9:25	50	65/75	2							//																			
	138		276	7A		9:35	50	65/75	2							//																			
	139		277	8A		9:40	50	65/75	2							//																			
	140		280	9A		9:50	50	65/75	2							//																			
	141		301	10A		10:00	50	65/75	2							//						48	18												
	142		302	11A		10:05	50	65/75	2							//																			
	143		303	12A		11:00	50	65/75	2							//																			
	144		304	13A		11:10	50	65/75	2							//																			
	145		305	14A		11:20	50	65/75	2							//																			
	146		306	15A		11:30	50	65/75	2							//																			
	147		307	16A		11:40	50	65/75	2							//																			
	148		310	17A		11:50	50	65/75	2							//																			
	149		311	18A		12:00	50	65/75	2							//																			
	150		312	19A		12:10	50	65/75	2							//																			
	151		313	20A		12:20	50	65/75	2							//																			
	152		314	21A		12:30	50	65/75	2							//																			
	153		315	22A		1:15	50	65/75	2							//																			
	154		316	23A		1:25	50	65/75	2							//																			
	155		317	24A		1:38	50	65/75	2							//																			
	156		320	25A		1:40	50	65/75	2							//																			
	157		321	26A		1:50	50	65/75	2							//																			
	158		322	27A		2:00	50	65/75	2							//																			
	159		323	28A		2:10	50	65/75	2							//																			

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN	
							SAME

DFS III SYSTEM PARAMETERS:
 GAIN CONSTANT 320 DB
 UPPER SET LIMIT 62.5 %
 LOWER SET LIMIT 25 %
 FORMAT TYPE:
 9 TRACK 21 TRACK
 GALVO LEVEL:
 1-24 21 DB AUX 15 DB
 OTHER:

MISCELLANEOUS INFORMATION:
 196-2

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																					
NAVY		195	NPR-4	Barrow	Alaska	USA	2:00	8:00	9:00	10:00	B/AR/75	R. WEIR	2 of																					
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	SHOT		NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	SPREAD				CDP SWITCH	SETUP	TAPE				PARITY ERRORS	MODE	GAIN						FILTERS		REMARKS
								TOP	BOT.					6 SEIS OFFSET	SEIS WIDTH	RECORD LENGTH	1-4/24			5-8	9-12	13-16	17-20			21-24	INITIAL GAIN (DB)	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	SLOPE	

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT _____ DB

UPPER SET LIMIT _____ %

LOWER SET LIMIT _____ %

FORMAT TYPE:

9 TRACK 21 TRACK

GALVO LEVEL:

1-24 _____ DB AUX _____ DB

OTHER:

MISCELLANEOUS INFORMATION:

JULY TRUCK STUCK
HAD TO PULL HIM OUT
WITH RECORDER

CLIENT		PARTY NO.		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE					
NAVY		195		NPR-4		Barrow		ALASKA		USA		7:00		7:30						9/19/65		R. WEIK		1 of 3					
LINE	PROFILE	IDENTIFICATION		SHOT CAL.	PLAY BACK	TIME	SIZE	SHOT		SP. OFFSET	NO. 1 DIR.	SPREAD			TAPE		GAIN						REMARKS						
		REEL NUMBER	FILE NUMBER					TOP	NO CAPS			SEIS. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.
								BOT.					1	2	4	1-4/24	5-8	9-12	13-16	17-20	21-24				FREQ.	SLOPE	IN	OUT	
51	180	672567	354	1A	RAW	9:00	50	67/75	2	5'	10'	1/5	1	✓	65R	AGC	48	48	48	48	48	48	90	MED	.512	120	8	36	out
	181		355	2A		8:10	50	67/75	2			1/9																	
	182		356	3A		8:20	50	65/75	2			1/13																	
	183		357	4A		8:30	50	67/75	2			1/17																	
	184		360	5A		8:40	50	67/75	2			1/21																	
	185		361	6A		8:45	50	67/75	2			1/25																	
	186		362	7A		8:50	50	65/75	2			1/29																	
	187	672568	363	8A		9:00	50	67/75	2			1/33																	
	188		364	9A		9:10	50	65/75	2			1/37																	
	189		368	10A		9:15	50	67/75	2			1/41																	
	190		366	11A		9:25	50	67/75	2			1/45																	
	191		367	12A		9:35	50	67/75	2			1/49																	
	192		370	13A		10:35	50	67/75	2			1/5	2																
	193		371	14A		10:45	50	67/75	2			1/5	3																
	194		372	15A		11:15	50	67/75	2			1/9																	
	195		373	16A		11:25	50	67/75	2			1/13																	
	196		374	17A		11:30	50	67/75	2			1/17																	
	197		375	18A		11:40	50	67/75	2			1/21																	
	198		376	19A		11:50	50	67/75	2			1/25																	
	199		377	20A		11:55	50	67/75	2			1/29																	
	200		400	21A		12:00	50	67/75	2			1/33																	
	201		401	22A		12:45	50	67/75	2			1/5	4																
	202		402	23A		12:55	50	67/75	2			1/9																	
	203		403	24A		1:00	50	67/75	2			1/13																	
	204		403	25A		1:10	50	67/75	2			1/17																	
	205		404	26A		1:20	50	67/75	2			1/21																	
	206		405	27A		1:30	50	67/75	2			1/25																	
	207		406	28A		1:35	50	67/75	2			1/29																	

REMARKS FILE # 351 to 353
USED FOR TESTS.

SHOT RECORD (END of TAPE)

TAPE CHANGE

47 DEAD

NO RECORD BOTH CARS DEAD DOWN HOLE

SEISMOMETER AND SPREAD INFORMATION

SHOT CONFIGURATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SAME

DFS III SYSTEM PARAMETERS:
GAIN CONSTANT 30 DB
UPPER SET LIMIT 62.5 %
LOWER SET LIMIT 25 %
FORMAT TYPE:
 9 TRACK 21 TRACK
GALVO LEVEL:
1. 21 DB AUX 15 DB
OTHER:

MISCELLANEOUS INFORMATION:

CLIENT		PARTY NO		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE															
NAVY		195		NPR-4		Barrow		ALASKA		USA		2:00		7:30						9/10/68		R. White		2 of 3															
LINE	PROFILE	IDENTIFICATION		SHOT CAL	PLAY BACK	TIME	SIZE	SHOT		NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	TAPE				MODE	GAIN						FILTERS		REMARKS							
		REEL NUMBER	FILE NUMBER					TOP	BOT										SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	1-4		5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY		HIGH CUT FREQ.	LOW CUT FREQ.	SLOPE	NOTCH IN	OUT		
51	208	622588	407	29"	RAW	1:40	50	65/75	2			5'			10'		1/23	4	✓	65000	AGL	10	10	78	78	78	92	24	90	1100	512	124	8	36	out	* 97 DEAD			
	209		410	30"		1:50	50	65/75	2								1/21																						
	210		411	31"		2:20	50	65/75	2								1/5	5																					
	211		412	32"		3:30	50	65/75	2								1/9																						
	212		414	32"		3:40	50	65/75	2								1/5	6																					
	213			34"													1/9																						
	214			35"													1/13																						
	215			36"													1/17																						
	216		415	37"		4:10	50	65/75	2								1/21																						
	217		416	38"		4:20	50	65/75	2			40'					1/25																						
	218		417	39"		4:30	50	65/75	2								1/29																						
	219		420	40"		5:30	50	65/75	2								1/25	7																					
	220		421	41"		5:40	50	65/75	2			250'S					1/9																						
	221		422	42"		5:50	50	65/75	2								1/13																						
	222		423	43"		6:00	50	65/75	2								1/17																						
	223		424	44"		6:10	50	65/75	2								1/21																						
	224		425	45"		6:20	50	65/75	2								1/25																						
	225		426	46"		6:30	50	65/75	2								1/29																						
	226		427	47"		6:40	50	65/75	2								1/33																						
	227		428	48"		6:50	50	65/75	2								1/37																						
	228		431	49"		7:00	50	65/75	2								1/41																						
	229		432	50"		8:00	50	65/75	2								1/5	8																					
	230		433	51"		8:10	50	65/75	2								1/9																						
	231		434	52"		8:20	50	65/75	2								1/13																						
	232		435	53"		8:30	50	65/75	2			165'S					1/17																						
	233		436	54"		8:40	50	65/75	2								1/21																						
	234		437	55"		8:50	50	65/75	2			200'S					1/25																						
	235		440	56"		9:00	50	65/75	2								1/29																						

(FIG 412 MISFIRE)

SKIPPED BECAUSE OF MEND ROVER

42 DEAD " 46 "

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION		DFS III SYSTEM PARAMETERS:		MISCELLANEOUS INFORMATION:		
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN			GAIN CONSTANT	DB		
									UPPER SET LIMIT	%		
									LOWER SET LIMIT	%		
									FORMAT TYPE:			
									<input type="checkbox"/> 9 TRACK	<input type="checkbox"/> 21 TRACK		
									GALVO LEVEL:			
									1-24	DB	AUX	DB
									OTHER:			

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																					
NAVY		195	NPR-4	BARROW	ALASKA	USA	7:00	7:30	10:30	11:00	9/14/75	R. Wain	3 of 3																					
IDENTIFICATION					SHOT				SPREAD				TAPE				GAIN				FILTERS			REMARKS										
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. DIR.	CODE	S.P. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH	
57	236	622568	441	57A	RAW	9:10	50	65/75	2			B			10'	1/33	B	✓	6500		AGC	98	98	98	98	98	98	90	MED	512	124	8	36	out
	237		442	58A		9:20	50	65/75	2																									
	238		443	59A		9:30	50	65/75	2																									
	239		444	60A		9:40	50	65/75	2																									

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT _____ DB

UPPER SET LIMIT _____ %

LOWER SET LIMIT _____ %

FORMAT TYPE:

9 TRACK 21 TRACK

GALVO LEVEL:

1-24 _____ DB AUX _____ DB

OTHER:

MISCELLANEOUS INFORMATION:

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																							
Navy		195	NPR-4	BARROW	ALASKA	USA	7:00	8:00	8:30	10:00	10/10/65	R. WEIR	1																							
LINE	PROFILE	IDENTIFICATION		SHOT	PLAY BACK	TIME	SIZE	SHOT		S.P. OFFSET	SPREAD				TAPE			GAIN					MODE	INITIAL GAIN (DB)				FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH		REMARKS
		REEL NUMBER	FILE NUMBER					TOP	NO CAPS		NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	1-4	5-8	9-12		13-16	17-20	21-24	FREQ					SLOPE	IN	OUT		

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN	
							SAME

* 46 SHORTED

* 22 DEAD

(CDP WRONG)

* 45 DEAD

* 48/40 DEAD

READJUSTED TRANSPORT SPEED (WAS SLOW)

DFS III SYSTEM PARAMETERS:	MISCELLANEOUS INFORMATION:
GAIN CONSTANT 30 DB	
UPPER SET LIMIT 62.5 %	
LOWER SET LIMIT 25 %	
FORMAT TYPE:	
<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	
GALVO LEVEL:	
14 21 DB AUX 15 DB	
OTHER:	

CLIENT		PARTY NO	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																
NAVY		195	BAR NPR-4	BARROW	ALASKA	USA	7:00	8:00	4:50	10:00	10/26/68	R. White	2 of 2																
LINE	PROFILE	IDENTIFICATION		SHOT	PLAY BACK	TIME	SIZE	SHOT		SPREAD		TAPE		GAIN						REMARKS									
		REEL NUMBER	FILE NUMBER					NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	P. SEIS. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS		MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT _____ DB

UPPER SET LIMIT _____ %

LOWER SET LIMIT _____ %

FORMAT TYPE:

9 TRACK 21 TRACK

GALVO LEVEL:

1-24 _____ DB AUX _____ DB

OTHER:

MISCELLANEOUS INFORMATION:

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																		
NAVY		195	NAL-4	BARROW	ALASKA	USA	7:00	8:00	9:00	10:00	11/14/75	R. WEIR	1 of 2																		
LINE	PROFILE	IDENTIFICATION		SHOT CAL	PLAY BACK	TIME	SIZE	SHOT		SPREAD				TAPE				GAIN					FILTERS		REMARKS						
		REEL NUMBER	FILE NUMBER					TOP	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	D. SEIS. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT
51	285	672576	534	1A	MON	9:00	50	65'	2		S	10'	1/5	1	6300	AGC		1-4/24	5-8	9-12	13-16	17-20	21-24	90	MOD. STR	129	8	36	OUT	* SHOOTER SETUP ON	
	284		535	2A	RAW	9:10	50	65'	2				1/5																		* WRONG S-P
	286		536	3A		9:20	50	65'	2				1/3																		
	287		537	4A		9:30	50	65'	2				1/7																		
	288		540	5A		9:40	50	65'	2				1/21																		
	289		541	6A		9:50	50	65'	2				1/25																		
	290		542	7A		10:00	50	65'	2				1/29																		
	291		543	8A		10:10	50	65'	2				1/33																		* 21 DEAD AMP.
	292		544	9A		10:20	50	65'	2				1/37																		
	293		545	10A		10:30	50	65'	2				1/41																		
	294		546	11A		10:40	50	65'	2				1/45																		
	295		547	12A		10:50	50	65'	2				1/49																		
	296		550	13A		11:30	50	65'	2				1/5 2																		
	297		551	14A		11:40	50	65'	2				1/9																		
	298		552	15A		11:50	50	65'	2				1/13																		
	299		553	16A		12:00	50	65'	2				1/17																		
	300		554	17A		12:10	50	65'	2				1/21																		
	301		555	18A		12:20	50	65'	2				1/25																		
	302		556	19A		12:30	50	65'	2				1/29																		
	303		557	20A		12:40	50	65'	2				1/33																		* 47 SHORTED
	304		560	21A		1:45	50	65'	2				1/5 3																		* 5 DEAD
	305		561	22A		1:55	50	65'	2				1/9																		
	306		562	23A		2:00	50	65'	2				1/13																		
	307		563	24A		2:10	50	65'	2				1/17																		
	308		564	25A		2:20	50	65'	2				1/21																		
	309		565	26A		2:30	50	65'	2				1/25																		
	310		566	27A		2:40	50	65'	2				1/29																		
	311		567	28A		2:50	50	65'	2				1/33																		

SHOT 285 BEFORE SP 284
 CDP IN WRONG

File # 531 to 533
 USED FOR TESTS ON TAPE
 # 672569

* 21 DEAD AMP.

* 47 SHORTED
 * 5 DEAD

SEISMOMETER AND SPREAD INFORMATION

SHOT CONFIGURATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SAME

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB
 UPPER SET LIMIT 12.5 %
 LOWER SET LIMIT 23 %
 FORMAT TYPE:
 9 TRACK 21 TRACK
 GALVO LEVEL:
 14821 DB AUX 15 DB
 OTHER:

MISCELLANEOUS INFORMATION:

CHANGED CAPSTAN DRIVING
 SEEMS TO HAVE CURED
 SPEED PROBLEM

CLIENT		PARTY NO.		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE												
NAVY		195		NPR-4		BARROW		ALASKA		USA		7:00		8:00		9:00		10:00		11/18/78		R. WEIR		2 of 2												
LINE	PROFILE	IDENTIFICATION		SHOT	PLAY BACK	TIME	SIZE	SHOT		NO CAPS	CODE	SP. OFFSET	NO. 1 DIR.	CODE	SP. SEIS. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	TAPE				MODE	GAIN					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FILTERS		NOTCH	REMARKS
		REEL NUMBER	FILE NUMBER					TOP	BOT										SAMPLE RATE MS	1	2	4		1-4/24	5-8	9-12	13-16	17-20					21-24	LOW CUT FREQ.		
51	312	6757	570	29A	RAW	4:00	50	65/75	2		190's	5	10'			1/5	4	✓	LOGIC	ACC	48	78	90	98	12	24	90	MED	3/16	124	8	36	cut			
	313		571	20A		4:10	50	65/75	2							1/9																			#48 DOND	
	314		572	31A		4:20	50	65/75	2							1/13																				
	315		573	32A		4:30	50	65/75	2							1/17																				
	316		574	33A		4:40	50	65/75	2							1/21																				
	317		575	34A		4:50	50	65/75	2							1/25																				
	318		576	35A		5:00	50	65/75	2							1/29																				#21 AMP DEAD
	319		577	36A		5:15	50	65/75	2							1/21	5																			
	320		600	37A		6:00	50	65/75	2							1/21	6																			
	321		601	38A		6:10	50	65/75	2							1/25																				
	322		602	39A		6:30	50	65/75	2							1/29																				SHOOTER PRELOADING LAST
	323		603	40A		6:40	50	65/75	2							1/33																				6 HOLES
	324		604	41A		6:50	50	65/75	2							1/10	7																			#2 DEAD
	325		605	42A		7:30	50	65/75	2							1/5																				
	326		606	43A		7:45	50	65/75	2							1/9																				
	327		607	44A		8:00	50	65/75	2							1/13																				
END OF LINE - COMPLETE PICK UP.																																				

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:	
GAIN CONSTANT	_____ DB
UPPER SET LIMIT	_____ %
LOWER SET LIMIT	_____ %
FORMAT TYPE:	
<input type="checkbox"/> 9 TRACK	<input type="checkbox"/> 21 TRACK
GALVO LEVEL:	
1-24 _____ DB	AUX _____ DB
OTHER:	

MISCELLANEOUS INFORMATION:	