

CLIENT		PARTY NO.		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																	
NAVY		195		NPR 4		Barrow		ALASKA		U.S.A		7:00	9:30	8:30	9:00	18 MAR 75	NEIGHBORS	1																	
IDENTIFICATION				SHOT				SPREAD				TAPE		GAIN				FILTERS		REMARKS															
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	TOP BOT	NO CAPS	CODE	S.P. OFFSET	NO. DIR.	CODE	SIES	SPREAD	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	SLOPE	NOTCH IN OUT		
																		1 2 4				1-4/24	5-8	9-12	13-16	17-20	21-24								
54	201	610	1A	RAW			50	6075	2			5	10					1/5	1		AGC	48	48	48	28	42	36	90	Med.	512	124	8	36	Rec. No. 600 607 D.R.D.	
	202	611	2A				50	6075	2									1/10																	
	203	612	3A				50	6075	2									1/13																	
	204	613	4A				50	6075	2									1/17																	
	205	614	5A				50	6075	2									1/21																	
	206	616	6A				50	6075	2									1/25																	
	207	617	7A				50	6075	2									1/29																	
	208	620	8A				50	6075	2									1/33																	
	209	621	9A				50	6075	2									1/37																	
	210	622	10A				50	6075	2									1/41																	
	211	623	11A				50	6075	2	60N								1/45	2																
	212	624	12A				50	6075	2									1/5																	
	213	625	13A				50	6075	2									1/9																	
	214	626	14A				50	6075	2									1/13																	
	215	627	15A				50	6075	2									1/17																	
	216	630	16A				50	6075	2									1/21																	
	217	631	17A				50	6075	2									1/25																	
	218	632	18A				50	6075	2									1/29																	
	219	633	19A				50	6075	2	60N								1/35																	
	220	634	20A				50	6075	2									1/37																	

REMARKS  
 No. F.T.B.  
 REC NO 615  
 MISEIRS  
 SPIKES ON REC.

CABLE SPIKES ON  
 BOTTOM END OF RECORD  
 #45 DEAD  
 NOT SHOT

NOTE: NOISE ON  
 TAIL SPREAD IS DUE TO  
 BRUSHING OPERATIONS

SEISMOMETER AND SPREAD INFORMATION				SHOT CONFIGURATION		
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GR. INT.	SPREAD PATTERN
	MANUAL SITE	9	15	IN LINE	330	SINGLE HOLES 1320' INT.

DFS III SYSTEM PARAMETERS:	
GAIN CONSTANT	30 DB
UPPER SET LIMIT	62.5 %
LOWER SET LIMIT	25 %
FORMAT TYPE:	
<input type="checkbox"/> 9 TRACK	<input checked="" type="checkbox"/> 21 TRACK
GALVO LEVEL:	
1-24	21 DB AUX 16 DB
OTHER:	

MISCELLANEOUS INFORMATION:  
 LAYING OUT SPREAD - INCLUDING  
 TAIL SPREAD WITH HELP OF  
 CAT - 4 HRS.  
 ONLY ONE JUG TRUCK - USED  
 FOR PICKING UP & MOVING  
 CABLES. OTHER ONE USED FOR  
 SHOOTING. SHOOTING TRUCK DOWN -  
 CHARGING SYS. INOPERATIVE.

CLIENT		PARTY NO		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE														
NAVY		195		NPR-C1		Barrow		ALASKA		U.S.A.										FIMARTS		NEIGHBORS		2														
LINE	PROFILE	IDENTIFICATION		SHOT	PLAY BACK	TIME	SIZE	SHOT		NO. CAPS	CODE	S.P. OFFSET	NO. DIR.	CODE	SPREAD		SETUP	TAPE		MODE	GAIN						RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FILTERS		NOTCH	REMARKS					
		REEL NUMBER	FILE NUMBER					TOP	BOT						S.P. SEIS. OFFSET	SEIS. DEPTH		CDP SWITCH	SAMPLE RATE MS		RECORD LENGTH	PARITY ERRORS	1-4	5-8	9-12	13-16				17-20	21-24			FINAL GAIN DB	LOW CUT	SLOFF	IN	OUT
54	248	67553	734	29A	RAW		50	6775	2			5			10	1/5	5	✓	6	AGC	48	48	48	48	42	36	90	MED	572	124	8	36	OUT	ITL DEAD				
	249		735	30A			50	6775	2							1/4																						
	250		736	31A			50	6775	2							1/3																						
	251		737	32A			50	6775	2							1/7																						
	252		740	33A			50	6775	2							1/2																						
	253		741	34A			50	6775	2		200 N					1/26																						
	254		742	35A			50	6775	2							1/29																						
	255		743	36A			50	6775	2							1/33																						
	256		744	37A			50	6775	2							1/36																						
	257		745	38A			50	6775	2							1/17																						
	258		746	39A			50	6775	2							1/21																						
	259		747	40A			50	6775	2							1/25																						

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION		DFS III SYSTEM PARAMETERS:		MISCELLANEOUS INFORMATION:		
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN						
									GAIN CONSTANT		DB	
									UPPER SET LIMIT		%	
									LOWER SET LIMIT		%	
									FORMAT TYPE:			
									<input type="checkbox"/> 9 TRACK	<input type="checkbox"/> 21 TRACK		
									GALVO LEVEL:			
									1-24	DB	AUX	DB
									OTHER:			

CLIENT		WARRANTY NO.		PROSPECT		COUNTRY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE														
NAVV		195		NPR 1		Barrow		ALASKA		U.S.A.		7:00		7:30		9:30		10:00		PM 075		NEIGHBORS		1														
LINE	PROFILE	IDENTIFICATION		SHOT CAL	PLAY BACK	TIME	SIZE	SHOT		NO. CAPS	CODE	S.P. OFFSET	NO. DIR.	SPRFAD		C.D.P. SWITCH	SETUP	TAPE		MODE	GAIN						RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FILTERS		NOTCH IN/OUT	REMARKS					
		REFL NUMBER	FILE NUMBER					TOP	BOT.					1	2			4	1-4/24		5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB				PHED	SLOPE							
220	6252	637	1A	RAW		50	6075	2				5	10	1/1	1			6	AGC	36	48	48	48	48	48	48	48	48	90	MCA	.572	124	8	36	Rec. No. 634-635 AGC TEST			
221		640	2A			50	6075	2						1/5																								
222		641	3A			50	6075	2						1/9																								
223		703	4A			50	6075	2						1/5	2																							
224		704	5A			50	6075	2						1/9																								
225		705	6A			50	6075	2						1/5																								
226		706	7A			50	6075	2						1/9																								
227		707	8A			50	6075	2						1/21																								
228		710	9A			50	6075	2						1/25																								
229		711	10A			50	6075	2						1/29																								
230		712	11A			50	6075	2						1/33																								
231		713	12A			50	6075	2						1/37																								
232	6253	714	13A			50	6075	2						1/5	3																							
233		715	14A			50	6075	2						1/9																								
234		716	15A			50	6075	2						1/13																								
235		717	16A			50	6075	2						1/17																								
236		720	17A			50	6075	2						1/21																								
237		721	18A			50	6075	2						1/25																								
238		722	19A			50	6075	2						1/29																								
239		723	20A			50	6075	2						1/33																								
240		724	21A			50	6075	2						1/5	4																							
241		725	22A			50	6075	2						1/9																								
242		726	23A			50	6075	2						1/13																								
243		727	24A			50	6075	2						1/17																								
244		730	25A			50	6075	2						1/21																								
245		731	26A			50	6075	2						1/25																								
246		732	27A			50	6075	2						1/29																								
247		733	28A			50	6075	2						1/33																								

SEISMOMETER AND SPREAD INFORMATION				SHOT CONFIGURATION		
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN
	MANUAL 8 Hz	9	15	LINE	330	SINGLE HOLES 1320' INT.

DFS III SYSTEM PARAMETERS:	
GAIN CONSTANT	30 DB
UPPER SET LIMIT	62.5 %
LOWER SET LIMIT	25 %
FORMAT TYPE:	
<input type="checkbox"/> 9 TRACK	<input checked="" type="checkbox"/> 21 TRACK
GALVO LEVEL:	
1-24	21 DB AUX 15 DB
OTHER:	

MISCELLANEOUS INFORMATION:	

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																							
NAVY		195	NPR-1	BARROW	ALASKA	USA	7:00	8:00	9:00	10:00	20 MAR 75	NEIGHBORS	1																							
LINE	PROFILE	IDENTIFICATION		SHOT CAL	PLAY BACK	TIME	SHOT		NO. CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SPREAD		CDP SWITCH	SETUP	TAPE		MODE	GAIN									FILTERS			REMARKS			
		REEL NUMBER	FILE NUMBER				SIZE	TOP						SPREAD	RECORD LENGTH			PARITY ERRORS	INITIAL GAIN (DB)									FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH		
																						1-4/24 5-8 9-12 13-16 17-20 21-24														

SEISMOMETER AND SPREAD INFORMATION					
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.
	HANDHEL	9	15	INLINE	330

SHOT CONFIGURATION  
 SINGLE HOLES

DFS III SYSTEM PARAMETERS:	MISCELLANEOUS INFORMATION:
GAIN CONSTANT <u>30</u> DB	
UPPER SET LIMIT <u>62.5</u> %	
LOWER SET LIMIT <u>20</u> %	
FORMAT TYPE:	
<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	
GALVO LEVEL:	
1-24 <u>21</u> DB AUX <u>15</u> DB	
OTHER:	

REMARKS  
 REC. No 750-757  
 D.R.D.  
 #29 DEAD  
 SKIP.  
 REC. No. 775 MISFIRE  
 TAPE CHANGE  
 #32 DEAD  
 CABLE SPIKES - #30 DEAD  
 CABLE SPIKES  
 #12 DEAD  
 REC. No. 1024 MISFIRE

CLIENT		PARTY NO.		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE																					
NAVY		195		NPR-4		BARROW		ALASKA		U.S.A.										20 MAR 75		NEIGHBORS		2																					
LINE	PROFILE	IDENTIFICATION		SHOT CAL	PLAY BACK	TIME	SIZE	SHOT		NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SPREAD		S.D. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	TAPE		MODE	GAIN					RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FILTERS		NOTCH	REMARKS									
		REEL NUMBER	FILE NUMBER					TOP	BOT						S.1	S.2						1	2		4	1-4	24	3-8	8-12				13-16	17-20			21-24	FINAL GAIN DB	FREQ.	SLOPE	IN	OUT			
288	288	255	1027	28A	RAW		50	60	75	2		5			10	1/3	4				6	AGC	48	48	48	48	48	48	36	42	48	48	90	MED	512	124	8	36	OUT						
289	289		1030	29A			50	60	75	2						1/7																													
290	290		1031	30A			50	60	75	2						1/21																													
291	291		1032	31A			50	60	75	2						1/25																													
292	292		1033	32A			50	60	75	2						1/29																													
293	293		1034	33A			50	60	75	2						1/33																													
294	294		1035	34A			50	60	75	2						1/5	5																												
295	295		1036	35A			50	60	75	2						1/9																													
296	296		1037	36A			50	60	75	2						1/3																													
297	297		1040	37A			50	60	75	2						1/7																													
298	298		1041	38A			50	60	75	2						1/20																													
299	299		1042	39A			50	60	75	2						1/5																													

SHOT IN MANUAL GAIN: 78db.  
SHOT IN FINAL GAIN - 6db

No E.T.B.

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION		DFS III SYSTEM PARAMETERS:		MISCELLANEOUS INFORMATION:	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN			GAIN CONSTANT	UPPER SET LIMIT	LOWER SET LIMIT
									_____ DB	_____ %	_____ %
									FORMAT TYPE:	<input type="checkbox"/> 9 TRACK	<input type="checkbox"/> 21 TRACK
									GALVO LEVEL:	1-24 _____ DB	AUX _____ DB
									OTHER:		





CLIENT		PARTY NO	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																					
NAVY		195	NPR-4	Barrow	ALASKA	U.S.A.					21 Mar 75	NEIGHBORS	2																					
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS		REMARKS												
LINE	PROFILE	REEL NUMBER	FILE NUMBER	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SEIS. OFFSET	SEIS. DEPTH	COP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH		
																	1	2	4		1-4/24		5-8	9-12	13-16	17-20	21-24		FREQ	SLOPE	IN	OUT		
54	328	2255	1110	29A	RAW	50	60/75	2			3		10	1/8	5		U	6		AGC	48	48	48	48	42	36	90	Med	152	134	8	36	OUT	
	329		1111	30A		50	60/75	2						1/9																				
	330		1112	31A		50	60/75	2						1/13																				
	331		1113	32A		50	60/75	2						1/9																				
	332		1114	33A		50	60/75	2						1/21																				
	333		1115	34A		50	60/75	2						1/25																				
	334		1116	35A		50	60/75	2						1/27																				

CABLE SPIKES

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:  
 GAIN CONSTANT \_\_\_\_\_ DB  
 UPPER SET LIMIT \_\_\_\_\_ %  
 LOWER SET LIMIT \_\_\_\_\_ %  
 FORMAT TYPE:  
 9 TRACK  21 TRACK  
 GALVO LEVEL:  
 1-24 \_\_\_\_\_ DB AUX \_\_\_\_\_ DB  
 OTHER:

MISCELLANEOUS INFORMATION: