

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																							
NAVY		195	NPR-1	Barrow	ALASKA	U.S.A.	7:00	8:00	9:00	10:00	22MAR75	NGIGHBORS	1																							
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS		REMARKS														
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	TOP	BOT	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.EIS. OFFSET	S.EIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT	NOTCH	REMARKS		
																			1	2	4		1-4/24	5-8	9-12	13-16	17-20	21-24		FREQ.	SLOPE	IN	OUT			
55	1	612553	1127	1A	RAW		50	64	75	2		SW	10'			1/5	1		4	6		AGC	48	48	48	48	42	36	90	MED.	512	124	8	36	OUT	425 DEAD
	2		1130	2A			50	68	75	2						1/6																				
	3		1131	3A			50	67	75	2						1/13																				
	4		1132	4A			50	60	75	2						1/17																				
	5		1133	5A			50	60	75	2						1/21																				
	6		1134	6A			50	67	75	2						1/25																				
	7		1135	7A			50	67	75	2						1/29																				
	8		1136	8A			50	67	75	2						1/37																				
	9		1137	9A			50	67	75	2						1/37																				
	10		1140	10A			50	67	75	2						1/41																				
	11		1141	11A			50	67	75	2						1/45																				
	12		1142	12A			50	69	75	2						1/4																				
	13		1143	13A			50	67	75	2						1/5																				
	14		1144	14A			50	67	75	2						1/9																				
	15		1145	15A			50	67	75	2						1/13																				
	16		1146	16A			50	67	75	2						1/17																				
	17		1147	17A			50	67	75	2						1/21																				
	18		1150	18A			50	67	75	2						1/25																				
	19		1151	19A			50	67	75	2						1/29																				
	20		1152	20A			50	67	75	2						1/33																				
	21		1153	21A			50	68	75	2						1/5																				
	22		1154	22A			50	67	75	2						1/9																				
	23		1155	23A			50	67	75	2						1/13																				
	24		1156	24A			50	67	75	2						1/17																				
	25		1157	25A			50	67	75	2						1/21																				
	26		1160	26A			50	67	75	2						1/26																				
	27		1161	27A			50	67	75	2						1/29																				
	28		1162	28A			50	67	75	2						1/33																				

SEISMOMETER AND SPREAD INFORMATION					
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.
	MANUREL 104E	9	15'	INLINE	1320'

SHOT CONFIGURATION
SINGLE HOLES

DFS III SYSTEM PARAMETERS:
 GAIN CONSTANT 30 DB
 UPPER SET LIMIT 62.5 %
 LOWER SET LIMIT 25 %
 FORMAT TYPE:
 9 TRACK 21 TRACK
 GALVO LEVEL:
 1-24 21 DB AUX 15 DB
 OTHER:

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																							
NAVY		195	NPR-4	Barrow	ALASKA	U.S.A.	7:00	8:00	11:00	11:30	23 MAR 75	NGIGHBORS	1																							
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS		REMARKS														
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	TOP BOT	NO CAPS	CODE	S.P. OFFSET	NO. DIR.	CODE	S.P. SEIS. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE		INITIAL GAIN (DB)				FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	SLOPE	NOTCH IN/OUT			
55	45	1205	1A	1A	RAW		50	60775	2			SW	10			1/5	1	4	6		ACC	48	48	48	48	48	90	MED.	512	124	8	36	OUT	1202-1203 - INST. NOISE		
46		1205	2A	2A			50	60775	2							1/4																				
47		1206	3A	3A			50	60775	2							1/3																				
48		1207	4A	4A			50	60775	2							1/7																				
49		1210	5A	5A			50	60775	2							1/21																				
50		1211	6A	6A			50	60775	2							1/25																				
51		1212	7A	7A			50	60775	2							1/29																				
52		1213	8A	8A			50	60775	2							1/33																				
53		1214	9A	9A			50	60775	2							1/8	2																			
54		1215	10A	10A			50	60775	2							1/5																				
55		1216	11A	11A			50	60775	2							1/9																				
56		1217	12A	12A			50	60775	2							1/13																				
57		1220	13A	13A			50	60775	2							1/17																				
58		1221	14A	14A			50	60775	2							1/21																				
59		1222	15A	15A			50	60775	2							1/25																				
60		1223	16A	16A			50	60775	2							1/29																				148 DEAD
61		1224	17A	17A			50	60775	2							1/5	3																			
62		1225	18A	18A			50	60775	2							1/9																				
63		1226	19A	19A			50	60775	2							1/13																				
64		1227	20A	20A			50	60775	2							1/17																				
65		1230	21A	21A			50	60775	2							1/21																				
66		1231	22A	22A			50	60775	2							1/25																				
67		1232	23A	23A			50	60775	2							1/29																				
68		1233	24A	24A			50	60775	2							1/33																				
69		1234	25A	25A			50	60775	2							1/5	4																			
70		1235	26A	26A			50	60775	2							1/9																				
71		1236	27A	27A			50	60775	2							1/9																				
72		1237	28A	28A			50	60775	2							1/17																				

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN
	MINI-DIGITAL 10KHZ	9	15	INLINE	330'	1320'

SHOT CONFIGURATION
SINGLE HOLES

DFS III SYSTEM PARAMETERS:
GAIN CONSTANT 30 DB
UPPER SET LIMIT 62.5 %
LOWER SET LIMIT 25 %
FORMAT TYPE:
 9 TRACK 21 TRACK
GALVO LEVEL: 1
1-24 21 DB AUX 15 DB
OTHER:

MISCELLANEOUS INFORMATION:

CLIENT		PARTY NO.		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE																						
NAW		195		NPR-4		BARRROW		ALASKA		USA										22 MAR 75		NG1643072.5		2																						
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN						FILTERS		REMARKS																						
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	TOP		NO CAPS	CODE	SP OFFSET	NO. 1 DIR.	CODE	SPREAD		CDP SWITCH	SETUP	SAMPLE RATE MS			RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH									
								TOP	BOT.						S.P. SEIS. OFFSET	SEIS. DEPTH			1	2	4				1-4/24	5-8	9-12	13-18	17-20	21-24					FREQ.	SLOPE	IN	OUT								
35	29	12555	1163	29A	RAW		50	60	75	2		SW			10		1/5	4						AGC	48	48	48	48	48	48	48	48	90	Med.	512	124	8	36	OUT							
	30		1164	30A			50	60	75	2																																				
	31		1165	31A			50	60	75	2																																				
	32		1166	32A			50	60	75	2																																				
	33		1167	33A			50	60	75	2																																				
	34		1170	34A			50	60	75	2																																				
	35		1171	35A			50	60	75	2																																				
	36		1172	36A			50	60	75	2																																				
	37		1173	37A			50	60	75	2																																				
	38		1174	38A			50	60	75	2																																				
	39		1175	39A			50	60	75	2																																				
	40																																													
	41		1176	40A			50	60	75	2																																				
	42		1177	41A			50	60	75	2																																				
	43		1200	42A			50	60	75	2																																				
	44		1201	43A			50	60	75	2																																				

SKIP

SEISMOMETER AND SPREAD INFORMATION					
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	SPREAD PATTERN

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:	
GAIN CONSTANT	_____ DB
UPPER SET LIMIT	_____ %
LOWER SET LIMIT	_____ %
FORMAT TYPE:	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK
GALVO LEVEL:	1-24 _____ DB AUX _____ DB
OTHER:	

MISCELLANEOUS INFORMATION:	

