

CLIENT		PARTY NO.		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE																								
NAVY		195		NPR-4		BARROW		ALASKA		U.S.		19:00		9:30						3/6/75		R. WEIR		1																								
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN						FILTERS				REMARKS																						
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	TOP		NO CAPS	CODE	SP OFFSET	NO. 1 DIR.	SEIS. OFFSET	SEIS. DEPTH	COP SWITCH	SETUP	SAMPLE RATE MS				RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH											
								1	2									4	1-4/24	5-8	9-12				13-16	17-20	21-24	FREQ.	SLOPE	IN					OUT													
56	1	672549	424	1A	RAW		50	60	125	2		SW	10'		1	1	✓	6sec				AGL	48	48	48	48	42	36	90	MOD	512	224	8	36	out			used For Tests.										
	2		426	2A			50	60	125	2																																						
	3		427	3A			50	60	125	2																																						
	4		430	4A			50	60	125	2																																						
	5		431	5A			50	60	125	2																																						
	6		432	6A			50	60	125	2																																						
	7		433	7A			50	60	125	2																																						
	8		434	8A			50	60	125	2																																						

File #425 MISFILE

SEISMOMETER AND SPREAD INFORMATION					
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.

SHOT CONFIGURATION

SW PROGRESSING NE  
NO 1 TO THE SW.

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB  
 UPPER SET LIMIT 62.5 %  
 LOWER SET LIMIT 25 %  
 FORMAT TYPE:  
 9 TRACK  21 TRACK  
 GALVO LEVEL:  
 142.1 DB AUX 18 DB  
 OTHER:

MISCELLANEOUS INFORMATION:

CLIENT		PARTY NO.		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE													
NAVY		195		NPR-4		Barrow		ALASKA		U.S.A.		7:00		8:00						8 MAR 75		NEIGHBORS		1													
IDENTIFICATION					SHOT					SPREAD					TAPE					GAIN					FILTERS			REMARKS									
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	TOP BOT	NO CAPS	CODE	SP OFFSET	NO. 1 DIR.	CODE	SP. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH				
																						1-4/24	5-8	9-12	13-16	17-20					21-24	FREQ.	SLOPE	IN	OUT		
56	37	62	542	1A	RAW		25	67/75	1			SW	10'	-	1/1	1		6			AGC	48	48	48	48	48	30	90	MED.	.512	124	8	36	OUT	#1-DEAD		
	38		543	2A			50	67/75	2						1/5																						
	39		544	3A			25	67/75	1						1/9																						
	40		545	4A			25	67/75	1						1/13																						
	41		546	5A			50	67/75	2						1/17																						
	42		547	6A			25	67/75	1						1/21																						
	43		550	7A			50	67/75	2						1/25																						
	44		551	8A			25	67/75	1						1/30																						
	45		552	9A			25	67/75	1						1/33																						
	46		553	10A			50	67/75	2						1/4		2																				
	47		554	11A			50	67/75	2						1/5																						
	48		555	12A			50	67/75	2						1/9																						
	49		556	13A			50	67/75	2						1/5		3																		#10 DEAD		
	50		557	14A			50	67/75	2						1/9																						
	51		560	15A			50	67/75	2						1/13																						
	52																																			SKIP	
	53		561	16A			50	67/75	2						1/23																					REC NO 562 & 563 MISFIRE	
	54		564	17A			50	67/75	2						1/25																						
	55		566	18A			50	67/75	2						1/29																						REC NO 565 MISFIRE
	56		567	19A			50	67/75	2						1/33																						
	57		570	20A			50	67/75	2						1/37																						
	58		571	21A			50	67/75	2						1/5		4																				
	59		572	22A			50	67/75	2						1/9																						
	60		573	23A			50	67/75	2						1/15																						
	61		574	24A			50	67/75	2						1/17																						
	62		575	25A			50	67/75	2						1/21																						
	63		576	26A			50	67/75	2						1/25																						
	64		577	27A			50	67/75	2						1/29																						

SEISMOMETER AND SPREAD INFORMATION				
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN
	MANUAL	9	15	INLINE
	8HZ			
		GP. INT.	SPREAD PATTERN	
		330'		

SHOT CONFIGURATION

SINGLE HOLES  
PROGRESSING - NE

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB  
UPPER SET LIMIT 62.5 %  
LOWER SET LIMIT 25 %

FORMAT TYPE:  
 9 TRACK  21 TRACK

GALVO LEVEL:  
1-24 21 DB AUX 15 DB

OTHER:

MISCELLANEOUS INFORMATION:

CLIENT **NAVY** PARTY NO. **195** PROSPECT **NPR-4** COUNTY **USA** STATE **ALASKA** COUNTRY **Barrow** LEFT STORAGE **7:00** ARRIVED FIELD **9:30** ARRIVED STORAGE **7 Mar 75** OBSERVER **NEIGHBARS** PAGE **1**

LINE	PROFILE	IDENTIFICATION		SHOT CAL	PLAY BACK	TIME	SIZE	SHOT		NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SPREAD		SUS. DEPTH	CDP SWITCH	SETUP	TAPE				RECORD LENGTH	PARITY ERRORS	MODE	GAIN						RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FILTERS		NOTCH IN/OUT	REMARKS
		REEL NUMBER	FILE NUMBER					TOP	BOT.						1	2				4	1-4/24	5-8	9-12				13-16	17-20	21-24	FINAL GAIN DB	FREQ.	SLOPE							
56	9	6734	446	1A	RAW		50	607	75	2		SW	10			1/1	1		6	AGC	48	48	49	48	42	30	90	MGD	512	124	8	36	OUT	Rec No. 435-444 - DRD 445 - PULSE					
56	10		447	2A			50	607	75	2						1/1																			445 - NOISE				
56	11		450	3A			50	607	75	2						1/1																							
56	12		451	4A			50	607	75	2						1/1																							
56	13		452	5A			50	607	75	2						1/1																							
56	14		453	6A			50	607	75	2						1/21																							
56	15		454	7A			50	607	75	2						1/25																							
56	16		455	8A			50	607	75	2						1/29																							
56	17		456	9A			50	607	75	2						1/33																							
56	18		457	10A			50	607	75	2						1/37																							
56	19		460	11A			50	607	75	2						1/41																			Rec No 460 - MISFIRE				
56	20		462	12A			50	607	75	2						1/45																			CHANGED TAPES * REC NOS ADVANCED FROM 473 TO 514				
56	21	6734	473	13A			50	607	75	2						1/5	2																						
56	22		514	14A			50	607	75	2						1/9																							
56	23		515	15A			50	607	75	2						1/13																							
56	24		516	16A			25	607	75	2						1/7																							
56	25		517	17A			50	607	75	2						1/21																							
56	26		520	18A			25	607	75	2						1/25																							
56	27		521	19A			50	607	75	2		200'E				1/29																			HOLE BLOWN				
56	28		522	20A			25	607	75	2						1/33																							
56	29		523	21A			50	607	75	2						1/5	3																						
56	30		524	22A			50	607	75	2						1/9																							
56	31		525	23A			50	607	75	2						1/13																							
56	32		526	24A			25	607	75	2						1/17																			Rec No 527 - MISFIRE *				
56	33		540	25A			50	607	75	2						1/21																							
56	34		541	26A			50	607	75	2						1/25																							
56	35															1/29																				SKIP			
56	36																																			SKIP			

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN	
	MANDRA 8cpa	9	15	INLINE	330	48 INLINE	SINGLE HOLES PROGRESSING N.E.

DFS III SYSTEM PARAMETERS:  
 GAIN CONSTANT 32 DB  
 UPPER SET LIMIT 62.5 %  
 LOWER SET LIMIT 20 %  
 FORMAT TYPE:  
 9 TRACK  21 TRACK  
 GALVO LEVEL:  
 1-24 21 DB AUX 15 DB  
 OTHER:

MISCELLANEOUS INFORMATION:  
 \* RECORD NOS ADVANCED FROM 462 TO 473 ON S.P. 21.  
 \* RECORD NO ADVANCED FROM 527 TO 540

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																								
NAVY		195	NPR-4	Barrow	ALASKA	U.S.A.		6:30	7:00	6 MAR 75	NEIGHBORS	2																									
IDENTIFICATION				SHOT			SPREAD				TAPES		GAIN					FILTERS		REMARKS																	
LINE	PROFILE	REEL NUMBER	FILE NUMBER	PLAY BACK	TIME	SIZE	SHOT		NO. CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S. SEIS. OFFSET	S. SEIS. DEPTH	COP SWITCH	SETUP	SAMPLE RATE MS			RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH	
							TOP	BOT.										1	2					4	1-4/24	3-8	9-12	13-16	17-20					21-24	FREQ.	SLOPE	IN

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

SAME AS PAGE ONE

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT \_\_\_\_\_ DB

UPPER SET LIMIT \_\_\_\_\_ %

LOWER SET LIMIT \_\_\_\_\_ %

FORMAT TYPE:

9 TRACK  21 TRACK

GALVO LEVEL:

1-24 \_\_\_\_\_ DB AUX \_\_\_\_\_ DB

OTHER:

MISCELLANEOUS INFORMATION:

CLIENT: **NAVY** PARTY NO: **195** PROSPECT: **NPR-4** COUNTY: **BARROW** STATE: **ALASKA** COUNTRY: **USA** LEFT STORAGE: **7:00** ARRIVED FIELD: **7:45** LEFT FIELD: ARRIVED STORAGE: DATE: **9 MAR 75** OBSERVER: **NEIGHAMERS** PAGE: **1**

LINE	PROFILE	IDENTIFICATION		PLAY BACK	TIME	SIZE	SHOT			NO. CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	SPREAD				SETUP	TAPE		MODE	GAIN					FILTERS		NOTCH	REMARKS					
		FILE NUMBER	SHOT CAL				TOP	BOT.	D					E	F	G	RECORD LENGTH		PARITY ERRORS	INITIAL GAIN (DB)					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.			FREQ.	SLOPE	IN	OUT	
56	66	603	1A	RAW		50	607	70	2		SW	10	1/5			V	6	AGC	38	48	48	48	42	30	90	MD	572	124	8	36	REPT	RECORD NO 6014602 AGC.			
	67	604	2A			50	69	75	2				1/9																					SHORT RECORD - END OF TAPE	
	68	605	3A			50	69	75	2				1/13																					CHANGE TAPE - #142 DEAD	
	69	001	4A			50	69	75	2				1/17																						
	70	002	5A			50	69	75	2				1/21																						
	71	003	6A			50	69	75	2				1/25																						#142 DEAD
	72	004	7A			50	69	75	2				1/29																						#142 DEAD
	73	005	8A			50	69	75	2				1/33																						

~~END OF LINE 56~~

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN
	MANDBEL 8HZ	9	15	IN LINE	330	330 GROUP INTERVAL 1320 S.P. INTERVAL

SHOT CONFIGURATION

**SINGLE HOLES**

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB  
 UPPER SET LIMIT 62.5 %  
 LOWER SET LIMIT 25 %  
 FORMAT TYPE:  
 9 TRACK  21 TRACK  
 GALVO LEVEL:  
 1-24 21 DB AUX 15 DB  
 OTHER:

MISCELLANEOUS INFORMATION:

BETWEEN S.P. 71 & S.P. 72  
 SPACING = 1185'  
 SPT1  
 A ← 330 ← 330 ← 330 ← 330 ←