

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																			
NAVY		195	NPR-4	BARROW	ALASKA	USA	7:00	8:30			11 MAR 75	NEIGHBOR	1																			
LINE	PROFILE	IDENTIFICATION		SHOT CAL.	PLAY BACK	TIME	SIZE	SHOT		NO. CAPS	CODE	SPREAD			TAPE		MODE	GAIN					RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FILTERS		NOTCH IN/OUT	REMARKS			
		REEL NUMBER	FILE NUMBER					TOP	BOT.			S.P. OFFSET	NO. 1 DIR.	CODE	S.P. OFFSET	SEIS DEPTH		CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS				1-4	5-8			9-12	13-16	17-20
57	1	070	1A	RAW			50	60775	2		NE	10'	1/5	1	✓	6	AGC	48 48	48 48	48 48	48 48	90	Med	512	124	8	36	OUT	REC No's 65466 INST. NOISE			
	2	071	2A				50	60775	2				1/9																			
	3	072	3A				50	60775	2				1/13																			
	4	073	4A				50	60775	2				1/17																			
	5	074	5A				50	60775	2				1/21																			
	6						50	60775	2				1/25																			
	7	076	6A				50	60775	2				1/29																		Tape ran out No Record - NO LOW TAPE STOP TAPE CHANGE	
	8	077	7A				50	60775	2				1/33																			
	9	100	8A				50	60775	2				1/37																			
	10	102	9A				50	60775	2	20'NW			1/41	2																	REC NO 101 - MISFIRE	
	11	103	10A				50	60775	2				1/45																			
	12	104	11A				50	60775	2				1/49																			
	13	105	12A				50	60775	2				1/53																			RECORD NO SKIPPED FROM 105 TO 116
	14	116	13A				50	60775	2				1/57																			
	15	117	14A				50	60775	2				1/61																			
	16	120	15A				50	60775	2				1/65																			
	17	120	16A				50	60775	2				1/69																			
	18	122	17A				50	60775	2				1/73	3																		
	19	123	18A				50	60775	2				1/77																			
	20	124	19A				50	60775	2				1/81																			
	21	135	20A				50	60775	2				1/85																			REC. NO ADVANCED FROM 124 TO 135
	22	136	21A				50	60775	2				1/89																			
	23	140	22A				50	60775	2				1/93																			
	24	141	23A				50	60775	2	50'SG			1/97	4																		REC NO 137 - MISFIRE
	25	142	24A				50	60775	2				1/101																			
	26	143	25A				50	60775	2				1/105																			
	27	144	26A				50	60775	2				1/109																			
	28	145	27A				50	60775	2				1/113																			

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN	
	MINI-DISK 8 Hz	9	15	IN LINE	330	S.P. INT. 1320	SINGLE HOLES

DFS III SYSTEM PARAMETERS:			
GAIN CONSTANT	30	DB	
UPPER SET LIMIT	62.5	%	
LOWER SET LIMIT	25	%	
FORMAT TYPE:			
<input type="checkbox"/> 9 TRACK	<input checked="" type="checkbox"/> 21 TRACK		
GALVO LEVEL:			
1-24	21	DB	AUX 15
OTHER:			

MISCELLANEOUS INFORMATION:	

CLIENT		PARTY NO. PROSPECT		COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																						
NAVY		195 NPR-4		BARROW	ALASKA	U.S.A.	7:00	7:30			BMAETS	NEIGHBORS	1																						
LINE	PROFILE	IDENTIFICATION		SHOT	SIZE	NO CAPS	CODE	S.P. OFFSET	SPREAD			SETUP	SAMPLE RATE MS	TAPE	RECORD LENGTH	PARITY ERRORS	MODE	GAIN					RELEASE RATE	TRIP DELAY	HIGH CUT FREQ	FILTERS		REMARKS							
		REEL NUMBER	FILE NUMBER						CAL	PLAY BACK	TIME							TOP	BOT	NO. 1 DIR.	CODE	SEIS. OFFSET				SEIS. DEPTH	CDP SWITCH		1-4	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB
57	71	365	1A	RAW	50	60	75	2		NE	10	1/5	1	6	AGC			18.48	18.48	18.48	18.48	18.48	18.48	18.48	18.48	18.48	90	MED	512	124	8	36	OUT	REC NO 363 & 364 NOISE TEST	
	72	366	2A		50	60	75	2				1/9																							
	72A	367	2B		25	20	28	1				1/9																							
	73	370	3A		50	60	75	2	40'SW			1/13																							
	74	371	4A		50	60	75	2				1/17																							
	75	372	5A		50	60	75	2				1/21																							
	76	373	6A		50	60	75	2				1/25																							
	77	374	7A		50	60	75	2				1/29																							
	78	375	8A		50	60	75	2	40'SW			1/35																							
	79	376	9A		50	60	75	2				1/37																							
	80	377	10A		50	60	75	2	40'SW			1/37	2																						
	81	400	11A		50	60	75	2				1/37																							
	82	401	12A		50	60	75	2				1/39																							
	83	402	13A		50	60	75	2				1/13																							
	84	403	14A		50	60	75	2				1/17																							
	85	404	15A		50	60	75	2				1/21																							
	86	405	16A		50	60	75	2				1/25																							
	87	406	17A		50	60	75	2				1/29																							
	88	407	18A		50	60	75	2				1/33																							
	89	410	19A		50	60	75	2				1/5	3																						
	90	411	20A		50	60	75	2				1/9																							
	91	412	21A		50	60	75	2	40'SW			1/13																							
	92	413	22A		50	60	75	2				1/17																							
	93	414	23A		50	60	75	2				1/21																							
	94	415	24A		50	60	75	2	40'NE			1/25																							
	95	416	25A		50	60	75	2				1/29																							
	96	417	26A		50	60	75	2				1/33																							
	97	420	27A		50	60	75	2				1/5	4																						

SEISMOMETER AND SPREAD INFORMATION				SHOT CONFIGURATION		
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN
	HANDDC	9	15	INLINE	330	SR. INT. 1320
	5-HZ					SINGLE HOLES

DFS III SYSTEM PARAMETERS:	
GAIN CONSTANT	30 DB
UPPER SET LIMIT	25 %
LOWER SET LIMIT	25 %
FORMAT TYPE:	
<input type="checkbox"/> 9 TRACK	<input checked="" type="checkbox"/> 21 TRACK
GALVO LEVEL:	
1-24	21 DB AUX 15 DB
OTHER:	

MISCELLANEOUS INFORMATION.	
REC NO.	420 MISFIRE

CLIENT		PARTY NO		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE											
NAVY		195		NPR-4		Barrow		ALASKA		U.S.A.		7:00		8:30						12 MAR 75		NEIGHBORS		1											
LINE	PROFILE	IDENTIFICATION		SHOT CAL.	PLAY BACK	TIME	SIZE	SHOT		NO. CAPS	CODE	S.P. OFFSET	NO. DIR.	CODE	SPREAD		S.C. UP	TAPE		MODE	GAIN					RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FILTERS		NOTCH	REMARKS			
		REEL NUMBER	FILE NUMBER					TOP	BOT.						SPREAD	DEPTH		RECORD LENGTH	PARITY ERRORS		INITIAL GAIN (DB)	1-2	3-8	9-12	13-16				17-20	21-24			FINAL GAIN DB	LOW CUT	SLOPE
57	38	261	1A	RAW			50	60	75	2		NE	10		1/5	1	6	AGC	48	48	48	48	42	36	90	MED	512	124	8	36	OUT	REC NO ADV 160 TO 261			
	39	272	2A				50	60	75	2					1/9																	" " " 261 TO 272			
	40	273	3A				50	60	75	2					1/13																				
	41	274	4A				50	60	75	2					1/17																				
	42	275	5A				50	60	75	2					1/21																				
	43	306	6A				50	60	75	2					1/25																		REC. NO ADVANCED FROM 275 TO 306		
	44	307	7A				50	60	75	2					1/29																				
	45	310	8A				50	60	75	2					1/33																				
	46	311	9A				50	60	75	2					1/37																				
	47	312	10A				50	60	75	2					1/5	2																			
	48	313	11A				50	60	75	2					1/9																			TAPE CHANGE.	
	49	314	12A				50	60	75	2					1/13																			REC. NO. 315 MISFIRE	
	50	316	13A				50	60	75	2					1/17																				
	51	317	14A				50	60	75	2					1/21																				
	52	320	15A				50	60	75	2					1/25																				
	53	321	16A				50	60	75	2					1/29	3																			
	54	322	17A				50	60	75	2					1/33																				
	55	323	18A				50	60	75	2					1/5	4																			
	56	324	19A				50	60	75	2					1/9																				
	57	325	20A				50	60	75	2					1/13																				
	58	326	21A				50	60	75	2					1/17																				REC. NO ADVANCED FROM 326 TO 337
	59	337	22A				50	60	75	2					1/21																				
	60	340	23A				50	60	75	2					1/25																				
	61	341	24A				50	60	75	2					1/29																				
	62	342	25A				50	60	75	2					1/33																				
	63	343	26A				50	60	75	2					1/5	5																			
	64	354	27A				50	60	75	2					1/9																				REC. NO ADVANCED FROM 343 TO 354
	65	355	28A				50	60	75	2					1/13																				

SEISMOMETER AND SPREAD INFORMATION					SHOT CONFIGURATION	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN
	ANALOG	9	15	INLINE	330	S.P. INT. 1320

SINGLE HOLES

DFS III SYSTEM PARAMETERS:	
GAIN CONSTANT	30 DB
UPPER SET LIMIT	62.5 %
LOWER SET LIMIT	25 %
FORMAT TYPE:	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 24 TRACK
GALVO LEVEL:	1-24 21 DB AUX. 15 DB
OTHER:	

MISCELLANEOUS INFORMATION:  
 LOST 3 HRS. HURR OF SHOOTING  
 TRUCK BROKEN.

CLIENT		PARTY NO / PROSPECT		COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																								
NAVY		195 NPR 4		BARROW	ALASKA	USA		7:30	8:00		12 MAR 75	NEIGHBORS	2																								
LINE	PROFILE	IDENTIFICATION		SHOT	PLAY BACK	TIME	SIZE	SHOT		NO. CAPS	CODE	SP OFFSET	NO. 1 DIR	CODE	SPREAD			CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	GAIN					RELEASE RATE	TRIP DELAY	HIGH CUT FREQ	FILTERS		NOTCH	REMARKS		
		REEL NUMBER	FILE NUMBER					TOP	BOT						A	B	C							1-4	5-8	9-12	13-16	17-20				21-24	LOW CUT			IN	OUT
57	66	356	356	29A	RAW		50	6775	2				NE	10	1/7								AGC	48 48 48 48 48 48 48 48	36 42 48 48 48 48 48 48	90	MED, 512	24	8	36	OUT						
	67		357				50	6775	2						1/21																						
	68		360				50	6775	2						1/25																						
	69		361				50	6775	2						1/29																						
	70		362				50	6775	2						1/33																						

HOLE BLOW

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT \_\_\_\_\_ DB

UPPER SET LIMIT \_\_\_\_\_ %

LOWER SET LIMIT \_\_\_\_\_ %

FORMAT TYPE:

9 TRACK  21 TRACK

GALVO LEVEL:

1-24 \_\_\_\_\_ DB AUX \_\_\_\_\_ DB

OTHER:

MISCELLANEOUS INFORMATION:

CLIENT		PARTY NO		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE						
NAVY		195		NPR-4		Barrow		Alaska		U.S.A.										11MAY75		NEIGHBORS		2						
LINE	PROFILE	IDENTIFICATION		SHOT	PLAY BACK	TIME	SHOT		SPREAD				TAPE		GAIN					FILTERS			REMARKS							
		RFL NUMBER	FILL NUMBER				SIZE	TOP	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.W. SET	NO. 2 DIR.	CODE	S.W. SET	NO. 3 DIR.	CODE	S.W. SET	NO. 4 DIR.	CODE		S.W. SET	1-4/24	5-8	9-12	13-16	17-20	21-24
57	29	146	28A	RAW		50	60	2			NE	10	1/5	5	✓	6	AGC	48	48	48	42	36	90	MED	512	124	8	36		
	30	147	29A			50	60	2					1/9																	
	31	150	30A			50	60	2					1/13																	
	32	150	31A			50	60	2					1/17																	
	33	150	32A			50	60	2					1/21																	
	34	153	33A			50	60	2					1/25																	
	35	154	34A			50	60	2					1/29																	
	36	155	35A			50	60	2					1/33																	
	37	156	36A			50	60	2					1/37																	

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT \_\_\_\_\_ DB

UPPER SET LIMIT \_\_\_\_\_ %

LOWER SET LIMIT \_\_\_\_\_ %

FORMAT TYPE:

9 TRACK  21 TRACK

GALVO LEVEL:

1-24 \_\_\_\_\_ DB AUX. \_\_\_\_\_ DB

OTHER:

MISCELLANEOUS INFORMATION:

CLIENT		PARTY NO. PROSPECT		COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																																		
NAVY		195	NPR-1	Barrow	ALASKA	USA					13 MAR 75	NEIGHBORS	2																																		
LINE	PROFILE	IDENTIFICATION			TIME	SHOT			SPREAD				TAPE			GAIN						FILTERS		REMARKS																							
		REEL NUMBER	FILE NUMBER	SHOT CAL		PLAY BACK	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	NO. 2 SEIS. OFFSET	NO. 3 SEIS. OFFSET	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH																
																		1-4/2-4	5-8	9-12	13-16	17-20	21-24	FREQ.		SLOPE	IN		OUT																		

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT \_\_\_\_\_ DB

UPPER SET LIMIT ..... %

LOWER SET LIMIT ..... %

FORMAT TYPE:

9 TRACK  12 TRACK

GALVO LEVEL:

1-24 \_\_\_\_\_ DB AUX \_\_\_\_\_ DB

OTHER:

MISCELLANEOUS INFORMATION:

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																									
NAVY		195	NPRC	BARROW	ALASKA	USA	7:00	7:45	7:05	8:00	14 MAR 75	NEIGHBORS	1																									
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS		REMARKS																
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	TOP	NO CAPS	LOG	SP. OFFSET	NO. 1 DIR.	CODE	NO. 2 DIR.	SPREAD	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FREQ	SLOPE	NOTCH IN/OUT	REMARKS			
57	113	6250	451	1A	RAW		50	60	2			NE	10		1/9	1		✓			AGC	48	48	48	48	48	48	90	MED	512	124	8	36	OUT	REC No 491 to 450 D.R.D.			
	114		452	2A			50	60	2						1/13																							
	115		453	3A			50	60	2						1/17																							
	116		454	4A			50	60	2						1/21																							
	117		455	5A			50	60	2						1/25																							
	118		456	6A			50	60	2						1/29																							
	119		457	7A			50	60	2						1/33																							
	120		460	8A			50	60	2						1/37		2																					
	121		461	9A			50	60	2						1/9																							
	122		462	10A			50	60	2						1/13																							
	123		463	11A			50	60	2						1/17																							
	124		465	12A			50	60	2						1/21																							
	125		466	13A			50	60	2						1/25																							
	126		467	14A			50	60	2						1/29																							
	127		470	15A			50	60	2						1/33																							
	128		471	16A			50	60	2						1/37																							
	129		472	17A			50	60	2						1/41																							
	130		473	18A			50	60	2						1/45																							
	131		474	19A			50	60	2						1/49																							
	132		475	20A			50	60	2						1/5		3																					
	133		476	21A			50	60	2						1/9																							
	134		477	22A			50	60	2						1/13																							
	135		500	23A			50	60	2						1/17																							
	136		501	24A			50	60	2						1/21																							
	137		502	25A			50	60	2						1/25																							
	138		503	26A			50	60	2						1/29																							
	139		504	27A			50	60	2						1/33																							
	140	6251	505	28A			50	60	2			NE			1/37		5																					

REC. NO. 464 - MISFIRE

TAPE CHANGE

SEISMOMETER AND SPREAD INFORMATION				SHOT CONFIGURATION		DFS III SYSTEM PARAMETERS:		MISCELLANEOUS INFORMATION:	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN			
	MANDREL 8 Hz	9	15'	INCLINE	330'	SINGLE HOLES 1320' INTERVAL	GAIN CONSTANT	30 DB	
							UPPER SET LIMIT	62.5 %	
							LOWER SET LIMIT	25 %	
							FORMAT TYPE:		
							<input type="checkbox"/> 9 TRACK	4821 TRACK	
							GALVO LEVEL:		
							1-24	21 DB AUX	15 DB
							OTHER:		

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																						
NAVY		195	NPR-4	BARRAW	ALASKA	U.S.A.					4 MAR 75	NEIGHBORS	2																						
LINE	PROFILE	IDENTIFICATION			PLAY BACK	TIME	SIZE	SHOT		NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	SPREAD				SETUP	TAPE			GAIN					FILTERS		REMARKS						
		REEL NUMBER	FILE NUMBER	SHOT CAL.				TOP	BOT					NO. 2 DIR.	NO. 3 DIR.	NO. 4 DIR.	NO. 5 DIR.		NO. 6 DIR.	NO. 7 DIR.	NO. 8 DIR.	NO. 9 DIR.	NO. 10 DIR.	NO. 11 DIR.	NO. 12 DIR.	NO. 13 DIR.	NO. 14 DIR.	NO. 15 DIR.		NO. 16 DIR.	NO. 17 DIR.	NO. 18 DIR.	NO. 19 DIR.	NO. 20 DIR.	NO. 21 DIR.

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT \_\_\_\_\_ DB

UPPER SET LIMIT \_\_\_\_\_ %

LOWER SET LIMIT \_\_\_\_\_ %

FORMAT TYPE:

9 TRACK  21 TRACK

GALVO LEVEL:

1-24 \_\_\_\_\_ DB AUX \_\_\_\_\_ DB

OTHER:

MISCELLANEOUS INFORMATION:



CLIENT		PARTY NO. PROSPECT		COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																						
NAVY		195 NPR.4		Barrow	ALASKA	U.S.A.	7:00	8:00	8:00	8:30	15 MAR 75	NEIGHBORS	1																						
LINE	PROFILE	IDENTIFICATION		SHOT	PLAY BACK	TIME	SIZE	SHOT		NO. CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SPREAD		COP SWITCH	SETUP	TAPE		PARITY ERRORS	MODE	GAIN						RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FILTERS		NOTCH IN/OUT	REMARKS
		REEL NUMBER	FILE NUMBER					CAL.	TOP						BOT.	A SEIS. OFFSET			B SEIS. DEPTH	SAMPLE RATE MS			RECORD LENGTH	1-4/24	5-8	9-12	13-16	17-20				21-24	FINAL GAIN DB		

SEISMOMETER AND SPREAD INFORMATION			
CODE	SEIS. TYPE	NO./GP.	INT.
	MANUAL 8412	9	330 15
GROUP PATTERN		GP. INT.	SPREAD PATTERN
INLINE		330	

SHOT CONFIGURATION  
SINGLE HOLES  
1320 INT.

DFS III SYSTEM PARAMETERS:  
GAIN CONSTANT 30 DB  
UPPER SET LIMIT 62.5 %  
LOWER SET LIMIT 25 %  
FORMAT TYPE:  
 9 TRACK  21 TRACK  
GALVO LEVEL:  
1-24 21 DB AUX 15 DB  
OTHER:

MISCELLANEOUS INFORMATION:  
WINDY IN AFTERNOON.

REC. NO. 522 MISFIRE

REC. NO. ADVANCED FROM 524 TO 535 #48 DEAD

SKIP? COULDN'T SKIP LOAD HOLES.

REC. NO. 515 & 516 A.I.G.C.

CLIENT		PARTY NO		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE								
NAVY		195		NPR		BARROW		ALASKA		USA										15 MAR 75		NEIGHBORS		2								
LINE	PROFILE	IDENTIFICATION		SHOT	PLAY BACK	TIME	SIZE	SHOT		NO. CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SPREAD				CDP SWITCH	SETUP	TAPE		MODE	GAIN					FILTERS			REMARKS
		REEL NUMBER	FILE NUMBER					TOP	BOT.						1	2	4	RECORD LENGTH			PARITY ERRORS	INITIAL GAIN (DB)		FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT	NOTCH			
57	176	2551	562	29A	RAW		50	6/75	2			NE	10		1/9	5		6	AGC	49	48	48	48	48	36	90	MED	512	124	8	36	OUT
	177		563				50	6/75	2						1/3																	
	178		564				50	6/75	2						1/7																	

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION		DFS III SYSTEM PARAMETERS:		MISCELLANEOUS INFORMATION:		
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP INT.	SPREAD PATTERN			GAIN CONSTANT	DB	UPPER SET LIMIT	%
									LOWER SET LIMIT	%	FORMAT TYPE:	
									<input type="checkbox"/> 9 TRACK	<input type="checkbox"/> 21 TRACK	GALVO LEVEL:	
									1-24	DB	AUX	DB
									OTHER:			

CLIENT		PARTY NO. PROSPECT		COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																							
NAVY		195 NPR 4		Barrow	ALASKA	USA	7:00	7:30	1:30	5:00	16 MAR 75	NEIGHBORS	1																							
IDENTIFICATION				SPREAD								TAPE				GAIN				FILTERS		REMARKS														
LINE	PROFILE	RFEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	TOP	NO CAPS	CODE	SP OFFSET	NO. DIR.	CODE	SP. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE			RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)					RELEASE RATE	TRIP DELAY	HIGH CUT FREQ	LOW CUT		NOTCH		
								BOT										1	2	4				1-4	5-8	9-12	13-16	17-20				21-24	FINAL GAIN DB	FREQ	SLOPE	

END OF LINE

Tape change  
noise on records  
is being caused  
by camp near  
line  
  
tail spread to sp. 90  
+ 3 geo. stations

SEISMOMETER AND SPREAD INFORMATION							SHOT CONFIGURATION		DFS III SYSTEM PARAMETERS:	MISCELLANEOUS INFORMATION:
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN	SINGLE HOLES		GAIN CONSTANT 30 DB UPPER SET LIMIT 62.5 % LOWER SET LIMIT 25 % FORMAT TYPE: <input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK GALVO LEVEL: 1-24 21 DB AUX 15 DB OTHER:	
	MANDRA 8 Hz	9	15	INLINE	330					