



CLIENT: U.S. NAVY PARTY NO: 182 PROSPECT: N.P.R. 4 COUNTY: STATE: COUNTRY: LEFT STORAGE: ARRIVED FIELD: LEFT FIELD: ARRIVED STORAGE: DATE: 5-17-75 OBSERVER: F. Carlsenius PAGE: 2072

LINE	PROFILE	IDENTIFICATION		SHOT CAL	PLAY BACK	TIME	SHOT				SPREAD				TAPE			GAIN						FILTERS			REMARKS								
		REEL NUMBER	FILE NUMBER				SIZE	TOP	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	R. DIR. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ	LOW CUT		NOTCH	
		1-4/24	5-8				9-12	13-16	17-20	21-24	1	2	4	1-4/24	FREQ	SLOPE	IN	OUT																	
77	66	534	126	27	R/W		1X35	61	75	2		SE	10'		1	3	✓	6	NOISE	78	48	48	48	48	42	90	Fast	768	124	8	36	OUT	No Monitor (0.15)		
	67		127	28			1X35	61	75	2		"	"		1	5	✓	"	"	42	48	48	48	48	"	"	"	"	"	"	"	"			
	68		130	29			1X35	61	75	2		"	"		1	9	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"			
	69		131	30			1X35	61	75	2		"	"		1	13	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"			
	70		132	31			1X35	61	75	2		"	"		1	17	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"			
	71		133	32			1X35	61	75	2		"	"		1	21	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"			
	72		134	33			1X35	61	75	2		"	"		1	25	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"			
	73		135	34			1X35	61	75	2		"	"		1	29	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"			
	74		136	35			1X35	61	75	2		"	"		1	33	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	Caught up to drill		

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION		DFS III SYSTEM PARAMETERS:		MISCELLANEOUS INFORMATION:		
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN			GAIN CONSTANT	DB	UPPER SET LIMIT	%
									LOWER SET LIMIT	% <td>FORMAT TYPE:</td> <td></td>	FORMAT TYPE:	
									<input type="checkbox"/> 9 TRACK	<input type="checkbox"/> 21 TRACK	GALVO LEVEL:	
									1-24	DB	AUX	DB
									OTHER:			

CLIENT: **U.S. NAVY** PARTY NO: **1B2** PROSPECT: **N.P.R.-4** COUNTY: STATE: **ALASKA** COUNTRY: **U.S.A.** LEFT STORAGE: **700** ARRIVED FIELD: **730** LEFT FIELD: **600** ARRIVED STORAGE: **630** DATE: **5-16-75** OBSERVER: **F. Carlsonius** PAGE: **1 of 2**

LINE	PROFILE	IDENTIFICATION		SHOT	PLAY BACK	TIME	SHOT		NO CAPS	CODE	S.P. OFFSET	NO. DIR.	CODE	SPREAD		SETUP	TAPE				GAIN					FILTERS		REMARKS				
		REEL NUMBER	FILE NUMBER				TOP	BOT						SEIS. DEPTH	CDP SWITCH		SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)					RELEASE RATE	TRIP DELAY		HIGH CUT FREQ.	LOW CUT	NOTCH	
		698	532	020	1	2	8	1X20	20			SE	10'	1	17	1	✓	6	DIFER	48	48	48	48	48	42	90	Fast	768	124	8	36	out
6			021	2			1X35	25	40	2		"	"		21	✓	"	"	"	42	48	48	48	48	48	"	"	"	"	"	"	"
7			022	3			1X35	60	75	2		"	"		25	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
8			023	4			1X35	60	75	2		"	"		29	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
9			024	5			1X35	60	75	2		"	"		33	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
10			025	6			1X50	50	70	2		"	"		37	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
11			026	7			1X50	50	70	2		"	"		41	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
12			027	8			1X50	50	70	2		"	"		45	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
13			030	9			1X50	50	70	2		"	"		49	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
14			031	10			1X50	50	70	2		"	"		1	2	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	Moved up to S.P. #20 (Long Detour)
15			032	11			1X50	50	70	2		"	"		5	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
16			033	12			1X50	50	70	2		"	"		9	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
17			034	13			1X50	50	70	2		"	"		13	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
18			035	14			1X50	50	70	2		"	"		17	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
19			036	15			1X50	50	70	2		"	"		21	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
20			037	16			1X50	50	70	2		"	"		25	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
21			040	17			1X50	50	70	2		"	"		29	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
22			041	18			1X50	55	75	2		"	"		33	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
23			042	19			1X50	35	55	2		"	"		37	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
24			043	20			1X50	50	70	2		"	"		41	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
25			044	21			1X50	55	75	2		"	"		45	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
26			045	22			1X50	50	70	2		"	"		49	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
27			046	23			1X50	50	70	2		"	"		1	3	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
28			047	24			1X50	40	60	2		"	"		5	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
29			050	25			1X50	55	75	2		"	"		9	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
30			051	26			1X50	40	60	2		"	"		13	✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION		DFS III SYSTEM PARAMETERS:		MISCELLANEOUS INFORMATION:		
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN			GAIN CONSTANT	UPPER SET LIMIT	LOWER SET LIMIT	
									30	62.5	18	
									FORMAT TYPE:			
									<input type="checkbox"/> 9 TRACK	<input checked="" type="checkbox"/> 21 TRACK		
									GALVO LEVEL:			
									1-24	21	AUX	21
									OTHER:			

File # 006 - 015 = DRD.  
 File # 016 = Pulse test  
 File # 017 = Test 7-B.



CLIENT: U.S. NAVY PARTY NO: 102 PROSPECT: N.P.R. -4 COUNTY: STATE: ALASKA COUNTRY: U.S.A. LEFT STORAGE: 700 ARRIVED FIELD: 800 LEFT FIELD: 530 ARRIVED STORAGE: 630 DATE: 5-17-75 OBSERVER: F. Carlsenius PAGE: 1072

LINE	PROFILE	IDENTIFICATION			PLAY BACK	TIME	SHOT			SPREAD				TAPE		GAIN							FILTERS			REMARKS									
		REEL NUMBER	FILE NUMBER	SHOT CAL			SIZE	TOP	NO CAPS	NO. DIR.	CODE	S.P. SEIS. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)							FINAL GAIN DB	RELEASE RATE	TRIP DELAY Hz to	HIGH CUT FREQ	LOW CUT FREQ	SLOPE	NOTCH IN	NOTCH OUT	
77	40	533	075	1	R/W		1X50	40/60	2		SE	10'	1/1	1	✓	6	OPEN	48	48	48	48	48	42	90	Fast	768	124	8	36	out	#1 open in table				
	41		076	2			1X35	30/45	2		"	"	1/5		✓	"	"	42	48	48	48	48	48	"	"	"	"	"	"	"	"	#17			
	42		077	3			1X50	50/70	2		"	"	1/9		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	#13			
	43		100	4			1X50	55/75	2		"	"	1/13		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	#9			
	44		101	5			1X35	36/50	2		"	"	1/17		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	#5			
	45		102	6			1X50	50/70	2		"	"	1/21		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	#1			
	46		103	7			1X50	20/40	2		"	"	1/25		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"			
	47		104	8			1X50	55/75	2		"	"	1/29		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	both cups dead (SKIP)		
	48		104	9			1X50	50/70	2		"	"	1/33		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"			
	49		105	10			1X50	55/75	2		"	"	1/37		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"		
	50		106	11			1X50	55/75	2		"	"	1/41		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"		
	51		107	12			1X50	50/70	2		"	"	1/45		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"		
	52		110	13			1X50	60/90	2		"	"	1/49		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"		
	53		111	14		1200	1X50	50/70	2		"	"	1/1		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	Moved up to S.P. #59	
	54		112	15			1X50	50/70	2		"	"	1/5		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
	55		113	16			1X50	50/70	2		"	"	1/9		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
	56		114	17			1X50	50/70	2		"	"	1/13		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
	57		115	18			1X35	50/70	2		"	"	1/17		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
	58		116	19			1X35	30/70	2		"	"	1/21		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
*	59	698 534	117	20			1X35	61/75	2		"	"	1/25		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	Tape change (698534)	
	60		120	21			1X35	61/75	2		"	"	1/29		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
	61		121	22			1X35	61/75	2		"	"	1/33		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
	62		122	23			1X35	61/75	2		"	"	1/37		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
	63		123	24			1X35	61/75	2		"	"	1/41		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
	64		124	25			1X35	61/75	2		"	"	1/45		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
	65		125	26			1X35	61/75	2		"	"	1/49		✓	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	Moved up to S.P. #72

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION		DFS III SYSTEM PARAMETERS:		MISCELLANEOUS INFORMATION:	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN			GAIN CONSTANT	UPPER SET LIMIT	LOWER SET LIMIT
									30	62.5	18
									FORMAT TYPE:		
									<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK		
									GALVO LEVEL:		
									1-24 21 DB AUX 21 DB		
									OTHER:		

File # 063-071 = D.R.D.  
 File # 072 = Pulse test  
 File # 073 = Test T.B.





