

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																							
NAVY		1186	NPR-4	N Slope	ALASKA	USA	7:00	9:00			3/14/76	R. White	1 of 1																							
LINE	PROFILE	IDENTIFICATION		SHOT CAL.	PLAY BACK	TIME	SIZE	SHOT		NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SPREAD			CDP SWITCH	SETUP	TAPE				MODE	GAIN					RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FILTERS		NOTCH IN/OUT	REMARKS
		REEL NUMBER	FILE NUMBER					TOP	BOT.						1	2	4			1-4/24	5-8	9-12	13-16		17-20	21-24	FINAL GAIN DB	FREQ.	SLOPE							

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:	MISCELLANEOUS INFORMATION:
GAIN CONSTANT <u>30</u> DB	
UPPER SET LIMIT <u>62.2</u> %	
LOWER SET LIMIT <u>18</u> %	
FORMAT TYPE:	
<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	
GALVO LEVEL:	
1- <u>18</u> DB AUX <u>15</u> DB	
OTHER:	

REMARKS  
FILE # 001 & 002  
USED FOR TESTS.

WAIT ON SURVEYORS 3 hrs.

TRACE NO. 45 DEAD  
TRACE NO. 43 DEAD

TRACE NO. 47 DEAD  
TRACE NO. 43 DEAD

TRACE NO. 36 DEAD

TRACES NO. 5, 6, 21 DEAD  
TRACES NO. 1, 2, 17 DEAD  
TRACES NO. 27 & 28 DEAD

UP-HOLE SHORTED  
CABLE BREAK

Last Shot of Day

CLIENT		PARTY NO.		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE															
US NAVY		1186		NPR 4		North Slope		Alaska		USA		7		8		9:00		10:00		2-11-76		R WEIR		2 of 2															
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS				REMARKS															
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	TOP BOT	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SEIS. OFFSET	SEIS. OFFSET	CDP SWITCH	SETUP	SAMPLE RATE MS				RECORD LENGTH	PARITY ERRORS		MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH	
																		1	2	4	1-4/24					5-8	9-12	13-16/7-20	21-24	FREQ.	SLOPE					IN	OUT		
134	136	67262	101	29 <sup>A</sup>	RAW	3:25	50	50/75	2			W		10'		1/21	6	X	6500			AGC	54	54	54	30	40	48	90	Fast	700	124	8	36	out				
<del>135</del>	137		102	30 <sup>A</sup>		3:35	50	60/75	2							1/25																							
	<del>138</del>		103	31 <sup>A</sup>		3:40	50	60/75	2							1/29																							
	139		104	32 <sup>A</sup>		3:45	50	60/75	2							1/33																							
	140		105	33 <sup>A</sup>		4:15	50	60/75	2							1/5	7																						
	141		106	34 <sup>A</sup>		4:35	50	60/75	2							1/9																							
	142		107	35 <sup>A</sup>		4:55	50	60/75	2							1/13																							
	143		110 <sup>A</sup>	36 <sup>A</sup>		5:15	50	60/75	2							1/17																							
	144		111	37 <sup>A</sup>		5:25	50	60/75	2							1/21																							
	145		112	38 <sup>A</sup>		5:35	50	60/75	2							1/25																						Note Blank	
	146		113	39 <sup>A</sup>		5:45	50	60/75	2							1/29																							
	147		114	40 <sup>A</sup>		5:50	50	60/75	2							1/33																							
	148		115	41 <sup>A</sup>		6:10	50	60/75	2							1/5	8																						
	149		116	42 <sup>A</sup>		6:20	50	60/75	2							1/9																							
	150		117	43 <sup>A</sup>		6:25	50	60/75	2							1/13																							
	151		120	44 <sup>A</sup>		6:30	50	60/75	2							1/17																							
	152		121	45 <sup>A</sup>		6:40	50	60/75	2							1/21																							
	153		122	46 <sup>A</sup>		6:50	50	60/75	2							1/25																							
	154		123	47 <sup>A</sup>		7:00	50	60/75	2							1/29																							
	155		124	48 <sup>A</sup>		7:10	50	60/75	2							1/33																							

SEISMOMETER AND SPREAD INFORMATION					
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	SPREAD PATTERN

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:  
 GAIN CONSTANT 30 DB  
 UPPER SET LIMIT 62.5 %  
 LOWER SET LIMIT 18 %  
 FORMAT TYPE:  
 9 TRACK  21 TRACK  
 GALVO LEVEL:  
 150 DB AUX 15 DB  
 OTHER:

MISCELLANEOUS INFORMATION:

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																							
NAU4		186	NPR 4	North Slope	Alaska	USA	7	8	9:00	10:00	3-11-76	R Weir	1 of 2																							
LINE	PROFILE	IDENTIFICATION		SHOT	PLAY BACK	TIME	SHOT		NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SPREAD		CDP SWITCH	SETUP	TAPES				PARITY ERRORS	MODE	GAIN						RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FILTERS		NOTCH	REMARKS
		FILE NUMBER	REF. NUMBER				TOP	BOT.						SEIS. OFFSET	SEIS. DEPTH			1	2	4	INITIAL GAIN (DB)						LOW CUT	IN	OUT							
				CAL			SIZE											1-4/24	3-8	9-12	13-16	17-20	21-24	FINAL GAIN DB				FREQ.	SLOPE							

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 36 DB

UPPER SET LIMIT 62.5 %

LOWER SET LIMIT 18 %

FORMAT TYPE:

9 TRACK  21 TRACK

GALVO LEVEL:

18 DB AUX 15 DB

OTHER:

MISCELLANEOUS INFORMATION:

Received na 37-43  
 Duce test 44  
 41 Rev.  
 Changing out Red cable.  
 37 #41 REVERSED  
 33 #37 "  
 29 #38 "  
 25 #29 "  
 21 #25 "  
 17 #21 "  
 13 #17 REVERSED  
 CABLE Decay  
 " " "  
 #47 DEND  
 Moved to Fix Group

SP #125 Lost on tape 672623  
 Trace #46 Dend

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																							
NAVY		1186	NPR-4		ALASKA	USA	7:00	7:30	8:00	9:00	3/12/76	R. Klein	1 of 1																							
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	SHOT		NO CAPS	CODE	S.P. OFFSET	NO. DIR.	CODE	SPREAD		CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	GAIN						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH IN/OUT	REMARKS
								TOP	BOT						SEIS OFFSET	SEIS DEPTH							1-24	5-8	9-12	13-18	17-20	21-24					FREQ.	SLOPE		

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION			
NO. DIR.	CODE	SEIS OFFSET	SEIS DEPTH
W	10'	1/5	1
		1/9	
		1/12	
		1/17	
		1/21	
		1/25	
		1/29	
		1/33	
		1/37	
		1/41	
		1/45	3
		1/49	
		1/53	
		1/57	
		1/61	
		1/65	
		1/69	
		1/73	
		1/77	
		1/81	
		1/85	4
		1/89	
		1/93	

DFS III SYSTEM PARAMETERS:	
GAIN CONSTANT	30 DB
UPPER SET LIMIT	62.5 %
LOWER SET LIMIT	18 %
FORMAT TYPE:	
<input type="checkbox"/> 9 TRACK	<input checked="" type="checkbox"/> 21 TRACK
GALVO LEVEL:	
1# 18 DB	AUX 15 DB
OTHER:	

REMARKS File # 125-86127 used FOR TESTS.

CABLE Delay #32 DEAD UP-HOLE DATA

SHORT RECORD (EOT) TAPE CHANGE

48 49 50 18 92 30  
30 92 48 48 48 48  
24

CLIENT		PARTY NO	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																						
NAVY		186	NPR-4		ALASKA	USA	7:00	7:30	8:00	9:00	8/12/56	R. L. ...	2 of 2																						
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS		REMARKS													
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE		INITIAL GAIN (DB)					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	SLOPE	NOTCH IN	OUT
																		1	2	4			1-4/24	5-8	9-12	13-16	17-20	21-24							
134	184	622625	164	29A	RAW	3:10	50	60/75	2			W			10'	1/17	4	✓	6300			ACC	48	48	48	48	48	48	90	F51	768	129	8	56	out
	185		165	30A		3:20	50	60/75	2																										
	186		166	31A		3:30	50	60/75	2																										
	187		167	32A		3:40	50	60/75	2																										
	188		170	33A		3:50	50	60/75	2																										
	189		171	34A		4:50	50	60/75	2																										
	190		172	35A		5:00	50	60/75	2																										
	191		173	36A		5:15	50	60/75	2																										
	192		174	37A		5:35	50	60/75	2																										
	193		175	38A		5:45	50	60/75	2																										
	194		176	39A		6:00	50	60/75	2																										
	195		177	40A		6:15	50	60/75	2																										
	196		200	41A		6:25	50	60/75	2																										
	197		201	42A		6:30	50	60/75	2																										
	198		202	43A		6:40	50	60/75	2																										

# FB READ  
 REPLANT SOME PROWES

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION		DFS III SYSTEM PARAMETERS:		MISCELLANEOUS INFORMATION:	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN			GAIN CONSTANT	UPPER SET LIMIT	LOWER SET LIMIT
									_____ DB	_____ %	_____ %
								FORMAT TYPE:			
								<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK			
								GALVO LEVEL:			
								1-24 _____ DB AUX _____ DB			
								OTHER:			

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																								
Navy		186	NPR-4		Alaska	USA	7:00	7:30			3/13/76	R. White	1 of 2																								
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS		REMARKS															
LINE	PROFILE	REF. NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	P. SEIS. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE		INITIAL GAIN (DB)					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH			
																		1	2	4			1-4/24	5-8	9-12	13-16	17-20	21-24			FREQ.	SLOPE	IN	OUT			
134	199	2225	216	1A	RAW	8:00	50	60/75	2			W		10'	1/5	1	✓	6sec			AGC	48	48	48	48	48	48	90	Fast	.70	129	8	38	out	File # 203 to 215 used for tests.		
	200		217	2A	RAW	8:10	50	60/75	2						1/5																						
	201		220	3A		8:20	50	60/75	2						1/9																						
	202		221	4A		8:30	50	60/75	2						1/17																						
	203		222	5A		9:00	50	60/75	2						1/19																					Cable Delay	
	204		223	6A		9:10	50	60/75	2						1/21																						
	205							SKIP																													
	206		224	7A		9:20	50	60/75	2						1/29																					DEAD UP-HOLE	
	207		225	8A		10:15	50	60/75	2						1/5	2																					
	208		226	9A		10:25	50	60/75	2						1/9																						
	209		227	10A		10:40	50	60/75	2						1/13																						
	210		230	11A		10:55	50	60/75	2						1/17																						
	211		231	12A	DPB	11:10	50	60/75	2						1/21	✓																					
	212		232	13A	RAW	11:20	50	60/75	2						1/25																						
	213		233	14A		11:25	50	60/75	2						1/29																						
	214		234	15A		11:30	50	60/75	2						1/33																						
	215		235	16A		11:35	50	60/75	2						1/37																						48 to 98 DEAD
	216		236	17A		12:10	50	60/75	2						1/13	3																				*1 DEAD	
	217		237	18A		12:20	50	60/75	2						1/17																						
	218		240	19A		12:35	50	60/75	2						1/21																						
	219		241	20A		12:45	50	60/75	2						1/25																						
	220		242	21A		1:00	50	60/75	2						1/29																						
	221		243	22A		1:10	50	60/75	2						1/33																						
	222		244	23A		1:15	50	60/75	2						1/37																						
END OF LINE #134														COMPLETE PICK-UP & LAYOUT ON NEW LINE																							

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN	

DFS III SYSTEM PARAMETERS:	
GAIN CONSTANT	30 DB
UPPER SET LIMIT	62.5 %
LOWER SET LIMIT	18 %
FORMAT TYPE:	
<input type="checkbox"/> 9 TRACK	<input checked="" type="checkbox"/> 21 TRACK
GALVO LEVEL:	
1-18 DB	AUX 15 DB
OTHER:	

MISCELLANEOUS INFORMATION:	