

CLIENT		PARTY NO	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																						
Navy		1186	NPR-4	North Slope	Alaska	USA	7:00	8:00		8:30	4/23/66	R. Rubin	2 of 2																						
LINE	PROFILE	IDENTIFICATION		SHOT	PLAY BACK	TIME	SIZE	SHOT		SPREAD				TAPE		GAIN					FILTERS		REMARKS												
		REEL NUMBER	FILE NUMBER					NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)					FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	SLOPE	NOTCH IN	NOTCH OUT			
138	13	67063	015	28 ^A	RAW	5:55	100	75	190	2		West	10'	1/5	4	✓	6sec	AGC	EAMS					90	Fast	640	124	8	36	out	Cable Delay				
	14		016	29 ^A		6:00	100	75	190	2																						*48 DEAD			
	15		017	30 ^A		6:10	100	75	190	2																									
	16		020	31 ^A		6:25	100	75	190	2																									
	17		021	32 ^A		6:35	100	75	190	2																									
	18		022	33 ^A		7:00	100	75	190	2																									
	19		023	34 ^A		7:10	100	75	190	2																									
	20		024	35 ^A		7:15	100	75	190	2																									
	21		025	36 ^A		7:30	100	75	190	2																									+48 Noisy *95 DEAD

SEISMOMETER AND SPREAD INFORMATION						
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB

UPPER SET LIMIT 62.5%

LOWER SET LIMIT 18 %

FORMAT TYPE:

9 TRACK 21 TRACK

GALVO LEVEL:

1.48 DB AUX 15 DB

OTHER:

MISCELLANEOUS INFORMATION:

CLIENT		PARTY NO	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																							
NAVY		1186	NPR-4	NORTH SLOPE	ALASKA	USA	7:00	7:30	8:00	9:30	4/24/76	R. Wain	2 of 2																							
LINE	PROFILE	IDENTIFICATION		SHOT CAL.	PLAY BACK	TIME	SIZE	SHOT		NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SPREAD		S.P. SEIS. OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	TAPE			MODE	GAIN					RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FILTERS		NOTCH	REMARKS
		FILE NUMBER	REEL NUMBER					TOP	BOT.						SEIS. DEPTH	RECORD LENGTH					PARITY ERRORS	1-4/24	5-8		9-12	13-16	17-20	21-24	FINAL GAIN DB				FREQ.	SLOPE		

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION		DFS III SYSTEM PARAMETERS:		MISCELLANEOUS INFORMATION:	
CODE	SEIS. TYPE	NO./GR.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN					
									GAIN CONSTANT	30	DB
									UPPER SET LIMIT	62.5	%
									LOWER SET LIMIT	18	%
									FORMAT TYPE:		
									<input type="checkbox"/> 9 TRACK	<input checked="" type="checkbox"/> 21 TRACK	
									GALVO LEVEL:		
									1-18 DB	AUX 15 DB	
									OTHER:		

Began Using ALL STICK POWDER

W.D.P.

#97x98 DEAD

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																										
US NAVY		1186	APR 4	NORTH SLOPE	ALASKA	USA	700	7:30	8:00	9:30	4-24-76	R WEIR	1 of																										
IDENTIFICATION					SHOT					SPREAD					TAPE					GAIN					FILTERS			REMARKS											
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SEIS. OFFSET	SEIS. DEPTH	COP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	1-4/24	5-8	9-12	13-16	17-20	21-24		FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	SLOPE	NOTCH IN OUT				
138	22	67263	041	1 ^A	DPS MON	9:25	100	75/90	2			W		10'		1		X	6sec		AGC	98	98	98	98	98	98	90	FAST	640	124	8	36	OUT	Records #26 to #40 used for tests.				
	23		042	2 ^A	RAW	9:35	100	75/90	2																														
	24		043	3 ^A		9:40	100	75/90	2																														
	25		044	4 ^A		10:05	100	75/90	2																														
	26		045	5 ^A		10:45	100	75/90	2																														
	27		046	6 ^A		10:25	100	75/90	2																														
	28		047	7 ^A		10:30	100	75/90	2																														
	29		050	8 ^A		10:40	100	90/105	2*																														
	30		051	9 ^A		11:35	100	90/105	2*																														
	31		052	10 ^A		11:50	100	75/90	2																														
	32		053	11 ^A		12:15	100	75/90	2																														
	33		054	12 ^A		12:25	100	75/90	2																														
	34		055	13 ^A		1:05	100	75/90	2																														
	35		056	14 ^A		1:15	100	90/105	2*																														
	36		057	15 ^A		1:25	100	75/90	2																														
	37		060	16 ^A		1:45	100	75/90	2																														
	38		061	17 ^A		1:50	100	75/90	2																														
	39		062	18 ^A		2:30	100	90/105	2*																														
	40		063	19 ^A		2:35	100	75/90	2																														
	41		064	20 ^A		2:45	100	90/105	2*																														
	42		065	21 ^A		2:55	100	75/90	2																														
	43		066	22 ^A		3:05	100	75/90	2																														
	44		067	23 ^A		3:15	100	75/90	2																														
	45		070	24 ^A		3:25	100	75/90	2																														
	46	67264	071	25 ^A		4:20	100	75/90	2																														
	47		072	26 ^A		4:25	100	75/90	2																														
	48		073	27 ^A		4:35	100	90/105	2*																														
	49		074	28 ^A		4:55	100	75/90	2																														

(1-4 DEAD *KDP WRONG)

TAPE CANNEL

SEISMOMETER AND SPREAD INFORMATION					
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.

SHOT CONFIGURATION				
NO.	DIR.	CODE	SEIS. DEPTH	SETUP

DFS III SYSTEM PARAMETERS:
GAIN CONSTANT 30 DB
UPPER SET LIMIT 62.5 %
LOWER SET LIMIT 18 %
FORMAT TYPE:
<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK
GALVO LEVEL:
1-48 18 DB AUX 15 DB
OTHER:

MISCELLANEOUS INFORMATION:

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																								
NAVY		1186	NPR-4	NORTH SLOPE	Alaska	USA	7:20	8:30	9:30	10:00	4/25/76	R. LAKE	1 of 2																								
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS		REMARKS															
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S. SEIS. OFFSET	SEIS. DIR. H.T.	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FREQ.	SLOPE	NOTCH IN/OUT			
138	60	67264	122	1A	RAW	9:50	100	85/90	2			WEST		10'		1/1	1	✓	650			AEC	48 48 48 48 48 48	30 42 48 48 48 48	90	Fast	389	129	2	30	cut	W.O.D.					
61			123	2A	RAW	10:00	50	85/90	2	*						1/5																					
62			124	3A		10:05	105	85/90	1		16'E					1/9																			* 4 DEAD ← BEAM BEING COOKED PARALLEL & 5lbs STUCK FOR PRIMER		
63			125	4A		10:10	105	85/90	1							1/9																					
64			126	5A		10:15	105	85/90	1							1/7																					
65			127	6A		10:20	105	85/90	1		19'E					1/21																					
66			130	7A		10:30	105	85/90	1							1/25																					
67			131	8A		10:40	105	85/90	1							1/29	✓																				
68			132	9A		10:45	105	85/90	2							1/23																					
69			133	10A		10:50	105	85/90	2							1/27																					
70			134	11A		11:20	105	85/90	2							1/5	2																				
71			135	12A		11:30	105	85/90	2							1/9																					
72			136	13A		11:50	105	85/90	2							1/12																					W.O.D.
73			137	14A		12:10	105	85/90	2							1/7																					
74			140	15A		12:20	105	85/90	2							1/21																					
75			141	16A		12:50	105	85/90	2							1/25	✓																				W.O.D.
76			142	17A		1:54	105	85/90	2							1/33	3																				
77			143	18A		2:00	105	85/90	2							1/17																					
78			144	19A		2:10	105	85/90	2							1/21																					
79			145	20A		2:20	105	85/90	2							1/25																					
80			146	21A		2:25	105	85/90	2							1/29																					* 45 DEAD
81			147	22A		2:35	105	85/90	2							1/37																					* 41 "
82			150	23A	DPB	3:20	105	85/90	2							1/44	4																				* Hole Blew
83			151	24A		3:30	105	85/90	2							1/5	✓						48 48 48 48 48 48	34 42 48 48 48 48													
84			152	25A		3:49	105	85/90	2							1/8																					
85			153	26A		4:26	105	85/90	2							1/13																					Hole Blew
86			154	27A	DPB	4:39	105	85/90	2							1/19																					Hole Blew
87			155	28A		4:55	105	85/90	2							1/21																					W.O.D.

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION		DFS III SYSTEM PARAMETERS:		MISCELLANEOUS INFORMATION:	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.						

GAIN CONSTANT 50 DB
 UPPER SET LIMIT 62.5 %
 LOWER SET LIMIT 18 %
 FORMAT TYPE:
 P TRACK 21 TRACK
 GALVO LEVEL:
 1-# 18 DB AUX 15 DB
 OTHER:

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																							
us navy		1186	APR 4	North Slope	Alaska	USA	7:00	8:30	9:30	10:00	4-25-76	R WEIR	2 of 2																							
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS		REMARKS														
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	4 S/OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE		1-4/24	5-8	9-12	13-16/27-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	SLOPE	NOTCH IN	OUT	
138	88	67264	156	29 ^A	RAW	5:25	105	85/90	2			West	10'		1/25	4	X	6sec			AGC	48 24	48 42	48 48	48 48	48 48	90	FAST	384	124	8	36	out			
	89		157	30 ^A		5:34	105	85/90	2						1/29	✓																				
	90		160	31 ^A		5:04	105	85/90	2						1/30	5																				
	91		161	32 ^A	RAW DPB	6:23	105	85/90	2						1/31																				WOD	
	92		162	33 ^A	DPB	6:36	105	85/90	2						1/32																				ONE DRILL IN FIELD	
	93		163	34 ^A	RAW	6:45	105	85/90	2						1/33																				TWO DOWN T	
	94	11265	164	35 ^A		7:45	105	85/90	2						1/34																				WOD (tape change)	
	95		165	36 ^A		8:10	105	85/90	2						1/35																				WOD	
	96		166	37 ^A		8:20	105	85/90	2						1/36																				TRACE 45 DEAD	
	97		167	38 ^A		8:50	105	85/90	2						1/37	✓																			TRACE NO 46 DEAD	
	98		170	39 ^A		9:15	105	85/90	2						1/38																					
	99		171	40 ^A		9:35	105	85/90	2						1/39																					TRACE NO 48 DEAD
	100		172	41 ^A		9:45	105	85/90	2						1/40																				LAST SECTOR DAY	

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION				DFS III SYSTEM PARAMETERS:		MISCELLANEOUS INFORMATION:	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.								
										GAIN CONSTANT 30 DB			
										UPPER SET LIMIT 62.5 %			
										LOWER SET LIMIT 18 %			
										FORMAT TYPE:			
										<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK			
										GALVO LEVEL:			
										1-48 18 DB AUX 15 DB			
										OTHER:			