

LINE	IDENTIFICATION				PLAY BACK	TIME	SHOT				SPREAD				TAPE		GAIN						FILTERS		REMARKS												
	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL			SIZE	TOP BOT	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS. OFFSET	SEIS. DEPTH	COP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH IN/OUT			
																						1-4/24	5-8	9-12		13-16	17-20					21-24	FREQ.		SLOPE		
30	452	172645001		1 <sup>A</sup>	RAW	340	50	60/75	2					E	10'					6sec	ACC	54	54	54	30	42	42	90	FAST	540	124	B	36	CLT	Line change time 12:00:35		
	453		002	2 <sup>A</sup>		350	50	60/75	2																												
	454		3	3 <sup>A</sup>		355	50	60/75	2																												
	455		4	4 <sup>A</sup>		400	50	60/75	2																												
	456		5	5 <sup>A</sup>		405	50	60/75	2																												
	457		6	6 <sup>A</sup>		410	50	60/75	2																												
	458		7	7 <sup>A</sup>		415	50	60/75	2																												
	459		10	8 <sup>A</sup>		425	50	60/75	2																												
	460		11	9 <sup>A</sup>		430	50	60/75	2																												
	461		12	10 <sup>A</sup>		435	50	60/75	2																												
	462		13	11 <sup>A</sup>		450	50	60/75	2																												
	463		14	12 <sup>A</sup>		5:30	50	60/75	2																												
	464		15	13 <sup>A</sup>		600	50	60/75	2																												
	465		16	14 <sup>A</sup>		610	50	60/75	2																												
	466		17	15 <sup>A</sup>		615	50	60/75	2																												
	467		20	16 <sup>A</sup>		620	50	60/75	2																												
	468		21	17 <sup>A</sup>		620	50	60/75	2																												
	469		22	18 <sup>A</sup>		635	50	60/75	2																												
	470		23	19 <sup>A</sup>		640	50	60/75	2																												
	471		24	20 <sup>A</sup>		645	50	60/75	2																												

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION				DPS III SYSTEM PARAMETERS:				MISCELLANEOUS INFORMATION:		
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN					GAIN CONSTANT <u>30</u> DB UPPER SET LIMIT <u>62.5</u> % LOWER SET LIMIT <u>18</u> % FORMAT TYPE: <input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK GALVO LEVEL: <u>1.18</u> DB AUX <u>15</u> DB OTHER:					

LINE	PROFILE	IDENTIFICATION		SHOT CAL.	PLAY BACK	TIME	SIZE	SHOT		NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SPREAD				TAPE		GAIN						FILTERS			REMARKS						
		REEL NUMBER	FILE NUMBER					TOP	BOT.						S. P. OFFSET	REIS. DEPT.	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB		RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH
		1-4/24	5-8					9-12	13-16						17-20	21-24	1	2	4	1	2	4	1	2	FREQ.	SLOPE	IN	OUT								
500	27264	76	39 <sup>A</sup>	Raw	1:50	50	60/75	2				E	10'		1/21	5	X	6sec	ACC	59	51	34	50	42	48	90	Fast	646	124	8	36	out	Tape change			
501	27264	77	30 <sup>A</sup>		1:55	50	60/75	2							1/25																					
502	27264	100	31 <sup>A</sup>		2:00	50	60/75	2							1/29																					
503	27264	101	32 <sup>A</sup>		2:15	50	60/75	2							1/33																					
504	27264	102	33 <sup>A</sup>	DRB	2:35	50	60/75	2							1/4	6																				
505	27264	103	34 <sup>A</sup>	Raw	2:50	50	60/75	2							1/4																			Camera repair		
506	27264	104	35 <sup>A</sup>		3:00	50	60/75	2							1/3																			walking on Ranter		
507	27264	105	36 <sup>A</sup>		3:10	50	60/75	2							1/2																					
508	27264	106	37 <sup>A</sup>		3:25	50	60/75	2							1/21																					
509	27264	107	38 <sup>A</sup>		3:45	50	60/75	2							1/25																					
510	27264	110	39 <sup>A</sup>		3:50	50	60/75	2				200'E			1/29																			Trace no 47 suspected		
511	27264	110	40 <sup>A</sup>		3:55	50	60/75	2							1/33																			Trace no 48 Dead		
512	27264	112	41 <sup>A</sup>		4:20	50	60/75	2							1/5	7																		Trace no 47 Dead		
513	27264	113	42 <sup>A</sup>		4:25	50	60/75	2							1/4																					
514	27264	114	43 <sup>A</sup>		4:30	50	60/75	2							1/3																					
515	27264	115	44 <sup>A</sup>		4:45	50	60/75	2							1/7																					
516	27264	116	45 <sup>A</sup>		4:55	50	60/75	2							1/21																					
517	27264	117	46 <sup>A</sup>		5:00	50	60/75	2							1/25																					
518	27264	120	47 <sup>A</sup>		5:05	50	60/75	2							1/29																					
519	27264	121	48 <sup>A</sup>		5:10	50	60/75	2							1/33																					
520	27264	122	49 <sup>A</sup>	DRB	5:45	50	60/75	2							1/5	8																				
521	27264	123	50 <sup>A</sup>	Raw	6:00	50	60/75	2							1/4																				Trace no 1 Pinkney Dead	
522	27264	123	51 <sup>A</sup>		6:10	50	60/75	2							1/3																					
523	27264	124	52 <sup>A</sup>	DRB	6:20	50	60/75	2				300 W			1/7																					
524	27264	125	53 <sup>A</sup>	Raw	6:45	50	60/75	2				200 S			1/21																					Trace no 48 1 Dead
525	27264	126	54 <sup>A</sup>		6:55	50	60/75	2							1/29																				no in trace!	
526	27264	127	55 <sup>A</sup>		7:00	50	60/75	2							1/29																				Trace 28 Dead also 1-4	
527	27264	130	56 <sup>A</sup>		8:00	50	60/75	2							1/33																				Bad cable and traces 41	

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

NO. 1 DIR.	CODE	S.P. OFFSET	REIS. DEPT.	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE
E		10'		1/21	5	X	6sec		ACC

DPF III SYSTEM PARAMETERS:  
 GAIN CONSTANT 30 DB  
 UPPER SET LIMIT 12.5 %  
 LOWER SET LIMIT 18 %  
 FORMAT TYPE:  
 9 TRACK  21 TRACK  
 GALVO LEVEL:  
 1-92 18 DB AUX 15 DB  
 OTHER:

MISCELLANEOUS INFORMATION:  
 36  
 32

LINE	IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS			REMARKS													
	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	TOP BOT	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	R SEIS OFFSET	R SEIS DIR.	COP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH				
																					1-4/24	5-8	9-12		13-16	17-20					21-24	FREQ.	SLOPE	IN	OUT		
30	472	672245	42	1 <sup>A</sup>	SPB	8:15	50	60/75	2			E	10'	1/5	1	X	6500			AGC	54	54	54	30	42	48	90	145	540	124	8	36	OUT	test Rec. no. 25-36 Pulse test 41 Rec'd 3744 no gain Trace no. 44 Dead			
	473		43	2 <sup>A</sup>	RAW	8:30	50	60/75	2					1/5																							
	474		44	3 <sup>A</sup>	SPB	8:45	50	60/75	2					1/5	2																				Trace no. 37 Dead		
	475		45	4 <sup>A</sup>	SPB	9:00	50	60/75	2					1/5																					Trace no. 33 Dead		
	476		46	5 <sup>A</sup>	SPB	9:15	50	60/75	2					1/5																					Trace no. 29 Dead		
	477		47	6 <sup>A</sup>	RAW	9:30	50	60/75	2					1/5																							
	478		50	7 <sup>A</sup>	RAW	9:30	50	60/75	2					1/5																							
	479		51	8 <sup>A</sup>		9:35	50	60/75	2					1/5																							
	480		52	9 <sup>A</sup>	SPB	10:00	50	60/75	2					1/5	3																						
	481		53	10 <sup>A</sup>	RAW	10:20	50	60/75	2					1/5																						CDP set wrong	
	482		54	11 <sup>A</sup>	RAW	10:25	50	60/75	2					1/5																					Camera Repair		
	483		55	12 <sup>A</sup>		10:30	50	60/75	2					1/5																							
	484		56	13 <sup>A</sup>		10:40	50	60/75	2					1/5																							
	485		57	14 <sup>A</sup>		10:50	50	60/75	2					1/5																							
	486		60	15 <sup>A</sup>		11:00	50	60/75	2					1/5																							
	487		61	16 <sup>A</sup>		11:10	50	60/75	2					1/5																							
	488		62	17 <sup>A</sup>		11:35	50	60/75	2					1/5	4																						
	489		63	18 <sup>A</sup>		11:45	50	60/75	2					1/5																							
	490		64	19 <sup>A</sup>		11:50	50	60/75	2					1/5																							
	491		65	20 <sup>A</sup>		12:00	50	60/75	2					1/5																							
	492		66	21 <sup>A</sup>		12:10	50	60/75	2					1/5																							
	493		67	22 <sup>A</sup>		12:20	50	60/75	2					1/5																							
	494		70	23 <sup>A</sup>		12:25	50	60/75	2					1/5																							
	495		71	24 <sup>A</sup>		12:30	50	60/75	2					1/5																							
	496		72	25 <sup>A</sup>	SPB	1:00	50	60/75	2					1/5	5																						
	497		73	26 <sup>A</sup>	RAW	1:10	50	60/75	2					1/5																							
	498		74	27 <sup>A</sup>	SPB	1:30	50	60/75	2					1/5																							
	499		75	28 <sup>A</sup>	RAW	1:35	50	60/75	2					1/5																							

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

NO. 1 DIR.	R SEIS OFFSET	R SEIS DIR.	COP SWITCH	SETUP

SEIS III SYSTEM PARAMETERS:  
 GAIN CONSTANT 30 DB  
 UPPER SET LIMIT 62.5 %  
 LOWER SET LIMIT 18 %  
 FORMAT TYPE:  
 9 TRACK  21 TRACK  
 GALVO LEVEL:  
1.48 DB AUX 1.5 DB  
 OTHER:

MISCELLANEOUS INFORMATION:  
 2 1/2 Antony on Printer  
second rec. end of tape

CLIENT: US Navy PARTY NO.: 1186 PROSPECT: NPR 4 COUNTY: NOOKS CO. STATE: ALASKA COUNTRY: USA LEFT STORAGE: 7 ARRIVED FIELD: 73 LEFT FIELD: 845 ARRIVED STORAGE: DATE: 3/31/76 OBSERVER: G. Gaudet PAGE: 3 of 3

LINE	IDENTIFICATION				SHOT				SPREAD				TAPE		GAIN						FILTERS		REMARKS														
	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	SP. OFFSET	NO. 1 DIR.	CODE	A SEIS. OFFSET	B SEIS. OFFSET	CDP DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE		INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH	
																								1-4/24	5-8	9-12	13-16	17-20	21-24					FREQ.	SLOPE	IN	OUT
30	528	677646	131	57 <sup>H</sup>	RAW	810	50	60/15	2					10'	1/2	9			2	6sec		AGC	54	54	54	54	54	54	90	FAT	140	124	8	36	60	60	
	529		132	58 <sup>A</sup>		815	50	60/15	2																												
	530		133	59 <sup>H</sup>		820	50	60/15	2																												
	531		134	60 <sup>H</sup>		830	50	60/15	2																												
	532		135	61 <sup>H</sup>		845	50	60/15	2																												

LAST SHOT OF DAY!

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

NO.	TYPE	DEPTH	SPREAD	OTHER

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB  
 UPPER SET LIMIT 22.5 %  
 LOWER SET LIMIT 18 %  
 FORMAT TYPE:  
 9 TRACK  21 TRACK  
 GALVO LEVEL:  
 1-34 DB AUX 15 DB  
 OTHER:

MISCELLANEOUS INFORMATION:



CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																						
U.S. NAVY		1186	NR4	NEKSON	Alaska	USA	700	800			4-1-76	Gibson	1 of 1																						
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS				REMARKS											
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	TOP BOT	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH	
30	533	67264	143	1 <sup>A</sup>	RWAV	830	50	60/75	2			E		10'	1/25	1	X	6500			AGC	54/48	54/48	54/30	54/34	54/54	90	FRT	640	124	8	36	out	Bad weather strong wind shut down EARLY  Trace no 34 Dead  SP nos 541-551 skips  hole blew no uphole  Trace no 47 Dead Trace no 43 Dead Last shot of Day	
	534		144	2 <sup>A</sup>		845	50	60/75	2																										
	535		145	3 <sup>A</sup>		855	50	60/75	2																										
	536		146	4 <sup>A</sup>		900	50	60/75	2																										
	537		147	5 <sup>A</sup>		910	50	60/75	2																										
	538		150	6 <sup>A</sup>		915	50	60/75	2																										
	539		151	7 <sup>A</sup>		925	50	60/75	2																										
	540		152	8 <sup>A</sup>		935	50	60/75	2								2																		
	541					SKIP																													
	542					SKIP																													
	543					SKIP																													
	552		153	9 <sup>A</sup>		2:15	50	60/75	2		300'						3																		
	553		154	10 <sup>A</sup>		2:36	50	60/75	2																										
	554		155	11 <sup>A</sup>		2:45	50	60/75	2																										
	555		156	12 <sup>A</sup>		3:00	50	60/75	2																										
TRIP	556	67214b	157	13 <sup>A</sup>		3:10	50	60/75	2																										
	557	67215a	160	14 <sup>A</sup>		3:30	50	60/75	2																										
	558		161	15 <sup>A</sup>		3:40	50	60/75	2																										
	559		162	16 <sup>A</sup>		3:56	50	60/75	2																										

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION		DFS III SYSTEM PARAMETERS:		MISCELLANEOUS INFORMATION:	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN			GAIN CONSTANT	UPPER SET LIMIT	LOWER SET LIMIT
									30 DB	82.5 %	18 %
									FORMAT TYPE:		
									<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK		
									GALVO LEVEL:		
									148 DB AUX 15 DB		
									OTHER:		

CLIENT		PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE																													
US Army		1186	APR 4	Adak scope	ALASKA	USA	7	830			4 2 76	Clubert	1 of																													
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS		REMARKS																				
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL.	PLAY BACK	TIME	SIZE	TOP BOT.	NO CAPS	CODE	S.P. OFFSET	NO. DIR.	CODE	S.P. OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE		INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH IN/OUT							
																			1 2 4				1-4/24	5-8	9-12	13-16	17-20	21-24														
30	560	17247	1768	1 <sup>A</sup>	RAW	9:15	50	60/75	2			E			10'	1/5	1		X		6sec	AGC	54/48	50/42	50/30	50/30	50/30	50/30	50/30	90	FAST	690	124	30	act	tests 153 - 184 Pulse tests 185 recovered numbers						
	561		1777	2 <sup>A</sup>		9:30	50	60/75	2							1/4																										
	562		200	3 <sup>A</sup>		9:40	50	60/75	2							1/3																										
	563		201	4 <sup>A</sup>		9:50	50	60/75	2							1/2																										
	564		202	5 <sup>A</sup>		10:00	50	60/75	2							1/2																										
	565		203	6 <sup>A</sup>		10:15	50	60/75	2							1/2.5																										
	566		204	7 <sup>A</sup>		10:30	50	60/75	2							1/2.9																										
	567		205	8 <sup>A</sup>		10:35	50	60/75	2							1/3.3																										
	568		206	9 <sup>A</sup>		11:00	50	60/75	2							1/5	2																									
	569		207	10 <sup>A</sup>		11:15	50	60/75	2							1/5																										
	570		210	11 <sup>A</sup>		11:25	50	60/75	2							1/5																										
	571		211	12 <sup>A</sup>		11:30	50	60/75	2							1/7																										
	572		212	13 <sup>A</sup>		12:00	50	60/75	2							1/5	3																									
	573		213	14 <sup>A</sup>		12:20	50	60/75	2							1/9																										
	574		214	15 <sup>A</sup>		12:30	50	60/75	2							1/13																										
	575		215	16 <sup>A</sup>		12:45	50	60/75	2							1/17	6						48/48	48/42	48/30	48/30	48/30	48/30														
	576		216	17 <sup>A</sup>		1:00	50	60/75	2							1/21																										
	577		217	18 <sup>A</sup>		1:15	50	60/75	2							1/25																										
	578		220	19 <sup>A</sup>		2:10	50	60/75	2							1/5	4																									
	579		221	20 <sup>A</sup>		2:20	50	60/75	2							1/5																										
	580		222	21 <sup>A</sup>		2:45	50	60/75	2							1/5.5																										
	581		223	22 <sup>A</sup>		2:50	50	60/75	2							1/3																										
	582		224	23 <sup>A</sup>		3:00	50	60/75	2							1/3																										
	583		225	24 <sup>A</sup>		3:15	50	60/75	2							1/2																										
	584		226	25 <sup>A</sup>		3:30	50	60/75	2							1/2.1																										
	585		227	26 <sup>A</sup>		4:00	50	60/75	2							1/2.5																										
	586		230	27 <sup>A</sup>		4:15	50	60/75	2							1/2.9																										
	587		231	28 <sup>A</sup>		4:20	50	60/75	2							1/3.3																										

SEISMOMETER AND SPREAD INFORMATION						SHOT CONFIGURATION	
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN	

DFS III SYSTEM PARAMETERS:	
GAIN CONSTANT	30 DB
UPPER SET LIMIT	125 %
LOWER SET LIMIT	18 %
FORMAT TYPE:	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK
GALVO LEVEL:	1-12 DB AUX 15 DB
OTHER:	

MISCELLANEOUS INFORMATION:	





CLIENT: U.S. MARCY PARTY NO: 186 PROSPECT: APR 4 COUNTY: North Slope STATE: Alaska COUNTRY: USA LEFT STORAGE: 7 ARRIVED FIELD: 400\* LEFT FIELD: ARRIVED STORAGE: DATE: 4476 OBSERVER: H. H. Heston PAGE: 1 of 1

LINE	PROFILE	IDENTIFICATION		SHOT CAL	PLAY BACK	TIME	SIZE	SHOT		NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SPREAD			CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	GAIN						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	FILTERS		REMARKS		
		REEL NUMBER	FILE NUMBER					TOP	BOT						SEIS. OFFSET	SEIS. DEPTH	1							2	4	INITIAL GAIN (DB)								LOW CUT	NOTCH			
																										1-4/24	5-8	9-12	13-16					17-20	21-24		FREQ.	SLOPE
30	451	677850	14	1A	DRB	500	50	790	2				W		10'	1/17	1	*	600		AGC	18	25	30	35	40	45	50	90	FAST	640	124	8	36	cut	test Records #1-12 Pulse test Rec. no. 13 traces 1-4 Dead 4 1/2 sec. Record		

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

LINE	SHOT	NO. 1 DIR.	SPREAD	CDP SWITCH	SETUP
30	1A	W	10'	1/17	1

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB  
 UPPER SET LIMIT 62.5 %  
 LOWER SET LIMIT 15 %  
 FORMAT TYPE:  
 9 TRACK  21 TRACK  
 GALVO LEVEL:  
~~15~~ 12 DB AUX 15 DB  
 OTHER:

MISCELLANEOUS INFORMATION: \*  
 Long camp move to line  
 started moving at 700  
 started capping out at 300





CLIENT: US NAVY PARTY NO: 1186 PROSPECT: NPRU COUNTY: North Slope Alaska STATE: USA COUNTRY: USA LEFT STORAGE: 700 ARRIVED FIELD: 730 LEFT FIELD: 14:9:00 ARRIVED STORAGE: 4-5-76 DATE: 4-5-76 OBSERVER: C. Robert PAGE: 2 of 2

LINE	IDENTIFICATION				PLAY BACK	TIME	SHOT			SPREAD				SETUP	TAPE		GAIN						FILTERS		REMARKS									
	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL			SIZE	TOP	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE		S.P. OFFSET	SEIS DEPTH	CDP SWITCH	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH	
																					1-4/24	5-8	9-12	13-16		17-20					21-24	FREQ.		SLOPE
30	422	672150	65	28 <sup>A</sup>	Raw	3:10	50	60/75	2		W	10'	1/17	7	X	6sec	AGC	48	48	48	30	42	48	90	Fast	140	124	8	36	out				
	421		66	29 <sup>A</sup>		4:15	50	60/75	2				1/23	8																	Withing on logs			
	420		67	30 <sup>A</sup>		4:25	50	60/75	2				1/24																					
	419		70	31 <sup>A</sup>		4:30	50	60/75	2				1/23																					
	428		71	32 <sup>A</sup>	RAW	4:45	50	60/75	2				1/17																					
	417		72	33 <sup>A</sup>	RAW	4:55	50	60/75	2				1/25																					
	416		73	34 <sup>A</sup>	RAW	5:00	50	60/75	2				1/25																					
	415		74	35 <sup>A</sup>		5:20	50	60/75	2				1/29																					
	414		75	36 <sup>A</sup>		5:30	50	60/75	2				1/33																					
	413		76	37 <sup>A</sup>		5:35	50	60/75	2				1/37																					
	412		77	38 <sup>A</sup>		5:40	50	60/75	2				1/41																					
	411		100	39 <sup>A</sup>		5:55	50	60/75	2				1/45																					
	410		101	40 <sup>A</sup>		6:00	50	60/75	2				1/49																					
	409		102	41 <sup>A</sup>	DRB	6:45	50	60/75	2				1/5																					
	408		103	42 <sup>A</sup>	DRB	6:50	50	60/75	2				1/9																					
	407		104	43 <sup>A</sup>		7:00	50	60/75	2				1/13																					
	406		105	44 <sup>A</sup>		7:10	50	60/75	2				1/17																			last shot of day		

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

NO. 1 DIR.	NO. 2 DIR.	NO. 3 DIR.	NO. 4 DIR.	NO. 5 DIR.	NO. 6 DIR.	NO. 7 DIR.	NO. 8 DIR.	NO. 9 DIR.	NO. 10 DIR.

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB  
 UPPER SET LIMIT 62.5 %  
 LOWER SET LIMIT 18 %  
 FORMAT TYPE:  
 9 TRACK  21 TRACK  
 GALVO LEVEL:  
 1.48 18 DB AUX 15 DB  
 OTHER:

MISCELLANEOUS INFORMATION:



CLIENT		PARTY NO.		PROSPECT		COUNTY		STATE		COUNTRY		LEFT STORAGE		ARRIVED FIELD		LEFT FIELD		ARRIVED STORAGE		DATE		OBSERVER		PAGE												
Navy		1186		NPR-4		Alaska		Alaska		USA		7:00		7:30						1/16/76		R. H. Hain		2 of 2												
IDENTIFICATION				SHOT				SPREAD				TAPE				GAIN				FILTERS				REMARKS												
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY BACK	TIME	SIZE	TOP BOT	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.E. OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH		
																						1-4/24	8-8		8-12	13-16/17	20-21-24					24	FREQ.	SLOPE	IN	OUT
30	377	1255	155	29 <sup>A</sup>	RAW	3:30	50	60/75	2			W	10'		1/21	4	✓	6500	AGC	54	54	54	54	54	54	90	Fast	0.690	124	8	36	out				
	376		156	30 <sup>A</sup>		3:40	50	60/75	2						1/25																					
	375		157	31 <sup>A</sup>		3:50	50	60/75	2						1/29																					
	374		160	72 <sup>A</sup>		4:00	50	60/75	2						1/33																		97498 Dead			
	373		161	33 <sup>A</sup>		4:50	50	60/75	2						1/5	5																	Cable Delay			
	372		162	34 <sup>A</sup>		5:00	50	60/75	2						1/9																					
	371		163	35 <sup>A</sup>		5:15	50	60/75	2						1/9																					
	370		164	36 <sup>A</sup>		5:30	50	60/75	2						1/17																		48 Dead			
	369		165	37 <sup>A</sup>		5:45	50	60/75	2						1/21																					
	368		166	38 <sup>A</sup>		6:00	50	60/75	2						1/25																					
	367		167	39 <sup>A</sup>		6:15	50	60/75	2						1/29																					
	366		170	40 <sup>A</sup>		6:30	50	60/75	2						1/33																			47498 Dead		
	365		171	41 <sup>A</sup>		7:00	50	60/75	2						1/1	6																	CDP in wrong position			
	364		172	42 <sup>A</sup>		7:10	50	60/75	2						1/13																					
	363		173	43 <sup>A</sup>		7:20	50	60/75	2						1/17																					
	362		174	44 <sup>A</sup>		7:25	50	60/75	2						1/21																			Trace no 48 Dead		
	361		175	45 <sup>A</sup>		7:35	50	60/75	2						1/5	7																	Moved up to six feet			
	360		176	46 <sup>A</sup>		7:40	50	60/75	2						1/4																					
	359		177	47 <sup>A</sup>		7:50	50	60/75	2						1/13																					
	358		200	48 <sup>A</sup>		8:00	50	60/75	2						1/9																			Last shot of Day		

SEISMOMETER AND SPREAD INFORMATION					
CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.

SHOT CONFIGURATION	

DFS III SYSTEM PARAMETERS:
GAIN CONSTANT <u>30</u> DB
UPPER SET LIMIT <u>62.5</u> %
LOWER SET LIMIT <u>25</u> %
FORMAT TYPE:
<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK
GALVO LEVEL:
1- <u>18</u> DB AUX <u>15</u> DB
OTHER:

MISCELLANEOUS INFORMATION:



CLIENT **NAVY** PARTY NO. **1186** PROSPECT **NPR-4** COUNTY STATE **Alaska** COUNTRY **USA** LEFT STORAGE **7:00** ARRIVED FIELD **8:00** LEFT FIELD DATE **4/17/76** OBSERVER **R. Weir** PAGE **1 of 1**

LINE	IDENTIFICATION				SHOT	PLAY BACK	TIME	SIZE	TOP BOT	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	SPREAD				SETUP	TAPE				GAIN						FILTERS		REMARKS							
	PROFILE	REEL NUMBER	FILE NUMBER	CAL										SEIS. OFFSET		SEIS. DEPTH	CDP SWITCH		RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY		HIGH CUT FREQ.	LOW CUT	NOTCH				
														A	B							1-47 24	8-8	8-12	13-16	17-20	21-24					FREQ.	SLOPE	IN OUT				
30	357	172652	214	1A	max 248	9:45	50	60/75	2			W	10'	1/5	1	✓	6500			AGC	54	54	54	54	48	56	90	Fast	.690	124	8	36	out	FIXING JUGS				
	356		215	2A		9:15	50	60/75	2					1/4																								
	355		216	3A		9:20	50	60/75	2					1/13																								
	354		217	4A		9:30	50	60/75	2					1/7																								
	353		220	5A		9:40	50	60/75	2					1/21																								
	352		221	6A		9:50	50	60/75	2					1/25																								
	351		222	7A		10:00	50	60/75	2					1/29																								
	350		223	8A		10:10	50	60/75	2					1/33																					* 48 DEAD			
	349		224	9A		11:00	50	60/75	2					1/5	2					lots															* HIGH PARITY			
	348		225	10A		11:10	50	60/75	2					1/9																								
	347		226	11A		11:20	50	60/75	2					1/13																								
	346		227	12A		11:30	50	60/75	2					1/17																								
	345		230	13A		12:00	50	60/75	2					1/21																								
	344		231	14A		12:10	50	60/75	2					1/25																								
	343		232	15A		12:30	50	60/75	2					1/29																								
	342		233	16A		1:15	50	60/75	2					1/33																								
	341		234	17A		1:30	50	60/75	2					1/37																								
	340		235	18A		2:05	50	60/75	2					1/41	3																							
	339		236	19A		2:15	50	60/75	2					1/5																								
	338		237	20A		2:30	50	60/75	2					1/9																								
	337		240	21A		2:50	50	60/75	2					1/13																								
	336		241	22A		3:30	50	60/75	2					1/17																								
	335		242	23A		4:00	50	60/75	2					1/21																								
	334		243	24A		4:20	50	60/75	2					1/25																								
	333		244	25A		4:40	50	60/75	2					1/29																								
	332		245	26A		4:50	50	60/75	2					1/33																								
	331		246	27A		5:30	50	60/75	2					1/17	4																							
	330		247	28A		5:40	50	60/75	2					1/21																								

SEISMOMETER AND SPREAD INFORMATION

DE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

NO.	TYPE	DEPTH	ANGLE	SPREAD

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 50 DB  
 UPPER SET LIMIT 12.5 %  
 LOWER SET LIMIT 18 %  
 FORMAT TYPE:  
 9 TRACK  3-2 TRACK  
 GALVO LEVEL:  
148.18 DB AUX 15 DB  
 OTHER:

MISCELLANEOUS INFORMATION:

\* 17 DEAD  
 \* 48 DEAD  
 \* 48 NOISY  
 \* 48 DEAD  
 \* 48 NOISY  
 \* 48 DEAD  
 \* 48 NOISY



RECORDER FIELD DATA TI-12250-A

CLIENT NAVY PARTY NO. 1186 PROSPECT NPR-4 COUNTY STATE ALASKA COUNTRY USA LEFT STORAGE 7:00 ARRIVED FIELD 8:00 LEFT FIELD ARRIVED STORAGE DATE 7/17/66 OBSERVER R. Rubin

LINE	PROFILE	REEL NUMBER	FILE NUMBER	IDENTIFICATION		TIME	SIZE	SHOT		NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	SPREAD				SETUP	SAMPLE RATE MS	TAPE		GAIN						FILTERS		REMARKS								
				CAL	PLAY BACK			TOP	BOT						R SEIS OFFSET	L SEIS OFFSET	CDP SWITCH	1			2	4	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB)						FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT		NOTCH	
																										1-4	5-8	9-12	13-16	17-20						21-24	FREQ.		SLOPE
30	329	172652	250	29A	RAW	6:05	50	60'	75'	2		WEST		10'	125	A	✓	6000	AGC	48	48	48	48	42	56	90	FAST	.60	124	8	56	out							
	328		251	30A		6:10	50	60'	75'	2		280' WEST																											
	327		252	31A		6:15	50	60'	75'	2																													
	326		253	32A		6:25	50	60'	75'	2																													
	325		254	33A		6:30	50	60'	75'	2																													
	324		255	34A		6:40	50	60'	75'	2		450' WEST																				*47 DEAD + 40-HOLE							
	323		256	35A		6:45	50	60'	75'	2																					*43								
	322		257	36A		6:50	50	60'	75'	2																					*39 DEAD								
<p>END OF LINE 30 — COMPLETE PICKUP —</p>																																							

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB

UPPER SET LIMIT 63.5 %

LOWER SET LIMIT 18 %

FORMAT TYPE:

9 TRACK  1 TRACK

GALVO LEVEL:

1.40 DB AUX 1.5 DB

OTHER:

MISCELLANEOUS INFORMATION: