

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky Oil</u>	PROSPECT: <u>Det 4</u>	AREA: <u>North Slope Alaska</u>	LINE NO: <u>122</u>					
	PARTY NO: <u>1186</u>	INST. ENG: <u>APPY/Hubert</u>		DATE: <u>MO 4 DAY 12 YR 77</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III	<input checked="" type="checkbox"/> DES X <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 2 TRACK	FORMAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) (2) (3) (4) (5) (6) (7)	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____ DATA CHANNEL NOS. _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS. _____					
PARAMETER	RECORD LENGTH: <u>B</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input checked="" type="checkbox"/> FINAL	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	H1 CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>30</u> db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Inline</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <u>Geo Space</u>	PATTERN: <u>Inline</u>	RESISTANCE: <u>170</u> ohms	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>220</u>	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>1200%</u>	DIRECTION OF PROGRESSION: <u>North</u>	LEADING GROUP: <u>96</u>			

DIAGRAMS/MISC. INFORMATION: YRANIC time = 2 hours  
Recording time = 13 hours 13.0 TOTAL.

Start of Line 122

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT			SPREAD		REMARKS:	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TR 1-48
400	6727335	11	22/23	26/27	29/30	32	35	37			1		
401	6727336	11			110	105					540		
402		9			110	105					545		
403		10			110	105					550		
404		11			110	105					600		
405		12			110	105					610		
406		13			110	105	3130	North			615		
407		14			110	605					625		
408		15			110	105					630		
409		16			110	105					640		
410		17			110	105					645		
411		18			110	105		W. S. E.			700		

tail spread 6 traces

96 Party errors R1-R3 S1 Fault lights

9-1-2 Dead Instrument Problems

1-2-9 Dead

1-2-9 Dead

1-2-9 Dead

1-2-9 Dead no upHole

1-2-9 Dead

91 Party errors R1 R3 S1 Fault lights

1-2-9-22 Dead

1-2-9-22 Dead

1-2-9-22 Dead no upHole

9-22 Dead no upHole LAST Shot of Day

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky Oil</u>	PROJECT: <u>Dot 4</u>	AREA: <u>North Slope ALASKA</u>	LINE NO: <u>127</u>					
	PARTY NO: <u>1186</u>	INST. ENG: <u>U. K. K. K.</u>		DATE: <u>4 DAY 13 77</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVEN	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input checked="" type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT:	INPUT IMPEDANCE:	ohms	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:				AUXILIARY DATA:				
	DATA CHANNEL NOS.:				AUXILIARY CHANNEL NOS.:				
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS:	LO CUT HZ SLOPE	H CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE:	NUMBERS ON MAG. TAPE	DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/>	ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Twine</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CHG/ HOLE: <u>110</u>	HOLE DEPTH: <u>105</u>	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: <u>Geo Space</u>	PATTERN: <u>Twine</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: <u>Series</u>	RESISTANCE: <u>770</u> ohms							
SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>1200%</u>	DIRECTION OF PROGRESSION: <u>North</u>	OFFSET GROUP 1:	OFFSET GROUP 96:	LEADING GROUP: <u>96</u>	

DIAGRAMS/MISC. INFORMATION:

travel time = 3  
recording time = 12 1/2      15 1/2

SHOTPOINT	TR. 10		TR. 10		SHOT			SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	NO.	DEPTH	NO. OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR. 10	TR. 10	TR. 10	TR. 10
4112	6121738	30			11	105	11		13	900	1				
4113		31			12	105	12		14	915					
4114		32			13	105	13		15	925					
4115		33			14	105	14		16	930					
4116		34			15	105	15		17	945					
4117		35			16	105	16		18	1130	2				
4118		36			17	105	17		19	1200					
4119		37			18	105	18		20	1210					
420		38			19	105	19		21	1215					
421		39			20	105	20		22	1230					
422		40			21	105	21		23	1240					
423		41			22	105	22		24	1250					
424		42			23	105	23		25	100					
425		43			24	105	24		26	110					
426		44			25	105	25		27	435	3				
427		45			26	105	26		28	445					
428		46			27	105	27		29	500					
429		47			28	105	28		30						

Remarks: Most records - 19 - 28  
rest same break record no 29

1-13-82 Dead

10 Dead

6 Dead

moved up

1-4 Dead

waiting on smaller trucks! 96 Dead

1-33-43 Dead

trace no 5 Dead

trace no 1 Dead

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky Oil</b>	PROJECT: <b>Refy</b>	AREA: <b>North Slope</b>	LINE NO: <b>122</b>								
	PARTY NO: <b>1186</b>	INST. ENG: <b>L. TOUBERT</b>		DATE: <b>MO 4 DAY 13 YE 77</b>								
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input checked="" type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 600 BPI			
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1)	(2)	(3)	(4)	(5)	(6)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____			(ON MAG TAPE)			AUXILIARY DATA:					
PARAMETER	DATA CHANNEL NOS. _____						AUXILIARY CHANNEL NOS. _____					
DISPLAY	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 50 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
CFS I	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG. TAPE		DOWNBREAK <input type="checkbox"/> ON DISPLAY		R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
RECEIVER	TYPE: <b>GEOSPACE</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
SPREAD	CONNECTION: <b>SERIES</b>	RESISTANCE: <b>770</b> ohms	STAGGER: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP. _____				
	NO. OF GROUPS: _____	GROUP INTERVAL: <b>220</b>	SHOTPOINT INTERVAL: <b>880</b>	FOLD: <b>120V%</b>		DIRECTION OF PROGRESSION: <b>NORTH</b>		LEADING GROUP: <b>96</b>				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT					SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		HT.	HT.	HT.	HT.
430	672	737	449		110	105	19			1/21	725	3				
431		50			110	105	20			1/25	430					
432		51			110	105	21			1/29	440					
433		52			110	105	22			1/5	400	4				
434		53			110	105	23			1/9	625					
435		54			110	105	24			1/13	635					
436		55			110	105	25			1/15	700					
437		56			110	105	26			1/19	710					
438		57			110	105	27			1/23	720					
439		58			110	105	28			1/27	730					
440		59			110	105	29			1/31	735					

IFP Test Record no 48



moved up

95 Dead  
91 Dead

LAST SHOT OF DAY

# LAND SEISMIC RECORDING LOG

1-12



	CLIENT: <u>Husky o.c.</u>	PROSPECT: <u>Poly</u>	AREA: <u>North Slope Alaska</u>	LINE NO: <u>122</u>					
PARTY NO: <u>1186</u>		INST. ENG: <u>Carroll</u>		DATE: <u>MO 4 DAY 14 YR 77</u>					
INSTRUMENT [9-TRACK]	<input checked="" type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS	TYPE: <input type="checkbox"/> DFS III	<input checked="" type="checkbox"/> 9 TRACK	<input type="checkbox"/> GAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI	(HI) <input type="checkbox"/> 712 BPI	<input type="checkbox"/> 1900 BPI
	<input checked="" type="checkbox"/> 2 SYSTEM	<input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> EVENS	<input type="checkbox"/> DFS IX	<input type="checkbox"/> 21 TRACK	<input type="checkbox"/> UNGAPPED			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____		(ON MAG TAPE)		AUXILIARY DATA:				
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL	<input type="checkbox"/> MANUAL	FILTERS: _____				
DISPLAY	MODE: <input checked="" type="checkbox"/> AOC	INITIAL GAIN: <u>30</u> db	JRIP SENS: _____ db	<input type="checkbox"/> FINAL	<input type="checkbox"/> OPERATE	LO CUT HZ SLOPE: _____		HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE	PATTERN: <u>Inline</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	CONNECTION: <u>Geo space</u>	RESISTANCE: <u>770</u> ohms	CHG/HOLE: <u>110</u>	HOLE DEPTH: <u>105</u>	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>2.70</u>	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>1700%</u>	DIRECTION OF PROGRESSION: <u>North</u>		LEADING GROUP: <u>96</u>		

DIAGRAMS/MISC. INFORMATION: TRAVEL time = 2  
Recording time = 11

SHOTPOINT	TR. 10		TR. 10		SHOT								SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	STP	Y1-48	Y2-48		Y3-48		
441	672739	98			110	105	1			1/2	930	1						
442		99			110	105	2			1/2	945							
443		100			110	105	3			1/2	955							
444		101			110	105	4	120	S	1/2	1000							
445		102			110	105	5			1/2	1010							
446	672740	103			110	105	6			1/2	1020							

REMARKS: Safety tests Rec. 88-96  
Long Drive Stonecamp test time Break em 9 min

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky oil</u>	PROSPECT: <u>Pet 4</u>	AREA: <u>NORTH SLOPE ALASKA</u>	LINE NO: <u>122</u>					
	PARTY NO: <u>1186</u>	INST. ENG: <u>CARR 40 Reet</u>		DATE: <u>4 DAY 14 YR 77</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS: <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> 1-TRACK <input type="checkbox"/> 2-TRACK	FORMAT: <u>B</u> SEG: <u>3</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: _____			AUXILIARY DATA: _____			AUXILIARY CHANNEL NOS: _____		
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	H CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> MAG <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>30</u> db	ZIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____	DOWNBREAK UPBREAK: <input type="checkbox"/> ON DISPLAY	R.C.U. NORM/ALT SW: _____	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Inline</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <u>Geo SPACE</u>	PATTERN: <u>Inline</u>	NO. OF ELEMENTS: <u>18</u>	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
SPREAD	CONNECTION: <u>Series</u>	RESISTANCE: <u>770</u> ohms	SHOTPOINT INTERVAL: <u>880'</u>	OFFSET GROUP: _____	FOLD: <u>1200%</u>	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: <u>North</u>	LEADING GROUP: <u>96</u>	



DIAGRAMS/MISC. INFORMATION:

Travel time = 2.  
Recording time = 11.

SHOTPOINT	TR. 10		TR. 10		SHOT				SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	HT.	REC.	HT.
446	1172	340	1109	10	110	105	6	11	11	25	10 20				
447		1109			110	105	7	11	11	29	10 30				
448		1109			110	105	8	11	11	33	10 45				
449		1107			110	105	9	11	11	37	11:00				
450		1108			110	105	10	11	11	3	12 00	2			
451		1107			110	105	11	11	11	9	12:10				
453		1110			110	105	12	11	11	13	12:20				
453		1111			110	105	13	11	11	17	12:30				
454		1112			110	105	14	11	11	21	12:35				
455		1113			110	105	15	11	11	25	12:45				
456		1114			110	105	16	11	11	29	12:55				
457		1115			110	105	17	11	11	3	3:25	3			
458		1116			110	105	18	11	11	7	3:30				
458		1117			110	105	19	11	11	11	3:35				
460		1118			110	105	20	11	11	15	3:45				
461		1119			110	105	21	11	11	19	3:55				
462		1120			110	105	22	11	11	23	4:00				
463		1121			110	105	23	11	11	27	4:10				
464		1122			110	105	24	11	11	31	4:15				
465		1123			110	105	25	11	11	35	4:25				

98 Partly EPRR R1 fault west last spread of record  
93 Dead  
moving up 89# Dead  
83 Dead  
moved up waiting on large cables  
ROTALONG ?? TOB HARD P.M.  
ROTALONG ??

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Alaska o.c.</u>	PROJECT: <u>Ref 4</u>	AREA: <u>NORWEL SLOPE ALASKA USA</u>	LINE NO: <u>182</u>						
PARTY NO:		INST. ENG.:		DATE: <u>MO 4 DAY 14 YR 77</u>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FORMAT SEG: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(11) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: _____	LO CUT: _____ HZ	HI CUT: _____ HZ	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	E.C.U. NORM/ALT SW.	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> ADC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>30</u> db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONES: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____		DOWNBREAK UPBREAK: <input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REDUCTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:				
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Inline</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	TYPE: <u>Geo SPACE</u>	PATTERN: <u>Inline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
SPREAD	CONNECTION: <u>Series</u>	RESISTANCE: <u>770</u> ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____				
NO. OF GROUPS: <u>96</u>		GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>1200%</u>	DIRECTION OF PROGRESSION: <u>North</u>		LEADING GROUP: <u>96</u>			

DIAGRAMS/MISC. INFORMATION:

Recording Hours = 2  
Travel time = 11. 13.0 TOTAL

SHOTPOINT	TR. No		TR. No		SHOT								DIR.	CDP SWITCH	SPREAD LINE GROUPS	REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET									TR 1-48	TR 49-96	TR 1-48	TR 49-96
466	672	125	17	2223	20	27	29	30	33	35	37			39	430	3				
467		126												43	445	3	96 Dead in water			
468		127												5	600	4				
469		128												5	615					
470		129												13	625					
471		130												17	635					
472		131												23	645		no up hole			
473		132												25	650					
474		133												29	700					
475		134												33	716					
476		135												37	715					
477		136												41	720					
478		137												45	730		last satisfactory 94.9.91 Demand			

# LAND SEISMIC RECORDING LOG

1070

CLIENT: <b>Husky oi</b>	PROSPECT: <b>Ref 4</b>	AREA: <b>North Slope Alaska USA</b>	LINE NO: <b>122</b>
PARTY NO: <b>1186</b>	INST. ENG: <b>Carlson</b>		DATE: <b>MO 4 DAY 15 YR 77</b>

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> B-F5 X <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 2 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(11) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI
-------------------------	--	---	---	---	--	--	----------------------	--	--	---

CONFIGURATION (MAG TAPE)	AUXILIARY DATA:
FIELD TRACE NOS.:	AUXILIARY CHANNEL NOS.:
DATA CHANNEL NOS.:	(ON MAG TAPE)

PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. _____	LO CUT HZ SLOPE _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DE FLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>30</b> db	JRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	DOWNBREAK / UPBREAK: <input type="checkbox"/> ON DISPLAY
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW. _____

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Inline</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG/ HOLE: <b>110</b>	HOLE DEPTH: <b>405</b>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____

RECEIVER	TYPE: <b>Geo space</b>	PATTERN: <b>Inline</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: <b>Series</b>	RESISTANCE: <b>770</b> ohms	STAGGER: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____

SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>1200%</b>	DIRECTION OF PROGRESSION: <b>North</b>	LEADING GROUP: <b>96</b>
--------	--------------------------	-----------------------------	---------------------------------	--------------------	--	--------------------------

DIAGRAMS/MISC. INFORMATION:



Parallel time = 1.0  
 Recording time = 12.5  
 13.5 TOTAL

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT			SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TR 1-48	TR 49-96
479	11727	1150	11727	1150	1140	105	11			1/4	800			
480		1151			1140	105	12			1/5	810			
481		1152			1140	105	13			1/6	815			
482		1153			1140	105	14			1/7	820			
483		1154			1140	105	15			1/8	830			
484		1155			1140	105	16			1/9	845			
485		1156			1140	105	17			1/10	855			
486		1157			1140	105	18			1/11	900			
487		1158			1140	105	19			1/12	915			
488		1159			1140	105	20			1/13	925			
489		1160			1140	105	21			1/14	1100			
490		1161			1140	105	22			1/15	1115			
491		1162			1140	105	23			1/16	1130			
492		1163			1140	105	24			1/17	1135			
493		1164			1140	105	25			1/18	1145			
494		1165			1140	105	26			1/19	1150			
495		1166			1140	105	27			1/20	1200			
496		1167			1140	105	28			1/21	1210			
497		1168			1140	105	29			1/22	1220			
498		1169			1140	105	30			1/23	1230			

REMARKS: Darcy tests 138-147  
 test time break 148  
 149 no good  
 159 no good

98 Dead  
 89 Dead  
 84 Dead  
 80 Dead  
 76 Dead  
 72 Dead  
 68 Dead  
 64 95 94 Dead Chasing Down Bad cable  
 60-91-90 Dead  
 moved up 98 parity errors R1 S1  
 52 Dead  
 Plane on line  
 1-21-44 Dead Jameson spread  
 18 40 Dead

# LAND SEISMIC RECORDING LOG

	CLIENT: Husky o.l	PROSPECT: Pet 4	AREA: North slope Alaska USA	LINE NO: 122					
PARTY NO: 1186		INST. ENG: Larry Oberst		DATE: MO 4 DAY 15 yr 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 2 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input checked="" type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) (2) (3) (4) (5) (6) (7)		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____ DATA CHANNEL NOS. _____ (ON MAG TAPE)			AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 22 ms. _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	H CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> MAGG <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 30 db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	DOWNBREAK UPBREAK: <input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW: _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Inline</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <u>Geo Space</u>	PATTERN: <u>Inline</u>	NO. OF ELEMENTS: 18	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	CONNECTION: <u>Series</u>	RESISTANCE: 770 ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 330'	FOLD: 1200%	DIRECTION OF PROGRESSION: <u>North</u>	LEADING GROUP: 96			

DIAGRAMS/MISC. INFORMATION: Travel time = 1.0  
Recording time = 12.5  
13.5 total

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT				SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SP	TR 1-48	TR 49-96	TR 1-48
499	6172743	1771			110	105	21			1/45	1245	2	JEP test record on #170			
500		1772			110	105	22			1/49	1255		moved up			
501		1773			110	105	23			1/5	225	3				
502		1774			110	105	24			1/5	230					
503		1775			110	105	25			1/3	245		A2P plane on spread			
504		1776			110	105	26			1/7	300		waiting on plane to Buzz off!			
505		1777			110	105	27			1/21	310					
506		1778			110	105	28			1/25	320					
507		1779			110	105	29			1/29	330					
508		1780			110	105	30			1/23	340					
509		1781			110	105	31			1/37	350					
510		1782			110	105	32			1/40	400					
511		1783			110	105	33			1/45	410					
512		1784			110	105	34			1/49	420		moved up			
513		1785			110	105	35			1/5	530	4				
514		1786			110	105	36			1/9	530					
515		1787			110	105	37			1/3	540					
516		1788			110	105	38			1/3	545					
517		1789			110	105	39			1/21	555		Changing tape			



# LAND SEISMIC RECORDING LOG

DUT

	CLIENT: <u>Auskyoic</u>	PROSPECT: <u>Dist 4</u>	AREA: <u>North Slope Alaska</u>	LINE NO: <u>127</u>						
	PARTY NO: <u>1186</u>	INST. BNG: <u>Carlynsort</u>		DATE: <u>MO 4 DAY 15 YR 77</u>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: <u>B</u> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 355 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: _____			AUXILIARY CHANNEL NOS.: _____			
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 0.3 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	LO CUT HZ SLOPE: _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>30</u> db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R. C. U. NORM / ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Twelve</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	CONNECTION: <u>Geo space series</u>	RESISTANCE: <u>770</u> ohms	CHG/ MOLE: <u>110</u>	HOLE DEPTH: <u>105</u>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>880</u>	OFFSET GROUP: _____	FOLD: <u>1200%</u>	DIRECTION OF PROGRESSION: <u>North</u>	LEADING GROUP: <u>96</u>			



DIAGRAMS/MISC. INFORMATION:

TRAFFIC time = 11.0  
Recording time = 12.5  
13.5 Total

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT								DIR.	CDP SWITCH	SPREAD LINE GROUPS	REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	1	2	3	4					5	6	7	8
518	672794	181			110	105	40							1/25	580	41				
519		182			110	105	41							1/29	615					
520		183			110	105	42							1/32	630					
521		184			110	105	43							1/37	645					93 Dead
522		185			110	105	44							1/41	700					93-89 Dead
523		186			110	105	45							1/45	710					89-85 Dead
524		187			110	105	46							1/49	720					last shot today

# LAND SEISMIC RECORDING LOG

10\*



	CLIENT: <u>Husky oil</u>	PROSPECT: <u>Det 4</u>	AREA: <u>North slope Alaska</u>	LINE NO: <u>127</u>					
PARTY NO: <u>1186</u>		INST. ENG: <u>W. R. Lambert</u>		DATE: <u>4 DAY 16 yr 77</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____ DATA CHANNEL NOS. _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS. _____					
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>30</u> db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	<input type="checkbox"/> ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>LINE</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <u>Geo Space</u>	PATTERN: <u>LINE</u>	RESISTANCE: <u>770</u> ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: <u>26</u>	GROUP INTERVAL: <u>970'</u>	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>1200%</u>	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: <u>NORTH</u>	LEADING GROUP: <u>96</u>		

DIAGRAMS/MISC. INFORMATION:

*Frank Home -  
Revised times -  
Daisy tests 199-207  
test time break rec in 208*

SHOTPOINT	TR. 10		TR. 10		SHOT				CDP SWITCH	SPREAD LINE GROUPS	REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET				TR. 10	TR. 48-96	REC.
525	177	209			110	105	1		1/5	800				
526		210			110	105	2		1/9	815				
527		211			110	105	3		1/13	825				
528		212			110	105	4		1/17	830				
529		213			110	105	5		1/21	845				
530		214			110	105	6		1/25	855				
531		215			110	105	7		1/29	930	Fixing logs on line			
532		216			110	105	8	120 south	1/33	945	changed tapes			
533		217			110	105	9		1/37					

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky Oil</b>	PROSPECT: <b>Ref 4</b>	AREA: <b>North slope</b>	LINE NO.: <b>122</b>								
	PARTY NO.: <b>1186</b>	INST. ENG.: <b>Arthurbert</b>		DATE: <b>4 DAY 16 YR 77</b>								
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI			
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:				AUXILIARY DATA:							
	DATA CHANNEL NOS.:				AUXILIARY CHANNEL NOS.:							
PARAMETER	RECORD LENGTH: <b>3</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: LO CUT HZ SLOPE _____ HI CUT HZ SLOPE _____ FREQ. _____								
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>30</b> db	TRIP SENS: _____ db	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: _____		<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I.	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Inline</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
		CHG./HOLE: <b>110</b>	MOLE DEPTH: <b>105</b>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.			
RECEIVER	TYPE: <b>Geo Space</b>	PATTERN: <b>Inline</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
	CONNECTION: <b>Series</b>	RESISTANCE: <b>770</b> ohms										
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>880'</b>	OFFSET INTERVAL:	FOLD: <b>1200%</b>	OFFSET GROUP:	DIRECTION OF PROGRESSION: <b>North</b>		LEADING GROUP: <b>96</b>			

DIAGRAMS/MISC. INFORMATION:

Recording time =  
TRAVEL time =

SHOTPOINT	TR. 10'		TR. 20'		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-20'
533	1722	220			110	105	9	1610	South	37	1080		
534		221			110	105	10	1610	South	41	1045		
535		222			110	105	11			45	1100		
536		223			110	105	12			49	1115		
535		224					13			43	1130		
546		225					14			49	1155		
537		226			110	105	15			5	1100		
538		227			110	105	16			9	1115		
539		228			110	105	17			15	1120		
540		229			119	105	18			17	1135		
541		230			110	105	19			21	1145		
542		231			110	105	20			25	200		
543		232			110	105	21			29	215		
544		233			110	105	22			33	230		
545		234			110	105	23			37	315		
546		235			110	105	24			41	335		
547		236			110	105	25			45	355		

86

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Askyo</u>	PROSPECT: <u>Pet 4</u>	AREA: <u>North Slope Alaska</u>	LINE NO: <u>122</u>					
PARTY NO: <u>1186</u>		INST. ENG: <u>ARR, rest</u>		DATE: <u>4 DAY 16 YR 77</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	LOGS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 350 BPI (H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1000 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) (2) (3) (4) (5) (6) (7)		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____ DATA CHANNEL NOS. _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS. _____					
PARAMETER	RECORD LENGTH: <u>8</u> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input checked="" type="checkbox"/> FINAL	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> GAGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>30</u> db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____	DOWNBREAK <input type="checkbox"/> ON DISPLAY <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>JULINE</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <u>Geo Space</u>	PATTERN: <u>JULINE</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>220</u> ft	SHOTPOINT INTERVAL: <u>880</u> ft	OFFSET GROUP: _____	OFFSET GROUP: _____	FOLD: <u>1200</u> %	DIRECTION OF PROGRESSION: <u>North</u>	LEADING GROUP: <u>96</u>	

DIAGRAMS/MISC. INFORMATION: Recording time = 11.0  
Process time = 1.5  
Total 12.5

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT								SPREAD		REMARKS	CORE STACK			
	REEL NO.	REC.	REEL-NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SET	TR 1-48	TR 49-96		TR 1-48	TR 49-96		
<del>548</del>	672746	238			110	10526				1	525	3	JEP test rec no 237						
549		239			110	10527				5	530								
550		240			110	10528				9	540								
551		241			110	10529				13	550								
552		242			110	10530				17	600								
553		243			110	10531				21	610								
554		244			110	10532				25									

95 Dead last shot of Day

# LAND SEISMIC RECORDING LOG

	CLIENT: <i>Husky 0.2</i>	PROSPECT: <i>Pet 4</i>	AREA: <i>North Slope</i>	LINE NO: <i>122</i>					
	PARTY NO: <i>186</i>	INST. ENG: <i>CARRINGTON</i>		DATE: <i>MO 4 DAY 17 YR 77</i>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: <i>SEG B</i>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____ DATA CHANNEL NOS. _____ (ON MAG TAPE)			AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: <i>8</i> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 4 ms. <input type="checkbox"/> 16 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <i>30</i> db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/>	DOWNBREAK UPBREAK <input type="checkbox"/>	ON DISPLAY <input type="checkbox"/>	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <i>Inclined</i>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <i>Gen Space</i>	PATTERN: <i>Inclined</i>	NO. OF ELEMENTS: <i>18</i>	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	CONNECTION: <i>Series</i>	RESISTANCE: <i>770</i> ohms	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
	NO. OF GROUPS: <i>96</i>	GROUP INTERVAL: <i>220'</i>	SHOTPOINT INTERVAL: <i>380'</i>	FOLD: <i>1200%</i>	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: <i>North</i>	LEADING GROUP: <i>96</i>		

DIAGRAMS/MISC. INFORMATION:

*TRAVEL time =*  
*Recording time =*

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT			SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	SET UP	TR 1-10	TR 11-20
<i>555</i>	<i>6172</i>	<i>7446</i>	<i>258</i>		<i>110</i>	<i>105</i>	<i>11</i>			<i>1/5</i>	<i>10-30</i>	<i>1</i>			
<i>556</i>		<i>7519</i>			<i>110</i>	<i>105</i>	<i>12</i>			<i>1/7</i>	<i>10-45</i>				
<i>557</i>		<i>760</i>			<i>110</i>	<i>105</i>	<i>13</i>			<i>1/13</i>	<i>10-55</i>				
<i>558</i>		<i>761</i>			<i>110</i>	<i>105</i>	<i>14</i>			<i>1/17</i>	<i>11-00</i>				
<i>559</i>		<i>762</i>			<i>110</i>	<i>105</i>	<i>15</i>			<i>1/21</i>	<i>11-15</i>				
<i>560</i>		<i>763</i>			<i>110</i>	<i>105</i>	<i>16</i>			<i>1/25</i>	<i>11-25</i>				
<i>561</i>		<i>764</i>			<i>110</i>	<i>105</i>	<i>17</i>			<i>1/31</i>					

*Remarks: Daily tests Rec no 246-254*  
*test time break 257* *(256 258 245 no good)*  
*Waiting on drill and Perlander*  
*41 Dead*  
*37 Dead*  
*34 Dead moved up changed hole*  
*33*

*93 party RRS*

# LAND SEISMIC RECORDING LOG

104



	CLIENT: <b>Husky o/c</b>	PROSPECT: <b>Det 4</b>	AREA: <b>north slope</b>	LINE NO: <b>122</b>										
	PARTY NO: <b>1186</b>	INST. ENG: <b>CARRINGTON</b>		DATE: <b>NO 4 DAY 17 YR 77</b>										
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI					
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1)	(2)	(3)	(4)	(5)	(6)	(7)	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:							
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL	MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. _____	LO CUT HZ SLOPE _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE				NUMBERS ON ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> PAGE <input type="checkbox"/> DEFLAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>30</b> db	TRIP SENS: _____ db	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.						
CFS I	TYPE STACK:	GATE LENGTH:												
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Trine</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:					
RECEIVER	TYPE: <b>Geo Space</b>	PATTERN: <b>Trine</b>	NO. OF ELEMENTS: <b>18</b>	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:							
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>1200%</b>	OFFSET GROUP 48/96:	DIRECTION OF PROGRESSION: <b>North</b>		LEADING GROUP: <b>96</b>						

DIAGRAMS/MISC. INFORMATION:

TRACE TIME = 1.5  
RECORDING TIME = 12.0  
TOTAL 13.5

SHOTPOINT	TR. to		TR. to		SHOT			DIR.	CDP SWITCH	SPREAD LINE GROUPS	SET	REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.						OFFSET	TR 1-48	TR 49-96	REC.
561	6727	47	265	17	110	105	17		1/5	115	2	IFP Rec 264				
562		266			110	105	18		1/9	125		25 Dead Running with one DATA				
563		267			110	105	19		1/13	150		21 Dead				
564		268			110	105	20		1/15	135		17 Dead				
565		269			110	105	21		1/21	235		24(17) Dead checking for bad group				
566		270			110	105	22		1/22	415		90 waiting on DATA				
567		271			110	105	23		1/29	430		5 Dead				
568		272			110	105	24		1/33	530		1 Dead				
569		273			110	105	25		1/39	550		waiting on DATA				
570		274			110	105	26		1/41	600						
571		275			110	105	27		1/45	610						
572		276			110	105	28		1/49	615		LAST of DAY!				

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky oil</b>	PROSPECT: <b>Dex 4</b>	AREA: <b>North Slope Alaska</b>	LINE NO: <b>172</b>						
PARTY NO: <b>1186</b>		INST. ENG: <b>Allen Belt</b>		DATE: <b>4 DAY 18 YR 77</b>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS	TYPE: <input type="checkbox"/> DFS III	<input checked="" type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI	(HI) <input type="checkbox"/> 712 BPI
	<input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 48 & 49-96	<input type="checkbox"/> EVENS	<input type="checkbox"/> DFS IV	<input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 21 TRACK	SEG: <b>B</b>	<input type="checkbox"/> UNGAPPED	<input type="checkbox"/> 800 BPI	<input checked="" type="checkbox"/> 1600 BPI
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: _____			RECORD NUMBERS: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____			
PARAMETER	RECORD LENGTH: <b>8</b> sec	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: _____		LO CUT HZ SLOPE: _____		HI CUT HZ SLOPE: _____		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> GGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>30</b> db	TRIP SENS: _____ db	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON ON MAG. TAPE: _____		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____		NOISE THRESHOLD: _____		CORR. SCALING: _____		R.C.U. NORM/ALT SW: _____
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Inline</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	CONNECTION: <b>Gen Space Solder</b>	RESISTANCE: <b>770</b> ohms	CHG/HOLE: <b>110</b>	HOLE DEPTH: <b>105</b>	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>1200%</b>	OFFSET GROUP 48/96: _____		DIRECTION OF PROGRESSION: <b>north</b>		LEADING GROUP: <b>96</b>	

DIAGRAMS/MISC. INFORMATION:

TRAVEL TIME =  
RECORDING TIME =

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT								SPREAD		REMARKS: <b>DAILY tests 276-286</b>	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SET UP	HT.	REC.		HT.	REC.		
<del>573</del>	<del>672</del>	<del>747</del>	<del>288</del>		<del>110</del>	<del>105</del>	<del>11</del>			<del>1/2</del>	<del>800</del>	<del>1</del>							
<del>574</del>			<del>289</del>		<del>110</del>	<del>105</del>	<del>12</del>			<del>1/2</del>	<del>815</del>								
<del>575</del>			<del>290</del>		<del>110</del>	<del>105</del>	<del>13</del>			<del>1/2</del>	<del>920</del>								
<del>576</del>			<del>292</del>		<del>110</del>	<del>105</del>	<del>14</del>			<del>1/2</del>									

wasting on debris changed notes

LAND SEISMIC RECORDING LOG

LK

CLIENT: <i>Cusky on</i>		PROSPECT: <i>Pet 4</i>		AREA: <i>Norsk Slope</i>		LINE NO: <i>122</i>	
PARTY NO: <i>1186</i>		INST. ENGR: <i>W. R. Burnett</i>		DATE: <i>4 DAY 10 77</i>		NO: <i>4</i> DAY <i>10</i> YR <i>77</i>	
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 49-96	<input type="checkbox"/> ODDS <input checked="" type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <i>B</i>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	PACKING DENSITY: (L) <input type="checkbox"/> 386 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			DATA CHANNEL NOS.: _____			AUXILIARY DATA:
PARAMETER	RECORD LENGTH: <i>30</i> sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	HI CUT HZ SLOPE: _____
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input checked="" type="checkbox"/> AGC	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT	INITIAL GAIN: <i>30</i> db	JRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR SCALING: _____	R.C.U. NORM./ALT SW. _____
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <i>In Line</i>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____
RECEIVER	TYPE: <i>Geo Space</i>	PATTERN: <i>In Line</i>	NO. OF ELEMENTS: <i>18</i>	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____
SPREAD	CONNECTION: <i>Series</i>	RESISTANCE: <i>770</i> ohms	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____
SPREAD	NO. OF GROUPS: <i>96</i>	GROUP INTERVAL: <i>220'</i>	SHOTPOINT INTERVAL: <i>880'</i>	FOLD: <i>1200%</i>	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: <i>North</i>	LEADING GROUP: <i>96</i>

DIAGRAMS/MISC. INFORMATION: *Vertical Time = 10*  
*Recording Time 10* Total *11.0*

SHOTPOINT	TR 10		TR 10		SHOT		DIR.	CDP SWITCH	SPREAD	LINE GROUPS	REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH						NO.	OFFSET	TR 1-20	TR 21-40
576	1722748	292			110	105	11		17	935					
577		293			110	105	15		21	945	<i>was long on drills</i>				
578		294			110	105	16		25	1000					
579		295			110	105	17		29	1020					
580		296			110	105	18		33	1030	<i>94 Dead</i>				
581		<del>297</del>			<del>110</del>	<del>105</del>	<del>19</del>		<del>37</del>		<i>skipped moved up waiting on produced</i>				
582		297			110	105	10		31	130	<i>12 Dead</i>				
583		298			110	105	11		35	140					
584		299			110	105	12		39	220					
585		300			110	105	13		43	230					
586		301			110	105	14		47	245	<i>70-96 Dead!</i>				
587		302			110	105	15		51	325	<i>95 Dead</i>				
588		303			110	105	16		55	335	<i>91</i>				
589		304			110	105	17		59	345	<i>87 Dead</i>				
590		305			110	105	18		63	400	<i>83 Dead</i>				
591		306			110	105	19		67	415	<i>82-79 Dead</i>				
592		307			110	105	20		71	430	<i>77-74 Dead</i>				
593		308			110	105	21		75	445	<i>71-83 94 Dead</i>				



# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Kusky oil</u>	PROSPECT: <u>Pet 4</u>	AREA: <u>NORTH SLOPE</u>	LINE NO.: <u>122</u>					
PARTY NO.: <u>1186</u>		INST. ENG.: <u>CARRY</u>		DATE: <u>4</u> DAY <u>19</u> YR. <u>87</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	POP MAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 350 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: _____					
PARAMETER	DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: _____					
DISPLAY	RECORD LENGTH: <u>8</u> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
CFS I	MODE: <input checked="" type="checkbox"/> PAGE <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>30</u> db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE _____	DOWNBREAK <input type="checkbox"/> ON DISPLAY <input type="checkbox"/> UPBREAK	R.C.U. NORM./ALT SW. _____	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Twelve</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <u>Geo space</u>	PATTERN: <u>Twelve</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	CONNECTION: <u>Series</u>	RESISTANCE: <u>770</u> ohms	STAGGER: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>200'</u>	SHOTPOINT INTERVAL: <u>880'</u>	OFFSET GROUP _____	OFFSET GROUP _____	FOLD: <u>1200%</u>	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: <u>NORTH</u>	LEADING GROUP: <u>96</u>

DIAGRAMS/MISC. INFORMATION: TRAFFIC time = \_\_\_\_\_

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT			SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		COP SWITCH	LINE GROUPS	SET UP	TR 1-48
594	672749	3119			110	105	11			1/5	800	1		
595		320			110	105	12			1/7	835			
596		321			110	105	13			1/13	920			
597		322			110	105	14			1/17	940			
598		323			110	105	15			1/21	1000			
599		324			110	105	16			1/25	1010			
600		325			110	105	17			1/29	1030			
601		326			110	105	18			1/33	1040			
602		327			110	105	19			1/37	1050			
603		328			110	105	20			1/41	1100			
604		329			110	105	21			1/45	1115			
605		330			110	105	22			1/49	1120			
606		331			110	105	23			1/5	115	2		
607		332			110	105	24			1/9	130			
608		333			110	105	25			1/13	145			
609		334			110	105	26			1/17	150			
610		335			110	105	27			1/21	200			
611		336			110	105	28			1/25	230			
612		337			110	105	29			1/29	240			
613	672749	338			110	105	30			1/33	250			

RECORDING TIME: \_\_\_\_\_

REMARKS: Early tests Rec no. 309-317  
test time blank no. 318

Shooter moving around block  
waiting on camp to move off spread

1-4 Dead

1-2 Dead

changed tape

# LAND SEISMIC RECORDING LOG

CLIENT: <b>Husky oil</b>		PROSPECT: <b>Pet 4</b>			AREA: <b>NORTH SLOPE ALASKA USA</b>			LINE NO: <b>122</b>	
PARTY NO: <b>1186</b>		INST. ENG: <b>ARRY ROBERT</b>			DATE: <b>MO 4 DAY 19 YR 77</b>				
INSTRUMENT (9-TRACK)		NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS:	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.:			DATA CHANNEL NOS.:			AUXILIARY DATA:	
PARAMETER		RECORD LENGTH: <b>8</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. _____	
DISPLAY		MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>30</b> db		TRIP SENS: _____ db		POLARITY CONVENTION: _____	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>Inline</b>		NO. OF POSITIONS:		INLINE SPACING:	
RECEIVER		TYPE: <b>Gen Space</b>		PATTERN: <b>Inline</b>		NO. OF ELEMENTS: <b>18</b>		INLINE SPACING:	
SPREAD		NO. OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>1200' 820'</b>		FOLD: <b>1200' 26</b>	

DIAGRAMS/MISC. INFORMATION: Recording time =  
Travel time =

SHOTPOINT	TR. to		TR. to		SHOT				SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH		LINE GROUPS	TR 1-48
6114	170752	340			110	105	21			1/37	310		
6115		341			110	105	22			1/41	2:15		
6116		342			110	105	23			1/45	6:45	3	
6117		343			110	105	24	110	EAST	1/47	7:00		57 Dead
6118		344			110	105	25			1/49	7:15		53 Dead
6119		345			110	105	26	80	WEST	1/51	7:30		49 95 91 Dead
6120		346			110	105	27			1/53	7:40		45 91 Dead
6121		347			110	105	28			1/55	7:45		92-96 Dead Series unplugged cables
6122		348			110	105	29			1/57	8:00		37 Dead
6123		349			110	105	30			1/59	8:10		33 Dead
6124		350			110	105	31			1/61	8:15		29 Dead
6125		351			110	105	32			1/63	8:25		25 Dead
6126		352			110	105	33			1/65	8:35		21 Dead
6127		353			110	105	34			1/67	8:45		17 Dead last shot of day

# LAND SEISMIC RECORDING LOG

104C

	CLIENT: <b>Husky Oil</b>	PROJECT: <b>Pet 4</b>	AREA: <b>North Slope Alaska USA</b>	LINE NO: <b>192</b>	
	PARTY NO: <b>1186</b>	INST. ENG: <b>APPY, Bert</b>		DATE: <b>4/20/77</b>	

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	POP. MAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input checked="" type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:		NO. BYTES IN RECORD ID:		RECORD NUMBERS:		GAIN CONSTANT:		INPUT IMPEDANCE:	
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> IFF		FILTERS: FREQ. _____		LO CUT HZ SLOPE _____		HI CUT HZ SLOPE _____	
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFOAT	INITIAL GAIN: <b>30</b> db	JTRIP SENS: _____ db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Triline</b>	NO. OF POSITIONS: _____		INLINE SPACING: _____		LATERAL SPACING: _____		STAGGER: _____	
RECEIVER	TYPE: <b>Geo space</b> CONNECTION: <b>series</b>	PATTERN: <b>Triline</b>	RESISTANCE: <b>770</b> ohms		STAGGER: _____		LENGTH: _____		LATERAL SPACING: _____	
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>880 to 1760'</b>		FOLD: <b>1200% to 600%</b>		DIRECTION OF PROGRESSION: <b>North</b>		LEADING GROUP: <b>96</b>	

DIAGRAMS/MISC. INFORMATION: went back into 600% on SP630. Recording time = 20 13.0  
 627 628 (629) 630 631 TRAVEL time = 13 2.0  
 1-880-1-1760-1-1760-1

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT			DIR.	CDP SWITCH	SPREAD	LINE GROUPS	REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.						OFFSET	TR 1-48	TR 49-96	TR 1-48
627	172750	366	1200%	110	105	1			1	800	73419	Dead				
629	172751	367	1200%	110	105	2			1	805		into 600% or 225 Dead				
630		368	800%	110	105	3			1	820		6 1/2 - 83 Dead				
631		369	600%	110	105	4			1	900		Reprogramming line				
632		370	600%	110	105	5			1	910		49 Dead				
633		371		110	105	6			1	930		moved up				
634		372		110	105	7			1	1200	2					
635		373		110	105	8			1	1215						
636		374		110	105	9			1	1230		Shooting line down!				
637		375		110	105	10			1	1250						
638		376		110	105	11	110	noth	1	100		moved up				
639		377		110	105	12	110	sack	1	295	3	CDP off				
640		378		110	105	13	330	noth	1	300		CDP off				
641		379		110	105	14			1	400		CDP off				
642		380		110	105	15			1	410						
643		381		110	105	16			1	420		moved up				
644		382		110	105	17			1		4	Chirgeal tapes				

## LAND SEISMIC RECORDING LOG

		CLIENT: <b>Husk</b>		PROJECT: <b>Set 4</b>		AREA: <b>North Slope Alaska</b>		LINE NO.: <b>122</b>			
PARTY NO.: <b>1186</b>		INST. ENG.: <b>C. R. ...</b>						DATE: <b>MO 4 DAY 20 YR 77</b>			
INSTRUMENT [9-TRACK] <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		<input type="checkbox"/> 0 TRACK <input type="checkbox"/> 21 TRACK		FOPMAT: SEG <b>B</b> <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
NO. BYTES IN HEADER REC.:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT		GAIN CONSTANT: _____ db		INPUT IMPEDANCE: _____ ohms	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.:		DATA CHANNEL NOS. (ON MAG TAPE)		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:			
PARAMETER		RECORD LENGTH: <b>8</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: _____ FREQ. _____		LO CUT HZ SLOPE _____ HI CUT HZ SLOPE _____	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>30</b> db		TRIP SENS.: _____ db		POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>Fulline</b>		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:	
		CHG./HOLE: <b>110</b>		HOLE DEPTH: <b>105</b>		SWEEP POSITION:		SWEEP START:		SWEEP END:	
RECEIVER		TYPE: <b>GeoSpace Series</b>		PATTERN: <b>Fulline</b>		NO. OF ELEMENTS:		INLINE SPACING:		LATERAL SPACING:	
		CONNECTION:		RESISTANCE: <b>770</b> ohms		STAGGER:		LENGTH:		WIDTH:	
SPREAD		NO. OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>1760'</b>		FOLD: <b>600%</b>		DIRECTION OF PROGRESSION: <b>North</b>	
		OFFSET GROUP 1:		OFFSET GROUP:		OFFSET GROUP:		OFFSET GROUP 48/96:		LEADING GROUP: <b>96</b>	

DIAGRAMS/MISC. INFORMATION: **1**



TRAVEL TIME = 20S  
Recording time = 13

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT		SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	SET	TR 1-48
644	672752	283			110	105	16				630	4		
645		284			110	105	17				640			
646		285			110	105	18				700			
647		286			110	105	19				735			
648		287			110	105	20				800			

Wait shot of Day

# LAND SEISMIC RECORDING LOG

1072



	CLIENT: <b>Husky oil</b>	PROSPECT: <b>Pet 4</b>	AREA: <b>North Slope Alaska USA</b>	LINE NO: <b>122</b>									
PARTY NO: <b>1186</b>		INST. ENG: <b>Alfred Albert</b>		DATE: <b>MO 4 DAY 21 YR 77</b>									
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input checked="" type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>SEG B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	
	NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: _____		(1) _____ (2) _____ (3) _____ (4) _____		(5) _____ (6) _____ (7) _____				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____				AUXILIARY DATA: _____				AUXILIARY CHANNEL NOS.: _____				
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL	FILTERS: _____		LO CUT HZ SLOPE: _____	FREQ. _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
DISPLAY	MODE: <input checked="" type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> GAG <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>30</b> db	TRIP SENS: _____ db	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE: _____		DOWNBREAK UPBREAK: <input type="checkbox"/> ON DISPLAY				
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____		NOISE THRESHOLD: _____	CORR. SCALING: _____		R.C.U. NORM./ALT SW: _____				
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Indone</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____				
RECEIVER	CONNECTION: <b>Geo Space Series</b>	RESISTANCE: <b>770</b> ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____							
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>1760'</b>	FOLD: <b>600%</b>	DIRECTION OF PROGRESSION: <b>North</b>		LEADING GROUP: <b>96</b>						

DIAGRAMS/MISC. INFORMATION: Travel time = 2  
Recording time = 13

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT			SPREAD		REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TR 49	TR 50	TR 51	TR 52
649	377	398	17	2223	26	29	30	32	35	37	1	915				
650		400			110	103	2				1	930				
651		401			110	103	3				1	945				
652		402			110	103	4	500	500	500	1	1000				
653		403			110	103	5				1	1015				
654		404			110	103	6				1	1030				
655		405			110	103	7				1	1:15	2			
656		406			110	103	8				1	1:35				
657		407			110	103	9				1	1:45				
658		408			110	103	10				1	200				
659		409			110	103	11				1	2:10				

writing analogies to layout w-c  
93-96 dead mudup  
94 Dead  
18 parity errors R-L R3 Result layout



# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky oil</u>	PROSPECT: <u>Det 4</u>	AREA: <u>West Slope</u>	LINE NO: <u>122</u>					
	PARTY NO: <u>1181</u>	INST. ENG: <u>WFF Subject</u>		DATE: <u>MO 4 DAY 26 YR 77</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	POP MAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI 800 BPI (HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 3600 BPI	
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: _____			AUXILIARY CHANNEL NOS.: _____		
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>30</u> db	JRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	P.C.U. NORM./ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Surf</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	CONNECTION: <u>Series</u>	RESISTANCE: <u>270</u> ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>1760'</u>	FOLD: <u>600'</u>	DIRECTION OF PROGRESSION: <u>West</u>	LEADING GROUP: <u>96</u>			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. to		TR. to		SHOT				DIR.	CDP SWITCH	SPREAD		REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET			LINE GROUPS	SET		TR 21-28	TR 29-36	TR 37-44	TR 45-52
660	6727	53	411		110	105	12			5	430	3	FFP trace no 410				
661			412		110	105	13			11	445		1 Dead				
662			413		110	105	14			19	500						
663			414		110	105	15			27	515						
664			415		110	105	16			33	625						
665			416		110	105	17			43	635		moved up				
666			417		110	105	18			3	730	4	1-3 Dead				
667			418		110	105	19			11	745						
668			419		110	105	20			19	755						
669			420		110	105	21			27	810						
670			421		110	105	22			35	820		no up hole				
671			422		110	105	23			43	830		" last shot of day				

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky Oil</b>	PROSPECT: <b>Def 4</b>	AREA: <b>north slope</b>	LINE NO.: <b>122</b>	
PARTY NO.: <b>186</b>		INST. ENG.: <b>CARRYBERT</b>		DATE: <b>MO 4 DAY 22 YR 77</b>	

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-40 <input checked="" type="checkbox"/> 48 & 49-96 <input type="checkbox"/> ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	TRACKS: <input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACKS	FOP.MAT: <b>B</b> SEG	GAPPED: <input type="checkbox"/> UNGAPPED: <input type="checkbox"/>	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HT) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI			
NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.			
FIELD TRACE NOS.: _____			AUXILIARY DATA:						
DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: _____						
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input checked="" type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____ HZ	HI CUT _____ HZ	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>30</b> db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Incline</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <b>Geospace</b>	PATTERN: <b>Incline</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>270</b>	SHOTPOINT INTERVAL: <b>1760'</b>	FOLD: <b>600</b>	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: <b>north</b>	LEADING GROUP: <b>96</b>		

DIAGRAMS/MISC. INFORMATION:

*Traffic time = 2*  
*Recording time = 12*

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT		SPREAD		REMARKS	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH	LINE GROUPS	HT.	HT.	HT.	HT.
672	672	433			110	105	1			3	825					
673		434			110	105	2			4	830					
674		435			110	105	3			13	845					
675		436			110	105	4			27	915					
676		437			110	105	5			35	930					

*changing tape*

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky oil</u>	PROSPECT: <u>Det 4</u>	AREA: <u>North Slope Alaska</u>	LINE NO: <u>122</u>	
	PARTY NO: <u>1136</u>	INST. ENG: <u>Carlybert</u>		DATE: <u>MO 4 DAY 23 77</u>	

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
(9-TRACK)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____			AUXILIARY DATA: _____			AUXILIARY CHANNEL NOS. _____		
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>30</u> db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Inline</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <u>Geospace</u>	PATTERN: <u>Inline</u>	NO. OF ELEMENTS: <u>18</u>	STAGGER: _____	LENGTH: _____	SWEEP LENGTH: _____	SWEEP TAPE: _____	PHASE COMP: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>220</u>	SHOTPOINT INTERVAL: <u>1760'</u>	FOLD: <u>600</u>	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: <u>West</u>		LEADING GROUP: <u>96</u>	



DIAGRAMS/MISC. INFORMATION: TRAJIC time = 2  
Recording time = 12

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT			SPREAD		REMARKS	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-48	TR 49-96	TR 1-48	TR 49-96
678	673759	439			110	105	6		43	945	1				
678		440			110	105	7		3	1200	2				
679		441			110	105	8		19	1210					
680		442			110	105	9		19	1225					
681		443			110	105	10		121	1230					
682		444			110	105	11		35	1240					
683		445			110	105	12		43	1250					
684		446			110	105	13		13	315	3				
685		447			110	105	14		11	330					
686		448			110	105	15		19	335					
687		449			110	105	16		27	400					
688		450			110	105	17		25	415					
689		451			110	105	18		1	600	4				
690		452			110	105	19		19	615					
691		453			110	105	20		17	635					
692		454			110	105	21		25	710					
693		455			110	105	22		33	720					
694		456			110	105	23		41	730					

LAST SHOT OF DAY!



# LAND SEISMIC RECORDING LOG

	CLIENT: <b>HUSKY</b>	PROSPECT: <b>PET. 4</b>	AREA: <b>REC. 2</b>	LINE NO: <b>122</b>								
	PARTY NO: <b>1186</b>	INST. ENG: <b>F. Carlsenius</b>		DATE: <b>4 DAY 23 YR 77</b>								
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI			
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: <b>5000</b> ohms.	(1)	(2)	(3)	(4)	(5)	(6)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 20 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>8</b> LO CUT HZ SLOPE <b>18</b>	FREQ. <b>128</b> HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT					
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>18</b> db	JRIP SENS: <b>73</b> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY					
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	F.C.U. NORM./ALT SW					
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>1</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
	CHG./HOLE: <b>110</b>	HOLE DEPTH: <b>105</b>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.				
RECEIVER	TYPE: <b>Geo-Space 10D</b>	PATTERN:	NO. OF ELEMENTS: <b>18/trace</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
	CONNECTION: <b>Series</b>	RESISTANCE:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:						
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL:	FOLD: <b>600%</b>	DIRECTION OF PROGRESSION: <b>NORTH</b>							
	OFFSET GROUP 1:	OFFSET GROUP:	OFFSET GROUP:	OFFSET GROUP 48/96:	LEADING GROUP: <b>96</b>							

DIAGRAMS/MISC. INFORMATION: **Tape # 672654 - Daily Tests File # 457-464 Test T.B. # 465 ON Tape # 672655**  
**Travel = 2 hours Total = 14.5**

SHOTPOINT	TR. to		TR. to		SHOT				SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH		LINE GROUPS	TR 41-48	TR 41-48	TR 41-48	TR 41-48
695	672655	466			110	95	1			1/1	1					
696		467					2			1/9						
697		468					3			1/17						
698		469					4			1/25						
699		470					5			1/33						
700		471					6			1/5	2					
701		472					7			1/13						
702		473					8			1/21						
703		474					9			1/29						
704		475					10			1/37						
705		476					11			1/45						
706		477					12			1/5	3					
707		478					13			1/13						
708		479					14			1/21						
709		480					15			1/29 (1/30)						
710		481					16			1/37						
711		482					17			1/3	4					
712		483					18			1/11						
713		484					19			1/19						
714	672655	485			110	95	20			1/27						

NOTE: No. 5 Pod switch on FM card.



# LAND SEISMIC RECORDING LOG

	CLIENT: <b>HUSKY</b>	PROSPECT: <b>PET. 4</b>	AREA: <b>REC. 2</b>	LINE NO.: <b>122</b>									
	PARTY NO.: <b>1186</b>	INST. ENG.: <b>F. Carlsenius</b>		DATE: <b>MO 4 DAY 24 YR 77</b>									
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1000 BPI			
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36 db</b>	INPUT IMPEDANCE: <b>5000 ohms</b>	(1)	(2)	(3)	(4)	(5)	(6)	(7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			DATA CHANNEL NOS.:			(ON MAG TAPE)						
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> IFF	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. <b>8</b>	LO CUT HZ SLOPE <b>18</b>	FREQ. <b>124</b>	H CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT				
DISPLAY	MODE: <input checked="" type="checkbox"/> MAG <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>18 db</b>	TRIP SENS.: <b>3</b> db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEDPHONE:	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	<input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM. ALT SW.						
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>1</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
RECEIVER	TYPE: <b>Geo-Space 10-D</b>	PATTERN:	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
SPREAD	CONNECTION: <b>SERIES</b>	RESISTANCE: ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:							
	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL:	SHOTPOINT INTERVAL: <b>1760'</b>	FOLD: <b>600%</b>	DIRECTION OF PROGRESSION: <b>NORTH</b>	LEADING GROUP: <b>96</b>							
	OFFSET GROUP 1:	OFFSET GROUP:	OFFSET GROUP:	OFFSET GROUP 48/96:									

DIAGRAMS/MISC. INFORMATION: **Tape # 672756 File # 489-498 Daily Tests File # 494 N.G. Tidwell - 3 hrs. Total = 15.5 hrs. File # 499 Test T.B.**

SHOTPOINT	TR 10		TR 10		SHOT				SPREAD		REMARKS	CORE STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-48	TR 49-96	TR 1-48	TR 49-96
717	672756	S00			110	105	1				1/3	13-26-93				
718		S01					2				1/11	5-18-85				
719		S02					3				1/19	10-77				
720		S03					4				1/27	1-2-90-69				
721		S04					5				1/35	61-82				
722		S05					6				1/43	53-74-96				
723		S06					7				1/3	37-45				
724		S07					8				1/11	29-37				
725		S08					9				1/19	21-29				
726		S09					10				1/27	13-21				
727		S10					11				1/35	5-13				
728		S11					12				1/1	5-93				
729		S12					13				1/9	85				
730		S13					14				1/17					
731	672756	S14			110	105	15				1/25					

# LAND SEISMIC RECORDING LOG

Page 2 of 2

	CLIENT: <b>Husky</b>	PROSPECT:	AREA:	LINE NO: <b>122</b>									
	PARTY NO: <b>1186</b>	INST. ENG: <b>E. Carlensius</b>		DATE: <b>4/24/77</b>									
INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI			
(9-TRACK)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1)	(2)	(3)	(4)	(5)	(6)	(7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____				AUXILIARY DATA:								
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: _____								
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIED <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY				
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.						
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
	CHG/HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:					
RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
	CONNECTION:	RESISTANCE:	ohms	STAGGER:	LENGTH:								
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:								
	OFFSET GROUP 1:	OFFSET GROUP _____:	OFFSET GROUP _____:	OFFSET GROUP 48/96:	LEADING GROUP:								

DIAGRAMS/MISC. INFORMATION: Tape # 672757 - File # 515 IEP. OSC (6 seconds)

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT							SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	HT.	TR 48-96		HT.	TR 48-96		
732	672757	516			11	105	16				1/33	3	Open traces					
733		517					17				1/41	4	90					
734		518					18				1/1		82-93					
735		519					19				1/9		74-85					
736		520					20				1/17		66-77					
737		521					21				1/25		58-69					
738		522					22				1/33		50-61					
739	672757	523			110	10523					1/41		42-53					



# LAND SEISMIC RECORDING LOG

Page 2 of 3.

	CLIENT: <b>HUSKY</b>	PROSPECT: <b>N.P.R. 4</b>	AREA: <b>REC. 2</b>	LINE NO: <b>122</b>	
PARTY NO: <b>1186</b>		INST. ENG: <b>F. Carlsenius</b>		DATE: <b>4 DAY 25 YR 77</b>	

INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input checked="" type="checkbox"/> DFS I <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: _____ SEG: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: _____ (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 600 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI	
(9-TRACK)	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: _____					
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT: _____ HZ	HI CUT: _____ HZ	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AOC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	DOWNBREAK UPBREAK: <input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW: _____		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>1</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ MOLE: <b>110</b>	HOSE DEPTH: <b>105</b>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: _____	RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>1760'</b>	FOLD: <b>600%</b>	DIRECTION OF PROGRESSION: <b>North.</b>	OFFSET GROUP 1: _____	OFFSET GROUP _____: _____	LEADING GROUP: <b>96</b>	



DIAGRAMS/MISC. INFORMATION: **Tape # 672758 File # 545 IFF. OSC. (6 seconds)**  
**File # 554 - Test T.B.**

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT				DIR.	COP SWITCH	SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET			LINE GROUPS	ST		TR 1-28	TR 29-36	TR 37-44	TR 45-52
750	672758	546			110	105	11	37		1/33		2	open traces 90-93				
751		547					12			1/41			85				
752		548					13			1/11		3	22-27-40 weak				
753		549					14			1/9			14-19-32				
754		550					15			1/7			6-11-86				
755		551					16			1/25			3-78				
756		552					17			1/33			70				
757		553	use 577				18			1/41			62 TR went into Rev. erased Record.				
758		554					19			1/11		4	-				
759		555					20	660 S		1/9			-				
760	672758	556	use 578		110	105	21			1/7	91 Parities		- Faults R-1 R-3 S-1				
													Ran tests - some parities and R-1 R-3 faults.				
													Changed Tape.				



# LAND SEISMIC RECORDING LOG

Page 1 of 1

	CLIENT: <b>Husky</b>	PROSPECT: <b>N.P.R. 4</b>	AREA: <b>REC 2</b>	LINE NO: <b>122</b>								
PARTY NO: <b>1166</b>		INST. ENG: <b>F. Carlenius</b>		DATE: <b>MO 4 DAY 26 YR 77</b>								
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: <b>5000</b> ohms.					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:				AUXILIARY DATA:							
	DATA CHANNEL NOS.:				AUXILIARY CHANNEL NOS.:							
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> JFP	FILTERS: FREQ. <b>8</b> LO CUT HZ SLOPE <b>18</b>		FREQ. <b>124</b>	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT				
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>318</b> db	TRIP SENS: <b>3</b> db	POLARITY CONVENTION:		PRESSURE INCREASE ON GEOPHONE:		<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM. ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>1</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
		CHG/ HOLE: <b>110</b>	HOLE DEPTH: <b>105</b>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.			
RECEIVER	TYPE: <b>Geo-Space 10-D</b>	PATTERN:	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING:		LATERAL SPACING:		STAGGER:		LATERAL OFFSET:		
	CONNECTION: <b>Series</b>	RESISTANCE: <b>770</b> ohms	STAGGER:	LENGTH:		WIDTH:		LATERAL OFFSET:				
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>1760'</b>	FOLD: <b>600%</b>		DIRECTION OF PROGRESSION: <b>North</b>		LEADING GROUP: <b>96</b>				

DIAGRAMS/MISC. INFORMATION: **Tape 672759 - File #562-574 Daily Tests (complete)**  
**575 Pulse test**  
**576 Test T.O.**  
Hours -  
Travel - 1 hour.

SHOTPOINT	TR. No		TR. to		SHOT								SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SET UP	TR 1-48	TR 49-96			
757R	672759	577	17	22 23	26 27	29 30	32	35	37		117		1	Only 16 grps South. (93-96 open)			
760R		578									117		2	1-8 open			
762		579									133			Full spread			
763	672759	580			110	105					141			48 grp. Tail-spread.			
														Redrilled S.P. #757 & 760			
														*On S.P. 757 cable disconnected in wrong place so 93-96 open.			
														Run complete set of tests after checking all cards in Controller Mod.			
														Tests were all okay			
														Completed shooting			
														LINE #122			
														Picked up all of spread.			