



LAND SEISMIC RECORDING LOG

	CLIENT: <i>HUSKY OK</i>	PROSPECT: <i>N.P.R. 4</i>	AREA:	LINE NO: <i>131</i>							
	PARTY NO: <i>1186</i>	INST. ENG: <i>F. Carlsenius</i>		DATE: <i>MO 1 DAY 22 YR 77</i>							
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <i>B</i>	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 358 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI PE		
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <i>36</i> db	INPUT IMPEDANCE: <i>2000</i> ohms.	(1) (2) (3) (4) (5) (6) (7)			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <i>1-96</i>			AUXILIARY DATA:						AUXILIARY CHANNEL NOS.:	
	DATA CHANNEL NOS.:			[ON MAG TAPE]:							
PARAMETER:	RECORD LENGTH: <i>8</i> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> . . . ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS:	FREQ: <i>OUT</i>	LO CUT HZ: <i>18</i>	FREQ: <i>128</i>	HI CUT HZ: <i>18</i>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEPLOY <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.				
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <i>1 hole</i>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
	<i>Plus Pelletol</i>	CHG/ HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.		
RECEIVER	TYPE: <i>Geo-space 20 D</i>	PATTERN: <i>INLINE</i>	NO. OF ELEMENTS: <i>18</i>	INLINE SPACING: <i>25'</i>	LATERAL SPACING:	STAGGER:	LENGTH: <i>425'</i>	WIDTH:	LATERAL OFFSET:		
	CONNECTION: <i>Series-Parallel</i>	RESISTANCE: <i>10</i> ohms	STAGGER:	LENGTH: <i>425'</i>	WIDTH:	LATERAL OFFSET:					
SPREAD	NO. OF GROUPS: <i>96</i>	GROUP INTERVAL: <i>220'</i>	SHOTPOINT INTERVAL: <i>1760'</i>	FOLD:	OFFSET GROUP 48/96:	DIRECTION OF PROGRESSION: <i>SOUTH</i>	LEADING GROUP:				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to <i>96</i>		TR. _____ to _____		SHOT									SPREAD	REMARKS:	COWL STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	HT.	TR 1-48			HT.	TR 49-96	
1	<i>6172</i>	<i>4716</i>			<i>160</i>	<i>175</i>	<i>11</i>		<i>West</i>	<i>1/1</i>				<i>50" Pelletol + 10" Geo-gel</i>				
2		<i>4719</i>			<i>160</i>	<i>175</i>	<i>12</i>		<i>West</i>	<i>1/9</i>				<i>Fit # 68 N.G.</i>				
3		<i>4710</i>			<i>160</i>	<i>175</i>	<i>13</i>	<i>510</i>	<i>West</i>	<i>1/7</i>				<i>" "</i>				
4		<i>4711</i>			<i>150</i>	<i>175</i>	<i>13</i>	<i>510</i>	<i>West</i>	<i>1/25</i>				<i>50" Geogel + 2 caps.</i>				
5		<i>472</i>			<i>160</i>	<i>175</i>	<i>15</i>			<i>1/33</i>		<i>? check position</i>		<i>No UH. - Bad take-out on cable.</i>				
6		<i>473</i>			<i>160</i>	<i>175</i>	<i>16</i>			<i>1/41</i>				<i>Paper jammed</i>				

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY OIL	PROSPECT: REC.#2	AREA: N.P.R.4	LINE NO.: 131							
	PARTY NO.: 118	INST. ENG.: F. Carlensius		DATE: MO 1 DAY 27 YR 77							
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG.B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: 1600 (LO)	<input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC.: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 2000 ohms.					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA:							
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: _____							
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> IFF	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: B	LO CUT 18	HZ SLOPE	FREQ. 128	HI CUT	HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT <input type="checkbox"/> DIRECT	AMPLIFIER	INITIAL GAIN: 12 db	TRIP SENS.: 0 db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE:	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	R.C.U. NORM/ALT SW.
CFS I	TYPE STACK:	DATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:					
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1 hole	NO. OF POSITIONS:	INLINE SPACING: 1200'	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
		CHG/ HOLE: 60	HOLE DEPTH: 75'	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.		
RECEIVER	TYPE: D-20	PATTERN:	NO. OF ELEMENTS: 18	INLINE SPACING: 220'	LATERAL SPACING:	STAGGER:	LENGTH: 225'	WIDTH:	LATERAL OFFSET:		
	CONNECTION:	RESISTANCE: _____ ohms									
SPREAD	NO. OF GROUPS: 1	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 6	DIRECTION OF PROGRESSION:			LEADING GROUP: 1			
	OFFSET GROUP 1:	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96:							

DIAGRAMS/MISC. INFORMATION: **MDN. DAY YR LINE# PARTY#**
CONSTANTS: 01 27 77 131 186 HEADER. File #'s 090,091, 092,096 N.G. Misfires & Test T.B.'s.

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT							SPREAD		REMARKS:	CORR. STACK							
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SEC		TR 1-48	TR 49-96	TR 1-48	TR 49-96				
1	672676	083			160	75	11				1/1											
2		084			160	75	12				1/9			Appears only about 25' charge fired								
3		085			160	75	13				1/17											
4		086			160	75	14				1/25											
5		087			160	75	15				1/33											
6		088			160	75	16				1/41											
7	672677	089			160	75	17				1/1	2										
8		093			160	75	18				1/9											
9		094			160	75	19				1/17											
10		095			160	75	10				1/25		offset 45' West & 19' North.									
11		097			160	75	10				1/33											

LAND SEISMIC RECORDING LOG

CLIENT: HUSKY OIL	PROSPECT: N.P.R. 4			AREA: REC 2 ALASKA			LINE NO: 131		
PARTY NO: 1186	INST. ENG.: F. CARLSENIS			DATE: MO 1 DAY 28 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE:	<input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input checked="" type="checkbox"/> DFS X <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG SEGB	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: 1600 P/L	<input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI <input checked="" type="checkbox"/> 1600 BPI	(HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT:	<input type="checkbox"/> (1) <input type="checkbox"/> (2) <input type="checkbox"/> (3) <input type="checkbox"/> (4) <input type="checkbox"/> (5) <input type="checkbox"/> (7)	INPUT IMPEDANCE: 2000 ohms.		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input checked="" type="checkbox"/> IPP <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS:	FREQ. 8	LO CUT HZ SLOPE: 18	HI CUT HZ SLOPE:	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> AOC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 db	TRIP SENS.: _____ db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	R.C.U. NORM/ALT SW.	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/HOLE: 60	HOLE DEPTH: 90	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	
RECEIVER	TYPE: D-20	PATTERN:	NO. OF ELEMENTS: 18/trace.	INCLINE SPACING: 225'	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION:	RESISTANCE:	ohms						
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 6	DIRECTION OF PROGRESSION: SOUTH	OFFSET GROUP _____	OFFSET GROUP 48/96:	LEADING GROUP: 1	

DIAGRAMS/MISC. INFORMATION:
MON. DAY YEAR LINE PARTY
Header: 01 28 77 131 1186

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT			SPREAD			REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	HT.	REC.	HT.	REC.
118	47267	1108			60	75	1			1/41		1				
119		1109			60	75	2			1/1		2				
120		1110			60	90	3			1/9						
121		1111			60	90	4			1/17						
122		1112			60	90	5			1/25						
123		1113			60	90	6			1/33						
124		1114			60	90	7			1/41						
125		1115			60	90	8			1/25		3				
126		1116			60	90	9			1/33						
												Daily Tests File No. 098-107				

LAND SEISMIC RECORDING LOG



CLIENT: **MUSKY OIL** PROSPECT: **N.P.R. 4** AREA: **REC. 2 ALASKA** LINE NO: **131**
 PARTY NO: **1186** INST. ENG.: **N.F. CARLSEN IUS** DATE: **1 DAY 29 VR 77**



INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE:	<input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI
(9-TRACK)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 2000 ohms.	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA:				
	DATA CHANNEL NOS.:			AUXILIARY CHANNEL NOS.:				
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18				HIGH CUT HZ SLOPE
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:	CORR. SCALING:	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	
	CHG/HOLE: 60	HOLE DEPTH: 90	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	
RECEIVER	TYPE: D-20	PATTERN:	NO. OF ELEMENTS: 18	INCLINE SPACING:		LATERAL SPACING:		
	CONNECTION: Series-Parallel	RESISTANCE: _____ ohms	STAGGER:	LENGTH:		WIDTH:		
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:		DIRECTION OF PROGRESSION: SOUTH		
	OFFSET GROUP 1:	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96:		LEADING GROUP: 1		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1		TR. 2		SHOT					SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-33	TR 34-44	TR 45-55	TR 56-66
27	672	1132			60	90	1				1/17						
28		1133			60	90	2				1/25						
29		1134			60	90	3				1/33						
30		1135			60	90	4				1/41						
31		1136			60	90	5				1/49						
32		1137			60	90	6				1/3						
33		1138			60	90	7				1/11						
34		1139			60	90	8				1/19						
35		1140			60	90	9				1/27						
36		1141			60	90	10				1/35						
37		1142			60	90	11				1/43						
38		1143			60	90	12				1/3						
39		1144			60	90	13				1/11						
40		1145			60	90	14				1/19						
41		1146			110	90	15				1/27						
42		1147			110	90	16				1/35						
43		1148			110	90	17				1/43						

Daily Tests File #122-130
 Test T.B. " #131
 NOTE: File No's 117 to 121 NG.

LAND SEISMIC RECORDING LOG

	CLIENT: <u>HUSKY OIL</u>	PROSPECT: <u>N.P.R. 4</u>	AREA: <u>REC#2 ALASKA-</u>	LINE NO: <u>131</u>						
PARTY NO: <u>1186</u>	INST. ENG: <u>E. Parkenius</u>		DATE: <u>1 30 77</u>	MO. <u>1</u> DAY <u>30</u> YR <u>77</u>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS <input type="checkbox"/> ODDS <input checked="" type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input checked="" type="checkbox"/> DFS X <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u> SEG.	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	<input type="checkbox"/> (LO) 356 BPI <input type="checkbox"/> 800 BPI	<input type="checkbox"/> (HI) 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____		DATA CHANNEL NOS.: _____ (ON MAG TAPE)		AUXILIARY DATA: _____					AUXILIARY CHANNEL NOS.: _____
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input checked="" type="checkbox"/> 1PP <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT <u>18</u> Hz	HI CUT _____ Hz	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	DOWNBREAK <input type="checkbox"/> UPBREAK <input checked="" type="checkbox"/>	ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____			
SOURCE	<input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
		CHG/ HOLE: <u>60</u>	HOLE DEPTH: <u>110'</u>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: <u>D-20</u>	PATTERN: _____		NO. OF ELEMENTS: _____	INCLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
	CONNECTION: _____	RESISTANCE: _____ ohms		STAGGER: _____					LATERAL OFFSET: _____	
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: <u>1760'</u>	FOLD: _____	DIRECTION OF PROGRESSION: <u>SOUTH</u>					
	OFFSET GROUP 1: _____	OFFSET GROUP _____: _____	OFFSET GROUP _____: _____	OFFSET GROUP 48/96: _____	LEADING GROUP: <u>1</u>					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	SHOT										SPREAD		REMARKS	CORR. STACK			
	TR. _____ TO _____		TR. _____ TO _____		SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	ST		TR. 48		TR. 96	
	REEL NO.	REC.	REEL NO.	REC.										HI	REC.	HI	REC.
444	1672	159			110	90	1			1/3							
445		1610				90	2			1/11							
446		1611				90	3			1/19							
447		1642				90	4			1/27							
448		1643				90	5			1/35							
449		1644				90	6			1/43							
501		1615				90	7			1/3			2				
511		1616				90	8			1/11							
521		1617				90	9			1/19							
531		1618				90	10			1/27							
541		1619				90	11			1/5			3				
551		170				90	12			1/13							
561		171				90	13			1/21							
571						90				1/29							
58		176			110	90	14			1/37							
Both cups open.																	
File # 172, 173, 174, 175 NG.																	
DAILY TEST FILE 149-157																	
TEST T.B-158																	



LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY OIL	PROSPECT: N.P.R. # 4	AREA: REC # 2 ALASKA	LINE NO.: 131					
	PARTY NO.: 1186	INST. ENG.: N.E. Carlsenius		DATE: MO 1 DAY 31 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600-BPI
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID.	NO. BYTES PER SCAN.	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 2000 ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:				DATA CHANNEL NOS.:				(ON MAG TAPE)
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. B LO CUT HZ SLOPE 18		FREQ. 128 HI CUT HZ SLOPE		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER DIRECT	INITIAL GAIN: 12.8 db	TRIP SENS: 0 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE POSITIVE		NUMBERS ON MAG. TAPE <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:		R.C.U. NORM/ALT SW.	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1 hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: 110	HOLE DEPTH: 90'	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: D-20	PATTERN:	NO. OF ELEMENTS: 18	INCLINE SPACING:		LATERAL SPACING:			
	CONNECTION: Series-Parallel	RESISTANCE: ohms	STAGGER:	LENGTH:		WIDTH:		LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: 9	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 6		DIRECTION OF PROGRESSION: SOUTH			
	OFFSET GROUP 1:	OFFSET GROUP:	OFFSET GROUP:	OFFSET GROUP 48/96:		LEADING GROUP: 1			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT			SPREAD			REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	HT.	REC.	HT.	REC.
59	672680	188			110	90	11				1/3					
60		189			110	90	12				1/11					
61		190			110	90	3				1/19					
62		191			110	90	4	25	E		1/27					
63		192			110	90	5				1/35					
64		193			110	90	6				1/43					
65		194			110	90	7				1/3					
66		195			110	90	8				1/11					
67		196			110	90	9				1/19					
68		198			110	90	10				1/27					
69		199			110	90	11				1/35					
70		200			110	90	12				1/43					
71		203			110	90	13				1/3					
72		204			110	90	14				1/11					
73		205			110	90	15				1/19					

LAND SEISMIC RECORDING LOG

	CLIENT: Husky Oil	PROSPECT: N-P.R. 4	AREA: REC 2 ALASKA	LINE NO: 131	
PARTY NO: 1166		INST. ENG: N.F. Carlsenius		DATE: MO 2 DAY 1 YR 77	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI									
NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) _____	(2) _____	(3) _____	(4) _____	(5) _____	(6) _____	(7) _____					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: _____			AUXILIARY CHANNEL NOS.: _____										
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ml. <input type="checkbox"/> 2 ml. _____ mm.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	H1 CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	DOWNBREAK UPBREAK: <input type="checkbox"/> ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW. _____	SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	CONNECTION: _____	PATTERN: _____	RESISTANCE: _____ ohms	STAGGER: _____	INCLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT					SPREAD		REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 1-48	TR 49-96	TR 1-48	TR 49-96	
764	1721	181	219	223	219	110	90	11			1/3	File No. A 214-217 Daily Tests File No. 218 = Test T.B.					
765					220	110	90	2			1/11						
766					221	110	90	3			1/19						
767					222	110	90	4			1/27						
768					223	110	90	5			1/35						
769					224	110	90	6			1/43						
800					225	110	90	7			1/3						
815					226	110	90	8	110 S		1/11						
824					227	110	90	9	300 N		1/19						
833					228	110	90	10			1/27						
844					229	110	90	11			1/35						
855					230	110	90	12			1/43						

LAND SEISMIC RECORDING LOG



	CLIENT: <i>Husky Oil</i>	PROSPECT: <i>NPR 4</i>	AREA: <i>Rec 2 Alaska</i>	LINE NO: <i>131</i>							
	PARTY NO: <i>186</i>	INST. ENG: <i>Harvey Beat</i>		DATE: <i>MO 2 DAY 7 YR 77</i>							
INSTRUMENT [9-TRACK]	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____		DATA CHANNEL NOS.: _____ (ON MAG TAPE)							AUXILIARY DATA: _____	
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	FREQ. _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW.				
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
	CHG/HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____			
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____								
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____								
	OFFSET GROUP 1: _____	OFFSET GROUP: _____	OFFSET GROUP: _____								

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT		SPREAD				REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	SEV	TR 1-24	TR 25-48	TR 49-96
86	672681	243			110	9.0	1				3					
87		243			110	9.0	2				11					
88		2415			110	9.0	15				19					
89	672682	246			110	9.0	4				27					
90		247			110	9.0	3				35					

LAND SEISMIC RECORDING LOG





CLIENT: <i>Asky oic</i>	PROSPECT: <i>APR 4</i>	AREA: <i>Rec-2 ALASKA</i>	LINE NO: <i>131</i>
PARTY NO: <i>186</i>	INST. ENG: <i>LARRY BURD</i>		DATE: <i>MO 2 DAY 8 YR 77</i>

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: _____ (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____				AUXILIARY DATA: _____				
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: _____				
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	FREQ: _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM / ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP. _____	
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	STAGGER: _____	INCLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL SPACING: _____	LATERAL OFFSET: _____
	CONNECTION: _____	RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____			
	OFFSET GROUP 1: _____	OFFSET GROUP _____: _____	OFFSET GROUP _____: _____	OFFSET GROUP 48/96: _____					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD		REMARKS:	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	HT.	TR 1-48	REC.	HT.	TR 49-96	REC.
91	1213	10	22	23	24	27	29	30	32									
92	1268	1368			110	170				1								
93		1269			110	190				1								
94		1270			110	190				1								
95		1271			110	190				1								
95		1272			110	190				1			2	Changed tape because PARTIAL RECORDS TO EXCESS OF 91				

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky o/c</u>	PROSPECT: <u>APR 4</u>	AREA: <u>Rec-2 Alaska</u>	LINE NO: <u>131</u>	
PARTY NO: <u>1186</u>		INST. ENG: <u>CARRY COBERT</u>		DATE: <u>MO 2 DAY 8 YR 77</u>	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	CODES <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI			
NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: _____		RECORD NUMBERS: _____		GAIN CONSTANT: _____ db		INPUT IMPEDANCE: _____ ohms.	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: _____				AUXILIARY DATA:					
		DATA CHANNEL NOS.: _____ (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____		LO CUT HZ SLOPE	FREQ. _____	HI CUT HZ SLOPE	NOYCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____		NOISE THRESHOLD: _____	CORR. SCALING: _____		B.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____		WIDTH: _____		LATERAL OFFSET: _____			
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____		DIRECTION OF PROGRESSION: _____		LEADING GROUP: _____			
OFFSET GROUP 1: _____		OFFSET GROUP: _____	OFFSET GROUP: _____	OFFSET GROUP 48/96: _____							

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT		SPREAD		REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR 1-48	TR 49-96	TR 1-48	TR 49-96
1196	1213	1213	1213	1213	110	190	35	37					
1197	1213	1213	1213	1213	110	190							
1198	1213	1213	1213	1213	110	190							
1199	1213	1213	1213	1213	110	190							
1100	1213	1213	1213	1213	110	190			8				
1101	1213	1213	1213	1213	110	190							
1102	1213	1213	1213	1213	110	190							
1103	1213	1213	1213	1213	110	190							
1104	1213	1213	1213	1213	110	190							
1105	1213	1213	1213	1213	110	190				4	← wrong Board.		
1106	1213	1213	1213	1213	110	190							
1107	1213	1213	1213	1213	110	190							

LAND SEISMIC RECORDING LOG

CLIENT: Husky oic PROSPECT: APR 4 AREA: REC-2 ALASKA LINE NO: 131

PARTY NO: 1186 INST. ENG: LARIVIERE DATE: MO 2 DAY 9 YR 77

INSTRUMENT: 1 SYSTEM 2 SYSTEMS 1-24 & 25-48 1-48 & 49-96 ODDS EVENS

TYPE: DFS III DFS IV DFS V OTHER

9 TRACK 21 TRACK

FORMAT: B GAPPED UNGAPPED

PACKING DENSITY: (L0) 356 BPI (M1) 712 BPI 800 BPI 1600 BPI

NO. BYTES IN HEADER REC: _____ NO. BYTES IN RECORD ID: 90 NO. BYTES PER SCAN: 254

RECORD NUMBERS: DEC. OCT. GAIN CONSTANT: 36 db INPUT IMPEDANCE: 5000 ohms.

FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)

AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____

PARAMETER: RECORD LENGTH: 8 sec. SAMPLE RATE: 1 ms. 4 ms. GAIN MODE: INITIAL MANUAL FINAL OPERATE

FILTERS: FREQ. Scrub LO CUT HZ SLOPE 18 HI CUT HZ SLOPE _____ NOTCH FILTER: IN OUT

DISPLAY: MODE: FLOAT AMPLIFIER DEFOAT DIRECT INITIAL GAIN: _____ db TRIP SENS.: _____ db POLARITY CONVENTION: NEGATIVE POSITIVE

CFS I: TYPE STACK: _____ GATE LENGTH: _____ RECORD REJECTION: _____ NOISE REDUCTION: _____ NOISE THRESHOLD: _____ CORR. SCALING: _____ R.C.U. NORM/ALT SW.

SOURCE: TYPE: DYNAMITE VIBROSEIS OTHER PATTERN: IN LINE NO. OF POSITIONS: _____ INLINE SPACING: _____ LATERAL SPACING: _____ STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____

RECEIVER: TYPE: GEOSPACE 10-D PATTERN: _____ NO. OF ELEMENTS: 18 INCLINE SPACING: _____ LATERAL SPACING: _____ CONNECTION: SERIES / PARALLEL RESISTANCE: 770 ohms STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____

SPREAD: NO. OF GROUPS: 144 GROUP INTERVAL: 220 FT SHOTPOINT INTERVAL: 1760 FT FOLD: 600% DIRECTION OF PROGRESSION: SOUTH OFFSET GROUP 1: _____ OFFSET GROUP _____ OFFSET GROUP 48/96: _____ LEADING GROUP: _____

DIAGRAMS/MISC. INFORMATION: LINE 131 SP#1 1760' SP#2

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SIZE	DEPTH	SHOT			SPREAD			REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.			NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	TR 1-48		TR 48-96	TR 1-48	TR 48-96		
1113	6721684	3104	22	23	26	27	29	30	32	33	37							
1114		3105			110	90												
1115		3106			110	90												
1116		3107			110	90												
1117		3108			110	90												
1118		3109			110	90												
1119		3110			110	90												
1120		3111			110	90												
1121		3112			110	90												
1122		3113			110	90							*	1-4 DEAD IE MISTAKE				
1123		3114			110	90												
1124		3115			110	90								TRACE 81 DEAD				
1125		3116			110	90								LAST SHOT OF DAY				

LAND SEISMIC RECORDING LOG

		CLIENT: Husky Oil 	PROSPECT: NPR 4 	AREA: ALASKA 	LINE NO: 131 				
PARTY NO: 1186 		INST. ENG: CARL HUBERT 			DATE: MO 2 DAY 10 YR 77 				
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG B 	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input checked="" type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: 80 	NO. BYTES PER SCAN: 254 	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 5000 ohms.		(1) (2) (3) (4) (5) (6) (7)	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.: _____		
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms. _____	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ 8cycle LO CUT 18 HI CUT _____	PRESSURE INCREASE <input type="checkbox"/> NEGATIVE } NUMBERS ON ON GEOPHONE. } POSITIVE } ON MAG. TAPE		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	CORR. SCALING: _____		R.C.U. NORM / AET SW.		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: IN LINE 	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
RECEIVER	TYPE: GEO SPACE 10-D 	PATTERN: _____	NO. OF ELEMENTS: 18 	INCLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: SERIES / PARALLEL 	RESISTANCE: 770 ohms							
SPREAD	NO. OF GROUPS: 144 	GROUP INTERVAL: 220 FT 	SHOTPOINT INTERVAL: 1760 FT 	FOLD: 600% 	DIRECTION OF PROGRESSION: SOUTH. 				
	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____				

DIAGRAMS/MISC. INFORMATION:

LINE 131

SHOTPOINT	TR. 1 to 16		TR. 17 to 32		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 1-16	TR 17-32	TR 33-48	TR 49-64	
1126	1127	1332									5						
1127	1334				1110	190					11						
1128	1335				1110	190											
DAXY tests records no. 317-329 Record no 323-325-326 NO GOOD																	

