

LAND SEISMIC RECORDING LOG



CLIENT: **HUSKY** PROSPECT: **PET. 4 REC #2** AREA: _____ LINE NO.: **133**
 PARTY NO.: **1186** INST. ENG.: **F. Carlsenius** DATE: **MO. 2 DAY 20 YR. 77**

INSTRUMENT: 1 SYSTEM 2 SYSTEMS 1-24 & 25-48 1-48 & 49-96 ODDS EVENS
 TYPE: DFS III DFS II OTHER 9 TRACK 21 TRACK
 FORMAT: **B** GAPPED UNGAPPED PACKING DENSITY: (10) 356 BPI (11) 712 BPI (12) 800 BPI (13) 1600 BPI
 NO. BYTES IN HEADER REC: _____ NO. BYTES IN RECORD ID: **80** NO. BYTES PER SCAN: **254** RECORD NUMBERS: DEC. OCT. GAIN CONSTANT: **36** db INPUT IMPEDANCE: **5000** ohms.

CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)
 AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____

PARAMETER: RECORD LENGTH: **B** sec. SAMPLE RATE: 1 ms. 4 ms. 2 ms. _____ ms. GAIN MODE: INITIAL FINAL LIP MANUAL OPERATE
 DISPLAY: MODE: FLOAT AMPLIFIER DEFLOAT DIRECT INITIAL GAIN: **18** db TRIP SENS.: **0** db POLARITY CONVENTION: PRESSURE INCREASE ON GEOPHONE NEGATIVE POSITIVE
 CFS I: TYPE STACK: _____ GATE LENGTH: _____ RECORD REJECTION: _____ NOISE REDUCTION: _____ NOISE THRESHOLD: _____ CORR. SCALING: _____ R.C.U. NORM / ALT SW. _____

SOURCE: TYPE: DYNAMITE VIBROSEIS OTHER CHG/ HOLE: **110** HOLE DEPTH: **105** NO. OF POSITIONS: _____ INLINE SPACING: _____ LATERAL SPACING: _____ STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____

RECEIVER: TYPE: **Geo-space 10-D** PATTERN: **IN LINE** NO. OF ELEMENTS: **18** INCLINE SPACING: _____ LATERAL SPACING: _____ CONNECTION: **Series-Parallel** RESISTANCE: **770** ohms STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____

SPREAD: NO. OF GROUPS: **144** GROUP INTERVAL: **220 feet** SHOTPOINT INTERVAL: **1760'** FOLD: **600%** DIRECTION OF PROGRESSION: **SOUTH** OFFSET GROUP 1: _____ OFFSET GROUP _____ OFFSET GROUP 48/96: _____ LEADING GROUP: _____

DIAGRAMS/MISC. INFORMATION: File # **001 - #013** Daily tests & Test T.B. Total hours = **13.5**
 North #1 Tail Spread 48 SP 1 SHORT SP 201
 South #1 1170' P Recorder set-up on S.P. #203.

SHOTPOINT	TR. to		TR. to		SHOT		SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR 48-96	TR 24-48
200	1722	0114	1723	0115	110	105	1	1/1	Travel time 6 hours Between S.P. #1 & #201 Distance 1170 feet = strings grouped close together.		
201		0115			110	105		1/9			
202		0116			110	105		1/17			
203		0117			110	105		1/25			
204		0118			110	105		1/33			
205		0119			110	105		1/5		2	
206		0120			110	105		1/13			
207		0121			110	105		1/21			
208		0122			110	105		1/29			
209		0123			110	105		1/37			
210		0124			110	105		1/45			

LAND SEISMIC RECORDING LOG

Page 1 of 2

		CLIENT: HUSKY			PROSPECT: PET. 4			AREA: REC #2			LINE NO: 133															
PARTY NO: 1186		INST. ENG: F. Carlsson						DATE: MO 2 DAY 26 YR 77																		
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96		<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV		<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		FORMAT: SEG. B		<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPM <input type="checkbox"/> 800 BPM (HI)		<input type="checkbox"/> 712 BPM <input checked="" type="checkbox"/> 1600 BPM PC									
	NO. BYTES IN HEADER REC: _____				NO. BYTES IN RECORD ID: _____				NO. BYTES PER SCAN: _____				RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: _____ db		INPUT IMPEDANCE: _____ ohms.									
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____							DATA CHANNEL NOS.: _____ (ON MAG TAPE)							AUXILIARY DATA: _____						AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: 8 sec.		SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		<input checked="" type="checkbox"/> IFF <input type="checkbox"/> FINAL		FILTERS: FREQ. 8		LO CUT HZ SLOPE 18		HI CUT HZ SLOPE 18		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT											
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		AMPLIFIER: <input type="checkbox"/> DIRECT		INITIAL GAIN: 78 db		TRIP SENS: 0 db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: _____		<input type="checkbox"/> NUMBERS ON MAG. TAPE		<input checked="" type="checkbox"/> DOWNBREAK ON DISPLAY		<input type="checkbox"/> UPBREAK									
CFS I	TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____		NOISE THRESHOLD: _____		CORR. SCALING: _____		R.C.U. NORM/ALT SW.													
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: _____		NO. OF POSITIONS: _____		INLINE SPACING: _____		LATERAL SPACING: _____		STAGGER: _____		LENGTH: _____		WIDTH: _____		LATERAL OFFSET: _____									
RECEIVER	TYPE: _____		PATTERN: _____		NO. OF ELEMENTS: _____		INLINE SPACING: _____		LATERAL SPACING: _____		STAGGER: _____		LENGTH: _____		WIDTH: _____		LATERAL OFFSET: _____									
SPREAD	NO. OF GROUPS: _____		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 1760'		FOLD: 600%		DIRECTION OF PROGRESSION: SOUTH		LEADING GROUP: 96															

DIAGRAMS/MISC. INFORMATION: **Left storage 1:00 P.M. Arrived field 3:00 P.M. Recording hours 9.5**
Left field. 9:30 Arrived Storage 9:30 A.M.

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT								SPREAD			REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	TR. 41-46	TR. 41-46	TR. 41-46	TR. 41-46			
211	672690	036			110	105	1			1/5				FILE # 025-034 Daily tests				
212	672690	037			110	105	2			1/13				FILE # 30 N.G. FILE # 03435 Test T.B.				
213	672690	038			110	105	3			1/21				Change Tape				



LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROJECT: PET. #4 - REC. #2	AREA: ALASKA	LINE NO.: 133
	PARTY NO.: 1186	INST. ENG.: F. CARLSENIUS		DATE: MO. 2, DAY 27, YR. 77
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	
	NO. BYTES IN HEADER REC: _____		NO. BYTES PER SCAN: _____	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)		GAIN CONSTANT: 36 db	
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	FILTERS: FREQ. 8
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 E 24 db	TRIP SENS: 0 db	LO CUT HZ SLOPE 18
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	H1 CUT HZ SLOPE 18
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INCLINE SPACING: _____
		CHG/ HOLE: 110	HOLE DEPTH: 105	LATERAL SPACING: _____
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	STAGGER: _____
	CONNECTION: _____	RESISTANCE: _____	STAGGER: _____	LENGTH: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: _____	FOLD: 600%
	OFFSET GROUP 1: _____	OFFSET GROUP: _____	OFFSET GROUP: _____	DIRECTION OF PROGRESSION: SOUTH

DIAGRAMS/MISC. INFORMATION: *File # 042-051 Daily Tests File # 50 NG. File # 052-Test T-B.* Travel Time: 5.5 hrs. Total time: 15.0 hrs.

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT		SPREAD			REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		LINE GROUPS	TR 1-41	TR 42-92
217	672691	058	17	2223	26	27	29	30	32	11	1/5		
218		057								12	1/13		
219		058								13	1/21		
220		056								14	1/29		
221		057								15	1/37		
222		058								16	1/45		
223		059								17	1/5		
224		060								18	1/14	(1/13)	operator error - 1/2 sp. too far South.
225		061								19	1/21		
226		062								110	1/29		
227		063								111	1/38	(1/37)	operator error - 1/2 sp. too far South.
228		064								112	1/45		
229		065								113	1/5		
230		066								114	1/13		
231	672691	067								115	1/21		
													tape change

LAND SEISMIC RECORDING LOG

	CLIENT: MUSKY		PROSPECT: PET. 4			AREA: Rec #2 ALASKA			LINE NO: 133			
	PARTY NO: 1186	INST. ENG: F. Carlsenius						DATE: 2 DAY 27 77				
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96		ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IIC	<input checked="" type="checkbox"/> DFS 3 <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:					AUXILIARY DATA:						
	DATA CHANNEL NOS.:					AUXILIARY CHANNEL NOS.:						
PARAMETER	RECORD LENGTH: 8 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: 8 LO CUT HZ SLOPE 18		FREQ. 128	HI CUT HZ SLOPE 18	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AOC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS: D db		POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY		
CFS I	TYPE STACK:		GATE LENGTH:	RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:	CORR. SCALING:		R.C.U. NORM / ALT SW.	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER			PATTERN:		NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: 110		HOLE DEPTH: 105		SWEEP POSITION:		SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE:			PATTERN:		NO. OF ELEMENTS:		INCLINE SPACING:		LATERAL SPACING:		
	CONNECTION:			RESISTANCE: _____ ohms		STAGGER:		LENGTH:		WIDTH: _____ LATERAL OFFSET:		
SPREAD	NO. OF GROUPS:		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 1760		FOLD: 600%		DIRECTION OF PROGRESSION: SOUTH			
	OFFSET GROUP 1:		OFFSET GROUP _____		OFFSET GROUP _____		OFFSET GROUP 48/96:		LEADING GROUP: 96			

DIAGRAMS/MISC. INFORMATION: **Tape # 672692 - File # 068 - I.F.P.O.S.C. Test = 8 seconds.**

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT							SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 1-48		TR 49-96	TR 1-48	TR 49-96	
232	672692	069			110	105	16						3					
233		070			110	105	17											
234	672692	071			110	105	18											

LAND SEISMIC RECORDING LOG

CLIENT: HUSKY		PROSPECT: N.P.R. #4		AREA: REC #2		LINE NO: 133			
PARTY NO: 1186		INST. ENG: F. Carlsenius				DATE: MO -2 DAY 28 YR 77			
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS (9-TRACK)		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		TRACKS: <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		FORMAT: B		GAPPED: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	
NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		RECORD NUMBERS: DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: 36 db		INPUT IMPEDANCE: _____ ohms.	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: _____		AUXILIARY DATA: _____		(1) (2) (3) (4) (5) (6) (7)		PACKING DENSITY: (LO) <input type="checkbox"/> 256 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI	
PARAMETER		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE		FILTERS: 8 LO CUT 18 HI CUT 128		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY		MODE: <input checked="" type="checkbox"/> AOC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		TRIP SENS: 0 db		POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____		NOISE THRESHOLD: _____	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: _____		NO. OF POSITIONS: _____		INLINE SPACING: _____	
RECEIVER		CONNECTION: _____		RESISTANCE: _____ ohms		STAGGER: _____		INCLINE SPACING: _____	
SPREAD		NO. OF GROUPS: _____		GROUP INTERVAL: 220'		SNOTPOINT INTERVAL: 1760'		FOLD: 600	
DIAGRAMS/MISC. INFORMATION:		Tape # 672692 - File # 072-079 Daily tests File # 080 - Pulse test File # 081 - Test T.B.				Travel time: 3.5 hours. Total Time: 15.5 hours. 15.0 hrs.			

SHOTPOINT	TR. NO.		TR. NO.		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR 1-48	TR 49-96	TR 97-144	TR 145-192
235	672692	082			110	105	11	115					
236		083			110	105	12	113					
236		084			110	120	13	113	EXPERIMENTAL	TOTAL OF 45 MINS. TIME TO SHOOT 3 EXP. SHOTS.			
236		085			110	135	14	113	SHOTS DEEPER				
236		086			110	150	15	113	WITH same powder size.				
237		087				105	16	121					
238		088				120	17	129					
239		089				135	18	137					
240		090				105	19	113					
241		091					10	112	* (111) grp. to for South				
242		092					11	119					
243		093					12	127					
244		094					13	135					
245		101					14	111					
246	672692	102			110	105	15	119	3 Move up. Inst. failure? Only 2 seconds. Rec # jumped to #101 3 PARITY ERRORS. JUST DRAY ON NEXT SHOT # 102.				

LAND SEISMIC RECORDING LOG

Page 2 of 2.



	CLIENT: HUSKY	PROSPECT:	AREA:	LINE NO: 133			
	PARTY NO: 1186	INST. ENG: F. Carlsenius		DATE: 2 DAY 28 YR 77			
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI
CONFIGURATION (MAG TAPE)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC <input type="checkbox"/> OCT.	GAIN CONSTANT:	INPUT IMPEDANCE: ohms
PARAMETER	FIELD TRACE NOS.:	DATA CHANNEL NOS. (ON MAG TAPE)		AUXILIARY DATA: AUXILIARY CHANNEL NOS.:			
DISPLAY	RECORD LENGTH: sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF	FILTERS: FREQ.	LO CUT HZ SLOPE	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
CFS I	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: db.	TRIP SENS: db.	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:
RECEIVER	CONNECTION:	RESISTANCE: ohms	STAGGER:	INCLINE SPACING:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	LEADING GROUP:	

DIAGRAMS/MISC. INFORMATION: **Tape # 672693 File # 103 I.F.P. OSC. TEST.**

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT _____					SPREAD _____		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		HT.	HT.	HT.	HT.
247	672693	1109			110	105	16			1/17						
248		1109					17			1/25						
249		1109					18			1/33						
250		1109					19			1/5						
251		1108					20			1/13						
252		1109					21			1/21						
253		110					22			1/29						
254	672693	1111			110	105	23			1/37						

LAND SEISMIC RECORDING LOG

Page 1 of 2

	CLIENT: HUSKY	PROJECT: N.P.R. #4	AREA: REC.#2	LINE NO: 133	
	PARTY NO: 1186	INST. ENG: F. Carlsenius		DATE: 3 1 77	

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI
(9-TRACK)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.	(1) (2) (3) (4) (5) (6) (7)

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)	AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____
--------------------------	---	--

PARAMETER	RECORD LENGTH: B	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 18	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 & 24 db	TRIP SENS.: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	DOWNBREAK ON DISPLAY: <input type="checkbox"/> UPBREAK	R.C.U. NORM/ALT SW: _____
CFS I	TYPE STACK: _____	DATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____		

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1 hole	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	

RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INCLINE SPACING: _____	LATERAL SPACING: _____
	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____
					LATERAL OFFSET: _____

SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: SOUTH
	OFFSET GROUP 1: _____	OFFSET GROUP: _____	OFFSET GROUP: _____	OFFSET GROUP 48/96: _____	LEADING GROUP: 96

DIAGRAMS/MISC. INFORMATION: **Tape # 672693 - File # 112-119 Daily Tests**
File # 120 Pulse Test
File # 121 Test + B

Travel time = 2 hours
Total = 13.5 hours

SHOTPOINT	TR. No		TR. No		SHOT		SPREAD		REMARKS:	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	HT.	REC.	HT.	REC.
2515	672693	120			110	100	11			1/3						
2516		123			110	105	12			1/11						
2517		124					13			1/19						
2518		125					14			1/27						
2519		126					15			1/5						
260		127			110	105	16			1/13						
261		128			110	103	17			1/21						
262		129			110	105	18			1/29						
263	672693	130			110	105	19			1/37						

LAND SEISMIC RECORDING LOG



CLIENT: HUSKY	PROSPECT: N.P.R 4	AREA:	LINE NO: 133
PARTY NO: 1186	INST. ENG: F. Carlsenius		DATE: MO 3 DAY 1 YR 77



INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) (2) (3) (4) (5) (6) (7)		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:	DATA CHANNEL NOS.:			(ON MAG TAPE)				
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: LO CUT HZ SLOPE _____ HI CUT HZ SLOPE _____ FREQ. _____	<input type="checkbox"/> NEGATIVE } NUMBERS ON <input type="checkbox"/> POSITIVE } ON MAG. TAPE	<input type="checkbox"/> NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW.		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:				
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	CONNECTION:	RESISTANCE: _____ ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:				
	OFFSET GROUP 1:	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96:	LEADING GROUP:				

DIAGRAMS/MISC. INFORMATION: **Tape 672694 File # 131 IFA DSCTEST.**

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD		REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-48	TR 49-96	TR 1-48	TR 49-96
264	672694	1312			110	105	11			1/3						
265		1313					11			1/11						
266		1314					11			1/19						
267		1315					11			1/27						
268		1316					11			1/35						
269		1317					11			1/1						
270		1318					11			1/19						
271		1319					11			1/17						
272		1320					11			1/25						
273	672694	1341			110	105	11			1/33						

LAND SEISMIC RECORDING LOG



Page 2 of 2

	CLIENT: MUSKY	PROSPECT: N.P.R. 4	AREA: REC 2	LINE NO.: 133						
PARTY NO.: 1186		INST. ENG.: F. Carlsenius		DATE: MO 3 DAY 2 YR 77						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-40	<input type="checkbox"/> ODDS EVENS	TYPE: <input type="checkbox"/> DFS III	<input type="checkbox"/> DFS X	<input type="checkbox"/> 9 TRACK	FORMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI	(H) <input type="checkbox"/> 712 BPI
	<input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-48 & 49-96		<input type="checkbox"/> DFS III	<input type="checkbox"/> OTHER	<input type="checkbox"/> 21 TRACK		<input type="checkbox"/> UNGAPPED	<input type="checkbox"/> 800 BPI	<input type="checkbox"/> 1600 BPI
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: _____			GAIN CONSTANT: _____ db			
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: _____		LO CUT: _____	H1 CUT: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	JRIP SENS: _____ db	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: _____		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____		NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	CHG/HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____		DIRECTION OF PROGRESSION: _____		LEADING GROUP: _____		

DIAGRAMS/MISC. INFORMATION: **Tape # 672695 - File # 161 IFR OSC Test**
File # 163 Test T.B.

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT								SPREAD		REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SET UP	TR 1-48	TR 49-96		TR 1-48	TR 49-96		
* 280	672695	1162			1110	1105	17				117		2	No Record - Operator error Record switch in ACCAL.					
281		1164					18				125								
282		1165					19				133								
283		1166					10				15		3						
284		1167					11				13								
285		1168					12				21								
286		1169					13				29								
287	672695	1170			110	195	14				37								

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: N.P.R. 4	AREA: REC 2	LINE NO: 133	
PARTY NO: 1186	INST. ENG: F. Carenius			DATE: MO 3 DAY 3 YR 77	

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	DOOS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input checked="" type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms			

CONFIGURATION (MAG TAPE)	AUXILIARY DATA:
FIELD TRACE NOS. _____	AUXILIARY CHANNEL NOS. _____
DATA CHANNEL NOS. _____	(ON MAG TAPE) _____

PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms. ms.	GAIN MODE: <input checked="" type="checkbox"/> IFF <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 18	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____	NUMBERS ON ON MAG. TAPE: _____	DOWNBREAK UPBREAK: _____ ON DISPLAY
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ MOLE: 110	HOLE DEPTH: 105	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	

RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____
	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____

SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 600%	DIRECTION OF PROGRESSION: SOUTH
	OFFSET GROUP: _____	OFFSET GROUP: _____	OFFSET GROUP: _____	OFFSET GROUP 48/96: _____	LEADING GROUP: 96

DIAGRAMS/MISC. INFORMATION: File # 171-178 Daily Tests IFR OSC = 7 seconds. Travel time = 5 hours
 " 179 = Pulse test Total = 11.5 hours
 " 180 = Test T.B.

SHOTPOINT	TR. NO.		TR. NO.		SHOT								SPREAD		REMARKS	CORR. STACK			
	REEL NOS.	REC.	REEL NOS.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			TR 1-48		TR 49-96			
288	672695	181			1110	105	1		SE	1/3									
289		182					2			1/11									
290		183					3			1/19									
291		184					4			1/27									
292		185					5			1/35				offset 3 stations South.					
293		186					6			1/43									
294		187					7			1/15				2 Only 3.2 second recording?					
295		188					8			1/23				Trouble in tape transport (head cover)					
296		189					9			1/31									
297		190					10			1/39									
298	672695	191			1110	105	11			1/47				low tape - Picked override Tape stopped after 39 seconds					