

LAND SEISMIC RECORDING LOG

1 of 1



		CLIENT: HUSKY	PROSPECT: N.P.R.-4	AREA: REC-2	LINE NO: 137				
PARTY NO: 1186		INST. ENG: F. Carlsenius			DATE: 3 DAY 8 YR 77				
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____ DATA CHANNEL NOS. _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS. _____					
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input checked="" type="checkbox"/> JFF <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	FREQ. 128 HI CUT HZ SLOPE 18	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 37.8 db	TRIP SENS: 0 db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	E.C.U. NORM./ALT SW. _____		
SOURCE	<input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: _____	RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: NORTH	OFFSET GROUP 48/96: _____	LEADING GROUP: 96		

DIAGRAMS/MISC. INFORMATION: **File #001-008 - Daily Tests** **Moved to new line - laid out - wait for cholas**
009 - Pulse test **Travel - 7 hours -**
010 - Test T-B. **24grp. tail-spread.** **Total - 15 hours -**

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT								CORR. SWITCH	SPREAD	REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	LINE GROUPS	HY.	REC.				HY.	REC.		
1	672700	111			11	105	11					11		A good part of line was in deep snow - poor seis plants. offset 50' N & 50' W.					
2		112					12					119							
3		113					13					117							
4		114					14					125							
5		115					15					133							
6		116					16	150 W				141							
7	672700	117					17					149							

LAND SEISMIC RECORDING LOG

Page 1 of 2

	CLIENT: HUSKY	PROSPECT: N.P.R. 4	AREA: REC 2	LINE NO.: 137					
	PARTY NO.: 1186	INST. ENG.: F. Carlsenius		DATE: _____					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____	INPUT IMPEDANCE: _____	db		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA:					
	DATA CHANNEL NOS.: _____			AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> 1PP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT 18 HZ	HI CUT 128 HZ	LO SLOPE _____	HI SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 db	TRIP SENS: 0 db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE } NUMBERS ON MAG. TAPE <input checked="" type="checkbox"/> POSITIVE }	<input type="checkbox"/> DOWNBREAK } <input type="checkbox"/> UPBREAK }	ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG./HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
RECEIVER	TYPE: _____	PATTERN: 1	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: _____	RESISTANCE: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: NORTH				
	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96: _____	LEADING GROUP: 96				



DIAGRAMS/MISC. INFORMATION: **File # 18-26 Daily Tests #21 N.G.** **Travel - 3.5 hours.**
File # 27 - Pulse Test **Total - 13.5 hours**
File # 28 & 29 N.G. **File # 30 Test T.B.**

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT					SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-24		TR 25-48	
														HY.	REC.	HY.	REC.
1	672700	31			110	105	1				1/3						
9		32					2				1/11						
10		33					3				1/19						
11		34					4				1/27						
12		35					5				1/35						
13		36					6				1/43						
14		37					7				1/3						
15		38					8				1/11						
16	672700	39			110	105	9				1/19						

1 second record - Operator error.
Had last trouble - was checking - failed to
change to 8 second record length.
Shot down - cable in front
took up.

LAND SEISMIC RECORDING LOG

Page 1 of 1



	CLIENT: MUSKY	PROSPECT: N.R.R. 4	AREA: REC 2	LINE NO: 137						
PARTY NO: 1186		INST. ENG: F. Carlsenius		DATE: MO 3 DAY 10 YR 77						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 336 BPI (20) <input type="checkbox"/> 600 BPI	(11) <input type="checkbox"/> 712 BPI (12) <input checked="" type="checkbox"/> 1000 BPI	
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: _____						
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: _____						
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ 18	HI CUT HZ 18	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEPLOY	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 db	TRIP SENS: 0 db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE: _____	<input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	P.C.U. NORM/ALT SW. _____			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
		CHG/HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
	CONNECTION: _____	RESISTANCE: _____ ohms								
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: NORTH					
	OFFSET GROUP 1: _____	OFFSET GROUP: _____	OFFSET GROUP: _____	OFFSET GROUP 48/96: _____	LEADING GROUP: 96					

DIAGRAMS/MISC. INFORMATION: File# **41-48 = Daily Tests**
49 = Pulse Test
50 = Test T.B.

Travel = 3 hours
Total = 13 hours.

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	SET UP	TR 1-48	TR 48-96	TR 1-48
117	672701	511			110	105	1				1/3					
118		512					2				1/11					
119		513					3				1/19					
120		514					4				1/27					
121		515					5				1/35					
122		516					6				1/43					
123		517					7				1/3	2				
124		518					8				1/11					
125		519					9				1/19					
126		160				110	105	10			1/27					
127		161				110	105	11			1/35					
128		162						12			1/1	3				
129		163						13			1/19					
130		164						14			1/17					
131		165						15			1/25					
132	672701	166			110	105	16				1/33					

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: N.P.R. 4	AREA: REC 2	LINE NO: 137	
	PARTY NO: 1186	INST. ENG: F. Carenius		DATE: MO 3 DAY 11 YR 77	

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI		
[9-TRACK]	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____		DATA CHANNEL NOS.: _____		[ON MAG TAPE]						
PARAMETER	RECORD LENGTH: _____	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	FREQ. _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____	TRIP SENS: _____	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON. MAG. TAPE: _____	DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/>	ON DISPLAY			
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____				
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
RECEIVER	CONNECTION: _____	RESISTANCE: _____	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____				
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: _____					

DIAGRAMS/MISC. INFORMATION: **Tape 672701 - File # 67-71 D.R.D.** **Travel - 3 hours**
Tape 672702 - File # 72-75 Daily tests **Very Cold.**
File # 76 shot T.B. **Total = 13 hours.**



SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT			SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH		LINE GROUPS	HT.	REC.	HT.
33	672702	77			110	105	1		1/5					
34		78					2		1/13					
35		79					3		1/21					
36		80					4		1/29					
37		81					5		1/37					
38		82					6		1/45					
39		83					7		1/5		2			
40		84					8		1/13					
41		86					9		1/21					
42		87					10		1/29					
43		88					11		1/37					
44		89					12		1/3		3			
45	672702	90			100	105	13		1/11					

} Very high frequency noise on records. Camp with 4 strings was moving at this time also.

File # 95 I.F.P.O.S.C. (INST. CHECK)
 Reported most of line.
 Some phones in Deep snow.
 Tried to improve by setting them in track but this was run loose snow and deep quags.
 Shut down as there seem to be inst. trouble.

LAND SEISMIC RECORDING LOG

Page 1 of 2



	CLIENT: HUSKY	PROSPECT: N.P.R. 4	AREA: REC 2	LINE NO.: 137					
	PARTY NO.: 1186	INST. ENG.: F. Carlsenus		DATE: MO 3 DAY 14 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input checked="" type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA:					
	DATA CHANNEL NOS.: _____			AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	FREQ. 128	HI CUT HZ SLOPE 18	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> MAG <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT	AMPLIFIER: <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 db	TRIP SENS.: 0 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	CONNECTION:	RESISTANCE: _____ ohms	CHG./HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	OFFSET GROUP:	SHOTPOINT INTERVAL:	OFFSET GROUP:	FOLD:	OFFSET GROUP 48/96:	DIRECTION OF PROGRESSION: NORTH	LEADING GROUP:

DIAGRAMS/MISC. INFORMATION: *Tape 672703 File # 100-107 Daily Tests*
File # 108 - Pulse Test
File # 109 - Test T.B.

Short handed. Had to dig cable and seis strings out of snow from the storm. Slow going.

SHOTPOINT	TR. 10		TR. 10		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-48
53	672703	1110			110	110	11				113		
54		1111					12				111		
55		1112					13	50 E			119		
56		1113					14	25 E			127		
57		1114					15				135		
58		1115					16				143		
59		1116					17				113		
60		1117					18				111		
61		1118					19				119		
62	672703	1119			110	110	10				127		
										<i>Travel 5 hours.</i>			
										<i>Total = 15 hours.</i>			
										<i>Change Tape.</i>			

LAND SEISMIC RECORDING LOG

	CLIENT: MUSKY	PROSPECT: N.P.R. 4	AREA: Rec 2	LINE NO.: 137	
	PARTY NO.: 1186	INST. ENG.: F. Carlsenius		DATE: 3 DAY 14 77	

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-40 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOMAT: _____ SEG: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: _____ (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
(9-TRACK)	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____	(ON MAG TAPE)	AUXILIARY DATA:
	DATA CHANNEL NOS.: _____		AUXILIARY CHANNEL NOS.: _____

PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT: _____ HZ SLOPE	HI CUT: _____ HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	<input type="checkbox"/> MODE <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	<input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	<input type="checkbox"/> NUMBERS ON ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY

SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	

RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: _____	RESISTANCE: _____ ohms							



SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: NORTH.
	OFFSET GROUP 1: _____	OFFSET GROUP: _____	OFFSET GROUP: _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____

DIAGRAMS/MISC. INFORMATION: **Tape 672704 - File #120 IFR OSC. 1 second.**
File #121 IFR OSC. 4 seconds.

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT		SPREAD		REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-48
63	672704	122			110	105	11			135			
64		123			111	105	12			143			
65		124			112	105	13			13			
66		125			113	105	14			111			
67		126			114	105	15			118			
68		127			115	105	16			127			
69	672704	128			116	105	17			135			

LAND SEISMIC RECORDING LOG

Page 1 of 2

	CLIENT: HUSKY	PROSPECT: N.P.R. 9	AREA: REC 2	LINE NO.: 137						
PARTY NO.: 1186		INST. ENG.: F. Carlsenius		DATE: MO 3 DAY 15 YR 77						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input checked="" type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT SEG: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 800 BPI	(N) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.: _____			
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input checked="" type="checkbox"/> R.I.F. <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: 8	LO CUT: 1200 Hz	H) CUT: 18 Hz	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS.: 0 db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	CONNECTION:	RESISTANCE: _____ ohms	CHG/ MOLE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION: NORTH					
DIAGRAMS/MISC. INFORMATION:		Tape # 672704 File # 129-136 Daily Tests			Travel = 5.5 hours			Picked up.		
		File # 137 = Pulse Test			Total = 17.5 hours			Spread in storm.		
		File # 138 = Test T.B.								

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-24
70	672704	139			110	145	1				1		
71		140					2						
72		141					3						
73		142					4	150	W				
74		143					5				2		
75		144					6						
76		145					7						
77		146					8						
78		147					9						
79		148					10						
80	672704	149			110	145	11				3		

