



LAND SEISMIC RECORDING LOG

	CLIENT: HEUSKY NPA OPERATIONS	PROSPECT: NPA-4	AREA: NORTH SLOPE	LINE NO: 29	
PARTY NO: 1173	INST. ENG: DAVID OREAUX	Total Hours 14		TRAVEL 6	
DATE: MO 3 DAY 9 YR 77					
INSTRUMENT (9-TRACK): <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC: 228	ODDS & EVENS: <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	TRACKS: <input type="checkbox"/> 19 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 712 BPI
NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: 1-96 DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)	AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 1/8 HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
PARAMETER: RECORD LENGTH: 8 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	TRIP SENS.: 12 db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG. TAPE	DOWNBREAK UPBREAK ON DISPLAY
DISPLAY: MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 42 db	GATE LENGTH: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE	NO. OF POSITIONS: 1	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____
CHG/HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____
RECEIVER: TYPE: GEOSPAC 203 10 HZ	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____
CONNECTION: SEALS	RESISTANCE: 450 ohms	SWEEP TAPER: _____	PHASE COMP: _____	DIRECTION OF PROGRESSION: NORTH	LEADING GROUP: #1
SPREAD: NO. OF GROUPS: 96	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	OFFSET GROUP 48/96: 10450'	

DIAGRAMS/MISC. INFORMATION: **File # 001 8 SEC ALL ONES** **File # 15 TEST TIME BREAK**
File # 2-14 DAILY TESTS **WAITED 4 HOURS FOR DALLS**

SHOTPOINT	TR #1		TR #2		SHOT			SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH		#1	LINE GROUPS	TR 1-48	TR 49-96
470	75162	16			110	105	1		49	453-4	TS4-2			
461		17			110	105	1		49	453-4	TS4-2			
468		18			110	105	1		49	453-4	TS4-2			
467		19			110	105	1		49	453-4	TS4-2			
466		20			110	105	1		49	453-4	TS4-2			
465		21			110	105	1		49	453-4	TS4-2			
464		22			110	105	1	50 E	49	453-4	TS4-2			
463		23			110	105	1		45	452-4	TS4-2			
462		24			110	105	1		41	451-4	TS4-2			
461		25			110	105	1		39	450-2	TS4-2			
460		26			110	105	1		33	449-4	TS4-1			
459		27			110	105	1		29	448-4	TS4-1			

UNABLE TO SHOOT (AIRPLANE NOISE)
 AIRPLANE NOISE IS DELAYING RECORDING
 ALMOST EVERY SHOT
 WRONG CDP SWITCH SETTING

LAND SEISMIC RECORDING LOG

	CLIENT: Husky NPL OPERATIONS	PROSPECT: NPA-4	AREA: NORTH SLOPE	LINE NO: 29				
	PARTY NO: 1173	INST. ENG: DAVID BREAU	TOTAL HOURS: 13 1/2	TAPES: 4	DATE: 3 DAY 10 YR 78			
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS	TYPE: <input type="checkbox"/> DPS III	<input checked="" type="checkbox"/> 9 TRACK	<input type="checkbox"/> GAPPED	PACKING DENSITY: (LOI <input type="checkbox"/> 356 BPI	(HI) <input type="checkbox"/> 712 BPI
	<input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> EVENS	<input type="checkbox"/> DPS IX	<input type="checkbox"/> 21 TRACK	<input checked="" type="checkbox"/> UNGAPPED	(LOI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 1600 BPI
NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: DEC.	<input type="checkbox"/> OCT.	GAIN CONSTANT: 36	db	INPUT IMPEDANCE: _____	ohms
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	DATA CHANNEL NOS.: 1-96	(ON MAG TAPE)		AUXILIARY DATA:	AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL	<input type="checkbox"/> MANUAL	FILTERS: FREQ. 8	LO CUT HZ SLOPE: 18	HI CUT HZ SLOPE: 128	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER	INITIAL GAIN: 42 db	<input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	<input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	POLARITY CONVENTION: <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK	<input type="checkbox"/> UPBREAK ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE	PATTERN: SINGLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
	<input type="checkbox"/> VIBROSEIS	CHG/ HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:
	<input type="checkbox"/> OTHER							PHASE COMP:
RECEIVER	TYPE: GEOSPACE 200 10HZ	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
	CONNECTION: SERIES	RESISTANCE: 150 ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 12	DIRECTION OF PROGRESSION: NORTH	LEADING GROUP: #1		
	OFFSET GROUP 1: 10450'	OFFSET GROUP 96: 110'	OFFSET GROUP 49: 110'	OFFSET GROUP 48/96: 10450'				

DIAGRAMS/MISC. INFORMATION: **FILE # 42 8SEC ALL ONES** **FILE # 43 TEST TIME BREAK**

TAPE # 751524 - File # 28-41 DAILY TESTS

SHOTPOINT	TR 1 to 96		TR 10		SHOT			SPREAD			REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET DIR.	COP SWITCH	LINE GROUPS #1	SP		TR 41	TR 42-96
H58	751525	45			110	105	1	49	470-1	447-4	452		
H57		46			110	105	1	45	469-1	446-4			
H56		47			110	105	1 330 5	41	468-1	445-4			
H55		48			110	105	1	37	467-1	444-4			
H54		50			110	105	1	33	466-1	443-4			
H53		51			110	105	1	29	465-1	442-4			
H62		62			110	105	1	25	464-1	441-4			
H51		63			110	105	1	21	463-1	440-4			
H50		54			110	105	1	17	462-1	439-4			
H49		65			110	105	1	13	461-1	438-4			
H48		66			110	105	1	9	460-1	437-4			
H47		67			110	105	1	5	459-1	436-4			
H46		60			110	105	1	1	458-1	435-4			
H45		61			110	105	1	45	457-1	434-4	440		
H44		62			110	105	1	41	456-1	433-4			
H43		63			110	105	1	37	455-1	432-4			
H42		64			110	105	1	33	454-1	431-4			
H41	751526	66			110	105	1	29	453-1	430-4			
H40		67			110	105	1	25	452-1	429-4			
H39		68			110	105	1	21	451-1	428-4			

OMIT FILE # 44

SP# 456 EARLY START OF RECORD

FILE # 48 TEST TIME BREAK

NO PRELOAD LOG

SP# 448 EARLY START OF RECORD

EARLY START OF RECORD

FILE # 58, 59 TEST TIME BREAK

FILE # 65 8SEC ALL ONES

LAND SEISMIC RECORDING LOG



CLIENT: **Haskey NPA OPERATIONS** PROSPECT: **NPR-4** AREA: **NORTH SLOPE** LINE NO: **29**
 PARTY NO: **1173** INST. ENG.: **DAVID BREAUX** **Total Hours 13 1/2** **TRAVEL 4** DATE: **MO 3 DAY 10 YEAR 1977**

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS NO. BYTES IN READER REC.: 228	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 48 & 49-96 ODDS EVENS NO. BYTES IN RECORD ID: 2	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER NO. BYTES PER SCAN: 254	<input checked="" type="checkbox"/> 1 TRACK <input checked="" type="checkbox"/> 2 TRACK RECORD NUMBERS: 4 DEC <input type="checkbox"/> OCT GAIN CONSTANT: 36 db PACKING DENSITY: (1) (2) (3) (4) (5) (6) (7)	FOPMAT: B <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED INPUT IMPEDANCE: ohms.
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:
PARAMETER	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL		FILTERS: FREQ. 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE	
DISPLAY	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	TRIP SENS.: 42 db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE } NUMBERS ON MAG. TAPE	
CFS I	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 42 db	RECORD REJECTION:	NOISE REDUCTION: NOISE THRESHOLD: CORR. SCALING: R.C.U. NORM./ALT SW.	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:
RECEIVER	TYPE: GEOSPAGE JOB 10AZ	CHG/HOLE: 110	HOLE DEPTH: 105	SWEEP START:	SWEEP END:
SPREAD	CONNECTION: SERIES	RESISTANCE: 450 ohms	STAGGER:	INLINE SPACING: 18	LATERAL SPACING:
	NO. OF GROUPS: 96	GROUP INTERVAL:	SHOTPOINT INTERVAL: 880'	FOLD: 12	DIRECTION OF PROGRESSION: NORTH
	OFFSET GROUP 1: 10450'	OFFSET GROUP 18 : 110'	OFFSET GROUP 47 : 110'	OFFSET GROUP 48/96: 10450'	LEADING GROUP: #1

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 No. 96		TR 10		SHOT			SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		COP SWITCH	#96 LINE GROUPS	#1	TR 1-48 REC.
438	751624	69			110	105	11			17	440-1	427-4	440	
437		70			110	105	11			13	449-1	426-4		
436		71			110	105	11			9	448-1	425-4		
435		72			110	105	11			41	447-1	424-4	431	
434		73			110	105	11			37	446-1	423-4		
433		74			110	105	11			33	445-1	422-4		
432		75			110	105	11			29	444-1	421-4		
431		76			110	105	11			25	443-1	420-4		
430		77			110	105	11			21	442-1	419-4		
429		78			110	105	11			17	441-1	418-4		
428		79			110	105	11	55 S		13	440-1	417-4		
427		80			110	105	11			9	439-1	416-4		

SP# 438 (WEAK)
 DELAY IN SHOOTING [AIRPLANE NOISE]
 " " " " " "

LAND SEISMIC RECORDING LOG

CLIENT: Husky NPR OPERATIONS	PROSPECT: NPR-4	AREA: NORTH SLOPE	LINE NO: 29
PARTY NO: 1173	INST. ENG: DAVID BREAWY	Total Hours 13 TRAVEL 2 1/2	DATE: 3 DAY 11 YR 77

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS <input type="checkbox"/> ODDS <input checked="" type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input checked="" type="checkbox"/> DFS X <input type="checkbox"/> OTHER	9 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAT: B SEG.	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (11) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI				
NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: ohms	(1)	(2)	(3)	(4)	(5)	(6)	(7)

CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-96 DATA CHANNEL NOS.: 96 (ON MAG TAPE)	AUXILIARY DATA: AUXILIARY CHANNEL NOS.:
---	--

PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	LO CUT HZ SLOPE: 18	HI CUT HZ SLOPE: 120	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 42 db	TRIP SENS: 42 db	POLARITY CONVENTION: <input checked="" type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	PRESSURE INCREASE ON GEOPHONE: <input checked="" type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	NUMBERS ON ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON DISPLAY

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/HOLE: 110	HOLE DEPTH: 105	SWEET POSITION:	SWEET START:	SWEET END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	

RECEIVER	TYPE: GEOSPACE 200 104Z	PATTERN: INLINS	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:
	CONNECTION: SERIES	RESISTANCE: 450 ohms	STAGGER:	LENGTH:	WIDTH:

SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 12	DIRECTION OF PROGRESSION: NORTH
	OFFSET GROUP 1: 10450'	OFFSET GROUP: 110'	OFFSET GROUP: 110'	OFFSET GROUP 48/96: 10450	LEADING GROUP: #1

DIAGRAMS/MISC. INFORMATION: TAPE# 751526 File# 81-96 DAILY TEST

TAPE# 751527 File# 97 8sec ALL ONES File# 98 TEST TIME BREAK

SHOTPOINT	TR 1 to 96		TR 10 to		SHOT			SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		#1	LINE GROUPS	#96	TR 1-48
H206	751527	99			110	105	11			41	415-4	438-1	442		
H25		100			110	105	11			37	414-4	437-1			
H24		101			110	105	11			33	413-4	436-1			
H23		102			110	105	11			29	412-4	435-1			
H22		103			110	105	11			25	411-4	434-1			
H21		104			110	105	11			21	410-4	433-1			
H20		106			110	105	11			17	409-4	432-1			
H19		106			110	105	11			13	408-4	431-1			
H18		107			110	105	11			9	407-4	430-1			
H17		108			110	105	11	60 W/W		5	406-4	429-1			
H16		109			110	105	11			1	405-4	428-1			
H15		110			110	105	11			45	404-4	427-1	H10		
H14		111			110	105	11			41	403-4	426-1			
H13		112			110	105	11			37	402-4	425-1			
H12		113			110	105	11			33	401-4	424-1			
H11		114			110	105	11			29	400-4	423-1			
H10		116			110	105	11			25	399-4	422-1			
H09		116			110	105	11			21	398-4	421-1			
H08	751528	118			110	105	11			17	397-4	420-1			
H07		119			110	106	11			13	396-4	419-1			

LAND SEISMIC RECORDING LOG



CLIENT: Husky NPR OPERATIONS		PROSPECT: NPR-4		AREA: NORTA SLOPE		LINE NO: 29	
PARTY NO: A-1173		INST. ENG: DAVID BREAUX		Total Hours 13		DATE: MO 3 DAY 11 YR 77	
INSTRUMENT (9-TRACK): <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		ODDS: <input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		FORMAT: B	
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input checked="" type="checkbox"/> OFF		FILTERS: 8		LO CUT 18 HZ SLOPE	
PARAMETER: RECORD LENGTH: 8 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 2 ms <input checked="" type="checkbox"/> 4 ms		TRIP SENS: 42 db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	
DISPLAY: MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> DEPLOY <input type="checkbox"/> DIRECT		INITIAL GAIN: 42 db		NOISE REDUCTION: _____		CORR SCALING: _____	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE		NO. OF POSITIONS: 1		LATERAL SPACING: _____	
RECEIVER: TYPE: GEOSCOPE 20B 10HZ		PATTERN: INLINE		NO. OF ELEMENTS: 18		LATERAL SPACING: _____	
SPREAD: NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'		FOLD: 12F	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 96		TR 10 to		SHOT			SPREAD			REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-24	TR 41-96
H06	351528	128			110	105	11			9	396-8	418-1	410	
H05		121			110	105	11			5	395-4	417-1		
H04		122			110	105	11			1	395-8	416-1		DELAY SHOOTING AIRPLANE NOISE
H03		123			110	105	11			45	394-4	415-1	398	
H02		124			110	105	11			41	394-8	414-1		DELAY SHOOTING AIRPLANE NOISE
H01		125			110	105	11			37	393-4	413-1		
H00		126			110	105	11			33	393-8	412-1		DELAY SHOOTING AIRPLANE NOISE
399		127			120	105	11			29	392-4	411-1		
398		128			110	105	11			25	392-8	410-1		DELAY SHOOTING AIRPLANE NOISE
397		129			110	105	11			21	391-4	409-1		

LAND SEISMIC RECORDING LOG



CLIENT: Husky DPR-4	PROSPECT: DPR-4	AREA: NORTH SLOPE	LINE NO: 29
PARTY NO: 173	INST. ENG: DAVID BREACH		DATE: MO 3 DAY 12 YR 77

INSTRUMENT (9-TRACK)	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: DEC	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: ohms
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)			AUXILIARY DATA:	
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: 1 ml. 4 ml. 8 ml. 16 ml.	GAIN MODE: INITIAL FINAL	FILTERS: FREQ: 8	LO CUT HZ SLOPE: 18	HI CUT HZ SLOPE: 128
DISPLAY	MODE: AGC FLOAT AMPLIFIER DIRECT	INITIAL GAIN: 42 db	TRIP SENS: 42 db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE:	NUMBERS ON MAG TAPE
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:
SOURCE	TYPE: DYNAMITE VIBROSEIS OTHER	PATTERN: SINGLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:
RECEIVER	TYPE: GEOSPACE 200 10HZ	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:	STAGGER:
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL:	SHOTPOINT INTERVAL: 880/1760	FOLD: 12/6	DIRECTION OF PROGRESSION: NORTH	LEADING GROUP: #1

DIAGRAMS/MISC. INFORMATION:

File # 145 TEST TIME BREAK

LOST 1 HOUR ~~REPLACE~~ REPLACE RADIO HARNESS IN JUB TOWER

SHOTPOINT	TR 10 96		TR 10 96		SHOT			SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH		#1	LINE GROUPS	TR 1-48	TR 49-96	TR 97-144
396	751628	146			110	105	11		41	390-8	408-1				
395		147			110	105	11		33	390-8	406-1				
394		148			110	105	11		25	389-8	404-1				
393	751629	149			110	105	11		17	388-8	402-1				
392		150			110	105	11		9	387-8	400-1				
391		151			110	105	11		1	386-8	398-1				
390		152			110	105	11		1	386-8	398-1				
389		153			110	105	11		41	385-8	396-1				
388		154			110	105	11		33	384-8	395-1				
387		155			110	105	11		25	383-8	394-1				
386		156			110	105	11		17	382-8	393-1				
385		157			110	105	11		9	381-8	392-1				
384		158			110	105	11		49	380-8	391-1				
383		159			110	105	11		41	379-8	390-1				
382		160			110	105	11		33	378-8	389-1				
381		161			110	105	11		25	377-8	388-1				
380		162			110	105	11		17	376-8	387-1				
379		163			110	105	11		9	375-8	386-1				
378		164			110	105	11		1	374-8	385-1				
377		165			110	105	11		41	373-8	384-1				
376		166			110	105	11		33	372-8	383-1				

AT SP# 395 SHOOTING 6 FOLD COVERAGE

File # 145 8 SEC ALLONES

DELAY SHOOTING AIRPLANE NOISE

Groups 374-2 AND 374-3

250' APART TR 79, 80, 81 ARE 11 W/ TR. 78

TR 79, 80, 81 ARE 11 W/ TR. 78

LAND SEISMIC RECORDING LOG



CLIENT: **Husky, NPR OPERATIONS** PROSPECT: **NPR-4** AREA: **NORTH SLOPE** LINE NO: **29**
 PARTY NO: **1173** INST. ENG.: **DAVID BRENNY** DATE: **3 DAY 12 YR 77**

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: B SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: DEC	GAIN CONSTANT: 36	INPUT IMPEDANCE: _____ ohms				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: L96	DATA CHANNEL NOS.: L96 (ON MAG TAPE)			AUXILIARY DATA: _____				
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input checked="" type="checkbox"/> OFF <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: _____	LO CUT HZ SLOPE: 18	H CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 42 db	TRIP SENS: 42 db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	DOWNBREAK <input type="checkbox"/> ON DISPLAY <input type="checkbox"/> UPBREAK		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW: _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	CONNECTION: GEOSPACE 200 10HZ SERIES	RESISTANCE: 450 ohms	NO. OF ELEMENTS: _____	STAGGER: _____	LENGTH: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: 1760'	FOLD: 6	OFFSET GROUP 1: 10450'	OFFSET GROUP 96: 10450'	DIRECTION OF PROGRESSION: NORTH	LEADING GROUP: #1	LATERAL OFFSET: _____

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 96		TR 97 to 192		SHOT		DIR.	CDP SWITCH	SPREAD	REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH					NO.	OFFSET
378	151524	167	151524	167	110	105	11	25	153-8 382-1 378	TR 79, 80, 81	ARE 11 27.78	
375	151524	168	151524	168	110	105	11	17	154-8 381-1	FILE #168 8 SEC ALL ONES TR 79, 80, 81	ARE 11 27.78	
374	151524	169	151524	169	110	105	11	9	155-8 380-1	END OF LINE		

$$\frac{470}{396} = 1.19$$