



# LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: APR-4	AREA: NORTH SLOPE, ALASKA	LINE NO: 036					
PARTY NO: 1195		INST. ENG: BERISCH		DATE: MO 3 DAY 2 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG 3	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (M) <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: 208	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: db	INPUT IMPEDANCE: ohms	(1) (2) (3) (4) (5) (6) (7)	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: 7w 70 76 82 88			AUXILIARY CHANNEL NOS.: 0 1 2 3 4		
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL	FILTERS: FREQ. 8	LO CUT: 18	HI CUT: 72	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS: 42 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: INLINE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: D21-10	PATTERN: INLINE	NO. OF ELEMENTS: LATERAL - 10	INCLINE SPACING: 22'	LATERAL SPACING:	STAGGER:	LENGTH: 380'	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: SEC-PAR	RESISTANCE: 450 ohms	STAGGER:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	FOLD: 1200	DIRECTION OF PROGRESSION:	LEADING GROUP:
	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 800'	OFFSET GROUP 48: 110'	OFFSET GROUP 48/96: 10450				

**DIAGRAMS/MISC. INFORMATION:**

LINE MOVED IN MORNING, WAIT ON SURVEYORS & DRILLS, LAY-OUT LINE #36, AND BEGIN PRODUCTION

SHOTPOINT	TR. 10		TR. 10		SHOT				SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		#96 LINE GROUPS	TR 1-10	TR 48-96
4100	7513	10			1015	105				85	400-1	411-4	415	DAILY TEST F#1-9
4101		11								81	400-1	412-4		TEST TO REC. F#10 TAILING ON LINE 36
4102		12								77	400-1	413-4		
4103		13								73	400-1	414-4		
4104		14								69	400-1	415-4		
4105		15								65	400-1	416-4		
4106		16								61	400-1	417-4		
4107		17								57	400-1	418-4		
4108		18								53	400-1	419-4		
4109		19								49	400-1	420-4		
4110		20								45	400-1	421-4		
4111		21								41	400-1	422-4		
4112		22								37	400-1	423-4		
4113		23								33	401-1	424-4		
4114		24								29	402-1	425-4		
4115		25								25	403-1	426-4		
4116		26								21	404-1	427-4		
4117		27								17	405-1	428-4		

18-3.0 mi

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-1</u>	AREA: <u>North Slope Alaska</u>	LINE NO: <u>036</u>					
	PARTY NO: <u>1195</u>	INST. ENG: <u>Beetsch</u>		DATE: <u>MO 3 DAY 8 YR 77</u>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAT: _____ SEG: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 350 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: <u>228</u>	NO. BYTES IN RECORD ID: <u>2</u>	NO. BYTES PER SCAN: <u>254</u>	RECORD NUMBERS: <u>DEC</u> <input type="checkbox"/> OCT	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>	DATA CHANNEL NOS.: <u>1-96</u> (ON MAG TAPE)		AUXILIARY DATA: <u>TW TB NC NR SPS</u>	AUXILIARY CHANNEL NOS.: <u>0 1 2 3 4</u>				
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____ HZ	HI CUT _____ HZ	NOYCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>24</u> db	TRIP SENS: <u>42</u> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>INLINE</u>	NO. OF POSITIONS: <u>1</u>	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <u>DZD-10</u>	PATTERN: <u>INLINE</u>	NO. OF ELEMENTS: <u>18</u>	INCLINE SPACING: <u>22'</u>	STAGGER: _____	LENGTH: <u>380'</u>	WIDTH: _____	LATERAL OFFSET: _____	
SPREAD	CONNECTION: <u>SEB-PAR</u>	RESISTANCE: <u>450</u> ohms	SHOTPOINT INTERVAL: <u>880'</u>	OFFSET GROUP 48/96: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____		
DIAGRAMS/MISC. INFORMATION:									



CONTINUE ON LINE #36, SHOOTER BECAME SICK - LATE START, 1 JUG TRK DOWN PART OF THE DAY. SHORTMANDED ON JUG CREW

SHOTPOINT	TR. 10		TR. 10		SHOT									SPREAD		REMARKS	CORR. STACK (feet)				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SP	TR. 10	TR. 20	TR. 30		TR. 40				
4110	751/13117	136												49	906-1	429-4	424				
4119		137												45	407-1	430-4					
4210		138												41	408-1	431-4					
4211		139												37	409-1	432-4					
4222		410												33	410-1	433-4					
423		411												29	411-1	434-4					
424		412												25	412-1	435-4					
425		413												21	413-1	436-4					
426		414												17	414-1	437-4					
427		415												13	415-1	438-4					
428		416												9	416-1	439-4					
429		417												5	417-1	440-4					
430		418												37	418-1	441-4	433				
431		419												33	419-1	442-4					
432		50												27	420-1	443-4					
433		51												25	421-1	444-4					
434		52												21	422-1	445-4					
435		53												17	423-1	446-4					
436																					

CDP SWITCH SET FOR SP 436, SW. POS. #13

18-3.0 MC

# LAND SEISMIC RECORDING LOG



	CLIENT: <b>HUSKY</b>	PROSPECT: <b>NPR-4</b>	AREA: <b>NORTH SLOPE, AK</b>	LINE NO.: <b>036</b>	
	PARTY NO.: <b>1195</b>	INST. ENG.: <b>BERESCH</b>	DATE: <b>MO 3 DAY 8 YR 72</b>		
	ODDS EVENTS: <input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>36</b> db
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>	AUXILIARY DATA: (1) <b>TW</b> (2) <b>TB</b> (3) <b>NC</b> (4) <b>NC</b> (5) <b>SPS</b> (6) (7)		AUXILIARY CHANNEL NOS.: <b>0 1 2 3 4</b>	
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>1 HOLE</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	INCLINE SPACING: _____	LATERAL SPACING: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT									SPREAD			REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS #1	#2	#3	HT.	REC.	HT.		REC.		
4136	75113118	55									13	424-1	447-4	483	Dummy Rec F#54					
4137		56									9	425-1	448-4							
4138		57									5	426-1	449-4							
4139		58									1	427-1	450-4							
4410		59									27	428-1	451-4	710						
4411		60									23	429-1	452-4							
4412		61									19	430-1	453-4							
4413		62									15	431-1	454-4							

26-4.5 mi  
24-9.0 mi



# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-4</u>	AREA: <u>NORTH SLOPE, ALASKA</u>	LINE NO.: <u>036</u>	
PARTY NO.: <u>1195</u>		INST. ENG.: <u>BERNSCH</u>		DATE: <u>MO 3 DAY 9 YR 77</u>	
INSTRUMENT [9-TRACK] <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER		<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
NO. BYTES IN HEADER REC.: <u>228</u>		NO. BYTES IN RECORD ID: <u>2</u>		NO. BYTES PER SCAN: <u>254</u>	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: <u>1-96</u> DATA CHANNEL NOS.: <u>1-96</u> (ON MAG TAPE)		AUXILIARY DATA: AUXILIARY CHANNEL NOS.: <u>0 1 2 3 4</u>		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT. GAIN CONSTANT: _____ db INPUT IMPEDANCE: _____ ohms.	
PARAMETER RECORD LENGTH: <u>8</u> sec.		SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms.		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	
DISPLAY MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <u>24</u> db		TRIP SENS.: <u>42</u> db	
CFS I TYPE STACK:		GATE LENGTH:		RECORD REJECTION:	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER <u>NITROCEL</u>		PATTERN: <u>INLINE</u>		NO. OF POSITIONS: <u>1</u>	
RECEIVER TYPE: <u>020-10</u>		PATTERN: <u>INLINE</u>		NO. OF ELEMENTS: <u>18</u>	
CONNECTION: <u>SER-PAR</u>		RESISTANCE: <u>450</u> ohms		STAGGER:	
SPREAD NO. OF GROUPS: <u>96</u>		GROUP INTERVAL: <u>220'</u>		SHOTPOINT INTERVAL: <u>880'</u>	
OFFSET GROUP 1: <u>10450</u>		OFFSET GROUP <u>42</u> : <u>110'</u>		OFFSET GROUP <u>49</u> : <u>110'</u>	
DIAGRAMS/MISC. INFORMATION:		CHG/HOLE: <u>105</u>		HOLE DEPTH: <u>105</u>	
		SWEEP POSITION:		SWEEP START:	
		SWEEP END:		SWEEP LENGTH:	
		SWEEP TAPER:		PHASE COMP:	
		LATERAL SPACING:		LATERAL OFFSET:	
		STAGGER:		LENGTH:	
		LENGTH:		WIDTH:	
		CORR. SCALING:		R.C.U. NORM/ALT SW.	
		INCLINE SPACING: <u>22'</u>		LATERAL SPACING:	
		LENGTH: <u>380</u>		WIDTH:	
		FOLD: <u>1200</u>		DIRECTION OF PROGRESSION: <u>NORTH</u>	
		OFFSET GROUP 48/96: <u>16450</u>		LEADING GROUP:	

SHOTPOINT	TR. No		TR. No		SHOT					SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#96 LINE GROUPS #1	#2		TR 1-36	TR 37-72	TR 73-108	TR 109-144
442	75113118	61			105					49	430-1	453-4	448	DAILY TESTS F# 62-69			
443		61								45	431-1	454-4		TEST TB REC F#70			
444		63								41	432-1	455-4		TEST TB REC F#72			
445		64								37	433-1	456-4					
446		65								33	434-1	457-4					
447		66								29	435-1	458-4					
448		68								25	436-1	459-4		No FIRE, INTERFERENCE ON RADIO			
449		77								21	437-1	460-4					
450		80								17	438-1	461-4					
451		81								49	439-1	462-4	457				
452		82								45	440-1	463-4					
453		83								41	441-1	464-4					
454	75113119	85								37	442-1	465-4		Dummy Rec F# 84			
455		86								33	443-1	466-4					
456		87								29	444-1	467-4					
457		88								25	445-1	468-4					
458		89								21	446-1	469-4					
459		90								17	447-1	470-4					

18-3m

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-4</b>	AREA: <b>NORTH SLOPE ALASKA</b>	LINE NO.: <b>036</b>	
PARTY NO.: <b>1195</b>		INST. ENG.: <b>DEBSCN</b>		DATE: <b>NOV 2 DAY 9 YR 77</b>	
SAME PARAMETERS AS ON SHEET #1					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> GDS <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS X <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER		<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK
	NO. BYTES IN HEADER REC: _____		NO. BYTES PER SCAN: _____		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT. GAIN CONSTANT: _____ db INPUT IMPEDANCE: _____ ohms.
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____				AUXILIARY DATA: _____
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: _____
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS:    _____ FREQ. _____
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DFLLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db		LO CUT HZ SLOPE: _____ FREQ. _____
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____		HI CUT HZ SLOPE: _____ FREQ. _____
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: _____		NOISE REDUCTION: _____
	CHG/ HOLE: _____	HOLE DEPTH: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	NOISE THRESHOLD: _____
RECEIVER	TYPE: _____		PATTERN: _____		NO. OF ELEMENTS: _____
	CONNECTION: _____		RESISTANCE: _____ ohms		STAGGER: _____
SPREAD	NO. OF GROUPS: _____		GROUP INTERVAL: _____		SHOTPOINT INTERVAL: _____
	OFFSET GROUP 1: _____		OFFSET GROUP _____		OFFSET GROUP 48/96: _____

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT										SPREAD		REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	STAGGER	LENGTH	WIDTH	Y1-48	Y1-48 REC		Y1-48	Y1-48 REC		
460	751311A	91			105	105					13	448-1	471-4	457							
461		912									9	449-1	472-4								
462		913									5	450-1	472-8								
463		914									1	451-1	473-4								
464		915									33	452-1	473-8	466							
465		916									29	453-1	474-4								
466		917									25	454-1	474-8								
467		918									21	455-1	475-4								
468		919									17	456-1	475-8								
469		100									13	457-1	476-4								
470		101									9	458-1	476-8								
471		102									5	459-1	477-4								
472		103									1	460-1	477-8								
CHANGE TAPE																					
473	751320	105			105	105					47	462-1	478-8	475	CHANGE TO 800 FOLD, 1260' BETWEEN SP 472-51 473						
474		106									39	464-1	479-8		DUMMY REC F# 104						
475		107									31	466-1	480-8								
476		108									23	468-1	481-8								
477		109									15	470-1	482-8		MISFIRE F# 109, RELEASE OF ARM SWITCH.						

36-6.8 mi

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-4</b>	AREA: <b>NORTH SLOPE</b>	LINE NO: <b>036</b>					
	PARTY NO: <b>1195</b>	INST. ENG: <b>BERTSCH</b>	DATE: <b>NOV 10 1977</b>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 24-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: <b>3</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI		
	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>			AUXILIARY DATA: <b>TW TB NC NC SEP</b>					
	DATA CHANNEL NOS.: <b>1-96</b> (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: <b>0 1 2 3 4</b>					
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>8</b>	LO CUT HZ SLOPE: <b>18</b>	H1 CUT HZ SLOPE: <b>72</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>24</b> db	TRIP SENS: <b>42</b> db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	DOWNBREAK: <input type="checkbox"/> ON DISPLAY	UPBREAK: _____		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW: _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>INLINE</b>	NO. OF POSITIONS: <b>1</b>	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ HOLE: <b>105</b>	HOLE DEPTH: <b>105</b>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: <b>D20-10</b>	PATTERN: <b>NLINE</b>	NO. OF ELEMENTS: <b>18</b>	INCLINE SPACING: <b>22'</b>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: <b>380'</b>	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: <b>SER-PR2</b>	RESISTANCE: <b>450 ohms</b>							
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>1760</b>	FOLD: <b>600</b>	DIRECTION OF PROGRESSION: <b>NORTH</b>	OFFSET GROUP 1: <b>10450</b>	OFFSET GROUP 96: <b>10450</b>	LEADING GROUP: <b>1</b>	



**DIAGRAMS/MISC. INFORMATION:**

**LATE START - LONG DRIVE TO LINE, ROUGH TERRAIN CAUSE DELAYS**

SHOTPOINT #	TR. 1		TR. 2		SHOT		SPREAD		REMARKS	DEAD CORR. STACK GRPS		
	TR. NO.	REC.	TR. NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	#1
478	751	120	1119		105	105	49	472-1	483-8	481		
479		120					41	473-1	484-8			
480		121					33	474-1	485-8			
481		118					25	475-1	486-8			
482		123					12	476-1	487-8			
483		124					9	477-1	488-8			
484		125					43	478-1	489-8	486		
485		126					35	479-1	490-8			
486		127					27	480-1	491-8			
487		128					19	481-1	492-8			
488		129					11	482-1	493-8			
489		130					3	483-1	494-8			

12-4.0 mi

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-1</u>	AREA: <u>NORTH SLOPE ALASKA</u>	LINE NO: <u>036</u>						
PARTY NO: <u>1195</u>		INST. ENG: <u>BERTSCH</u>		DATE: <u>MO 3 DAY 11 YR 77</u>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-40 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> OFS I <input type="checkbox"/> OFS II <input type="checkbox"/> OFS III <input checked="" type="checkbox"/> OFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: <u>228</u>	NO. BYTES IN RECORD ID: <u>2</u>	NO. BYTES PER SCAN: <u>254</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>			AUXILIARY DATA: (1) <u>TW</u> (2) <u>70</u> (3) <u>NC</u> (4) <u>NC</u> (5) <u>SPS</u> (6) _____ (7) _____			AUXILIARY CHANNEL NOS.: <u>0 1 2 2 4</u>			
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>8</u> LO CUT HZ SLOPE <u>18</u> HI CUT HZ SLOPE <u>72</u>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT					
DISPLAY	MODE: <input checked="" type="checkbox"/> AOC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>24</u> db	TRIP SENS: <u>42</u> db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____		NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	E.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>INLINE</u>	NO. OF POSITIONS: <u>1</u>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	TYPE: <u>D20-10</u>	PATTERN: <u>INLINE</u>	NO. OF ELEMENTS: <u>18</u>	INCLINE SPACING: <u>22'</u>	LATERAL SPACING:	STAGGER:	LENGTH: <u>300'</u>	WIDTH:	LATERAL OFFSET:	
SPREAD	CONNECTION: <u>SER-DAP</u>	RESISTANCE: <u>450 ohms</u>	STAGGER:	INCLINE SPACING: <u>22'</u>	LATERAL SPACING:	STAGGER:	LENGTH: <u>300'</u>	WIDTH:	LATERAL OFFSET:	
	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>9760'</u>	FOLD: <u>1200</u>	DIRECTION OF PROGRESSION: <u>NORTH</u>		LEADING GROUP: <u>1</u>			
	OFFSET GROUP 1: <u>10450</u>	OFFSET GROUP 48: <u>110'</u>	OFFSET GROUP 49: <u>110'</u>	OFFSET GROUP 48/96: <u>10450'</u>						

DIAGRAMS/MISC. INFORMATION:

LATE START - DELAY FOR CAMP MOVE - CROSSED LINE, ALSO RILLY TERRAIN

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT								SPREAD		REMARKS:	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SP	HT	TR 48-96			
490	251321	1410			105	105					49	484-1	495-8	493	DAILY TESTS F#130-130 TAPE #151320		
491		1411									41	485-1	496-8		DUMMY REC F#139		
492		1413									33	486-1	497-8		TEST TB REC F#142, 2 SEC		
493		1414									25	487-1	498-8				
494		1415									19	488-1	499-8				
495		1416									9	489-1	500-8				
496		1417									49	490-1	501-8	499			
497		1418									41	491-1	502-8		SURVEYING LAY-OUT ERROR - 9/8 LINE & HOLES		
498		1419									33	492-1	503-8		- CABLE TAKE-OUTS REMAIN CONSISTENT - 220' #10		
499		1450									25	493-1	504-8		- NO UP-HOLES, SP 497-SP 500		
500		1451									29	494-1	505-8				
501		1452									9	495-1	506-8				
502		1453									37	496-1	507-8	493			
503		1454									29	497-1	508-8				
504		1455									21	498-1	509-8				
505		1456									13	499-1	510-8		SHOT FIRED, NO RECORD		

16-5.3 mi

# LAND SEISMIC RECORDING LOG

I

CLIENT: <b>Husky NPR</b>		PROSPECT: <b>NPR-4</b>		AREA: <b>NORTH SCEPTER BASIN</b>		LINE NO: <b>36</b>	
PARTY NO: <b>1195</b>		INST. ENG: <b>BERTSCH &amp; REID</b>		DATE: <b>MO 3 DAY 12 YE 77</b>			
NO. BYTES IN HEADER REC: <b>228</b>		NO. BYTES IN RECORD ID: <b>2</b>		NO. BYTES PER SCAN: <b>254</b>		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
FIELD TRACE NOS.: <b>1-96</b>		DATA CHANNEL NOS.: <b>1-96</b> (ON MAG TAPE)		AUXILIARY DATA: <b>8 7 2 3 4 5 6 7</b>		AUXILIARY CHANNEL NOS.: <b>JW JB NC NC SPS</b>	
RECORD LENGTH: <b>8</b> sec.		SAMPLE RATE: <input checked="" type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec.		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. <b>8</b> LO CUT HZ SLOPE <b>18</b> HI CUT HZ SLOPE <b>12</b> NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
MODE: <input checked="" type="checkbox"/> MAG <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>24</b> db		TRIP SENS: <b>42</b> db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	
TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION: NOISE THRESHOLD: CORR. SCALING: R.C.U. NORM/ALT SW.	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>INLINE</b>		NO. OF POSITIONS: <b>1</b>		LATERAL SPACING: INCLINE SPACING: <b>22'</b>	
CONNECTION: <b>54V - POR</b>		RESISTANCE: <b>450</b> ohms		SWEEP POSITION: SWEEP START: SWEEP END:		SWEEP LENGTH: <b>380</b> SWEEP TAPER: PHASE COMP. LATERAL OFFSET:	
NO. OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>1760</b>		FOLD: <b>600%</b> DIRECTION OF PROGRESSION: <b>NORTH</b>	
OFFSET GROUP 1: <b>10450</b>		OFFSET GROUP 1: <b>110</b>		OFFSET GROUP 2: <b>110</b>		OFFSET GROUP 48/96: <b>10450</b> LEADING GROUP: <b>1</b>	

DIAGRAMS/MISC. INFORMATION:



**TR# 75 1322 LATE START - LONG DRIVE TO FIELD, DELAY TO RE-DRILL SP505, ONE JULY TRK DOWN**

SHOTPOINT	TR. 1 NO. 96		TR. 10		SHOT								SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	*96 LINE GROUPS	TR	TR	TR		TR			
505	175	167									49	500-1	510-8	F# 157 7' 16" DAILY TESTS					
506		168									41	500-1	511-8	TEST TB REC'S. F# 165, 166; RE-SHUNT SP505					
507		169									38	501-1	512-8						
508		170									25	502-1	513-8						
509		171									33	503-1	514-8						
510		172									27	504-1	515-8						
511		173									19	505-1	516-8						
512		174									11	506-1	517-8						
513		175									3	507-1	518-8	TR# 6 DEAD					
514		176									43	508-1	519-8						
515		177									35	509-1	520-8						
516		178									45	510-1	521-8						
517		179									37	511-1	522-8						
518		180									29	512-1	523-8						
519		181									21	513-1	524-8						
520		182									13	514-1	525-8	TR# 1 DEAD - NO FTB					
														SHOT FIRED 2 1/2 HRS LATE					



# LAND SEISMIC RECORDING LOG

I

	CLIENT: <b>Husky NPR</b>	PROSPECT: <b>NPR-4</b>	AREA: <b>NORTH SLOPE</b>	LINE NO: <b>36</b>	
PARTY NO: <b>1195</b>		INST. ENG: <b>REID</b>		DATE: <b>9 DAY 17 77</b>	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		FORMAT: <b>B</b>	
NO. BYTES IN HEADER REC: <b>228</b>		NO. BYTES IN RECORD ID: <b>R</b>		NO. TRACKS: <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
FIELD TRACE NOS.: <b>1-96</b>		NO. BYTES PER SCAN: <b>254</b>		PACKING DENSITY: (10) <input type="checkbox"/> 384 BPI (11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 800 BPI (13) <input type="checkbox"/> 880 BPI (14) <input type="checkbox"/> 960 BPI (15) <input type="checkbox"/> 1040 BPI (16) <input type="checkbox"/> 1120 BPI (17) <input type="checkbox"/> 1200 BPI	
DATA CHANNEL NOS.: <b>1-96</b> (ON MAG TAPE)		AUXILIARY DATA: <b>12 13 14 15 16 17</b>		GAIN CONSTANT: <b>36</b> db	
PARAMETER: RECORD LENGTH: <b>8</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 16 ms		FILTERS: <input checked="" type="checkbox"/> 9 HZ <input type="checkbox"/> 12 HZ <input type="checkbox"/> 15 HZ <input type="checkbox"/> 20 HZ	
DISPLAY: MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>24</b> db		LO CUT HZ SLOPE: <b>18</b>	
CFS I: TYPE STACK:		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		HI CUT HZ SLOPE: <b>22</b>	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>INLINE</b>		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
RECEIVER: TYPE: <b>200-10KZ</b>		NO. OF POSITIONS: <b>1</b>		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	
CONNECTION: <b>201-POR</b>		INLINE SPACING: <b>18</b>		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	
SPREAD: NO. OF GROUPS: <b>96</b>		SWEEP POSITION: <b>105</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT SW	
OFFSET GROUP 1: <b>10450</b>		SWEEP START: <b>105</b>		R.C.U. NORM/ALT SW: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
GROUP INTERVAL: <b>220'</b>		SWEEP END: <b>105</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
OFFSET GROUP 2: <b>110</b>		LATERAL SPACING: <b>18</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
SHOTPOINT INTERVAL: <b>1760</b>		STAGGER: <b>22'</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
OFFSET GROUP 3: <b>110</b>		LENGTH: <b>380'</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
SHOTPOINT INTERVAL: <b>1760</b>		WIDTH: <b>1000'</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
OFFSET GROUP 4: <b>110</b>		PHASE COMP: <b>1</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
SHOTPOINT INTERVAL: <b>1760</b>		LATERAL SPACING: <b>18</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
OFFSET GROUP 5: <b>110</b>		LENGTH: <b>380'</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
SHOTPOINT INTERVAL: <b>1760</b>		WIDTH: <b>1000'</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
OFFSET GROUP 6: <b>110</b>		PHASE COMP: <b>1</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
SHOTPOINT INTERVAL: <b>1760</b>		LATERAL SPACING: <b>18</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
OFFSET GROUP 7: <b>110</b>		LENGTH: <b>380'</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
SHOTPOINT INTERVAL: <b>1760</b>		WIDTH: <b>1000'</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
OFFSET GROUP 8: <b>110</b>		PHASE COMP: <b>1</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
SHOTPOINT INTERVAL: <b>1760</b>		LATERAL SPACING: <b>18</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
OFFSET GROUP 9: <b>110</b>		LENGTH: <b>380'</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
SHOTPOINT INTERVAL: <b>1760</b>		WIDTH: <b>1000'</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	
OFFSET GROUP 10: <b>110</b>		PHASE COMP: <b>1</b>		CORR. SCALING: <input type="checkbox"/> NORM <input type="checkbox"/> ALT	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 26		TR. 27 to 30		TR. 31 to 34		TR. 35 to 38		TR. 39 to 42		TR. 43 to 46		TR. 47 to 50		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.		TR 1-48	TR 49-96	TR 97-144	TR 145-192	
521	751323	183													F# 191 - DUMMY RECORD F# 192 - PARTIAL T.D DAILY TEST # 127 - NO TAPES 751323 TR# 1-9 DEAD 98 PARTIES 1-16 "					
522		184																		
523		185																		
524		186																		
525		187																		
526		188																		
527		189																		
528		200																		
529		201																		
530		202																		
531		203													F# 203 DUMMY RECORD TR# 1-16 DEAD 1-24 DEAD ALL ONES END OF LINE # 36					
532		204																		
		205																		
		206																		