

LAND SEISMIC RECORDING LOG

Page 1 of 2

	CLIENT: HUSKY	PROSPECT: N.P.R. 9	AREA: REC-2	LINE NO: 63					
	PARTY NO: 1186	INST. ENG: F. Carlseius		DATE: MO 3 DAY 21 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input checked="" type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600-BPI PE
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____	HZ SLOPE 18	FREQ. 128	HI CUT _____	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER	INITIAL GAIN: 18 db	TRIP SENS: _____	0 db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	
RECEIVER	CONNECTION:	RESISTANCE: _____ ohms	STAGGER: _____	NO. OF ELEMENTS: Travel 2.5 hrs.	INLINE SPACING:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	OFFSET GROUP 48/96:	DIRECTION OF PROGRESSION: NE	LEADING GROUP: 96		
	OFFSET GROUP 1:	OFFSET GROUP _____	OFFSET GROUP _____						

DIAGRAMS/MISC. INFORMATION: **Tape # 672706 - Files 1-8 Daily Justo - File # 9 - Pulse Justo - File # 10 - Test T.B.**



High frequency noise on spread - waited for camp to move further off line. Still getting noise.

SHOTPOINT NO.	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD				REMARKS:	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SET UP		TR 1-48 REC	TR 49-96 REC
6015	672706	11			1.10	105	1					1			
6014		12					2								
6013		13					3								
6012		14					4								
6011		15					5								
6010		16					6								
6009		17					7								
6008		18					8					2			
6007		19					9								
6006		20					10								
6005		21					11								
6004		22					12						3	Moved up to help find hole at SP # 607	
6003		23					13								
6002		24					14								
6001		25				1.05	15								
6000		26				0.95	16						4	NOTE! SP# 600 95'	
5999		27				1.05	17								
5998	672706	28			1.10	105	18								

Tape change.

LAND SEISMIC RECORDING LOG

Page 2 of 2.



	CLIENT: HUSKY	PROSPECT: N.P.R. 4	AREA: REC. 2	LINE NO: 63	
	PARTY NO: 1186	INST. ENG: F. Carstens		DATE: 3 DAY 25 YR 77	
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input checked="" type="checkbox"/> 9 TRACK FORMAT: B <input type="checkbox"/> GAPPED PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> EVENS <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> 21 TRACK SEG <input type="checkbox"/> UNGAPPED (L) <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 1600 BPI		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT GAIN CONSTANT: 36 db INPUT IMPEDANCE: 5000 ohms. (1) (2) (3) (4) (5) (6) (7)		
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	AUXILIARY DATA: _____	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____		AUXILIARY CHANNEL NOS.: _____		
PARAMETER	RECORD LENGTH: 8.20 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> 1 IF <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL FILTERS: FREQ: 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 18 NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER INITIAL GAIN: 24 db	TRIP SENS: 0 db	POLARITY CONVENTION: PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____
	CHG/ HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____
RECEIVER	TYPE: Geo-Space 10D.	PATTERN: _____	NO. OF ELEMENTS: 18	INLINE SPACING: _____	LATERAL SPACING: _____
	CONNECTION: SERIES.	RESISTANCE: 770 ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 600%	DIRECTION OF PROGRESSION: NE
	OFFSET GROUP 1: _____	OFFSET GROUP: _____	OFFSET GROUP: _____	OFFSET GROUP 48/96: _____	LEADING GROUP: 96

DIAGRAMS/MISC. INFORMATION: Tape #672-711

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				DIR.	CDP SWITCH	SPREAD	REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET					TR 1-24	TR 25-48	TR 49-96	TR 100-120	
530	672711	145			110	105	16			1/27	20 seconds	3					
529		146					17			1/35	20 seconds		8-11-16				
528		147					18			1/43	20 seconds		51-56				
527		148					19			1/3	20 seconds	4	7-83				
526		149					20			1/11	20 seconds		75-92				
525		150					21			1/19	8 "		67-84				
524		151					22	150 SW		1/27			59-76				
523		152					23			1/35			51-68				
522		153					24			1/43			43-60				
521		154					25			1/3		5	21-26-58				
520	672711	155			110	105	26	100 W		1/11	8 seconds		13-18-50				

LAND SEISMIC RECORDING LOG

Page 1.

	CLIENT: HUSKY	PROSPECT: N.P.R. 4	AREA: REC 2	LINE NO: 63								
	PARTY NO: 1186	INST. ENG: F. Carlsenius		DATE: MO 3 DAY 26 YR 77								
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 800 BPI	<input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI			
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 5000 ohms.	(1)	(2)	(3)	(4)	(5)	(6)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:				AUXILIARY DATA:				AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> IFP	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	FREQ. 128	HI CUT HZ SLOPE 18	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS: 0 db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE:	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	<input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR SCALING:	R.C.U. NORM./ALT SW.					
SOURCE	<input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
	CHG/ HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:				
RECEIVER	TYPE:	PATTERN: 1	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
	CONNECTION:	RESISTANCE: 770 ohms										
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 600%	DIRECTION OF PROGRESSION: NE	LEADING GROUP: 96						

DIAGRAMS/MISC. INFORMATION: **Tape # 672712 File # 171-173 Daily Test (Balance) File # 174 Pulse Test Travel-2 hrs. File # 156-165 N.G. Tape 672711 #175 Test T.O. Total=11.5 hrs.**

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				SPREAD			REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48 REC.
519	672712	176			110	105	17			1/1		1		
518		177					12			1/9				
517		178					13	50 SW		1/17				
516		179					14			1/25	3 parity errors			
515		180					15	200 NE		1/3		2		
514		181					16			1/11				
513		182					17	50 SW 300 E		1/19				
512		183					18			1/27				
511		184					19			1/35				
510		185					20			1/43				
509		186					21			1/3		3		
508		187					22	450 E		1/11	1 parity error			
507		188					23	310 NE		1/19				
506		189					24			1/27				
505		190					25			1/35				
504	672712	191			110	105	26			1/43				

LAND SEISMIC RECORDING LOG

Page 1 of 2

CLIENT: HUSKY	PROSPECT: N.P.R. 4	AREA: REC-2	LINE NO: 63
PARTY NO: 1186	INST. ENG: F. Carlsenius	DATE: MO 3 DAY 27 YR 77	

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	POP MAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 5000 ohms		

CONFIGURATION (MAG TAPE)	AUXILIARY DATA:
FIELD TRACE NOS.:	AUXILIARY CHANNEL NOS.:
DATA CHANNEL NOS.:	(ON MAG TAPE)

PARAMETER	RECORD LENGTH: 20.58 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 18	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS.: 0 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/HOLE: 110 HOLE DEPTH: 105'	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:		

RECEIVER	TYPE: Geo-space 100	PATTERN:	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: Series	RESISTANCE: 770 ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			

SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 600%	DIRECTION OF PROGRESSION: NE	LEADING GROUP: 96
--------	--------------------------	-----------------------------	----------------------------------	-------------------	-------------------------------------	--------------------------

DIAGRAMS/MISC. INFORMATION: **Type # 672712 - File # 192 - 199 Daily Tests - File # 200 Test T.B. Travel = 3 hrs. 672713 - File # 201 1st Record. TOTAL = 14.5 hrs.**

SHOTPOINT	TR. 1 to		TR. 2 to		SHOT			SPREAD		REMARKS	CORR STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		COP SWITCH	LINE GROUPS	TR 1	TR 2	TR 3	TR 4
503	672713	201			110	105	1			1/3	Offset 110' SW					
504		202					2			1/11						
501		203					3			1/19						
500		204					4			1/27						
499		205				105	5			1/35						
498		206				0.95	6			1/43	SP# 498 95'					
497		207				1.05	7			1/3		2				
496		208					8			1/11						
495		209					9	140 SW		1/19						
494		210					10			1/27						
493		211					11			1/35						
492	672713	212			110	105	12			1/43						
48 group Tail-spread. E.O.L. # 63.																

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: N.P.R. 4	AREA: REC-2	LINE NO: 63					
	PARTY NO: 1186	INST. ENG: F. Carlsenius		DATE: MO 3 DAY 23 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input checked="" type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI	
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: 80	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 5000 ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: _____			AUXILIARY CHANNEL NOS.: _____		
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 128	HI CUT HZ SLOPE 18	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 & 24 db	TRIP SENS: 0 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/>	NUMBERS ON MAG TAPE: <input type="checkbox"/>	DOWNBREAK ON DISPLAY: <input type="checkbox"/>	UPBREAK ON DISPLAY: <input type="checkbox"/>	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: Geo-Space 10D	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	CONNECTION: Series	RESISTANCE: 770 ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 600%	DIRECTION OF PROGRESSION: N.E.	LEADING GROUP: 96			

DIAGRAMS/MISC. INFORMATION: **Tape #672708 - File #62-69 Daily Tests File # 70 N.G. Travel = 3 hours. Total = 13.5 hours.**
File # 71 Pulse Test
File # 72 Test T-B.

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD		REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	SET UP	TR 1-24	TR 25-48	TR 49-96
578	672708	73			110	105	11				1/3	1				
577		74					2				1/11					
576		75					3				1/19					
575		76					4				1/27					
574		77					5				1/35					
573		78					6				1/43					
572		79					7				1/3	2				
571		80					8				1/11					
570		81					9				1/19					
569		82					10				1/27					
568		83					11				1/35					
567		84					12				1/43					
566		85					13				1/3	3				
565		86					14				1/11					
564	672708	87			110	105	15				1/19					

REPLACED CABLE WITH ZOPEN IN IT.
 Open traces or weak or noisy 3, 11, 16
 3, 8, 94
 43, 81
 29, 49
 21-41
 13-33
 5-25
 77-95
 9-87
 1-40-79 Blew-out
 32-71
 24-63 Check on depth? Blew-out.
 16, 55-95 (in 3 diff cables)
 8-47-87

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: N.P.R. 4	AREA: REC 2	LINE NO: 63						
	PARTY NO: 1186	INST. ENG: F. Garkenius		DATE: 3 24 77						
INSTRUMENT [9-TRACK]	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENTS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 5000 ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (7) _____			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: _____			AUXILIARY CHANNEL NOS.: _____			
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> TRIP	<input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18	FREQ. 128 HI CUT HZ SLOPE 18	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT	AMPLIFIER: <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS.: 0 db	RECORD REJECTION: _____	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEDPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW. _____				
SOURCE	<input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	TYPE: Geo-space 100	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
SPREAD	CONNECTION: SERIES	RESISTANCE: 770 ohms	CHG/HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP. _____
	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 600%	OFFSET GROUP: _____	LEADING GROUP: 96	DIRECTION OF PROGRESSION: NE			

DIAGRAMS/MISC. INFORMATION: **Tape 672709 File # 92-99 Daily Inst**
File # 100 - Pulse Test
File # 101 - Test T.B.

Travel = 3.5
Total = 13.5

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT		SPREAD		REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	SET UP	TR 1-41	TR 41-73
5160	672709	1102			110	105	11			1/3		1	Replaced 1 cable - Foxes biting into them.		
5159		1103					12			1/11	50 SE/50 W offset		open traces 15, 89		
5158		1104					13			1/19			81		
5157		1105					14			1/27			73		
5156		1106					15			1/35			65-94		
5155		1107					16			1/1		2	57, 86, 91		
5154		1108					17			1/19			5, 10, 40, 42		
5153		1109					18			1/19			2, 32, 34		
5152		1110					19			1/25			26, 24		
5151		1111					20			1/33			16, 18, 53		
5150		1112					21			1/5		3	8, 10, 45		
5149		1113					22			1/13			2, 44		
5148		1114					23			1/21			36		
5147	672709	1115			110	105	24			1/29			28, 96		
													20, 88		

LAND SEISMIC RECORDING LOG

Page 1 of 2

	CLIENT: HUSKY	PROSPECT: N.P.R. 4	AREA: REC. 2	LINE NO: 63					
	PARTY NO: 1186	INST. ENG: F. Carlsenius		DATE: MO 3 DAY 25 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 400 BPI	(H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 5000 ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: 8, 20 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ 8	LO CUT HZ SLOPE 18	FREQ 128	HI CUT HZ SLOPE 18	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AOC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS: 0 db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY	
CFS 1	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:		P.C.U. NORM./ALT SW.	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: Geo-space 100	PATTERN:	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 600%	DIRECTION OF PROGRESSION: NE	LEADING GROUP: 96			

DIAGRAMS/MISC. INFORMATION: **Tape # 672710 File # 118 - 126 Daily Tests File # 127 N-6 - Travel 4.5 hours**
File # 128 - Pulse Test Total = 15.5 hours.
File # 129 - Test T-6.

SHOTPOINT	TR. to		TR. to		SHOT				SPREAD		REMARKS:	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH		LINE GROUPS	HT.	REC.	HT.	REC.	
543	672710	130	17	22	23	26	27	29	30	32	1	50	SW	1/3	4, 11, 16, 21, 92		
544		131									2	110	SW	1/11	38, 13, 84		
543		132									3			5			
542		133									4			2-75			
541		134									5			67			
540		135									6			59-89-92			
539		136									7			49			
538		137									8			41, 76			
537		138									9			33-68			
536		139									10			25-60-96			
535		140									10.5			17-52-88			
534		141									0.95			9-80-44	NOTE #534 95'		
533		142									1.05			1-91-96			
532		143									14			88-83			
531	672710	144									11.0			119	First 20 second record.		