



LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY-NPR OPERATIONS	PROSPECT: NPR-4	AREA: UMIAT-NORTH SLOPE-ALASKA	LINE NO: 68 E					
	PARTY NO: 1184	INST. ENG: VIC DONALD	REC. HOUS - 12	DATE: MO 1 DAY 23 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 2-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (H1) <input type="checkbox"/> 712 BPI	<input type="checkbox"/> 800 BPI <input type="checkbox"/> 1400 BPI
	NO. BYTES IN HEADER REC: 2 2 8	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 2 5 4	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: ohms	(3)	(6)	(7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: TW T.B. (3) S.P.S.					
	DATA CHANNEL NOS.: 1-96 G-101 (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: 1 2 3 4 5					
PARAMETER	RECORD LENGTH: 9 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 120	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
DISPLAY R.A.W.	MODE: <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 12 db	TRIP SENS: 4.8 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: 105 104	HOLE DEPTH: 105 FT	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	
RECEIVER	TYPE: GEO SPACE 200-1072	PATTERN: INLINE	NO. OF ELEMENTS: 18	INCLINE SPACING: 25	LATERAL SPACING:	STAGGER:	LENGTH: 425	WIDTH:	LATERAL OFFSET:
	CONNECTION: SERIES-PARALLEL	RESISTANCE: ohms							
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 880	FOLD: 12 F	DIRECTION OF PROGRESSION: W	OFFSET GROUP 1: 10450	OFFSET GROUP 96: 10450	LEADING GROUP: 96	

DIAGRAMS/MISC. INFORMATION:
⁴⁷ EAST ⁴⁴ & ⁴⁹ WEST - NO GAP AT SP.

SHOTPOINT	TR. 1 to 96		TR. 10		SHOT		SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR. 48	TR. 96
600	523261	0114			10.5	10.5	1	1	1/13 BEEN 1/2 → 1-48		
601		0115			10.5	10.5			1/5 5-101		
602		0116			10.5	10.5			1/9 9-105		
603		0117			10.5	10.5			1/13 13-109		
604		0119			10.5	10.5			1/17 17-113 - GAP 94-96		
605		0220			10.5	10.5			1/21 21-117 - GAP 90-96		
606		0231			10.5	10.5	170	5	1/25 25-121 GA 80-96		
607		0222			10.5	10.5			1/29		
608		0233			10.5	10.5			1/33		
609		0234			10.5	10.5			1/37		
610	SKIP DUE TO UNACCESSIBLE										
	TYPE CHANGE										



LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY-NPR-OR	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 68E	
PARTY NO: 1184		INST. ENG: DONALD RAINER		DATE: MO 1 DAY 24 YR 77	
TOTAL REC. HOURS: 14 1/2		REC. HAS: 11 1/2		TRAVEL TIME: 3	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS <input checked="" type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER		FORMAT: B <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254	
FIELD TRACE NOS.: 1-96		AUXILIARY DATA: TR 1 TR 2 TR 3 TR 4 TR 5		GAIN CONSTANT: 36 db	
DATA CHANNEL NOS.: 6-101		AUXILIARY CHANNEL NOS.: 1 2 3 4 5		INPUT IMPEDANCE: _____ ohms	
RECORD LENGTH: 8 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms		FILTERS: FREQ. 8 LO CUT HZ 18 HI CUT HZ 128	
MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPERIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
TYPE STACK: _____		GATE LENGTH: _____		CORR. SCALING: _____	
SOURCE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE HOLE		NO. OF POSITIONS: 1	
CHG/HOLE: 100/65		HOLE DEPTH: 105		SWEEP POSITION: _____	
RECEIVER: GEOSPACE-20D-10 Hz		PATTERN: IN LINE		NO. OF ELEMENTS: 18	
CONNECTION: SERIES PARALLEL		RESISTANCE: _____ ohms		STAGGER: _____	
NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'	
OFFSET GROUP 1: 10450'		OFFSET GROUP 48: 110'		OFFSET GROUP 96: 110'	
SPREAD: _____		GROUP INTERVAL: _____		SHOTPOINT INTERVAL: _____	
OFFSET GROUP 1: _____		OFFSET GROUP _____: _____		OFFSET GROUP _____: _____	

DIAGRAMS/MISC INFORMATION:

SHOTPOINT	TR. 1 to 96		TR. 10 to 19		TR. 20 to 29		TR. 30 to 39		TR. 40 to 49		TR. 50 to 59		TR. 60 to 69		TR. 70 to 79		TR. 80 to 89		TR. 90 to 96		CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	
611	23	139																					
612		140																					
613		141																					
614		142																					
615		143																					
616		144						150 N															
617		145						150 N															
618		146						500 N															

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY-NPR-OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE, ALASKA	LINE NO: 68E	
PARTY NO: 1184		INST. ENG. DONALD BRINER		DATE: MO 1 DAY 25 YR 1979	
INSTRUMENT (9-TRACK) <input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		ODDS EVENS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-96 DATA CHANNEL NOS.: 6-101		AUXILIARY DATA: TW 7B (3) (4) 505 (6) (7)		AUXILIARY CHANNEL NOS.: 1 2 3 4 5	
PARAMETER RECORD LENGTH: 8 sec.		SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec. <input type="checkbox"/> 2 sec. <input type="checkbox"/> 1 sec.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	
DISPLAY MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT		INITIAL GAIN: 36 db		TRIP SENS.: 36 db	
CFS I TYPE STACK:		GATE LENGTH:		RECORD REJECTION:	
SOURCE <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE HOLE		NO. OF POSITIONS: 1	
RECEIVER Type: GEOSPACE 200-10M		PATTERN: INLINE		NO. OF ELEMENTS: 18	
SPREAD NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'	
DIAGRAMS/MISC. INFORMATION 464 220' 444 449 450		CHG/ HOLE: 105/105'		HOLE DEPTH: 105'	
CONNECTION: SERIES - PARALLEL		RESISTANCE:		STAGGER:	
OFFSET GROUP 1: 10450'		OFFSET GROUP 48: 110'		OFFSET GROUP 49: 110'	
NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:	
POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE:		NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
FILTERS: FREQ. 8 LO CUT HZ SLOPE 18		FREQ. 128 HI CUT HZ SLOPE 12		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
LATERAL SPACING:		STAGGER:		LENGTH:	
INCLINE SPACING: 25		LATERAL SPACING:		WIDTH:	
LENGTH: 425'		SWEEP LENGTH:		SWEEP TAPER:	
DIRECTION OF PROGRESSION: WEST		SWEEP START:		SWEEP END:	
LEADING GROUP: 96		SWEEP POSITION:		PHASE COMP:	

SHOTPOINT	TR. 1		TR. 2		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	SEC.	REEL NO.	SEC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	TR 1-24	TR 25-96
619	252	362	3058		105	105	1	300	S	1/5	5-101		
620		358			105	105	1	100	S	1/9	9-105		
621		369			105	105	1			1/13	13-109		
622		361			105	106	1			1/17	17-113		
T A P E C H A N G E													
RECORDED 47-57 TESTS													
TR 25 DEAD													
TR 21 "													
TR 17 "													
TR 13 " N.R. - BAD TAPE - SYNC ERROR - HIGH PAPER													



LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY-NPR-OPERATION		PROSPECT: NPR-4		AREA: NORTH SLOPE ALASKA		LINE NO.: 68E		
	PARTY NO.: 1184		INST. ENG.: DONALD I BRINER		RECORDING NOTES: 12/2		DATE: 1 DAY 25 1977		
INSTRUMENT (9-TRACK)		NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 6-101		AUXILIARY DATA: FW 9P		AUXILIARY CHANNEL NOS.: 1 2 3 4 5	
PARAMETER		RECORD LENGTH: 8 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. 8 LO CUT HZ SLOPE 18	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		TRIP SENS: 36 db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE HOLE		NO. OF POSITIONS: 1		INLINE SPACING:	
RECEIVER		TYPE: GEOSPAC 700-40Hz		PATTERN: INLINE		NO. OF ELEMENTS: 18		INCLINE SPACING: 25	
SPREAD		NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'		FOLD: 12 F	
		OFFSET GROUP 1: 10450'		OFFSET GROUP 4: 110'		OFFSET GROUP 19: 110'		OFFSET GROUP 48/96:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 10		TR. 20		SHOT		SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS
623	523260	67			105	106				1/21	21-117	TR#9 DEAD
624		68			105	105				1/25	25-121	TR#5 DEAD
625		69			105	105				1/29	29-125	TR#1 DEAD
626		70			105	105				1/37	33-129	
627		71			105	105				1/37	37-133	
628		72			105	105	50	N		1/41	41-137	
										NO. WAIT ON DRILLS		


LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY-NPR-OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 68E					
	PARTY NO: 1184	INST. ENG: DONALD BRINER	RECORDING HOURS: 10 A.M. 3	DATE: MO 1 DAY 26 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IX	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: 5	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: (3) _____ (5) _____ (6) _____ (7) _____			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96		AUXILIARY DATA: ZW 78 525		AUXILIARY CHANNEL NOS.: 1 2 3 4 5				
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ 18	HIGH CUT HZ SLOPE 172	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: 36 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CRG/ HOLE: 10516 HOLE DEPTH: 105'	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: GEOSPACE 20D-10M	PATTERN: IN LINE	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: SERIES-PARALLEL	RESISTANCE: _____ ohms	STAGGER:	LENGTH: 425'	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 12 F	DIRECTION OF PROGRESSION: WEST				
	OFFSET GROUP 1: 10450'	OFFSET GROUP 48: 110'	OFFSET GROUP 49: 110'	OFFSET GROUP 96: 10450'	LEADING GROUP: 96				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT							DIR.	CDP SWITCH	SPREAD	REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	LINE GROUPS	TR. 48					TR. 48-96	TR. 48-96	TR. 48-96	
1239	523264	145										1/9	9-104	NEW TAPE REC# 72-80 TEST T.B.S. DAILY TEST					
														REC# 91-96 SKIPPED ON TAPE - REC# 89-94 TEST T.B.S.					
														NO SHUT DOWN AND WENT TO CAMP - BAD PARITY ERRORS					

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY-NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 68 E						
	PARTY NO: 1184	INST. ENG: DONALD	RECORDING HRS: 12	DATE: 1 DAY 27 1977						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI			
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: (6) (7)				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96		AUXILIARY DATA: HW 75		AUXILIARY CHANNEL NOS.: 1 2 3 4 5					
PARAMETER	RECORD LENGTH: 8 sec	SAMPLE RATE: <input type="checkbox"/> 1 sec <input type="checkbox"/> 4 sec	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE: 18	FREQ. 128 HI CUT HZ SLOPE: 42	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input checked="" type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> ACC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 42 db	TRIP SENS: 36 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH: 25'	WIDTH: 425'	LATERAL OFFSET:	
RECEIVER	CONNECTION: SERIES PARALLEL	RESISTANCE: ohms	CHG. HOLE: 15/15	HOLE DEPTH: 105'	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 200'	SHOTPOINT INTERVAL: 880'	OFFSET GROUP: 110'	OFFSET GROUP #/96: 10450'	FOLD: 12 F	DIRECTION OF PROGRESSION: WEST	LEADING GROUP: 96		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. No		TR. No		SHOT								CDP SWITCH	LINE GROUPS	REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	NO.	NO.	NO.				NO.			
630	523264	100			105	105	130		E	1/5	1-96	10	REC# 96-99 TESTS						
631		11011			105	105	130			1/5	5-100		TAP #2 HOOKED TO CABLE IN SERIES. JAGGAMP WEST OF SDC 26 BEAD						
632		1102			105	105				1/9	9-104		ON ALL SHOTS - NOT A LONG BOX						
633		1103			105	105				1/3	13-108		I.T.B.						
634		1104			105	105				1/7	17-112		BAD REC - A1-A3-S1 FAULTS - PARTY						
635		1106			110	240				1/21	21-116		-2 HOLE - 40' APART - REC# 105 - TEST 708						
636		1107			105	105				1/25	25-120								
637		1108			105	105				1/29	29-124								
638		1109			105	105				1/33	33-128								
639		1110			105	105				1/37	37-132		REC# 111 - TEST TB						
	TAP #2 HOOKED TO CABLE IN SERIES																		

LAND SEISMIC RECORDING LOG



		CLIENT: MUSKY-NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE, ALASKA	LINE NO.: 68E				
PARTY NO.: 1184		INST. ENG.: DONALD	RECORDING NRS: 12		DATE: 1 29 77	NO. 1 DAY 29 YR 77			
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: 8	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(11) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1500 BPI
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: 11W 12R (3) 13S 14S (6) 15			AUXILIARY CHANNEL NOS.: 1 2 3 4 5		
	DATA CHANNEL NOS.: 6-101 (ON MAG TAPE)			FILTERS: 8 LO CUT HZ SLOPE 18 FREQ. 128 H1 CUT HZ SLOPE 172 NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE } NUMBERS ON ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY		
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	TRIP SENS: 36 db	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	RECORD REJECTION: _____	CORR. SCALING: _____		R.C.U. NORM/ALT SW. _____			
CFS I	TYPE STACK: RAW	GATE LENGTH: _____	NOISE REDUCTION: _____		NOISE THRESHOLD: _____		CORR. SCALING: _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/HOLE: 105/63	HOLE DEPTH: 105'	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: GEOSPAC 200-10H	PATTERN: INLINE	NO. OF ELEMENTS: 18	INCLINE SPACING: 25'	LATERAL SPACING: _____	STAGGER: _____	LENGTH: 425'	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	CONNECTION: SERIES PARALLEL	RESISTANCE: _____ ohms	STAGGER: _____	INCLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 12+	DIRECTION OF PROGRESSION: WEST	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 12+
OFFSET GROUP 1: 10450'	OFFSET GROUP 18: 110'	OFFSET GROUP 49: 110'	OFFSET GROUP 96: 10450'	LEADING GROUP: 96					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. TO		TR. TO		SHOT				SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	HT.
640	523265	1114			105	105				15	5-100		
641		1115			105	105				19	9-104		
642		1116			105	105				13	13-108		
643		1117			105	105				17	17-102		
644		1118			105	105				21	21-116		
645		1119			105	105				25	25-120		
646		1120			105	105				29	29-124		
647		1121			105	105		110	E	33	33-128		
648		1122			105	105				37	37-132		
649		1124			105	105				5	5-100		
650		1125			105	105				9	9-104		
651		1126			105	105		60'S		13	13-108		
652		1127			105	105				17	17-112		
653		1128			105	105				21	21-117		
654		1129			105	105				25	25-121		
655		1130			105	105				29	29-125		

LAND SEISMIC RECORDING LOG

PAGE 1 OF 3


	CLIENT: USKY-NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 68E					
	PARTY NO: 1184	INST. ENG: DONALD IRWIN	RECORDING NRS. 14 1/2	TT: 4	DATE: MO 1 DAY 28 YR 74				
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (M1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCG	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: FW 7B					
	DATA CHANNEL NOS.: 6-101 (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: 1 2 3 4 5					
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 12	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: 36 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE } NUMBERS ON MAG. TAPE <input type="checkbox"/> UPBREAK } ON DISPLAY				
CFS I	TYPE STACK: RAW	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____ R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG/ HOLE: 105/65	HOLE DEPTH: 105'	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
RECEIVER	TYPE: GEOSPACE 200-10Kz	PATTERN: INLINE	NO. OF ELEMENTS: 18	INCLINE SPACING: _____	LENGTH: 25'	LATERAL SPACING: _____	WIDTH: _____	LATERAL OFFSET: _____	
	CONNECTION: SERIES PARALLEL	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: 425'					
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	POLO: 12 f	DIRECTION OF PROGRESSION: WEST				
	OFFSET GROUP 1: 10450'	OFFSET GROUP 48: 110'	OFFSET GROUP 96: 110'	OFFSET GROUP 10450': 10450'	LEADING GROUP: 96				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR-48	TR-48	TR-48	TR-48
656	533266	138	17	2223	20	27	20	30	35	37	1/9	9/104				
657		138			2155	160					1/3	13-108				
					TAPES CHANGED											

LAND SEISMIC RECORDING LOG

PAGE 2 of 3


	CLIENT: MUSKY NPR-OPER.	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 68E					
	PARTY NO: 1184	INST. ENG: DONALD BRINER	RECORDING HRS: 14 1/2	DATE: MO. 1 DAY 28 YR 1977					
INSTRUMENT [9-TRACK]	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI	
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: TR 98			AUXILIARY CHANNEL NOS.: 1 2 3 4 5		
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: 8 Hz	LO CUT: 18 Hz	HI CUT: 172 Hz	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> OFFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: 36 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK: _____	DATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	E.C.V. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: GEOSPACE 20 D-10N	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 25	LATERAL SPACING: _____	STAGGER: _____	LENGTH: 425	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 12 f	DIRECTION OF PROGRESSION: WEST	OFFSET GROUP 1: 10450	OFFSET GROUP 96: 10450'	LEADING GROUP: 96	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. to		TR. to		SHOT			DIR.	CDP SWITCH	SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.			OFFSET	LINE GROUPS		TR 1-48	TR 49-96	TR 1-48	TR 49-96
658	1252	2616	140	140	105	105			Y17	17-112	REC# 139 DUMMY REC.					
659		141			105	105			Y21	21-116	-9 PARITY ERRORS					
660		142			105	105			Y25	25-120						
661		143			105	105			Y29	29-124						
662		144			105	105			Y33	33-128	-NOISE CAUSED BY AIRPLANE					
663		145			105	105			Y37	37-132	REC# 145 TEST TR.					
664		147			105	105			Y41	41-136						
665		148			105	105			Y9	9-104	58-1 AND 58-3 DEAD					
666		149			105	105			Y13	13-108	(CABLE) (CABLE)					
667		150			105	105			Y17	17-112						
668		151			105	105	150 N		Y21	21-116						
669		152			105	105			Y25	25-120	INTEGRAL TR.					
670		153			105	105			Y29	29-124	REC# 153-155 - TEST TR. NEW TONE BOX					
671		154			105	105			Y33	33-128	*N SHORTERS RECORDING TRUCK					
672		158			105	105			Y37	37-132						
673		159			105	105			Y17	17-112						
674		160			105	105			Y21	21-116						
675		161			105	105			Y25	25-120						
676		162			105	105			Y29	29-124						

TANK C/NANOE

LAND SEISMIC RECORDING LOG



	CLIENT: WUSKY NPR OPER.	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA 68E	LINE NO.: 68E					
	PARTY NO.: 1184	INST. ENG.: DONALD	RECORDING NRS. 14 1/2	DATE: MO. 1 DAY 28 YEAR 77					
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 800 BPI	(11) <input type="checkbox"/> 732 BPI <input type="checkbox"/> 1600 BPI
(9-TRACK)	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96				AUXILIARY DATA:				
	DATA CHANNEL NOS.: 6-104 1-96 (ON MAG TAPE)				AUXILIARY CHANNEL NOS.:				
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TRIP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. 5 LO CUT HZ SLOPE 18		FREQ. 128 HZ CUT SLOPE 72		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> XGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER DIRECT	INITIAL GAIN: _____ db	TRIP SENS.: 36 db	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: _____		<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	<input type="checkbox"/> NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK UPBREAK ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:		R.C.U. NORM/ALT SW.	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CHG/ HOLE: 10516	HOLE DEPTH: 105'	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.
RECEIVER	TYPE: GEOSPAC 200 100A	PATTERN: INLINE	NO. OF ELEMENTS: 18	INCLINE SPACING: 25	LATERAL SPACING:	STAGGER:	LENGTH: 425	WIDTH:	LATERAL OFFSET:
	CONNECTION: SERIES PARALLEL	RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 12f	DIRECTION OF PROGRESSION: WEST		OFFSET GROUP 1: 10450'	OFFSET GROUP 96: 10450'	LEADING GROUP: 96

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT								SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SET UP	TR. 1-24	TR. 25-34			
678	52326	164	323267		105	105					33-128	37					
679		166			105	105					37-132	37					

REMARKS: **REC # 163 DUMMY REC**

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY-NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 68E	
PARTY NO: 1184		INST. ENG: DONALD BRINER RECORDING		DATE: T.T. 5 HRS M.H. 9 HRS	
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254	
INSTRUMENT <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS <input checked="" type="checkbox"/> DFS <input type="checkbox"/> OTHER		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-96 DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)		AUXILIARY DATA: (1) 7W (2) 7R (3) (4) 5205 (6) (7)		AUXILIARY CHANNEL NOS.: 1 2 3 4 5	
PARAMETER RECORD LENGTH: 8 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	
DISPLAY MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		TRIP SENS: 36 db	
CFS I TYPE STACK: MAN		GATE LENGTH: _____		RECORD REJECTION: _____	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE HOLE		NO. OF POSITIONS: 1	
		CHG/ HOLE: 105/105'		HOLE DEPTH: 105'	
RECEIVER TYPE: GEOSPAC 200		PATTERN: INLINE		NO. OF ELEMENTS: 12	
CONNECTION: SERIES PARALLEL		RESISTANCE: _____ ohms		STAGGER: _____	
SPREAD NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'	
OFFSET GROUP 1: 10450'		OFFSET GROUP 48: 110'		OFFSET GROUP 49: 110'	
				FOLD: 12F	
				DIRECTION OF PROGRESSION: WEST	
				LEADING GROUP: 96	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT			SPREAD			REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-48	TR 49-96
679	5232167	172			105	105				15	SP-67 → SP-91			
680		173			105	105		1010	S	19	SP-68 → SP-92			
681		174			105	105				13	SP-69 → SP-93			
682		175			105	105				17	SP-70 → SP-94			
683		176			105	105				21	SP-71 → SP-95			
684		177			105	105				25	SP-72 → SP-96			
685		178			105	105				29	SP-73 → SP-97			
686		179			105	105				33	SP-74 → SP-98			
687		180			105	105				37	SP-75 → SP-99			
688		181			105	105				41	SP-76 → SP-100			
689		182			105	105				45	SP-77 → SP-01			
END OF DAY														

LAND SEISMIC RECORDING LOG

HUSKY

CLIENT: HUSKY-NPR OPER.		PROSPECT: NPR-4		AREA: NORTH SLOPE ALASKA			LINE NO.: 68E		
PARTY NO.: 1184		INST. ENG.: DONALD BRINER			RECORDING HRS.: 18			DATE: MO 1 DAY 31 YR 77	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS & EVENS		<input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV		<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	
[9-TRACK] NO. BYTES IN HEADER REC.: 228		NO. BYTES IN RECORD ID.: 2		NO. BYTES PER SCAN: 254		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: 36 db	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)			AUXILIARY DATA: (1) TW (2) 18 (3) (4) (5) (6) (7)				
PARAMETER RECORD LENGTH: 8 sec.		SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. 8		LO CUT HZ SLOPE: 18	
DISPLAY MODE: <input checked="" type="checkbox"/> AOC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: db		TRIP SENS: 36 db		POLARITY CONVENTION:		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	
CFS I TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE		PATTERN: SINGLE HOLE		NO. OF POSITIONS: 1		INLINE SPACING:		LATERAL SPACING:	
<input type="checkbox"/> VIBROSEIS		CHG. HOLE: 105/105'		HOLE DEPTH: 105'		SWEEP START:		SWEEP END:	
<input type="checkbox"/> OTHER		RESISTANCE: ohms		STAGGER: 18		INCLINE SPACING: 25'		LATERAL SPACING:	
RECEIVER TYPE: GEOSPACE 70D 10 Hz		PATTERN: IN LINE		NO. OF ELEMENTS: 18		LENGTH: 425'		WIDTH:	
CONNECTION: SERIES - PARALLEL		RESISTANCE:		STAGGER:		LENGTH: 425'		LATERAL OFFSET:	
SPREAD NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'		FOLD: 12 F		DIRECTION OF PROGRESSION: WEST	
OFFSET GROUP 1: 10450'		OFFSET GROUP 18: 110'		OFFSET GROUP 49: 110'		OFFSET GROUP 96: 10450'		LEADING GROUP: 96	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. to		TR. to		SHOT				SPREAD				REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			TR 1-48	TR 49-96
6890	5123267	187			105	105				1/1	SP678-SP702				
6891		187			105	105				1/5	SP679-SP703				
6892		187			105	105				1/9	SP680-SP704				

- WAIT ON DRILLS
TAPE CHANGE

LAND SEISMIC RECORDING LOG



	CLIENT: HUSKY NPR- OPER.	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 68E					
	PARTY NO: 1184	INST. ENG: DONALD / BRINER	RECORDING HRS. 18	DATE: MO 1 DAY 31 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS X <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (H1) <input type="checkbox"/> 800 BPI (H2) <input type="checkbox"/> 712 BPI (H3) <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	DATA CHANNEL NOS.: 1-96	(ON MAG TAPE)	AUXILIARY DATA: HW 18	AUXILIARY CHANNEL NOS.: 1 2 3 4 5				
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFF	FILTERS: FREQ. 8 LO CUT HZ 18 HI CUT HZ 12	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: 36 db	POLARITY CONVENTION: <input checked="" type="checkbox"/> PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK				
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: GEOSPACE 200 10 Hz	PATTERN: IN LINE	NO. OF ELEMENTS: 18	INCLINE SPACING: 25'	LATERAL SPACING: _____	STAGGER: _____	LENGTH: 425'	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 12 f	DIRECTION OF PROGRESSION: WEST	OFFSET GROUP 1: 10450	OFFSET GROUP 48: 110'	OFFSET GROUP 96: 10450	LEADING GROUP: 96

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS		SET UP	TR 1-48	TR 49-96	TR 1-48
683	523	268			190	105	105			113	SP681-705	①				
684					194	105	105			117	SP682-SP706					
685					195	105	105			121	SP683-SP707					
686					196	105	105			125	SP684-SP708					
687					197	105	105			129	SP685-SP709					
688					198	105	105			119	SP686-SP710	②				
689					199	105	105			113	SP687-SP710-4		NO SP710 LAST SP. OF 12F-6 HOLES TO THE M.			
700					200	105	105			117	SP688-SP711		SP711 FIRST SP OF 6F - 3 HOLES TO THE M.			
701					201	105	105			121	SP689-SP712-4					
702					202					125	SP690-SP712					
													- 2 LINE TRUCKS BROKE DOWN.			

LAND SEISMIC RECORDING LOG

PAGE 1 OF 2



	CLIENT: HUSKY - NPA OPERATIONS	PROSPECT AREA: NOATH SLOPE - ALASKA	AREA: PROSPECT NPA-4	LINE NO.: 68E	
PARTY NO.: 1184		INST. ENG.: DONALD / BAINEA REC HAS. 13		DATE: MO 2 DAY 1 YR 77	
INSTRUMENT (9-TRACK): <input type="checkbox"/> 3 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS <input type="checkbox"/> TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER		NO. BYTES IN RECORD REC: 228		NO. BYTES PER SCAN: 254	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
PARAMETER: RECORD LENGTH: 9 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	
DISPLAY: MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 36 db		TRIP SENS: 42 db	
SOURCE: TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: INLINE		NO. OF POSITIONS: 18	
RECEIVER: TYPE: GEO-SPACE 20P-10HZ		CONNECTION: SERIES PARALLEL		STAGGER: 25'	
SPREAD: NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880 TO SP 710 - 1760 AFTER SP 710	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to		TR. 2 to		SHOT			SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-20	TR 21-40	TR 41-60
703	523	210			1015	1015				Y5	SP 691-712-4				
704		211			1015	1015				Y9	SP 692-713				
705		212			1015	1015				Y13	SP 693-713-4				
706		213			1015	1015				Y17	SP 694-714				
707		214			1015	1015				Y21	SP 695-715-4				
708		215			1015	1015				Y25	SP 696-715				
709		216			1015	1015				Y29	SP 697-715-4				
710		217			1015	1015				Y33	SP 698-716	END OF 12 FOLD COVERAGE			
TABE OUTSIDE															

LAND SEISMIC RECORDING LOG

PAGE 2 OF 2

	CLIENT: HUSKY	PROSPECT: NPA-4	AREA: NORTH SLOPE ALASKA	LINE NO: 68E						
	PARTY NO: 1184	INST. ENG: RONALD BAIBER	REC HRS: 13	DATE: MO 2 DAY 1 YR 77						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: ohms.	(1) (2) (3) (4) (5) (6) (7)			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:		DATA CHANNEL NOS.:		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 16 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 128 NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY			
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS: 42 db	POLARITY CONVENTION:		CORR. SCALING:		R.C.U. NORM/ALT SW.		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:				
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: INCLINE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	TYPE: GEO-SPACE-200-10HZ	PATTERN: INCLINE	NO. OF ELEMENTS: 18	INCLINE SPACING: 25'	LATERAL SPACING:	STAGGER:	LENGTH: 425'	WIDTH:	LATERAL OFFSET:	
SPREAD	CONNECTION: SERIES PARALLEL	RESISTANCE: ohms	STAGGER:	FOLD: 6 FOLD	DIRECTION OF PROGRESSION: N	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760	OFFSET INTERVAL: 10450'	LEADING GROUP: 96

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT		SPREAD		REMARKS: REC# 218 - DUMMY REC. - NEW TAPE	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-31	TR 32-41	TR 42-51
711	520269	219			105	105			41	SP 700-717	①				
712		220			105	106			41	SP 702-718	②				
713		221			105	105			49	SP 704-719					
714		222			105	106			47	SP 706-720					
715		223			105	105			45	SP 708-721					
716		224			105	105			43	SP 710-SP 722					
717		225			105	105			41	SP 711-723					
718		226			105	105			49	SP 712-724					



LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY - NPR OPERATIONS	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 68E					
	PARTY NO: 1184	INST. ENG.: DONALD	REC HRS: TT 2 NH 8	DATE: MO 2 DAY 2 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input checked="" type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI	
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	DATA CHANNEL NOS.: 1-96	(ON MAG TAPE)			AUXILIARY DATA: TRU FB (3) (4) (5) (6) (7)	AUXILIARY CHANNEL NOS.: 1 2 3 4 5		
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms. ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 128	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT				
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT	INITIAL GAIN: 36 db	TRIP SENS: 42 db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK				
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: GEO-SPACE 200 10HZ	PATTERN: INLINE	NO. OF ELEMENTS: 18	INCLINE SPACING: 25'	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	CONNECTION: SEALIES - PARALLEL	RESISTANCE: _____ ohms	STAGGER: _____	INCLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: 425'	WIDTH: _____	LATERAL OFFSET: _____
	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 850' 1760'	FOLD: 6f	DIRECTION OF PROGRESSION: WEST	OFFSET GROUP 1: 10450	OFFSET GROUP 48: 110'	OFFSET GROUP 96: 10450	LEADING GROUP: 96

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD		REMARKS	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	SP	TR 1-48	TR 49-96	TR 97-144	TR 145-192	
719	1252	2313	17	2223	26	27	29	30	32	35	37	1/9	SP713 → 725	①				
720		2314										1/17	SP714 → 726					
721		2315										1/25	SP715 → 727					
722		2316										1/33	SP716 → 728					
723		2317										1/17	SP717 → 729	②				
724		2318										1/25	SP718 → 730					
725												1/33	SP719 → 731					
															COLD WHETHER -55° → -60°			

LAND SEISMIC RECORDING LOG



	CLIENT: MUSKY-NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 08E					
	PARTY NO: 1184	INST. ENG: DONALD BRINER	RECORDING OPS: 12	DATE: MO 2 DAY 3 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LQ) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	(ON MAG TAPE)		AUXILIARY DATA: 1W 18	AUXILIARY CHANNEL NOS.: 1 2 3 4 5				
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18	FREQ. 128 HI CUT HZ SLOPE 128	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS.: 40 db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE } NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK } ON DISPLAY			
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____ E.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE NOLE	NO. OF POSITIONS: 1	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: 20 SPACE 200 10 Hz	PATTERN: SERIES PARALLEL	RESISTANCE: _____ ohms	NO. OF ELEMENTS: 18	STAGGER: _____	INCLINE SPACING: 25'	LENGTH: 425'	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 1760	FOLD: 6	OFFSET GROUP 48/96: 10450	DIRECTION OF PROGRESSION: WEST			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT			SPREAD		REMARKS: FILE # 239 - 245 DAILY TESTS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TH	TR	TH
725	1252	246	1253	246	105	105	35	37	49	SP719 → 731					
726		247		247	105	105			117	SP720 → 732					
727		248		248	105	105			125	SP721 → 733					
728									133	SP722 → 734					
TRAPERS CWD RANGE															

LAND SEISMIC RECORDING LOG



PAGE 2 OF 7

	CLIENT: AGSXY-NPR OPER	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 08E					
PARTY NO: 184		INST. ENG: DONALD BRINER		DATE: MO 2 DAY 3 YR 17					
RECORDING: 12		T.T. 2		R.M. 10					
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
(9-TRACK)	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: TW 78			AUXILIARY CHANNEL NOS.: 1 2 3 4 5		
PARAMETER	RECORD LENGTH: 8 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 12 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 12	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT				
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS: 42 db	POLARITY: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: GEOSPARE 70D 10Hz	PATTERN: IN LINE	NO. OF ELEMENTS: 18	INCLINE SPACING: 25'	STAGGER:	LENGTH: 425'	WIDTH:	LATERAL OFFSET:	
SPREAD	CONNECTION: SERIES-PARALLEL TO SP 734	RESISTANCE: _____ ohms	SHOTPOINT INTERVAL: 1760'	FOLD: 67	OFFSET GROUP: 10450'	DIRECTION OF PROGRESSION: WEST	LEADING GROUP: 96		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1		TR. 2		SHOT		SPREAD		REMARKS	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR. 1	TR. 2	TR. 3	TR. 4
728	5232	2510			105	105			1/33	SP722-734	①					
729		2511			105	105			1/41	SP723-735						
730		2512			105	105			1/49	SP724-736						
731		2513			105	105			1/19	SP725-737	②					
732		2514			105	105			1/17	SP726-738						
733		2515			105	105			1/25	SP727-739						
734		2516			105	105			1/33	SP728-740						
735		2517			105	105			1/14	SP729-741	③					
736		2518			105	105			1/25	SP730-742						
737		260			105	105			1/33	SP731-743						
738		261			105	105			1/41	SP732-744	④					
739		262			105	105			1/25	SP733-745						
740		263			105	105			1/33	SP734-746						
741		264			105	105			1/41	SP735-747						
742		265			105	105			1/49	SP736-748						

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO.: 68E	
PARTY NO.: 1184		INST. BKG.: BRINER		DATE: MO 2 DAY 4 YR 77	
NO. BYTES IN HEADER REC.: 228		NO. BYTES IN RECORD ID.: 2		NO. BYTES PER SCAN: 254	
FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 1-96		AUXILIARY DATA: 1 2 3 4 5	
RECORD LENGTH: 8 sec.		SAMPLE RATE: 36 db		GAIN CONSTANT: 36 db	
MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 36 db		LO CUT HZ SLOPE: 18	
TYPE STACK:		GATE LENGTH:		CORRECTION: 18	
TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE HOLE		NO. OF POSITIONS: 1	
CHG. HOLE: 110/16		HOLE DEPTH: 105		SWEEP POSITION: 1	
NO. OF GROUPS: 96		GROUP INTERVAL: 200'		SHOTPOINT INTERVAL: 1760'	
OFFSET GROUP 1: 10450'		OFFSET GROUP 48 : 110'		OFFSET GROUP 49 : 110'	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD			REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 1-48	TR 49-96	TR 1-48	TR 49-96
7473	52	2177			110	105				119	SP737-749					
744		2178			110	105				1117	SP738-750					
745		2179			110	105				1125	SP739-751					
746		2180			110	105				1133	SP740-752					
747		2181			110	105				1117	SP741-753					
748		2182			110	105				1125	SP742-754					
749		280			110	105		60'	E	1133	SP743-755					
750		281			110	105		90'	S	1141	SP744-756					
751		282			110	105				1149	SP745-757					
752		283			110	105				119	SP746-758					
753		284			110	105				1117	SP747-759					
754		285			110	105				1125	SP748-760					
755		286			110	105				1133	SP749-761					

LAND SEISMIC RECORDING LOG

	CLIENT: ALASKA NPR-OPERATION				PROSPECT: NPR-4				AREA: NORTH SLOPE ALASKA				LINE NO: 68E											
PARTY NO: 1184		INST. BKG: BRINER			REC HRS: 14			TT 2			DATE: Dec 12			MO: 2 DAY: 5 YR: 77										
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS				<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96				ODDS & EVENS				TYPE: <input type="checkbox"/> DFS <input checked="" type="checkbox"/> DFS <input checked="" type="checkbox"/> OTHER		<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		FORMAT: B		<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI			
(9-TRACK)	NO. BYTES IN HEADER REC: 228				NO. BYTES IN RECORD ID: 2				NO. BYTES PER SCAN: 254				RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: 36 db		INPUT IMPEDANCE: _____ ohms							
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96												AUXILIARY DATA: TW 18											
	DATA CHANNEL NOS.: 1-96				(ON MAG TAPE)								AUXILIARY CHANNEL NOS.: 1 2 3 4 5											
PARAMETER	RECORD LENGTH: 8 sec.				SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.				GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE				FILTERS: FREQ: 8 LO CUT HZ SLOPE 18		FREQ: 28 HI CUT HZ SLOPE 72		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT							
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT				INITIAL GAIN: 36 db				TRIP SENS: 42 db				POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY							
CFS I	TYPE STACK:				GATE LENGTH:				RECORD REJECTION:				NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM/ALT SW.					
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER				PATTERN: SINGLE HOLE				NO. OF POSITIONS: 1 1				INLINE SPACING:		LATERAL SPACING:		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:	
					CHG/ HOLE: 110/65 HOLE DEPTH: 105'				SWEEP START:				SWEEP END:		SWEEP LENGTH:		SWEEP TAPER:		PHASE COMP:					
RECEIVER	TYPE: GEOSPACE 20D 10HE				PATTERN: INLINE				NO. OF ELEMENTS: 18				INCLINE SPACING: 25'		LATERAL SPACING:		STAGGER:		LENGTH: 425'		WIDTH:		LATERAL OFFSET:	
	CONNECTION: SERIES				RESISTANCE: _____ ohms				STAGGER:				INCLINE SPACING:		LATERAL SPACING:		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: 396				GROUP INTERVAL: 220'				SHOTPOINT INTERVAL: 1760'				FOLD: 6E		DIRECTION OF PROGRESSION: WEST									
	OFFSET GROUP 1: 10450				OFFSET GROUP 48 : 110'				OFFSET GROUP 48 : 110'				OFFSET GROUP #/96: 10450		LEADING GROUP: 96									

DIAGRAMS/MISC. INFORMATION :

SHOTPOINT	TR.	to	TR.	to	SHOT				SPREAD				REMARKS	CORR STACK						
					REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR	REC.	TR	REC.
756	252	327	288									116	SP1750-762	FILE # 288-92 NOT USED						
757			285									113	SP1751-763	FILE # 288-92 TEST						
758			286									112	SP1752-764							
759												119	SP1753-765							

NEW TAPES



LAND SEISMIC RECORDING LOG

	CLIENT: WASKY NPR OPERATION	PROSPECT: NPR-4	AREA: NORTA SLOPE ALASKA	LINE NO: 68E				
	PARTY NO: 1184	INST. ENG: PRINER	REC HRS: 1A	REL: 12	DATE: MO 2 DAY 5 YE 77			
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.	(3) _____ (4) _____ (6) _____ (7) _____	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: 1 2 3 4 5				
	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: _____				
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ: 8 LO CUT HZ SLOPE: 18 HI CUT HZ SLOPE: 22	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS: 42 db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE <input checked="" type="checkbox"/> NEGATIVE POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY			
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORE SCALING: _____ R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE NOISE	NO. OF POSITIONS: 1	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____		
RECEIVER	TYPE: GEOSPACE 200 10#	PATTERN: IN LINE	NO. OF ELEMENTS: _____	INCLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____		
SPREAD	CONNECTION: SERIES	RESISTANCE: _____ ohms	STAGGER: _____	INCLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____		
	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1160	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____		
	OFFSET GROUP 1: 10450'	OFFSET GROUP: 110'	OFFSET GROUP: 110'	OFFSET GROUP 48/96: _____				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT					SPREAD			REMARKS:	CORE STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			SET	TR 1-24	TR 25-48	TR 49-72
1759	5232	272	2223	2627	110	105	35	37		1129	SP753-765		(1)				
1760		271			110	105				1137	SP754-766						
1761		300			110	105				1119	SP755-767		(2)				
1762		301			110	105				1117	SP756-768						
1763					110	105				1125	SP757-769			LOST SHOT OPERATOR ERROR			
1764		302			110	105				1133	SP758-770						
1765		303			110	105				1117	SP759-771		(3)				
1766		304			110	105				1125	SP760-772						
1767		305			110	105				1133	SP761-773						
1768		306			110	105				1141	SP762-774						



LAND SEISMIC RECORDING LOG

	CLIENT: WASKY NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO.: 68E	
PARTY NO.: 1184		INST. ENG.: BRINER		DATE: MO 2 DAY 6 YR 77	
NO. BYTES IN HEADER REC.: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254	
FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 1-96		AUXILIARY DATA: 1 2 3 4 5	
RECORD LENGTH: 8 sec		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms		GAIN CONSTANT: 36 db	
MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: 36 db		LO CUT HZ SLOPE: 18	
TYPE STACK: 8		GATE LENGTH: 42 db		FREQ. 128 HZ SLOPE 72	
SOURCE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE HOLE		NO. OF POSITIONS: 1	
RECEIVER: GEOSPACE 200 104K		PATTERN: INLINE		NO. OF ELEMENTS: 18	
SPREAD: 10450'		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 1760'	
OFFSET GROUP: 10450'		OFFSET GROUP: 110'		OFFSET GROUP: 110'	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	REEL NO.		REC.		SHOT		SPREAD		REMARKS	CORR. STACK			
	TR. NO.	TR. NO.	TR. NO.	TR. NO.	SIZE	DEPTH	NO.	OFFSET		TR. 1-48	TR. 49-96	TR. 1-48	TR. 49-96
1768	152	172	315		110	105	11	1763	①	LINE 307-314 TEST			
1770			316		110	105		1764					
1772			317		110	105		1765					
1774			318		110	105		1766					
1776			319		110	105		1767					
1778			320		110	105		1768	②				
1780			321		110	105		1769					
1782			322		110	105		1770					
1784			323		110	105		1771					

LAND SEISMIC RECORDING LOG

	CLIENT: NUSKY NPR OPER	PROSPECT: NPR 4	AREA: NORTH SLOPE ALASKA	LINE NO: 68E	
PARTY NO: 1184		INST. ENG: GRINER		DATE: MO 2 DAY 6 YR 77	
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254	
INSTRUMENT (9-TRACK)		TYPE: <input checked="" type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		FORMAT: <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: 1-96		AUXILIARY DATA: 2W 7B	
PARAMETER		DATA CHANNEL NOS.: 1-26 (ON MAG TAPE)		AUXILIARY CHANNEL NOS.: 1 2 3 4 5	
DISPLAY		RECORD LENGTH: 8 sec.		GAIN CONSTANT: 36 db	
CFS I		SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.		INPUT IMPEDANCE: _____ ohms.	
SOURCE		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
RECEIVER		TRIP SENS: 42 db		CORR. SCALING: _____	
SPREAD		RECORD REJECTION: _____		NOISE REDUCTION: _____	
DIAGRAMS/MISC. INFORMATION:		NOISE THRESHOLD: _____		CORR. SCALING: _____	
TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE HOLE		NO. OF POSITIONS: 1	
CHG. HOLE: 110/63		HOLE DEPTH: 105		SWEEP POSITION: _____	
PATTERN: IN LINE		RESISTANCE: _____ ohms		STAGGER: _____	
NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 1760'	
OFFSET GROUP 1: 10450'		OFFSET GROUP 48: 100'		OFFSET GROUP 96: 100'	
NO. OF ELEMENTS: 18		INCLINE SPACING: _____		LATERAL SPACING: _____	
STAGGER: _____		LENGTH: 25'		WIDTH: _____	
SWEEP LENGTH: _____		SWEEP TAPER: _____		PHASE COMP: _____	
SWEEP END: _____		INCLINE SPACING: _____		LATERAL SPACING: _____	
FOLD: 67		LENGTH: 425'		WIDTH: _____	
DIRECTION OF PROGRESSION: WEST		LATERAL SPACING: _____		LATERAL OFFSET: _____	
LEADING GROUP: 96		FOLD: _____		DIRECTION OF PROGRESSION: _____	

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-48	TR 49-96	TR 49-96
1773	S33208	325			1/11	105					SP772-1784				
1778		324			1/19	105					SP773-1785				
1780		327			1/17	105					SP774-1786				
1781		329			1/25	105					SP775-1787				
1782		329			1/33	105					SP776-1788				



LAND SEISMIC RECORDING LOG

	CLIENT: NUSKY NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO.: 68E							
	PARTY NO.: 1184	INST. ENG.: BRINER	RECORDING MRS. 13.5 2 1/2 TT 11 Rec			DATE: MO 2 DAY 8 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: 8	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (H1) <input type="checkbox"/> 712 BPI	<input type="checkbox"/> 800 BPI	<input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)			AUXILIARY DATA:	1	2	3	4	5	(6) _____ (7) _____
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> IFP	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18	FREQ. 108 HI CUT HZ SLOPE 12	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS: 42 db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY				
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW.				
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE NOLE	NO. OF POSITIONS: 1	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
RECEIVER	TYPE: GEOSPACE 20	PATTERN: INLINE	NO. OF ELEMENTS: 18	INCLINE SPACING: 25'	LATERAL SPACING: _____	STAGGER: _____	LENGTH: 425'	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 1760'	FOLD: 65	DIRECTION OF PROGRESSION: WEST	OFFSET GROUP 1: 10450'	OFFSET GROUP 48: 110'	OFFSET GROUP 96: 10450	LEADING GROUP: 96		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-48	TR 49-96	TR 1-48
783	253278	337			160	105				1114	SP1777-1789				
784		338			160	105				1125	SP1778-1790				
785		339			160	105				1133	SP1779-1791				
786		340			160	105				1141	SP1780-1792				
787		341			160	105				1149	SP1781-1793				
788		342			160	105				119	SP1782-1794				
789		343			160	105				1114	SP1783-1795				
790		344			160	105				1125	SP1784-1796				
791		345			160	105				1133	SP1785-1797				
792		346			160	105				1141	SP1786-1798				
793		347			160	105				111	SP1787-1799				
794		348			160	105				119	SP1788-800				
795		349			160	105				1117	SP1789-801				
796					160	105				1125	SP1790-802				

LAND SEISMIC RECORDING LOG

	CLIENT: <i>RUSKY NPR OPERATION</i>	PROSPECT: <i>NPR-4</i>	AREA: <i>NORTH SLOPE ALASKA</i>	LINE NO.: <i>68E</i>								
PARTY NO.: <i>1184</i>	INST. BKG.: <i>DRINER</i>	REC NRS: _____			DATE: <i>MO 2 DAY 8 YR 77</i>							
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <i>B</i>	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(L) <input type="checkbox"/> 356 BPI	(M) <input type="checkbox"/> 712 BPI	(H) <input checked="" type="checkbox"/> 1600 BPI	
(9-TRACK)	NO. BYTES IN HEADER REC: <i>228</i>	NO. BYTES IN RECORD ID: <i>2</i>	NO. BYTES PER SCAN: <i>254</i>	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <i>36</i>	INPUT IMPEDANCE:	ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <i>1-96</i>	DATA CHANNEL NOS.: <i>1-96</i>	(ON MAG TAPE)	AUXILIARY DATA:	<i>(1) 741 (2) 25 (3) (4) 383 (6) (7)</i>	AUXILIARY CHANNEL NOS.: <i>1 2 3 4 5</i>						
PARAMETER	RECORD LENGTH: <i>8</i>	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS:	FREQ: <i>8</i>	LO CUT HZ SLOPE: <i>18</i>	HI CUT HZ SLOPE: <i>172</i>	<input type="checkbox"/> IN FILTER. <input checked="" type="checkbox"/> OUT	<input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	<input type="checkbox"/> NUMBERS ON MAG. TAPE <input type="checkbox"/> UPBREAK	ON DISPLAY
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <i>36</i>	TRIP SENS: <i>42</i>	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE:							
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:						R.C.U. NORM/ALT SW.
SOURCE	<input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <i>SINGLE HOLE</i>	NO. OF POSITIONS: <i>1</i>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
RECEIVER	TYPE: <i>GEOSPAC 200</i>	PATTERN: <i>INLINE</i>	NO. OF ELEMENTS: <i>18</i>	INCLINE SPACING: <i>25'</i>	LATERAL SPACING:	STAGGER:	LENGTH: <i>425'</i>	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: <i>96</i>	GROUP INTERVAL: <i>220'</i>	SHOTPOINT INTERVAL: <i>1760'</i>	FOLD: <i>65</i>	DIRECTION OF PROGRESSION: <i>WEST</i>	OFFSET GROUP: <i>48</i>	OFFSET GROUP: <i>110'</i>	OFFSET GROUP: <i>10450'</i>	LEADING GROUP: <i>96</i>			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 21-30	TR 41-50
<i>176</i>	<i>25274</i>	<i>37</i>	<i>22</i>	<i>23</i>	<i>20</i>	<i>27</i>	<i>29</i>	<i>30</i>	<i>35</i>	<i>37</i>	<i>1125</i>	<i>SPT 790-802</i>		

LAND SEISMIC RECORDING LOG

	CLIENT: MUSKY NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 68E					
	PARTY NO: 1184	INST. ENG: BRINER	REC NRS: 14	T.T. 3 REC. 11	DATE: MO 2 DAY 9 YR 77				
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: 2	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	AUXILIARY DATA: TRU TR (3) (4) (5) (6) (7)		AUXILIARY CHANNEL NOS.: 1 2 3 4 5					
	DATA CHANNEL NOS.: 1-96	(ON MAG TAPE)							
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT 18 HZ SLOPE 18	HIGH CUT 172 HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS: 42 db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GECPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG. HOLE: 11016	HOLE DEPTH: 105'	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
RECEIVER	TYPE: GEOSPACE 200	PATTERN: IN LINE	NO. OF ELEMENTS: 18	INCLINE SPACING: 25'	LATERAL SPACING: _____	STAGGER: _____	LENGTH: 425'	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: SERIES	RESISTANCE: _____							
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 6+	DIRECTION OF PROGRESSION: WEST				
	OFFSET GROUP 1: 10450	OFFSET GROUP 48 110'	OFFSET GROUP 110'	OFFSET GROUP 4876	LEADING GROUP: 96				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD				REMARKS:	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			TR 1-48	TR 49-96
797	352	357			110	105					119	SP791-803	①		
798		360			110	105					117	SP792-804			
799		361			110	105					125	SP793-805			
800		362			110	105					133	SP794-806			
801		363			110	105					141	SP795-807			
802		364			110	105					149	SP796-808			
803		365			110	105					119	SP797-809	②		
804		367			110	105					117	SP798-810		FILE#366 NOT PRODUCTION	
805		369			110	105					125	SP799-811		FILE#368 NOT PRODUCTION	
806		370			110	105					133	SP800-812			
807		371			110	105	100	5			117	SP801-813	③		
808		372			110	105					125	SP802-814			
809		373			110	105					133	SP803-815			
810		374			110	105					141	SP804-816			
811		375			110	105					149	SP805-817			



LAND SEISMIC RECORDING LOG

	CLIENT: WISKY NPR OPER.	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO.: 68E		
	PARTY NO.: 1184	INST. EMP.: CRINER	REC. HRS.: 15	DATE: MO 2 DAY 10 YR 77		
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-28 & 29-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI
	NO. BYTES IN HEADER REC.: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)		AUXILIARY DATA:	AUXILIARY CHANNEL NOS.: 1 2 3 4 5	
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	FILTERS: 8 PREQ.	LO CUT: 18 HZ	HI CUT: 42 HZ
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS.: 42 db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:
RECEIVER	TYPE: GEOSPARE 70 D. 10 A.	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 25'	LATERAL SPACING:	STAGGER:
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1M60'	FOLD: 6+	DIRECTION OF PROGRESSION: WEST	LEADING GROUP: 96

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT			SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TR. 1-48
812	25230175	384			110	105				1/3	SP 806-818		
813		385			110	105				1/11	SP 807-819		
814		386			110	105				1/19	SP 808-820		
815		387			110	105				1/27	SP 809-821		
816		388			110	105				1/17	SP 810-822	FILE # 388	MISFIRE
817		389			110	105				1/25	SP 811-823		
818		390			110	105				1/33	SP 812-824		
819		391			110	105				1/41	SP 813-825		
820		392			110	105	230	N		1/1	SP 814-826	FILE # 393	MISFIRE

LAND SEISMIC RECORDING LOG

	CLIENT: <i>MUSKY NPR OPERATION</i>	PROSPECT: <i>NPR-4</i>	AREA: <i>NORTH SLOPE ALASKA</i>	LINE NO.: <i>68E</i>	
	PARTY NO.: <i>1184</i>	INST. ENG.: <i>BRINER</i>	REC NRS.: <i>13</i>		
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> EVENS		<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK FORMAT: <i>B</i> <input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> EVENS	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT. GAIN CONSTANT: <i>36</i> db INPUT IMPEDANCE: ohms. NO. BYTES IN READER REC.: <i>228</i> NO. BYTES IN RECORD ID: <i>2</i> NO. BYTES PER SCAN: <i>254</i>	(9-TRACK)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <i>1-96</i> DATA CHANNEL NOS.: <i>1-96</i> (ON MAG TAPE)	AUXILIARY DATA: <i>121 7B 13 4</i> AUXILIARY CHANNEL NOS.: <i>1 2 3 4 5</i>	FILTERS: LO CUT: <i>18</i> HZ HI CUT: <i>72</i> HZ NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT POLARITY CONVENTION: PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE NUMBERS ON MAG. TAPE: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY		
PARAMETER	RECORD LENGTH: <i>8</i> sec. MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 10 ms. INITIAL GAIN: <i>36</i> db	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input checked="" type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE TRIP SENS.: <i>42</i> db	NOISE REDUCTION: NOISE THRESHOLD: CORR. SCALING: R.C.U. NORM./ALT SW.	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER PATTERN: <i>SINGLE HOLE</i> NO. OF POSITIONS: <i>1</i> CHG. HOLE: <i>110/105</i> HOLE DEPTH: <i>105</i> SWEEP POSITION: SWEEP START: SWEEP END:	INCLINE SPACING: LATERAL SPACING: STAGGER: LENGTH: WIDTH: LATERAL OFFSET:			
RECEIVER	TYPE: <i>GEOSPACE 200 10 Hz</i> CONNECTION: <i>SERIES</i>	PATTERN: <i>INLINE</i> NO. OF ELEMENTS: <i>18</i> RESISTANCE: ohms	INCLINE SPACING: <i>25'</i> STAGGER: LENGTH: <i>425'</i> WIDTH: LATERAL OFFSET:		
SPREAD	NO. OF GROUPS: <i>96</i> OFFSET GROUP 1: <i>10450'</i>	GROUP INTERVAL: <i>220'</i> OFFSET GROUP <i>48</i> : <i>110'</i>	SHOTPOINT INTERVAL: <i>11760'</i> OFFSET GROUP <i>48</i> : <i>110'</i>	FOLD: <i>6.7</i> OFFSET GROUP <i>96</i> : <i>10450'</i>	DIRECTION OF PROGRESSION: <i>WEST</i> LEADING GROUP: <i>96</i>

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. <u>10</u>		TR. <u>20</u>		SHOT			SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR. 10	TR. 20	TR. 30
<i>820</i>	<i>12523215</i>	<i>401</i>			<i>110</i>	<i>105</i>	<i>36</i>	<i>150</i>	<i>N</i>	<i>111</i>	<i>SP814-826</i> ⓐ				
<i>821</i>		<i>403</i>			<i>110</i>	<i>105</i>				<i>119</i>	<i>SP815-827</i>				
<i>822</i>		<i>404</i>			<i>110</i>	<i>105</i>				<i>117</i>	<i>SP816-828</i>				
<i>823</i>		<i>405</i>			<i>110</i>	<i>105</i>				<i>125</i>	<i>SP817-829</i>				
<i>824</i>		<i>406</i>			<i>110</i>	<i>105</i>				<i>119</i>	<i>SP818-830</i> ⓐ				
											<i>CHANGE TAPE</i>				


LAND SEISMIC RECORDING LOG

	CLIENT: NUSKY NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO.: 68E					
	PARTY NO.: 1184	INST. ENG.: BRANNER	REC. NRS.: REG. NRS.	DATE: MO 2 DAY 11 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC.: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	(ON MAG TAPE)			AUXILIARY DATA:	1 2 3 4 5	AUXILIARY CHANNEL NOS.: 1 2 3 4 5		
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT 12 HI CUT 12 HZ SLOPE 12	<input type="checkbox"/> NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS.: 42 db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK				
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: GEOSPAC 200	PATTERN: IN LINE	NO. OF ELEMENTS: 18	INCLINE SPACING: 25'	LATERAL SPACING:	STAGGER:	LENGTH: 425'	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1160'	FOLD: 67	DIRECTION OF PROGRESSION: WEST	OFFSET GROUP 1: 10450'	OFFSET GROUP 96: 10450'	LEADING GROUP: 96	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD		REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DR.	CDP SWITCH		LINE GROUPS	TR 1-48	TR 49-96	TR 1-48
825	573	408	223	408	110	105	35	37		1/19	SP819 → 831				
826		409			110	105				1/25	SP820 → 832				
827		410			110	105				1/33	SP821 → 833				
828		411			110	105				1/41	SP822 → 834				
829		412			110	105				1/1	SP823 → 835				
830		413			110	105				1/19	SP824 → 836				
831		414			110	105				1/17	SP825 → 837				
832		415			NO	NO				1/25	SP826 → 838				

LAND SEISMIC RECORDING LOG

	CLIENT: <u>NUSKY NPR OPER.</u>	PROSPECT: <u>NPR-4</u>	AREA: <u>NORTH SLOPE ALASKA</u>
	PARTY NO:	INST. ENG.:	LINE NO: <u>68E</u>
INSTRUMENT (9-TRACK)		DATE: <u>MO 2 DAY 12 YR 77</u>	
<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC.: <u>228</u>		<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96 NO. BYTES IN RECORD ID: <u>2</u>	
CONFIGURATION (MAG TAPE)		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT. GAIN CONSTANT: <u>36</u> db INPUT IMPEDANCE: _____ oh	
PARAMETER		AUXILIARY DATA: <u>1 2 3 4 5</u> AUXILIARY CHANNEL NOS.: _____	
DISPLAY		FILTERS: _____ FREQ: <u>8</u> LO CUT HZ SLOPE <u>18</u>	
CFS I		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> ON MAG. TAPE <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY	
SOURCE		NOISE REDUCTION: _____ NOISE THRESHOLD: _____ CORR. SCALING: _____ R.C.U. NORM/ALT SW. _____	
RECEIVER		TYPE: <u>GEOSPAC 200</u> CONNECTION: <u>SERIAL</u> PATTERN: <u>INLINE</u> NO. OF ELEMENTS: <u>18</u>	
SPREAD		INCLINE SPACING: <u>25'</u> LENGTH: <u>425'</u> WIDTH: _____ LATERAL SPACING: _____ LATERAL OFFSET: _____	
DIAGRAMS/MISC. INFORMATION:		NO. OF GROUPS: <u>96</u> OFFSET GROUP 1: <u>10450'</u> GROUP INTERVAL: <u>220'</u> OFFSET GROUP: <u>48 110</u> SHOTPOINT INTERVAL: <u>1460'</u> OFFSET GROUP: <u>49 120'</u> DIRECTION OF PROGRESSION: <u>WEST</u> LEADING GROUP: <u>96</u>	



SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT		DIR.	CDP SWITCH	SPREAD	REMARKS	CORR. STAGE	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH					NO.	OFFSET
833	25D-3216	424			110	105	33		119 SP834 → 839	FILE # 416-423 TESTS		
834		425			110	105			1117 SP828 → 840	2 SECOND RECORD		
835		426			110	105			1125 SP829 → 841			
836		427			110	105			1133 SP830 → 842			
837		428			110	105			1141 SP831 → 843			
838		429			110	105			1141 SP831 → 843			
839		430			110	105			1119 SP833 → 845	WRONG CDP SHOULD BE 1-49 832 → 844		
840		431			110	105			1114 SP834 → 846			
841		432			110	105			1125 SP835 → 847			
842		433			110	105			1133 SP836 → 848			
843		434			110	105			1141 SP837 → 849			

LAND SEISMIC RECORDING LOG

	CLIENT: MUSKY NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO.: 68E	
	PARTY NO.: 1184	INST. ENG.: BRINER	Rec Hrs: 15.5	DATE: NO 2 DAY 13 YR 77	
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	NO. BYTES IN HEADR REC.: 228	NO. BYTES IN RECORD ID.: 2	NO. BYTES PER SCAN: 254
	TYPE: <input type="checkbox"/> DPS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> GAPS <input type="checkbox"/> EVENTS	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 575 ohms
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	DATA CHANNEL NOS.: 1-96	(ON MAG TAPE)		
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> IFF	FILTERS: FREQ. 8 Hz	LO CUT HZ SLOPE: 18
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS.: 42 db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:
RECEIVER	TYPE: GEOSPARE 200 10Hz	CHG/ HOLE: 11016	HOLE DEPTH: 105	SWEEP START:	SWEEP END:
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	INCLINE SPACING: 25'	LATERAL SPACING: 425'
	OFFSET GROUP 1: 10450'	OFFSET GROUP 48: 110'	OFFSET GROUP 96: 110'	LENGTH: 6.7	WIDTH: 10450
DIAGRAMS/MISC. INFORMATION:					

SHOTPOINT	TR. 1-24		TR. 25-48		SHOT		SPREAD		REMARKS	CORR. STACK	
	TR. NO.	REC.	TR. NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR. 1-24	TR. 25-48
844	443				110	105	11	8038 → 850	FILE 435-442 TESTS HOLE BLOW!		
845	444			110	105	119	8039 → 851				
846	445			110	105	1119	8040 → 852				
847	446			110	105	1125	8041 → 853				
848	447			110	105	119	8042 → 854				
849	448			110	105	1119	8043 → 855				
850	449			110	105	1125	8044 → 856				
851	450			110	105	1133	8045 → 857				
852	451			110	105	1114	8046 → 858				
853				110	105	1125	8047 → 859				



LAND SEISMIC RECORDING LOG

	CLIENT: RUSKY NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 68E					
PARTY NO: 1184		INST. BRAND: BRINER		DATE: NO 2 DAY 14 YR 1977					
REC NRS: 15.5		TT 2.5		REG: 130					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (N1) <input type="checkbox"/> 712 BPI (N2) <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.	(10) _____ (11) _____ (12) _____ (13) _____ (14) _____ (15) _____ (16) _____ (17) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: 1 2 3 4 5					
	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 Hz	LO CUT 18 Hz	HZ SLOPE 42	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AOC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS: 42 db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON DISPLAY	R.C.U. NORM/ALT SW.		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG/ HOLE: 110/15	HOLE DEPTH: 105'	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
RECEIVER	TYPE: GEOSPAC 200 10/12	PATTERN: INLINE	NO. OF ELEMENTS: 18	INCLINE SPACING: 25'	LATERAL SPACING: _____	STAGGER: _____	LENGTH: 425'	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: SERIES	RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 6	DIRECTION OF PROGRESSION: NWEST	OFFSET GROUP #/96: 10450'	LEADING GROUP: 96		
	OFFSET GROUP 1: 10450'	OFFSET GROUP #/96: 110'	OFFSET GROUP #/96: 110'						

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR.	REC.	TR.	REC.
853	12	523377	4159	2223	NO 100	2000	33	37		1/25	SP847 → 859					
854			400		110	75				1/33	SP848 → 860					
855			462		NO 100					1/41	SP849 → 861	FILE # 461 MISFIRE				
856										1/4	SP850 → 862	CHANGE TAPE				

LAND SEISMIC RECORDING LOG

	CLIENT: WISKEY NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 68E					
	PARTY NO: 1184	INST. ENG: BRINER	REC NRS: 155	DATE: 2 DAY 14 77					
			2.5 TT						
			13.6 Rec						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.	(3) _____ (4) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)		AUXILIARY DATA: 1 2 3 4 5	AUXILIARY CHANNEL NOS.: _____				
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 hr. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 1 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. 8 Hz	LO CUT HZ SLOPE: 18	FREQ. 28 Hz	HI CUT HZ SLOPE: 172	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AOC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 30 db	TRIP SENS: 42 db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> UPBREAK <input checked="" type="checkbox"/> DOWNBREAK	ON DISPLAY: <input type="checkbox"/> UPBREAK <input checked="" type="checkbox"/> DOWNBREAK		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	E.C.U. NORM/ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: IN LINE SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: GEOSPACE JOP 10Hz	PATTERN: IN LINE	NO. OF ELEMENTS: 18	STAGGER: _____	LENGTH: 25'	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760	FOLD: 65	INCLINE SPACING: 425'	DIRECTION OF PROGRESSION: WEST			
	OFFSET GROUP 1: 110'	OFFSET GROUP 48 : 110'	OFFSET GROUP 49 : 110'	OFFSET GROUP 96 : 10450					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____		TR. _____		SHOT				SPREAD			REMARKS:	CORR. STACK	
	TR. NO.	REC.	TR. NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR. 1-24	TR. 25-96
856	464	464	2223	2627	110	105	1	110'		1-1	SP 850 → 862			
857	465	465			110	105	1	110'		1-9	SP 851 → 863			
858	466	466			110	105	1	110'		1-14	SP 852 → 864			
859	467	467			110	105	1	110'		1-25	SP 853 → 865			
860	468	468			110	105	1	110'		1-33	SP 854 → 866			
861	469	469			110	105	1	110'		1-41	SP 855 → 867			
862	470	470			110	105	1	110'		1-1	SP 856 → 868			
863	471	471			110	105	1	110'		1-9	SP 857 → 869			
864	472	472			110	105	1	110'		1-14	SP 858 → 870			
865	473	473			110	105	1	110'		1-25	SP 859 → 871			
866	474	474			110	105	1	110'		1-33	SP 860 → 872			
867	475	475			110	105	1	110'		1-5	SP 861 → 873			
868	476	476			110	105	1	110'		1-13	SP 862 → 874			
869	477	477			110	105	1	110'		1-21	SP 863 → 875			
870	478	478			110	105	1	110'		1-29	SP 864 → 876			

LAND SEISMIC RECORDING LOG

	CLIENT: NUSKY NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 68E								
PARTY NO: 1184		INST. ENG: BRIMER		DATE: MG 2 DAY 15 YR 49								
REC NOS: 14.0		TT 2.5		Rec 11.5								
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> OOPS	TYPE: <input type="checkbox"/> DFS III	<input type="checkbox"/> DFS II	<input checked="" type="checkbox"/> 9 TRACK	FORMAT: B	<input checked="" type="checkbox"/> GAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI	(HI) <input type="checkbox"/> 712 BPI	
	<input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> EVENS									<input type="checkbox"/> DFS III
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254		RECORD NUMBERS:		<input checked="" type="checkbox"/> DEC.	<input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db		INPUT IMPEDANCE: _____ ohms.
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96					AUXILIARY DATA: W JB (3) (4) 55 (6) (7)						
	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)					AUXILIARY CHANNEL NOS.: 1 2 3 4 5						
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL	<input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL	<input type="checkbox"/> OPERATE	FILTERS:	FREQ. 8	LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 42	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT <input type="checkbox"/> DIRECT	AMPLIFIER	INITIAL GAIN: 36 db	TRIP SENS: 40 db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE:		NUMBERS ON MAG. TAPE: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM / ALT SW.	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIRROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE NOLE		NO. OF POSITIONS: 1		INLINE SPACING:		LATERAL SPACING:		STAGGER:	
	CHO / HOLE: 110/65		NOLE DEPTH: 105		SWEEP POSITION:		SWEEP START:		SWEEP END:		SWEEP LENGTH:	
RECEIVER	TYPE: GEOSPAC 200 10 Hz		PATTERN: INLINE		NO. OF ELEMENTS: 18		INLINE SPACING: 25'		LATERAL SPACING:		LATERAL OFFSET:	
	CONNECTION: SERIES		RESISTANCE: _____ ohms		STAGGER:		LENGTH: 425'		WIDTH:		LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 1160'		FOLD: 67		DIRECTION OF PROGRESSION: WEST		LEADING GROUP: 96	
	OFFSET GROUP 1: 10450'		OFFSET GROUP 48 : 110'		OFFSET GROUP 49 : 110'		OFFSET GROUP 96 : 10450'					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD				REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			TR. 48	TR. 49	TR. 50	TR. 51
8747	153278	492	17	2233	110	105	37	37			1-1	SP865 → 844					
8772		493			110	105					1-9	SP866 → 848					
8773		494			110	105					1-17	SP864 → 849					
													SHORT RECORD				
													END OF TAPE				

LAND SEISMIC RECORDING LOG

	CLIENT: NUSKY NPR OPERATION	PROSPECT: NPR-4	AREA: NORTA SLOPE ALASKA	LINE NO.: 68E	
PARTY NO.: 1184		INST. ENG.: BRINE		DATE: MO 2 DAY 15 YR 74	
NO. BYTES IN HEADER REC.:		NO. BYTES IN RECORD ID.:		NO. BYTES PER SCAN:	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS II <input type="checkbox"/> OTHER		<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS.: 1-96		AUXILIARY DATA: W 18 (3) 4 5 (6) (7)	
PARAMETER: RECORD LENGTH: 8 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	
DISPLAY: MODE: <input type="checkbox"/> AOC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 36 db		TRIP SENS.: 42 db	
CFS I: TYPE STACK:		GATE LENGTH:		RECORD REJECTION:	
SOURCE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE HOLE		NO. OF POSITIONS: 1	
RECEIVER: TYPE: GEOSPACE 200 10 Hz		CONNECTION: SERIES		PATTERN: IN LINE	
SPREAD: NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 1460'	
OFFSET GROUP 1: 10450		OFFSET GROUP 48: 110'		OFFSET GROUP 49: 110'	
CORR. SCALING:		NOISE THRESHOLD:		CORR. SCALING:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 10		TR. 20		SHOT		SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		LINE GROUPS	TR 1-20
8774	523218	496			110	105			1-1 SP868 → 890 (2)		
8775		497			110	105			1-9 SP869 → 881		
8776		498			110	105			1-14 SP870 → 882		
8777		499			110	105			1-25 SP871 → 883		
8778		500			110	105			1-33 SP872 → 884		
8779		501			110	105			1-41 SP873 → 885		
8780		502			110	105			1-49 SP874 → 886		
8781		503			110	105			1-9 SP875 → 887 (3)		
8782		504			110	105			1-14 SP876 → 888		

LAND SEISMIC RECORDING LOG

		CLIENT: HUSKY NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO.: 68E		
PARTY NO.: 1184		INST. EMG.: BRINER		TT 2	DATE: MO 2 DAY 16 YR 77		
NO. BYTES IN HEADER REC.: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254		REC. HRS: 14	
INSTRUMENT (9-TRACK)		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS X <input type="checkbox"/> OTHER		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: 36 db	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: 1-96		AUXILIARY DATA: 1 2 3 4 5		INPUT IMPEDANCE: _____ ohms	
PARAMETER		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 8 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: _____	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		TRIP SENS: 42 db		POLARITY CONVENTION: _____	
CFS I		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE MOVE		NO. OF POSITIONS: 1	
RECEIVER		TYPE: GEOSPACE 200 101A		PATTERN: INLINE		NO. OF ELEMENTS: 18	
SPREAD		NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 1760'	

DIAGRAMS/MISC. INFORMATION :

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD			REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 1-48	TR 48-96
883	5222	512			110	105				1-1	877 → 889 ①			
884		513			110	105				1-9	878 → 890			
885		514			110	105				1-17	879 → 891			
886		515			110	105				1-25	880 → 892			
887		516			110	105				1-33	881 → 893			
888		517			110	105				1-17	882 → 894 ②			
889		518			110	105				1-25	883 → 895			
890		519			110	105				1-33	884 → 896			
891		520			110	105				1-41	885 → 897			
892		521			110	105				1-49	886 → 898			
893					110	105				1-9	884 → 899 ③			

LAND SEISMIC RECORDING LOG

CLIENT: NISKY NPR OPERATION		PROSPECT: NPR-4		AREA: NORTH SLOPE ALASKA		LINE NO.: 68E	
PARTY NO.: 1184		INST. ENG.: KRINER		REC HRS.: 14		DATE: MO. 2 DAY 16 YR 77	
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS	<input type="checkbox"/> DFS III	<input checked="" type="checkbox"/> 9 TRACK	<input type="checkbox"/> GAPPED	<input type="checkbox"/> 356 BPI
	<input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> EVENTS	<input type="checkbox"/> DFS IX	<input type="checkbox"/> 2) TRACK	<input type="checkbox"/> UNGAPPED	<input type="checkbox"/> 800 BPI
NO. BYTES IN HEADER REC.: 228	NO. BYTES IN RECORD ID.: 2	NO. BYTES PER SCAN: 254		RECORD NUMBERS: DEC. OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: ohms.	
FIELD TRACE NOS.: 1-96	AUXILIARY DATA: <u>W FB</u>		AUXILIARY CHANNEL NOS.: 1 2 3 4 5		PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input checked="" type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
DATA CHANNEL NOS.: 1-96	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> DIFF		FILTERS: FREQ. 8 LO CUT 18 HZ SLOPE 18		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	TRIP SENS.: 42 db		POLARITY CONVENTION: <input checked="" type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	RECORD REJECTION:		NOISE REDUCTION: NOISE THRESHOLD.		CORR. SCALING: R.C.U. NORM./ALT SW.	
TYPE STACK:	GATE LENGTH:	PATTERN: <u>INLINE HOLE</u>		NO. OF POSITIONS: 1		LATERAL SPACING:	
TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		CHG./HOLE: 10/165	HOLE DEPTH: 105	INLINE SPACING:		STAGGER:	
TYPE: <u>GRANDSPACE 200.0MHz</u>		PATTERN: <u>INLINE</u>		NO. OF ELEMENTS: 18		INCLINE SPACING: 25'	
CONNECTION: <u>SERIES</u>		RESISTANCE:		STAGGER:		LENGTH: 425'	
NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 11460'		FOLD: 6	
OFFSET GROUP 1: 10450'		OFFSET GROUP 1: 110'		OFFSET GROUP 1: 110'		DIRECTION OF PROGRESSION: WEST	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT		SPREAD		REMARKS:	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH	LINE GROUPS	TR 1-48	TR 24-96	REC.	REC.
893	524	524			140	105				1-9	887 → 899					
894		524			140	105				1-14	888 → 900					
895		525			140	105				1-25	889 → 901					
896		526			140	105				1-33	890 → 902					

LAND SEISMIC RECORDING LOG

		CLIENT: NUSKY NPR OPERATION		PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA		LINE NO.: 68E		
PARTY NO.: 1184		INST. ENG.: BRINER		REC NOS.: 11.5		TT: 1.5	DATE: 2-DAY 17-YR 77		
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (M1) <input type="checkbox"/> 712 BPI
NO. BYTES IN HEADER REC.: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms	
FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)		AUXILIARY DATA: 1 2 3 4 5		AUXILIARY CHANNEL NOS.: 1 2 3 4 5			
RECORD LENGTH: 8 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ma. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ma. <input type="checkbox"/> 4 ms.		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 12		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 7a db		TRIP SENS.: 42 db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		CORR. SCALING:	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE NOTE		NO. OF POSITIONS: 1		INLINE SPACING:		LATERAL SPACING:	
		CHO/HOLE: 110		HOLE DEPTH: 105		SWEEP POSITION:		SWEEP START:	
						SWEEP END:		SWEEP TAPER:	
RECEIVER TYPE: GEOSPACE 200 10Hz		PATTERN: INLINE		NO. OF ELEMENTS: 18		INCLINE SPACING: 25'		LATERAL SPACING:	
CONNECTION: SERIES		RESISTANCE: _____ ohms		STAGGER:		LENGTH: 425'		WIDTH: _____	
NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 1460'		FOLD: 6+		DIRECTION OF PROGRESSION: WEST	
OFFSET GROUP 1: 10450'		OFFSET GROUP 48 110'		OFFSET GROUP 49 110'		OFFSET GROUP 48/96 10450'		LEADING GROUP: 96	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				DIR.	CDP SWITCH	SPREAD LINE GROUPS	REMARKS	CORR. STAGE			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET					TR 1-41	TR 42-96	TR 1-41	TR 42-96
897	52380	534			110	105				1-5	891-1 TO 902-8	FILE # 527 → 533 TESTS				
898		535			110	105				1-13	892-1 TO 903-8					
899		536			110	105				1-21	893-1 TO 904-8					
900		537			110	105				1-29	894-1 TO 905-8					
901		538			110	105				1-1	895-1 TO 906-8					
902		539			110	105				1-9	896-1 TO 907-8					
903		540			110	105				1-17	897-1 TO 908-8					
904		541			110	105				1-25	898-1 TO 909-8					
905		542			110	105				1-9	899-1 TO 910-8					
906		543			110	105				1-17	900-1 TO 911-8					
907		544			110	105				1-25	901-1 TO 912-8					
908		545			110	105				1-33	902-2 TO 913-8					
					110	90						CHANGE TAPE				

LAND SEISMIC RECORDING LOG

	CLIENT: Husky NPR Operations	PROSPECT: NPR-4	AREA: North Slope, Alaska	LINE NO: 68F	
	PARTY NO: 1184	INST. ENG: Briner	Rec Hrs: 11.5 TT 1.5 Rec 10	DATE: MO 2 DAY 17 YR 77	

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: 3 SEG	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 320 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254		RECORD NUMBERS: DEC. OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: ohms	

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96 DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)	AUXILIARY DATA: TW PB SPS AUXILIARY CHANNEL NOS.: 1 2 5
--------------------------	---	--

PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL	MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE: 18	HI CUT HZ SLOPE: 72	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER	INITIAL GAIN: 36 db	TRIP SENS.: 42 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/>	NUMBERS ON MAG. TAPE: 1 2 5	DOWNBREAK: <input type="checkbox"/>	ON DISPLAY: <input type="checkbox"/>

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE	PATTERN: Single Hole	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	<input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	CHO/ HOLE: 110	HOLE DEPTH: 105'	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.



RECEIVER	TYPE: GeoSpace	PATTERN: INLine	NO. OF ELEMENTS: 18	INLINE SPACING: 25'	LATERAL SPACING:	STAGGER:	LENGTH: 425'	WIDTH:	LATERAL OFFSET:
	CONNECTION: Series	RESISTANCE: ohms							

SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760	FOLD: 6	DIRECTION OF PROGRESSION: West
	OFFSET GROUP 1: 10450	OFFSET GROUP 42: 110'	OFFSET GROUP 49: 110'	OFFSET GROUP 48/96: 10450	LEADING GROUP: 96

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1		TR. 2		SHOT						DIR.	CDP SWITCH	SPREAD	LINE GROUPS	REMARKS:	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	IN	OUT						IN	OUT	IN	OUT		
1008	2522	28	2523	29	20	27	29	30	32	35	37	1-41	9038 to 9148	⑤	FILE # 546 DUMMY						



LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO.: 68E					
	PARTY NO.: 1184	INST. ENG.: W. R. R. R.	REC. MGR.: 16	DATE: 2-DAY 18-77					
			TT 3 REL 13						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: 5	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LQ) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI	(H) <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC.: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) 525 (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: _____		AUXILIARY CHANNEL NOS.: 1 2 3 4 5			
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE: 18	FREQ. 120 HZ SLOPE 72	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> DIRECT	TRIP SENS: 42 db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> ON MAG. TAPE <input type="checkbox"/> UPBREAK	DOWNBREAK ON DISPLAY: <input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1 IN 6 1/2 HOLE	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHO: _____	HOLE: 110	HOLE DEPTH: 100	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP. _____
RECEIVER	TYPE: GEOSPACE	PATTERN: 1 IN 6 1/2	NO. OF ELEMENTS: 18	INCLINE SPACING: 25'	LATERAL SPACING: _____	STAGGER: _____	LENGTH: 425'	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: SERIES	RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760	FOLD: 6	DIRECTION OF PROGRESSION: N-E-S				
	OFFSET GROUP 1: 10450'	OFFSET GROUP 48 : 110'	OFFSET GROUP 49 : 110'	OFFSET GROUP 96 : 10450'	LEADING GROUP: 96				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT					SPREAD					REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS					TR. 1-48	TR. 49-96	TR. 97-144
910	53281	553			NO	105				1-1	924-1 TO 915-8							
911		554			NO	105				1-9	925-1 TO 916-8							
912		557			NO	105				1-17	926-1 TO 917-8							
913		558			NO	95				1-25	927-1 TO 918-8							
914		559			NO	100				1-33	928-1 TO 919-8							
915		560			NO	100				1-5	929-1 TO 920-8							
916		561			NO	105				1-13	910-1 TO 921-8							
917		562			NO	105				1-21	911-1 TO 922-8							
918		563			NO	105				1-29	912-1 TO 923-8							
919		564			NO	105				1-37	913-1 TO 924-8							
920		565			NO	105				1-9	914-1 TO 925-8							
921		566			NO	105				1-17	915-1 TO 926-8							
922		567			NO	105				1-25	916-1 TO 927-8							


LAND SEISMIC RECORDING LOG

	CLIENT: USKY NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 08E	
PARTY NO: 1184		INST. ENG: BRINER		DATE: MO 2 DAY 19 YE 77	
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS. 1-96		AUXILIARY DATA: 1 2 3 4 5		GAIN CONSTANT: 36 db	
PARAMETER: RECORD LENGTH: 8 sec		SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms <input type="checkbox"/> 2 ms		FILTERS: FREQ. 8 LO CUT HZ SLOPE 18	
DISPLAY: MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: 36 db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	
CFS I: TYPE STACK: 8		GATE LENGTH: 40 db		NOISE REDUCTION: <input type="checkbox"/> COR. SCALING: <input type="checkbox"/>	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE		PATTERN: SINGLE NOLE		NO. OF POSITIONS: 1	
RECEIVER: TYPE: 200 SPIKE 200 PWA		PATTERN: INLINE		NO. OF ELEMENTS: 18	
SPREAD: NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 1460'	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 10		TR. 10		SHOT				SPREAD				REMARKS	CORE STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			TR 1-4	TR 44-50
920	523	520			140	105					1-19	919-1 to 930-8	①		
921		519			140	105					1-27	920-1 to 931-8			
922		520			140	105					1-5	921-1 to 932-8	②		
923		521			140	105					1-13	922-1 to 933-8			
924		522			140	105					1-21	923-1 to 934-8			
925		523			140	105					1-29	924-1 to 935-8			
926		524			140	105					1-37	925-1 to 936-8			
927		525			140	105					1-9	926-1 to 937-8	③		
928		526			140	105					1-17	927-1 to 938-8			
929		527			140	105					1-25	928-1 to 939-8			
930		528			140	105					1-33	929-1 to 940-8			
931		529			140	105					1-41	930-1 to 941-8			
932		530			140	105					1-49	931-1 to 942-8			



LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY NPR OPERATION	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 68E						
	PARTY NO: 1184	INST. ENG.: BRINER	REC. NRS.: REC NRS.	DATE: MO 2 DAY 20 YR 77						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 354 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 715 BPI <input type="checkbox"/> 1400 BPI
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36	db	INPUT IMPEDANCE:		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA:						
	DATA CHANNEL NOS.: 1-96			(ON MAG TAPE)						
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input checked="" type="checkbox"/> IFF <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	FREQ. 128	HI CUT HZ SLOPE 12	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DE FLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS: 42 db	RECORD REJECTION:	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY:		
CFS I	TYPE STACK:	GATE LENGTH:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM / ALT SW.				
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CRG/ HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:		
RECEIVER	TYPE: GEOSPAC 200 10 NA	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 25'	LATERAL SPACING:	STAGGER:	LENGTH: 425'	WIDTH:	LATERAL OFFSET:	
	CONNECTION:	RESISTANCE:	ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	OFFSET GROUP 48/96:	LEADING GROUP:			
	OFFSET GROUP 1:	OFFSET GROUP:	OFFSET GROUP:							

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. to		TR. to		SHOT				SPREAD				REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			TR 1-48	TR 49-96	TR 97-144	TR 145-192	
938	1251	328	58	17	22	23	26	27	29	30	35	37	1-3	932-1 TO 943-8				
939													1-11	933-1 TO 944-8				
940													1-19	934-1 TO 945-8				
941													1-27	935-1 TO 946-8				
942													1-35	936-1 TO 947-8				
															TAPES CHANGE			

LAND SEISMIC RECORDING LOG

			CLIENT: <u>WUSKY NPR OPERATION</u> PROSPECT: <u>NPR-4</u>						AREA: <u>NORTH SLOPE ALASKA</u> LINE NO: <u>68E</u>														
PARTY NO: <u>1184</u>			INST. ENG: <u>BRINER</u>			REC NRS: <u>REC NRS</u>			DATE: <u>MO 2 DAY 20 YR 77</u>														
INSTRUMENT (9-TRACK)			<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS			<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96			<input type="checkbox"/> ODDS EVENS			TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS X <input type="checkbox"/> OTHER			<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK			FORMAT: <u>SEG 5</u> <input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED			PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (M1) <input type="checkbox"/> 712 BPI		
			NO. BYTES IN HEADER REC: <u>228</u>			NO. BYTES IN RECORD ID: <u>2</u>			NO. BYTES PER SCAN: <u>2534</u>			RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.			GAIN CONSTANT: <u>36</u> db			INPUT IMPEDANCE: _____ ohms.					
CONFIGURATION (MAG TAPE)			FIELD TRACE NOS.: <u>1-96</u>						AUXILIARY DATA: <u>14/18</u> (3) (4) <u>18/25</u> (6) (7)														
			DATA CHANNEL NOS.: <u>1-96</u> (ON MAG TAPE)						AUXILIARY CHANNEL NOS.: <u>1 2 3 4 5</u>														
PARAMETER			RECORD LENGTH: <u>8</u> sec.			SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.			GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE			FILTERS: FREQ: <u>8</u> LO CUT HZ SLOPE <u>18</u> HI CUT HZ SLOPE <u>42</u> NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT											
DISPLAY			MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT			AMPLIFIER: <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT			INITIAL GAIN: <u>36</u> db			TRIP SENS: <u>42</u> db			POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE			PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE					
CFS I			TYPE STACK: _____			GATE LENGTH: _____			RECORD REJECTION: _____			NOISE REDUCTION: _____			NOISE THRESHOLD: _____			CORR. SCALING: _____ R.C.U. NORM / ALT SW: _____					
SOURCE			TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER			PATTERN: <u>SINGLE HOLE</u>			NO. OF POSITIONS: <u>1</u>			INLINE SPACING: _____			LATERAL SPACING: _____			STAGGER: _____					
			CHG/ HOLE: <u>110</u>			HOLE DEPTH: <u>105</u>			SWEEP POSITION: _____			SWEEP START: _____			SWEEP END: _____			SWEEP LENGTH: _____					
RECEIVER			TYPE: <u>CONDSPACE 200 10Hz</u>			PATTERN: <u>INLINE</u>			NO. OF ELEMENTS: <u>18</u>			INLINE SPACING: <u>25'</u>			LATERAL SPACING: _____			STAGGER: _____					
			CONNECTION: <u>SERIES</u>			RESISTANCE: _____			STAGGER: _____			LENGTH: <u>475'</u>			WIDTH: _____			LATERAL OFFSET: _____					
SPREAD			NO. OF GROUPS: <u>96</u>			GROUP INTERVAL: <u>220'</u>			SHOTPOINT INTERVAL: <u>1400'</u>			FOLD: <u>64</u>			DIRECTION OF PROGRESSION: <u>WEST</u>								
			OFFSET GROUP 1: <u>10450'</u>			OFFSET GROUP <u>18</u> : <u>110'</u>			OFFSET GROUP <u>19</u> : <u>110'</u>			OFFSET GROUP <u>40/96</u> : <u>10450'</u>			LEADING GROUP: <u>96</u>								

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT					SPREAD		REMARKS:	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS		SET	TR 1-48	TR 49-96	REC
<u>940</u>	<u>2533203</u>	<u>68E</u>			<u>160</u>	<u>105</u>				<u>1-35</u>	<u>936-1 to 944-8</u>	<u>10</u>				
<u>943</u>		<u>68E</u>			<u>160</u>	<u>105</u>				<u>1-33</u>	<u>934-1 to 948-8</u>					
					<u>END OF LINE</u>											