



LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY - NPR OPERATIONS	PROSPECT: NRR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 73						
PARTY NO: 1773		INST. ENG: Left Camp TRAVEL 4		DATE: total hrs 14						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAT: SEG. <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC.: 228		NO. BYTES IN RECORD ID.: 2		NO. BYTES PER SCAN.: (254)		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: (1) SURF SURVEY TRACKING			AUXILIARY CHANNEL NOS.: 1 2 3			
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 18 Hz		LO CUT HZ SLOPE: 18	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
PLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS.: _____ db	POLARITY CONVENTION: PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY: <input type="checkbox"/> ON DISPLAY		
TYPE STACK:	GATE LENGTH: _____		RECORD REJECTION: _____	NOISE REDUCTION: _____		NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/HOLE:	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____		
SERVER	TYPE: _____		PATTERN: _____	NO. OF ELEMENTS: 18	INCLINE SPACING: 25	LATERAL SPACING: _____				
	CONNECTION: _____		RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: 4.25	WIDTH: _____	LATERAL OFFSET: _____			
HEAD	NO. OF GROUPS: _____		GROUP INTERVAL: 200'	SHOTPOINT INTERVAL: 880'	FOLD: (12.5)	DIRECTION OF PROGRESSION: _____				
	OFFSET GROUP 1: 10450		OFFSET GROUP: 110'	OFFSET GROUP 2: 110'	OFFSET GROUP 3: 10450	LEADING GROUP: _____				

GRAMS/MISC. INFORMATION:
tape 696550 SPS 1-11

TR. NO.	TR. TO	TR. NO.	TR. TO	SHOT				DIR.	CDP SWITCH	SPREAD	REMARKS	CORR. STACK			
				SIZE	DEPTH	NO.	OFFSET					TR. 1-48	TR. 49-96	TR. 1-48	TR. 49-96
50	13	12	14	11	11	11	11				<i>2.2" ...</i>				
51	13	12	14	11	11	11	11				<i>2.2" ...</i>				
52	13	12	14	11	11	11	11				<i>2.2" ...</i>				
53	13	12	14	11	11	11	11				<i>2.2" ...</i>				
54	13	12	14	11	11	11	11				<i>2.2" ...</i>				
55	13	12	14	11	11	11	11				<i>2.2" ...</i>				
56	13	12	14	11	11	11	11				<i>2.2" ...</i>				
57	13	12	14	11	11	11	11				<i>2.2" ...</i>				
58	13	12	14	11	11	11	11				<i>2.2" ...</i>				
59	13	12	14	11	11	11	11				<i>2.2" ...</i>				
60	13	12	14	11	11	11	11				<i>2.2" ...</i>				



LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: WPR-4	AREA: Pat-4 ALASKA	LINE NO: 2 73						
PARTY NO: 1173		INST. ENG: TRAVEL 6 TOTAL 12		DATE: MO 1 DAY 21 YR 77						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 7-24 & 25-46 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u>	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: <u>278</u>		NO. BYTES IN RECORD ID: <u>2</u>		NO. BYTES PER SCAN: <u>254</u>		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: _____ ohms.	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>			AUXILIARY DATA: <u>(1) Sync (2) Sync (3) Timing</u>			AUXILIARY CHANNEL NOS.: <u>1 2 3</u>			
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> JFF	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>8</u>	LO CUT HZ SLOPE: <u>cut 18</u>	HI CUT HZ SLOPE: <u>128</u>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input checked="" type="checkbox"/> AGC	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORE SCALING:	R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Triangle Hole</u>	NO. OF POSITIONS: <u>1</u>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	TYPE: <u>Geospace 200 - 10 Hz</u>	PATTERN: <u>Incline Single Hole</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>25'</u>	LATERAL SPACING: <u>400'</u>	STAGGER:	LENGTH: <u>12 F</u>	WIDTH:	LATERAL OFFSET:	
SPREAD	CONNECTION: <u>Series Parallel</u>	RESISTANCE: _____ ohms	STAGGER:	FOLD: <u>12 F</u>	DIRECTION OF PROGRESSION:	LEADING GROUP:				
NO. OF GROUPS: <u>96</u>		GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>880</u>	OFFSET GROUP: <u>110'</u>	OFFSET GROUP: <u>10450</u>					
OFFSET GROUP 1: <u>10450'</u>		OFFSET GROUP: <u>110'</u>	OFFSET GROUP: <u>110'</u>	OFFSET GROUP: <u>110'</u>	OFFSET GROUP: <u>10450</u>					

DIAGRAMS/MISC. INFORMATION:



SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD				REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			HT.	REC.	HT.	REC.	
1	1213	14	17	2223	20	27	29	30	32	33	37							
2	1213	14			1111	11	15	11	22	N/E	21	Change used	SP	Daily Logs - 025 -				
3		028									17			File - 031 - NG (Feb-35) 116				
4		028												Two Log books down, 3rd string				
5														on Recorder - 3rd #				
6														SP # 4 + 5 Skipped. 037 missing				
7																		
8																		
9																		
10																		
11																		
12																		
13																		
14																		
15																		
16																		
17																		
18																		
19																		
20																		
21																		
22																		
23																		
24																		
25																		
26																		
27																		
28																		
29																		
30																		
31																		
32																		
33																		
34																		
35																		
36																		
37																		
38																		
39																		
40																		
41																		
42																		
43																		
44																		
45																		
46																		
47																		
48																		
49																		
50																		

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky-NPR OPERATIONS</u>	PROSPECT: <u>NLR 4</u>	AREA: <u>NORTH SLOPE</u>	LINE NO: <u>73</u>	
PARTY NO:		INST. ENG:		DATE: <u>1 DAY 24 YR 77</u>	
<u>RE-RECORD 11 HRS 13 TOTAL 2 TRAVEL</u>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 24 & 25-48 <input type="checkbox"/> 48 & 49-96	ODDS EVENS	TYPE <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK
NO. BYTES IN HEADER REC: <u>278</u>		NO. BYTES IN RECORD ID: <u>2</u>		NO. BYTES PER SCAN: <u>254</u>	
CONFIGURATION (MAG TAPE)			AUXILIARY DATA:		
FIELD TRACE NOS.: <u>1-96</u>			AUXILIARY CHANNEL NOS.:		
DATA CHANNEL NOS.: <u>1-96</u>			(ON MAG TAPE)		
PARAMETER		RECORD LENGTH: <u>3</u> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	
DISPLAY		MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <u>1.0E2</u> db	
CFS I		TYPE STACK:		GATE LENGTH:	
SOURCE		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>SINGLE HOLE</u>	
RECEIVER		TYPE: <u>GEOSCOPE 200-104</u>		PATTERN: <u>IN LINE</u>	
SPREAD		NO. OF GROUPS: <u>96</u>		GROUP INTERVAL: <u>220 FT.</u>	
DIAGRAMS/MISC. INFORMATION		<u>LINE 73</u>			

SHOTPOINT	TR. 1		TR. 10		SHOT					SPREAD		REMARKS	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DHR.	CDP SWITCH	LINE GROUPS		TR 1-10	TR 11-20	TR 21-30	TR 31-40			
16	5232419	13	17	2223	26	27	29	30	32	35	39	N	29	1-96	7	FILE # 33-36 DAILY TESTS CABLE TROUBLE DRAWS ON LINE			
17													25						
18													21						
19													17			Initial Run 2			
20													13						
21													9						
22	5233340															All mag.			
23													29						
24													25						
25													21						
26													11						

LAND SEISMIC RECORDING LOG

	CLIENT: Husky NPRO OPERATIONS	PROSPECT: APR 4	AREA: NORTH SLOPE	LINE NO.: 73					
PARTY NO.: 117B		INST. ENG.: RECORDING HOURS total 13 1/2 hrs		DATE: 1 DAY 25 YR					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: 0	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI	
	NO. BYTES IN HEADER REC.: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: 6 DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 30 db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: 0 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> TRF	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: 8	LO CUT HZ SLOPE: OFF	FREQ. 128 HZ CUT	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 1002 db	TRIP SENS: 7 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: GEOSPACE 20D - 10Hz	PATTERN: INLINE	NO. OF ELEMENTS: 18	INCLINE SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	CONNECTION: SERIES - PARALLEL	RESISTANCE: 450 ohms	SHOTPOINT INTERVAL: 800 FT.	FOLD: 12 F	DIRECTION OF PROGRESSION: NORTH	LEADING GROUP: # 1			
DIAGRAMS/MISC. INFORMATION:									

SHOTPOINT NO.	TR. 1 to 96		TR. _____ to _____		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48	TR 49-96	REC.	REC.
16	52	3228			56	110	105	4	1	1	37	1-96	19				
17					57	110	105	4			33						
18					58	110	105	4			29						
19					59	110	105	4			25						
20					60	110	105	4			21						
21					61	110	105	4			17						
22					62	110	105	4			13						
23					63	110	105	4			9						
24					64	110	105	4			29						
25					65	110	105	4			25						
26					66	110	105	4			21						
27					67	110	105	4			17						
28					68	110	105	4			13						
29					69	110	105	4			9						
30					70	110	105	4			5						
31					72	110	105	4			1						



LAND SEISMIC RECORDING LOG

	CLIENT: <i>WASKY NBR OPERATIONS</i>	PROSPECT: <i>NPR 4</i>	AREA: <i>NORTH SLOPE</i>	LINE NO.: <i>73</i>	
PARTY NO.: <i>1172</i>		INST. ENG.: <i>13 1/2 total</i>		DATE: <i>1 DAY 26 YR 77</i>	
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX		FORMAT: <i>B</i>	
NO. BYTES IN HEADER REC.: <i>228</i>		NO. BYTES IN RECORD ID.: <i>2</i>		NO. BYTES PER SCAN: <i>254</i>	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: <i>1-96</i>		DATA CHANNEL NOS.: <i>1-96</i>		AUXILIARY DATA: AUXILIARY CHANNEL NOS.:	
PARAMETER RECORD LENGTH: <i>8</i>		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	
DISPLAY MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <i>10A2</i>		TRIP SENS.: <i>7</i>	
CFS I TYPE STACK:		GATE LENGTH:		RECORD REDUCTION:	
SOURCE TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <i>SINGLE HOLE</i>		NO. OF POSITIONS: <i>1</i>	
RECEIVER TYPE: <i>3 FOSPAC 208 10Hz</i>		PATTERN: <i>INLINE</i>		NO. OF ELEMENTS: <i>18</i>	
SPREAD NO. OF GROUPS: <i>96</i>		GROUP INTERVAL: <i>220 ft</i>		SHOTPOINT INTERVAL: <i>880 ft</i>	
OFFSET GROUP 1: <i>10450 ft</i>		OFFSET GROUP 48: <i>110 ft</i>		OFFSET GROUP 49: <i>110 ft</i>	

DIAGRAMS/MISC. INFORMATION:



SHOTPOINT	TR. 1 to 96		TR. to		SHOT				SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-48
32	523321				79	110	105	11	N	45	1-96		
33					80	110	105	11		41			
34					81	110	105	11		37			
35					82	110	105	11		33			
36					83	110	105	11		29			
37					84	110	105	11		25			
38					85	110	105	11		21			
39					86	110	105	11		11			
40					87	110	105	11		37			
41					88	110	105	11		37	WRONG CDP		
42					89	110	105	11		25	SETTING		
43					90	110	105	11		17			
44					91	110	105	11		9			

LAND SEISMIC RECORDING LOG

	CLIENT: <u>WILKINS OAR OPERATIONS</u>	PROSPECT: <u>NOR 4</u>	AREA: <u>WATER SHORE</u>	LINE NO.: <u>73</u>	
PARTY NO.: <u>1173</u>		INST. ENG.: <u>John B. Lee</u>		DATE: <u>1 DAY 27 YR 77</u>	
INSTRUMENT		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	
NO. BYTES IN HEADER REC: <u>228</u>		NO. BYTES IN RECORD ID: <u>2</u>		GAIN CONSTANT: <u>36</u> db	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: <u>1-96</u>		AUXILIARY DATA:	
DATA CHANNEL NOS.: <u>1-96</u>		(ON MAG TAPE)		AUXILIARY CHANNEL NOS.:	
PARAMETER		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms		FILTERS: <u>8</u> LO CUT HZ SLOPE <u>18</u> HI CUT HZ SLOPE	
DISPLAY		INITIAL GAIN: <u>101.2</u> db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	
CFS I		GATE LENGTH: <u>100</u>		NOISE REDUCTION: <input type="checkbox"/> CORR. SCALING: <input type="checkbox"/>	
SOURCE		PATTERN: <u>SINGLE</u>		NO. OF POSITIONS: <u>18</u>	
RECEIVER		CONNECTION: <u>SERIES - PARALLEL</u>		RESISTANCE: <u>450</u> ohms	
SPREAD		NO. OF GROUPS: <u>96</u>		SHOTPOINT INTERVAL: <u>1760 FT</u>	
DIAGRAMS/MISC. INFORMATION:		CHG/ HOLE: <u>110</u>		HOLE DEPTH: <u>105</u>	
		PATTERN: <u>INLINE</u>		NO. OF ELEMENTS: <u>18</u>	
		GROUP INTERVAL: <u>220 FT</u>		SHOTPOINT INTERVAL: <u>1760 FT</u>	
		OFFSET GROUP 1: <u>10450 FT</u>		OFFSET GROUP 19: <u>110 FT</u>	

SHOTPOINT	TR. 1 to 76		TR. to		SHOT			SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TR 1-24	TR 25-48	TR 49-72
45	523322				199	110	105	1	1	43	1-76				
46					199	110	105	1	1	35					
47					101	110	105	1	1	27					
48	523322				102	110	105	1	1	19					
49					104	110	105	1	1	11					
50					105	110	105	1	1	45					
51					106	110	105	1	1	37					
52					107	110	105	1	1	29					
53					108	110	105	1	1	2					



LAND SEISMIC RECORDING LOG

	CLIENT: Husky NBR OPERATIONS	PROSPECT: NPR 4	AREA: NORTH SLOPE	LINE NO: 73	
PARTY NO. 1173		INST. ENG.		DATE: 1 DAY 28 YE 77	
INSTRUMENT			TOTAL HOURS = 13		
<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> ODDS EVENS			TYPE: <input type="checkbox"/> DFS <input checked="" type="checkbox"/> DFS <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK		
NO. BYTES IN HEADER REC: 228 NO. BYTES IN RECORD ID: 2 NO. BYTES PER SCAN: 254			RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT. GAIN CONSTANT: 36 db INPUT IMPEDANCE: _____ ohms.		
FIELD TRACE NOS.: 1-96 DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____		
RECORD LENGTH: 8 sec. SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.			GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> _____		
DISPLAY: <input checked="" type="checkbox"/> RUC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER DIRECT			FILTERS: FREQ. 8 LO CUT HZ SLOPE OUT HI CUT HZ SLOPE _____ POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT DOWNBREAK ON MAG. TAPE <input type="checkbox"/> UPBREAK ON DISPLAY		
CFS I			R.C.U. NORM/ALT SW.		
SOURCE			RECEIVER		
TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER			TYPE: GEOSPACE 200 10 HZ CONNECTION: SERIES-PARALLEL		
PATTERN: SINGLE CHG/ HOLE: 110 HOLE DEPTH: 105			PATTERN: INLINE RESISTANCE: 450 ohms		
NO. OF POSITIONS: _____ SWEEP POSITION: _____			NO. OF ELEMENTS: 18 STAGGER: _____		
INLINE SPACING: _____ SWEEP START: _____			LATERAL SPACING: _____ SWEEP END: _____		
STAGGER: _____ SWEEP LENGTH: _____			LENGTH: _____ SWEEP TAPER: _____		
WIDTH: _____ PHASE COMP: _____			LATERAL SPACING: _____ WIDTH: _____ LATERAL OFFSET: _____		
SPREAD			DIRECTION OF PROGRESSION: NORTH		
NO. OF GROUPS: 96 OFFSET GROUP 1: 10450 ft.			GROUP INTERVAL: 220 ft. OFFSET GROUP 18: 110 ft.		
SHOTPOINT INTERVAL: 1760 ft. OFFSET GROUP 19: 110 ft.			FOLD: GF OFFSET GROUP 48/96: _____		
LEADING GROUP: #1					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT #	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD			REMARKS:	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 1-48	TR 49-96
54	523322				115	110	105	11		49	1-96	57		
55					116	110	105	11		41				
56					117	110	105	11		33				
57					118	110	105	11		25				
58					119	110	105	11		17				
59					120	110	105	11		9				
60					121	110	105	11		1				
61					122	110	105	11		41		63		
62					123	110	105	11		33				
63	523323				124	110	105	11		25				
64					125	110	105	11		17				
65					126	110	105	11		9				
66					127	110	105	11		1				

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-4	AREA: NORTH SLOPE	LINE NO.: 73				
	PARTY NO.: 1173	INST. ENG.:	Hours: TOTAL=12 1/2	DATE: 1 DAY 28 YR 77				
			TRAVEL = 2 hrs					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-24 & 49-96	ODS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> ORGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI
	NO. BYTES IN HEADER REC.: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: D-DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms	(1) (2) (3) (4) (5) (6) (7)	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	DATA CHANNEL NOS.: 1-96	(ON MAG TAPE)	AUXILIARY DATA:	AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> OFF <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE OLT	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 1 or 2 db	TRIP SENS: 7 db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	NUMBERS ON ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGER:	LENGTH:	WIDTH:
		CHG/ HOLE: 1/10	HOLE DEPTH: 105	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.:
RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INCLINE SPACING:	LATERAL SPACING:	STAGER:	LENGTH:	WIDTH:
	CONNECTION:	RESISTANCE:	ohms	STAGER:	LENGTH:	STAGER:	LENGTH:	WIDTH:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	OFFSET GROUP 48/96:	DIRECTION OF PROGRESSION: NORTH	LEADING GROUP: #1	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 96		TR 10 to 22		TR 23 to 35		TR 36 to 48		TR 49 to 61		TR 62 to 74		TR 75 to 87		TR 88 to 100		CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS	REMARKS	REEL	REC.	REEL	REC.	REEL	REC.
67	523327				140	110	105	11		47	1-96	FILE #130-137 DAILY TEST TEST TIME DATA						
68					149	110	105	11		39								
69					142	110	105	11		31								
70					143	110	105	11		23								
71					144	110	105	11		15		Laying cable 1030 -> 1130						
72					146	110	105	11		7								
73					146	110	105	11		47								
74					147	110	106	11		39								
75					148	110	105	11		31								
76					149	110	106	11		23								
77					150	110	105	11		15								
78					151	110	105	11		49								
79	523328				153	110	105	11		41		FILE #152 8sec ALL ONES						
80					154	110	105	11		33								
81					155	110	105	11		25								
82					156	110	105	11		17								
83					157	110	105	11		9								

Tape No.
 * ~~File~~ WAS NOT CHANGED
 ON CONSTANT SWITCHES
 FOR REEL # 523324

