

LAND SEISMIC RECORDING LOG

	CLIENT: Husky OPR OPERATIONS	PROSPECT: WPR-4	AREA: NORTH SLOPE	LINE NO.: 78						
	PARTY NO.: 173	INST. ENG.:	Total Hours 13	2hrs TRAVEL	DATE: 1 DAY 31 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input checked="" type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 300 db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> DIFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: 8 LO CUT HZ SLOPE	FREQ. 128 HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> BUT	R.C.U. NORM/ALT SW.			
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEPLOY <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 20 db	TRIP SENS.: 1 db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE:	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	<input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:				
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLES	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CHG/ HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.		
RECEIVER	TYPE: GEOSPAC 200 10HZ	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION: SERIES-PARALLEL	RESISTANCE: 450 ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220 ft.	SHOTPOINT INTERVAL: 1760 ft.	FOLD: 6F	DIRECTION OF PROGRESSION: SOUTH					
	OFFSET GROUP 1: 10450 ft.	OFFSET GROUP 48: 110 ft.	OFFSET GROUP 49: 110 ft.	OFFSET GROUP 48/96:	LEADING GROUP: #96					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 no 96		TR. 10		SHOT								SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	FILE #	TR 1-48	TR 49-96		REC.	HT.	REC.	HT.
1	5233226				87	110	105	11		1	1-96	4	FILE # 001 8 SEC ALLONES						
2					91	110	105	11	100 W	9			FILE # 002-006 DAILY TESTS						
3					112	110	105	11		17			FILE # 007 TEST TIME BREAK						
4					113	110	105	11		25			FILE # 10, 11 OMIT						
5					141	110	105			33									
6					151	110	105			41									
7					161	110	105			49									

LAND SEISMIC RECORDING LOG

	CLIENT: Husky NPR OPERATIONS	PROSPECT: NPR-4	AREA: NORTH SLOPE	LINE NO.: 78						
	PARTY NO.: 1173	INST. ENG.: Total hours 13	TRAVEL: 2 hrs			DATE: MO 2 DAY 1 YR 77				
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI	<input type="checkbox"/> 800 BPI	<input type="checkbox"/> 1500 BPI
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA:						
	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)			AUXILIARY CHANNEL NOS.:						
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: 8 Hz SLOPE	LO CUT: _____ Hz	HI CUT: 28 Hz SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 2 db	TRIP SENS: 7 db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____		NUMBERS ON ON MAG. TAPE		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:		R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DIAPHRAGM <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CHG/ HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.		
RECEIVER	TYPE: GEOSPACE 200 10Hz	PATTERN: INLINE	NO. OF ELEMENTS: 18	INCLINE SPACING:		LATERAL SPACING:		LATERAL OFFSET:		
	CONNECTION: SERIES PARALLEL	RESISTANCE: 450 ohms	STAGGER:	LENGTH:		WIDTH:		LATERAL OFFSET:		
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220 ft.	SHOTPOINT INTERVAL: 1760 ft.	FOLD: 6F	DIRECTION OF PROGRESSION: SOUTH			LEADING GROUP: # 96		
	OFFSET GROUP 1: 10450 ft.	OFFSET GROUP 48 : 110 ft.	OFFSET GROUP 49 : 110 ft.	OFFSET GROUP 48/96 :						

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 96		TR. 10 to		SHOT				SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR. 1-18
8	523026	15	17	22/23	24	10	105	11		3	1-96		
9					25	10	105	11		11			
10					26	10	105	11		19			
11					27	10	105	11		27			
12					28	10	105	11		17		13	
12					29	10	105	11		25			
14					30	10	105	11		33			
15	523326	17			32	10	105	11		41		FILE # 31 8 SEC ALL ONES	
16					33	10	105	11		49			
17					34	10	105	11		9		19	
18					35	10	105	11		17			
19					36	10	105	11		25			
20					37	10	105	11		33		PICKING UP CAMP NOISE	
21					38	10	105	11		41			
22					39	10	105	11		49			

LAND SEISMIC RECORDING LOG

	CLIENT: Husky NPR OPERATIONS	PROSPECT: NPR-4	AREA: NORTH SLOPE	LINE NO.: 78	
	PARTY NO.: 1173	INST. ENG.:	Total Hrs 9	TRAVEL 2	
				DATE: MO 2 DAY 3 YR 77	

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> ODDS EVENS	TYPE:	<input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> DFS X <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY:	(L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
(9-TRACK)	NO. BYTES IN HEADER REC.: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE:	ohms.

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	AUXILIARY DATA:
	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)	AUXILIARY CHANNEL NOS.:

PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 8 ms.	GAIN MODE: <input checked="" type="checkbox"/> TPP <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> DGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	TRIP SENS.: 7 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBEAR <input type="checkbox"/> UPBEAR <input type="checkbox"/> ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:

SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CHG/ HOLE: 110	HOLE DEPTH: 185	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.

RECEIVER	TYPE: GEOSACE 200 10 HZ	PATTERN: INLINE	NO. OF ELEMENTS: 18	INCLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: SCALES - PARALLEL	RESISTANCE: 450 ohms	STAGGER:						

SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220 FT	SHOTPOINT INTERVAL: 1760 FT	FOLD: 6P	DIRECTION OF PROGRESSION: SOUTH
	OFFSET GROUP 1: 10450 FT	OFFSET GROUP 41 : 110 FT	OFFSET GROUP 41 : 110 FT	OFFSET GROUP 48/96:	LEADING GROUP: #96

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 96		TR. to		SHOT					SPREAD			REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SEP		TR 1-41	TR 42-96
23			52	324	42	110	105	11		9	1-96	25	FILE #40 8 SEC ALL ONES / FILE #41 TEST BREAK		
24					43	110	105	11		17			CHANGED INITIAL GAIN to 12 db		
25					44	110	105	11		35			TRIP DELAY 1/2 SEC.		
26					48	110	105	11		33			ANOTHER SHOT IN AREA DURING		
27					50	110	105	11		41			(FILE #44 SYNC ERROR) SHOT #25		
													FILE #45 8 SEC ALL ONES		
													46 8 SEC TEST CAL.		
													47 8 SEC " "		
													48 8 SEC " "		

LAND SEISMIC RECORDING LOG



	CLIENT: Husky NPR OPERATIONS	PROSPECT: NPR 4	AREA: NORTH SLOPE	LINE NO: 78						
	PARTY NO: 1173	INST. ENG:	TOTAL HOURS: 13	TRAVEL: 3		DATE: MO 2 DAY 4 YR 77				
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 712 BPI	(12) <input type="checkbox"/> 800 BPI (13) <input checked="" type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96				AUXILIARY DATA:					
	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)				AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: 8 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ: 8	LO CUT HZ SLOPE	FREQ: 128	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input checked="" type="checkbox"/> DIRECT	INITIAL GAIN: 4 db	TRIP SENS: 7 db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SAMPLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CHG/ HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:		
RECEIVER	TYPE: GEOSPACE 200 10HZ	PATTERN: INLINE	NO. OF ELEMENTS: 18	INCLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION: SERIES-PARALLEL	RESISTANCE: 450 ohms								
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220 ft.	SHOTPOINT INTERVAL: 1760 ft.	FOLD: 6F	DIRECTION OF PROGRESSION: SOUTH	LEADING GROUP: #96				
	OFFSET GROUP 1: 10450 ft.	OFFSET GROUP 18: 110 ft.	OFFSET GROUP 49: 110 ft.	OFFSET GROUP 96: _____						

DIAGRAMS/MISC. INFORMATION:

OMIT FILE # 9002-9004

SHOTPOINT	TR. 1 to 96		TR. 1 to 96		SHOT				SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH		LINE GROUPS	TR 1-24	TR 25-48	TR 49-72
28	523327				67	10	105	11		1	1-96				
29					58	10	105	11		9					
30					69	10	105	11		17					
31					60	10	105	11		25					
32					61	10	105	11		33					
33					62	10	105	11		41					
34					63	10	105	11		1					
35					64	10	105	11		9					
36	523328				65	10	105	11		17					
37					66	10	105	11		25					
38					67	10	105	11		33					
39					68	10	105	11		41					
40					69	10	105	11		49					
41					70	10	105	11		33					
42					71	10	105	11		41					
43					72	10	105	11		49					
					73	10	105	11							

LAND SEISMIC RECORDING LOG

	CLIENT: Husky NPR OPERATIONS	PROSPECT: NPR-4	AREA: NORTH SLOPE	LINE NO.: 78	
	PARTY NO.: 1173	INST. ENG.:	Total Hours 14 TRAVEL 3	DATE: MO 2 DAY 5 YR 77	
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	FORMAT: B
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)		AUXILIARY DATA:	
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: 2 sec.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL	FILTERS: 8 FREQ.	LO CUT HZ SLOPE: 128
DISPLAY	MODE: <input checked="" type="checkbox"/> AOC <input type="checkbox"/> DEFOAT	AMPLIFIER: <input type="checkbox"/> DIRECT	TRIP SENS: 7 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	HI CUT HZ SLOPE: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:
	CHG/HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:
RECEIVER	TYPE: (AEROSPACE 200) NAZ	PATTERN: INLINE	NO. OF ELEMENTS: 18	INCLINE SPACING:	LATERAL SPACING:
	CONNECTION: SERIES-PARALLEL	RESISTANCE: 450 ohms	STAGGER:	LENGTH:	WIDTH:
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220 ft.	SHOTPOINT INTERVAL: 1760 ft.	FOLD: 6F	DIRECTION OF PROGRESSION: SOUTH
	OFFSET GROUP 1: 10450 ft	OFFSET GROUP: 110 ft.	OFFSET GROUP: 49.	OFFSET GROUP 48/96:	LEADING GROUP: # 76

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1-96		TR. 10		SHOT			DIR.	CDP SWITCH	SPREAD	REMARKS #	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.					OFFSET	TR 1-28	TR 29-40	TR 41-52	TR 53-64
44	523328				81	114	105	1	9	1-96	46					
45					82	85	105	1	17							
46					83	110	105	1	23							
47					84	85	105	1	33							
48					85	110	105	1	41							
49					86	85	105	1	1		52					
50	523329				88	110	105	1	9			FILE # 87 8 SEC ALLOWES				
51					89	85	105	1	17							
52					90	110	105	1	25							
53					91	85	105	1	9		55					
54					92	110	105	1	17							
55					93	85	105	1	25							
56					94	110	105	1	9		58	* SP# 56 TIMEBREAK INCORRECT RADIO INTERFERENCE				
57					95	85	105	1	17							
58					96	110	105	1	25							

LAND SEISMIC RECORDING LOG

	CLIENT: Husky NPA OPERATIONS	PROSPECT: NPA-4	AREA: NORTH SLOPE	LINE NO: 78					
	PARTY NO: 1173	INST. ENG:	Total Hours 1 1/2	TRAVEL 2 1/2		DATE: MO 2 DAY 7 YR 77			
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OFF	FILTERS: FREQ. 8	LO CUT <input checked="" type="checkbox"/> HI SLOPE	FREQ. 128	HI CUT <input type="checkbox"/> HI SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 42 db	TRIP SENS.: 7 db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	<input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR SCALING:	B.C.U. NORM / ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: 110	HOLE DEPTH: 105	SWEET POSITION:	SWEET START:	SWEET END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: GEOSPACE 205 10HZ	PATTERN: INLINE	NO. OF ELEMENTS: 18	INCLINE SPACING:	LENGTH:	WIDTH:	LATERAL OFFSET:		
	CONNECTION: SERIES-PARALLEL	RESISTANCE: 450 ohms	STAGGER:						
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220 ft.	SHOTPOINT INTERVAL: 1760 ft.	FOLD: 6 F	DIRECTION OF PROGRESSION: South	LEADING GROUP: #96			
	OFFSET GROUP 1: 10450 ft.	OFFSET GROUP 48 : 110 ft.	OFFSET GROUP 49 : 110 ft.	OFFSET GROUP 48/96:					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				DIR.	COP SWITCH	SPREAD LINE GROUPS	REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET					TR 1-48	TR 49-96	TR 1-48	TR 49-96	
59	523329				107	85	105	1		9	1-96	61	FILE #97-105 DAILY TEST / FILE #106				
60					108	100	105	1		17							
61					109	85	105	1		25							
62					110	110	105	1		33							
63					111	85	105	1		41							
64					112	110	105	1		49							
65	52333P				114	110	105	1		9		67	FILE #113 8 SEC ALLOWES				
66					115	110	105	1		17							
67					116	110	105	1		25							
68					117	110	105	1		33							
69					118	110	105	1		33							
70					119	110	105	1		33							
71					120	110	105	1		33							
72					121	110	105	1		33			INCORRECT TIME BREAK ON SP #72				
73					122	110	105	1		33							
74					123	110	105	1		33							