





LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY WPR OPERATIONS	PROSPECT: WPR-4	AREA: NORTH SLOPE	LINE NO.: 79						
	PARTY NO.: 1173	INST. ENG.: ORAND	RECORDING HOURS: 13	TRAVEL: 4	DATE: NOV 3 DAY 3 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> ONGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(11) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> REC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18	FREQ. 128 HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 40 db	TRIP SENS: 40 db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input checked="" type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE		NUMBERS ON MAG. TAPE: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	TYPE: GEOSPACER 200	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 6	DIRECTION OF PROGRESSION: SOUTH	LEADING GROUP: #96				

DIAGRAMS/MISC. INFORMATION: **FILE # 2-16 DAILY TEST**
FILE # 1 8 SEC ALL LINES **FILE # 17 TEST TIME BREAK**

SHOTPOINT	TR 1-70		TR 71-140		SHOT				DIR	CDP SWITCH	SPREAD		REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET			#1	LINE GROUPS		HT.	REC.	HT.	REC.
1	18	18	18	18	110	105	11		25	T53-1	9-8	4					
2	19	19	19	19	110	105	11	100 W	25	T53-1	9-8						
3	20	20	20	20	110	105	11		25	T53-1	9-8						
4	21	21	21	21	110	105	11		25	T53-1	9-8						
5	22	22	22	22	110	105	11		33	T52-1	10-8						
6	23	23	23	23	110	105	11		41	T51-1	11-8						
7	24	24	24	24	110	105	11		49	1-1	12-8						
8	25	25	25	25	110	105	11		27	2-1	13-8	76					

LAND SEISMIC RECORDING LOG



	CLIENT: Husky NPR OPERATIONS	PROSPECT: NPR-4	AREA: NORTH SLOPE	LINE NO.: 79	
PARTY NO.: 1173		INST. ENG.: ORAND		DATE: MO 3 DAY 4 YR 77	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS <input checked="" type="checkbox"/> DFS <input type="checkbox"/> OTHER		RECORD NUMBERS: DEC. 0 CT.	
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS.: 1-96		AUXILIARY DATA:	
DATA CHANNEL NOS.: 1-96		(ON MAG TAPE)		AUXILIARY CHANNEL NOS.:	
PARAMETER: RECORD LENGTH: 8 sec.		SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL	
DISPLAY: MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: 42 db		TRIP SENS.: 42 db	
CFS I: TYPE STACK:		RECORD REJECTION:		NOISE REDUCTION:	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE		NO. OF POSITIONS: 1	
RECEIVER: TYPE: GEOSPACE 200 10Hz		PATTERN: INLINE		NO. OF ELEMENTS: 18	
CONNECTION: SERIES		RESISTANCE: 450 ohms		STAGGER:	
SPREAD: NO. OF GROUPS: 96		GROUP INTERVAL: 220ft		SHOTPOINT INTERVAL: 1760'	
OFFSET GROUP 1: 10450'		OFFSET GROUP: 110'		OFFSET GROUP 48/96: 10450'	

DIAGRAMS/MISC. INFORMATION: **File # 26-39 DAILY TESTS**
File # 40 TEST TIME BREAK

SHOTPOINT	TR. 1 to 96		TR. 100 to 192		SHOT		SPREAD		REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH	#	LINE GROUPS #96	TR 1-48 REC
9	16	18	41		110	105	1			17	3-1	14-8		
10			42		110	105	1			25	4-1	15-8		
11			43		110	105	1			33	5-1	16-8		
12	75	1519	45		110	106	1			41	6-1	17-8		
13			46		110	105	1			49	7-1	18-8		
14			47		110	105	1			9	8-1	19-8		
15			48		110	105	1			17	9-1	20-8		
16			49		110	105	1			25	10-1	21-8		
17			50		110	105	1			33	11-1	22-8		
18			51		110	105	1			41	12-1	23-8		
19			52		110	105	1			49	13-1	24-8		
20			53		110	105	1			9	14-1	25-8		
21			54		110	105	1			17	15-1	26-8		
22			55		110	105	1			25	16-1	27-8		
23			56		110	105	1			33	17-1	28-8		
24			57		110	105	1			41	18-1	29-8		
25			58		110	105	1			49	19-1	30-8		

SHUTTLE TRACK NOT OPERATING
 WAITING AN ALTERNATE
 File #44 8 SEC ALL ONES (TAP CHANGE)



LAND SEISMIC RECORDING LOG

	CLIENT: Husky NPR OPERATIONS	PROSPECT: NPR-4	AREA: NORTH SLOPE	LINE NO: 79	
PARTY NO: 1173		INST. ENG: ORAND		DATE: MO 3 DAY 5 YR 77	
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254	
FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 1-96		AUXILIARY DATA:	
RECORD LENGTH: 8		SAMPLE RATE: 2 ms		GAIN MODE: INITIAL	
MODE: MAG		INITIAL GAIN: 42 db		TRIP SENS: 42 db	
TYPE: DYNAMITE		PATTERN: SINGLE		NO. OF POSITIONS: 1	
CONNECTION: GEOSPAC 20D 10HZ		RESISTANCE: 450 ohms		STAGGER:	
NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 1700' / 850'	
OFFSET GROUP 1: 10450'		OFFSET GROUP 48: 110'		OFFSET GROUP 48/96: 10450'	

DIAGRAMS/MISC. INFORMATION: **FILE #59-73 DAILY TESTS**
FILE #74 TEST TIME BREAK

SHOTPOINT	TR 1 to 96		TR 10 to 19		TR 20 to 29		TR 30 to 39		SHOT		SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#1	LINE GROUPS		TR 1-25	TR 26-50	
26	75	15	19	76	110	105	11			9	20-1	31-8	28	11	11	FILE #76 8SEE ALLONES (TAPE CHANGE)
27	76	16	20	77	110	105	11			17	21-1	32-8				
28		78			110	105	11			25	22-1	33-8				
29		79			110	105	11			33	23-1	34-8				
30		80			110	105	11			41	24-1	35-8				
31		81			110	105	11			49	25-1	36-8				
32		82			110	105	11			9	26-1	37-4	34			
33		83			110	105	11			17	27-1	41-4				
34		84			110	105	11			25	28-1	42-4				
35		85			110	105	11			33	29-1	45-4				
36		86			110	105	11			41	30-1	47-4				
37		87			110	105	11			9	30-5	48-4	41			START 12 FOLD COVERAGE @ SP# 37
38		88			110	105	11			13	31-1	49-4				
39		89			110	105	11			17	31-5	50-4				
40		92			110	105	11			21	32-1	51-4				FILE #90 OMIT FILE 91 TEST TIME BREAK
41		93			110	105	11			25	32-5	52-4				
42		94			110	105	11			29	33-1	53-4				
43		95			110	105	11			9	33-5	54-4	47			
44	75	15	21	97	110	105	11			13	34-1	55-4				FILE #96 8SEE ALLONES (TAPE CHANGE)
45		99			110	105	11			17	34-5	56-4				FILE 94 OMIT

LAND SEISMIC RECORDING LOG



	CLIENT: Husky	PROSPECT: NPR-4	AREA: NORTH SLOPE	LINE NO: 79	
PARTY NO: 1173		INST. ENG: ORAND		DATE: MO 3 DAY 6 YR 77	
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254	
RECORD LENGTH: 8 sec.		SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN CONSTANT: 36 db	
MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 42 db		POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	
TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE		NO. OF POSITIONS: 1	
CHG/ HOLE: 110		HOLE DEPTH: 105		SWEEP POSITION: 110	
TYPE: GEOSPACE 205 10HZ		PATTERN: SERIES		RESISTANCE: ohms	
NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'	
OFFSET GROUP 1: 10450'		OFFSET GROUP 48: 110'		OFFSET GROUP 96: 16450'	

DIAGRAMS/MISC. INFORMATION: **File #103, 117 TEST TIME BREAK**

File #104-116 DAILY TESTS

SHOTPOINT	TR 1 to 96		TR 10 to 96		SHOT		SPREAD		REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	#	LINE GROUPS	TR 1-21	TR 48-96
51	7.51.521				118	110	105	11		9	37-1	10-4	53		
52					119	110	105	11		13	38-1	61-4			
53					120	110	105	11		17	39-1	62-4			
54					121	110	105	11		21	40-1	63-4			
55					122	110	105	11		25	41-1	64-4			
56					123	110	105	11		29	42-1	65-4			
57					124	110	105	11		33	43-1	66-4			UNABLE TO SHOOT DUE TO AIRPLANE NOISE
58					125	110	105	11		37	44-1	67-4			UNABLE TO SHOOT DAILY AND JUG
59					126	110	105	11		41	45-1	68-4			TRUCK STUCK ON LINE
60	7.51.522				128	110	105	11		45	46-1	69-4			File # 127 8 SEC ALLOWES (TAPE CHANGE)
61					129	110	105	11		49	47-1	70-4			
62					130	110	105	11		5	48-1	71-4	65		
63					131	NP	105	11		9	49-1	72-4			
64					132	110	105	11		13	50-1	73-4			
65					133	110	105	11		17	51-1	74-4			
66					134	110	105	11		21	52-1	75-4			
67					135	NP	105	11	60 N	25	53-1	76-4			
68					136	110	105	11		29	54-1	77-4			
69					137	110	105	11		21	55-1	78-4	68		
70					138	110	105	11		25	56-1	79-4			



LAND SEISMIC RECORDING LOG

	CLIENT: Husky NPA OPERATIONS	PROSPECT: NPA-4	AREA: NORTH SLOPE	LINE NO: 79	
PARTY NO: 1173		INST. ENG: ORAND		DATE: MO 3 DAY 6 YR 77	
INSTRUMENT (9-TRACK)		NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)	
PARAMETER		RECORD LENGTH: 8 sec.		SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	
DISPLAY		MODE: <input checked="" type="checkbox"/> RAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 42 db	
CFS I		TYPE STACK:		GATE LENGTH:	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE	
RECEIVER		TYPE: GEOSPACE 200 10HZ		PATTERN: INLINE	
SPREAD		NO. OF GROUPS: 96		GROUP INTERVAL: 220'	
DIAGRAMS/MISC. INFORMATION:		CHG/ HOLE: 110		HOLE DEPTH: 105	

DIAGRAMS/MISC. INFORMATION: ~~SEE OFFERS 27~~ ~~(SEE LOG)~~

SHOTPOINT	TR. 1 to 96		TR. 10 to 19		TR. 20 to 29		TR. 30 to 39		TR. 40 to 49		TR. 50 to 59		TR. 60 to 69		TR. 70 to 79		TR. 80 to 89		TR. 90 to 96		CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	
61	135	16	136	17	137	18	138	19	139	20	140	21	141	22	142	23	143	24	144	25	145	26	
70																							
71																							
72																							

LAND SEISMIC RECORDING LOG

	CLIENT: Asky NPR OPERATIONS	PROSPECT: NPR-4	AREA: NORTH SLOPE	LINE NO: 79	
PARTY NO: 1173		INST. ENG: DAVE BREAU		DATE: 3 DAY 7 YR 77	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		ODDS: <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		EVENTS: <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: L96		DATA CHANNEL NOS.: L96		AUXILIARY DATA:	
PARAMETER: RECORD LENGTH: 4 sec		SAMPLE RATE: <input type="checkbox"/> 1 ms <input checked="" type="checkbox"/> 2 ms <input type="checkbox"/> 4 ms		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	
DISPLAY: MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT		INITIAL GAIN: 42 db		TRIP SENS: 42 db	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE		NO. OF POSITIONS: 1	
RECEIVER: TYPE: GEOPACK 20's 10HZ		PATTERN: INLINE		NO. OF ELEMENTS: 18	
SPREAD: NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 890'	

DIAGRAMS/MISC. INFORMATION: **TAPE #761522 FILE #143-155**
TAPE #751523 FILE #156 8 SEC ALLONES FILE

SHOTPOINT	TR. 1 to 96		TR. 10 to 19		TR. 20 to 29		TR. 30 to 39		TR. 40 to 49		TR. 50 to 59		TR. 60 to 69		TR. 70 to 79		TR. 80 to 89		TR. 90 to 96		CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	HT	REC
73	761523				150	110	105	11					15	61-1	84-4	75-2						
74					159	110	105	11					19	62-1	85-4							
75					160	110	105	11					23	63-1	86-4							
76					161	85	76	11					27	64-1	87-4							
77					162	110	105	11					31	65-1	88-4							
78					163	110	105	11					35	66-1	89-4							
79					164	110	105	11	330	N			39	67-1	90-4							
80					165	110	105	11	300	S			39	67-1	90-4							
81					166	110	105	11					39	67-1	90-4							
82					167	110	105	11					39	67-1	90-4							
83					168	110	105	11					39	67-1	90-4							
84					169	110	105	11					39	67-1	90-4							
85					170	110	105	11	170	S			39	67-1	90-4							
86					171	110	105	11					39	67-1	90-4							
87					172	110	105	11					39	67-1	90-4							
88					173	110	105	11					39	67-1	90-4							
89					174	110	105	11					39	67-1	90-4							
90					175	110	105	11					39	67-1	90-4							
91					176	110	105	11					39	67-1	90-4							

LINE ROUGH & DEEP SNOW
 End of LINE