

LAND SEISMIC RECORDING LOG



CLIENT: Husky NPR		PROSPECT: NPR-4		AREA: NORTH SLOPE BANERA		LINE NO: 07	
PARTY NO: 1195		INST. ENG: REID, BERTON		DATE: 07:00 → 11:00pm		DATE: MO 2 DAY 01 YR 77	
INSTRUMENT (9-TRACK)		NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: 1-96		AUXILIARY DATA: (1) TW (2) TD (3) NC (4) NC (5) 375 (6) (7)		AUXILIARY CHANNEL NOS.: 0 1 2 3 4	
PARAMETER		RECORD LENGTH: 8 sec.		SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: 36 db		TRIP SENS: 42 db	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: INLINE		NO. OF POSITIONS: 1	
RECEIVER		TYPE: GEOSPAC 20D-10M		PATTERN: INLINE		NO. OF ELEMENTS: 18	
SPREAD		NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 1760	
		OFFSET GROUP 1: 10450		OFFSET GROUP 2: 110		OFFSET GROUP 3: 10450	



DIAGRAMS/MISC. INFORMATION:

TAPE # 751287

WAIT ON DRMS IN RT & SHOOTING UNIT BROKE DOWN

SHOTPOINT	TR. 1 to 26		TR. 27 to 52		SHOT		SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR. 1-26	TR. 27-52
300	751287	111			110	110				1	7518	305-B		
301		113								9	7540	306-B		
302		115								17	7522	307-B		
303		116								25	7524	308-B		
304		118								33	7516	309-B		
305		119				90				41	758	310-B		
306														

LAND SEISMIC RECORDING LOG



	CLIENT: Husky - NPR	PROSPECT: NPR-4	AREA: NORTH SLOPE, ALASKA	LINE NO: 007	
PARTY NO: 1195		INST. ENG: BERTSCH, R.E.P.		DATE: MO 2 DAY 6 YR 72	
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254	
INSTRUMENT: 1 SYSTEM		TYPE: DFS III		9 TRACK	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS: 1-96		DATA CHANNEL NOS: 1-96		AUXILIARY DATA: (1) TW (2) TB (3) NC (4) NC (5) SPS (6) (7)	
PARAMETER: RECORD LENGTH: 8 sec.		SAMPLE RATE: 1 ms		GAIN CONSTANT: 36 db	
DISPLAY: MODE: AGC		INITIAL GAIN: 36 db		NOISE REDUCTION: NOISE THRESHOLD:	
SOURCE: TYPE: DYNAMIC		PATTERN: INLINE		NO. OF POSITIONS: 1	
RECEIVER: TYPE: D20-10		PATTERN: INLINE		NO. OF ELEMENTS: 18	
SPREAD: NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 1760, 880 FT	

DIAGRAMS/MISC. INFORMATION:

TAP 751289

SHOTPOINT	TR. 1 to 10		TR. 11 to 20		SHOT		SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR. 1-10	TR. 11-20
327	251	289	70		110	105	1	321-1	335-4	380	DAILY TESTS FA 62-67
328			71				9	322-1	337-4		Noise from mobile camp - TR# 55-65 approx.
329			72				17	323-1	339-4		Noise from drill up ahead - TR# 91-96
330			73				25	324-1	341-4		TR# 87 DEAD
331			74				5	324-5	340-4	336	CHANGE TO 1200 FOLD, TR# 1 + 2 DEAD, 800A BETWEEN SP'S.
332			75				9	325-1	343-1		
333							13	325-5	344-4		
											WAIT ON CAMP TO MOVE FROM SPREAD - 2 HRS
											WAIT ON DRILL ALL DAY

LAND SEISMIC RECORDING LOG

	CLIENT: Husky - NPR	PROSPECT: NPR-4	AREA: NORTH SLOPE, ALASKA	LINE NO: 007	
PARTY NO: 1195		INST. ENG: BERTSCH, ZEID		DATE: MO 2 DAY 9 YE 77	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		RECORD NUMBERS: <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)		AUXILIARY DATA: (1) TW (2) 78 (3) NC (4) NC (5) SPS (6) (7)	
PARAMETER: RECORD LENGTH: 8 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> AUTO	
DISPLAY: MODE: <input checked="" type="checkbox"/> TAGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 36 db		TRIP SENS: 42 db	
CFS I: TYPE STACK:		GATE LENGTH:		RECORD REJECTION:	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: INLINE		NO. OF POSITIONS: 1	
RECEIVER: TYPE: 200-10 HZ		CONNECTION: BER-PAR		RESISTANCE: 450 ohms	
SPREAD: NO. OF GROUPS: 96		GROUP INTERVAL: 220		SHOTPOINT INTERVAL: 880	
OFFSET GROUP 1: 10450		OFFSET GROUP 48: 110		OFFSET GROUP 96: 10450	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. to		TR. to		SHOT					SPREAD		REMARKS:	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		HT.	FT.
3166	751	1292	1319		110	105				1	354-1	378-4		
3167			140							5	355-1	378-4		
3168			141							9	356-1	379-4		
3169			142							13	357-1	380-4		
3170			143							17	358-1	381-4		
3171			144							21	359-1	382-4		
3172			145							25	360-1	383-4		
3173			146							29	361-1	384-4		
3174			147							33	362-1	385-4		
3175			148							37	363-1	386-4		
3176			149							41	364-1	387-4		
3177			150							45	365-1	388-4		
3178			151							49	366-1	389-4		

LAND SEISMIC RECORDING LOG

		CLIENT: Husky NPR	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 007		
PARTY NO: 1195		INST. ENG: BERTSON - REID		DATE: MO 2 DAY 10 YR 77			
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254		RECORD NUMBERS: DEC	
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX		<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		FORMAT: SEG B	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-96 DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL		FILTERS: FREQ: 8		GAPPED <input type="checkbox"/> UNGAPPED <input type="checkbox"/>	
PARAMETER RECORD LENGTH: 8		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		LO CUT HZ SLOPE: 18		PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI	
DISPLAY MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 96 db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		INPUT IMPEDANCE: _____ ohms	
CFS I TYPE STACK:		GATE LENGTH:		NOISE REDUCTION:		CORR. SCALING:	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: INLINE		NO. OF POSITIONS: 1		STAGGER:	
RECEIVER TYPE: G.S.C 200-10HZ		PATTERN: INLINE		NO. OF ELEMENTS: 18		INCLINE SPACING: 22'	
SPREAD NO. OF GROUPS: 96		GROUP INTERVAL: 220		SHOTPOINT INTERVAL: 880		LENGTH: 380'	
OFFSET GROUP 1: 10450		OFFSET GROUP 2: 110		OFFSET GROUP 3: 110		WIDTH: _____	

DIAGRAMS/MISC. INFORMATION:

TAPE # 751293

SHOTPOINT	TR. 1 to 96		TR. to		SHOT				SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		#1	LINE GROUPS	TR 1-48	TR 48-96
1	751293	1510													
379		1510								5	367-1	370-4			
380		1519								9	368-1	391-4			
381		160								13	369-1	392-4			
382		161								17	370-1	393-4			
383		1612								21	371-1	394-4			
384		1613								25	372-1	395-4			
385		1614								29	373-1	396-4			
386		1615								33	374-1	397-4			
387		1616								37	375-1	398-4			
388		1617								41	376-1	399-4			
389		1618								45	377-1	400-4			
390		1619								49	378-1	401-4			
391		1716								17	379-1	402-4	393	TR* 83 DEAD	
392		1717								21	380-1	403-4		TR* 18 DEAD	
393		1712								25	381-1	404-4			
394		1723								29	382-1	405-4			
395		1714								33	383-1	406-4		TR* 95-96 DEAD	

LAND SEISMIC RECORDING LOG

T

		CLIENT: Husky - NPR	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO.: 007		
PARTY NO.: 1195		INST. ENG.: REID		DATE: 07:00 -> 7:30		MO. 2 DAY 11 YR 77	
INSTRUMENT (9-TRACK)		<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> ODDS <input type="checkbox"/> EVENTS		TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER		<input checked="" type="checkbox"/> 2 TRACK <input type="checkbox"/> 21 TRACK FORMAT: SEG. B <input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	
NO. BYTES IN HEADER REC: 224		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT GAIN CONSTANT: 36 db INPUT IMPEDANCE: _____ ohms.	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: 1 - 96		AUXILIARY DATA:		(1) TN (2) TA (3) NC (4) NC (5) SPS (6) _____ (7) _____ AUXILIARY CHANNEL NOS.: 0 1 2 3 4	
PARAMETER		RECORD LENGTH: 4 sec.		SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input type="checkbox"/> TFP <input type="checkbox"/> FINAL	
DISPLAY		<input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 36 db		FILTERS: FREQ. 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 72 POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION: _____ NOISE REDUCTION: _____ NOISE THRESHOLD: _____ CORR. SCALING: _____ R.C.U. NORM/ALT SW.	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: INLINE		NO. OF POSITIONS: 1 INCLINE SPACING: _____ LATERAL SPACING: _____ STAGGER: _____ CHG/ HOLE: 110 HOLE DEPTH: 105 SWEEP POSITION: _____ SWEEP START: _____ SWEEP END: _____	
RECEIVER		TYPE: G.S.C 200-10HZ CONNECTION: SEI-PAR.		PATTERN: INLINE		NO. OF ELEMENTS: 18 INCLINE SPACING: 22' RESISTANCE: 450 Ω ohms STAGGER: _____ LENGTH: 380' WIDTH: _____ LATERAL SPACING: _____ LATERAL OFFSET: _____	
SPREAD		NO. OF GROUPS: 96 OFFSET GROUP 1: 10450		GROUP INTERVAL: 220' OFFSET GROUP 96 : 110		SHOTPOINT INTERVAL: 880 OFFSET GROUP 96 : 110	
FOLD: 1200		DIRECTION OF PROGRESSION: SOUTH		LEADING GROUP: 96			

DIAGRAMS/MISC. INFORMATION:

TAPE # 751294

SHOTPOINT	TR. 1 to 96		TR. 10 to 19		TR. 20 to 29		TR. 30 to 39		TR. 40 to 49		TR. 50 to 59		TR. 60 to 69		TR. 70 to 79		TR. 80 to 89		TR. 90 to 96		CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	
38	751294	1183																					
396	751294	1184																					
397		1185																					
398		1186																					
399		1187																					
400		1188																					
401		1189																					
402		1190																					
403		1191																					
404		1192																					
405		1193																					
406		1194																					
407		1195																					
408		1196																					
409		1197																					
410		1198																					
411		1199																					

LAND SEISMIC RECORDING LOG



CLIENT: <u>HUSKEY</u>		PROSPECT: <u>APR-4</u>		AREA: <u>NORTH SLOPE ALASKA</u>		LINE NO: <u>007</u>	
PARTY NO: <u>1195</u>		INST. ENG: <u>BERESCH REID</u>		TIME: <u>0700 TO 1930HRS</u>		DATE: <u>MO 2 DAY 12 YR 77</u>	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV		<input checked="" type="checkbox"/> 2 TRACK <input type="checkbox"/> 21 TRACK		PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
NO. BYTES IN HEADER REC: <u>228</u>		NO. BYTES IN RECORD ID: <u>2</u>		NO. BYTES PER SCAN: <u>254</u>		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	
FIELD TRACE NOS.: <u>1-96</u>		DATA CHANNEL NOS.: <u>1-96</u>		AUXILIARY DATA: <u>TW 78 NC NC SPS</u>		GAIN CONSTANT: _____ db	
PARAMETER: RECORD LENGTH: <u>8</u> sec		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms <input type="checkbox"/> _____ ms		GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> TFP		FILTERS: FREQ: <u>8</u> LO CUT HZ SLOPE <u>18</u>	
DISPLAY: MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AOC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <u>36</u> db		TRIP SENS: <u>42</u> db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	
CFS I: TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: NOISE THRESHOLD: _____	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>INLINE</u>		NO. OF POSITIONS: <u>1</u>		LATERAL SPACING: _____	
RECEIVER: TYPE: <u>20D-10N</u>		PATTERN: <u>INLINE</u>		NO. OF ELEMENTS: <u>18</u>		INCLINE SPACING: <u>22'</u>	
CONNECTION: <u>SER-PAD</u>		RESISTANCE: <u>450</u> ohms		STAGGER: _____		LENGTH: <u>380'</u>	
SPREAD: NO. OF GROUPS: <u>96</u>		GROUP INTERVAL: <u>220'</u>		SHOTPOINT INTERVAL: _____		FOLD: <u>1200</u>	
OFFSET GROUP 1: <u>16450</u>		OFFSET GROUP 2: <u>110</u>		OFFSET GROUP 49: <u>110</u>		OFFSET GROUP 48/96: <u>10950</u>	
DIAGRAMS/MISC. INFORMATION: _____							

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD			REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#1		LINE GROUPS #96	TR. 48
30	75V	249H												
412		249B			110	105				5	401-1	423-4	317	
	75V	249S								+				
413		249B			110	105				9	401-1	424-4		
414		249B								13	402-1	425-4		
415		249B								17	403-1	426-4		
416		249B								21	404-1	427-4		
417		249B								25	405-1	428-4		
418		249B								29	406-1	429-4		
419		249B								33	407-1	430-4		
420		249B								37	408-1	431-4		
421		249B								41	409-1	432-4		
422		249B								45	410-1	433-4	323	
423		249B								25	411-1	434-4		



LAND SEISMIC RECORDING LOG

CLIENT: <u>Husky</u>		PROSPECT: <u>NPR-4</u>		AREA: <u>NORTH SLOPE ALASKA</u>		LINE NO: <u>007</u>			
PARTY NO: <u>1195</u>		INST. ENG: <u>BERTSCH, Reid</u>		TIME: <u>7:00 AM → 8:30 PM</u>		DATE: <u>13.5.HAS</u>		MO: <u>2</u> DAY: <u>13</u> YR: <u>77</u>	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> OPS III <input type="checkbox"/> OPS II <input type="checkbox"/> OTHER		RECORD NUMBERS: <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		FORMAT: <u>8</u> SEG		PACKING DENSITY: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	
NO. BYTES IN HEADER REC: <u>228</u>		NO. BYTES IN RECORD ID: <u>2</u>		NO. BYTES PER SCAN: <u>254</u>		GAIN CONSTANT: <u>36</u> db		INPUT IMPEDANCE: _____ ohms	
FIELD TRACE NOS.: <u>1-96</u>		DATA CHANNEL NOS.: <u>1-96</u> (ON MAG TAPE)		AUXILIARY DATA: <u>FW 18 NC NC SPS</u>		AUXILIARY CHANNEL NOS.: <u>0 1 2 3 4</u>		FILTERS: <input type="checkbox"/> LO CUT <input type="checkbox"/> HI CUT <input type="checkbox"/> NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
RECORD LENGTH: <u>8</u> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FREQ: <u>8</u>		LO CUT HZ SLOPE: <u>18</u>	
DISPLAY: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <u>36</u> db		TRIP SENS: <u>42</u> db		POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEDPHONE: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____		NOISE THRESHOLD: _____	
SOURCE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>INLINE</u>		NO. OF POSITIONS: <u>1</u>		INLINE SPACING: _____		LATERAL SPACING: _____	
CHG/ HOLE: <u>110</u>		HOLE DEPTH: <u>165</u>		SWEEP POSITION: _____		SWEEP START: _____		SWEEP END: _____	
RECEIVER: <u>20 D -10 Hz</u>		PATTERN: <u>INLINE</u>		NO. OF ELEMENTS: <u>18</u>		INCLINE SPACING: <u>22'</u>		LATERAL SPACING: _____	
CONNECTION: <u>SER-PAR</u>		RESISTANCE: <u>450</u> ohms		STAGGER: _____		LENGTH: <u>380'</u>		WIDTH: _____	
SPREAD: <u>96</u> GROUPS		GROUP INTERVAL: <u>220'</u>		SHOTPOINT INTERVAL: <u>880'</u>		FOLD: <u>1200</u>		DIRECTION OF PROGRESSION: <u>South</u>	
OFFSET GROUP 1: <u>10450'</u>		OFFSET GROUP 48: <u>110</u>		OFFSET GROUP 44: <u>110'</u>		OFFSET GROUP 48/96: <u>10450'</u>		LEADING GROUP: <u>96</u>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		#/ LINE GROUPS	TR 1-48	TR 49-96		
424	751	1296	1230		110	105					17	412-1	435-4	426		
425			1231								21	413-1	436-4			
426			1232								25	414-1	437-4			
427			1233								29	415-1	438-4			
428			1234								33	416-1	439-4			
429			1235								37	417-1	440-4			
430			1236								41	418-1	441-4	236		
431	751	1296	1239								3	419-1	442-4	-2		
432			240								1	420-1	443-4	238		
433			1241								5	421-1	444-4			
434			1242								9	422-1	445-4			
435			1243								13	423-1	446-4			
436			1244								17	424-1	447-4			
437											21	425-1	448-4			

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-4</u>	AREA: <u>KURTIT SLOPE, ALASKA</u>	LINE NO: <u>007</u>	
PARTY NO: <u>1195</u>		INST. ENG: <u>BERTSCH</u>		DATE: <u>MO 2 DAY 15 YR 72</u>	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
NO. BYTES IN HEADER REC: <u>228</u>		NO. BYTES PER SCAN: <u>254</u>		GAIN CONSTANT: <u>36</u> db	
FIELD TRACE NOS.: <u>1-96</u>		AUXILIARY DATA: <u>7W 7B 7C 7E 7S</u>		INPUT IMPEDANCE: <u>ohms</u>	
DATA CHANNEL NOS.: <u>1-96</u>		AUXILIARY CHANNEL NOS.: <u>0 1 2 3 4</u>		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT <u>453</u>	
PARAMETER: RECORD LENGTH: <u>8</u> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 4 ms.		FREQ: <u>8</u> LO CUT HZ SLOPE <u>18</u>	
MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER DIRECT		INITIAL GAIN: <u>36</u> db		HI CUT HZ SLOPE <u>72</u>	
TYPE STACK:		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	
CHGT/ HOLE: <u>110</u>		HOLE DEPTH: <u>105</u>		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>INLINE</u>		CORR. SCALING: <u>R.C.U. NORM/ALT SW.</u>	
NO. OF POSITIONS: <u>1</u>		INLINE SPACING:		STAGGER:	
CHGT/ HOLE: <u>110</u>		SWEEP POSITION:		SWEEP LENGTH:	
RECEIVER: TYPE: <u>200-10 Hz</u>		PATTERN: <u>INLINE</u>		LENGTH: <u>22'</u>	
CONNECTION: <u>SER PAR</u>		RESISTANCE: <u>450</u> ohms		LATERAL SPACING:	
NO. OF GROUPS: <u>96</u>		GROUP INTERVAL: <u>220'</u>		STAGGER:	
OFFSET GROUP 1: <u>10450</u>		OFFSET GROUP 1B: <u>110</u>		LENGTH: <u>300'</u>	
SPREAD: NO. OF GROUPS: <u>96</u>		SHOTPOINT INTERVAL: <u>300'</u>		WIDTH: <u>1200</u>	
OFFSET GROUP 1: <u>10450</u>		OFFSET GROUP 49: <u>110</u>		DIRECTION OF PROGRESSION: <u>SOUTH</u>	
OFFSET GROUP 1B: <u>110</u>		OFFSET GROUP 48/90: <u>10450</u>		LEADING GROUP: <u>96</u>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD				REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	#1	LINE GROUPS		SET	TR 1-48
451	751	297	270		110	105	11			5	439-1	462-4	456		
452		279								9	440-1	463-4			
453		280								13	441-1	464-4			
454		281								17	442-1	465-4			
455		282								21	443-1	466-4			
456		283								25	444-1	467-4			
457		284								29	445-1	468-4			
458		285								33	446-1	469-4			
459		286								37	447-1	470-4			
460		287				60				5	448-1	471-4	465		
461		288				70E				9	449-1	472-4			
462		289				60				13	450-1	473-4			
463		290				320	105	5	SSN-S	17	451-1	474-4			
464		291				110	105			21	452-1	475-4			
465		292							220 W	25	453-1	476-4			
466		END OF TAPE								29	454-1	477-4			

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: NPR-4	AREA: NORTH SLOPE, ALASKA	LINE NO: 007	
PARTY NO: 195		INST. ENG.: BERTSCH		DATE: MO 2 DAY 16 YR 77	
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254	
INSTRUMENT (9-TRACK) <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-96 DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)		AUXILIARY DATA: AUXILIARY CHANNEL NOS.: 0 1 2 3 4		GAIN CONSTANT: 36 db	
PARAMETER RECORD LENGTH: 8 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		FILTERS: LO CUT HZ SLOPE: 13	
DISPLAY MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 36 db		HI CUT HZ SLOPE: 72	
CFS I TYPE STACK:		GAIN MODE: <input checked="" type="checkbox"/> OFF <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: INLINE		NOISE REDUCTION: NOISE THRESHOLD:	
RECEIVER TYPE: 200-10		NO. OF POSITIONS: 10		CORR. SCALING:	
CONNECTION: SER-PAR		INLINE SPACING: 22'		R.C.U. NORM/ALT SW.	
RESISTANCE: 450 ohms		SWEEP POSITION:		STAGGER:	
SPREAD NO. OF GROUPS: 96		SWEEP START:		LENGTH:	
GROUP INTERVAL: 220'		SWEEP END:		WIDTH:	
SHOTPOINT INTERVAL: 880		SWEEP TAPER:		LATERAL SPACING:	
OFFSET GROUP 1: 10450		SWEEP COMP:		LATERAL OFFSET:	
OFFSET GROUP 48: 110		PHASE COMP:		DIRECTION OF PROGRESSION: SOUTH	
OFFSET GROUP 96: 10450		LEADING GROUP: 96			

DIAGRAMS/MISC. INFORMATION:

FINISH PROFILE 007, PICK-UP LINE AND HEAD FOR CAMP -

SHOTPOINT	TR. 10		TR. 10		SHOT		SPREAD		REMARKS	CORR. STACK	
	TR. NO.	REC.	TR. NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR 1-48	TR 49-96
473	751298	309			110	105	5	461-1	484-4	278	
474		310					7	462-1	485-4		
475		311					11	463-1	486-4		
476		312					15	464-1	487-4		
477		313			110	105	19	465-1	488-4		
478		314					23	466-1	489-4		
479		315			110	105	27	467-1	489-4		
480		316					31	468-1	489-4		
481		317					35	469-1	489-4		
482		318					39	470-1	489-4		
483		319					43	471-1	489-4		
CHANGE TAPE											
484	751299	321			110	105	47	472-1	489-4		
485		322					51	473-1	489-4		
486		323					55	474-1	489-4		
487		324					59	475-1	489-4		
488		325					63	476-1	489-4		
489		326			110	75	67	477-1	489-4		
490		327					71	478-1	489-4		