

## LAND SEISMIC RECORDING LOG



CLIENT: Husky NPR OPERATIONS PROSPECT: NPR-4 AREA: NORTH SLOPE LINE NO: 80  
 PARTY NO: 1173 (INST. ENG.) Total Hours 13 TRAVEL 8 DATE: 3 13 77  
 MO 3 DAY 13 YR 77

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS    TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		<input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> EVENS		<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED    PACKING DENSITY:    (LO) <input type="checkbox"/> 356 BPI    (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI			
	NO. BYTES IN HEADER REC:    NO. BYTES IN RECORD ID:    NO. BYTES PER SCAN:    RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.    GAIN CONSTANT:    db    INPUT IMPEDANCE:    ohms.		(1)    (2)    (3)    (4)    (5)    (6)    (7)		(1)    (2)    (3)    (4)    (5)    (6)    (7)			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:				AUXILIARY DATA:			
	DATA CHANNEL NOS.:				AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH:    sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS:    FREQ.    LO CUT    HZ SLOPE    HI CUT    HZ SLOPE    NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN:    db		TRIP SENS:    db		POLARITY CONVENTION:    PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE    NUMBERS ON MAG. TAPE	
DISPLAY	TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:    NOISE THRESHOLD:	
	NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:		STAGGER:    LENGTH:    WIDTH:    LATERAL OFFSET:	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		CHG/HOLE:		HOLE DEPTH:		SWEEP POSITIONS:    SWEEP START:    SWEEP END:	
	PATTERN:		RESISTANCE:    ohms		STAGGER:		LENGTH:    WIDTH:    LATERAL OFFSET:	
RECEIVER	CONNECTION:		RESISTANCE:    ohms		STAGGER:		LENGTH:    WIDTH:    LATERAL OFFSET:	
	TYPE:		PATTERN:		NO. OF ELEMENTS:		INLINE SPACING:	
SPREAD	NO. OF GROUPS:		GROUP INTERVAL:		SHOTPOINT INTERVAL:		FOLD:	
	OFFSET GROUP 1:		OFFSET GROUP:		OFFSET GROUP:		DIRECTION OF PROGRESSION:    LEADING GROUP:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____			TR _____ to _____			SHOT					SPREAD			REMARKS:	CORR. STACK			
	REEL NO.		REC.	REEL NO.		REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			REC.	TR 20-30		REC.
	7	12-15	16	17	21-23	24-27	28-30	31	35	37									
1	56	7	12-15	16	17	21-23	24-27	28-30	31	35	37								

1 HOUR TRAVEL TO LINE 23

3 HOUR PICKUP CABLE

5 HOURS LINE CHANGE

2 HOURS LAY CABLE ON LINE 80

2 HOURS TRAVEL BACK TO CAMP

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky NPA OPERATIONS</b>	PROSPECT: <b>NPR-4</b>	AREA: <b>NORTH SLOPE</b>	LINE NO: <b>80</b>	
	PARTY NO: <b>1173</b>	INST. ENG: <b>DAVID BREWIN</b>	Travel 3 Recording 9.5 hrs. Total 12.5 hrs.		DATE: <b>MO 3 DAY 14 YR 77</b>
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III	<input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER
	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>36</b> db
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>			AUXILIARY DATA:	
	DATA CHANNEL NOS.: <b>1-96</b> (ON MAG TAPE)			AUXILIARY CHANNEL NOS.:	
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> TRF <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>8</b> Hz	LO CUT <b>18</b> Hz
DISPLAY	MODE: <input checked="" type="checkbox"/> MAG <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>42</b> db	TRIP SENS: <b>42</b> db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS: <b>1</b>	INLINE SPACING:	LATERAL SPACING:
	CHG/ HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:
RECEIVER	TYPE: <b>GEOSPAC 200 MHz</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING:	LATERAL SPACING:
	CONNECTION: <b>SERIES</b>	RESISTANCE: <b>450</b> ohms	STAGGER:	LENGTH:	WIDTH:
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>1760'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>
	OFFSET GROUP 1: <b>10450'</b>	OFFSET GROUP <b>96</b> : <b>110'</b>	OFFSET GROUP <b>1</b> : <b>110'</b>	OFFSET GROUP 48/96: <b>10450'</b>	LEADING GROUP: <b>#96</b>

DIAGRAMS/MISC. INFORMATION: **FILE #1 8 SEC ALL ONES** **METEA 6 STAMPS OF TUBS**

**FILE #2-14 DAILY TESTS FILE #15 TEST TIME BREAK**

SHOTPOINT	TR 1 to 96		TR 10		SHOT		SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR 1-48	TR 49-96
1	751531	16			110	105	1	05	1 156-1 6-8 4		
2		17			110	105	1		9 155-1 7-8		
3		18			110	105	1		17 154-1 8-8		
4		19			110	105	1		25 153-1 9-8		
5		20			110	105	1		33 152-1 10-8		
6		21			110	105	1		17 151-1 11-8		
7		22			110	105	1		25 1-1 12-8		
8		23			110	105	1		33 2-1 13-8		
9		24			110	105	1		41 3-1 14-8		
10		25			110	105	1		49 4-1 15-8	DELAY SHOOTING AIRPLANE NOISE	
11		26			110	105	1		9 5-1 16-8	DELAY SHOOTING AIRPLANE NOISE	
12		27			110	105	1		17 6-1 17-8	HOLE BLEW	
13		28			110	105	1		1 7-1 18-8		
14		29			110	105	1		9 8-1 19-8		
15		30							17 9-1 20-8	NO LOG FOR HOLE	
16	751532	31			110	105	1		25 10-1 21-8	FILE #31 8 SEC ALL ONES	
17		32			110	105	1		9 11-1 22-8		
18		33			110	105	1		17 12-1 23-8		
19		34			110	105	1		25 13-1 24-8		
20		35			110	105	1		33 14-1 25-8		

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky NPR OPERATIONS</b>	PROSPECT: <b>NPR-4</b>	AREA: <b>NORTH SLOPE</b>	LINE NO: <b>80</b>											
	PARTY NO: <b>1173</b>	INST. ENG: <b>DAVID BREAUX</b>	<b>Total Hours 15</b>	<b>TRAVEL 2</b>	DATE: <b>MO 3 DAY 15 YR 77</b>										
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 336 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI	NO. BYTES IN HEADER REC: <b>228</b>		NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms
	CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:							
PARAMETER	RECORD LENGTH: <b>9</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>8</b> LO CUT HZ SLOPE <b>18</b> HI CUT HZ SLOPE		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT									
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>42</b> db	ZIP SENS: <b>42</b> db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: _____		NUMBERS ON MAG. TAPE		DOWNBREAK <input checked="" type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY					
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM / ALT SW.					
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS: <b>1</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:						
RECEIVER	TYPE: <b>GEOSPACE 200 10HZ</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>18</b>	CONNECTION: <b>SERIES</b>	RESISTANCE: <b>450</b> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:						
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>1740'</b>	OFFSET GROUP 1: <b>10450 ft.</b>	OFFSET GROUP 48: <b>110'</b>	OFFSET GROUP 49: <b>110'</b>	OFFSET GROUP 96: <b>10450'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>		LEADING GROUP: <b>#96</b>				



DIAGRAMS/MISC. INFORMATION: **FILE # 36-48 DAILY TESTS**

**1-96 FILE # 49 TEST TIME BREAK**

SHOTPOINT	TR 1 to 96		TR 10 to 19		TR 20 to 29		TR 30 to 39		TR 40 to 49		TR 50 to 59		TR 60 to 69		TR 70 to 79		TR 80 to 89		TR 90 to 96		CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	#1	LINE GROUPS	#2	LINE GROUPS	REMARKS:	TR 1-49	TR 50-96	TR 1-49	TR 50-96	TR 1-49	TR 50-96		
20	751532	50	22	23	110	105	1			9	14-1	25-8	22		HOLE BLEW								
21		51			110	105	1			17	15-1	26-8											
22		52			110	105	1			25	16-1	27-8											
23		53			110	105	1			33	17-1	28-8											
24		54			110	105	1			41	18-1	29-8											
25		55			110	105	1			49	19-1	30-8											
26		56			110	105	1			9	20-1	31-8	28		LOST 1/2 HOUR REPAIR TRACK ON JOB TRACK								
27		57			110	105	1			17	21-1	32-8			DELAY SHOOTING; WAITING ON CAMP MOVE								
28		58			110	105	1			25	22-1	33-8											
29		59			110	105	1			33	23-1	34-8											
30		60			110	105	1			41	24-1	35-8											
31		61			110	105	1			49	25-1	36-8											
32	751533	62			110	105	1			9	26-1	37-8	34		FILE # 62 SEE ALLOWES								
33		63			110	105	1			17	27-1	38-8											
34		64			110	105	1			25	28-1	39-8											
35		65			110	105	1			33	29-1	40-8											
36		66			110	105	1			41	30-1	41-8											
37		67			110	105	1			49	31-1	42-8											
38		68			110	105	1			9	32-1	43-8	40										
39		69			110	105	1			17	33-1	44-8			LOST 1/2 HOUR JOB TRACK WOULD NOT START								
		70													SP # 39 WEAK SHOT								



# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Hasky NAR OPERATIONS</b>	PROSPECT: <b>NAR-4</b>	AREA: <b>NORTH SLOPE</b>	LINE NO: <b>80</b>					
	PARTY NO: <b>1173</b>	INST. ENG: <b>DAVID BREAUX</b>	<b>Total Hours 13 1/2</b>	<b>Tape 2</b>	DATE: <b>MO 3 DAY 16 YR 77</b>				
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III	<input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>96</b>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TFF <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>8</b>	LO CUT HZ SLOPE: <b>18</b>	FREQ. <b>128</b>	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>42</b> db	TRIP SENS: <b>42</b> db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE:	NUMBERS ON MAG. TAPE		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS: <b>1</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: <b>110</b>	HOLE DEPTH: <b>105</b>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: <b>GEOSPACE 20D</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: <b>SEATES</b>	RESISTANCE: <b>450</b> ohms							
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>1760'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>				
	OFFSET GROUP 1: <b>10450'</b>	OFFSET GROUP <b>48</b> : <b>110'</b>	OFFSET GROUP <b>119</b> : <b>110'</b>	OFFSET GROUP <b>48/96</b> : <b>10450'</b>	LEADING GROUP: <b>#</b>				

DIAGRAMS/MISC. INFORMATION: **FILE# 77 8 SEC ALLONES FILE# 78-93 DAILY TESTS**  
**TAPE# 751534 96 FILE# 94- TEST TIME BREAK**

SHOTPOINT	TR. 1 to 96		TR. 10		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		CDP SWITCH	#/ LINE GROUPS	#/ SP	TR 1-48
44	<del>751534</del>	96		2223	110	105	11		9	38-1	49-8	46	
45	751534	96			110	105	11		17	39-1	50-8		
46		97			110	105	11		25	40-1	51-8		
47		98			110	105	11		33	41-1	52-8		
48		99			110	105	11		41	42-1	53-8		
49		100			110	105	11		49	43-1	55-4		
50		101			110	105	11		9	44-1	57-4	52	
51		102			110	105	11		17	45-1	59-4		
52		103			110	105	11		25	46-1	61-4		
53		104			110	105	11		33	47-1	63-4		
54		105			110	105	11		41	48-1	65-4		
55		106			110	105	11		45	48-5	66-4		
56		107			110	105	11		1	49-1	67-4	62	
57		108			110	105	11		5	49-5	68-4		
58	051535	112			110	105	11		9	50-1	69-4		
59		113			110	105	11		13	50-5	70-4		
60		114			110	105	11		17	51-1	71-4		
61		115			110	105	11		21	51-5	72-4		

**NO. HOLD**

**1 hour lost repairs ignition on Job Tapes**

**START 12 fold COVERAGE AT SP# 55**

**FILE# 107 108 TEST TIME BREAK 1/2 hour**

**DELAY 10 SHOTS WAITING ON CAMP MOVE**

**FILE# 111 8 SEC ALLONES**

**LOST CAMP MOVE**

# LAND SEISMIC RECORDING LOG



	CLIENT: <b>Husky NPA OPERATIONS</b>	PROSPECT: <b>NPA-4</b>	AREA: <b>NORTH SLOPE</b>	LINE NO: <b>80</b>							
	PARTY NO: <b>1173</b>	INST. ENG: <b>DAVID BREAK</b>	<b>Total Hours 13</b>	<b>TRAVEL 2 1/2</b>	DATE: <b>3 DAY 17 YR 77</b>						
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS X <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>D</b>	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
(9-TRACK)	NO. BYTES IN HEADER REC: <b>254</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>228</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>26</b> db	INPUT IMPEDANCE: _____ ohms.					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>				AUXILIARY DATA:						
	DATA CHANNEL NOS.: <b>1-96</b> (ON MAG TAPE)				AUXILIARY CHANNEL NOS.:						
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. <b>8</b>	LO CUT HZ SLOPE <b>18</b>	FREQ. <b>128</b>	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>42</b> db	TRIP SENS: <b>42</b> db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE:		NUMBERS ON MAG TAPE		DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:		R.C.U. NORM./ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
	CHG/HOLE: <b>110</b>	HOLE DEPTH: <b>105'</b>	SWEET POSITION:	SWEET START:	SWEET END:	SWEET LENGTH:	SWEET TAPER:	PHASE COMP:			
RECEIVER	TYPE: <b>GENSPACE 20D 10HZ</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
	CONNECTION: <b>SERIES</b>	RESISTANCE: <b>450</b> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:					
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>850'</b>	FOLD: <b>12</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>			LEADING GROUP: <b>#96</b>			
	OFFSET GROUP 1: <b>10450'</b>	OFFSET GROUP <b>48</b> : <b>110'</b>	OFFSET GROUP <b>49</b> : <b>110'</b>	OFFSET GROUP <b>96</b> : <b>10450'</b>							

DIAGRAMS/MISC. INFORMATION: **FILE # 116-128 DAILY TEST**  
**1 96 FILE # 129-130 TEST TIME BREAK**  
**DELAYED GAS BAD VISABILITY HIGH WINDS**

SHOTPOINT	TR 1a		TR 1b		SHOT				DIR.	CDP SWITCH	SPREAD		REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET			#1	LINE GROUPS		TR 1a	TR 1b	TR 48-49	TR 48-49
62	131	131	131	131	110	105	11	35	1	52-1	73-4	68	NO UP HOLD				
63	132	132	132	132	110	105	11	37	5	52-5	74-4		NO UP HOLD				
64	133	133	133	133	110	105	11	39	9	53-1	75-4		NO UP HOLD				
65	134	134	134	134	110	105	11	41	13	53-5	76-4						
66	135	135	135	135	110	105	11	43	17	54-1	77-4						
67	136	136	136	136	110	105	11	45	21	55-1	78-4						
68	137	137	137	137	110	105	11	47	25	56-1	79-4						
69	138	138	138	138	110	105	11	49	29	57-1	80-4						



# LAND SEISMIC RECORDING LOG



	CLIENT: <b>Ausky NPR OPERATIONS</b>	PROSPECT: <b>NPR-4</b>	AREA: <b>NORTH SLOPE</b>	LINE NO: <b>80</b>						
	PARTY NO: <b>1173</b>	INST. ENG: <b>DAVID BREAUX</b>	TOTAL HOURS <b>13.5</b> TRAVEL <b>4</b>		DATE: <b>MO 3 DAY 19 YR 77</b>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H1) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>				AUXILIARY DATA:					
	DATA CHANNEL NOS.: <b>1-96</b> (ON MAG TAPE)				AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input checked="" type="checkbox"/> IFP <input type="checkbox"/> FINAL	FILTERS: FREQ: <b>8</b> LO CUT HZ SLOPE <b>18</b> HI CUT HZ SLOPE _____		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT				
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>42</b> db	TRIP SENS: <b>42</b> db	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:		R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>SINGLE</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/HOLE: <b>110</b>	HOLE DEPTH/OS: <b>105</b>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:		
RECEIVER	TYPE: <b>SERIES GEOSPACE 10M2</b>		PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: <b>SERIES</b>		RESISTANCE: <b>450</b> ohms			STAGGER:	LENGTH:	WIDTH:		
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>800'</b>	FOLD: <b>12</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>					
	OFFSET GROUP 1: <b>10450'</b>	OFFSET GROUP 48: <b>110'</b>	OFFSET GROUP 49: <b>110'</b>	OFFSET GROUP 48/96: <b>10450'</b>	LEADING GROUP: <b>#96</b>					

DIAGRAMS/MISC. INFORMATION: **File # 156-169 DAILY TEST**  
**File # 170 TEST TIME BREAK**

SHOTPOINT	TR 1 to 96		TR 10 to		SHOT				SPREAD				REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#	LINE GROUPS		#	TR 1-48 REC.
70	751536	171			110	105	1			21	58-1	81-4	71		
71		172			110	105	11			25	59-1	82-4			
72					110	105	11			29	60-1	83-4		SP#72 OMIT File # 173 NO RECORD CHANGE FIELD EARLY	
73		174			110	105	11			33	61-1	84-4			
74		175			110	105	11			37	62-1	85-4			
75		176			110	105	11			29	63-1	86-4	74	DELAY SHOOTING AIRPLANE NOISE	
76		177			110	105	11			33	64-1	87-4		" " " "	
77		179			110	105	11			37	65-1	88-4		OMIT File # 178	
78		180			110	105	11			5	66-1	89-4	83		
79		181			110	105	11			9	67-1	90-4			
80		182			110	105	11			13	68-1	91-4		DELAY SHOOTING AIRPLANE NOISE	
81		183			110	105	11			17	69-1	92-4			
82		184			85	85	11			21	70-1	93-4			
83	751537	186			110	105	11			25	71-1	94-4		File # 185 8500 ALL ONES (TAPE CHANGE)	
84		187			110	105	11			17	72-1	95-4	86		
85		188			110	105	11			21	73-1	96-4			
86		189			110	105	11			25	74-1	97-4			
87		190			110	105	11			29	75-1	98-4			
88		191			110	105	11			33	76-1	99-4			
89		192			110	105	11			37	77-1	100-4			



# LAND SEISMIC RECORDING LOG



	CLIENT: <b>Musk NPA- OPERATIONS</b>	PROSPECT: <b>NPR-4</b>	AREA: <b>NORTH SLOPE</b>	LINE NO: <b>80</b>						
	PARTY NO: <b>1173</b>	INST. ENG: <b>DAVID BREAUX</b>	Total Hours <b>13.5</b> TRAVEL <b>4</b>		DATE: <b>3 DAY 19 YR 77</b>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	POP MAT: <b>B</b>	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <b>D DEC</b> <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>				AUXILIARY DATA:					
	DATA CHANNEL NOS.: <b>1-96</b>				AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: <b>8</b> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>8</b> LO CUT HZ SLOPE <b>18</b>	FREQ. <b>128</b> HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT				
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>42</b> db	TRIP SENS.: <b>42</b> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE		<input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:		R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS: <b>1</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
		CHG/ HOLE: <b>110</b>	HOLE DEPTH: <b>105</b>	SWEEP POSITION:	SWEEP START:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:		
RECEIVER	TYPE: <b>GEOSPACE 203 10 Hz</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION: <b>SERIES</b>	RESISTANCE: <b>450</b> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>12</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>					
	OFFSET GROUP 1: <b>10450'</b>	OFFSET GROUP 48: <b>110'</b>	OFFSET GROUP 49: <b>110'</b>	OFFSET GROUP 48/96: <b>10450'</b>	LEADING GROUP: <b>#96</b>					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 96		TR 10		SHOT			SPREAD			REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH	#1 LINE GROUPS		SEC	TR 1-24 REC.	TR 48-72 REC.
90	751537	193			110	105	1		41	78-1	101-4	86		
91		194			110	105	1		45	79-1	102-4			
92		196			110	105	1		49	80-1	103-4			
93		196			110	105	1		5	81-1	104-4	98		
94		197			110	105	1		9	82-1	105-4			
95		198			110	105	1		13	83-1	106-4			
96	751538	<del>198</del> 200			110	105	1		19	84-1	107-4			
97		201			110	105	1		21	85-1	108-4			
98		208			110	105	1		25	86-1	109-4			

DELAY SHOOTING AIRPLANE NOISE  
 File # 198 PARITY ERROR (HIGH COUNT) FILE # 198 8 SEC ALLOWS  
 FILE # 203, 204 8 SEC ALLOWS (TAPE CHANGE) 199  
 FILE # 205 8 SEC OF NOISE



# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky NPR OPERATIONS</b>	PROSPECT: <b>NPR-4</b>	AREA: <b>NORTH SLOPE</b>	LINE NO: <b>80</b>	
PARTY NO: <b>1173</b>		INST. ENG:		DATE: MO <b>3</b> DAY <b>20</b> YR <b>77</b>	
Total Hours <b>15</b> TRAVEL <b>1 1/2</b>					
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> ODDS EVENS	TYPE: <input type="checkbox"/> DFS <input type="checkbox"/> DFS <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK FOPMAT: <b>B</b> SEG:	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY: (LO) <input type="checkbox"/> 350 BPI (HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1000 BPI	NO. BYTES IN HEADER REC: <b>228</b>
NO. BYTES IN RECORD ID: <b>2</b>		NO. BYTES PER SCAN: <b>254</b>		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
CONFIGURATION (MAG TAPE)					
FIELD TRACE NOS.: <b>1-96</b>			AUXILIARY DATA:		
DATA CHANNEL NOS.: <b>1-96</b>			AUXILIARY CHANNEL NOS.:		
PARAMETER		RECORD LENGTH: <b>8</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ml. <input checked="" type="checkbox"/> 2 ml. ms.	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>42</b> db	
CFS I		TYPE STACK:		GATE LENGTH:	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>SINGLE</b>	
RECEIVER		TYPE: <b>GEOSPACE JOB 1042</b>		PATTERN: <b>INLINE</b>	
SPREAD		NO. OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>220'</b>	
DIAGRAMS/MISC. INFORMATION:		File # <b>209-221</b> DAILY TESTS			
		File # <b>222</b> TEST TIME BREAK			

SHOTPOINT	TR 1 to 96		TR 10		SHOT		SPREAD		REMARKS	CORE STACK							
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	#1	LINE GROUPS	#96	HT.	REC.	HT.
99	151538	223			110	105	11		5	87-1		110-4	104				
100		224			110	105	11		9	88-1		111-4					
101		225			110	105	11		13	89-1		112-4					
102		226			110	105	11		17	90-1		113-4					
103		227			110	105	11		21	91-1		114-4					
104		228			110	105	11		25	92-1		115-4					
105		229			110	105	11		29	93-1		116-4					
106		230			110	105	11		33	94-1		117-4					
107		231			110	105	11		37	95-1		118-4					
108		232			110	105	11		41	96-1		119-4					
109	151539	233			110	105	11		45	97-1		120-4					
110		234			110	105	11		49	98-1		121-4					
111		235			110	105	11		5	99-1		122-4	116				
112		237			110	105	11		9	100-1		123-4					
113		238			110	105	11		13	101-1		124-4	119				
114		239			110	105	11		17	102-1		125-4					
115		240			110	105	11		21	103-1		126-4					
116		241			110	105	11		25	104-1		127-4					
117		242			110	105	11		29	105-1		128-4					
118		243			110	105	11		33	106-1		129-4					

DELAY SHOOTING WAITING FOR CAT TO MOVE AWAY FROM LINE AIRPLANE  
 AIR PLANE NOISE  
 FILE # 233 8 SEC ALLONES  
 (1 CAP) DELAY SHOOTING WAITING FOR CAT WAITING FOR DILLS TO REMOVE OFFLINE  
 LOST 2 HRS CABLE REPAIR DELAY SHOOTING AIRPLANE NOISE  
 SP# 114 HOLE BLEW

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky NPR OPERATIONS</b>	PROSPECT: <b>NPR-4</b>	AREA: <b>NORTH SLOPE</b>	LINE NO: <b>80</b>	
PARTY NO: <b>1173</b>		INST. ENG: <b>DAVID BREAU</b>		DATE: <b>MO 3 DAY 20 YR 77</b>	
NO. BYTES IN HEADER REC: <b>228</b>		NO. BYTES IN RECORD ID: <b>2</b>		NO. BYTES PER SCAN: <b>254</b>	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS <input checked="" type="checkbox"/> DFS <input type="checkbox"/> OTHER		9 TRACK <input checked="" type="checkbox"/> 21 TRACK	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: <b>1-96</b>		AUXILIARY DATA:		PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI	
PARAMETER: RECORD LENGTH: <b>8</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN CONSTANT: <b>36</b> db	
DISPLAY: MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>42</b> db		INPUT IMPEDANCE: _____ ohms.	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>SINGLE</b>		NO. OF POSITIONS: <b>1</b>	
RECEIVER: TYPE: <b>GEOSPACE 200 10HZ</b>		PATTERN: <b>INLINE</b>		NO. OF ELEMENTS: <b>18</b>	
SPREAD: NO. OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>880'</b>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 96		TR 10 to 19		SHOT		DIR.	CDF SWITCH	SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH			NO.	OFFSET		#1	LINE GROUPS	TR 1-18	TR 19-36	TR 37-54
119	751539	244			110	105	1		25	107-1	130-4	119				
120		245			110	105	1		29	108-1	131-4					
121		246			110	105	1		33	109-1	132-4					
122		247			110	105	1		37	110-1	133-4					
123		248			110	105	1		41	111-1	134-4					
124		249			110	105	1		41							
125		250			110	105	1		41							
126		251			110	105	1		41							
127		252			110	105	1		41							
128	751540	253			110	105	1		29							
129		255				90	1		29							
130		254			110	105	1		29							
131		257			110	105	1	H5 E	29							
132		258			110	105	1		29							

SP#127 EARLY START OF RECORD  
 122 FILE# 253 8 SEC ALL ONES  
 DELAY SHOOTING BAD RADIO SIGNALS  
 MOVED UP 3 SP'S  
 SP#128 EARLY START OF RECORD  
 SP#129 NO PRELOADER LOG  
 DELAY SHOOTING AIR PLANE NOISE  
 SP#132 EARLY START OF RECORD  
 END OF LINE