





# LAND SEISMIC RECORDING LOG

	CLIENT: <b>HUSKY NPR OPERATIONS</b>	PROSPECT: <b>NPR 4</b>	AREA: <b>NORTH SLOPE</b>	LINE NO.: <b>81</b>						
PARTY NO.: <b>1173</b>		INST. ENG.: <b>R BRAND</b>		DATE: MO <b>2</b> DAY <b>18</b> YR <b>77</b>						
L.C. <b>7:00</b> AC @ <b>45 (2045)</b>		AF <b>9:30 TRAVEL 3 1/2</b>		REC TIME <b>13 3/4</b>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: SEG <b>3</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC.: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>			AUXILIARY DATA:						
	DATA CHANNEL NOS.: <b>1-96</b> (ON MAG TAPE)			AUXILIARY CHANNEL NOS.:						
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFP <input type="checkbox"/> OPERATE	FILTERS:	FREQ. <b>8</b>	LO CUT HZ SLOPE <b>18</b>	FREQ. <b>128</b>	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>42</b> db	TRIP SENS.: <b>42</b> db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE:		<input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CHG/ HOLE: <b>110</b>	HOLE DEPTH: <b>105</b>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.		
RECEIVER	TYPE: <b>GEOSPAC 20K 10 HZ</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION: <b>Seisics</b>	RESISTANCE: <b>450</b> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>1760'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>South East</b>					
	OFFSET GROUP 1: <b>10,450</b>	OFFSET GROUP <b>18</b> : <b>110'</b>	OFFSET GROUP <b>49</b> : <b>110'</b>	OFFSET GROUP 48/96: <b>10,450'</b>	LEADING GROUP: <b># 1</b>					

DIAGRAMS/MISC. INFORMATION: *Rec 001 8 seconds ones  
Rec 002 -> 008 daily tests  
Rec 009 - Test T.R.*

SHOTPOINT	TR 10		TR 10		SHOT			SPREAD			REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		96 LINE GROUPS	1	SET UP	TR 1-48
1	751	1505			110	110	105	11		49	75-1	6-8	4		
2					111	110	105	11		41	755-1	7-8			
3					112	110	105	11		33	754-1	8-8			
4					113	110	105	11		25	753-1	9-8			
5					114	110	105	11		17	752-1	10-8			
6					115	110	105	11		9	751-1	11-8			
7					116	110	105	11		49	SP1-1	12-8	10		
8					117	110	105	11		41	SP2-1	13-8			
9					118	110	105	11		33	SP3-1	14-8			
10					119	110	105	11		25	SP4-1	15-8			



# LAND SEISMIC RECORDING LOG

	CLIENT: <b>HUSKY N.P.R. OPERATIONS</b>	PROSPECT: <b>NPR-4</b>	AREA: <b>NORTH SLOPE</b>	LINE NO: <b>81</b>						
PARTY NO: <b>1173</b>		INST. ENG: <b>R. GRAND</b>		DATE: MO <b>2</b> DAY <b>19</b> YR <b>77</b>						
L.C. <b>700</b>		L.F. <b>7:25</b>		TRAVEL TIME <b>13 1/4</b>						
AF <b>800</b>		ACB'S <b>2 HOURS</b>		REC. TIME <b>13 1/4</b>						
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVEN	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 400 BPI	(M) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
(9-TRACK)	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:			
	DATA CHANNEL NOS.: <b>1-96</b>			(ON MAG TAPE)						
PARAMETER	RECORD LENGTH: <b>3</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> IFP	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: <b>8</b> Hz	LO CUT HZ SLOPE: <b>18</b>	FREQ: <b>128</b>	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>42</b> db	JRIP SENS: <b>42</b> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____		R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
	CHG/ HOLE: <b>110</b>	HOLE DEPTH: <b>105</b>	SWEET POSITION: _____	SWEET START: _____	SWEET END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____		
RECEIVER	TYPE: <b>Geophone 20x 10 Hz</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
	CONNECTION: <b>SERIES</b>	RESISTANCE: _____ ohms	STAGGER: _____							
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>1760'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: _____					
	OFFSET GROUP 1: <b>10,450</b>	OFFSET GROUP 48: <b>110'</b>	OFFSET GROUP 49: <b>110'</b>	OFFSET GROUP 96: <b>10,450</b>	LEADING GROUP: <b>#1</b>					

DIAGRAMS/MISC. INFORMATION: **rec 20 → 25 daily tests**  
**rec 25 & 26 TB TESTS**

SHOTPOINT	TR 10		TR 10		SHOT			SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH		LINE GROUPS	SET UP	TR 1-21	TR 22-31	TR 32-41
11	751505	16	17	22	28	110	105	1	13	41	5-1	13				
12				23	29	110	105			33	6-1	17-8				
13				24	30	110	105			25	7-1	18-8				
14				25	31	110	105			17	8-1	19-8				
15				26	32	110	105			33	9-1	20-8	16			
16				27	33	110	105			25	10-1	21-8				
17	751506			28	35	110	105			17	11-1	22-8				
18				29	36	110	105			9	12-1	23-8				
19				30	37	110	105			1	13-1	24-8				
20				31	38	110	105			4	14-1	25-8	22			
21				32	39	110	105			33	15-1	26-8				
22				33	40	110	105			25	16-1	27-8				
23				34	41	110	105			17	17-1	28-8				
24				35	42	110	105			33	18-1	29-8	25			
25				36	43	110	105			25	19-1	30-8				

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>HUSKY N.P.R. OPERATIONS</b>	PROSPECT: <b>N.P.R. 4</b>	AREA: <b>NORTH SLOPE</b>	LINE NO: <b>81</b>	
PARTY NO: <b>1173</b>		INST. ENG: <b>B. GRAND</b>		DATE: <b>NO 2 DAY 20 YR 77</b>	
INSTRUMENT (9-TRACK)		NO. BYTES IN HEADER REC: <b>228</b>		NO. BYTES IN RECORD ID: <b>2</b>	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: <b>1-96</b>		AUXILIARY DATA:	
PARAMETER		RECORD LENGTH: <b>8</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>42</b> db	
CFS I		TYPE STACK:		GATE LENGTH:	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>SINGLE</b>	
RECEIVER		TYPE: <b>GEOSPAC 20X HZ 10</b>		PATTERN: <b>INLINE</b>	
SPREAD		NO. OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>220'</b>	

DIAGRAMS/MISC. INFORMATION: **rec 44 → 48 daily tests**  
**rec 49 TB test**

**LINE 81**

SHOTPOINT	TR 10		TR 10		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR 1-28	TR 29-36		
26	751506				50	110	105	41	20-1	31-8	28		
27					51	110	105	33	21-1	32-8			
28					52	110	105	25	22-1	33-8			
29					53	110	105	17	23-1	34-8			
30					54	110	105	33	24-1	35-8	31		
31					55	110	105	25	25-1	36-8			
32					56	110	105	41	26-1	37-8	34		
33					57	110	105	33	27-1	38-8			
34	751507				58	110	105	25	28-1	39-8			
35					60	110	105	41	29-1	40-8	37		
36					61	110	105	33	30-1	41-8			
37					62	110	105	25	31-1	42-8			
38					64	110	105	17	32-2	43-8			
39					65	110	105	9	33-2	44-8			

# LAND SEISMIC RECORDING LOG



CLIENT: <b>HUSKY N.P.R. OPERATIONS</b>	PROSPECT: <b>N.P.R. 4</b>	AREA: <b>NORTH SLOPE</b>	LINE NO: <b>81</b>
PARTY NO: <b>1173</b>	INST. ENG: <b>R. ORAND</b>	3 1/2 TRAVEL <b>Rec Time → 13 1/2</b>	
DATE: <b>MO 2 DAY 21 YR 77</b>			

INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS <input checked="" type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS X <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> FOPMAT: B <input checked="" type="checkbox"/> 21 TRACK <input type="checkbox"/> SEG <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 355 BPI    (M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI
(9-TRACK)	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>36</b> db    INPUT IMPEDANCE: _____ ohms.
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>			AUXILIARY DATA:	
	DATA CHANNEL NOS.: <b>1-96</b> (ON MAG TAPE)			AUXILIARY CHANNEL NOS.:	
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS:    FREQ. <b>8</b> LO CUT HZ SLOPE <b>18</b>	FREQ. <b>128</b> HI CUT HZ SLOPE _____    NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>7 = 42</b> db	TRIP SENS: <b>7 = 42</b> db	POLARITY CONVENTION:    PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK    ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:    CORR. SCALING:    R.C.U. NORM./ALT SW.
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Single</b>	NO. OF POSITIONS: <b>1</b>	INLINE SPACING:	LATERAL SPACING:
	CHG/ HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:
				SWEEP LENGTH:	SWEEP TAPER:
				LENGTH:	WIDTH:
				PHASE COMP:	LATERAL OFFSET:
RECEIVER	TYPE: <b>Geospace 20x 10Hz</b>	PATTERN: <b>inline</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING:	LATERAL SPACING:
	CONNECTION: <b>Series</b>	RESISTANCE: _____ ohms	STAGGER:	LENGTH:	WIDTH:
					LATERAL OFFSET:
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>1760'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SE</b>
	OFFSET GROUP 1: <b>10,450</b>	OFFSET GROUP <b>48</b> : <b>110'</b>	OFFSET GROUP <b>48</b> : <b>110'</b>	OFFSET GROUP 48/96: <b>10,450</b>	LEADING GROUP: <b># 1</b>

DIAGRAMS/MISC. INFORMATION: **Rec 66 → 76 TESTS**  
**Rec 77 TB**  
**LINE 81**

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT			SPREAD			REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		%	LINE GROUPS #1	TR 48-96	TR 48-96
40	7511	507			78	110	10.5	1			49	34-1	45-8	43	45-3 started stacking up out
41					79	110	10.5				41	35-1	46-8		
42					80	110	10.5				33	36-1	47-8		#1 dead
43					81	110	10.5				25	37-1	48-8		#9 dead
44					82	110	10.5				41	38-1	49-8	46	
45					83	110	10.5				33	39-1	50-8		
46					84	110	10.5				25	40-1	51-8		
47					85	110	10.5				17	41-1	52-8		







# LAND SEISMIC RECORDING LOG

		CLIENT: <b>HUSKY N.P.R. OPERATIONS</b>	PROSPECT: <b>N.P.R.-4</b>	AREA: <b>NORTH SCOPE</b>	LINE NO.: <b>81</b>		
PARTY NO.: <b>1173</b>		INST. ENG.: <b>B. GRAND</b>		<b>3 1/2 TRAVEL</b>		<b>14 1/2 REC TIME</b>	
DATE: <b>MO 2 DAY 24 YR 77</b>							
INSTRUMENT (9-TRACK)		<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS EVENS <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER <input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		FOPMAT: <b>B</b> <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY: (L) <input type="checkbox"/> 358 BPI    (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 900 BPI <input checked="" type="checkbox"/> 1600 BPI	
NO. BYTES IN HEADER REC: <b>228</b>		NO. BYTES IN RECORD ID: <b>2</b>		NO. BYTES PER SCAN: <b>254</b>		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: <b>1-96</b>		AUXILIARY DATA:		GAIN CONSTANT: <b>36</b> db	
DATA CHANNEL NOS.: <b>1-96</b>		(ON MAG TAPE)		AUXILIARY CHANNEL NOS.:		INPUT IMPEDANCE: _____ ohms.	
PARAMETER		RECORD LENGTH: <b>8</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	
DISPLAY		MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>42</b> db		TRIP SENS: <b>42</b> db	
CFS I		TYPE STACK:		RECORD REJECTION:		NOISE REDUCTION:	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>Single</b>		NO. OF POSITIONS: <b>1</b>	
		CHG/ HOLE: <b>110</b>		HOLE DEPTH: <b>105</b>		SWEEP POSITION:	
RECEIVER		TYPE: <b>Geospace 20x 10 HZ</b>		PATTERN: <b>inline</b>		NO. OF ELEMENTS: <b>18</b>	
		CONNECTION: <b>Series</b>		RESISTANCE: _____ ohms		STAGGER:	
SPREAD		NO. OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>1760'</b>	
		OFFSET GROUP 1: <b>10,450</b>		OFFSET GROUP <b>48</b> : <b>110'</b>		OFFSET GROUP <b>48/96</b> : <b>10,450</b>	

DIAGRAMS/MISC. INFORMATION: **REC 115 → 127 daily tests**  
**REC 128 TB**

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT				SPREAD			REMARKS:	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#96		LINE GROUPS #1	SET UP	TR 48	REC.	TR 48-96	REC.
58	7,51508				129	110	105	11		49	52-1	63-8	61					
59					130	110	105			41	53-1	64-8						
60					131	110	105			33	54-1	65-8						
61	7,51509				133	110	105			25	55-1	66-8						
62					134	110	105			17	56-1	67-8						
63					135	110	105			33	57-1	68-8	64					
64					136	110	105			25	58-1	69-8						
65					138	110	105			17	59-1	70-8						
66					139	110	105			33	60-1	71-8	67					

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky N.P.R. OPERATIONS</b>	PROSPECT: <b>N.P.R. - 4</b>	AREA: <b>NORTH SLOPE</b>	LINE NO: <b>81</b>	
PARTY NO: <b>1173</b>		INST. ENG: <b>B. O'RAID</b>		DATE: <b>NO 2 DAY 25 YR 77</b>	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS I <input checked="" type="checkbox"/> DFS II <input type="checkbox"/> OTHER		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
NO. BYTES IN HEADER REC: <b>228</b>		NO. BYTES IN RECORD ID: <b>2</b>		GAIN CONSTANT: <b>36</b> db	
NO. OF TRACKS: <b>1.5 OUT</b>		NO. OF TRACKS: <b>1.5 IN</b>		INPUT IMPEDANCE: _____ ohms	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: <b>1-96</b>		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:	
DATA CHANNEL NOS.: <b>1-96</b> (ON MAG TAPE)		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. <b>8</b> LO CUT HZ SLOPE <b>18</b>	
PARAMETER: RECORD LENGTH: <b>8</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		HI CUT HZ SLOPE _____	
DISPLAY: MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>42</b> db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I: TYPE STACK:		GATE LENGTH:		CORR. SCALING: _____	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>SINGLE</b>		NO. OF POSITIONS: <b>1</b>	
RECEIVER: TYPE: <b>GEOSPACE 20x 10 Hz</b>		PATTERN: <b>INLINE</b>		NO. OF ELEMENTS: <b>18</b>	
CONNECTION: <b>SERIES</b>		RESISTANCE: _____ ohms		STAGGER: _____	
SPREAD: NO. OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>320'</b>		SHOTPOINT INTERVAL: <b>1760'</b>	
OFFSET GROUP 1: <b>10,450</b>		OFFSET GROUP 48: <b>110'</b>		OFFSET GROUP 48/96: <b>10,450</b>	

DIAGRAMS/MISC. INFORMATION: **REC 140 → 152 daily tests**  
**LINE 81**      **REC 153 TB TEST**

SHOTPOINT	TR to		TR to		SHOT				SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#		LINE GROUPS	#	TR 1-48	TR 48-96
67	75150	16	17	22	154	110	105	11		49	61-1	72-8	70			
68					155	110	105			41	62-1	73-8				
69					156	110	105			33	63-1	74-8				
70					157	110	105			25	64-1	75-8				
71					158	110	105			17	65-1	76-8				
72					159	110	105			33	66-1	77-8	73			
73					160	110	105			25	67-1	78-8				
74					161	110	105			17	68-1	79-8				
75					162	110	105			9	69-1	80-8				
76					163	110	105			25	70-1	81-8	76			
77	751510				165	110	105	75	S	17	71-1	82-8				
78					166	110	105	75	S	9	72-1	83-8				

No shuttle truck today

rec 164 8 seconds ones  
rec 3201



