





LAND SEISMIC RECORDING LOG

	CLIENT: Husky WPR OPERATIONS	PROSPECT: NPA-4	AREA: NORTH SLOPE	LINE NO: 83					
PARTY NO: 1173		INST. ENG: Total 1 1/2 TRAVEL 1 1/2		DATE: MO 5 DAY 8 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: B	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: A DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96				AUXILIARY DATA:				
	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)				AUXILIARY CHANNEL NOS.:				
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LD CUT HZ SLOPE 18	FREQ. 128 HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 42 db	TRIP SENS: 42 db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____		NUMBERS ON MAG. TAPE: _____		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:		F.C.U. NORM./ALT SW.	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ MOLE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: GEOSPACE JOB 10HZ	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: SERIES	RESISTANCE: 450 ohms							
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 6	DIRECTION OF PROGRESSION: EAST		LEADING GROUP: 1		
	OFFSET GROUP 1: 11450'	OFFSET GROUP 96 : 110'	OFFSET GROUP 47 : 110'	OFFSET GROUP 96/96 : 16450'					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 96		TR 10		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET	TR 1-48	TR 49-96	TR 1-48	TR 49-96
21	75/16/15	37			110	105	1			33	15-1	26-8	22				
22		38			110	105	1			25	16-1	27-8					
23		39			110	105	1			17	17-1	28-8					
24		40			110	105	1	75 E		9	18-1	29-8					
25		41			110	105	1			1	19-1	30-8					
26		42			110	105	1			41	20-1	31-8	28				
27		43			110	105	1			33	21-1	32-8					
28		44			110	105	1			25	22-1	33-8					
29		45			110	105	1	60 E		17	23-1	34-8					

LAND SEISMIC RECORDING LOG

	CLIENT: Husky NPR OPERATIONS	PROSPECT: NPR-4	AREA: NORTH SLOPE	LINE NO: 83						
PARTY NO: 1173		INST. ENG: REC HRS 16.5 TRAVEL 1		DATE: 5 DAY 9 YR 77						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS	TYPE: <input type="checkbox"/> DFS III	<input checked="" type="checkbox"/> 9 TRACK	<input type="checkbox"/> GAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI	(H) <input type="checkbox"/> 712 BPI		
	<input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 17-48 & 49-96	<input type="checkbox"/> EVENS	<input type="checkbox"/> DFS II	<input type="checkbox"/> 21 TRACK	<input type="checkbox"/> UNGAPPED	(L) <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 1600 BPI		
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254		RECORD NUMBERS: 8 DEC		GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:			
DATA CHANNEL NOS.: 1-96		(ON MAG TAPE)								
PARAMETER	RECORD LENGTH: 8 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL	<input type="checkbox"/> MANUAL	FILTERS: FREQ. 8 LO CUT 18 HI CUT _____	<input type="checkbox"/> IN	NOTCH FILTER: <input type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> TRACE	<input type="checkbox"/> FLOAT	<input type="checkbox"/> AMPLIFIER	<input type="checkbox"/> FINAL	<input type="checkbox"/> OPERATE	<input type="checkbox"/> NEGATIVE	<input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE		
CFS I	TYPE STACK:	INITIAL GAIN: 42 db	TRIP SENS.: 42 db	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE	PATTERN: SINGLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
VIBROSEIS <input type="checkbox"/>		CHG/HQE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	
RECEIVER	TYPE: GEOSPACE 200 10HZ	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
CONNECTION: SERIES		RESISTANCE: 450 ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 6	DIRECTION OF PROGRESSION: EAST					
OFFSET GROUP 1: 10450'		OFFSET GROUP 48 : 110'	OFFSET GROUP 42 : 110'	OFFSET GROUP 48/96 : 10450'	LEADING GROUP: 1					

DIAGRAMS/MISC. INFORMATION: **FILE #46-58 DAILY TESTS**



FILE #59 TEST TIME BREAK

SHOTPOINT	TR 1 to 96		TR 10 to 19		SHOT		SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		CDP SWITCH	LINE GROUPS	TR 1-48
30	15	60	19	22	110	105	1	35	45	35-8	24-1	
31	15	61			110	105	1	37	37	36-8	25-1	
32		62			110	105	1	29	29	37-8	26-1	
33	15	64			110	105	1	21	21	38-8	27-1	
34		65			110	105	1	13	13	39-8	28-1	
35		66			110	105	1	41	41	40-8	29-1	37
36		67			110	105	1	33	33	41-8	30-1	
37		68			110	105	1	25	25	42-8	31-1	
38		69			110	105	1	17	17	43-8	32-1	
39		70			110	105	1	45	45	44-8	33-1	41
40		71			110	105	1	37	37	45-8	34-1	
41		72			110	105	1	29	29	46-8	35-1	
42		73			110	105	1	21	21	47-8	36-1	
43		74			110	105	1	13	13	48-8	37-1	
44		75			110	105	1	5	5	49-8	38-1	
45		76			110	105	1	45	45	50-8	39-1	41
46		77			110	105	1	37	37	51-8	40-1	
47		78			110	105	1	29	29	52-8	41-1	
48		79			110	105	1	21	21	53-8	42-1	
49		82			110	105	1	13	13	54-8	43-1	

FILE #63 8SEC ALL ONES (GAP CHANGE)

OMIT FILE #78, 79

LAND SEISMIC RECORDING LOG

	CLIENT: Hasky NPA OPERATIONS	PROSPECT: NPA-4	AREA: NORTH SLOPE	LINE NO: 83					
PARTY NO: 1173		INST. ENG.		DATE: MO 05 DAY 9 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18		HI CUT HZ SLOPE		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> AOC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 42 db	TRIP SENS.: 42 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:	
SOURCE	<input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: GEOSPACE 200 10A2	PATTERN: INLINE	RESISTANCE: 450 ohms	STAGGER:	INLINE SPACING:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: 76	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 6	DIRECTION OF PROGRESSION: EAST	LEADING GROUP: 1			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 96		TR. 10 to 96		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DR.	COP SWITCH	LINE GROUPS		SET	HY.	REC.	HY.	REC.
50	NS116117	84			110	105	1			41	55-8	44-1	52				
51		85			110	105	1			33	56-8	45-1					
52		86			110	105	1			28	57-8	46-1					
53		87			110	105	1			17	58-8	47-1					
54		88			110	105	1			45	59-8	48-1	54				
55		89			110	105	1			37	60-8	49-1					
56		90			110	105	1			29	61-8	50-1					
57		91			110	105	1			21	62-8	51-1					
58		92			110	105	1			13	63-8	52-1					
59		93			110	105	1			5	64-8	53-1					
60		94			110	105	1			45	65-8	54-1	54				
61		95			110	105	1			37	66-8	55-1					
62		96			110	105	1			27	67-8	56-1					
63		97			110	105	1			21	68-8	57-1					
64		98			110	105	1			13	69-8	58-1					

LAND SEISMIC RECORDING LOG

	CLIENT: Husky NPA OPERATIONS	PROSPECT: NPA-4	AREA: NORTH SLOPE	LINE NO: 83	
PARTY NO: 1173	INST. ENG: TOTAL 16 TRAVEL 1	DATE: MO 5 DAY 10 YR 77			

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: B <input type="checkbox"/> GAPPED <input type="checkbox"/> ONGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI
NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: (1) (2) (3) (4) (5) (6) (7) ohms		

CONFIGURATION (MAG TAPE)	AUXILIARY DATA:
FIELD TRACE NOS.: 1-96	AUXILIARY CHANNEL NOS.:
DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)	

PARAMETER	RECORD LENGTH: 8 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: <input checked="" type="checkbox"/> FREQ	LO CUT HZ SLOPE: 18	HI CUT HZ SLOPE: 128	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> GAG <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 42 db	TRIP SENS: 42 db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CHG/ HOLE: 100	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:

RECEIVER	TYPE: GEOSPACE 200 10HZ	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:
	CONNECTION: SERIES	RESISTANCE: 450 ohms	STAGGER:	LENGTH:	WIDTH:
					LATERAL OFFSET:



SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 1760'	FOLD: 6	DIRECTION OF PROGRESSION: EAST
	OFFSET GROUP 1: 10450'	OFFSET GROUP 48: 110'	OFFSET GROUP 49: 110'	OFFSET GROUP 48/96: 10450'	LEADING GROUP: 1

DIAGRAMS/MISC. INFORMATION: **TAPE # 751617 FILE # 99-112 DAILY TESTS** **LAST 1/2 POOR VISIBILITY**

TAPE # 751618 FILE # 113 PSEP ALLONS **FILE # 114 TEST TIME BREAK**

SHOTPOINT	TR. 1 to 96		TR. to		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-48
65	751618	115			110	105	11		41	70-8	59-1	67	
66		116			110	105	11		33	71-8	60-1		
67		117			110	105	11		49	72-8	61-1	70	
68		118			110	105	11		41	73-8	62-1		
69		119			110	105	11	330 W	33	74-8	63-1		UPHOLD JOB - 25' FROM HOLE
70		120			110	105	11	330 E	25	75-8	64-1		
71		121			110	105	11		17	76-8	65-1		
72		122			110	105	11		9	77-8	66-1		
73		123			110	105	11	75 3/4	1	78-8	67-1		
74		124			110	105	11	45 S	41	79-8	68-1	76	
75		125			110	105	11		33	80-8	69-1		
76		126			110	105	11	40 SW	25	81-8	70-1		
77		127			110	105	11		17	82-8	71-1		
78		128			110	105	11		9	83-8	72-1		
79		129			110	105	11		1	84-8	73-1		
80		130			110	105	11		41	85-8	74-1	82	
81		131			110	105	11		33	86-8	75-1		
82		132			110	105	11		25	87-8	76-1		
83		133			110	105	11		17	88-8	77-1		
84	751619	134			110	105	11		9	89-8	78-1		FILE # 134 PSEP ALLONS [TAPE CHANGE]

LAND SEISMIC RECORDING LOG

	CLIENT: Husky NPR OPERATIONS	PROSPECT: NPA-4	AREA: NORTH SLOPE	LINE NO: 83						
PARTY NO: 1173		INST. ENG:		DATE: MO 5 DAY 10 YR 77						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:			
PARAMETER	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)			GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE			FILTERS: FREQ. 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE _____			
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 12 db	TRIP SENS: 12 db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY: <input type="checkbox"/> IN <input type="checkbox"/> OUT
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM/ALT SW.
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	TYPE: GEOSPACE 2nd 10HZ	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 7760'	FOLD: 6	DIRECTION OF PROGRESSION: EAST		LEADING GROUP: 1			
DIAGRAMS/MISC. INFORMATION:										

SHOTPOINT	TR. 1 to 96		TR. 96 to 192		SHOT										SPREAD	REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIE	CDP SWITCH	LINE GROUPS 96		HY.	TR 1-96			HY.	TR 96-192		
85	136	136			19	105	1	50	W	19	90-8	79-1	88							
86	137				19	105	1			41	91-8	80-1								
87	138				19	105	1			33	92-8	81-1								
88	139				19	105	1	119	W	25	93-8	82-1								
89	140				19	105	1			41	94-8	83-1	91							
90	141				19	105	1			33	95-8	84-1								
91	142				19	105	1	145	W	25	96-8	85-1								
92	143				19	105	1			17	97-8	86-1								
93	144				19	105	1			17	98-8	87-1								
94	145				60	60	1			17	99-8	88-1								
95	146				19	105	1			17	100-8	89-1								
											*2x60' HOLES - 60 lbs / HOLES - 25' MAAT									