



LAND SEISMIC RECORDING LOG



	CLIENT: <u>AWRY</u>	PROSPECT: <u>NPR-4</u>	AREA: <u>NORTH SLOPE, ALASKA</u>	LINE NO: <u>085</u>						
PARTY NO: <u>119</u>		INST. ENG: <u>BEITSCHE</u>		DATE: <u>MO 4 DAY 28 YR 77</u>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 2 TRACK	POP. MAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: _____		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____				AUXILIARY DATA: _____					
	DATA CHANNEL NOS.: _____				AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE	FREQ. _____	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/>	INITIAL GAIN: _____ db	TRIP SENS: _____ db	RECORD REJECTION: _____	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE	DOWNBREAK UPBREAK } ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR SCALING: _____	R.C.U. NORM/ALT SW. _____				
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
	CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP. _____		
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
SPREAD	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____				
	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: <u>EAST</u>	LEADING GROUP: <u>1</u>				
DIAGRAMS/MISC. INFORMATION:										

DAILY TEST F# 1-9

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#96		LINE GROUPS	#1	#2	TR 1-48	TR 48-96
1	2511319A	11			10V	1015				49	T24	19-4	13				
2		12								49	T24	18-4					
3		13								49	T24	18-4					
4		14								49	T24	18-4					
5		15								49	T24	18-4					
6		16								49	T24	18-4					
7		17								49	T24	18-4					
8		18								49	T24	18-4					
9		19								49	T24	18-4					
10		20								45	T20	17-4					
11		21								41	T16	20-4					
12		22								37	T12	21-4					
13		23								33	T8	22-4					
14		24								29	T4	23-4					
15		25								25	1-1	24-4					
16		26								21	2-1	25-4					
17		27								17	3-1	26-4					
18		28								13	4-1	27-4					
19		29								9	5-1	28-4					
20	751140D	30								5	6-1	29-4					
21		31								1	7-1	30-4					
22		32								45	8-1	31-4	25				

CORR. STACK
 TR 1-48 REC. HY. TR 48-96 REC.
 3
 7
 11
 15
 19
 25, 26

LAND SEISMIC RECORDING LOG

	CLIENT: <u>HOJRY</u>	PROSPECT: <u>NPR-4</u>	AREA: <u>NORTH SLOPE ALASKA</u>	LINE NO: <u>085</u>					
PARTY NO: <u>1195</u>		INST. ENG: <u>Bertsch</u>		DATE: <u>MO 4 DAY 28 YR 77</u>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	POPMAT: SEG <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) (2) (3) (4) (5) (6) (7)		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: _____ DATA CHANNEL NOS: _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS: _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	DOWNBREAK UPBREAK: <input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				SPREAD			REMARKS	CORR. STACK TRS			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		#1	#2	#3	#4
121		1314								41	9-1	32-4				71
122		35								37	10-1	33-4				75
123		316								33	11-1	34-4				79
124		37								29	12-1	35-4				83
125		38								25	13-1	36-4				87
126		39								21	14-1	37-4				91
127		410								17	15-1	38-4				
128		41								49	16-1	39-4				
129		42								45	17-1	40-4				
130		43								41	18-1	41-4				
131		44								37	19-1	42-4				
132		45								33	20-1	43-4				
133		46								29	21-1	44-4				
134		47								25	22-1	45-4				
135		48								21	23-1	46-4				
136		49								17	24-1	47-4				
137		50								13	25-1	48-4				
138	2511404	52								9	26-1	49-4				FIRST FILE #58
139		53								5	27-1	50-4				
										1						

39-6.5 miles



LAND SEISMIC RECORDING LOG

	CLIENT: <u>HUSKY</u>	PROSPECT: <u>UPR-4</u>	AREA: <u>NORTH SWAMP, ALASKA</u>	LINE NO: <u>85</u>					
	PARTY NO: <u>1191</u>	INST. ENG: <u>Z. BERTSCH</u>		DATE: <u>MO 4 DAY 29 YR 77</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> J-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 2800 BPI	(M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: <u>220</u>	NO. BYTES IN RECORD ID: <u>2</u>	NO. BYTES PER SCAN: <u>257</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input checked="" type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>				AUXILIARY DATA: (1) <u>TW</u> (2) <u>72</u> (3) <u>NC</u> (4) <u>NC</u> (5) <u>SDS</u> (6) _____ (7) _____				
	DATA CHANNEL NOS.: <u>1-96</u> (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: <u>0</u> <u>1</u> <u>2</u> <u>3</u> <u>4</u>				
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ: <u>8</u>	LO CUT HZ SLOPE: <u>18</u>	HI CUT HZ SLOPE: <u>72</u>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT	INITIAL GAIN: <u>30</u> db	TRIP SENS: _____ db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		<input type="checkbox"/> ON DISPLAY
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW: _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>INLINE</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ HOLE: <u>105</u>	HOLE DEPTH: <u>105</u>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: <u>D20-10</u>	PATTERN: <u>INLINE</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>22'</u>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: <u>380'</u>	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: <u>SEA-PAR</u>	RESISTANCE: <u>150</u> ohms							
SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>720'</u>	SHOTPOINT INTERVAL: <u>980'</u>	FOLD: <u>1200</u>	OFFSET GROUP #1/96: <u>10450</u>	DIRECTION OF PROGRESSION: <u>EAST</u>	LEADING GROUP: <u>1</u>		
	OFFSET GROUP #: <u>10450</u>	OFFSET GROUP: <u>110</u>							

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD			REMARKS	DEAD CORR. STACK Yrs					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		A1	SEP	TE-1-75	REC.	TE-2-75	REC.
410	75114011	162			160	100				43	29-1	51-4	44					
411		163								39	29-1	52-4						
422		165								35	30-1	53-4						8
423		166								31	31-1	54-4						12
444		167								27	32-1	55-4						
445		168								23	33-1	56-4						
446		169								19	34-1	57-4						
447		170								15	35-1	58-4						
448		172								11	36-1	59-4						
449		173								7	37-1	60-4						
450		174								3	38-1	61-4						
451		175								239	39-1	62-4						15
452		176								49	40-1	62-4	98					23
453		177								45	41-1	63-4						
454		178								41	42-1	64-4						
455		179								37	43-1	65-4						
456	75114012	180								33	44-1	66-4						
457		182								29	45-1	67-4						
458		183								25	46-1	68-4						
459		184								21	47-1	69-4						



LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-4	AREA: North Slope, Alaska	LINE NO: 85	
PARTY NO: 1195		INST. ENG: R. Bernsott		DATE: MO 4 DAY 29 YEAR 77	
SAME PARAMETERS AS SHEET #1, RODNEY					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> GAPPED <input type="checkbox"/> 21 TRACK <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 350 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db INPUT IMPEDANCE: _____ ohms
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____	
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> IFF <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____ HI CUT HZ SLOPE _____ NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD: _____ CORR. SCALING: _____ R.C.U. NORM./ALT SW.
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:
	CHG/ HOLE:	HOLE DEPTH:	SWEPT POSITION:	SWEPT START:	SWEPT END:
				STAGGER:	LENGTH:
				SWEEP LENGTH:	SWEEP TAPER:
				PHASE COMP:	LATERAL OFFSET:
RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INLINE SPACING:	LATERAL SPACING:
	CONNECTION:	RESISTANCE:	STAGGER:	LENGTH:	WIDTH:
					LATERAL OFFSET:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:
	OFFSET GROUP 1:	OFFSET GROUP:	OFFSET GROUP:	OFFSET GROUP #8/96:	LEADING GROUP:

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#96		LINE GROUPS	#1	#2	TR 48-96	TR 48-96
160	751191012	A15			110V	110H					17	48-1	69-4	58			
161		A16									13	49-1	76-4				
162		A17									9	50-1	71-4				
163		A18									5	51-1	72-4				
164		A19									1	52-1	73-4				
165		A10									45	53-1	74-4	70			
166		A12									41	54-1	75-4				
167		A13									37	55-1	76-4				
168		A14									33	56-1	77-4				
169		A15									29	57-1	78-4				
170		A16									25	58-1	79-4				
171		A17									21	59-1	80-4				
172		A18									17	60-1	81-4				
173		A19									13	61-1	82-4				
174		A10									9	62-1	83-4				
175		A11									5	63-1	84-4				
176		A12									1	64-1	85-4				
177	75114015	A14									45	65-1	86-4	02	First File # 103		
178		A15									41	66-1	87-4				
179		A16									37	67-1	88-4				



LAND SEISMIC RECORDING LOG

	CLIENT: <u>Harley</u>	PROSPECT: <u>APR-4</u>	AREA: <u>North Slope</u>	LINE NO: <u>85</u>								
PARTY NO: <u>1195</u>		INST. ENG: <u>R. BERZDICH</u>		DATE: <u>MO 4 DAY 29 YR 77</u>								
SAME PARAMETERS												
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI	GAIN CONSTANT: _____ db		INPUT IMPEDANCE: _____ ohms	
	NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: _____		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.		(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____						AUXILIARY DATA: _____					
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)						AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE	FREQ. _____	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AOC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/>	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY			
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM / ALT SW.					
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
	CHG/HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____				
RECEIVER	TYPE: _____		PATTERN: _____		NO. OF ELEMENTS: _____		INLINE SPACING: _____		LATERAL SPACING: _____			
	CONNECTION: _____		RESISTANCE: _____ ohms		STAGGER: _____		LENGTH: _____		WIDTH: _____		LATERAL OFFSET: _____	
SPREAD	NO. OF GROUPS: _____		GROUP INTERVAL: _____		SHOTPOINT INTERVAL: _____		FOLD: _____		DIRECTION OF PROGRESSION: _____			
	OFFSET GROUP 1: _____		OFFSET GROUP _____		OFFSET GROUP _____		OFFSET GROUP 48/96: _____		LEADING GROUP: _____			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		SHOT					SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	SET UP	TR 1-48	TR 48-96	TR 1-48
80	7511403	108	17	22	105	165	35	37		33	68-1	89-4				
81		108								29	67-1	90-4				



LAND SEISMIC RECORDING LOG

	CLIENT: <u>HUKY</u>	PROSPECT: <u>APR-4</u>	AREA: <u>NORTH SLOPE ALASKA</u>	LINE NO: <u>85</u>					
PARTY NO: <u>1191</u>		INST. ENG: <u>BENTSON</u>		DATE: <u>4</u> DAY <u>30</u> YE <u>77</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>8</u> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI 800 BPI (HI) <input type="checkbox"/> 712 BPI 1600 BPI	
	NO. BYTES IN HEADER REC: <u>228</u>	NO. BYTES IN RECORD ID: <u>2</u>	NO. BYTES PER SCAN: <u>254</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>30</u> db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-94</u>			AUXILIARY DATA: <u>700</u> <u>78</u> <u>20</u> <u>20</u> <u>525</u> <u>16</u> <u>17</u>					
	DATA CHANNEL NOS.: <u>1-96</u> (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TRF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>8</u> LO CUT HZ SLOPE <u>18</u> HI CUT HZ SLOPE <u>72</u>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT				
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> GAGE <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY				
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>INLINE</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ HOLE: <u>10'</u>	HOLE DEPTH: <u>105'</u>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: <u>D20-10</u>	PATTERN: <u>INLINE</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>22'</u>	LATERAL SPACING: _____				
	CONNECTION: <u>SEB-PAR</u>	RESISTANCE: <u>450</u> ohms	STAGGER: _____	LENGTH: <u>300'</u>	WIDTH: _____				
SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>1200</u>	DIRECTION OF PROGRESSION: <u>EAST</u>				
	OFFSET GROUP 1: <u>10450</u>	OFFSET GROUP: <u>110'</u>	OFFSET GROUP: <u>110'</u>	OFFSET GROUP 48/96: <u>10450</u>	LEADING GROUP: <u>1</u>				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT				SPREAD			REMARKS	CORE STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	%		LINE GROUPS	#	SET	TR 1-24	TR 25-48	TR 49-72	TR 73-96
82	7511403	1109			105	105				49	70-1	98-4	88			14	44		
83		1110								45	71-1	94-4				5	9		
84		1111								41	72-1	95-4				9			
85		1112								37	73-1	96-4				13			
86		1113								33	74-1	97-4							
87		1114								29	75-1	98-4							
88		1115								25	76-1	99-4							
89		1116								21	77-1	100-4				6			
90		1118								17	78-1	101-4				10			
91		1119								13	79-1	102-4							
92		1120								9	80-1	103-4				29			
93		1122								5	81-1	104-4							
94		1124								49	82-1	105-4	100						
95		1125								45	83-1	106-4							
96		1126								41	84-1	107-4							
97	7511405	1127								37	85-1	108-4							
98		1130								33	86-1	109-4							
99		1139								29	87-1	110-4							

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husey</u>	PROSPECT: <u>NPR-4</u>	AREA: <u>NORTH SLOPE ALASKA</u>	LINE NO: <u>085</u>					
PARTY NO: <u>1195</u>		INST. ENG: <u>R. BERISCH</u>		DATE: <u>MO 4 DAY 30 YR 71</u>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> SEG <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LQ) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: _____		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____				AUXILIARY DATA:		(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: _____				
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____	HI CUT _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____	DOWNBREAK UPBREAK: <input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	P.C.U. NORM./ALT SW. _____		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____				
	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD				REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	M		1	2	3	4	
1100	7511405	140	17	22/23	26/27	29/30	32	35	37		25	88-1	111-4	100				
1101		141									21	89-1	112-4					
1102		142									17	90-1	113-4					
1103		143									13	91-1	114-4					
1104		144									9	92-1	115-4					
1105		145									5	93-1	116-4					
1106		146									1	94-1	117-4					
1107		147									45	95-1	118-4	112				
1108		148									41	96-1	119-4					
1109		149									37	97-1	120-4					
1110		150									33	98-1	121-4					
1111	7511410	151	CHANGE TAPE		100	100					29	99-1	122-4					
1112		152									25	100-1	123-4					
1113		153									21	101-1	124-4					
1114		154									17	102-1	125-4					
1115		155									13	103-1	126-4					
1116		156									9	104-1	127-4					
1117		157									5	105-1	128-4					
											1	106-1	129-4					

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husey</u>	PROSPECT: <u>NPR-C/</u>	AREA: <u>NORTH SLOPE, ALASKA</u>	LINE NO. <u>85</u>	
PARTY NO. <u>1155</u>		INST. ENG. <u>R. BERTSCH</u>		DATE: <u>4</u> DAY <u>30</u> YR <u>77</u>	

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODS & EVENS <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS X <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER		<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK FOPMAT: <input type="checkbox"/> SEG		<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
(9-TRACK)	NO. BYTES IN HEADER REC.:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:	
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. _____		LO CUT HZ SLOPE _____	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD: _____	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
RECEIVER	CONNECTION:	RESISTANCE: _____ ohms	NO. OF ELEMENTS:		INLINE SPACING:		LATERAL SPACING:	
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:		FOLD:		DIRECTION OF PROGRESSION:	
	OFFSET GROUP 1:	OFFSET GROUP _____:	OFFSET GROUP _____:		OFFSET GROUP 48/96:		LEADING GROUP:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT			SPREAD			REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH		LINE GROUPS #/	STY UP	TR. 1-48	TR. 48-96
1118	1157	1158	11	22	23	26	27	29	30	32	35	37			
1119		1159				60'	1.05'				49	108-1	130-4		
1120		1160									45	109-1	130-4		
1121		1161									41	108-1	132-4	CDP SET 37 FOR SP 121	
1122		1162									38	108-1	133-4		
1123		1163									33	110-1	134-4		
1124		1164									29	112-1	135-4		
											25	112-1	136-1		

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-1</u>	AREA: <u>NORTH SLOPE ALASKA</u>	LINE NO: <u>81</u>					
	PARTY NO: <u>1195</u>	INST. ENG: <u>RANDALL BEARDS</u>		DATE: <u>MO 5 DAY 2 YR 72</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>SEG 2</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC: <u>226</u>	NO. BYTES IN RECORD ID: <u>2</u>	NO. BYTES PER SCAN: <u>254</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>				AUXILIARY DATA:				
	DATA CHANNEL NOS.: <u>1-46</u> (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: _____				
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 8 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> STEP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>9</u>	LO CUT HZ SLOPE <u>19</u>	HI CUT HZ SLOPE <u>72</u>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>30</u> db	TRIP SENS.: <u>30</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>INLINE</u>	NO. OF POSITIONS: <u>1</u>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CHG/ HOLE: <u>105'</u>	DEPTH: <u>105'</u>	SWEEP POSITION:	SWEEP START:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: <u>D20-10</u>	PATTERN: <u>INLINE</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>22'</u>	LATERAL SPACING:	STAGGER:	LENGTH: <u>130'</u>	WIDTH:	LATERAL OFFSET:
	CONNECTION: <u>SER-PAR</u>	RESISTANCE: <u>450</u> ohms	STAGGER:	LENGTH: <u>130'</u>	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: <u>94</u>	GROUP INTERVAL: <u>226'</u>	SHOTPOINT INTERVAL: <u>380'</u>	FOLD: <u>1200</u>	DIRECTION OF PROGRESSION: <u>EAST</u>				
	OFFSET GROUP 1: <u>10450</u>	OFFSET GROUP <u>49</u> : <u>110'</u>	OFFSET GROUP <u>48</u> : <u>110'</u>	OFFSET GROUP 48/96: <u>16050</u>	LEADING GROUP: <u>1</u>				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD				REMARKS:	DEPT. CORR. STACK TIES				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#96	LINE GROUPS		M/	ST	TR. 1-18	TR. 19-36	TR. 37-54
11205	7511466	1779			105	105				45	113-1	136-4	130	DAILY TESTS #165-178				
11216		1783							128	N	41	114-1	137-4					
11217		1786									37	115-1	138-4					
11218		1787									33	116-1	139-4					
11219	7511407	1779			1105	1105				29	117-1	140-4	142	First Five #178				
11319		1820								25	118-1	141-4						
1131		1821								21	119-1	142-4						
1132		1822								17	120-1	143-4						
1133		1823								13	121-1	144-4						
1134		1824								9	122-1	145-4						
1136		1825								5	123-1	146-4						
1136		1826								1	124-1	147-4						
1137		1827								46	125-1	148-4	142					
1138		1828								41	126-1	149-4						
1139		1829								37	127-1	150-4						
1140		1830								33	128-1	151-4						
1141		1831								29	129-1	152-4						
1142		1832								25	130-1	153-4						

18-20 MILES

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Hoxby</u>	PROSPECT: <u>NPR-11</u>	AREA: <u>ALASKA NORTH SLOPE</u>	LINE NO: <u>85</u>						
	PARTY NO: <u>1195</u>	INST. ENG: <u>BERTSCH</u>		DATE: <u>MO 5 DAY 2 YR 77</u>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>SEG</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____		LO CUT HZ SLOPE: _____	H1 CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	CONNECTION:	RESISTANCE:	CHG./HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	OFFSET GROUP:	FOLD:		DIRECTION OF PROGRESSION:		LEADING GROUP:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT					SPREAD			REMARKS:	CORRECTION STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS #1	SET UP		TR 48	TR 48-24	TR 48-24	TR 48-24
1143	7511407	1913			105	1105				21	131-1	154-4	142				
1144		1914								17	132-1	155-4					
1145		1915								13	133-1	156-4					
1146		1916								9	134-1	157-4					
1147		1917								5	135-1	158-4					
1148		1918								1	136-1	159-4					
1149	7511408	200								45	137-1	160-4	154	First FILE #199			
1150		201						1010 N		41	138-1	161-4					
1151		202								37	139-1	162-4					
1152		203								33	140-1	163-4					
1153		204								29	141-1	164-4					
1154		205								25	142-1	165-4					
1155		206								21	143-1	166-4					
1156		207								17	144-1	167-4					#4
1157		208								13	145-1	168-4					#8
1158		209								9	146-1	169-4					*12
1159		210								5	147-1	170-4					*23, 16
1160		211								1	148-1	171-4					

LAND SEISMIC RECORDING LOG

	CLIENT: <i>Hussey</i>	PROSPECT: <i>NPR-4</i>	AREA: <i>NORTH SLOPE ALASKA</i>	LINE NO: <i>85</i>					
	PARTY NO: <i>1195</i>	INST. ENG: <i>Z BERTSCH</i>		DATE: <i>5 DAY 2 YR 77</i>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA:					
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____ HZ HZ SLOPE _____	H1 CUT _____ HZ HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DERLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____				
	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 10		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48	TR 48-96	REC.	REC.
1719	25114109	2332			100	180	35	37		33	167-1	190-4	181				
180		2334				105				29	169-1	191-4					
181		2335				160				25	169-1	192-4					
182		2337				100				21	170-1	193-4					
183		2339								17	171-1	194-4					
184		2339								13	172-1	195-4					
185		2410								9	173-1	196-4					
186		2411								5	174-1	197-4					

62 - 10.3 miles

LAND SEISMIC RECORDING LOG



CLIENT: Husky PROSPECT: NPR-4 AREA: NORTH SLOPE, ALASKA LINE NO: 95
 PARTY NO: 1195 INST. ENG: Z. BENTON DATE: MO 5 DAY 3 YR 77
 SAME PARAMETERS

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms				
CONFIGURATION (MAG TAPE)										
FIELD TRACE NOS.:										
DATA CHANNEL NOS.:										
(ON MAG TAPE)										
AUXILIARY DATA:										
AUXILIARY CHANNEL NOS.:										
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM / ALT SW			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>INLINE</u>	NO. OF POSITIONS: <u>1</u>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	CONNECTION:	CHG/ HOLE: <u>105</u>	HOLE DEPTH: <u>145</u>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPE:	PHASE COMP.	
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	OFFSET GROUP 1:	OFFSET GROUP _____	OFFSET GROUP 48/96:	DIRECTION OF PROGRESSION:			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT					SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#96 LINE GROUPS	#1		TR 1-48	TR 49-96	TR 1-48	TR 49-96	
12085	251	411	1271	1	CHANGE TAP	1105	1105				37	193-1	216-4	208				
12086		1272				90					33	194-1	212-4					
12087		1273				1105					29	195-1	218-4					
12088		1274									25	196-1	219-4					
12089		1276									21	197-1	220-4					
1210		1277				90	1105	5			17	198-1	221-4					
1211		1278				90					13	199-1	222-4					
1212		1279				1105					45	200-1	223-4	217				
1213		1280									41	201-1	224-4					
1214		1281				90					37	202-1	225-4					
1215		1282									33	203-1	226-4					
1216		1283									29	204-1	227-4					
1217		1284				90					25	205-1	228-4					
1218		1285									21	206-1	229-4					
1219		1286				90		NO N			17	207-1	230-4					
1220		1287									13	208-1	231-4					
1221		1288									9	209-1	232-4					
1222		1289									5	210-1	233-4					

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husley</u>	PROSPECT: <u>JPR-4</u>	AREA: <u>North Slope - Alaska</u>	LINE NO: <u>85</u>					
	PARTY NO: <u>1195</u>	INST. ENG: <u>Bertson</u>		DATE: <u>5 DAY 4 YR 22</u>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>SEG</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: _____			AUXILIARY CHANNEL NOS.: _____		
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	FREQ. _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/>	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R. C. U. NORM./ALT SW. _____		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	OFFSET GROUP 1: _____	DIRECTION OF PROGRESSION: _____			
DIAGRAMS/MISC. INFORMATION: _____									

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS #1		LINE GROUPS #2	TR 1-24	TR 25-48	TR 49-96
2440	751	1413	2218	2219	105	9.0	35			35	231-1	254-4				8
2441		2220				9.0				31	232-1	255-4				12
2442		2221				9.0				27	233-1	256-4				16, 4
2443		2222				9.0				23	234-1	257-4				20, 3
2444		2223				9.0	2100 N			19	235-1	258-4				
2445		2224				17.5				45	236-1	259-4	253			27
2446		2225				9.0				41	237-1	260-4				31
2447		2226				9.0				37	238-1	261-4				35
2448		2227				9.0				33	239-1	262-4				
2449		2228				9.0				29	240-1	263-4				
2450		2229				9.0				25	241-1	264-4				
2451		2230				9.0				21	242-1	265-4				14
2452		2231				9.0				17	243-1	266-4				18
2453		2232				9.0		1100 E		13	244-1	267-4				22
2454		2233				9.0				9	245-1	268-4				26
2455		2234				9.0				5	246-1	269-4				
2456		2235				9.0				25	247-1	270-4	259			
2457		2236				9.0				21	248-1	271-4				
2458		2237				9.0				17	249-1	272-4				

39 - 6.5 miles

LAND SEISMIC RECORDING LOG



CLIENT: _____ PROSPECT: _____ AREA: _____ LINE NO: _____
 PARTY NO: _____ INST. ENG: _____ DATE: MO 5 DAY 5 YR _____

INSTRUMENT (9-TRACK) 1 SYSTEM 2 SYSTEMS 1-24 & 25-48 1-48 & 49-96 ODDS & EVENS
 TYPE: DFS III DFS IV DFS V OTHER _____
 9 TRACK 21 TRACK | FOP/MAT: _____ SEG _____
 GAPPED UNGAPPED | PACKING DENSITY: (L) 356 BPI 800 BPI (H) 712 BPI 1800 BPI
 NO. BYTES IN HEADER REC: _____ NO. BYTES IN RECORD ID: _____ NO. BYTES PER SCAN: _____
 RECORD NUMBERS: DEC. OCT | GAIN CONSTANT: _____ db | INPUT IMPEDANCE: _____ ohms.
 (1) (2) (3) (4) (5) (6) (7)

CONFIGURATION (MAG TAPE)
 FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)
 AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____

PARAMETER
 RECORD LENGTH: _____ sec. | SAMPLE RATE: 1 ms. 4 ms. 2 ms. _____ ms.
 GAIN MODE: INITIAL MANUAL FINAL OPERATE
 FILTERS: FREQ. _____ LO CUT HZ SLOPE _____ HI CUT HZ SLOPE _____ NOTCH FILTER: IN OUT

DISPLAY
 MODE: FLOAT AMPLIFIER AOC DEFLOAT DIRECT | INITIAL GAIN: _____ db
 TRIP SENS: _____ db | POLARITY CONVENTION: _____ PRESSURE INCREASE ON GEOPHONE: NEGATIVE POSITIVE
 NUMBERS ON MAG TAPE: DOWNBREAK UPBREAK | ON DISPLAY

CFS I
 TYPE STACK: _____ | GATE LENGTH: _____ | RECORD REJECTION: _____ | NOISE REDUCTION: _____ NOISE THRESHOLD: _____ CORE SCALING: _____ R.C.U. NORM/ALT SW.

SOURCE
 TYPE: DYNAMITE VIBROSEIS OTHER _____ | PATTERN: _____ NO. OF POSITIONS: _____ INLINE SPACING: _____ LATERAL SPACING: _____ STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____
 CHG/HOLE: _____ HOLE DEPTH: _____ SWEEP POSITION: _____ SWEEP START: _____ SWEEP END: _____ SWEEP LENGTH: _____ SWEEP TAPER: _____ PHASE COMP: _____

RECEIVER
 TYPE: _____ | PATTERN: _____ NO. OF ELEMENTS: _____ INLINE SPACING: _____ LATERAL SPACING: _____ CONNECTION: _____ RESISTANCE: _____ ohms | STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____

SPREAD
 NO. OF GROUPS: _____ | GROUP INTERVAL: _____ | SHOTPOINT INTERVAL: _____ | FOLD: _____ | DIRECTION OF PROGRESSION: _____
 OFFSET GROUP 1: _____ | OFFSET GROUP _____ | OFFSET GROUP _____ | OFFSET GROUP 48/96: _____ | LEADING GROUP: _____

DIAGRAMS/MISC. INFORMATION:


SHOTPOINT	TR. No		TR. to		SHOT				SPREAD			REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS #1		SET	TR 1-48	TR 48-96	REC.	REC.
262	25114	149	3149		100	105				99	251-1	273-4	260			7	73.85
263			3510							45	251-1	274-4					77.88
264			3511							41	252-1	275-4					
265			3512							37	253-1	276-4					
266			3513							33	254-1	277-4					
267			3514							29	255-1	278-4				2	
268			3515			910				25	256-1	279-4					
269			3516							21	257-1	280-4					
270			3517			125				17	258-1	281-4					
271			3518							13	259-1	282-4					
272			3519							9	260-1	283-4					
273			3520							5	261-1	284-4					
274			3521							49	262-1	285-4	280				
275			3522							45	263-1	286-4					
276			3523							41	264-1	287-4					
277			3524				910			37	265-1	288-4					
278			3525							33	266-1	289-4					
279			3526				910			29	267-1	290-4					
280			3527				910			25	268-1	291-4					
281			3528				910			21	269-1	292-4					

MAGNET DISCONNECT CAP LEADS F# 359

" SWEEPER NOT CHARGED FULLY F# 261

TR3 #1, 2, 9, 0, 6, 0 - CABLE WAS PULLED LOOSE

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Huskey</u>	PROSPECT: <u>NPR-4</u>	AREA: <u>NORTH SLOPE HUSKEY</u>	LINE NO: <u>85-</u>					
	PARTY NO: <u>1191</u>	INST. ENG: <u>R. BERNSCH</u>		DATE: <u>MO 8 DAY 6 YR 72</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 212 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: <u>228</u>	NO. BYTES IN RECORD ID: <u>2</u>	NO. BYTES PER SCAN: <u>254</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>80</u> db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>			AUXILIARY DATA: <u>TW TB NC NC SPS</u>					
	DATA CHANNEL NOS.: <u>1-96</u> (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: <u>0 1 2 3 4</u>					
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>8</u>	LO CUT HZ SLOPE <u>18</u>	FREQ. <u>125</u>	HI CUT HZ SLOPE <u>72</u>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>2f</u> db	TRIP SENS.: <u>30</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/>	NUMBERS ON MAG. TAPE: <input type="checkbox"/>	DOWNBREAK UPBREAK: <input type="checkbox"/>	ON DISPLAY: <input type="checkbox"/>	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>NLINE</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: <u>10'</u>	HOLE DEPTH: <u>185-90</u>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: <u>D20-10</u>	PATTERN: <u>NLINE</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>22'</u>	LATERAL SPACING:	STAGGER:	LENGTH: <u>380'</u>	WIDTH:	LATERAL OFFSET:
	CONNECTION: <u>560-PAR</u>	RESISTANCE: <u>450</u> ohms							
SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>1200</u>	DIRECTION OF PROGRESSION: <u>EAST</u>				
	OFFSET GROUP 1: <u>10410</u>	OFFSET GROUP 48: <u>110'</u>	OFFSET GROUP 49: <u>110'</u>	OFFSET GROUP 48/96: <u>10410</u>	LEADING GROUP: <u>1</u>				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. No		TR. No		SHOT				SPREAD			REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		STY	TR 1-48	TR 49-96	TR 48-96
293	75114115	387	17	22	105	90	35	37		45	291-2	304-4	298	1	48	97,85,86
294		388				90				45	292-1	305-4		4		99,90
295		389				90				37	293-1	306-4		8		93,91
296		390				90				33	294-1	307-4		12		
297		391				90				29	295-1	308-4		16		
298		392				90				25	296-1	309-4				
299		393				90				25	297-1	310-4				
300		394				90				19	298-1	311-4				
301		395				90				13	299-1	312-4				
302	75114116	397				90				9	290-1	313-4				
303		398				90				5	291-1	314-4				
304		399				90				49	292-1	315-4	310			92,93,94
305		400				90				45	293-1	316-4				
306		401				90				41	294-1	317-4				
307		402				90				37	295-1	318-4				
308		403				75				33	296-1	319-4				
309		404				90				29	297-1	320-4				
310		405				90				25	298-1	321-4				

LAND SEISMIC RECORDING LOG

	CLIENT: <u>ANUKY</u>	PROSPECT: <u>NPR-4</u>	AREA: <u>NORTH SLOPE ALASKA</u>	LINE NO: <u>85</u>					
	PARTY NO: <u>1195</u>	INST. ENG: <u>Z. SEIBICH</u>	<u>Sam</u> <u>PARAMETERS</u>	DATE: <u>MO 4 DAY 6 YR 72</u>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG. _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 600 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____				AUXILIARY DATA: _____				
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: _____				
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____ HZ HZ SLOPE _____	FREQ. _____	HI CUT _____ HZ HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM / ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CNG/HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: _____	RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	OFFSET GROUP: _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		HT.	REC.	HT.	REC.	
311	75114116	4106			10.5	10.5	35	37		21	299-1	322-4	310				
312		4107								17	300-1	323-4					
313		4108								13	301-1	324-4					
314		4109								9	302-1	325-4					
315		4110								5	303-1	326-4					
316		4111								49	304-1	327-4					
317		4112								45	305-1	328-4					
318		4113								41	306-1	329-4					
319		4114								37	307-1	330-4					
320		4115								33	308-1	331-4					
321		4116								29	309-1	332-4					
322		NO RECORD								25	310-1	333-4		No Record - Shot Fired, Amp. Fault, Shotter Didn't Release Head -			
					CHANGE TAPE 105/105												
323	75114117	4125								21	311-1	334-4					
324		4126								17	312-1	335-4					
325		4127								13	313-1	336-4					
326		4128								9	314-1	337-4					
327		4129								5	315-1	338-4					
328		4130								1	316-1	339-4					



LAND SEISMIC RECORDING LOG

	CLIENT: <u>ANISIC</u>	PROSPECT: <u>NPR-4</u>	AREA: <u>NORTH SLOPE, ALASKA</u>	LINE NO: <u>EJ</u>							
	PARTY NO: <u>1195</u>	INST. ENG: <u>Z. BEUTSCH</u>	DATE: <u>MO 5 DAY 6 YR 22</u>								
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____	CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)		AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____		PARAMETER RECORD LENGTH: _____ sec. SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms. GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input type="checkbox"/> IFF <input type="checkbox"/> FINAL		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	FILTERS: _____ LO CUT HZ SLOPE _____ HI CUT HZ SLOPE _____ NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		POLARITY CONVENTION: _____ PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____ NOISE THRESHOLD: _____		CORR. SCALING: _____		R.C.U. NORM./ALT SW.			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	CHG/HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	GROUP OFFSET: _____	SHOTPOINT INTERVAL: _____	OFFSET GROUP: _____	FOLD: _____	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: _____		LEADING GROUP: _____	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR no		TR to		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		#1	#2	TR-48	TR-96	TR-48
329	251	17	431		100	100	35	37		45	317-1	340-4	314				
330			432							41	318-1	341-4					
331			433							37	319-1	342-4					
332			434							33	320-1	343-4					
333			435							29	321-1	344-4					
334			436							25	322-1	345-4					
335			437							45	323-1	346-4	340				
336			438							41	324-1	347-4					
337			439							37	325-1	348-4					
338			440							33	326-1	349-4					
339			441							29	327-1	350-4					
340			442							25	328-1	351-4					



LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>JPR-4</u>	AREA: <u>NORTH SLOPE, ALASKA</u>	LINE NO: <u>85</u>									
	PARTY NO: <u>1195</u>	INST. ENG: <u>Z. BEATSON</u>		DATE: <u>MO 5 DAY 7 YR 77</u>									
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>SEG-2</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 355 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI				
	NO. BYTES IN HEADER REC: <u>228</u>	NO. BYTES IN RECORD ID: <u>2</u>	NO. BYTES PER SCAN: <u>274</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: _____ ohms.	(1)	(2)	(3)	(4)	(5)	(6)	(7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-94</u>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:						
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. <u>E</u>		LO CUT HZ SLOPE: <u>18</u>	FREQ. <u>126</u>	H1 CUT HZ SLOPE: <u>72</u>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT				
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>24</u> db	TRIP SENS: _____ db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input checked="" type="checkbox"/>	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY					
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.					
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>INLINE</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____				
RECEIVER	TYPE: <u>D20-10</u>	PATTERN: <u>INLINE</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>22'</u>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: <u>39'</u>	WIDTH: _____	LATERAL OFFSET: _____				
SPREAD	CONNECTION: <u>SEA-PAN</u>	RESISTANCE: <u>450</u> ohms	STAGGER: _____	LENGTH: <u>39'</u>	WIDTH: _____	LATERAL OFFSET: _____							
	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>806'</u>	FOLD: <u>200</u>	DIRECTION OF PROGRESSION: <u>EAST</u>								
	OFFSET GROUP 1: <u>10150</u>	OFFSET GROUP <u>96</u> : <u>110</u>	OFFSET GROUP <u>45</u> : <u>110</u>	OFFSET GROUP 48/96: <u>10450</u>	LEADING GROUP: <u>1</u>								

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT			SPREAD			REMARKS:	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	SET UP	TR 1-48	TR 48-96	TR 1-48	TR 48-96
341	751410	451	CHANGE TAPE	105	105					45	329-1	352-4	340			29,31	
342		452								41	330-1	353-4				35	
343		453								37	331-1	354-4					
344		454								33	332-1	355-4					
345		455								29	333-1	356-4					
346		456								25	334-1	357-4					
347		457								21	335-1	358-4					
348		458								17	336-1	359-4					
349		459								13	337-1	360-4					
350		460								9	338-1	361-4					
351		461								5	339-1	362-4					
352		462								1	340-1	363-4					
353		463								45	341-1	364-4	358				
354		464								41	342-1	365-4				39	
355		465								37	343-1	366-4					
356		466								33	344-1	367-4					
357		467								29	345-1	368-4					
358		468								25	346-1	369-4					


LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO: 81						
PARTY NO: 1191		INST. ENG: Z. BERTSCH		DATE: MO 5 DAY 7 YR 77						
SAME PARAMETERS										
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 900 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC.		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:				AUXILIARY DATA:					
	DATA CHANNEL NOS.:				AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. _____		LO CUT HZ SLOPE	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	RECORD REJECTION:	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE:	NUMBERS ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK:	GATE LENGTH:	NOISE REDUCTION:		NOISE THRESHOLD:	CORR. SCALING:		R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:		
RECEIVER	TYPE:		PATTERN:	NO. OF ELEMENTS:	INLINE SPACING:		LATERAL SPACING:			
	CONNECTION:		RESISTANCE:	STAGGER:	LENGTH:		WIDTH:		LATERAL OFFSET:	
SPREAD	NO. OF GROUPS:		GROUP INTERVAL:	SHOTPOINT INTERVAL:		FOLD:		DIRECTION OF PROGRESSION:		
	OFFSET GROUP 1:		OFFSET GROUP:	OFFSET GROUP:		OFFSET GROUP 48/96:		LEADING GROUP:		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT				SPREAD			REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS #		SP	TR 1-36	TR 48-96	TR 1-36	TR 48-96	
														HI	REC	HI	REC	
359	251	141	19	18	17	22	23	26	27	29	30	32	33	37				
					CHIMAINIQUE TRAPLINE 100' / 1100'					21	347-1	370-4	450					
360										17	348-1	371-4						
361										13	349-1	372-4						
362										9	350-1	373-4						
363										5	351-1	374-4						
364										1	352-1	375-4						
365										45	353-1	376-4	470					
366										41	354-1	377-4						
367										37	355-1	378-4						
368										33	356-1	379-4						
369										29	357-1	380-4						
370										25	358-1	381-4						
371										21	359-1	382-4						
372										17	360-1	383-4						
373										13	361-1	384-4						
374										9	362-1	385-4						
375										5	363-1	386-4						
376										1	364-1	387-4						



LAND SEISMIC RECORDING LOG

	CLIENT: <u>HURRY</u>	PROSPECT: <u>APR-4</u>	AREA: <u>NORTH SLOPE FLORIDA</u>	LINE NO: <u>95</u>					
	PARTY NO: <u>195</u>	INST. ENG: <u>Z BECKER</u>		DATE: <u>5</u> DAY <u>22</u> YR <u>72</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 48 & 49-96	ODDS EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG <u>5</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 336 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: <u>228</u>	NO. BYTES IN RECORD ID: <u>2</u>	NO. BYTES PER SCAN: <u>254</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>	DATA CHANNEL NOS.: <u>1-96</u>	[ON MAG TAPE]			AUXILIARY DATA: <u>72</u> <u>72</u> <u>72</u> <u>72</u> <u>72</u> <u>72</u>	AUXILIARY CHANNEL NOS.: <u>0</u> <u>1</u> <u>2</u> <u>3</u> <u>4</u>		
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 8 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TRIP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>8</u> LO CUT HZ SLOPE <u>18</u> HI CUT HZ SLOPE <u>126</u>	INDICH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT				
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>24</u> db	JRIP SENS: <u>30</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>INLINE</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/HOLE: <u>105</u>	HOLE DEPTH: <u>105</u>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	
RECEIVER	TYPE: <u>D20-10</u>	PATTERN: <u>INLINE</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>22'</u>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: <u>SER-PAR</u>	RESISTANCE: <u>400</u> ohms							
SPREAD	NO. OF GROUPS: <u>06</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>200'</u>	FOLD: <u>1200</u>	DIRECTION OF PROGRESSION: <u>EAST</u>	LEADING GROUP:			
	OFFSET GROUP 1: <u>10450</u>	OFFSET GROUP <u>06</u> : <u>110'</u>	OFFSET GROUP <u>07</u> : <u>110</u>	OFFSET GROUP <u>08</u> : <u>10450</u>					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT								SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUP	SET	TR 1-23	TR 24-32		TR 33-41	TR 42-50		
377	7511420	4917			105	110'				45	365-1	388-4	382	DAILY Tapes TAPE # 75149 F*490-495					
378		498								41	366-1	389-4		FIRST FILE # 496					
379		499								37	367-1	390-4							
380		500								33	368-1	391-4							
381		501								29	369-1	392-4							
382		502								25	370-1	393-4							
383		503								21	371-1	394-4							
384		504								17	372-1	395-4							
385		505								13	373-1	396-4							
386		506								9	374-1	397-4							
387		508								5	375-1	398-4		F*507- Record of 1104 SHOT - (2) SEC, LINE 87, SP 313, (CDP SET # 5)					
388		509								1	376-1	399-4		MORE THAN A SET RECORD					
389		510								41	377-1	400-4	394						
390		511								41	378-1	401-4							
391		5112								37	379-1	402-4							
392		5113								33	380-1	403-4							
393		5114								29	381-1	404-4							
394		5115								25	382-1	405-4							
395		5116								21	383-1	406-4							

LAND SEISMIC RECORDING LOG

	CLIENT:	PROSPECT:	AREA:	LINE NO:				
	PARTY NO:	INST. ENG:		DATE:				
				MO: DAY: YE:				
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> SEG <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 336 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:	
	DATA CHANNEL NOS.:			(ON MAG TAPE)				
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	H1 CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____	NUMBERS ON MAG. TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	B.C.U. NORM / ALT SW.	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
		CHG/ HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:
								PHASE COMP:
RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
	CONNECTION:	RESISTANCE:	ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL SPACING:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	LEADING GROUP:		
	OFFSET GROUP 1:	OFFSET GROUP _____:	OFFSET GROUP _____:	OFFSET GROUP 48/96:				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT				SPREAD			REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#96 LINE GROUPS		#1	#2	TR 1-24	TR 25-48	TR 49-96
396	2511	421	518	ORANGE TAPE	105	100				17	394-1	4024	394				
397			519							13	395-1	4094					
398			520							9	386-1	4094					
399			521							5	397-1	4104					
400			522							1	398-1	411-4					
401			524							45	389-1	412-4					
402			525							41	390-1	413-4					
403			526							37	391-1	414-4					
404			527							33	392-1	415-1					
405										29	393-1	416-4					
406										25	394-1	417-4					
407										21	395-1	418-4					
408										17	396-1	419-4					
409										13	397-1	420-4					
410										9	398-1	421-4					
										5	399-1	422-4					
										1							



LAND SEISMIC RECORDING LOG

	CLIENT: BERTSCH Husky	PROSPECT: NPR-4	AREA: MOUNT SCOPPE ALASKA	LINE NO: 85					
	PARTY NO: 195	INST. ENG: 12 Bertsch		DATE: DAY 9 YR 72					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: 2 SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	AUXILIARY DATA: (11) TW (12) TB (13) NC (14) JC (15) SPS (16) (17)	AUXILIARY CHANNEL NOS.: 0 1 2 3 4						
PARAMETER	RECORD LENGTH: 3 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> TRIP	FILTERS: FREQ 8 LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 72	NOISE FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: WLINE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: D20-10	CONNECTION: SEE PAR	PATTERN: WLINE	RESISTANCE: 430 ohms	STAGGER:	LENGTH: 380'	WIDTH:	LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 890'	FOLD: 1200	DIRECTION OF PROGRESSION: EAST	LEADING GROUP: 1			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 10		SHOT			SPREAD			REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS #/	HT	TR 48 REC	HT
4015	7511421	536			110"	1015	1			33	393-1	416-4	412	2, 42,	93-96
4016		536								49	394-1	417-4		6, 46	
4017		537								45	395-1	418-4		10	
4018		538								41	396-1	419-4		2, 14	
4019		539								37	397-1	420-4		6, 18	
4110		540								33	398-1	421-4		10, 22	
4111		541								29	399-1	422-4		3, 14, 26	94
4112		542								25	400-1	423-4		37, 18, 30	
					CHANGE TAPE									7, 11, 23, 24	
4113	7511422	544								21	401-1	424-4		7, 11, 23, 24	
4114		545								17	402-1	425-4		7, 11, 23, 24	
4115		546								13	403-1	426-4		7, 11, 23, 24	
4116		547								9	404-1	427-4			
4117		NO RECORD								5	405-1	428-4			
4118		549								49	406-1	429-4	424		
4119		549								45	407-1	430-4			
4210		550								41	408-1	431-4			
4211		551								37	409-1	432-4		4	
4222		553								33	410-1	433-4		8	
4223		553								29	411-1	434-4			

LAND SEISMIC RECORDING LOG

	CLIENT: <i>HUSKY</i>	PROSPECT: <i>NPR-4</i>	AREA: <i>NORTH SLOPE ALASKA</i>	LINE NO: <i>85</i>						
	PARTY NO: <i>1195</i>	INST. ENG: <i>BERTSCH</i>	SOURCE PARAMETERS		DATE: <i>DAY 9</i> YR <i>77</i>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> SEG <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LD) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____ DATA CHANNEL NOS. _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS. _____						
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	JRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____	DOWNBREAK UPBREAK ON DISPLAY: <input type="checkbox"/> <input type="checkbox"/>			
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW: _____			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	CHG/HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	OFFSET GROUP: _____	NO. OF ELEMENTS: _____	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT									SPREAD				REMARKS	CORE STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS #/		SET	TR 1-48	TR 49-96	TR 1-48	TR 49-96					
														NY	NY	NY	NY					
4124	7511422	5554			1165	1105					25	412-1	435-4	424			12					
4125		5555									21	413-1	436-4				16	52				
4126		5557									17	414-1	437-4				20	56				
4127		5558									13	415-1	438-4				24					
4128		5559									9	416-1	439-4				5	28				
4129		5560									5	417-1	440-4				9	32				
4130		5561									49	418-1	441-4									
4131		5562									45	419-1	442-4				3					
4132		5563									41	420-1	443-4				7					
4133		5564									37	421-1	444-4				11					
4134		5565									33	422-1	445-4				15					
4135	7511423	5566									29	423-1	446-4				4	19				
4136		5568									25	424-1	447-4									
4137		5569									21	425-1	448-4									
4138		5570									27	426-1	449-4									
4139		5571									13	427-1	450-4									
4140		5572									9	428-1	451-4									
4141		5573									5	429-1	452-4									
4142		5574									1	430-1	453-4									

78-633 miles

LAND SEISMIC RECORDING LOG



	CLIENT: Husky	PROSPECT: NPR-2/	AREA: NORTH SLOPE / LAKOTA	LINE NO.: 81						
	PARTY NO.: 1191	INST. ENG.: Z. BEITSCHE	DATE: MO 5 DAY 10 YR 77							
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DPS III <input type="checkbox"/> DPS IX <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC.: 228	NO. BYTES IN RECORD ID.: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-94				AUXILIARY DATA: (1) ZW (2) 78 (3) 102 (4) ALC (5) 525 (6) (7)					
	DATA CHANNEL NOS.: 1-94 (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: 3 1 2 3 4					
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 10 HI CUT HZ SLOPE 2 NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT					
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> FLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS.: 30 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE				NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: INLINE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: 105	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:		
RECEIVER	TYPE: 02010		PATTERN: INLINE	NO. OF ELEMENTS: 19	INLINE SPACING: 22'	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: SEA PAR		RESISTANCE: 450 ohms			STAGGER:	LENGTH: 280'	WIDTH:	LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: 94	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 890'	FOLD: 1200	DIRECTION OF PROGRESSION: EAST					
	OFFSET GROUP 1: 10450	OFFSET GROUP 48 : 110'	OFFSET GROUP 43 : 110'	OFFSET GROUP 48/96 : 10450	LEADING GROUP: 1					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	YR 1-44	YR 45-50	YR 51-55	YR 56-60
4433	2511423	583			105	101				45	431-1	454-4	448				
4441		584								41	432-1	455-4					
4445		5815								37	433-1	456-4					
4446		5816								33	434-1	457-4					
4447		5817								29	435-1	458-4					
4448		5818								25	436-1	459-4					
4449		5819								21	437-1	460-4					
4450		5810								17	438-1	461-4					
4451		5811								13	439-1	462-4					
4452		5812								9	440-1	463-4					
4453	2511424	5813	CHANGE TAPE		101	105				5	441-1	464-4		FIRST FILE # ALT 573			
4454		5814								1	442-1	465-4					
4455		5815								15	443-1	466-4	460				
4456		5816								11	444-1	467-4					
4457		5817								37	445-1	468-4					
4458		5818								33	446-1	469-4					
4459		5819								29	447-1	470-4					
4460		16120								25	448-1	471-4					

19.30 MILES

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Huskey</u>	PROSPECT: <u>NPR-4</u>	AREA: <u>South Slope, Alaska</u>	LINE NO: <u>81</u>	
PARTY NO: <u>1195</u>	INST. ENG: <u>R. ZWISCH</u>	SHEET #2		DATE: <u>MO 5 DAY 10 YE 77</u>	



INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: <input type="checkbox"/> SEG <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI
(9-TRACK)	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____			AUXILIARY DATA:			
	DATA CHANNEL NOS. _____ (ON MAG TAPE)			AUXILIARY CHANNEL NOS. _____			
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____		LO CUT HZ SLOPE _____	HI CUT HZ SLOPE _____
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AOC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____		NEGATIVE <input type="checkbox"/> POSITIVE <input type="checkbox"/>	NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH: _____	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:
		CHG/HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:
							SWEEP TAPER:
							PHASE COMP:
							LATERAL OFFSET:
RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:
	CONNECTION:	RESISTANCE:	ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	LEADING GROUP:	
	OFFSET GROUP 1:	OFFSET GROUP _____:	OFFSET GROUP _____:	OFFSET GROUP 48/96:			

DIAGRAMS/MISC. INFORMATION:
1 Jug TR down with BURST RADIATOR HOSE

SHOTPOINT	TR. no		TR. to		SHOT			SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	HT	REC	HT	REC
461	7511420	1601			10.5	10.5				17	450-1	473-4				
462		1602								17	450-1	473-4				
463		1603								13	451-1	474-4				
464		1604								7	452-1	475-4				
465		1605								5	453-1	476-4				
466		1606								49	454-1	477-4	472			
467		1607								45	455-1	478-4				
468		1608								41	456-1	479-4				
469		1609								47	457-1	480-4				
470		1610								33	458-1	481-4				
471		1611								29	459-1	482-4				
472		1612								25	460-1	483-4				
473	7511425	1613			10.5	10.5				21	461-1	484-4				
474		1614								17	462-1	485-4				
475		1615								13	463-1	486-4				
476		1616								9	464-1	487-4				
477		1617								5	465-1	488-4				
478		1618								1	466-1	489-4				

36 - 6.0 miles

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NAD-4</u>	AREA: <u>NORTH SLOPE, ALASKA</u>	LINE NO: <u>85</u>					
PARTY NO: <u>1185</u>		INST. ENG: <u>R. BENTSON</u>		DATE: <u>MO 5 DAY 11 YE 72</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: <u>228</u>	NO. BYTES IN RECORD ID: <u>2</u>	NO. BYTES PER SCAN: <u>254</u>	RECORD NUMBERS: <input type="checkbox"/> REC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>			AUXILIARY DATA: (1) <u>TW</u> (2) <u>78</u> (3) <u>ALC</u> (4) <u>NR</u> (5) <u>SP3</u> (6) _____ (7) _____					
	DATA CHANNEL NOS.: <u>1-96</u> (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: <u>1 2 3 4 5</u>					
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input checked="" type="checkbox"/> PFP	FILTERS: FREQ. <u>8</u> LO CUT HZ SLOPE <u>18</u> HI CUT HZ SLOPE <u>72</u>		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> PACC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>24</u> db	TRIP SENS: <u>24</u> db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:	CORR. SCALING:	C.U. NORM/ALT SW.	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>IN LINE</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ MOLE: <u>105</u>	HOLE DEPTH: <u>105</u>	SWEET POSITION:	SWEET START:	SWEET END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: <u>D20-10</u>	PATTERN: <u>IN LINE</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>22'</u>	LATERAL SPACING:	STAGGER:	LENGTH: <u>300</u>	WIDTH:	LATERAL OFFSET:
	CONNECTION: <u>SQR PAR</u>	RESISTANCE: <u>450</u> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>850'</u>	SHOTPOINT INTERVAL: <u>850'</u>	FOLD: <u>100</u>	DIRECTION OF PROGRESSION: <u>EAST</u>				
	OFFSET GROUP 1: <u>10150</u>	OFFSET GROUP 49: <u>110'</u>	OFFSET GROUP 99: <u>110'</u>	OFFSET GROUP 48/96: <u>10450</u>	LEADING GROUP: <u>1</u>				

DIAGRAMS/MISC. INFORMATION:

WELL ON CAMP MADE

SHOTPOINT	TR. to		TR. to		SHOT				SPREAD			REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	INT.	REC.	INT.	REC.	
5103	7511426	16517			105	105				45	491-1	514-4	508				7324	
5104		16512								41	492-1	515-4					7728	
5105		16513								37	493-1	516-4					7824	
5106		16514								33	494-1	517-4						
5107		16515								29	495-1	518-4						
5108		16516								25	496-1	519-4						
5109		16517								21	497-1	520-4						
5110		16518								17	498-1	521-4	514					
			MECHANICAL TAPES															
5111	7511427	16610			105	105				37	499-1	522-4		First F.L.O. #659				
5112		16611								33	500-1	523-4						
5113		16612								33	500-1	523-4		CDP SET FOR SP 512 'oops'				
5114		16613								28	502-1	525-4						
5115		16614								21	503-1	526-4						
5116		16615								17	504-1	527-4						
5117		16616								13	505-1	528-4		Misfire #666 - VOLUME DOWN ON SHOOTER'S TAP 1				
5118		16618								15	506-1	529-4	483					
5119		16619								41	507-1	530-4						
5120		16710								37	508-1	531-4						

18 2.0 miles

LAND SEISMIC RECORDING LOG

	CLIENT: <i>ANOKI</i>	PROSPECT: <i>NPR-4</i>	AREA: <i>NORTH SLOPE ALASKA</i>	LINE NO: <i>85</i>								
	PARTY NO: <i>1195</i>	INST. ENG: <i>T. BERTSCH</i>		DATE: <i>MO 5 DAY 11 YR 77</i>								
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI 800 BPI (H) <input type="checkbox"/> 712 BPI 1000 BPI	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	
	NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: _____		RECORD NUMBERS: (1) (2) (3) (4) (5) (6) (7)		AUXILIARY DATA: _____			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____				AUXILIARY CHANNEL NOS.: _____				DATA CHANNEL NOS.: _____ (ON MAG TAPE)			
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT: _____ HZ SLOPE _____	FREQ. _____	HI CUT: _____ HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE			NUMBERS ON ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM. ALT SW.				
GFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	CORR. SCALING: _____		R.C.U. NORM. ALT SW.						
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
RECEIVER	CONNECTION: _____	RESISTANCE: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____						
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____			LEADING GROUP: _____				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD				REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS #	SET UP		TR 1-41	TR 42-50
15121	7511427	1621			100'	100'				33	509-1	532-4	523		
15122		1622								28	510-1	533-4			
15123		1623								25	511-1	534-4			
15124		1624								21	512-1	535-4			
15125		1625								17	513-1	536-4			59
15126		1626								13	514-1	537-4			63
15127		1627								9	515-1	538-4			67
15128		1628								5	516-1	539-4			71
15129		1629								49	517-1	540-4	335		75
15130		1630								45	518-1	541-4			
					CHANGE TAPE										
15131	7511428	1631			100'	100'				37	519-1	542-4		FIRST FILE # 68!	
15132		1632								33	520-1	543-4			2,4
15133		1633								33	521-1	544-4			
15134		1634								29	522-1	545-4			
15135		1635								25	523-1	546-4			79, 14, 18
15136		1636								21	524-1	547-4			
15137		1637								17	525-1	548-4			
15138		1638								13	526-1	549-4			

70.60 MILES

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: NPR-4	AREA: NORTH SLOPE, ALASKA	LINE NO: 81					
	PARTY NO: 1195	INST. ENG: R. BERTSCH		DATE: MO 5 DAY 11 YR 77					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AOC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	B.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: _____			
DIAGRAMS/MISC. INFORMATION: _____									

SHOTPOINT	TR. 1 to		TR. 10 to		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS		SET UP	TR 1-48	TR 49-96	TR 1-48	TR 49-96
5139	7514	1699			110 W	110 W				9	422-1	550-4	635				
5140		1690								5	428-1	551-4					
5141		1691								1	429-1	552-4					
5142		1692								45	530-1	553-4					
5143		1693								41	531-1	554-4					
5144		1694								37	532-1	555-4					
5145		1695								33	533-1	556-4					
5146		1696								29	534-1	557-4					
5147		1697								25	535-1	558-4					
5148		1698								21	536-1	559-4					1, 4
5149		1699								17	537-1	560-4					5, 8
5150		1700								13	538-1	561-4					12
5151		1701								9	539-1	562-4					14
5152		1702								5	540-1	563-4					20
5153		1703								1	541-1	564-4					

LAND SEISMIC RECORDING LOG

PAGE 1 OF 3

	CLIENT: HUSKY OPERATIONS	PROSPECT: DET - 4	AREA: NORTH SLOPE	LINE NO: 5885	
	PARTY NO: 1195	INST. ENG.:		DATE: MO 5 DAY 12 YR 77	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 2 TRACK	FOPMAT: _____ SEG: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.			
FIELD TRACE NOS.:	DATA CHANNEL NOS.:			(ON MAG TAPE)					
PARAMETER	RECORD LENGTH:	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> IFF <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	FREQ. _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEDPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	CONNECTION: Series	RESISTANCE: _____ ohms	STAGGER:	INLINE SPACING:	LENGTH:	WIDTH:	LATERAL OFFSET:		
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 12	DIRECTION OF PROGRESSION: E	OFFSET GROUP 1: 10,450	OFFSET GROUP 48: 110'	OFFSET GROUP 96: 10,450	LEADING GROUP: # 1



DIAGRAMS/MISC. INFORMATION:
 REC 704 → 707 cont
 708 → 717 daily tests

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				SPREAD		REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	BY	TR 48-50	TR 48-50	TR 48-50
554	751429	718			105	105	110		W	33		556				
555		719			110	105	110		W	29						
556		720			110	105				25						
557		721			110	105				21						
558		722			110	105				35		560				
559		723			110	105				31						
560		724			110	105				27						
561		725			110	105				23						
562		726			110	105				19						
563		727			110	105				15						
564		728			110	105				11						
565		729			110	105				49		571				
566		730			110	105				45						
567		731			110	105				41						
568		732			110	105				37						
569	751430	733			110	105				33						
570		735			110	105				29						
571		736			110	105				25						
572		737			110	105				21						
573		738			105	110	105			17						

Short Record 3/4 seconds long
 OMIT 734

LAND SEISMIC RECORDING LOG

PAGE 2 OF 3

	CLIENT: HUSKY OPERATIONS	PROSPECT: PET 4	AREA: NORTH SCOPE	LINE NO: 85					
PARTY NO:		INST. ENG.:		DATE: MO 5 DAY 12 YR 77					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. _____	LO CUT HZ SLOPE	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	JRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM. ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	CONNECTION:	RESISTANCE:	ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	OFFSET GROUP 48/96:	DIRECTION OF PROGRESSION:			
DIAGRAMS/MISC. INFORMATION:									

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT			SPREAD		REMARKS:	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		COP SWITCH	LINE GROUPS	TR 1-48	TR 49-96	TR 1-48	TR 49-96
574	751430	739			105	110	105			13						
575		740			110	105				9						
576		TT			110	105				5						
577		741			110	105				1						
578		742			110	105				45			583			
579		743			110	105				41						
580		744			110	105				37						
581		745			110	105				33						
582		746			110	105				29						
583		747			110	105				25						
584		748			110	105				45			589			
585		749			110	105				41						
586		750			110	105				37						
587		751			110	105				33						
588		752			110	105				29						
589		754			110	105				25						
590		755			110	105				21						
591	751431	756			110	105				41			585			
592		757			110	105		75 S		37						
593		758			105	110	105	110 E		33						

NO RECORD TYP problem



583

589

omit 753
7.4 second rec 590

585

LAND SEISMIC RECORDING LOG



	CLIENT: HUSKY OPERATIONS	PROSPECT: PET 4	AREA: NORTH SLOPE	LINE NO: 58 85						
PARTY NO: 1195		INST. ENG.:		DATE: MO 5 DAY 12 YR 77						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	CODES & EVENS	TYPE: <input type="checkbox"/> DPS III <input type="checkbox"/> DPS IX	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(L0) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(M1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) (2) (3) (4) (5) (6) (7)			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP	<input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. _____	LO CUT HZ SLOPE	HI CUT HZ SLOPE	NOISE FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AGC	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	JRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE:	<input type="checkbox"/> NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CHG/HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.		
RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION:	RESISTANCE:	ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	OFFSET GROUP 48/96:	LEADING GROUP:			
	OFFSET GROUP 1:	GROUP _____:	OFFSET GROUP _____:							

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48	TR 48-96	TR 1-48	TR 48-96
594	751143	759			105	110	105				29						
595		760			110	105					25						
596		761			110	105					21						
597		762			110	105					41		601				
598		763			110	105					37						
599		764			110	105					33						
600		765			110	105					29						
601		766			110	105					25						
602		767			110	105					21						
603		768			110	105					17						
604		769			105	110	105				13						

LAND SEISMIC RECORDING LOG

PAGE 1 of 3

	CLIENT: HUSKY OPERATIONS	PROSPECT: DET 4	AREA: NORTH SLOPE	LINE NO: 5885						
PARTY NO: 1195		INST. ENG:		DATE: MO 5 DAY 13 YR 77						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 800 BPI	(11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:				AUXILIARY DATA:					
	DATA CHANNEL NOS.:				AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 1 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> IFP	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	FREQ. 120	HI CUT HZ SLOPE 72	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS: 24 db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE:		<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	<input type="checkbox"/> NUMBERS ON MAG TAPE <input type="checkbox"/> UPBREAK	<input type="checkbox"/> ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: INLINE (single)	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CHG/ HOLE: 105	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:		
RECEIVER	TYPE: D20-10	PATTERN:	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION: SERIES	RESISTANCE:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:					
	OFFSET GROUP 1:	OFFSET GROUP:	OFFSET GROUP:	OFFSET GROUP 48/96:	LEADING GROUP:					

DIAGRAMS/MISC. INFORMATION:
rec 771 → 784 daily tests

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT			SPREAD			REMARKS:	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		# / LINE GROUPS	#%	TR 1-48	TR 48-96	TR 1-48	TR 48-96	
605	7511431	785			105	105				45	616-4	593-1	610					* 2 dead
606		786			105	105				41	617-4	594-1						6
607		787			105	105				37	618-4	595-1						10
608	7511432	788			105	105				33	619-4	596-1						14
609		789			105	105				29	620-4	597-1						18
610		790			105	105				25	621-4	598-1						22
611		791			105	105				21	622-4	599-1						26
612		792			105	105				17	623-4	600-1						30
613		793			105	105				13	624-4	601-1						34
614		794			105	105				9	625-4	602-1						1
615		795			105	105				41	626-4	603-1	619					5
616		796			105	105				37	627-4	604-1						9
617		797			105	105				33	628-4	605-1						
618		798			105	105				29	629-4	606-1						2
619		799			105	105				25	630-4	607-1						
620		800			105	105				21	631-4	608-1						
621		801			105	105				41	632-4	609-1	625					
622		802			105	105				37	633-4	610-1						
623		803			105	105				33	634-4	611-1						
624		804			105	105				29	635-4	612-1						

*620-4 WEAK ALL THROUGH
SPREAD (reversed?)*

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY OPERATIONS	PROSPECT: PET 4	AREA: NORTH SLOPE	LINE NO: 85						
	PARTY NO.:	INST. ENG.:		DATE: MO 5 DAY 13 YR 77						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG. _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(11) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____						
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE _____	DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/>	ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW.			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	CHG/HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 10		SHOT				SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH		#1	LINE GROUPS	#96	#57	TR 1-48
625	751432	805			105	105				25	636-4	613-1				
626		806			105	105				21	637-4	614-1				
627		807			105	105				41	638-4	615-1	631			
628		808			105	105				37	639-4	616-1				
629	751433	809			105	105				33	640-4	617-1				
630		810			105	105				29	641-4	618-1				
631		811			105	105				25	642-4	619-1				
632		812			105	105				21	643-4	620-1				
633		813			105	105				41	644-4	621-1	637			
634		814			105	105				37	645-4	622-1				
635		815			105	105				33	646-4	623-1				
636		816			105	105				29	647-4	624-1				
637		817			105	105				25	648-4	625-1				
638		818			105	105				21	649-4	626-1				
639		819			105	105				41	650-4	627-1	643			
640		820			105	105				37	651-4	628-1				
641		821			105	105				33	652-4	629-1				
642		822			105	105				29	653-4	630-1				
643		823			105	105				25	654-4	631-1				
644		824			105	105				21	655-4	632-1				

#1 dead

LAND SEISMIC RECORDING LOG

1	CLIENT: HUSKY	PROSPECT: NPR-4	AREA: NORTH SLOPE ALASKA	LINE NO.: 85
	PARTY NO.: 1195	INST. ENG.: Z. BERZSCH		DATE: 5 DAY 14 YR 77

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS <input checked="" type="checkbox"/> DFS <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B SEG:	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI
	NO. BYTES IN HEADER REC: 288	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 284	RECORD NUMBERS: 5 DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: (1) YW (2) TA (3) NC (4) NC (5) SPS (6) (7)				
	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: 0 1 2 3 4				
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: FREQ. B		LO CUT HZ SLOPE: 18	HI CUT HZ SLOPE: 72	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS: 24 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: INLINE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
	CONNECTION: SEN-PAR	RESISTANCE: 450 ohms	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.
RECEIVER	TYPE: 022-10	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 22'	LATERAL SPACING:			
	CONNECTION: SEN-PAR	RESISTANCE: 450 ohms	STAGGER:	LENGTH: 380'	WIDTH: LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: 94	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 850'	FOLD: 1200	DIRECTION OF PROGRESSION: EAST			
	OFFSET GROUP 1: 10450	OFFSET GROUP 43 : 110'	OFFSET GROUP 49 : 110'	OFFSET GROUP 48/90/10450'	LEADING GROUP: 1			

DIAGRAMS/MISC. INFORMATION:

WAITING ON DRILLS ALL DAY

SHOTPOINT	TR. 1		TR. 2		SHOT				SPREAD			REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#1		LINE GROUPS	#2	SET	TR 1-21	TR 22-33
1651	75/1434	1841			105	110S					17	662-4	639-1	655			
1652		1842									37	663-4	640-1				
1653		1843									33	664-4	641-1				
1654		1844						110W			29	665-4	642-1				
1655		1845									25	666-4	643-1				
1656		1846									21	667-4	644-1				
1657		1847						110S			17	668-4	645-1				
1658		1848									31	669-4	646-1	659			
1659		1849									27	670-4	647-1				
1660		1850									23	671-4	648-1				
1661		1851									19	672-4	649-1				
1662		1852									15	673-4	650-1				
1663		1853									11	674-4	651-1				
1664		1854						110W			31	675-4	652-1	645		44	
1665		1855						110E			27	676-4	653-1				
1666		1856									23	677-4	654-1				78
1667		1857									19	678-4	655-1				
1668	75/1435	1858									15	679-4	656-1				

LAND SEISMIC RECORDING LOG



		CLIENT: Husky	PROSPECT: NPR-4	AREA: North Slope, Alaska	LINE NO: 85				
PARTY NO: 1195		INST. ENG: R. BERTSCH		DATE: MO 5 DAY 15 YR 72					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input type="checkbox"/> OFF X <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: 226	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____					
	DATA CHANNEL NOS.: 1-94 (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TRIP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ 8	LO CUT HZ SLOPE 12	FREQ. 125 HI CUT HZ SLOPE 72	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS: 24 db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM / ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: INLINE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: 105	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: DZ6-10	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 22'	LATERAL SPACING:	STAGGER:	LENGTH: 380'	WIDTH:	LATERAL OFFSET:
	CONNECTION: See PRR	RESISTANCE: 450 ohms	STAGGER:	LENGTH: 380'	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 980'	FOLD: 1200	DIRECTION OF PROGRESSION: East				
	OFFSET GROUP 1: 10450	OFFSET GROUP 98 : 116'	OFFSET GROUP 99 : 110'	OFFSET GROUP 10450	LEADING GROUP: 1				

DIAGRAMS/MISC. INFORMATION:

Waiting on Drills All Day Again.

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD		REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		#96 LINE GROUPS #1	SEP	TR 1-48	TR 49-96
683	7511435	881			ADW	110K				45	671-1	694-4		82.60	
684		882								41	672-1	695-4		66.22	
685		883								37	673-1	696-4		20.74	
			CHANGE TABLE												
686	7511436	884			10K	110K				33	674-1	697-4	First file # 883		
687		887								29	675-1	698-4		62.78 84	
688		888								25	676-1	699-4		82.88	
689		889								21	677-1	700-4	WIND PICKING UP	86.92	
690		890				190				17	678-1	701-4		90.96	
691		891								13	679-1	702-4		94	
692		892								9	680-1	703-4			
693		893								5	681-1	704-4			
694		894								49	682-1	705-4	200		
695		895								45	683-1	706-4			
696		896								41	684-1	707-4			
697		897								37	685-1	708-4			
698		898								33	686-1	709-4			
699		899								29	687-1	710-4			
700		900								25	688-1	711-4			

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-4</u>	AREA: <u>NORTH SLOPE ALASKA</u>	LINE NO: <u>85</u>	
PARTY NO: <u>1191</u>		INST. ENG: <u>R. B. SCOTT</u>		DATE: <u>MO 5 DAY 15 YR 77</u>	

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 800 BPI (13) <input type="checkbox"/> 1600 BPI
(9-TRACK)	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.: _____	
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> OPERATE	FILTERS: FREQ. _____	LO CUT HZ SLOPE _____	HI CUT HZ SLOPE _____	NOYCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____	NUMBERS ON ON MAG TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
	CHG/HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:
RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
	CONNECTION:	RESISTANCE: _____ ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	LATERAL OFFSET:	
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	OFFSET GROUP _____	OFFSET GROUP 48/96:	LEADING GROUP:

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				SPREAD			REMARKS:	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS #1		SET UP	TR 1-48	TR 48-96	TR 1-48	TR 48-96	
701	7511436	901			105	105				21	689-1	712-4	70					
702		902								17	690-1	713-4						
703		903								13	691-1	714-4						
704		904								9	692-1	715-4						
			CHANGE TAP															
705	7511437	905			105	105				5	693-1	716-4						
706		906								49	694-1	717-4	712	WIND DIED DOWN COMPLETELY				
707		907								45	695-1	718-4		3rd TAP, No 20F				
708	7511438	908			105	105				41	696-1	719-4		FIRST FILE # 908				
709		909								37	697-1	720-4						
710		910								33	698-1	721-4						
711		911								29	699-1	722-4						

29 - 4.8 miles

