



LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-4</u>	AREA: <u>Key Creek</u>	LINE NO.: <u>KD-100</u>						
PARTY NO.: <u>1182</u>		INST. ENG.: <u>BACRAIG - J. Wingham</u>		DATE: <u>MO 3 DAY 18 YR 77</u>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> DDFS II <input checked="" type="checkbox"/> DDFS III	<input type="checkbox"/> DDFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAT: <u>TREC</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: [LO] <input type="checkbox"/> 355 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input checked="" type="checkbox"/> OCT.	GAIN CONSTANT: <u>30</u> db	INPUT IMPEDANCE: <u>500</u> ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:				AUXILIARY DATA:					
PARAMETER	RECORD LENGTH: <u>6</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. <u>8</u>	LO CUT HZ SLOPE <u>36</u>	FREQ. <u>124</u>	HI CUT HZ SLOPE <u>77</u>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>18</u> db	TRIP SENS: <u>24</u> db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Single Hole</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	TYPE: <u>GS-20d</u>	PATTERN: <u>In line</u>	NO. OF ELEMENTS: <u>18</u>	INCLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	CONNECTION: <u>Series-Parallel</u>	RESISTANCE: <u>500</u> ohms	CHG/HOLE: <u>75</u>	HOLE DEPTH: <u>90</u>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.
DIAGRAMS/MISC. INFORMATION:	NO. OF GROUPS: <u>48</u>				GROUP INTERVAL: <u>330'</u>	SHOTPOINT INTERVAL: <u>1320'</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>East to West</u>		



SHOTPOINT	TR. TO		TR. TO		SHOT		DIR.	CDP SWITCH	LINE GROUPS	REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH					NO.	OFFSET	TR 1-1	TR 1-2	TR 1-3
1	5435	17	2223	20	75	90	1	✓	F1 - SP-7	1	Trace #28 Dead				
2					75	90	2	✓	T4 - SP-8						
3					75	90	3	✓	T8 - SP-9						
4					75	90	4	✓	T12 - SP-10						
5					75	90	5	✓	T16 - SP-11						
6					75	90	6	✓	T20 - SP-12						
7					75	90	7	✓	SP-1 - SP-13		Trace #48 Dead				

LAND SEISMIC RECORDING LOG





CLIENT: **Husky** PROSPECT: **NPR-4** AREA: **Key Creek** LINE NO: **KD-100**
 PARTY NO: **1182** INST. ENG: **B. Leish - J. Windham** DATE: **MO 3 DAY 21 YR 77**
07.00 - 21.00 14 Hours

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS III	<input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input type="checkbox"/> 8 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAT: TRAC	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 500 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: (1) (2) (3) (4) (5) (6) (7)	INPUT IMPEDANCE: ohms.					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48	DATA CHANNEL NOS.: 1-48	(ON MAG TAPE)			AUXILIARY DATA:	AUXILIARY CHANNEL NOS.:				
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 36	FREQ. 124	HI CUT HZ SLOPE 72	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 db	TRIP SENS: 18 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	R.C.U. NORM/ALT SW.			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:					
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Single Hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
		CHG/ HOLE: 50	HOLE DEPTH: 90	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.		
RECEIVER	TYPE: GSC-20d	PATTERN: TWLine	NO. OF ELEMENTS:	INCLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
	CONNECTION: Series-Parallel	RESISTANCE: 500 ohms									
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 330'	SHOTPOINT INTERVAL: 1320'	FOLD: 6	DIRECTION OF PROGRESSION: East to west						
	OFFSET GROUP 1:	OFFSET GROUP: SP8	OFFSET GROUP:	OFFSET GROUP 48/96:	LEADING GROUP:						

DIAGRAMS/MISC. INFORMATION: **SP2 A xxx P** **Trace #1** **Trace #24** **Hole being shot** **Trace #25** **Trace #48** **SP14**
 Note * **RN-0043 Test TB - RN-0026 through RN-0042 Daily Instrument Tests**

SHOTPOINT	TR. 1 to 48		TR. 49 to 96		SHOT		DIR.	CDP SWITCH	SPREAD	LINE GROUPS	REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH						NO.	OFFSET	TR 1-48	TR 49-96	TR 1-48	TR 49-96
1																	
2																	
3																	
4																	
5																	
6																	
7																	
8																	
9																	
10																	
11																	
12																	
13																	
14																	
15																	
16																	
17																	
18																	
19																	
20																	
21																	
22																	
23																	
24																	
25																	
26																	
27																	

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-4	AREA: Key Creek	LINE NO: KD-100						
	PARTY NO: 1182	INST. ENG: B. Craig - J Windham	0700 - 2100	14 Hours	DATE: MO 3 DAY 21 YR 77					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9-TRACK <input checked="" type="checkbox"/> 2-TRACK	FORMAT: TRAC	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(M1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48				AUXILIARY DATA:				AUXILIARY CHANNEL NOS.:	
	DATA CHANNEL NOS.: 1-48				(ON MAG TAPE)					
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 36	FREQ. 124	HI CUT HZ SLOPE 72	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 db	TRIP SENS: 18 db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY <input type="checkbox"/>	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM / ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Single Hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CHG/ HOLE: 50	HOLE DEPTH: 90	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:		
RECEIVER	TYPE: RSC-20d	PATTERN: In line	NO. OF ELEMENTS: 18	INCLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION: Series-Parallel	RESISTANCE: 500 ohms								
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 330'	SHOTPOINT INTERVAL: 1320'	FOLD: 6	DIRECTION OF PROGRESSION: EAST TO WEST	OFFSET GROUP 1:	LEADING GROUP:			

DIAGRAMS/MISC. INFORMATION :

SHOTPOINT	TR. 1 to 18		TR. 19 to 36		TR. 37 to 54		SHOT		SPREAD		REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-18	TR 19-36
28	5435B5	0071					50	90	21			V37	SP22-SP34	2		
29		0072					50	90	22			V41	SP23-SP35			
30		0073					50	90	23			V45	SP24-SP36			
31		0074					50	90	24			V5	SP25-SP37	3		RN-0074 - mistfire
32		0076					50	90	25			V9	SP26-SP38			
33		0077					50	90	26			V13	SP27-SP39			
34		0100					50	90	27			V17	SP28-SP40			
35		0101					50	90	28	300	EAST	V21	SP29-SP41			
36		0102					50	90	29			V25	SP30-SP42			WAITING ON Drill 1.5 Hours
37		0103					50	90	30			V29	SP31-SP43			
38		0104				#50	50	170	31			V17	SP32-SP44	4		LOST 25# IN BAD HOLE
39		0105					50	90	32			V21	SP33-SP45			
40		0106					50	90	33			V25	SP34-SP46			
41		0107					50	90	34			V29	SP35-SP47			
42	5435B6	0110					50	90	35			V33	SP36-T-8			
43		0111					50	90	36			V37	SP37-T-12			
44		0112					50	90	37			V41	SP38-T-16			
45		0113					50	90	38			V45	SP39-T-20			
46		0114					50	90	39			V49	SP40-T-24			