



LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: REB-4457 CRAIG NRP-4	AREA: KEY CREEK	LINE NO.: KC-104					
	PARTY NO.: 1182	INST. ENG.: B. CRAIG	7:00 AM - 8:00 PM	13.0 hr	DATE: MO: Nov DAY: 10 YR: 77				
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input checked="" type="checkbox"/> 356 BPI 800 BPI	(M1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
CONFIGURATION (MAG TAPE)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT:	(1) (2) (3) (4) (5) (6) (7)	INPUT IMPEDANCE: ohms	
PARAMETER	FIELD TRACE NOS.: 1-48	DATA CHANNEL NOS.: 1-48	(ON MAG TAPE)	AUXILIARY DATA:	AUXILIARY CHANNEL NOS.:				
DISPLAY	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 5 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ: 8	LO CUT HZ SLOPE: 36	FREQ: 124	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
CFS I	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: db	TRIP SENS: db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE POSITIVE	NUMBERS ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	R.C.U. NORM/ALT SW.	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	CONNECTION:	PATTERN:	RESISTANCE: ohms	NO. OF ELEMENTS:	STAGGER:	INCLINE SPACING:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	OFFSET GROUP 1:	OFFSET GROUP 48/96:	LEADING GROUP:	

DIAGRAMS/MISC. INFORMATION:



SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT			SPREAD		REMARKS:	CORR. STAGE		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TR 1-48
1	5413-5810	23			50	90	1			1/5	to 7		
2		23					2			1/9	to 8		
3		24					3			1/5	to 9		
4		27					4			1/9	to 10		
5		30					5			1/3	to 11		
6		31					6			1/7	to 12		
7		32					7			1/21	1 to 13		
8		33					8			1/25	2 to 14		
9		34					9			1/27	3 to 15		
10		35					10			1/33	4 to 16		
11		38					11			1/27	5 to 17		
12		40					12			1/41	6 to 18		
13		41					13			1/45	7 to 19		
14		42					14	30 N		1/49	8 to 20		
15		43					15			1/1	9 to 21		
16		44					16			1/5	10 to 22		
17		45					17			1/9	11 to 23		
18		46					18			1/13	12 to 24		
19		47					19			1/17	13 to 25		
20		510					20			1/21	14 to 26		

LAND SEISMIC RECORDING LOG

CLIENT: HUSKY		PROSPECT: NPR-4			AREA: KEY CREEK			LINE NO.: KC-104													
PARTY NO.: 1182		INST. ENG.: BCRAIG					DATE: MO Mar DAY 10 YR 92														
INSTRUMENT (9-TRACK)		<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER <input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK FORMAT: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED <input type="checkbox"/> PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI 1600 BPI		RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT. GAIN CONSTANT: _____ db INPUT IMPEDANCE: _____ ohms.															
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.:			NO. BYTES IN HEADER REC.:			NO. BYTES IN RECORD ID:			NO. BYTES PER SCAN:			(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____							
PARAMETER		RECORD LENGTH: _____ sec.			SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> LO CUT <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE <input type="checkbox"/> HZ SLOPE		FREQ. _____		H1 CUT <input type="checkbox"/> IN <input type="checkbox"/> HZ SLOPE <input type="checkbox"/> NOTCH FILTER: <input type="checkbox"/> OUT										
DISPLAY		MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT			INITIAL GAIN: _____ db		TRIP SENS: _____ db		POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON ON MAG. TAPE <input type="checkbox"/> DOWNBREAK } ON DISPLAY UPBREAK <input type="checkbox"/> UPBREAK }								
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM/ALT SW.							
SOURCE		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER			PATTERN:			NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:	
RECEIVER		CONNECTION:			RESISTANCE: _____ ohms			SWEEP POSITION:		SWEEP START:		SWEEP END:		SWEEP LENGTH:		SWEEP TAPER:		PHASE COMP:			
SPREAD		NO. OF GROUPS:			GROUP INTERVAL:			SHOTPOINT INTERVAL:		FOLD:		DIRECTION OF PROGRESSION:		LEADING GROUP:							

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD		REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR. 1-48	TR. 49-96	TR. 1-48	TR. 49-96
21	543580	F1			150	900	1			1/25	15 to 29					
22		F2								1/29	16 to 28					

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: NPR-4	AREA: KEY CREEK	LINE NO: KD-104	
	PARTY NO: 1182	INST. ENG: Bruce Crac - Jerry Winham	DATE: MO: Mar DAY: 11 YR: 77		
			TIME: 13.5 HRS		
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS	<input type="checkbox"/> 9 TRACK	FORMAT SEG: TAC
	<input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> EVENS	<input type="checkbox"/> 21 TRACK	<input type="checkbox"/> GAPPED
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input checked="" type="checkbox"/> OCT.
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48			AUXILIARY DATA:	
	DATA CHANNEL NOS.:			AUXILIARY CHANNEL NOS.:	
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> IFF	FILTERS: FREQ: 8	LO CUT HZ SLOPE: 36
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE	HIGH CUT HZ SLOPE: _____
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:
	<input type="checkbox"/> VIBROSEIS	CHG/ HOLE: 50	NOLE DEPTH: 90	SWEEP POSITION:	SWEEP END:
RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INCLINE SPACING:	LATERAL SPACING:
	CONNECTION:	RESISTANCE:	STAGGER:	LENGTH:	WIDTH:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:
	OFFSET GROUP 1:	OFFSET GROUP:	OFFSET GROUP:	OFFSET GROUP 48/96:	LEADING GROUP:

DIAGRAMS/MISC. INFORMATION:

GROUP 4
SP 17 XXXY SP 18
GROUP 24
XXX
GROUP 25
XXXX
GROUP 44
XXXX SP 29

SP 17 XXXY SP 18 → XXX → XXXX → XXXX SP 29

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT		SPREAD		REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	Y1-2	Y1-3	Y1-4
23	5H3580	76			50	90	1		11	17 to 29	1				
24		77							15	18 to 30					
26		104							17	19 to 31					
26		106							13	20 to 32					
27		107							17	21 to 33					
28		110							29	22 to 34					
29		111							25	23 to 35					
30		112						165	29	24 to 36					
31		113							33	25 to 37					
32		114							25	26 to 38	2				
33	5H3581	1							29	27 to 39					
34		2							33	28 to 40					
36		3							37	29 to 41					
36		4							41	30 to 42					
37		5							45	31 to 43					
38		6							49	32 to 44					
38		7							45	33 to 45	3				
40		10							49	34 to 46					

TAPE CHANGE

E.O.L.