


LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: NPR-4	AREA: KEY CREEK Key Creek	LINE NO: KC-106					
	PARTY NO: 1182	INST. ENG: Bruce Craig - Jerry Washam	13 HRS						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	TYPE: <input checked="" type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAT: TIAC	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input checked="" type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
CONFIGURATION (MAG TAPE)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 30 db	INPUT IMPEDANCE: 500 ohms		
PARAMETER	FIELD TRACE NOS. 1-48	DATA CHANNEL NOS. 1-48 (ON MAG TAPE)		AUXILIARY DATA:					
DISPLAY	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 5 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 36	FREQ. 124	HI CUT HZ SLOPE 72	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
CFS I	MODE: <input checked="" type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS: 74 db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	<input type="checkbox"/> NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: IN line	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: G.S.-20d	PATTERN: IN line	NO. OF ELEMENTS: 18	INCLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: Series-Parallel	RESISTANCE: 500 ohms	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
	NO. OF GROUPS: 48	GROUP INTERVAL: 330'	SHOTPOINT INTERVAL: 1320'	FOLD: 6	DIRECTION OF PROGRESSION: South-North	LEADING GROUP:			

DIAGRAMS/MISC. INFORMATION:





SHOTPOINT	TR. 1 to 48		TR. 49 to 96		SHOT		SPREAD		REMARKS	CORR. STAGE					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	T1-48	T1-96	T1-96
1	514315182	20			17.5	110.5	11			V1	T1 - SP-7	1			
2		21					2			V5	T5 - SP-8				
3		22					3			V9	T9 - SP-9				
4		23					4			V13	T13 - SP-10				
5		24					5			V17	T17 - SP-11				
6		26					6			V21	T21 - SP-12				
7		26					7			V25	SP-1 - SP-13				
8		27					8			V29	SP-2 - SP-14				
9		31					9			V33	SP-3 - SP-15				
10		32					10			V1	SP-4 - SP-16	2			
11		33					11			V5	SP-5 - SP-17				
12		34					12			V9	SP-6 - SP-18				
13		35					13			V13	SP-7 - SP-19				
14		36					14			V17	SP-8 - SP-20				
15		37					15			V21	SP-9 - SP-21				
16		40					16			V25	SP-10 - SP-22				
17		41					17			V29	SP-11 - SP-23				
18		42					18			V33	SP-12 - SP-24				
19		43					19			V37	SP-13 - SP-25				
20		44					20			V1	SP-14 - SP-26	3			

B.A.P. WRWNG POSITION 1-12-13-24 37-48-

LAND SEISMIC RECORDING LOG

07⁰⁰ - 22³⁰ 15.5 Hours

	CLIENT: HUSKY	PROSPECT: NPR-4	AREA: KEY CREEK	LINE NO.: KC-106					
	PARTY NO.: 1182	INST. ENG.: B-CRAIG / J. WINDHAM.	DATE: 07⁰⁰ - 22³⁰ 15.5 Hours		DATE: MON DAY B. 22				
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input checked="" type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAT: TAC	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input checked="" type="checkbox"/> 384 BPI (11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 1400 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input checked="" type="checkbox"/> OCT.	GAIN CONSTANT: 30	INPUT IMPEDANCE: 500 ohms		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 36	FREQ. 124 HI CUT HZ SLOPE	<input type="checkbox"/> NOTCH FILTER: <input checked="" type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT	<input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> DIRECT	INITIAL GAIN: 18	TRIP SENS: 24	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	<input type="checkbox"/> NUMBERS ON MAG. TAPE <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	<input type="checkbox"/> ON DISPLAY		
CFS I	TYPE:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORB. SCALING:	E.C.U. NORM / ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE:	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INCLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	LEADING GROUP:			

DIAGRAMS/MISC. INFORMATION:

GROUP 1 P
 SP22 XXXX
 GROUP 24
 XXXX
 GROUP 25 P
 SP28 XXXX
 GROUP 48 P
 XXXX SP34

SHOTPOINT	TR. 1 to		TR. 2 to		SHOT				SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	T1
28	543582	24			75	105	1			1/1	SP 22 - SP 34	1	
29		25					2		30° E	1/9	SP 23 - SP 35		
30		26					3		25° W	1/13	SP 24 - SP 36		
31		70					4			1/17	SP 25 - SP 37		
32		100					5			1/21	SP 26 - SP 38		
33		101					6			1/25	SP 27 - SP 39		
34		102					7			1/29	SP 28 - SP 40		
35		103					8			1/33	SP 29 - SP 41		
36		104					9			1/37	SP 30 - SP 42		
37		105					10			1/41	SP 31 - T17		
38		106					11			1/45	SP 32 - T16	2	
39		107					12	25 S		1/49	SP 33 - T20		
40		110					13			1/49	SP 34 - T24		

RN 55 to 73 DAILY TESTS.
 RN 74 1 SEC RECORD NO GOOD
 TRACES 43 to 48 DEAD
 TRACE - 46 DEAD
 TRACE - 42 DEAD