

LAND SEISMIC RECORDING LOG



	CLIENT: Husky	PROSPECT: ALASKA NPR-4 KUCR CUTLER	AREA: ALASKA KUR RIVER	LINE NO: KD-1					
	PARTY NO: 1182	INST. ENG: HYDE		DATE: 1 22 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAL SEG: TIAC	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input checked="" type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input checked="" type="checkbox"/> OCT.	GAIN CONSTANT: 30 db	INPUT IMPEDANCE: 500 ohms	(1) (2) (3) (4) (5) (6) (7)		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
	DATA CHANNEL NOS.: 1-48			[ON MAG TAPE]					
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> IFP	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 124	LO CUT HZ SLOPE F/36	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	RECORD REJECTION:	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM / ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
RECEIVER	TYPE: _____	PATTERN: Inline	NO. OF ELEMENTS: 18	INCLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	INCLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 330'	SHOTPOINT INTERVAL: 1320'	FOLD: _____	DIRECTION OF PROGRESSION: _____	OFFSET GROUP 48: _____	LEADING GROUP: 48		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 48		TR. _____ to _____		SHOT					SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR-48	TR-48
40	543569	039			60	90				1/25				
41		036				90				1/29				
46A		036				90				1/33				
46B		037				75				1/33				
45		040				90				1/37				
44		041				105				1/41				
43		042				75				1/45				
42		043				90				1/49				
41		044				90				1/1				
40		045				90				1/5				
39		046				90				1/9				
38		047				90				1/13				
37		050				90				1/17				
36		051				85				1/21				
35		052				90				1/25				
34		053				90				1/29				
33		054				160				1/33				
32		055				90				1/37				
31		056				90				1/41				
30		057				90				1/45				

OFF SET 200' SW
SHOOTER AT WRANG HOOD - SHOT 5429
CDP SWITCH SET FOR SA 21 NO uphole
NO U.P. HOLE

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u> PARTY NO: <u>102</u>	PROSPECT: <u>Kuk RIVER</u>	AREA: <u>PET. 4</u>	LINE NO: _____				
INST. ENG: <u>J. Blalock</u>	DATE: MO <u>1</u> DAY <u>23</u> YR <u>77</u>							
INSTRUMENT <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS (9-TRACK)	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> DFS X <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG _____ <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: _____ (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
NO. BYTES IN HEADER REC: _____ NO. BYTES IN RECORD ID: _____ NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____ <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db (1) (2) (3) (4) (5) (6) (7)	INPUT IMPEDANCE: _____ ohms					
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ [ON MAG TAPE]	AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____							
PARAMETER RECORD LENGTH: _____ sec. SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____ LO CUT HZ _____ HI CUT HZ _____ FREQ. _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT					
DISPLAY MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT <input type="checkbox"/> AMPLIFIER	INITIAL GAIN: _____ db TRIP SENS: _____ db	POLARITY CONVENTION: _____ PRESSURE INCREASE ON GEOPHONE: _____ <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____ <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY				
CFS I TYPE STACK: _____ GATE LENGTH: _____	RECORD REJECTION: _____ NOISE REDUCTION: _____ NOISE THRESHOLD: _____	CORR. SCALING: _____ R.C.U. NORM/ALT SW. _____						
SOURCE <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER _____	PATTERN: _____ CHG/HOLE: _____ HOLE DEPTH: _____	NO. OF POSITIONS: _____ SWEEP POSITION: _____	INLINE SPACING: _____ SWEEP START: _____	LATERAL SPACING: _____ SWEEP END: _____	STAGGER: _____ SWEEP LENGTH: _____	LENGTH: _____ SWEEP TAPER: _____	WIDTH: _____ PHASE COMP. _____	LATERAL OFFSET: _____
RECEIVER TYPE: _____ CONNECTION: _____	PATTERN: _____ RESISTANCE: _____ ohms	NO. OF ELEMENTS: _____ STAGGER: _____	INCLINE SPACING: _____ LENGTH: _____	LATERAL SPACING: _____ WIDTH: _____	LATERAL OFFSET: _____			
SPREAD NO. OF GROUPS: _____ OFFSET GROUP 1: _____	GROUP INTERVAL: _____ OFFSET GROUP: _____	SHOTPOINT INTERVAL: _____ OFFSET GROUP: _____	FOLD: _____ OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: _____ LEADING GROUP: _____				

DIAGRAMS/MISC. INFORMATION :

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT								SPREAD		REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SLY	TR. 48		TR. 96	TR. 48	TR. 96	
1	7	12-15	17	22-23	26	27	29	30	32	35	37								

WEATHER DAY

LAND SEISMIC RECORDING LOG

	CLIENT: <i>Husky</i>	PROSPECT: <i>Kuk River</i>	AREA: <i>PRT 4</i>	LINE NO.:						
	PARTY NO.: <i>1182</i>	INST. ENG.: <i>C. J. RALLOCK</i>	DATE: <i>MO 1 DAY 24 YR 92</i>							
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> DFS X <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:	(ON MAG TAPE)				AUXILIARY DATA:				
	DATA CHANNEL NOS.:					AUXILIARY CHANNEL NOS.:				
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: _____	LO CUT HZ SLOPE _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/>	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/>	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH: _____	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CHG/ HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:		
RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INCLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION:	RESISTANCE:	ohms	STAGGER:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	OFFSET GROUP 48/96:	LEADING GROUP:			
	OFFSET GROUP 1:	OFFSET GROUP:	OFFSET GROUP:							

DIAGRAMS/MISC. INFORMATION :

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT							SPREAD		REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SET UP	TR. 48-96		REC.			
1	7	12	13	16	17	22	23	26	27	29	30	32	33	37				
<i>WEATHER DAY</i>																		

LAND SEISMIC RECORDING LOG



CLIENT: Husky	PROSPECT: ALASKA NPR-1	AREA: KUK RIVER	LINE NO: 1
PARTY NO: 1192	INST. ENG: Hyde		DATE: MO 1 DAY 22 YR 99

INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: _____	(LO) <input type="checkbox"/> 356 BPM (HI) <input type="checkbox"/> 712 BPM <input type="checkbox"/> 800 BPM <input type="checkbox"/> 1600 BPM
NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)	AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____								
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AOC <input type="checkbox"/> DEFOCAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	<input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW: _____			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
	CHG/HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____		
RECEIVER	CONNECTION: _____	PATTERN: _____	RESISTANCE: _____ ohms	NO. OF ELEMENTS: _____	STAGGER: _____	INCLINE SPACING: _____	LENGTH: _____	LATERAL SPACING: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____					
	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____					

DIAGRAMS/MISC. INFORMATION :

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT						SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP		TR 1-48	TR 48-96		
	HT.	REC.	HT.	REC.	HT.	REC.	HT.	REC.	HT.	REC.	HT.	REC.	HT.		REC.			
31	54	35	17	22	1610	1980				1/41								

LAND SEISMIC RECORDING LOG

	CLIENT: HASKY	PROSPECT: KUK RIVER	AREA: YET. 4.	LINE NO.:	
PARTY NO.: 1182		INST. ENG.: C. J. BLALOCK		DATE: MOL 26 DAY 26 YR 77	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG.	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(10) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
NO. BYTES IN HEADER REC.:		NO. BYTES IN RECORD ID.:		NO. BYTES PER SCAN:		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: _____ db		INPUT IMPEDANCE: _____ ohms		
CONFIGURATION [MAG TAPE]	FIELD TRACE NOS.:				AUXILIARY DATA:				AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	FREQ. _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: _____		<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH: _____	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD: _____	CORR. SCALING:		R.C.U. NORM/ALT SW.				
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:		NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
		CHG/ HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:			
RECEIVER	TYPE:	PATTERN:		NO. OF ELEMENTS:	INLINE SPACING:		LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION:	RESISTANCE: _____ ohms										
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:		SHOTPOINT INTERVAL:		FOLD:		DIRECTION OF PROGRESSION:		LEADING GROUP:		
	OFFSET GROUP 1:	OFFSET GROUP _____		OFFSET GROUP _____		OFFSET GROUP 48/96:						


DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT								SPREAD			REMARKS:	CORR. STACK											
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR. 1-48	TR. 48-96		TR. 1-48	TR. 48-96										
1	7	1213	16	17	22	23	26	27	29	30	32	33	37															

WEATHER DAY



LAND SEISMIC RECORDING LOG


	CLIENT: HUSKY OIL	PROSPECT: HOR#4 NPR#4	AREA: KUK RIVER	CINE NO: KD-1					
	PARTY NO: 1182	INST. ENG: Welcome & Blalock		DATE: MO 1 DAY 27 YR 77					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS III <input type="checkbox"/> DFS X <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAT: TAC SEG: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC. <input checked="" type="checkbox"/> OCT.	GAIN CONSTANT: 30 db	INPUT IMPEDANCE: 500 ohms		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48	DATA CHANNEL NOS.: 1-48	(ON MAG TAPE)	AUXILIARY DATA: FTB U/H 1TB FTB PIPER RN	AUXILIARY CHANNEL NOS.: 4 5 8 4950 4951 52				
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec. <input checked="" type="checkbox"/> 2 sec. <input type="checkbox"/> 8 sec.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> JEP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT 36 HI CUT _____	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT				
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: 0 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Single Hole	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/HOLE: 60	NOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____						
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 330 FT.	SHOTPOINT INTERVAL: 1320	FOLD: 6	DIRECTION OF PROGRESSION: NE	OFFSET GROUP 1: _____	OFFSET GROUP 48/96: _____	LEADING GROUP: 48	



SHOTPOINT	TR. 1 to 48		TR. 10		Bottom SHOT		SPREAD		REMARKS	CORE STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-48
208	519.35	2100			60	1601	1605	NE	1/1	# 45 dead	1		
217		2101			60	1602			1/5	# 41 dead			
226		2103			60	1603			1/9				
235		2104			60	1604			1/13				
244		2106			60	1606			1/17				
253		2107			60	1607			1/5		2		
262		2110			60	1607			1/9				
271		2111			60	1608			1/13				
280		2112			60	1609			1/17				
289		2113			60	1610			1/21				
298		2114			60	1611			1/25				

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY OIL	PROSPECT: NPR # 4	AREA: KUK RIVER	LINE NO: K001							
PARTY NO: 1182		INST. ENG: WELCOME & BLALOCK		DATE: NOV 28 1977							
1970 SHOOT 1620-2300 DRIVE TO LINE 093D											
0700-0930 DRIVE TO LINE 093D											
NO. 01 DAY 28 TR 77											
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM	<input checked="" type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III	<input type="checkbox"/> DFS II	<input type="checkbox"/> 9 TRACK	FORMAT: -SEG- TIAC	<input type="checkbox"/> GAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI	(11) <input type="checkbox"/> 712 BPI	
	<input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-40 & 49-96		<input checked="" type="checkbox"/> DFS IX	<input type="checkbox"/> OTHER	<input type="checkbox"/> 21 TRACK		<input type="checkbox"/> UNGAPPED	(12) <input type="checkbox"/> 800 BPI	(13) <input type="checkbox"/> 1600 BPI	
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS:	<input type="checkbox"/> DEC.	<input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48		AUXILIARY DATA: FTB UH TWO TR-PB UH-PB PIPPER RN		AUXILIARY CHANNEL NOS.: 4 5 8 50 49 51 52		FILTERS: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		LO CUT HZ SLOPE: 36 HI CUT HZ SLOPE: _____		
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> PULSE <input checked="" type="checkbox"/> OPERATE	TRIP SENS: 0 db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		CORR. SCALING: _____		R.C.U. NORM/ALT SW. <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	<input type="checkbox"/> FLAGG <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER DIRECT	INITIAL GAIN: 0 db	RECORD REJECTION: _____		NOISE REDUCTION: _____		NOISE THRESHOLD: _____		DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	PATTERN: SINGLE HOLE		NO. OF POSITIONS: _____		INLINE SPACING: _____		LATERAL SPACING: _____		
SOURCE	<input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	CHG/ HOLE: 50	HOLE DEPTH: 75	SWEEP POSITION: _____		SWEEP START: _____		SWEEP END: _____		SWEEP LENGTH: _____	
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____		INCLINE SPACING: _____		LATERAL SPACING: _____		LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 330	SHOTPOINT INTERVAL: 1320		FOLD: 6		DIRECTION OF PROGRESSION: NE		LEADING GROUP: 48		
OFFSET GROUP 1: _____		OFFSET GROUP _____: 24 x 25: 165		OFFSET GROUP _____: 50		OFFSET GROUP 48/96: _____		PHASE COMP. _____		PHASE COMP. _____	



SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT							SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS	TR. _____	TR. _____			
0117	51438	002117			0.60	90	21	165	NE	1/1				TRACE #37 BAD ON ALL PAPER RECORDS BUT GOOD ON TAPE		
0116		002116			0.60	90	22			1/5				UHT TMS		
0115		002115			0.60	90	23			1/9				PAPER JAM - P/B MADE		
0114		002114			0.60	90	24			1/13				UHT TMS		
0113		002113			0.60	90	25			1/17				UHT TMS		
0112		002112			0.50	90	26			1/31				PAPER JAM - P/B MADE		
0111		002111			0.60	90	27			1/35				UHT TMS		
0110		002110			0.50	90	28			1/39				UHT TMS		
0097		002097			0.60	90	29			1/43				UHT TMS		
018		002018			0.50	90	30			1/37				PAPER JAM - P/B MADE		
017		002017			0.60	90	31			1/41				UHT TMS		
016		002016			0.50	90	32			1/45				UHT TMS		
015		002015			0.60	90	33			1/49				UHT TMS		
014		002014			0.50	90	34			1/53				UHT TMS		
013		002013			0.60	90	35			1/57				UHT TMS		
012		002012			0.50	90	36			1/61				UHT TMS		
011		002011			0.60	90	37			1/65				UHT TMS		
010		002010			0.50	90	38			1/69				UHT TMS		
009		002009			0.60	90	39			1/73				UHT TMS		
008		002008			0.50	90	40			1/77				UHT TMS		
007		002007			0.60	90	41			1/81				UHT TMS		
006		002006			0.50	90	42			1/85				UHT TMS		
005		002005			0.60	90	43			1/89				UHT TMS		
004		002004			0.50	90	44			1/93				UHT TMS		
003		002003			0.60	90	45			1/97				UHT TMS		
002		002002			0.50	90	46			1/101				UHT TMS		
001		002001			0.60	90	47			1/105				UHT TMS		