




# LAND SEISMIC RECORDING LOG

	CLIENT: <b>HUSKY</b>	PROSPECT: <b>NPR 4</b>	AREA: <b>RUK RIVER</b>	LINE NO: <b>06</b>	
PARTY NO: <b>1182</b>		INST. ENG: <b>W. WELCOME</b>		DATE: <b>MO 02 DAY 12 YR 77</b>	
0700-0900 DRIVE TO LINE; DRILLS, CABLES & JOBS <del>VEHICAL PROBLEMS, ETC; 16.30-19.00 SHOOTING; 200 CAMP</del>					
INSTRUMENT (9-TRACK)		TYPE: <input checked="" type="checkbox"/> DFS III <input type="checkbox"/> DFS X <input type="checkbox"/> OTHER		RECORD NUMBERS: <input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	
NO. BYTES IN HEADER REC.		NO. BYTES IN RECORD ID		NO. BYTES PER SCAN	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: <b>1-48</b>		AUXILIARY DATA: <b>FTB UH T120 PBITA PBITB 1RHZ RN</b>	
PARAMETER		RECORD LENGTH: <b>6</b> sec.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER DIRECT		FILTERS: FREQ. <b>8</b> LO CUT HZ SLOPE <b>36</b> FREQ. <b>124</b> HI CUT HZ SLOPE	
CFS I		TYPE STACK		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VISROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>SINGLE HOLE</b>	
RECEIVER		CONNECTION: <b>S/P</b>		PATTERN: <b>IN LINE</b>	
SPREAD		NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>330'</b>	
DIAGRAMS/MISC. INFORMATION		CHG/ HOLE: <b>50</b>		HOLE DEPTH: <b>75'</b>	




SHOTPOINT	TR. #1 to 48		TR. to		SHOT		SPREAD		REMARKS: RECORD NOS. 0001-0020 USED FOR TESTS.	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-48
01	51435658	0022			250	275	01			1			
02		0022					02			1/2			
03		0023					03			1/3			
04		0024					04			1/4			
05		0025					05			1/5			
06		0026					06			1/6			
07		0027					07			1/7			
08		0030					08			1/8			
09		0031					09			1/9			
10		0032					10			1/10			
11		0033					11			1/11			
12		0034					12			1/12			
13		0035					13			1/13			
										1/14			
										1/15			
										1/16			
										1/17			
										1/18			
										1/19			
										1/20			
										1/21			
										1/22			
										1/23			
										1/24			
										1/25			
										1/26			
										1/27			
										1/28			
										1/29			
										1/30			
										1/31			
										1/32			
										1/33			
										1/34			
										1/35			
										1/36			
										1/37			
										1/38			
										1/39			
										1/40			
										1/41			
										1/42			
										1/43			
										1/44			
										1/45			
										1/46			
										1/47			
										1/48			

# LAND SEISMIC RECORDING LOG



CLIENT: <b>HUSKY OIL</b>		PROSPECT: <b>NPR 4</b>		AREA: <b>KUK RIVER</b>		LINE NO.: <b>06</b>	
PARTY NO.: <b>1182</b>		INST. ENG.: <b>W. WELCOME</b>		1000-0900 DRIVE TO LINE; CABLES & JUGS		DATE: <b>MO 02 DAY 13 YR 77</b>	
NO. SYSTEMS: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		DOGS: <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		FORMAT: <b>TIAC</b> <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	
NO. BYTES IN HEADER REC.		NO. BYTES IN RECORD ID:		RECORD NUMBERS: <input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK		PACKING DENSITY: (LO) <input checked="" type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
FIELD TRACE NOS.: <b>1-48</b>		DATA CHANNEL NOS.: <b>1-48</b> (ON MAG TAPE)		AUXILIARY DATA: <b>FTB 2H 30 T10 TB PIPPER RN</b>		AUXILIARY CHANNEL NOS.: <b>4 6 8 50 51 52</b>	
RECORD LENGTH: <b>6</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE		FILTERS: FREQ. <b>8</b> LO CUT HZ SLOPE <b>36</b> HI CUT HZ SLOPE <b>124</b>	
MODE: <input checked="" type="checkbox"/> MAG <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>6</b> db		TRIP SENS: <b>6</b> db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	
TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE THRESHOLD:	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>SINGLE HOLE</b>		NO. OF POSITIONS:		INLINE SPACING:	
CHG/ MOLE: <b>50</b>		HOLE DEPTH: <b>75</b>		SWEEP POSITION:		SWEEP START:	
RECEIVER TYPE:		PATTERN: <b>IN LINE</b>		NO. OF ELEMENTS:		LATERAL SPACING:	
CONNECTION:		RESISTANCE:		STAGGER:		LENGTH:	
SPREAD NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>330</b>		SHOTPOINT INTERVAL: <b>1320</b>		FOLD: <b>6</b>	
OFFSET GROUP 1:		OFFSET GROUP:		OFFSET GROUP:		DIRECTION OF PROGRESSION: <b>S</b>	






SHOTPOINT	TR. 1		TR. 2		SHOT			SPREAD			REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	HT.	HT.
14	00618	00617			050	275	01			1/1	1			
15	00620						02			1/5				
16	00611						03			1/9				
17	00622						04			1/13				
18	00613						05			1/17				
19	00614						06			1/21				
20	00615						07			1/25				
21	00616						08			1/29				
22	00617						09			1/33				
23	00170						10			1/37				
24	00271						11			1/41				
25	00172						12			1/45				
26	00173						13			1/49				





# LAND SEISMIC RECORDING LOG

	CLIENT: <b>HUSKY OIL</b>	PROSPECT: <b>NPR 4</b>	AREA: <b>KUK RIVER</b>	LINE NO.: <b>06</b>	
PARTY NO.: <b>1182</b>		INST. ENG.: <b>W. WELCOME</b>		DATE: <b>MO. 02 DAY 25 YR 77</b>	
NO. BYTES IN HEADER REC.: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: _____	
INSTRUMENT (9-TRACK) <input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER _____		9 TRACK <input checked="" type="checkbox"/> 21 TRACK	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: <b>1-48</b> DATA CHANNEL NOS.: <b>1-48</b> (ON MAG TAPE)		AUXILIARY DATA: <b>FTB UH T120 TB 1KHZ RN</b>		AUXILIARY CHANNEL NOS.: <b>4 6 8 30 51 52</b>	
PARAMETER RECORD LENGTH: <b>6</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input checked="" type="checkbox"/> IFFP	
DISPLAY MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>0</b> db		TRIP SENS: <b>6</b> db	
CFS I TYPE STACK: _____		DATE LENGTH: _____		RECORD REJECTION: _____	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER _____		PATTERN: <b>SINGLE HOLE</b>		NO. OF POSITIONS: _____	
RECEIVER TYPE: _____		PATTERN: <b>IN LINE</b>		NO. OF ELEMENTS: _____	
SPREAD NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>330</b>		SHOTPOINT INTERVAL: <b>1320</b>	
DIAGRAMS/MISC. INFORMATION: <b>N</b>		CHG/ HOLE: <b>50'</b>		HOLE DEPTH: <b>75'</b>	
RESISTANCE: _____ ohms		SWEEP POSITION: _____		SWEEP START: _____	
CONNECTION: _____		RESISTANCE: _____ ohms		STAGGER: _____	
OFFSET GROUP 1: _____		OFFSET GROUP 24: <b>165'</b>		OFFSET GROUP 25: <b>165'</b>	
NOISE REDUCTION: _____		NOISE THRESHOLD: _____		CORR. SCALING: _____	
POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: _____		NEGATIVE } NUMBERS ON MAG. TAPE POSITIVE } ON DISPLAY	
FILTERS: _____		LO CUT HZ SLOPE: <b>36</b>		HI CUT HZ SLOPE: _____	
FREQ: <b>8</b>		FREQ: <b>124</b>		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
CORR. SCALING: _____		R.C.U. NORM/ALT SW: _____		DOWNBREAK } ON DISPLAY UPBREAK }	



SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT		SPREAD		CDP SWITCH	LINE GROUPS	REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET				TR. 1-24	TR. 25-48
217	0143	0134	17	2223	20	29	30	32	35	37	UHT 15MS		
218	0135	0135							1/25	1-48	UHT 14MS		
219	0136	0136							1/29		UHT 20MS		
220	0137	0137							1/33		UHT 17MS		
221	0140	0140							1/37		UHT 14MS		
222	0141	0141							1/41		UHT 13MS		
223	0142	0142							1/45		UHT 14MS		
224									1/49				

REMARKS: FILE NOS. 0074-0133 USED FOR TESTS

TRACES 24-25 NOISY - SHOOTER EOL