


# LAND SEISMIC RECORDING LOG

CLIENT: <b>HUSKY</b>	PROSPECT: <b>NPR #4</b>	AREA: <b>KUK RIVER</b>	LINE NO: <b>109</b>
PARTY NO: <b>1182</b>	INST. ENG: <b>W. WELCOME</b>	DATE: <b>MO 03 DAY 01 YR 77</b>	
0700-0800 DRIVE TO LINE; CABLES & JOBS;		2400 IN CAMP	
<b>1000- SHOOTING</b>			
INSTRUMENT: <b>[9-TRACK]</b>	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____
CONFIGURATION (MAG TAPE):	FIELD TRACE NOS.: <b>1-48</b>	AUXILIARY DATA: <b>RAWLSIM RAWREFTB RAWUH SIM REFTB RN 1KHZ</b>	AUXILIARY CHANNEL NOS.: <b>49 50 51 52 53 54 55</b>
PARAMETER:	RECORD LENGTH: <b>6</b> sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> MANUAL
DISPLAY:	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>0</b> db	TRIP SENS: <b>6</b> db
CFS I:	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____
SOURCE:	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE HOLE</b>	NO. OF POSITIONS: _____
RECEIVER:	TYPE: <b>GS 200</b>	PATTERN: <b>IN LINE</b>	NO. OF ELEMENTS: <b>18</b>
SPREAD:	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>330</b>	SHOTPOINT INTERVAL: <b>1320</b>



SHOTPOINT	TR. 1 to 48		TR. to		SHOT		SPREAD		REMARKS	CORE STAGE				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		CDP SWITCH	LINE GROUPS	HT.	REC.	HT.
01	20214	14	20223	23	20227	27	20230	30	1/1	SP1-25 TO SP7-48				
02	20215	15							1/5	1-21 TO 8-48				
03	20216	16							1/9	1-17 TO 9-48				
04	20217	17							1/13	1-13 TO 10-48				
05	20218	18							1/17	1-9 TO 11-48				
06	20219	19							1/21	1-5 TO 12-48				
07	20220	20							1/25	1-1 TO 13-48				
08	20221	21							1/29	2-1 TO 14-48				
09	20222	22							1/33	3-1 TO 10-48				
10	20223	23							1/37	4 TO 16				
11	20224	24							1/41	5 TO 17				
12	20225	25							1/45	6 TO 18				
13	20226	26							1/49	7 TO 19				
14	20227	27							1/1	8-1 TO 20-48				
15	20228	28							1/5	9 TO 21				
16	20229	29							1/9	10 TO 22				
17	20230	30							1/13	11 TO 23				
18	20231	31							1/17	12 TO 24				
19	20232	32							1/21	13 TO 25				
20	20233	33							1/25	14 TO 26				

# LAND SEISMIC RECORDING LOG



CLIENT: <b>HUSKY</b>	PROSPECT: <b>NPR #4</b>	AREA: <b>KUK RIVER</b>	LINE NO: <b>09</b>
PARTY NO: <b>1182</b>	INST. ENG: <b>W. WELCOME</b>	DATE: <b>MO 02 DAY 01 YR 77</b>	

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAT: <b>TAC</b> SEG:	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI					
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input checked="" type="checkbox"/> OCT.	GAIN CONSTANT: <b>30</b> db	INPUT IMPEDANCE: <b>600</b> ohms.							
FIELD TRACE NOS.: <b>1-48</b>	DATA CHANNEL NOS.: <b>1-48</b> (ON MAG TAPE)			AUXILIARY DATA:					AUXILIARY CHANNEL NOS.:				
PARAMETER	RECORD LENGTH: <b>6</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 0.5 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>8</b>	LO CUT HZ SLOPE: <b>36</b>	HI CUT HZ SLOPE: <b>124</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT						
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>0</b> db	TRIP SENS: <b>6</b> db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK			ON DISPLAY				
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:			R.C.U. NORM/ALT SW.				
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE HOLE</b>	NO. OF POSITIONS:	IN-LINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
RECEIVER	TYPE: <b>G.S. 20 D</b>	PATTERN: <b>IN LINE</b>	NO. OF ELEMENTS: <b>18</b>	INCLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
SPREAD	CONNECTION: <b>S/P</b>	RESISTANCE: <b>500</b> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	NO. OF GROUPS: <b>48</b>			GROUP INTERVAL: <b>330</b>	SHOTPOINT INTERVAL: <b>1320</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>S</b>
DIAGRAMS/MISC. INFORMATION:													
N <span style="margin-left: 100px;">*24</span> <span style="margin-left: 100px;">*25</span> <span style="float: right;">#47</span> *6* <span style="margin-left: 300px;">SHOOTING</span> <span style="float: right;">S</span>													

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT			SPREAD			REMARKS:	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 1-48	TR 49-96
21	00435	00440			21	21			1/29	SP15-1 TO 27-48	2		
22	00441				22	22			1/33	16 TO 28			
23	00442				23	23			1/37	17 TO 29			
24	00443				24	24			1/41	18 TO 30			
25	00444				25	25			1/45	19 TO 31			
26	00445				26	26			1/49	20 TO 32			
27	00446				27	27			1/1	21 TO 33-48	3		
28	00447				28	28			1/5	22 TO 34			
29	00448				29	29			1/9	23 TO 35			
30	00449				30	30			1/13	24 TO 36			
31	00450				31	31			1/17	25 TO 37			
32	00451				32	32			1/21	26 TO 38			
33	00452				33	33			1/25	27 TO 39			
34	00453				34	34			1/29	28 TO 40			
35	00454				35	35			1/33	29 TO 41			
36	00455				36	36			1/37	30 TO 42			
37	00456				37	37			1/41	31 TO 43			
38	00457				38	38			1/45	32 TO 44			
39	00458				39	39			1/49	33 TO 45			
40	00459				40	40			1/45	34 TO 46	4		

# LAND SEISMIC RECORDING LOG



CLIENT: **HUSKY** PROSPECT: **NPR 4** AREA: **KUK RIVER** LINE NO: **09**  
 PARTY NO: **1182** INST. ENG: **W. WELCOME** **0700 - 0830 DRIVE TO LINE; CABLES PICKUP** DATE: **MU 03 DAY 02 YR 77**  
**1000-1030 SHOOTING;**

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS <input checked="" type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAT: <b>T1AC</b> <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input checked="" type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
(9-TRACK)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input checked="" type="checkbox"/> OCT.	GAIN CONSTANT: <b>30</b> db	INPUT IMPEDANCE: <b>500</b> ohms
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1 - 48</b>		AUXILIARY DATA: <b>RAWSIN RAWREFTB/RAWLWUH/RIM REFTB RN 1KHZ</b>		AUXILIARY CHANNEL NOS.: <b>49 50 51 52 53 54 55</b>		
PARAMETER	RECORD LENGTH: <b>6</b> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ: <b>8</b> LO CUT HZ SLOPE: <b>36</b> HI CUT HZ SLOPE: <b>124</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>0</b> db	TRIP SENS: <b>6</b> db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE HOLE</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: <b>GS-20D</b>	PATTERN: <b>IN LINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: <b>S/P</b>	RESISTANCE: <b>500</b> ohms	STAGGER:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	DIRECTION OF PROGRESSION: <b>S</b>		
	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>330</b>	SHOTPOINT INTERVAL: <b>1320</b>	FOLD: <b>6</b>	OFFSET GROUP 48/96:				
	OFFSET GROUP 1:	OFFSET GROUP 24: <b>165</b>	OFFSET GROUP 25: <b>165</b>	OFFSET GROUP 48/96: <b>48</b>					

DIAGRAMS/MISC. INFORMATION: **#24** **#25** **#48**  
**N** **PK** **SHOOTING** **S**

SHOTPOINT	TR. 1 to 48		TR. 10		SHOT								SPREAD		REMARKS: <b>RMS 0064 - 0075 USED FOR TESTS</b>	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR. 1-48	TR. 10		TR. 48-96	TR. 96		
441	514315176	00176										1/37	35 TO 41						
442	514315176	00177										1/41	36 TO 48						
443		0106										1/45	37 TO 47						
444		0101										1/49	38 TO 50						