


# LAND SEISMIC RECORDING LOG



	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>North Slope - Alaska</u>	LINE NO: <u>122-X</u>					
	PARTY NO: <u>1182</u>	INST. ENG: <u>Jerry Windham</u>		DATE: <u>MO 5 DAY 24 YR 78</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <u>134</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: _____ ohms	(1) (2) (3) (4) (5) (6) (7)		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: <u>1-48</u>			AUXILIARY DATA:					
	DATA CHANNEL NOS: <u>1-48</u>			AUXILIARY CHANNEL NOS: _____					
PARAMETER	RECORD LENGTH: <u>5</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: FREQ: <u>8</u>	LO CUT HZ SLOPE: <u>18</u>	HI CUT HZ SLOPE: <u>70</u>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>15</u> db	TRIP SENS: <u>0</u> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	DOWNBREAK: <input type="checkbox"/> ON DISPLAY <input type="checkbox"/> UPBREAK		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R. C. U. NORM / ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Inline</u>	NO. OF POSITIONS: <u>1</u>	INLINE SPACING: <u>880</u>	LATERAL SPACING:	STAGGER:	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ HOLE: <u>10</u>	HOLE DEPTH: <u>75</u>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	
RECEIVER	TYPE: <u>ESC-20d</u>	PATTERN: <u>Inline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>18'</u>	LATERAL SPACING:	STAGGER:	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: <u>Series-Parallel</u>	RESISTANCE: _____ ohms	STAGGER:	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>920'</u>	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>E to W</u>	LEADING GROUP: <u>48</u>			
	OFFSET GROUP 1: <u>5610'</u>	OFFSET GROUP 2: <u>550'</u>	OFFSET GROUP 25: <u>550'</u>	OFFSET GROUP 48: <u>5610'</u>					



SHOTPOINT	TR. 1 to 48		TR. _____ to _____		SHOT		SPREAD		REMARKS: <u>File # 1301 -&gt; 1313 DA-14 TESTS</u> <u>File # 1314 Test FB</u>	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TR 1-24	TR 41-24	TR 41-24
1	7511	18512	13115		120	167	1		25	T26 -> 26				
5		13116			120	167	2		29	T22 -> 30				
9		13118			120	167	3		33	T18 -> 34				
13		13119			120	167	4		37	T14 -> 38				
17		1320			120	167	5		41	T10 -> 42				
19		13227					6		42	T9 -> 43				
19		13226					7		43	T8 -> 44				
20		13336					8		44	T7 -> 45				
21		13314					9		45	T6 -> 46				
22		13338					10		46	T5 -> 47				
23		13142					11		47	T4 -> 48				
24		13416					12		48	T3 -> 49				
25		13510					13		49	T2 -> 50				
26		1354					14		50	T1 -> 51				
27		13158					15		51	1 -> 52				
28		13162					16		52	2 -> 53				
28		13616					17		53	3 -> 54				
30		13710					18		54	4 -> 55				
31		1376					19		55	5 -> 56				
32		1380					20		56	6 -> 57				

14-hours Recording Time

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>North Slope - Alaska</u>	LINE NO: <u>122-X</u>			
	PARTY NO: <u>1182</u>	INST. ENG: <u>Jeany Windham</u>		DATE: <u>MO 15 DAY 24 YR 78</u>			
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI
[9-TRACK]	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <u>134</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>56</u> db	INPUT IMPEDANCE: _____ ohms	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>	(ON MAG TAPE)		AUXILIARY DATA:	AUXILIARY CHANNEL NOS.: _____		
PARAMETER	RECORD LENGTH: <u>3</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input checked="" type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	FILTERS: FREQ <u>8</u>	LO CUT HZ SLOPE <u>18</u>	HI CUT HZ SLOPE <u>70</u>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> ACC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>30</u> db	JRP SENS: <u>0</u> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: _____
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW: _____
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input checked="" type="checkbox"/> OTHER <u>AIR Gun</u>	PATTERN: <u>IN line</u>	NO. OF POSITIONS: <u>1</u>	INLINE SPACING: <u>220'</u>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____
RECEIVER	TYPE: <u>RSC-20d</u>	PATTERN: <u>IN line</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>18'</u>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____
SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>220'</u>	FOLD: <u>24</u>	DIRECTION OF PROGRESSION: <u>E to W</u>	LEADING GROUP: <u>48</u>	

DIAGRAMS/MISC. INFORMATION:



SHOTPOINT	TR 1 to 48		TR _____ to _____		SHOT				SPREAD			REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		HT	TR 48-96	REC.	HT	TR 48-96	REC.
33	7511	1384					21			45	7 → 58	2						
34		1388					22			46	8 → 59							
35		1392					23			47	9 → 60							
36		1396					24			48	10 → 61							
37		1400					25			49	11 → 62							
38		1404					26			50	12 → 63							
39		1408					27			51	13 → 64							
40		1412					28			52	14 → 65							
41		1416					29			53	15 → 66							
42		1420					30			54	16 → 67							
43		1424					31			55	17 → 68							
44		1428					32			56	18 → 69							
45		1432					33			57	19 → 70							
46		1436					34			58	20 → 71							
47		1440					35			59	21 → 72							
48		1444					36			60	22 → 73							
49		1448					37			61	23 → 74							
50		1452					38			62	24 → 75							
51		1456					39			63	25 → 76							
52		1460					40			64	26 → 77							







# LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: Barrow Area	LINE NO: 1224								
PARTY NO: 1182		INST. ENG:		DATE: MO 5 DAY 25 YR 78								
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III	<input type="checkbox"/> DFS IV	<input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> P-TRACK	FORMAT: B	<input type="checkbox"/> GAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 350 BPI	(H) <input type="checkbox"/> 712 BPI	<input type="checkbox"/> 1000 BPI
	<input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-48 & 49-96		<input type="checkbox"/> DFS III	<input type="checkbox"/> DFS IV	<input type="checkbox"/> OTHER	<input type="checkbox"/> 21 TRACK	SEG	<input type="checkbox"/> UNGAPPED			
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: B-DEC	<input type="checkbox"/> OCT	GAIN CONSTANT: 36	db	INPUT IMPEDANCE: ohms					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:						AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)					
DATA CHANNEL NOS. (ON MAG TAPE)												
PARAMETER	RECORD LENGTH: 5 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	<input type="checkbox"/> FINAL	<input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	FREQ. 128	HI CUT HZ SLOPE 0	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER	<input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 db	TRIP SENS: 1 db	POLARITY CONVENTION: PRESSURE INCREASE ON GEOPHONE	<input type="checkbox"/> NEGATIVE	<input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE	<input type="checkbox"/> DOWNBREAK	<input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.					
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: In line (single hole)	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
RECEIVER	CONNECTION:	RESISTANCE: ohms	STAGGER:	INLINE SPACING: LENGTH:	LATERAL SPACING: WIDTH:	LATERAL OFFSET:						
SPREAD	NO. OF GROUPS:	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 6	DIRECTION OF PROGRESSION: S to N			LEADING GROUP: 48				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 52		TR to		SHOT								SPREAD			REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	COP SWITCH	LINE GROUPS	USY	SET UP	TR 1-24	TR 25-48				
1102	1518	53	1703		20	67	52		63	79	→	T14	1	No log				
1109			1704		20	67	53		64	80	→	T15		shot through cable - short tail spread				
1113			1705		20	67	54	440	5	64	80	→	T15	offset interval 440 ft				
1117			1706		20	67	55	840	5	64	80	→	T15	" " 840 ft				