


# LAND SEISMIC RECORDING LOG

PAGE 1 OF 1

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>SOUTHERN FOOTHILLS</b>	LINE NO: <b>51X</b>											
	PARTY NO: <b>1184</b>	INST. ENG: <b>Nic Donald</b>	REC HRS <b>10 11 1/2 - TOTAL 1 1/2</b>		DATE: <b>MO 1 DAY 22 YR 78</b>										
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III	<input checked="" type="checkbox"/> DFS II	<input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK	<input type="checkbox"/> 21 TRACK	FORMAT-SEG: <b>B</b>	<input checked="" type="checkbox"/> GAPPED	<input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI	(M1) <input type="checkbox"/> 712 BPI	(H1) <input checked="" type="checkbox"/> 1000 BPI	
	<input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-48 & 49-96		<input type="checkbox"/> DFS III	<input type="checkbox"/> DFS II	<input type="checkbox"/> OTHER				<input checked="" type="checkbox"/> DEC.	<input type="checkbox"/> OCT.	GAIN CONSTANT: <b>3.6</b> db	INPUT IMPEDANCE: _____ ohms		
	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: _____	AUXILIARY DATA: <b>SPS TB</b>										
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>			AUXILIARY CHANNEL NOS.: _____											
	DATA CHANNEL NOS.: <b>1-96</b> (ON MAG TAPE)														
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>8</b>	LO CUT HZ SLOPE <b>18</b>	FREQ. <b>128</b>	HI CUT HZ SLOPE <b>72</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT							
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>24</b> db	TRIP SENS: _____	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEDPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY							
CFS I	TYPE STACK: <b>R.A.W.</b>	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____								
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____						
RECEIVER	TYPE: <b>GEOSPACE 200</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>14'</b>	LATERAL SPACING: _____		LENGTH: <b>110'</b>		WIDTH: _____ LATERAL OFFSET: _____						
SPREAD	CONNECTION: <b>SERIES-PAR.</b>	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____		WIDTH: _____		LATERAL OFFSET: _____							
	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>		LEADING GROUP: <b>96</b>								
	OFFSET GROUP 1: <b>5225</b>	OFFSET GROUP <b>48, 55'</b>	OFFSET GROUP <b>49, 55'</b>	OFFSET GROUP <b>48/96: 5225</b>											



SHOTPOINT	TR 10		TR 10		SHOT		SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		HT.	REC.	HT.
600	275	1176	289		110	105	1		START OF NEW LINE WITH 48 GAP TAILSPREAD.			
601			290		110	105	2					
602			291		110	105	3					
603			292		110	105	4					
604			293		110	105	5					
605			294		110	105	6					
606			295		110	105	7					
607			296		110	105	8					
608			297		110	105	9					
609			298		110	105	10					
610			299		110	90	11					
611			300		110	105	12					
612			301		110	105	13					
613			303		110	105	14		RECORD # 302 MISFIRE			
614			304		110	105	15					
615			305		110	105	16					
616			306		110	105	17					
617			308		110	105	18		RECORD # 307 MISFIRE			
618			309		110	105	19		BAD WEATHER - COLD + WINDY - LAD TO DRILLS.			

# LAND SEISMIC RECORDING LOG

PAGE 1092

	CLIENT: <b>HUSKY</b>	PROJECT: <b>NPR-A</b>	AREA: <b>SOUTHERN FOOT HILLS</b>	LINE NO.: <b>51X</b>					
	PARTY NO.: <b>1184</b>	INST. ENG: <b>Vic Donald</b>	<b>AEC HRS 10 1/2 TT 1 1/2 TOTAL 12</b>	DATE: <b>1 DAY 23 YR 78</b>					
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 24 & 25-48 <input checked="" type="checkbox"/> 26 & 49-96	<input type="checkbox"/> OPS & EVENS <input type="checkbox"/> ODDS & EVENS	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	<input type="checkbox"/> COPART. SEG <input checked="" type="checkbox"/> B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	FACTORY PRECISION: <input type="checkbox"/> 110 <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	IMU: <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1000 BPI	
19-TRACK:	NO. BYTES IN HEADER REC: <b>229</b>	NO. BYTES IN REF. SRC. REC: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> 01 <input type="checkbox"/> 02	GAIN CONSTANT: <b>36</b>	INPUT IMPEDANCE: <b>36</b>	IMPEDANCE: <b>36</b>	IMPEDANCE: <b>36</b>	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>	DATA CHANNEL NOS.: <b>1-96</b>	NO. MAG TAPE:	AUXILIARY DATA: <b>SPS TB</b>	AUXILIARY CHANNEL NOS.:				
PARAMETER	RECORD LENGTH: <b>8</b>	CAMP. RATE: <input checked="" type="checkbox"/> 1 sec <input type="checkbox"/> 2 sec <input type="checkbox"/> 4 sec	SCAN MODE: <input checked="" type="checkbox"/> REF <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL	FILTERS: <b>8</b>	LO CUT: <b>18</b>	HZ SLOPE: <b>128</b>	HZ SLOPE: <b>22</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT	AMPLIFIER: <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>24</b>	NOISE REDUCTION: <b>6</b>	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input checked="" type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	NUMBERS ON MAG TAPE: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON DISPLAY	
CFS I	TYPE STACK: <b>R.A.W.</b>	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	P.C.U. NORM / ALT SW		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CHG. HOLE: <b>110</b>	HOLE DEPTH: <b>105</b>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:
RECEIVER	TYPE: <b>GEOSPACE 20D</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>14'</b>	LATERAL SPACING:	STAGGER:	LENGTH: <b>110'</b>	WIDTH:	LATERAL OFFSET:
	CONNECTION: <b>SERIES-PAR</b>	RESISTANCE: <b>ohms</b>	STAGGER:	LENGTH: <b>110'</b>	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>	OFFSET GROUP: <b>5225</b>	LEADING GROUP: <b>96</b>		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 20		SHOT		SPREAD			REMARKS	CORR STACK						
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET	GRP		CDP SWITCH	LINE GROUPS	SET UP	HT	REC	HT	REC
619	7511176	322			110	105	1			1/4	SP613-SP625	①					
620		323			110	105	2			1/4	SP614-SP626						
621		324			110	105	3			1/4	SP615-SP627						
622		325			110	105	4			1/4	SP616-SP628						
623		326			110	105	5			1/4	SP617-SP629						
624		328			110	105	6			1/4	SP618-SP630		RECORD # 327 MISFIRE				
625		330			110	105	7			1/4	SP619-SP631	②	RECORD # 329 MISFIRE				
626		332			110	105	8			1/4	SP620-SP632		RECORD # 331 MISFIRE				
627		334			110	105	9			1/4	SP621-SP633		RECORD # 333 MISFIRE				
628		335			110	105	10			1/4	SP622-SP634						
629		338			110	105	11			1/4	SP623-SP635		RECORD # 336 & 337 MISFIRE				
630		339			110	105	12			1/4	SP624-SP636						
631		340			110	105	13			1/4	SP625-SP637	③					
632		341			110	105	14			1/4	SP626-SP638						
633		342			110	105	15			1/4	SP627-SP639						
TARE CHANGE																	

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>HUSKY</b>	DEPT: <b>NPR-A</b>	AREA: <b>SOUTHERN FOOTHILLS</b>	LINE NO: <b>51X</b>	
	PARTY NO: <b>1184</b>	INS: <b>McDonald</b>	WELL: <b>NEC HRS 10 1/2</b>	DATE: <b>11/23/78</b>	
			TIME: <b>1 1/2</b>	TOTAL: <b>12 HRS.</b>	
INSTRUMENT	<input checked="" type="checkbox"/> SYSTEM	<input type="checkbox"/> 24 & 25-48	<input checked="" type="checkbox"/> 2-48 & 49-96	<input checked="" type="checkbox"/> TRACKS	<input type="checkbox"/> TRACKS
19-TRACK	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORDING: <b>2</b>	NO. BYTES IN TOTAL: <b>254</b>	FORMAT: <b>B</b>	PACK NO. DENSITY: <b>36</b>
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: <b>1-96</b>	DATA CHANNEL NOS: <b>1-96</b>	AUXILIARY DATA: <b>SPS TB</b>		
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 250	INITIAL GAIN: <b>24</b> db	FILTERS: <b>8</b>	NOISE REDUCTION: <b>18</b>
DISPLAY	MODE: <input checked="" type="checkbox"/> MAGC	<input type="checkbox"/> FLOAT	<input type="checkbox"/> AMPLIFIER	<input type="checkbox"/> OFFLINE	POLARITY CONVENTION: <b>8</b>
CFS I	TYPE STACK: <b>R.A.W.</b>	GATE LENGTH:	RECORD POSITION:	NOISE REDUCTION:	CORR SCALING:
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMIC	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:
	<input type="checkbox"/> VIBROSEIS	CHG. MOLE: <b>110'</b>	MOLE DEPTH: <b>105'</b>	SWEEP START:	SWEEP END:
RECEIVER	TYPE: <b>GEOSPACE 20D</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>14'</b>	LATERAL SPACING:
	CONNECTION: <b>SERIES-PAR</b>	RESISTANCE:	STAGGER:	LENGTH: <b>110</b>	WIDTH:
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLO: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>
	OFFSET GROUP: <b>5225</b>	OFFSET GROUP: <b>44, 55'</b>	OFFSET GROUP: <b>49, 55'</b>	OFFSET GROUP: <b>5225</b>	LEADING GROUP: <b>96</b>


DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 10		SHOT		SPREAD		REMARKS	CORE STACK	
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET		LINE GROUPS	TR 10-10
634	2751172	344			110	105	16		Y33 SP628-SP640 ③		
635		345			110	105	17		Y41 SP629-SP641		
636		346			110	105	18		Y49 SP630-SP642		
637		347			110	105	19		Y4 SP631-SP643 ④		
638		348			110	105	20		Y7 SP632-SP644		
639		349			110	105	21		Y25 SP633-SP645		
640		350			110	105	22		Y33 SP634-SP646		
641		351			110	105	23		Y41 SP635-SP647		
642		352			110	105	24		Y49 SP636-SP648		
643		353			110	105	25		Y4 SP637-SP649 ⑤		
644		354			110	105	26		Y7 SP638-SP650		
645		355			110	105	27		Y25 SP639-SP651		
646		356			110	105	28		Y33 SP640-SP652		
647		357			110	105	29		Y41 SP641-SP653		
648		358			110	105	30		Y49 SP642-SP654		



# LAND SEISMIC RECORDING LOG

		CLIENT: <b>HUSKY</b>		PROJECT: <b>NPR-A</b>		AREA: <b>SOUTHERN Foothills</b>		LINE NO: <b>51X</b>	
PARTY NO: <b>1184</b>		INST ENG: <b>McDonald</b>		REC HAS: <b>11/2</b>		T-T: <b>1/2</b>		TOTAL HAS: <b>13</b>	
DATE: <b>1</b>		DAY: <b>24</b>		YEAR: <b>78</b>					
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		NO BYTES IN HEADER REC: <b>228</b>		NO BYTES IN RECORD ID: <b>2</b>		NO BYTES IN TRACK: <b>254</b>		RECORD NUMBERS: <b>36</b>	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS: <b>1-96</b>		DATA CHANNEL NOS: <b>1-96</b>		AUTOMATIC CHANNEL NOS:		SPS: <b>TB</b>	
PARAMETER:		RECORD LENGTH: <b>8</b>		SAMPLE RATE: <input checked="" type="checkbox"/> 1 Hz <input type="checkbox"/> 5 ms		GAIN: <input checked="" type="checkbox"/> 10 <input type="checkbox"/> 100		FILTERS: <b>8</b>	
DISPLAY:		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMP/TICK		INITIAL GAIN: <b>24</b>		POLARITY: <input checked="" type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE		FREQ: <b>128</b>	
CFS I:		TYPE STACK: <b>R.A.W.</b>		GATE LENGTH:		NOISE THRESHOLD:		CORR SCALING:	
SOURCE:		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS		PATTERN: <b>SINGLE</b>		NO. OF POSITIONS:		INLINE SPACING:	
RECEIVER:		TYPE: <b>GEOSPAC 20D</b>		PATTERN: <b>INLINE</b>		NO. OF ELEMENTS: <b>9</b>		INLINE SPACING: <b>14'</b>	
SPREAD:		NO. OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>110'</b>		SHOTPOINT INTERVAL: <b>880'</b>		FOLD: <b>6</b>	
		OFFSET GROUP 1: <b>5225'</b>		OFFSET GROUP 48: <b>55'</b>		OFFSET GROUP 96: <b>55'</b>		DIRECTION OF PROGRESSION: <b>SOUTH</b>	



SHOTPOINT	TR		TR		SHOT		SPREAD		CDP SWITCH	LINE GROUPS	SET UP	CORR. STACK			
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET				TR 1-48	TR 48-96	HL	HL
649	751	117			110	105	1		X6	SP643-SP655	①				
650		372			110	105	2		X7	SP644-SP656					
651		373			110	105	3		X25	SP645-SP657					
652		374			110	105	4		X33	SP646-SP659					
653		375			110	105	5		X41	SP647-SP658					
654		376			110	105	6		X49	SP648-SP660					
655		377			110	105	7		X9	SP649-SP661	②				
656		378			110	105	8		X7	SP650-SP662					
657		379			110	105	9		X25	SP651-SP663					
658		380			110	105	10		X33	SP652-SP664					
659		381			110	105	11		X41	SP653-SP665					
660		382			110	105	12		X49	SP654-SP666					
661		383			110	105	13		X9	SP655-SP667	③				
662		384			110	105	14		X7	SP656-SP668					
663		385			110	105	15		X25	SP657-SP669					
664		386			110	105	16		X33	SP658-SP670					
665		387			110	105	17		X41	SP659-SP671					
666		388			110	105	18		X49	SP660-SP672					
667		389			110	105	19		X9	SP661-SP673	④				
668		390			110	105	20		X7	SP662-SP674					

WEAK SHOT

REMARKS: RECORD# 359-369 daily test  
RECORD# 370 test TB



# LAND SEISMIC RECORDING LOG

	CLIENT: <b>HUSKY</b>	PROJECT: <b>NPR-A</b>	AREA: <b>SOUTHERN FOOTHILLS</b>	LINE NO: <b>51X</b>	
	PARTY NO: <b>1184</b>	INST ENG: <b>Vic Donald</b>	REC HRS: <b>1 1/2</b>	T.T. <b>1 1/2</b>	TOTAL HRS: <b>13</b>
				DATE: <b>1 MAY 24 1978</b>	
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-28 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS & EVENS	<input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK
	NO BYTES IN HEADER REC: <b>228</b>	NO BYTES IN RECORD: <b>2</b>	NO BYTES IN LOG: <b>254</b>	RECORD NUMBER: <b>36</b>	INPUT IMPEDANCE: <b>36</b>
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>	DATA CHANNEL NOS.: <b>1-96</b>	ADJUTORY DATA: <b>SPS TB</b>	AUXILIARY CHANNEL NOS.:	
PARAMETER	RECORD LENGTH: <b>8</b>	SAMPLE RATE: <input checked="" type="checkbox"/> 1000 <input type="checkbox"/> 500	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: <b>8</b>	LOG CUT: <b>18</b>
DISPLAY	MODE: <input checked="" type="checkbox"/> ACC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>24</b>	JRIP SENS: <b>6</b>	REG: <b>12.8</b>
CFS I	TYPE STACK: <b>R.A.W.</b>	GATE LENGTH:	RECORD SELECTION:	NOISE REDUCTION:	NOISE THRESHOLD:
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:
		CHG. HOLE: <b>110</b>	HOLE DEPTH: <b>105'</b>	SWEEP POSITION:	SWEEP START:
RECEIVER	TYPE: <b>GEOSPACE 20 D</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>14'</b>	LATERAL SPACING:
	CONNECTION: <b>SERIES-PAR</b>	RESISTANCE:	STAGGER:	STAGGER LENGTH: <b>110'</b>	WIDTH:
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>
	OFFSET GROUP 1: <b>5225</b>	OFFSET GROUP 48: <b>55'</b>	OFFSET GROUP 49: <b>55'</b>	OFFSET GROUP 96: <b>5225</b>	LEADING GROUP: <b>76</b>

DIAGRAMS/MISC INFORMATION: **GEOPHONE ARRAY**  
 EACH PHONE 14' APART  
 - 5TH PHONE OF EACH 9 PHONE STAINING FALLS ON GAP FLAG  
 - STAINING ARE BUTTED END TO END.

SHOTPOINT	REEL NO.		PEEL NO.		SIZE		DEPTH		NO.	OFFSET	DIP	COP SWITCH	LINE GROUPS	REMARKS	CORR STACK				
	TR	TO	TR	TO	1	2	3	4							TR	REC	TR	REC	
669	751	1177	391		110	105	21		35			Y25	SP663-SP675	(4)					
670			392		110	105	22					Y3	SP664-SP676						
671			393		110	105	23					Y4	SP665-SP677						
672			394		110	105	24					Y49	SP666-SP678						
<b>TAPE CHANGE</b>																			

# LAND SEISMIC RECORDING LOG

PAGE 3 of 3


	CLIENT: <b>HUSKY</b>	PRJ. PECT: <b>NPR-A</b>	AREA: <b>SOUTHERN FOOTHILLS</b>	LINE NO.: <b>51X</b>	
	PARTY NO.: <b>1184</b>	INST. EMP.: <b>McDonald</b>	<b>AEC HRS 11 1/2</b>	<b>T-T 1 1/2</b>	<b>TOTAL 13</b>
	NO. BYTES IN HEADER REC: <b>229</b>	NO. BYTES IN RECORD: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <b>36</b>	DATE: <b>1 DAY 24 YR 78</b>
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: <b>1-96</b>			AUXILIARY DATA: <b>SPS TB</b>	
PARAMETER	RECORD LENGTH: <b>8</b>	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms	GAIN MODE: <input checked="" type="checkbox"/> A/T/P <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: <b>8</b>	EQ CUT: <b>18</b>
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>24</b>	TRIP SENS: <b>6</b>	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE
CFS I	TYPE STACK: <b>R.A.W.</b>	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:
RECEIVER	TYPE: <b>GEOSPACE 2.0D</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>14'</b>	LATERAL SPACING:
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>980'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>
	OFFSET GROUP 1: <b>5225</b>	OFFSET GROUP 48: <b>55'</b>	OFFSET GROUP 49: <b>55'</b>	OFFSET GROUP 96: <b>5225</b>	LEADING GROUP: <b>96</b>

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	COP SWITCH		LINE GROUPS	HT.
673	715	178	396		110	105	25	25		X6	SP667-SP679		
674			397		110	105	26	26		X7	SP668-SP680		
675			398		110	105	27	27		X5	SP669-SP681		
676			399		110	105	28	28		X3	SP670-SP682		
677			400		110	105	29	29		X1	SP671-SP683		
678			401		110	105	30	30		X9	SP672-SP684		
679			402		110	105	31	31		X6	SP673-SP685		
680			403		110	105	32	32		X7	SP674-SP686		
681			404		110	105	33	33		X5	SP675-SP687		
682			405		110	105	34	34		X3	SP676-SP688		
683			406		110	105	35	35		X1	SP677-SP689		
684			407		110	105	36	36		X9	SP678-SP690	(7) LATE TB FROM SHOOTER (BIG HILL)	
685			408		110	105	37	37		X6	SP679-SP691	AIRPLANE IN DISTANCE CAUSED SOME NOISE	
686			409		110	105	38	38		X7	SP680-SP692		
687			410		110	105	39	39		X5	SP681-SP693		
688			411		110	105	40	40		X3	SP682-SP694		
689			412		110	105	41	41		X1	SP683-SP695		
690			413		110	105	42	42		X9	SP684-SP696		

# LAND SEISMIC RECORDING LOG

PAGE 1 OF 1

	CLIENT: <b>HUSKY</b>	PROJECT: <b>NPR-A</b>	AREA: <b>SOUTHEAN FOOTHILLS</b>	LINE NO: <b>51 X</b>
	PARTY NO: <b>1184</b>	INST ENG: <b>Vic Donald</b>	REC HA: <b>10 1/2 T-T-3 1/2</b>	DATE: <b>25 YR 18</b>
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 24 & 25-48 <input type="checkbox"/> ODS & EYELES				
NO BYTES IN HEADR REC: <b>228</b> NO BYTES IN RECORD ID: <b>2</b> NO BYTES PER SCAN: <b>254</b> RECORD NUMBERS: <b>36</b>				
CONFIGURATION (MAG TAPE): <b>1-96</b> DATA CHANNEL NOS: <b>1-96</b> AUXILIARY DATA: <b>SPS 70</b>				
PARAMETER: RECORD LENGTH: <b>8</b> sec SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 2 ms				
DISPLAY: MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT INITIAL GAIN: <b>24 db</b> TRIP SENS: <b>6</b>				
CFS I: TYPE STACK: <b>RAW</b> GATE LENGTH: RECORD REJECTION: NOISE REDUCT ON: NOISE THRESHOLD: CORR. SCALING: <input type="checkbox"/> IN <input type="checkbox"/> B-DUT				
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER PATTERN: <b>SINGLE HOLE</b> NO. OF POSITIONS: INLINE SPACING: LATERAL SPACING: STAGGER: LENGTH: WIDTH: LATERAL OFFSET:				
RECEIVER: TYPE: PATTERN: <b>INLINE</b> NO. OF ELEMENTS: <b>9</b> INLINE SPACING: <b>14'</b> LATERAL SPACING: CONNECTION: RESISTANCE: STAGGER: LENGTH: <b>110'</b> WIDTH: LATERAL OFFSET:				
SPREAD: NO. OF GROUPS: <b>96</b> GROUP INTERVAL: <b>110</b> SHOTPOINT INTERVAL: <b>880'</b> FOLD: <b>6</b> DIRECTION OF PROGRESSION: <b>SOUTH</b> OFFSET GROUP 1: <b>5225</b> OFFSET GROUP: <b>48 55'</b> OFFSET GROUP: <b>49 55'</b> OFFSET GROUP: <b>5225'</b> LEADING GROUP: <b>96</b>				

DIAGRAMS/MISC. INFORMATION: **BY SHOT SP 671** **SP685** **SP691** **SP692** **SP697**  
**P 12** **THINGS P 11** **NORTH -> SOUTH** **55 110 110 110 110 110 110 110 55** **496**

SHOTPOINT	TR 1		TR 2		SHOT		DIR	CDP SWITCH	LINE GROUPS	REMARKS	CORR. STACK	
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH					HT	REC
691	751	1178	427		110	105	1	19	SP685-SP697	①		
692			428		110	105	2	17	SP686-SP698			
693			429		110	105	3	25	SP687-SP699			
694			430		110	105	4	33	SP688-SP700			
695			431		110	105	5	41	SP689-SP701			
696			432		110	105	6	49	SP690-SP702			
697			433		110	105	7	19	SP691-SP703	②		
698			434		110	105	8	17	SP692-SP704			
699			435		110	105	9	25	SP693-SP705			
700			436		110	105	10	33	SP694-SP706			
701			437		110	105	11	41	SP695-SP707			
702			438		110	105	12	41	SP696-SP708	③		
703			439		110	105	13	49	SP697-SP709			
704			440		110	105	14	17	SP698-SP710			
705			441		110	105	15	25	SP699-SP711			
706			442		110	105	16	33	SP700-SP712			
707			443		110	105	17	41	SP701-SP713			
708			444		110	105	18	49	SP702-SP714			

**TAKE CHANGE**

**SLOW GOING - WAITING ON DRILLS**



# LAND SEISMIC RECORDING LOG

PAGE 1 OF 2

	CLIENT: <b>HUSKY</b>	PROSPEC: <b>NPA-A</b>	AREA: <b>SOUTHEAST FOOTHILLS</b>	LINE NO: <b>51X</b>	
PARTY NO: <b>1184</b>	INST. ENG: <b>McDonald</b>	REC HRS <b>11/2</b> TT <b>1/2</b> TOTAL HRS <b>13</b>		DATE: <b>1 DAY 26 yr 78</b>	
INSTRUMENT	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> SYSTEMS	<input type="checkbox"/> 1-24 & 25 48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 1 TRACK <input type="checkbox"/> 21 TRACK
(9-TRACK)	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBER: <b>36</b>	PACKING DENSITY: <b>36</b>
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: <b>1-96</b>	DATA CHANNEL NOS: <b>1-96</b>	AUXILIARY DATA: <b>SPS TB</b>	AUXILIARY CHANNEL NOS: <b>ENERGY MONITOR ON TR 20 + TR 70 (M)</b>	
PARAMETER	RECORD LENGTH: <b>8</b>	SAMPLE RATE: <b>8</b>	GAIN: <b>24</b>	FILTERS: <b>8</b>	NO. CUT: <b>18</b>
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>24</b>	TRIP SENS: <b>6</b>	POLARITY CONVENTION: <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE
CFS I	TYPE STACK: <b>RAW</b>	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE HOLE</b>	NO. OF POSITIONS: <b>110</b>	INLINE SPACING: <b>105'</b>	LATERAL SPACING: <b>110'</b>
RECEIVER	TYPE: <b>SEA GEOSPACE 200-10HZ</b>	PATTERN: <b>IN/LINE</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>74'</b>	LATERAL SPACING: <b>110'</b>
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>880</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>
	OFFSET GROUP: <b>5225'</b>	OFFSET GROUP: <b>4855'</b>	OFFSET GROUP: <b>4855'</b>	OFFSET GROUP: <b>5225'</b>	LEADING GROUP: <b>96</b>

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT		SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		LINE GROUPS	TR 1-48
709	2751179	458			110	105	1		SP703-SP715 (1)		
710		459			110	105	2		SP704-SP716		
711		460			110	105	3		SP705-SP717		
712		461			110	105	4		SP706-SP718		
713		462			110	105	5		SP707-SP719		
714		463			110	105	6		SP708-SP720		
715		464			110	105	7		SP709-SP721		
716		465			110	105	8		SP710-SP722		
717		466			110	105	9		SP711-SP723		
718		467			110	105	10		SP712-SP724		
719		468			110	105	11		SP713-SP725		
720		469			110	105	12		SP714-SP726		
721		470			110	105	13		SP715-SP727 (3)		
722		471			110	105	14		SP716-SP728		
723		472			110	105	15		SP717-SP729		
724		473			110	105	16		SP718-SP730		
725		474			110	105	17		SP719-SP731		
726		475			110	105	18		SP720-SP732		
727		476			110	105	19		SP721-SP733 (4)		
728		477			110	105	20		SP722-SP734		

REMARKS: REC# 445-456 Daily test  
NEW TAPE RECORD# 457 Test TB

airplane on spread

# LAND SEISMIC RECORDING LOG

PAGE 2 of 2

CLIENT: <b>Husky</b>		PROJECT: <b>NPR-A</b>		AREA: <b>SOUTHERN FOOTHILLS</b>		LINE NO: <b>51X</b>	
PARTY NO: <b>1184</b>		INST ENG: <b>W. P. ...</b>		REC HRS: <b>1 1/2</b>		TT: <b>1 1/2</b>	
TOTAL HRS: <b>13</b>		DATE: <b>MO 1 DAY 26 YR 78</b>					
INSTRUMENT: <b>[9-TRACK] NO. BYTES IN HEADER REC: 228</b>		NO. BYTES IN RECORD ID: <b>2</b>		NO. BYTES PER SCAN: <b>254</b>		RECORD NUMBERS: <b>X DEC</b>	
CONFIGURATION (MAG TAPE): <b>FIELD TRACE NOS: 1-96</b>		DATA CHANNEL NOS: <b>1-96</b>		AUXILIARY DATA: <b>SPS TB</b>		AUXILIARY CHANNEL NOS:	
PARAMETER: <b>RECORD LENGTH: 8</b>		SAMPLE RATE: <b>2.4</b>		GAIN MODE: <b>6</b>		FILTERS: <b>FREQ: 8</b>	
DISPLAY: <b>MODE: ASC</b>		INITIAL GAIN: <b>2.4</b>		TRIP SENS: <b>6</b>		POLARITY: <b>NEGATIVE</b>	
CFS I: <b>TYPE STACK: R.A.W.</b>		GATE LENGTH:		RECORD REJECTION:		NOISE THRESHOLD:	
SOURCE: <b>PATTERN: SINGLE HOLE</b>		NO. OF POSITIONS: <b>110</b>		HOLE DEPTH: <b>105'</b>		INLINE SPACING: <b>14'</b>	
RECEIVER: <b>TYPE: GEOSPAGE 20D</b>		PATTERN: <b>INLINE</b>		NO. OF ELEMENTS: <b>9</b>		LATERAL SPACING: <b>110'</b>	
CONNECTION: <b>SERIES-PAR.</b>		RESISTANCE:		STAGGER:		LATERAL OFFSET:	
SPREAD: <b>NO. OF GROUPS: 96</b>		GROUP INTERVAL: <b>110'</b>		SHOTPOINT INTERVAL: <b>880'</b>		FOLD: <b>6</b>	
OFFSET GROUP: <b>5225</b>		OFFSET GROUP: <b>48 55'</b>		OFFSET GROUP: <b>48 55'</b>		DIRECTION OF PROGRESSION: <b>SOUTH</b>	
						LEADING GROUP: <b>96</b>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 10		TR. 11 to 20		TR. 21 to 30		TR. 31 to 40		TR. 41 to 50		TR. 51 to 60		TR. 61 to 70		TR. 71 to 80		TR. 81 to 90		TR. 91 to 96		
	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	
729	2751	478																			
730		479																			
731		480																			
732		481																			
733		482																			
734		483																			
735		484																			
736		485																			
737		486																			
738		487																			
739		488																			
740		489																			
741		490																			
742		491																			
743		492																			
744		493																			
Tape Change																					
Late TB FROM SHOOTER																					

# LAND SEISMIC RECORDING LOG

PAGE 1 OF 3

	CLIENT: <b>HUSKY</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>SOUTHERN FOOTHILLS</b>	LINE NO.: <b>51X</b>						
	PARTY NO.: <b>1184</b>	INST. ENG.: <b>McDonald</b>	<b>REC HAS 12 1/2 TT 1 1/2 TOTAL HAS 14</b>	DATE: <b>1 DAY 27 YR 78</b>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	CODES <input type="checkbox"/> ODD <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 3 TRACK	FORMAT: <b>B</b>	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 712 BPI (12) <input checked="" type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES A RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	NO. OF POSITIONS: <b>9</b>	AUXILIARY DATA: <b>SPS 78</b>	AUXILIARY CHANNEL NOS.	CONSTANT: <b>36</b>	INPUT IMPEDANCE: _____ ohms		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ: <b>9</b> LC CUT FZ SLOPE: <b>18</b>		HP CUT FZ SLOPE: <b>72</b> NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
	DATA CHANNEL NOS.: <b>1-96</b>		TRIP SENS: <b>6</b>		POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> JPBREAK			
PARAMETER	RECORD LENGTH: <b>8</b> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	INITIAL GAIN: <b>24</b> db	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORMAL SW		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIERS <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT									
CFS I	TYPE STACK: <b>R.A.W</b>	GATE LENGTH:								
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>SINGLE</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ HOLE: <b>110</b>	HOLE DEPTH: <b>105'</b>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____		
RECEIVER	TYPE: <b>GEDSPACE 200</b>		PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>14'</b>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: <b>SERIES-PAR.</b>		RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>880'</b>	POLO: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>					
	OFFSET GROUP: <b>5225</b>	OFFSET GROUP: <b>48 55'</b>	OFFSET GROUP: <b>49 55'</b>	OFFSET GROUP: <b>5225</b>	LEADING GROUP: <b>96</b>					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		YR _____ to _____		SHOT			SPREAD			REMARKS	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	SET UP	TR 1-48	TR 49-96	TR 1-48
745	751	506			110	105	1			49	SP739-SP751	①				
746		507			110	105	2			49	SP740-SP752					
747		508			110	105	3			49	SP741-SP753					
748		509			110	105	4			49	SP742-SP754					
749		510			110	105	5			49	SP743-SP755					
750		511			110	105	6			49	SP744-SP756					
751		512			110	105	7			49	SP745-SP757	②				
752		513			110	105	8			49	SP746-SP758					
753		514			110	105	9			49	SP747-SP759					
754		515			110	105	10			49	SP748-SP760					
755		516			110	105	11			49	SP749-SP761					
756		517			110	105	12			49	SP750-SP762					
757		518			110	105	13			49	SP751-SP763	③				
758		519			110	105	14			49	SP752-SP764					
759		520			110	105	15			49	SP753-SP765					
760		521			110	105	16			49	SP754-SP766					
761		522			110	105	17			49	SP755-SP767					
762		523			110	105	18	100.5		49	SP756-SP768					
763		524			110	105	19			49	SP757-SP769	④				
764		525			110	105	20			49	SP758-SP770					



# LAND SEISMIC RECORDING LOG

		CLIENT: <b>HUSKY</b>		PROSPECT: <b>NPR-A</b>		AREA: <b>SOUTHERN FOOTHILLS</b>		LINE NO: <b>51X</b>	
PARTY NO: <b>11804</b>		INST. ENG: <b>McDonald</b>		RECHRS: <b>12 1/2</b>		T.T.: <b>1 1/2</b>		TOTAL HRS: <b>14</b>	
DATE: <b>MO 1 DAY 27 YR 78</b>		NO. BYTES IN HEADER REC: <b>238</b>		NO. BYTES IN RECORD ID: <b>2</b>		NO. BYTES PER SCAN: <b>254</b>		RECORD NUMBERS: <b>X DEV</b>	
INSTRUMENT: <b>1 SYSTEM</b>		<input type="checkbox"/> 1-24 & 25-48		<input type="checkbox"/> CODES & EVENS		<input type="checkbox"/> DFS III		<input checked="" type="checkbox"/> DFS II	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS.: <b>1-96</b>		DATA CHANNEL NOS.: <b>1-96</b>		AUXILIARY DATA: <b>SPS TB</b>		AUXILIARY CHANNEL NOS.:	
PARAMETER: RECORD LENGTH: <b>8</b>		SAMPLE RATE: <input checked="" type="checkbox"/> 2 ms		GAIN MODE: <input checked="" type="checkbox"/> LFP		FILTERS: <b>8</b>		CUT FREQ: <b>128</b>	
DISPLAY: MODE: <input checked="" type="checkbox"/> AGC		INITIAL GAIN: <b>24</b>		TRIP SENS: <b>6</b>		POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE		NOTCH FILTER: <input type="checkbox"/> IN	
CFS I: TYPE STACK: <b>R.A.W.</b>		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		CORR SCALING:	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE		PATTERN: <b>SINGLE</b>		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:	
RECEIVER: TYPE: <b>GEOSPACE 200</b>		PATTERN: <b>INLINE</b>		NO. OF ELEMENTS: <b>9</b>		INLINE SPACING: <b>14'</b>		LATERAL SPACING:	
SPREAD: NO. OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>110'</b>		SHOTPOINT INTERVAL: <b>880'</b>		FOLD: <b>6</b>		DIRECTION OF PROGRESSION: <b>SOUTH</b>	
DIAGRAMS/MISC. INFORMATION:		CHG/HOLE: <b>110</b>		MOLE DEPTH: <b>105'</b>		SWEEP POSITION:		SWEEP START:	

SHOTPOINT	TR 1 to 10		TR 11 to 20		TR 21 to 30		TR 31 to 40		TR 41 to 50		TR 51 to 60		TR 61 to 70		TR 71 to 80		TR 81 to 90		TR 91 to 96		REMARKS	
	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.		
765	751	1810	526																			
766			527																			
767			528																			
768			529																			
769			530																			
770			531																			
771			532																			
772			533																			
773			534																			
774			535																			
775			536																			
776			537																			
777			538																			
778			539																			
779			540																			
780			541																			
781			542																			
782			543																			
783			544																			
TAPES CHANGE																						

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>HUSKY</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>SOUTHERN FOOTHILLS</b>	LINE NO: <b>51X</b>					
	PARTY NO: <b>1184</b>	INST. ENG: <b>Nic Donald</b>	REC HRS: <b>12 1/2</b>	T.T. <b>1 1/2</b> TOTAL HRS <b>14</b>	DATE: <b>MO 1 DAY 27, YR 78</b>				
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> E-SENS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input checked="" type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 7 TRACK	FORMAT SEG <b>B</b>	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 300 BPI (12) <input type="checkbox"/> 272 BPI (13) <input checked="" type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEL. <input type="checkbox"/> COPY	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. <b>1-96</b> DATA CHANNEL NOS.: <b>1-96</b> (ON MAG TAPE)			AUXILIARY DATA: <b>SPS TB</b>					
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ <b>9</b> Hz CUT <b>18</b> Hz SLOPE <b>18</b>	FREQ <b>128</b> Hz SLOPE <b>72</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>24</b> db	TRIP SENS: <b>6</b> db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input checked="" type="checkbox"/> NUMBERS ON MAG TAPE: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON DISPLAY			
CFS I	TYPE STACK: <b>R, A, W</b>	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <b>GEOSPACE 20D</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>14'</b>	LATERAL SPACING: <b>110'</b>	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>980'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>	SWEEP START: _____	SWEEP LENGTH: _____	SWEEP TAPE: _____	PHASE COMP: _____
DIAGRAMS/MISC. INFORMATION:									

SHOTPOINT	TR 10		TR 10		SHOT			SPREAD			REMARKS: <b>REC # 545 NEW TAPE</b>	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIP	COP SWITCH		LINE GROUPS	SET UP	TR 10	TR 10	TR 10
784	751	181	546		110	105	40			33	SP778-SP790	①				
785			547		110	105	41			41	SP779-SP791					
786			548		110	105	42	175	W	49	SP780-SP792					
787			549		110	105	43			49	SP781-SP793	②				
788			550		110	105	44			47	SP782-SP794					
789			551		110	105	45			45	SP783-SP795					
790			552		110	105	46			43	SP784-SP796					
791			553		110	105	47			41	SP785-SP797					
792			554		110	105	48			49	SP786-SP798					
793			555		110	105	49			49	SP787-SP799	③				
794			556		110	105	50			47	SP788-SP800					
795			557		110	105	51			45	SP789-SP801					
796			558		110	105	52			43	SP790-SP802					
797			559		110	105	53			41	SP791-SP803					
798			560		110	105	54			49	SP792-SP804					





# LAND SEISMIC RECORDING LOG

PAGE 2 OF 3

	CLIENT: <b>MUSKY</b>	PROSPECT: <b>NPA-A</b>	AREA: <b>SOUTHEARN. FOOTHILLS</b>	LINE NO: <b>51 X</b>							
	PARTY NO: <b>1184</b>	INST. ENG: <b>Vic Ronald</b>	<b>RECHAS 12</b>	<b>T.T. 1/2 TOTAL HRS 13 1/2</b>		DATE: <b>MO 1 DAY 28 TR 78</b>					
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>SEG 0</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 800 BPI	(11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 1000 BPI	
(9-TRACK)	NO BYTES IN HEADER REC: <b>254</b>	NO BYTES IN RECORD ID: <b>2</b>	NO BYTES PER SCAN: <b>228</b>	RECORD NUMBERS: <b>4 DEC 11 OCT</b>	GAIN CONSTANT: <b>36db</b>	INPUT IMPEDANCE: _____ ohms					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: <b>1-96</b>				AUXILIARY DATA: <b>SPS TA</b>						
	DATA CHANNEL NOS: <b>1-96</b> (ON MAG TAPE)				AUXILIARY CHANNEL NOS: <b>ENERGY MONITOR ON TR 20 + TR 70 (PAPER)</b>						
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 mi. <input type="checkbox"/> 4 mi. <input checked="" type="checkbox"/> 82 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	MANUAL OPERATE	FILTERS	FREQ: <b>8</b>	LO CUT HZ SLOPE: <b>18</b>	HIGH CUT HZ SLOPE: <b>72</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>24</b> db	TRIP SENS: _____ db	RECORD REJECTION: _____	POLARITY CONVENTION	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK: <b>RAW</b>	GATE LENGTH: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM. ALT SW. _____					
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE HOLE</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
		CHG/ HOLE: <b>110</b>	HOLE DEPTH: <b>105</b>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____		
RECEIVER	TYPE: <b>GEO SPACE 200-10HC</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>14'</b>	LATERAL SPACING: <b>110'</b>	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
	CONNECTION: <b>SERIES MARQUEE</b>	RESISTANCE: _____ ohms									
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>	OFFSET GROUP 1: <b>5225'</b>	OFFSET GROUP 49: <b>55'</b>	OFFSET GROUP 96: <b>5225'</b>	LEADING GROUP: <b>96</b>		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 10		SHOT					SPREAD			REMARKS	CORR STACK	
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET	DIP	CDP SWITCH	LINE GROUPS	SET		TR 10	TR 20
819	751181	592			110	105	21	35		1/25	SP813 → SP825	④			
820		593			110	105	22			1/33	SP814 → SP826				
821		594			110	105	23			1/41	SP815 → SP827				
822		595			110	105	24			1/49	SP816 → SP828				
823		596			110	105	25			1/4	SP817 → SP829				
824		597			110	105	26			1/17	SP818 → SP830				
<b>TAPE CHANGE</b>															

# LAND SEISMIC RECORDING LOG

		CLIENT: <b>HUSKY</b>	PROSPECT: <b>NPA-A</b>	AREA: <b>SOUTHERN FOOTHILLS</b>	LINE NO: <b>51 X</b>						
PARTY NO: <b>1184</b>		INST. ENG: <b>McDonald</b>		DATE: <b>DEC HAS 12 T.T. 1/2 TOTAL HAS 13 1/2</b>		MO: <b>1</b> DAY: <b>28</b> YR: <b>78</b>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE	<input type="checkbox"/> DFS II <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY	(L): <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H): <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <b>806</b>	DATE: <b>17 OCT</b>	TAPE CONSTANT: <b>36 db</b>	INPUT IMPEDANCE: _____ ohms				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>			AUXILIARY DATA: <b>SRS TB</b>			AUXILIARY CHANNEL NOS.: _____				
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> STEP <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ: <b>8</b> LC CUT: <b>18</b> HZ SLOPE: <b>18</b>	FREQ: <b>128</b> HZ SLOPE: <b>22</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>24 db</b>	TRIP SENS: _____	<b>6 db</b>	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____	DOWNBREAK: <input type="checkbox"/> ON DISPLAY				
CFS I	TYPE STACK: <b>RAW</b>	GATE LENGTH: _____	RECORD REFLECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR SCALING: _____	P.C.U. NORM. ALT SW: _____				
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE HOLE</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
RECEIVER	TYPE: <b>GEOSPACE 200-10HZ</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>14'</b>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: <b>110'</b>	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>480'</b>	OFFSET GROUP: <b>48.55'</b>	OFFSET GROUP: <b>48.55'</b>	FOLD: <b>6</b>	OFFSET GROUP: <b>48.55'</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>	LEADING GROUP: <b>96</b>		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT				SPREAD				REMARKS	CORR STACK				
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH	LINE GROUPS			SET UP	TR 1-10	REC.	TR 11-20	REC.
825	2751	589	17	2253	110	105	27	30	W	1/25	5P819	→	5P871	⑤				
826		600			110	105	28			1/33	5P820	→	5P832					
827		601			110	105	29			1/41	5P821	→	5P833					
828		602			110	80	30			1/49	5P822	→	5P834					
SLOW GOING--WAITING ON DRILLS -BAD CABLES.																		

# LAND SEISMIC RECORDING LOG

PAGE 1097

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>SOUTHERN FOOTHILLS</b>	LINE NO: <b>51X</b>					
	PARTY NO: <b>1184</b>	INST. ENG: <b>Nic Donald</b>	<b>DEC HAS 13 1/2</b>	<b>T.T. L TOTAL 14 1/2</b>	DATE: <b>NOV 29 1978</b>				
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (M) <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: (1) <input type="checkbox"/> 150 (4) <input type="checkbox"/> 150 (15) <input type="checkbox"/> 150 (6) <input type="checkbox"/> 150 (17) <input type="checkbox"/> 150			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: <b>1-96</b>				AUXILIARY DATA: <b>S/S T/B</b>				
	DATA CHANNEL NOS: <b>1-96</b> (ON MAG TAPE)				AUXILIARY CHANNEL NOS:				
PARAMETER	RECORD LENGTH: <b>8</b> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input checked="" type="checkbox"/> 2 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> I/FP	FILTERS: FREQ: <b>8</b>	LO CUT HZ: <b>18</b>	HIGH CUT HZ SLOPE: <b>72</b>	ENGLISH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> ACC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/>	INITIAL GAIN: <b>24</b> db	TRIP SENS: <b>6</b> db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/>	NUMBERS ON MAG TAPE: <input type="checkbox"/>	DOWNBREAK UPBREAK: <input type="checkbox"/>	ON DISPLAY: <input type="checkbox"/>
CFS I	TYPE STACK: <b>R.A.W.</b>	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR SCALING:	R.C.U. NORM / ALT SW		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CHG/ HOLE: <b>110</b>	HOLE DEPTH: <b>105</b>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:
RECEIVER	TYPE: <b>GEOSPACE 200</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>14'</b>	LATERAL SPACING:	STAGGER:	LENGTH: <b>110'</b>	WIDTH:	LATERAL OFFSET:
	CONNECTION: <b>SERIES-PAR</b>	RESISTANCE:	STAGGER:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:			
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>				
	OFFSET GROUP 1: <b>5225</b>	OFFSET GROUP: <b>48, 55'</b>	OFFSET GROUP: <b>49, 55'</b>	OFFSET GROUP #/96: <b>5225</b>	LEADING GROUP: <b>96</b>				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 110		TR 110		SHOT			SPREAD			REMARKS	CORR STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH		LINE GROUPS	TR 110
829	275	1182	615		110	105	1			1/4	SP823 → SP835		
830			616		110	105	2			1/4	SP824 → SP836		
831			617		110	105	3			1/4	SP825 → SP827		
832			618		110	105	4			1/4	SP826 → SP838		
833			619		110	105	5			1/4	SP827 → SP839		
834			620		110	60	6			1/4	SP828 → SP840		
835			621		110	105	7			1/4	SP829 → SP841	(2)	
836			622		110	105	8			1/4	SP830 → SP842		
837			623		110	105	9			1/4	SP831 → SP843		
838			624		110	105	10			1/4	SP832 → SP844		
839			625		110	105	11			1/4	SP833 → SP845		
840			626		110	105	12			1/4	SP834 → SP846		
841			627		110	105	13			1/4	SP835 → SP847	(3)	
842			628		110	105	14			1/4	SP836 → SP848		
843			629		110	105	15			1/4	SP837 → SP849		
844			630		110	105	16			1/4	SP838 → SP850		
845			631		110	105	17			1/4	SP839 → SP851		
846			632		110	105	18			1/4	SP840 → SP852		
847			633		110	105	19			1/4	SP841 → SP853	(4)	
848			634		110	105	20			1/4	SP842 → SP854	WEAK SHOT PROBABLY ONLY 10 db. WENT OFF.	



# LAND SEISMIC RECORDING LOG

PAGE 2 of 3

	CLIENT: <b>HUSKY</b>	PROJECT: <b>NPR-A</b>	AREA: <b>SOUTHERN FOOT HILLS</b>	LINE NO: <b>51X</b>					
	PARTY NO: <b>1184</b>	INST. ENG: <b>Nic Donald</b>	<b>REC HAS 13 1/2</b>	<b>T-T-L TOTAL 14 1/2</b>	DATE: <b>NO 1 DAY 29 YR 78</b>				
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input checked="" type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPIAT: <b>B</b>	<input checked="" type="checkbox"/> GARFED <input type="checkbox"/> UNGARFED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI (X) <input checked="" type="checkbox"/> 1600 BPI	
(9-TRACK)	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN: <b>36</b> db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: <b>1-96</b>	DATA CHANNEL NOS: <b>1-96</b> (ON MAG TAPE)			AUXILIARY DATA: <b>SPS TB</b>	AUXILIARY CHANNEL NOS: _____			
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input checked="" type="checkbox"/> SFP	FILTERS: <b>8</b>	EQ CUT: <b>18</b>	FREQ: <b>128</b>	HZ SLOPE: <b>72</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT <input checked="" type="checkbox"/> AGC	INITIAL GAIN: <b>24</b> db	TRIP SENS: <b>6</b> db	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		
CFS I	TYPE STACK: <b>R.A.W.</b>	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR SCALING: _____	A.C.U. NORM. ALT SW		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ HOLE: <b>110</b>	HOLE DEPTH: <b>105</b>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: <b>GEOSPACE 20D</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>14'</b>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: <b>110'</b>	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: <b>SERIES-PAR</b>	RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>	OFFSET GROUP #/96: <b>5225</b>	LEADING GROUP: <b>96</b>		
	OFFSET GROUP 1: <b>5225</b>	OFFSET GROUP <b>48</b> : <b>55'</b>	OFFSET GROUP <b>49</b> : <b>55'</b>						


DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 10		SHOT				SPREAD				REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS			SET UP	TR 1-28	TR 41-96	TR 1-28
849	2751	182	635		110	105	21				K25	SP843 → SP855	④				
850			636		110	105	22				K33	SP844 → SP856					
851			637		110	105	23				M1	SP845 → SP857		LATE TIME BREAK X			
852			638		110	105	24				K49	SP846 → SP858					
853			639		110	105	25				K9	SP847 → SP859	⑤				
854			640		110	105	26				K7	SP848 → SP860					
855			641		110	105	27				K25	SP849 → SP861					
856			642		110	105	28				K33	SP850 → SP862					
857			643		110	105	29				K41	SP851 → SP863					
858			644		110	105	30				K49	SP852 → SP864					
859			645		110	105	31				K9	SP853 → SP865	⑥				
860			646		110	105	32				K7	SP854 → SP866					
861			647		110	105	33				K25	SP855 → SP867					
862			648		110	105	34				K33	SP856 → SP868					
TAPE CHANGE																	



# LAND SEISMIC RECORDING LOG

PAGE 1 of 2


	CLIENT: <b>Husky</b>	PROJECT: <b>NPR-A</b>	AREA: <b>SOUTHERN FOOTHILLS</b>	LINE NO: <b>51X</b>					
	PARTY NO: <b>1184</b>	INST ENG: <b>Nic Donald</b>	REC HRS: <b>9 1/2</b>	T-T: <b>2</b>					
			TOTAL: <b>1 1/2</b>	DATE: <b>MO 1 DA 30 YR 78</b>					
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT-SEG: <b>B</b>	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: 101 <input type="checkbox"/> 356 BPI 102 <input type="checkbox"/> 800 BPI	1111 <input type="checkbox"/> 712 BPI 1112 <input checked="" type="checkbox"/> 1600 BPI
(9-TRACK)	NO. BYTES IN HEADER REC.: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: <b>1-96</b>				AUXILIARY DATA: <b>SPS TB</b>				
	DATA CHANNEL NOS: <b>1-96</b>				AUXILIARY CHANNEL NOS: _____				
PARAMETER	RECORD LENGTH: <b>8</b> sec	SAMPLE RATE: <input type="checkbox"/> 1 ml <input checked="" type="checkbox"/> 2 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> IFF	MANUAL OPERATE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: FREQ: <b>8</b>	LO CUT HZ SLOPE: <b>18</b>	H CUT HZ SLOPE: <b>72</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT	AMPLIFIER DIRECT: <input type="checkbox"/>	INITIAL GAIN: <b>24</b> db	JRIP SENS: <b>6</b> ds	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GLOPHONE: _____	<input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/>	<input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK
CFS I	TYPE STACK: <b>R.A.W.</b>	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM. ALT SW		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG/HOLE: <b>110</b>	HOLE DEPTH: <b>105</b>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
RECEIVER	TYPE: <b>GEO SPACE 20D</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>14'</b>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: <b>110'</b>	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTIONS: <b>SERIES-PAR.</b>	RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>880</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>	OFFSET GROUP 1: <b>5225</b>	OFFSET GROUP 96: <b>5225</b>	LEADING GROUP: <b>96</b>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT		SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		LINE GROUPS	TR 1-41	TR 41-96
883	7751183	683			110	105	1		19	SP878 → SP888		
884		684			110	105	2		17	SP878 → SP890		
885		685			110	105	3		25	SP879 → SP891		
886		686			110	105	4		33	SP880 → SP892		
887		687			110	105	5		41	SP881 → SP893		
888		688			110	105	6		1	SP882 → SP894		
889		689			110	105	7		19	SP883 → SP895		
890		690			110	105	8		27	SP884 → SP896		
891		691			110	105	9	320 N	25	SP885 → SP897		
892		692			110	105	10		33	SP886 → SP898		
893		693			110	105	11		41	SP887 → SP899		
894		694			110	105	12		1	SP888 → SP900		
895		695			110	105	13		19	SP889 → SP901		
896		696			110	105	14		27	SP890 → SP902		
897		697			110	105	15		25	SP891 → SP903		
898		698			110	105	16		33	SP892 → SP904		
899		699			110	105	17		41	SP893 → SP905		
900		700			110	105	18		19	SP894 → SP906		
TAPES CHANGE												



# LAND SEISMIC RECORDING LOG

	CLIENT: <b>HUSKY</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>SOUTHERN FOOTHILLS</b>	LINE NO: <b>51 X</b>					
	PARTY NO: <b>1184</b>	INST. ENG: <b>Nic Donald</b>	<b>BEC HAS 9 1/2 T.T. 2 TOTAL 11 1/2</b>	DATE: <b>1 DAY 30 YR 78</b>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	BODS & EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input checked="" type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>			AUXILIARY DATA: <b>SPS TB</b>					
	DATA CHANNEL NOS.: <b>1-96</b>			(ON MAG TAPE)					
PARAMETER	RECORD LENGTH: <b>8</b> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input checked="" type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ: <b>8</b>	LO CUT HZ SLOPE: <b>18</b>	H CUT HZ SLOPE: <b>72</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>24</b> db	TRIP SENS: <b>6</b> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY		
CFS I	TYPE STACK: <b>R.A.W.</b>	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	P.C.U. NORM/ALT SW: _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE HOLE</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG/ HOLE: <b>110</b>	HOLE DEPTH: <b>105'</b>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
RECEIVER	TYPE: <b>GEOSPACE 200</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>14'</b>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: <b>110'</b>	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: <b>SERIES PAR.</b>	RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>	LEADING GROUP: <b>96</b>			
	OFFSET GROUP 1: <b>5225</b>	OFFSET GROUP <b>48</b> : <b>55'</b>	OFFSET GROUP <b>49</b> : <b>55'</b>	OFFSET GROUP <b>96</b> : <b>5225</b>					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR	TR		TR		SHOT		SPREAD		REMARKS	CORR. STACK						
		REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	HT.	REC.	HT.	REC.
901	2	751	189	702		110	105	19			SP895 → SP907						
902				703		110	105	20			SP896 → SP908						
903				704		110	105	21			SP897 → SP909						
904				705		110	105	22			SP898 → SP910						
905				706		110	105	23			SP899 → SP911						
906				707		110	105	24			SP900 - TS 8						
907				708		110	105	25			SP901 - TS 16						
908				709		110	105	26			SP902 - TS 24						
909				711		110	105	27	330	S	SP903 - TS 32						
910				712		110	105	28			SP904 - TS 40						
911				713		110	105	29			SP905 - TS 48						
TAPE CHANGE																	

REMARKS: REC. # 901 DUMMY RECORD  
NEWTAPE

RECORD # 710 MISFIRE

END OF LINE WITH 48 GROUP TAILSPREAD