

LAND SEISMIC RECORDING LOG

	CLIENT: <i>Husky</i>	PROSPECT: <i>DRIET WOOD</i>	AREA: <i>NPR - A DAWSON</i>	LINE NO: <i>85X</i>					
	PARTY NO: <i>1186</i>	INST. ENG: <i>REIT</i>				DATE: <i>MO 3 DAY 2 YR 78</i>			
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS:			DATA CHANNEL NOS: _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____		
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> IFP <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ _____	LO CUT HZ SLOPE	HIGH CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY				
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	P.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	
RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION:	RESISTANCE: _____ ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:				
	OFFSET GROUP 1:	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96:	LEADING GROUP:				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT								SPREAD	REMARKS:	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SET UP			TR 1-24	TR 48-96	REC.	REC.			
																HY.	HY.	HY.	HY.		
1	9	1213	16	17	22	23	24	27	29	30	32	35	37								

WAIT ON DRILLS
 SERVICED VEHICLES
 CHECK & REPAIRED TRUCKS
 LAIN OUT ON LINE
 85X

LAND SEISMIC RECORDING LOG

1

		CLIENT: <u>HUSKY</u>	PROSPECT: <u>DRIFT WOOD</u>	AREA: <u>NPR-D ALASKA</u>	LINE NO: <u>85 X</u>					
PARTY NO: <u>1186</u>		INST. ENG: <u>REID</u>		DATE: <u>MO 3 DAY 3 YR 78</u>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u> SEG	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC: <u>128</u>	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: <u>254</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>			AUXILIARY DATA: (1) <u>1</u> (2) <u>2</u> (3) <u>3</u> (4) <u>4</u> (5) <u>5</u> (6) <u>6</u> (7) <u>7</u>						
	DATA CHANNEL NOS.: <u>1-96</u> (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: <u>SPS</u> <u>SPS</u> <u>STR</u>						
PARAMETER	RECORD LENGTH: <u>4</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> TRIP	FILTERS: FREQ <u>8</u> LO CUT HZ SLOPE <u>18</u>	HI CUT HZ SLOPE <u>22</u>	NOISE FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT				
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> XGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>36</u> db	TRIP SENS: <u>18</u> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY				
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM. ALT SW. _____			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>SINGLE Hole</u>	NO. OF POSITIONS: <u>1</u>	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ HOLE: <u>110</u>	HOLE DEPTH: <u>105</u>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____		
RECEIVER	TYPE: <u>GSE 200</u>		PATTERN: <u>INLINE</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>18</u>		LATERAL SPACING: _____		LATERAL OFFSET: _____	
	CONNECTION: <u>2 (313)</u>		RESISTANCE: <u>240</u> ohms	STAGGER: _____	LENGTH: _____		WIDTH: _____		LATERAL OFFSET: _____	
SPREAD	NO. OF GROUPS: <u>18</u>		GROUP INTERVAL: <u>220</u>	SHOTPOINT INTERVAL: <u>880</u>	FOLD: <u>12</u>		DIRECTION OF PROGRESSION: <u>EAST</u>			
	OFFSET GROUP 1: <u>10450</u>	OFFSET GROUP <u>48</u>	<u>110</u>	OFFSET GROUP <u>49</u> : <u>110</u>	OFFSET GROUP <u>96</u> : <u>10450</u>	LEADING GROUP: <u>1</u>				

DIAGRAMS/MISC. INFORMATION: WAIT ON DRILLS E 110' X 110' 110' 76 X W

26 TRACE TALL SPREAD 10450' 10450'

SHOTPOINT	TR. 1 to 96		TR. to		SHOT		SPREAD		REMARKS	CORR. STACK							
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	#1	LINE GROUPS	#96	SET UP	YR 1-78	YR 41-78
2000	672918	12			110	105					77	2011-4	TS26	12			
2001		13			110	105					67	2012-4	TS26				
2002		14			110	105					63	2013-4	TS26				
2003		15			110	105					59	2014-4	TS26				
2004		16			110	105	40 S				55	2015-4	TS26				
2005		17			110	105					51	2016-4	TS26				
2006		18			110	105					47	2017-4	TS24				
2007		19			110	105	38 W				43	2018-4	TS20				
2008																	
2009		20			110	105	20 E				35	2020-4	TS12				
2010		21			110	105	28 W				31	2021-4	TS8				
2011					110	105					27	2022-4	TS4				

LAND SEISMIC RECORDING LOG

11

		CLIENT Husky	PROSPECT: DRIFTWOOD	AREA: NPR-A ALASKA	LINE NO: 85X		
PARTY NO: 1186		INST. ENG: TERRY REID		DATE: MO 3 DAY 4 YR 78			
INSTRUMENT [9-TRACK]	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: SEG B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED
	NO. BYTES IN HEADER REC: 128	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA (1) (2) (3) (4) (5) (7)			
	DATA CHANNEL NOS.: 1-96 [ON MAG TAPE]			AUXILIARY CHANNEL NOS.: SPS SPS SPS			
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input checked="" type="checkbox"/> FINAL	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 12 NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	JIP SENS: 18 db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE } NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	P.C.U. NORM./ALT SW.
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH: WIDTH: LATERAL OFFSET:
		CHG/ HOLE: 160	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER: PHASE COMP:
RECEIVER	TYPE: G.S.C 20D	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 18	LATERAL SPACING:	STAGGER:	LENGTH: WIDTH: LATERAL OFFSET:
	CONNECTION: 2 (3+3)	RESISTANCE: 240 ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 880	FOLD: 12	DIRECTION OF PROGRESSION: EAST	LEADING GROUP: 1	
	OFFSET GROUP 1: 10450	OFFSET GROUP 2: 110	OFFSET GROUP 3: 110	OFFSET GROUP 4: 10450	LEADING GROUP:		

DIAGRAMS/MISC. INFORMATION: **TR#1** **48 77 47** **96**

SHOTPOINT	TR 1-96		TR 10		SHOT					SPREAD				REMARKS	CORR. STACK			
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#1	LINE GROUPS	SP		IP	TR 1-48	TR 48-96	
2012	672918	26			110	105				45	2022-4	75-4	20	16	F# 22 -> 25 TR#75			
2012		27			100	105				41	2023-4	2000-1			TR#1 DEAD			
2013		28			NR	105				37	2024-4	2001-1						
2014		29			NR	105				33	2025-4	2002-1						
2015		30			NR	105				29	2026-4	2003-1						
2016		31			NR	105		40 W		25	2027-4	2004-1						
	TR#2 CHANGE																	
2017	672919	33			NR	105				21	2028-4	2005-1						
2018		32			NR	105				17	2029-4	2006-1			F# 34 MISSFIRE			
2018		26			NR	105				13	2030-4	2007-1						
2020		37			NR	105				9	2031-4	2008-1						
2021		38			NR	105				5	2032-4	2009-1						
2022		39			NR	105				1	2033-4	2010-1						
2023		40			160	105		165 W		45	2034-4	2011-1	2029		122 160" CHEESE			
2024		41			160	105				41	2035-4	2012-1						
2025		42			160	105		45 S		37	2036-4	2013-1						
2026		43			160	105				45	2037-4	2014-1	2031		TR#91 DEAD			
2027		44			160	105				41	2038-4	2015-1			" 95 "			
2028		45			160	105				37	2039-4	2016-1			" 99 "			
2029		46			160	105				33	2040-4	2017-1			TR 93 DEAD			

LAND SEISMIC RECORDING LOG

3



	CLIENT: Husky	PROSPECT: BRIET WOOD	AREA: NPR-A ALASKA	LINE NO: 85x					
	PARTY NO: 1186	INST. ENG: REID		DATE: MO 3 DAY 1 YR 78					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: _____ SEG: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ [ON MAG TAPE]			AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	NO. OF ELEMENTS: _____	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	OFFSET GROUP: _____	FOLD: _____	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: LEADING GROUP: _____		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 16		TR 17 to 32		SHOT		SPREAD		REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH	LINE GROUPS		TR 1-16	TR 17-32
2030	67A919	47			160	105					29	2048-4	2088-1		
2031		48			160	105					25	2042-4	2019-1		
2032		49			160	105					21	2043-4	2020-1		
2033		50			160	105					17	2044-4	2021-1		
2034		51			160	105					15	2045-4	2022-1		
TAPES CHANGE															
2035		53			160	105					9	2046-4	2023-1		
2036		54			160	105					5	2047-4	2024-1		
2037		55			160	105					1	2048-4	2025-1		

LAND SEISMIC RECORDING LOG

4

	CLIENT: Husky	PROSPECT: DRIFT WOOD	AREA: NPR-A ALASKA	LINE NO: 85 X	
PARTY NO: 1186		INST. ENG: FEID		DATE: MO 3 DAY 5 YR 78	

INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 2 DFS V <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 2 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: B SELG	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 400 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI	
[9-TRACK]	NO. BYTES IN HEADER REC: 178	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 254	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms				

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	AUXILIARY DATA: (1) 1 (2) 2 (3) 3 (4) 4 (5) 5 (6) 6 (7) 7
	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)	AUXILIARY CHANNEL NOS.: 575 575 578

PARAMETER	RECORD LENGTH: 7 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TRIP <input type="checkbox"/> OPERATE	FILTERS: FREQ 8 LO CUT HZ 18 HI CUT HZ 72	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS.: 18 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> ON MAG TAPE <input type="checkbox"/> UPBREAK
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	CORR. SCALING: _____ R.C.U. NORM./ALT SW.

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CHG/ HOLE: 160 HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	

RECEIVER	TYPE: GSC 20 D	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 18	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: 2 (3A3)	RESISTANCE: 240 ohms							



SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 880	FOLD: 12	DIRECTION OF PROGRESSION: EAST
	OFFSET GROUP 1: 10450	OFFSET GROUP 98 : 110	OFFSET GROUP 99 : 110	OFFSET GROUP 96 : 10450	LEADING GROUP: 1


DIAGRAMS/MISC. INFORMATION: **E 78** **48 78** **49 78** **96** **W**

SHOTPOINT	TR. 1 to 96		TR. to		SHOT		SPREAD		REMARKS:	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH	LINE GROUPS	SET UP	TR 1-41
2038	622920	166			160	105				45	2049-4	2041-1		
2039		167			160	105				41	2050-4	2042-1		
2040		168			160	105	40	5		37	2051-4	2043-1		
2041		169			160	105				33	2052-4	2044-1		
2042		170			160	105				29	2053-4	2045-1		
2043		171			160	105				25	2054-4	2046-1		
2044		172			160	105				21	2055-4	2047-1		
2045		173			160	105				17	2056-4	2048-1		
2046		174			160	105				13	2057-4	2049-1		
2047		175			160	105				9	2058-4	2050-1		
2048		176			160	105				5	2059-4	2051-1		
2049		177			160	105				1	2060-4	2052-1		
2050		178			160	105				45	2061-4	2053-1		
2051		179			160	105				41	2062-4	2054-1		
2052	622922	181			160	105				37	2063-4	2055-1		FILE # 90 DUMMY
2053		182			160	105				33	2064-4	2056-1		
2054		183			160	105				29	2065-4	2057-1		
2055		184			160	105				25	2066-4	2058-1		
2056		185			160	105				21	2067-4	2059-1		
2057		186			160	105				17	2068-4	2060-1		

LAND SEISMIC RECORDING LOG

5

	CLIENT: HUSKY	PROSPECT: DRIFTWOOD	AREA: NPR-A ALASKA	LINE NO: 85X					
	PARTY NO: 1186	INST. ENG: TERRY		DATE: MO 3 DAY 5 YR 78					
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> OPS III <input checked="" type="checkbox"/> OPS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	POP MAT: B	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1000 BPI	
(9-TRACK)	NO. BYTES IN HEADER REC: 128	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____			AUXILIARY CHANNEL NOS.: SPT SPT SIB		
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 7 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL	FILTERS: FREQ _____	LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 72	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	JRIP SENS: 18 db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____	DOWNBREAK ON DISPLAY: <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW: _____		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG/ HOLE: 160	HOLE DEPTH: 105	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
RECEIVER	TYPE: GSC 20 D	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 18	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: 2 (8x8)	RESISTANCE: 240 ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 880	FOLD: 12	DIRECTION OF PROGRESSION: EAST	LEADING GROUP: 1			
	OFFSET GROUP 1: 10450	OFFSET GROUP 48: 110	OFFSET GROUP 49: 110	OFFSET GROUP 48/96: 10450					



SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT		SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	SET UP	TR 1-48
2061	6129	22	17	22	23	26	27	29	30	32	35	37		
2069											13	2069-4	2046-1	2055
2060											9	2070-4	2047-1	
2061											5	2071-4	2048-1	
2062											1	2072-4	2049-1	
2062											45	2073-4	2050-1	2067
2063											41	2074-4	2051-1	
2064											37	2075-4	2052-1	
2065											38	2076-4	2053-1	

LAND SEISMIC RECORDING LOG



	CLIENT: HUSKY	PROSPECT: DRIFTWOOD	AREA: NPR-A ALASKA	LINE NO.: 6					
	PARTY NO.: 1186	INST. ENG.: TERRY		DATE: MO 3 DAY 9 YR 78					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: SEG 8	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (H1) <input type="checkbox"/> 712 BPI (H2) <input type="checkbox"/> 800 BPI (H3) <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: 128	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: (1) 1 (2) 2 (3) 3 (4) 4 (5) _____ (6) _____ (7) _____					
	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: SP5 SP5 STB					
PARAMETER	RECORD LENGTH: Y sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 1/4 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input checked="" type="checkbox"/> TRF	FILTERS: FREQ. Y LO CUT HZ SLOPE 1Y	HI CUT HZ SLOPE 1Y	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS.: 1Y db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/>	NUMBERS ON MAG TAPE: <input type="checkbox"/>	DOWNBREAK UPBREAK: <input type="checkbox"/>	ON DISPLAY: <input type="checkbox"/>	
CFS I	TYPE: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM / ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG/ HOLE: 160	HOLE DEPTH: 105	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
RECEIVER	TYPE: GSC-20D	PATTERN: INLINE	NO. OF ELEMENTS: 1Y	INLINE SPACING: 1Y	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: 2 (3x3)	RESISTANCE: 240 ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 870	FOLD: 12	DIRECTION OF PROGRESSION: EAST				
	OFFSET GROUP 1: 10460	OFFSET GROUP 48 : 110	OFFSET GROUP 49 : 110	OFFSET GROUP 48/96: 10450	LEADING GROUP: 1				




SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT			SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET DIR	CDP SWITCH	LINE GROUPS	SET UP		TR 1-24	TR 25-48	TR 49-96	TR 100-120
2065	622922	105			510	105		33	2076-4	2053-1	VOID EV. 9# FILE 95-104 DAILY TEST				
2066		1106			160	105		29	2077-4	2054-1					
2067		1107			160	105		25	2078-4	2055-1					
2068		1108			160	105		21	2079-4	2056-1					
2069	622923	110			160	105		17	2080-4	2057-1	FILE 109 DUMMY				
2070		1111			160	105		13	2081-4	2058-1					
2071		1112			160	105		9	2082-4	2059-1					
2072		1113			160	105	145 W	5	2083-4	2060-1					
2073		1115			160	105	230 E	49	2084-4	2061-1	VOID FILE # 114				
2074		1116			160	105	210 S	45	2085-4	2062-1					
2075		1117			160	105	38 W	41	2086-4	2063-1					
2076		1118			160	105		37	2087-4	2064-1					
2077		1119			160	105	135 N	33	2088-4	2065-1					
2078		1120			160	105	175 N	29	2089-4	2066-1					
2079		1121			160	105		25	2090-4	2067-1					
2080		1122			160	105		21	2091-4	2068-1					
2081		1123			160	105		17	2092-4	2069-1					
2082		1124			160	105	55 N	13	2093-4	2070-1					
2083		1125			160	105	175 W	9	2094-4	2071-1					
2084		1126			160	105	215 W	5	2095-4	2072-1					

LAND SEISMIC RECORDING LOG



7

	CLIENT: HUSKY	PROSPECT: DRIFTWOOD	AREA: UPR-A ALASKA	LINE NO.: PSV					
PARTY NO.:		INST. ENG.:		DATE: MO 3 DAY 9 YR 28					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 48 & 49-96	<input type="checkbox"/> ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI	
	NO BYTES IN HEADER REC.:	128	NO BYTES IN RECORD ID:	NO BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)			AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (7) _____	AUXILIARY CHANNEL NOS.: SP5 0 SP5 0TB			
PARAMETER	RECORD LENGTH: Y	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL	MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	FREQ. _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS: 18 db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: GSC-20D	PATTERN: INLINE	RESISTANCE: 240 ohms	NO. OF ELEMENTS: 18	STAGGER: _____	INLINE SPACING: 18	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	CONNECTION: 2(3x3)	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 880	FOLD: 12	DIRECTION OF PROGRESSION: E	OFFSET GROUP 48/96: 10450	LEADING GROUP: 1		





SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		COP SWITCH	LINE GROUPS	SET UP	TR 1-48
2085	622923	127			160	105			1	2096-4 2073-1			
2086		128			160	105			45	2097-4 2074-1			
2087	622924	130			160	105		20 W	41	2098-4 2075-1			FILE # 129 DUMMY
2088		131			160	105			37	2099-4 2076-1			
2089		132			160	105			33	2100-4 2077-1			
2090		133			160	105			29	2101-4 2078-1			HOLE BLEW ON SIP 2090
2091		134			160	105			25	2102-4 2079-1			
2092		135			160	105			21	2103-4 2080-1			
2093		136			160	105			17	2104-4 2081-1			
2094		137			160	105			13	2105-4 2082-1			
2095		138			160	105			9	2106-4 2083-1			
2096		139			160	105			5	2107-4 2084-1			
2097		140			160	105		30 W	1	2108-4 2085-1			

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: DRIFT WOOD	AREA: NPRA ALASKA	LINE NO: 854						
PARTY NO:		INST. ENG:		DATE: MO 3 DAY 10 YR 75						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	POP MAT: B	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: 128	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (7) _____						
	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: SP5 SP5 STB						
PARAMETER	RECORD LENGTH: Y	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TRF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 1X HI CUT HZ SLOPE 22 NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT						
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> BAGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	JRIP SENS: 18 db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE. <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE HOLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: 160	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.		
RECEIVER	TYPE: GSC-20 D	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 18	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	CONNECTION: 2 (3X3)	RESISTANCE: 240 ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
DIAGRAMS/MISC. INFORMATION:	NO. OF GROUPS: 96	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: PRD	FOLD: 12	DIRECTION OF PROGRESSION: E.					
	OFFSET GROUP 1: 10450	OFFSET GROUP 41: 110	OFFSET GROUP 42: 110	OFFSET GROUP 48/96: 10450	LEADING GROUP: 1					

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT					SPREAD			REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			LET UP	TR 1-24	TR 25-48	TR 49-72	TR 73-96
21098	622924	144			160	105	1				45	2109-4	2096-1	2103	FILE # 141-143 DAILY TEST			
21099		145			160	105					41	2110-4	2097-1					
21100		146			160	105					37	2111-4	2098-1					
21101		147			160	105					33	2112-4	2099-1					
21102		148			160	105		120 W			29	2113-4	2090-1					
21103		149			160	105					25	2114-4	2090-1					
21104	622925	151			110	105					21	2115-4	2092-1		FILE # 150 DUMMY			
21105		152			110	105					17	2116-4	2093-1					
21106		153			160	105					13	2117-4	2094-1					
21107		154			110	105					9	2118-4	2095-1					
21108		155			110	105					5	2119-4	2096-1					
21109		156			110	105					1	2120-4	2097-1					
21110		157			110	105					45	2121-4	2098-1	2115				
21111		158			110	105					41	2122-4	2098-1					
21112		159			110	105					37	2123-4	2099-1					
21113		160			110	105					33	2124-4	2100-1					
21114		161			110	105					29	2125-4	2101-1					
21115		162			110	105					25	2126-4	2102-1					
21116		163			110	105					21	2127-4	2103-1					
21117		164			110	105		20.5			17	2128-4	2104-1					

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: DRIFTWOOD	AREA: NPR-A ALASKA	LINE NO: 9	
PARTY NO: 1186		INST. ENG: TERRY		DATE: MO 3 DAY 10 YR 72	


INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS & EVENS <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	FORMAT: _____ SEG _____ <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1000 BPI
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:		NO. BYTES PER SCAN:		GAIN CONSTANT: (1) (2) (3) (4) (5) (6) (7)
PARAMETER		NO. BYTES IN RECORD ID:		AUXILIARY DATA:	
DISPLAY		NO. BYTES IN RECORD ID:		AUXILIARY CHANNEL NOS.:	
CFS I		NO. BYTES IN RECORD ID:		AUXILIARY CHANNEL NOS.:	
SOURCE		NO. BYTES IN RECORD ID:		AUXILIARY CHANNEL NOS.:	
RECEIVER		NO. BYTES IN RECORD ID:		AUXILIARY CHANNEL NOS.:	
SPREAD		NO. BYTES IN RECORD ID:		AUXILIARY CHANNEL NOS.:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____				SHOT					SPREAD			REMARKS	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			REV	HT.	REC.	HT.	REC.
21113	12/13	165	17	22/23	26/27	29/30	32	35	37		13	2129-4	2105-1	2115				
21119		166			110	105					9	2130-4	2102-1					
21210		167			110	105					5	2131-4	2108-1					



LAND SEISMIC RECORDING LOG

		CLIENT: HUSKY	PROSPECT: DRIFTWOOD	AREA: NPRA ALASKA	LINE NO: 10					
PARTY NO: 1186		INST. ENG: TERRY		DATE: MO 4 DAY 2 YR 28						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI	
	NO. BYTES IN HEADER REC: 128	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____						
	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: 5P5 5P6 5P8						
PARAMETER	RECORD LENGTH: 8	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OFF <input type="checkbox"/> OPERATE	FILTERS: FREQ. Y LO CUT HZ SLOPE 1X	HI CUT HZ SLOPE 22	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT				
DISPLAY	MODE: <input checked="" type="checkbox"/> PAGE <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> DIRECT	TRIP SENS: 18 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON DISPLAY				
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	P.C.U. NORM./ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
	CHG/ MOLE: 110	MOLE DEPTH: 105	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____		
RECEIVER	TYPE: GSC-20D	PATTERN: 1/1 LINE	NO. OF ELEMENTS: 18	INLINE SPACING: 18	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
	CONNECTION: 2 (3x8)	RESISTANCE: 240 ohms	STAGGER: _____							
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 880	FOLD: 12	DIRECTION OF PROGRESSION: E	LEADING GROUP: 1				
	OFFSET GROUP 1: 10450	OFFSET GROUP: 110	OFFSET GROUP: 110	OFFSET GROUP 48/96: 10450						



SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT				SPREAD		REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH		LINE GROUPS	TR 1-48	TR 49-96	TR 1-48	TR 49-96
21121	6222	107			110	105				49	2132-4	2109-1				
21122		108			110	105				45	2133-4	2110-1				
21123		109			110	105				41	2134-4	2111-1				
21124		181			110	105				37	2135-4	2112-1				
21125		182			110	105				33	2136-4	2113-1				
21126		183			110	105				29	2137-4	2114-1				
21127		184			110	105		35W		25	2138-4	2115-1				
21128		185			110	105				21	2139-4	2116-1				
21129		186			110	105				17	2140-4	2117-1				
21130		187			110	105				13	2141-4	2118-1				
21131		188			110	105				9	2142-4	2119-1				
21132		189			110	105				5	2143-4	2120-1				
21133		190			110	105				1	2144-4	2121-1				

LAND SEISMIC RECORDING LOG



	CLIENT: HUSKY	PROSPECT: DRIETWOOD	AREA: NPR-A ALASKA	LINE NO: 11					
	PARTY NO:	INST. ENG:		DATE: MO 4 DAY 19 YR 78					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG B	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(M) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC: 128	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC. 0001	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____	AUXILIARY CHANNEL NOS.: SP5 OP5 OTB						
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 24 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TRF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ 8 LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 22 NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT				
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 42 db	TRIP SENS: 18 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY				
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD: _____				
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:				
	CHG/ HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:				
RECEIVER	TYPE: GSC-20D	PATTERN: SINGLE HOLE	NO. OF ELEMENTS: 18	INLINE SPACING: 18	LATERAL SPACING:				
	CONNECTION: 2(3X3)	RESISTANCE: 240 ohms	STAGGER:	LENGTH:	WIDTH:				
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 880	FOLD: 12	DIRECTION OF PROGRESSION: E.				
	OFFSET GROUP 1: 10450	OFFSET GROUP: 110	OFFSET GROUP: 110	OFFSET GROUP 48/96: 10450	LEADING GROUP: 7				



SHOTPOINT	TR 10		TR 10		SHOT			SPREAD			REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-18	TR 19-36	TR 37-54	TR 55-72
11134	4229164				110	105	1			45	2145-4	2122-1				
<p>WEATHER DAY</p> <p>NO PRODUCTION</p>																
<p>VOID FILE # 191 DAILY TEST FILE 192-195</p> <p>4-9-78 DAILY TEST</p> <p>FILE # 196-205</p>																

LAND SEISMIC RECORDING LOG

12

	CLIENT: HUSKY	PROSPECT: DRIFTWOOD	AREA: NPRA ALASKA	LINE NO: 85X	
	PARTY NO:	INST. ENG:		DATE: MO 4 DAY 9 YR 20	

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FOPMAT: B SEG	GAPPED <input type="checkbox"/> UNGAPPED <input type="checkbox"/>	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI
(9-TRACK)	NO. BYTES IN HEADER REC: 128	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: ohms		

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96 DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)	AUXILIARY DATA: (1) 1 (2) 2 (3) 3 (4) 4 (5) 5 (6) 6 (7) 7 AUXILIARY CHANNEL NOS.: SP5 SP5 SP5	
PARAMETER	RECORD LENGTH: 7 sec. SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input checked="" type="checkbox"/> OFF <input type="checkbox"/> FINAL	FILTERS: FREQ: 8 LO CUT HZ SLOPE: 18 HI CUT HZ SLOPE: 22 NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 42 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE } NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	NOISE REDUCTION: <input type="checkbox"/> CORR. SCALING: <input type="checkbox"/> R.C.U. NORM./ALT SW.

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: 110 HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:		

RECEIVER	TYPE: GSC-20D	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 18	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: 2 (3x3)	RESISTANCE: 240 ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			

SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 770	FOLD: 12	DIRECTION OF PROGRESSION: EAST
	OFFSET GROUP 1: 10450	OFFSET GROUP: 110	OFFSET GROUP: 110	OFFSET GROUP 48/96: 10450	LEADING GROUP: 1





SHOTPOINT	TR		TR		SHOT				SPREAD			REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 1-48	TR 48-96
2134	6229165	207			110	105				45	2145-4	2132-1		
2135		208			110	105				41	2146-4	2125-1		
2136		209			110	105				37	2147-4	2124-1		
2137		210			110	105				33	2148-4	2125-1		
2138		211			110	105				29	2149-4	2126-1		
2139		212			110	105				25	2150-4	2127-1		
2140		213			110	105				21	2151-4	2128-1		
2141		214			110	105				17	2152-4	2129-1		
2142		215			110	105				13	2153-4	2130-1		
2143		216			110	105				9	2154-4	2131-1		
2144		217			110	105				5	2155-4	2132-1		
2145		218			110	105				1	2156-4	2133-1		
2146		219			110	105				45	2157-4	2134-1		
2147		220			110	105				41	2158-4	2135-1		
2148		221			110	105				37	2159-4	2136-1		
2149		222			110	105				33	2160-4	2137-1		
2150		223			110	105				29	2161-4	2138-1		
2151		224			110	105				25	2162-4	2139-1		
2152		225			110	105				21	2163-4	2140-1		
2153	6229166	226			110	105				17	2164-4	2141-1		

VOID FILE # 227
FILE # 226 DUMMY

LAND SEISMIC RECORDING LOG

13

	CLIENT: <u>HUSKY</u>	PROSPECT: <u>DRIFT WOOD</u>	AREA: <u>NPR-A ALASKA</u>	LINE NO: <u>85X</u>	
	PARTY NO: <u>1186</u>	INST. ENG: <u>TERRY</u>		DATE: <u>MO 4 DAY 9 YR 28</u>	



INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: _____ SEG: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 386 BPI <input type="checkbox"/> 800 BPI	(H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI				
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1)	(2)	(3)	(4)	(5)	(6)	(7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.: _____						
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	<input type="checkbox"/> IFF <input type="checkbox"/> FINAL	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOISE FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____	DOWNBREAK UPBREAK: <input type="checkbox"/> ON DISPLAY						
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM. ALT SW. _____						
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____				
RECEIVER	CONNECTION: _____	PATTERN: _____	RESISTANCE: _____ ohms	NO. OF ELEMENTS: _____	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____				
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	OFFSET GROUP: _____	OFFSET GROUP: _____	FOLD: _____	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: _____		LEADING GROUP: _____			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT				SPREAD		REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH		LINE GROUPS	SET UP	TR 48	TR 96	TR 48	TR 96
2154	622966	229			110	105	110	10	N	13	2165-4	2142-1					
2155		230			110	105				9	2166-4	2143-1					
2156		231			110	105				5	2167-4	2144-1					
2157		232			110	105				49	2168-4	2145-1	HOLE BLEW OUT ON SIP 2157				
2158		233			110	105				45	2169-4	2146-1					
2159		234			110	105				41	2170-4	2147-1					
2160		235			110	105				37	2071-4	2148-1					
2161		236			110	105				33	2072-4	2149-1					
2162		237			110	105				29	2073-4	2150-1					
2163					110	105				25	2074-4	2151-1					

LAND SEISMIC RECORDING LOG

14

	CLIENT: HUSKY	PROSPECT: DRIFT WOOD	AREA: NPR-A ALASKA	LINE NO.: 75X	
PARTY NO:		INST. ENG.:		DATE: NO 4 DAY 10 VR 78	

INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 24 & 25-48 <input checked="" type="checkbox"/> 48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FOP MAT: 8 SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 900 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI	
(9-TRACK)	NO BYTES IN HEADER REC: 128	NO BYTES IN RECORD ID:	NO BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: L-96				AUXILIARY DATA:						
	DATA CHANNEL NOS.: 1-96				AUXILIARY CHANNEL NOS.: 325 2 3 4 525 078						
PARAMETER	RECORD LENGTH: 3 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. f LO CUT HZ SLOPE 18		FREQ. 128 HI CUT HZ SLOPE 22		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 42 db	TRIP SENS.: 18 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.				
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
		CHG./HOLE: 110 HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.			
RECEIVER	TYPE: GSC-20D	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 18		LATERAL SPACING:		LATERAL OFFSET:			
	CONNECTION: 2 (3x3)	RESISTANCE: 240 ohms	STAGGER:	LENGTH: 18		WIDTH:		LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 880	FOLD: 12		DIRECTION OF PROGRESSION: EAST		LEADING GROUP: 1			
	OFFSET GROUP 1: 10450	OFFSET GROUP: 110	OFFSET GROUP: 110	OFFSET GROUP 48/96: 10450		LEADING GROUP: 1					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT				SPREAD			REMARKS	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SEY	TR 1-48	TR 48-96	REC.	REC.		
21163	6729166	243			110	105				25	2074-4	2151-1	2163						
21164		244			110	105				21	2125-4	2152-1							
21165		245			110	105				17	2126-4	2153-1							
21166		246			110	105				13	2127-4	2154-1							
21167		247			110	105		1200 E.		9	2128-4	2155-1							
21168	6729167	249			110	105		1145 E.		5	2129-4	2156-1							
21169		250			110	105				1	2130-4	2157-1							
21170		251			110	105				45	2131-4	2158-1	2175						
21171		252			110	105		900 N		41	2132-4	2159-1							
21172		253			110	105				37	2133-4	2160-1							
21173		254			110	105				33	2134-4	2161-1							
21174		255			110	105				29	2135-4	2162-1							
21175		256			110	105				25	2136-4	2163-1							
21176		257			110	105				21	2137-4	2164-1							
21177		258			110	105		810 E		17	2138-4	2165-1							
21178		259			110	105				13	2139-4	2166-1							
21179		260			110	105				9	2140-4	2167-1							
21180		261			110	105				5	2141-4	2168-1							
21181		262			110	105				49	2142-4	2169-1	2187						
21182		263			110	105		150 E		45	2143-4	2170-1							

LAND SEISMIC RECORDING LOG

	CLIENT: <u>HUSKY</u>	PROSPECT: <u>DRIFTWOOD</u>	AREA: <u>UPRA ALASKA</u>	15 LINE NO: <u>Y5X</u>
	PARTY NO: <u>1186</u>	INST. ENG: <u>TERRY</u>		DATE: <u>MO 4 DAY 10 YR 78</u>
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS & EVENS <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS X <input type="checkbox"/> 9 TRACK <input type="checkbox"/> FOPMAT: _____ <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER _____ <input type="checkbox"/> 21 TRACK <input type="checkbox"/> SEG		<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT GAIN CONSTANT: _____ db INPUT IMPEDANCE: _____ ohms AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)			
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> _____ ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	FILTRES: FREQ _____ LO CUT HZ SLOPE _____ HI CUT HZ SLOPE _____	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
		RECORD REJECTION: _____	POLARITY CONVENTION: _____ NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIRROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____
		CHG/HOLE: _____	SWEEP POSITION: _____	LATERAL SPACING: _____
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____
	CONNECTION: _____	RESISTANCE: _____	STAGGER: _____	LENGTH: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____
	OFFSET GROUP 1: _____	OFFSET GROUP: _____	OFFSET GROUP: _____	WIDTH: _____
DIAGRAMS/MISC. INFORMATION:				LATERAL OFFSET: _____

SHOTPOINT	TR _____ TO _____		TR _____ TO _____				SHOT					SPREAD			REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH	LINE GROUPS		SECT	TR 1-48		TR 48-96	
2183	67296	264			110	105	35			41	2194-4	2171-1	218				
2184		265			110	105				37	2195-4	2172-1					
2185		266			110	105				33	2196-4	2173-1					
2186		267			110	105				29	2197-4	2174-1					
2187		270			110	105				25	2198-4	2175-1					
2188		271			110	105				21	2199-4	2176-1					
2189					170	105				27	2200-4	2177-1					

FILE # 268 DUMMY - VOID FILE # 218

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: ORIENT WOOD	AREA: NPR-A ALASKA	LINE NO: 16						
	PARTY NO: 1186	INST. ENG: TERRY		DATE: Y5X						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> -24 & 25-48 <input checked="" type="checkbox"/> -48 & 49-96	<input type="checkbox"/> ODS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 2-1000 BPI	
	NO. BYTES IN HEADER REC: 128	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: (1) 1 (2) 2 (3) 3 (4) 4 (5) _____ (6) _____ (7) _____						
	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: SP5 SP5 SPB						
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 1 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____ HZ	HZ SLOPE _____	HI CUT _____ HZ	HZ SLOPE _____	
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT	<input type="checkbox"/> DIRECT	INITIAL GAIN: 42 db	TRIP SENS: 15 db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW. _____			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
	CHG/ HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____		
RECEIVER	TYPE: GSC-200	PATTERN: INLINE	NO. OF ELEMENTS: 15	INLINE SPACING: 15	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
	CONNECTION: 2(3X3)	RESISTANCE: 240 ohms								
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 580	FOLD: 12	DIRECTION OF PROGRESSION: EAST	OFFSET GROUP 1: 10450	OFFSET GROUP 48/96: 10450	LEADING GROUP: 1		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT			SPREAD			REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-24 REC.
21897	622969	287			110	105			47	2200-4	2197-1		
21898		288			110	105			43	2201-4	2198-1		
21899		289			110	105	125 E.		39	2202-4	2199-1		
21900		290			110	105			35	2203-4	2190-1		
21901		291			110	105	140 W.		31	2204-4	2191-1		
21902		292			110	105	1140 E.		27	2205-4	2192-1		
21903		293			110	105	1100 E.		47	2206-4	2193-1	2200	
21904		294			110	105			43	2207-4	2194-1		
21905		295			110	105			39	2208-4	2195-1		
21906		296			110	105	140 E.		35	2209-4	2196-1		
21907		297			110	105	140 E.		31	2210-4	2197-1	TR# 94 DEAD	
21908		298			110	105			27	2211-4	2198-1		
21909		299			110	105			23	2212-4	2199-1		
21910		300			110	105			19	2213-4	2190-1		
22003		296			110	105			15	2214-4	2191-1		
22004	622969				110	150			11	2215-4	2192-1	FILE# 297 DUMMY	
22005		297			110	105			7	2216-4	2193-1	S/P 2214 DRILLED TO 150 FT.	
22006		298			110	105			3	2217-4	2194-1	MISS-FIRE ON S/P 2204 NO SHOT	
22007		300			110	105			47	2218-4	2195-1		
22008		301			110	105			43	2219-4	2196-1		

LAND SEISMIC RECORDING LOG

17

	CLIENT: HUSKY	PROSPECT: DRIEFT WOOD	AREA: NPR-A ALASKA	LINE NO: 75X	
	PARTY NO: 1186	INST. ENG: TERRY		DATE: MO 4 DAY 11 YR 78	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS <input type="checkbox"/> TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> 9 TRACK <input type="checkbox"/> GAPPED <input type="checkbox"/> PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 712 BPI <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> EVENS <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER <input type="checkbox"/> 21 TRACK <input type="checkbox"/> UNGAPPED (HI) <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI			
	NO. BYTES IN HEADER REC: NO. BYTES IN RECORD ID: NO. BYTES PER SCAN: RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT GAIN CONSTANT: db INPUT IMPEDANCE: ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: DATA CHANNEL NOS.: (ON MAG TAPE)		AUXILIARY DATA:	AUXILIARY CHANNEL NOS.:
PARAMETER	RECORD LENGTH: sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: LO CUT HZ SLOPE HI CUT HZ SLOPE NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: db	TRIP SENS: db	POLARITY CONVENTION: PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION: NOISE THRESHOLD: CORR. SCALING: R.C.U. NORM./ALT SW.
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: CHG/ HOLE:	NO. OF POSITIONS: SWEEP POSITION: SWEEP START:	INLINE SPACING: SWEEP END: SWEEP LENGTH: SWEEP TAPER: STAGGER: LENGTH: WIDTH: PHASE COMP:
RECEIVER	TYPE: CONNECTION:	PATTERN: RESISTANCE: ohms	NO. OF ELEMENTS: STAGGER:	INLINE SPACING: LENGTH: WIDTH: LATERAL OFFSET:
SPREAD	NO. OF GROUPS: OFFSET GROUP 1:	GROUP INTERVAL: OFFSET GROUP:	SHOTPOINT INTERVAL: OFFSET GROUP:	FOLD: DIRECTION OF PROGRESSION: LEADING GROUP:

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR				SHOT					SPREAD			REMARKS	CORR. STAGE				
	TR		TR		SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			SET ID	TR 1-48		TR 49-96	
	REEL NO.	REC.	REEL NO.	REC.							REC.	REC.			REC.	REC.	REC.	REC.
2209	6229-16	802			110	105		110	E	39	2220-4	2197-1	2212					
2210		803			110	105				35	2221-4	2198-1						
2211		804			110	105				31	2222-4	2199-1						
2212		805			110	105				27	2223-4	2200-1						
2213		806			110	105				23	2224-4	2201-1						
2214		807			110	105				19	2225-4	2202-1						
2215		808			110	105				15	2226-4	2203-1						
2216		809			110	105				11	2227-4	2204-1						

END OF LINE