

# LAND SEISMIC RECORDING LOG

		CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>North Slope - Alaska</b>	LINE NO: <b>B-15</b>		
PARTY NO: <b>1182</b>		INST. ENG: <b>Lenny Windham</b>			DATE: <b>MO 3 DAY 27 YR 78</b>		
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM	<input checked="" type="checkbox"/> 1-24 & 25-48	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK	FORMAT: <b>B</b>	<input checked="" type="checkbox"/> GAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI
	<input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-48 & 49-96		<input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input type="checkbox"/> 21 TRACK	SEG <b>B</b>	<input type="checkbox"/> UNGAPPED
CONFIGURATION (MAG TAPE)	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms.	
PARAMETER	FIELD TRACE NOS.: <b>1-48</b>	(ON MAG TAPE)		AUXILIARY DATA:			
DISPLAY	DATA CHANNEL NOS.: <b>1-48</b>	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms	GAIN MODE: <input checked="" type="checkbox"/> ITP <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FREQ: <b>8</b>	LO CUT HZ SLOPE: <b>18</b>	FREQ <b>128</b>	HI CUT HZ SLOPE: <b>70</b>
CFS I	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>12</b> db	TRIP SENS: _____ ds	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
SOURCE	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW. _____
RECEIVER	TYPE: <b>R5C-20d</b>	PATTERN: <b>Single-hole-Inline</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____
SPREAD	CONNECTION: <b>Series-Parallel</b>	RESISTANCE: _____ ohms	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____
DIAGRAMS/MISC. INFORMATION:	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>880'</b>	OFFSET GROUP 1: <b>5390'</b>	OFFSET GROUP 25: <b>330'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>S to N</b>
NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>880'</b>	OFFSET GROUP 1: <b>5390'</b>	OFFSET GROUP 25: <b>330'</b>	OFFSET GROUP 48/90: <b>5390'</b>	LEADING GROUP: <b>48</b>

T-25
SP1
SP2
SP7
SP8

P ← TRAIL
→ P P P P P
P P P P P ←
→ P P P P P


TRACE # 15
TRACE # 48
TRACE # 25
TRACE # 48

SHOTPOINT	TR. 1 to 48		TR. 10		SHOT					SPREAD			REMARKS:	CORR STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS	SET UP		TR 1-48	TR 48-96
11	751711	60164			20	16731				24	T-25 → 7+1	4		17 10	
2		60165			20	16732				28	T-21 → 8+1			17 20	
2B		60166			20	16733				27	T-20 → 8+2			17 25	
2B		60167			20	16734				30	T-19 → 8+3			17 27	
2C		60168			20	16735				31	T-18 → 8+4			17 30	
File # 6062 & 6063 TEST TA"															

11:10 am Recording time

# LAND SEISMIC RECORDING LOG

CLIENT: <b>Hasky</b>		PROSPECT: <b>NPR-A</b>		AREA: <b>NORTH-SLOPE - ALASKA</b>		LINE NO: <b>B-15</b>			
PARTY NO: <b>1182</b>		INST. ENG: <b>Jerry Windham</b>		DATE: <b>MO 3 DAY 27 YR 78</b>					
INSTRUMENT (9-TRACK)		<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input checked="" type="checkbox"/> DFS III <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK		FOPMAT: <b>B</b> <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT		GAIN CONSTANT: <b>36</b> db	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: <b>1-48</b>		DATA CHANNEL NOS.: <b>1-48</b>		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:	
PARAMETER		RECORD LENGTH: <b>3</b> sec		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE		FILTERS: <b>8</b> LO CUT HZ SLOPE <b>18</b> HI CUT HZ SLOPE <b>70</b> NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>36</b> db		TRIP SENS.: <b>0</b> db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE } NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION: NOISE THRESHOLD: CORR. SCALING: R.C.U. NORM./ALT SW.	
SOURCE		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input checked="" type="checkbox"/> OTHER <b>Air Gun</b>		PATTERN: <b>IN line</b>		NO. OF POSITIONS: <b>1</b>		INLINE SPACING: <b>220'</b>	
RECEIVER		TYPE: <b>GSC-20d</b>		PATTERN: <b>IN line</b>		NO. OF ELEMENTS: <b>18</b>		INLINE SPACING: <b>18'</b>	
SPREAD		NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>220'</b>		FOLD: <b>24</b>	
		OFFSET GROUP 1: <b>5830'</b>		OFFSET GROUP 24: <b>770'</b>		OFFSET GROUP 25: <b>770'</b>		OFFSET GROUP 48/96: <b>5830'</b>	



SHOTPOINT	TR 1 to 48		TR 17 to 24		SHOT		SPREAD		REMARKS	CORR. STACK	
	REEL NO	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR 1-16	TR 17-24
3A	60177	16	60180	17	36	30	30	T-19 → 9+3	4	17 <sup>SE</sup>	
3B	60181	17	60184	18	37	31	31	T-18 → 9+4			
3C	60185	18	60188	19	38	32	32	T-17 → 10+1			
4A	60189	19	60192	20	39	33	33	T-16 → 10+2			
4B	60193	20	60196	21	40	34	34	T-15 → 10+3		18 <sup>LE</sup>	
4C	60197	21	61000	22	41	35	35	T-14 → 10+4			
5A	61101	22	61104	23	42	36	36	T-13 → 11+1			
5B	61105	23	61108	24	43	37	37	T-12 → 11+2			
5C	61109	24	61112	25	44	38	38	T-11 → 11+3		18 <sup>SE</sup>	
6A	61113	25	61116	26	45	39	39	T-10 → 11+4			
6B	61117	26	61120	27	46	40	40	T-9 → 12+1			
6C	61121	27	61124	28	47	41	41	T-8 → 12+2			
7A	61125	28	61128	29	48	42	42	T-7 → 12+3		18 <sup>SE</sup>	
7B	61129	29	61132	30	49	43	43	T-6 → 12+4	6130 N6		
7C	61133	30	61136	31	50	44	44	T-5 → 12+1			
8A	61137	31	61140	32	51	45	45	T-4 → 13+2			
8B	61141	32	61144	33	52	46	46	T-3 → 13+3		18 <sup>SE</sup>	
8C	61145	33	61148	34	53	47	47	T-2 → 13+4			
9A	61149	34	61152	35	54	48	48	T-1 → 14+1			
9B	61153	35	61156	36	55	49	49	T-1 → 14+2			

# LAND SEISMIC RECORDING LOG


	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>North Slope - Alaska</u>	LINE NO: <u>B-15</u>				
	PARTY NO: <u>1182</u>	INST. ENG: <u>Sean Windham</u>		DATE: <u>NO 3 DAY 27 YR 78</u>				
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: _____ ohms	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>			AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: <u>3</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>8</u>	LO CUT HZ SLOPE <u>18</u>	FREQ. <u>128</u>	HI CUT HZ SLOPE <u>70</u>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> TAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>36</u> db	TRIP SENS: <u>0</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	DOWNBREAK UPBREAK	ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input checked="" type="checkbox"/> OTHER <u>Air Gun</u>	PATTERN: <u>Fall line</u>	NO. OF POSITIONS: <u>1</u>	INLINE SPACING: <u>220'</u>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
RECEIVER	TYPE: <u>GSC-20d</u>	PATTERN: <u>In line</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>18'</u>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
SPREAD	CONNECTION: <u>Series-Parallel</u>	RESISTANCE: _____ ohms	STAGGER:	FOLD: <u>24</u>	DIRECTION OF PROGRESSION: <u>5 to N</u>	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.
	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>220'</u>	OFFSET GROUP 1: <u>5830'</u>	OFFSET GROUP 24: <u>770'</u>	OFFSET GROUP 48/96: <u>5830'</u>	LEADING GROUP: <u>48</u>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 16		TR. 17 to 32		SHOT		SPREAD		REMARKS	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH	LINE GROUPS	SP	TR 1-16	TR 17-32	TR 33-48
8A	61157	61157	61160	61160	56	56	50	142	→	1413	4	18 <sup>55</sup>				
8B	61611	61611	6164	6164	57	57	51	143	→	1414						
8C	6165	6165	6168	6168	58	58	52	144	→	1511						
9A	6173	6173	6172	6172	59	59	53	211	→	1512						
9B	6177	6177	6176	6176	60	60	54	212	→	1513						
9C	6181	6181	6184	6184	61	61	55	213	→	1514						
10A	6185	6185	6188	6188	62	62	56	214	→	1611						
10B	6189	6189	6188	6188	63	63	57	311	→	1612						
10C	6189	6189	6192	6192	64	64	58	312	→	1613						19 <sup>30</sup>
10D	6193	6193	6196	6196	65	65	59	313	→	1614						
10E	6197	6197	6200	6200	66	66	60	314	→	1711						
10F	6201	6201	6204	6204	67	67	61	411	→	1712						
10G	6205	6205	6208	6208	68	68	62	412	→	1713	1713 Dead					19 <sup>45</sup>

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPRA</b>	AREA: <b>NORTH SLOPE - ALASKA</b>	LINE NO.: <b>B-15</b>						
	PARTY NO.: <b>1182</b>	INST. ENG.: <b>Lenny Windham</b>		DATE: <b>MO-3 DAY-28 YR-78</b>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM	<input checked="" type="checkbox"/> 1-24 & 25-48	TYPE: <input type="checkbox"/> DFS III	<input checked="" type="checkbox"/> TRACK 1	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI	(HI) <input type="checkbox"/> 712 BPI	<input type="checkbox"/> 1000 BPI
	<input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> DFS II	<input type="checkbox"/> TRACK 2	SEG	<input type="checkbox"/> UNGAPPED				
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC.	<input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>	DATA CHANNEL NOS.: <b>1-48</b>	(ON MAG TAPE)			AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)				
PARAMETER	RECORD LENGTH: <b>3</b> sec	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms	GAIN MODE: <input checked="" type="checkbox"/> GTF	FILTERS: FREQ <b>8</b>		LO CUT HZ SLOPE <b>18</b>	HI CUT HZ SLOPE <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT	<input type="checkbox"/> AMPLIFIER	INITIAL GAIN: <b>36</b> db	JRIP SENS: <b>0</b> db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE	NEGATIVE	NUMBERS ON MAG TAPE		DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE	PATTERN: <b>IN line</b>	NO. OF POSITIONS: <b>1</b>	INLINE SPACING: <b>220'</b>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	TYPE: <b>GSC-20d</b>	PATTERN: <b>IN line</b>	CONNECTION: <b>Series-Parallel</b>	RESISTANCE: _____ ohms	NO. OF ELEMENTS: <b>18</b>	STAGGER:	INLINE SPACING: <b>18'</b>	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>220'</b>	FOLD: <b>24</b>	OFFSET GROUP 1: <b>5830'</b>	OFFSET GROUP 24: <b>770'</b>	OFFSET GROUP 25: <b>770'</b>	OFFSET GROUP 48/96: <b>5830'</b>	DIRECTION OF PROGRESSION: <b>S to N</b>	LEADING GROUP: <b>48</b>



SHOTPOINT	TR. 1 to 10		TR. 11 to 20		TR. 21 to 30		TR. 31 to 40		TR. 41 to 50		TR. 51 to 60		TR. 61 to 70		TR. 71 to 80		TR. 81 to 90		TR. 91 to 100		CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	
111A	7511716	62227	7511717	62230																			
111B		62231		62234																			
111C		62235		62238																			
112		62239		62242																			
112A		62243		62246																			
112B		62247		62250																			
112C		62251		62254																			
113		62255		62258																			
113A		62259		62262																			
113B		62263		62266																			
113C	7511717	62268		62271																			
114		62272		62275																			
114A		62276		62279																			
114B		62280		62283																			
114C		62284		62287																			
115		62288		62291																			
115A		62292		62295																			
115B		62296		62299																			
115C		63000		63003																			
116		63004		63007																			

REMARKS: File # 6222 → 6226 Test TB's  
 File # 6209 → 6221 Daily Test's  
 09 20  
 6229 NB  
 6225 NA  
 09 30  
 6260 NB  
 6266 NB  
 09 40  
 NEW TAPE - File # 6267 Dummy Record  
 09 50  
 10 25  
 10 20

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>North slope - Alaska</b>	LINE NO: <b>B-15</b>					
	PARTY NO: <b>1182</b>	INST ENG: <b>Jerry Windham</b>		DATE: <b>MO 3 DAY 28 YR 78</b>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(M) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1000 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: <b>3</b> sec	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 16 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: <b>8</b>	LO CUT HZ SLOPE: <b>18</b>	HJ CUT HZ SLOPE: <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> G-OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>36</b> db	TRIP SENS: <b>0</b> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY: _____	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____		R.C.U. NORM/ALT SW: _____	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input checked="" type="checkbox"/> OTHER	PATTERN: <b>IN line</b>	NO. OF POSITIONS: <b>1</b>	INLINE SPACING: <b>220'</b>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	<b>Air Gun</b>	CHG/HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
RECEIVER	TYPE: <b>GSC-20d</b>	PATTERN: <b>IN line</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>18'</b>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: <b>Series-Parallel</b>	RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>220'</b>	FOLD: <b>24</b>	DIRECTION OF PROGRESSION: <b>S to N</b>				
	OFFSET GROUP 1: <b>5830'</b>	OFFSET GROUP 24: <b>770'</b>	OFFSET GROUP 48: <b>770'</b>	OFFSET GROUP 48/96: <b>5830'</b>	LEADING GROUP: <b>48</b>				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 7 to 48		TR 19 to 20		SHOT		SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		HT.	REC.	HT.
16A	75117117	6320	---	6311	21		59	9+3 → T-8	1	6304 N6		
16B		6312	---	6315	22		60	9+4 → T-9				
16C		6316	---	6319	23		61	10+1 → T-10		6316, 6318 N6		
17		6320	---	6323	24		62	10+2 → T-11			10 30	
17A		6324	---	6331	25		63	10+3 → T-12		File # 6324 → 6327 N.G.		
17B		6327	---	6335	26		64	10+4 → T-13				
17C		6336	---	6339	27		65	11+1 → T-14		6337 N6		
18		6340	---	6343	28		66	11+2 → T-15			10 30	
18A		6344	---	6347	29		67	11+3 → T-16				
18B		6348	---	6351	30		68	11+4 → T-17				
18C		6352	---	6355	31		69	12+1 → T-18				
19		6356	---	6359	32		70	12+2 → T-19		6356 N6		11 00
19A		6360	---	6363	33		71	12+3 → T-20		6363 N6		
19B		6364	---	6367	34		72	12+4 → T-21				
19C		6368	---	6371	35		73	13+1 → T-22				
20		6372	---	6375	36		74	13+2 → T-23				11 00
20A		6376	---	6379	37		75	13+3 → T-24				
20B		6380	---	6383	38		76	13+4 → T-25				
20C		6384	---	6387	39		76	13+4 → T-25				
21		6388	---	6391	40		76	13+4 → T-25		6388 N6		

E. O. L.