

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>North Slope - Alaska</u>	LINE NO: <u>B-25</u>	
	PARTY NO: <u>1182</u>	INST. ENG: <u>Lenny Werdham</u>		DATE: <u>MO 5 DAY 27 YR 78</u>	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> DFS X <input type="checkbox"/> OTHER	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>36</u> db INPUT IMPEDANCE: _____ ohms	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI
-------------------------	--	---	--	--	--

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u> DATA CHANNEL NOS.: <u>1-48</u> (ON MAG TAPE)	NO. BYTES IN RECORD ID: _____ NO. BYTES PER SCAN: <u>134</u>	AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____
-----------------------------	---	---	--

PARAMETER	RECORD LENGTH: <u>5</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: FREQ <u>8</u> LO CUT HZ SLOPE <u>18</u> HI CUT HZ SLOPE <u>70</u>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE
-----------	------------------------------	--	--	--	--

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Inline</u>	NO. OF POSITIONS: <u>1</u>	INLINE SPACING: <u>880'</u>	LATERAL SPACING: _____
--------	--	------------------------	----------------------------	-----------------------------	------------------------

RECEIVER	TYPE: <u>BSC-20d</u>	PATTERN: <u>Inline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>18'</u>	LATERAL SPACING: _____
----------	----------------------	------------------------	----------------------------	----------------------------	------------------------

SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>SE to NW</u>
--------	--------------------------	-----------------------------	---------------------------------	----------------	---

DIAGRAMS/MISC. INFORMATION: \_\_\_\_\_

SHOTPOINT	TR. 1 to 48		TR. 19 to 22		TR. 23 to 26		TR. 27 to 30		TR. 31 to 34		CDP SWITCH	LINE GROUPS	REMARKS: <u>Filed 2621 Dummy Record</u>	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.				TR 1-48	TR 49-96	TR 1-48	TR 49-96
50	75118160	26212									37	T-26 → 43+3					
49		26213									41	F-22 → 42+3					
48		26214									45	F-18 → 41+3					
47		26215									49	F-14 → 40+3					
46		26216									53	F-10 → 39+3					
45		26217									57	F-6 → 38+3					
44		26218									7	F-2 → 37+3					
43		26219									11	49+2 → 36+3					
42		2630									15	48+2 → 35+3					
41		2631									19	47+2 → 34+3					
40		2632									23	46+2 → 33+3					
39		2633									27	45+2 → 32+3					
38		2634									31	44+2 → 31+3					
37		2635									35	43+2 → 30+3					
36		2636									39	42+2 → 29+3					
35		2637									43	41+2 → 28+3					

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>North Slope Alaska</b>	LINE NO: <b>B-25</b>	
PARTY NO: <b>1182</b>		INST. ENG: <b>Jerry Windham</b>		DATE: <b>MO 5 DAY 28 YR 78</b>	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b> SEG: _____	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI
NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: <b>134</b>		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	


CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>	AUXILIARY DATA: _____
	DATA CHANNEL NOS.: <b>1-48</b> (ON MAG TAPE)	AUXILIARY CHANNEL NOS.: _____

PARAMETER	RECORD LENGTH: <b>5</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input checked="" type="checkbox"/> TYP	FILTERS: FREQ. <b>8</b>	LO CUT HZ SLOPE <b>18</b>	HI CUT HZ SLOPE <b>128</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> ABC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>12</b> db	TRIP SENS.: <b>0</b> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON DISPLAY

SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>INLINE</b>	NO. OF POSITIONS: <b>1</b>	INLINE SPACING: <b>880'</b>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG/HOLE: <b>20</b>	HOLE DEPTH: <b>75</b>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____


RECEIVER	TYPE: <b>RSC-20d</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>18'</b>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: <b>Series-Parallel</b>	RESISTANCE: _____ ohms							

SPREAD	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SE to NW</b>
	OFFSET GROUP 1: <b>5610'</b>	OFFSET GROUP 24: <b>550'</b>	OFFSET GROUP 25: <b>550'</b>	OFFSET GROUP 48: <b>5610'</b>	LEADING GROUP: <b>48</b>



SHOTPOINT	TR. 1 to 48		TR. 10		SHOT		SPREAD		REMARKS: File# 2638 → 2650 Daily Tests File# 2651 Test 78	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-48	TR 48-96	TR 1-48
34	75110160	2652			20	167	1		23	40+2 → 27+3	1				
33		2653			20	167	2		27	39+2 → 26+3					
32		2654			20	167	3		31	38+2 → 25+3					
31		2655			20	167	4		35	37+2 → 24+3					
30		2656			20	167	5		39	36+2 → 23+3					
29		2657			20	167	6		43	35+2 → 22+3					
28		2659			20	167	7		47	34+2 → 21+3					File# 2650 Mis fire
27		2660			20	167	8		51	33+2 → 20+3					
26		2661			20	167	9		55	32+2 → 19+3					
25		2662			20	167	10		59	31+2 → 18+3					
24		2663			20	167	11		21	30+2 → 17+3	2				
23		2664			20	167	12		25	29+2 → 16+3					
22		2665			20	167	13		29	28+2 → 15+3					
21		2666			20	167	14		33	27+2 → 14+3					
20		2667			20	167	15		37	26+2 → 13+3					
19		2668			20	167	16		41	25+2 → 12+3					
18		2669			20	167	17		45	24+2 → 11+3					
17		2670			20	167	18		49	23+2 → 10+3					
16		2671			20	167	19		53	22+2 → 9+3					
15		2672			20	167	20		57	21+2 → 8+3					

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>North Slope - Alaska</u>	LINE NO: <u>B-25</u>	
	PARTY NO: <u>1182</u>	INST. ENG: <u>Sony Windham</u>		DATE: <u>MO 5 DAY 28 YR 78</u>	
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <u>134</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	FORMAT: <u>B</u>
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>		AUXILIARY DATA:		
	DATA CHANNEL NOS.: <u>1-48</u>		AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: <u>5</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/>	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	LO CUT HZ SLOPE: <u>18</u>	HI CUT HZ SLOPE: <u>70</u>
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>12</u> db	TRIP SENS.: <u>0</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Inline</u>	NO. OF POSITIONS: <u>8</u>	INLINE SPACING: <u>880'</u>	LATERAL SPACING:
	CHG/ HOLE: <u>20</u>	HOLE DEPTH: <u>75</u>	SWEEP POSITION:	SWEEP START:	SWEEP END:
RECEIVER	TYPE: <u>BSC-20d</u>	PATTERN: <u>Inline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>18'</u>	LATERAL SPACING:
	CONNECTION: <u>Series-Parallel</u>	RESISTANCE: ohms	STAGGER:	LENGTH:	WIDTH:
SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>SE to NW</u>
	OFFSET GROUP 1: <u>5610'</u>	OFFSET GROUP 24: <u>550'</u>	OFFSET GROUP 25: <u>550'</u>	OFFSET GROUP 48: <u>5610'</u>	LEADING GROUP: <u>48</u>

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. <u>1</u> to <u>48</u>		TR. _____ to _____		SHOT					SPREAD			REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SET UP		TR 1-48	TR 48-96	TR 1-48	TR 48-96
16	21810	2673			20	167	21			61	20+2 → 7+3	2					
13		2674			20	167	22			65	19+2 → 6+3						
12		2675			20	167	23	1110	SE	69	18+2 → 5+3						
11		2676			20	167	24	1110	NW	73	17+2 → 4+3						
10		2677			20	167	25			77	16+2 → 3+3						
9		2678			20	167	26	220	SE	81	15+2 → 2+3						
8		2679			20	167	27	880	NW	85	14+2 → 1+3		offset 500' lateral SW				
7		2680			20	167	28	220	NW	87	13+4 → 1+1		No tail - shooting through cable				
6		2681			20	167	29			87	13+4 → 1+1						
5		2682			20	167	30			87	13+4 → 1+1						
4		2683			20	167	31			87	13+4 → 1+1						
3		2684			20	167	32			87	13+4 → 1+1						
2		2685			20	167	33			87	13+4 → 1+1						
1							34			87	13+4 → 1+1		NO hole				

S. O. L.