

LAND SEISMIC RECORDING LOG

| | | | | | | | | | |
|-----------------------------|--|--|---|--|--|---|---|--|-----------------|
| | CLIENT: Husk 4 | PROSPECT: NPR-A | AREA: | LINE NO: B-4 | | | | | |
| | PARTY NO: 1182 | INST. ENG: Windham | | DATE: NO 1 DAY 20 YE 78 | | | | | |
| INSTRUMENT (9-TRACK) | <input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS | <input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96 | EVENTS | TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV | <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK | FORMAT: SLG B | <input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED | PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI 800 BPI (H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI | |
| | NO. BYTES IN HEADER REC: | NO. BYTES IN RECORD ID: | NO. BYTES PER SCAN: | RECORD NUMBERS: <input checked="" type="checkbox"/> DEL <input type="checkbox"/> OCT | GAIN CONSTANT: 24 db | INPUT IMPEDANCE: _____ ohms. | (1) (2) (3) (4) (5) (6) (7) | | |
| CONFIGURATION (MAG TAPE) | FIELD TRACE NOS: 1-48 | DATA CHANNEL NOS: 1-48 | (ON MAG TAPE) | AUXILIARY DATA: | AUXILIARY CHANNEL NOS: | | | | |
| PARAMETER | RECORD LENGTH: 2 sec | SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. | GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE | FILTERS: FREQ CUT LO CUT HZ SLOPE | FREQ 256 HI CUT HZ SLOPE 72 | NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT | | | |
| DISPLAY | MODE: <input checked="" type="checkbox"/> TRACE <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT | INITIAL GAIN: _____ db | TRIP SENS: _____ db | POLARITY CONVENTION: _____ | PRESSURE INCREASE ON GEOPHONE: _____ | <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE | NUMBERS ON MAG TAPE: _____ | <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK | |
| CFS I | TYPE STACK: | GATE LENGTH: | RECORD REJECTION: | NOISE REDUCTION: | NOISE THRESHOLD: | CORR. SCALING: | R.C.U. NORM. ALT SW. | | |
| SOURCE | TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER | PATTERN: Single hole | NO. OF POSITIONS: | INLINE SPACING: | LATERAL SPACING: | STAGGER: | LENGTH: | WIDTH: | LATERAL OFFSET: |
| RECEIVER | TYPE: GSC-20d | PATTERN: TW line | NO. OF ELEMENTS: 3 | INLINE SPACING: 3' | LATERAL SPACING: | STAGGER: | LENGTH: | WIDTH: | LATERAL OFFSET: |
| SPREAD | NO. OF GROUPS: 48 | GROUP INTERVAL: 55' | SHOTPOINT INTERVAL: 220' | FOLD: 6 | DIRECTION OF PROGRESSION: N to E | OFFSET GROUP 1: | LEADING GROUP: | | |

DIAGRAMS/MISC. INFORMATION: **TAIL SPREAD** **TRACE # 247** **SP1** **SP2** **SP3** **SP4** **SP5** **SP6** **SP7** **SP8** **SP9** **SP10** **SP11** **SP12** **SP13** **SP14** **SP15** **SP16** **SP17** **SP18** **SP19** **SP20** **SP21** **SP22** **SP23** **SP24** **SP25** **SP26** **SP27** **SP28** **SP29** **SP30** **SP31** **SP32** **SP33** **SP34** **SP35** **SP36** **SP37** **SP38** **SP39** **SP40** **SP41** **SP42** **SP43** **SP44** **SP45** **SP46** **SP47** **SP48**

| SHOTPOINT | TR | | TR | | SHOT | | SPREAD | | REMARKS | CORR. STACK | |
|-----------|----------|------|----------|------|------|-------|--------|------------------|-----------------|-------------|-------------------------|
| | REEL NO. | REC. | REEL NO. | REC. | SIZE | DEPTH | NO. | OFFSET | | TR 1-48 | TR 49-96 |
| 1 | 75 | 1658 | 17 | 2223 | 10 | 71 | 12 | 3 | T-26 → Sp7+2 | 1 | File # 467 Donny Record |
| 2 | | 459 | | | 10 | 71 | 13 | 7 | T-22 → Sp8+2 | | No Log |
| 3 | | 460 | | | 10 | 71 | 14 | 11 | T-18 → Sp9+2 | | |
| 4 | | 461 | | | 10 | 71 | 15 | 15 | T-14 → Sp10+2 | | |
| 5 | | 462 | | | 10 | 71 | 16 | 19 | T-10 → Sp11+2 | | |
| 6 | | 463 | | | 10 | 71 | 17 | 23 | T-6 → Sp12+2 | | |
| 7 | | 464 | | | 10 | 71 | 18 | 27 | T-2 → Sp13+2 | | No Log |
| 8 | | 465 | | | 10 | 71 | 19 | 27 27 | SP T-2 → Sp14+2 | | Wrong CDP |
| 9 | | 466 | | | 10 | 71 | 20 | 35 | Sp2+3 → Sp15+2 | | |
| 10 | | 467 | | | 10 | 71 | 21 | 39 | Sp3+3 → Sp16+2 | | No Log |
| 11 | | 468 | | | 10 | 71 | 22 | 43 | Sp4+3 → Sp17+2 | | |
| 12 | | 469 | | | 10 | 71 | 23 | 47 | Sp5+3 → Sp18+2 | | |
| 13 | | 470 | | | 10 | 71 | 24 | 51 | Sp6+3 → Sp19+2 | | File # 470 Misfire |
| 14 | | 472 | | | 10 | 71 | 25 | 55 | Sp7+3 → Sp20+2 | | |
| 15 | | 473 | | | 10 | 71 | 26 | 59 | Sp8+3 → Sp21+2 | | |
| 16 | | 474 | | | 10 | 71 | 27 | 63 | Sp9+3 → Sp22+2 | | |
| 17 | | 475 | | | 10 | 71 | 28 | 67 | Sp10+3 → Sp23+2 | | No Log |
| 18 | | 476 | | | 10 | 71 | 29 | 71 | Sp11+3 → Sp24+2 | | |
| 19 | | 477 | | | 10 | 71 | 30 | 75 | Sp12+3 → Sp25+2 | | |
| 20 | | 478 | | | 10 | 71 | 31 | 79 | Sp13+3 → Sp26+2 | | |

LAND SEISMIC RECORDING LOG


| | | | | | | | | | | |
|--------------------------|--|---|--|--|---|-----------------------------|---|---|---|-------------|
| | CLIENT: Husky | PROSPECT: NPR-A | AREA: | LINE NO: B-4 | | | | | | |
| | PARTY NO: 1182 | INST ENG: Windham | | DATE: MO 1 DAY 20 YR 78 | | | | | | |
| INSTRUMENT (9-TRACK) | <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS | <input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 | <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS | TYPE <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV | <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK | FORMAT: B | <input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED | PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI | (M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI | |
| | NO. BYTES IN HEADER REC: | NO. BYTES IN RECORD ID: | NO. BYTES PER SCAN: | RECORD NUMBERS: | <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT | GAIN CONSTANT: 24 db | INPUT IMPEDANCE: _____ ohms | | | |
| CONFIGURATION (MAG TAPE) | FIELD TRACE NOS: 1-48 DATA CHANNEL NOS: 1-48 (ON MAG TAPE) | | | | AUXILIARY DATA: AUXILIARY CHANNEL NOS.: | | | | | |
| PARAMETER | RECORD LENGTH: 2 sec. | SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms. | GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL | <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE | FILTERS: FREQ. OUT LO CUT HZ SLOPE | | <input checked="" type="checkbox"/> FREQ. 256 HI CUT HZ SLOPE 72 | NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT | | |
| DISPLAY | MODE: <input checked="" type="checkbox"/> MAG <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT | <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT | INITIAL GAIN: 18 db | TRIP SENS: 18 db | POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE | | PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG TAPE | | <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK | |
| CFS I | TYPE STACK: | GATE LENGTH: | RECORD REJECTION: | NOISE REDUCTION: | | NOISE THRESHOLD: | CORR SCALING: | | R.C.U. NORM. ALT SW. | |
| SOURCE | TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER | PATTERN: Single hole | NO. OF POSITIONS: | INLINE SPACING: | LATERAL SPACING: | STAGGER: | LENGTH: | WIDTH: | LATERAL OFFSET: | |
| RECEIVER | CONNECTION: Parallel | RESISTANCE: _____ ohms | CHG/HOLE: 10 | HOLE DEPTH: 75 | SWEEP POSITION: | SWEEP START: | SWEEP END: | SWEEP LENGTH: | SWEEP TAPER: | PHASE COMP: |
| SPREAD | NO. OF GROUPS: 48 | GROUP INTERVAL: 55' | OFFSET GROUP 1: | SHOTPOINT INTERVAL: 220' | OFFSET GROUP: | FOLD: 6 | DIRECTION OF PROGRESSION: W to E LEADING GROUP: | | | |

DIAGRAMS/MISC. INFORMATION:

| SHOTPOINT | TR _____ to _____ | | TR _____ to _____ | | SHOT | | | | SPREAD | | | REMARKS: | CORR STACK | | | | |
|-----------|-------------------|------|-------------------|------|------|-------|-----|--------|--------|------------|-------------|-----------------|------------|-----|--------|-----|--------|
| | REEL NO. | REC. | REEL NO. | REC. | SIZE | DEPTH | NO. | OFFSET | DIR. | CDP SWITCH | LINE GROUPS | | SET UP | HT. | YR. 41 | HT. | YR. 41 |
| | | | | | | | | | | | | | | | REC. | | REC. |
| 21 | 251459 | 479 | | | 1.8 | 71 | 32 | | | | 11 | Sp14+3 → Sp27+2 | 2 | | | | |
| 22 | | 480 | | | 1.0 | 71 | 33 | | | | 15 | Sp15+3 → Sp28+2 | | | | | No Log |
| 23 | | 481 | | | 1.0 | 71 | 34 | | | | 19 | Sp16+3 → Sp29+2 | | | | | No Log |
| 24 | | 482 | | | 1.0 | 71 | 35 | | | | 23 | Sp17+3 → Sp30+2 | | | | | " |
| 25 | | 483 | | | 1.0 | 71 | 36 | | | | 27 | Sp18+3 → Sp31+2 | | | | | " |
| 26 | | 484 | | | 1.0 | 71 | 37 | | | | 31 | Sp19+3 → Sp32+2 | | | | | |
| 27 | | 485 | | | 1.0 | 71 | 38 | | | | 35 | Sp20+3 → Sp33+2 | | | | | |
| 28 | | 486 | | | 1.0 | 71 | 39 | | | | 39 | Sp21+3 → Sp34+2 | | | | | |

LAND SEISMIC RECORDING LOG

| | | | | | | | | | |
|--------------------------|---|---|---|---|--|---|---|---|-----------------|
| | CLIENT: Husky | PROSPECT: NPR-A | AREA: | LINE NO: B-4 | | | | | |
| PARTY NO: | | INST. ENG: | | DATE: MO 1 DAY 22 YR 78 | | | | | |
| INSTRUMENT (9-TRACK) | <input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS | <input checked="" type="checkbox"/> 24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 | ODDS & EVENS: <input type="checkbox"/> | TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER | <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK | FORMAT: SEG B | <input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED | PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI | |
| | NO. BYTES IN HEADCR REC: | NO. BYTES IN RECORD ID: | NO. BYTES PER SCAN: | RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT | GAIN CONSTANT: 24 db | INPUT IMPEDANCE: ohms | (1) (2) (3) (4) (5) (6) (7) | | |
| CONFIGURATION (MAG TAPE) | FIELD TRACE NOS: 1-48 | | | AUXILIARY DATA: | | | | | |
| PARAMETER | RECORD LENGTH: 2 sec | SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> 4 ms | GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL | FILTERS: FREQ CUT | | LO CUT HZ SLOPE: 72 | NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT | | |
| DISPLAY | MODE: <input checked="" type="checkbox"/> MAG <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT | AMPLIFIER: <input type="checkbox"/> | INITIAL GAIN: 18 db | POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE | | NUMBERS ON MAG TAPE: <input type="checkbox"/> | DOWNBREAK JPBREAK: <input type="checkbox"/> | | |
| CFS I | TYPE STACK: | GATE LENGTH: | RECORD REJECTION: | NOISE REDUCTION: | NOISE THRESHOLD: | CORR SCALING: | P.C.U. NORM/ALT SW | | |
| SOURCE | <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER | PATTERN: Single hole | NO. OF POSITIONS: | INLINE SPACING: | LATERAL SPACING: | STAGGER: | LENGTH: | WIDTH: | LATERAL OFFSET: |
| RECEIVER | TYPE: GSC-20d | PATTERN: Inline | NO. OF ELEMENTS: 3 | INLINE SPACING: 5' | LATERAL SPACING: | STAGGER: | LENGTH: | WIDTH: | LATERAL OFFSET: |
| SPREAD | CONNECTION: Parallel | RESISTANCE: ohms | SHOTPOINT INTERVAL: 55' | SHOTPOINT INTERVAL: 220' | FOLD: 6 | OFFSET GROUP 48/96: | DIRECTION OF PROGRESSION: W to E | LEADING GROUP: | |



| SHOTPOINT | TR 1 to 48 | | TR 24 to 25 | | SHOT | | SPREAD | | REMARKS | CORR. STACK | |
|-----------|------------|------|-------------|------|------|-------|--------|--------|-------------|-------------|-------|
| | REEL NO | REC. | PEEL NO | REC. | SIZE | DEPTH | NO. | OFFSET | | TR 41 | TR 42 |
| 29 | 75165R | 501 | | | 10 | 71 | 1 | 19 | 22+3 → 35+2 | | |
| 30 | | 502 | | | 10 | 71 | 2 | 23 | 23+3 → 36+2 | | |
| 31 | | 503 | | | 10 | 71 | 3 | 27 | 24+3 → 37+2 | | |
| 32 | | 505 | | | 10 | 71 | 4 | 31 | 25+3 → 38+2 | | |
| 33 | | 506 | | | 10 | 71 | 5 | 25 | 26+3 → 39+2 | | |
| 34 | | 507 | | | 10 | 71 | 6 | 39 | 27+3 → 40+2 | | |
| 35 | | 508 | | | 10 | 71 | 7 | 43 | 28+3 → 41+2 | | |
| 36 | | 509 | | | 10 | 71 | 8 | 47 | 29+3 → 42+2 | | |
| 37 | | 510 | | | 10 | 71 | 9 | 51 | 30+3 → 43+2 | | |
| 38 | | 511 | | | 10 | 71 | 10 | 55 | 31+3 → 44+2 | | |
| 39 | | 512 | | | 10 | 71 | 11 | 59 | 32+3 → 45+2 | | |
| 40 | | 513 | | | 10 | 71 | 12 | 63 | 33+3 → 46+2 | | |
| 41 | | 514 | | | 10 | 71 | 13 | 67 | 34+3 → 47+2 | | |
| 42 | | 515 | | | 10 | 71 | 14 | 71 | 35+3 → 48+2 | | |
| 43 | | 516 | | | 10 | 71 | 15 | 75 | 36+3 → 49+2 | | |
| 44 | | 517 | | | 10 | 71 | 16 | 79 | 37+3 → 50+2 | | |
| 45 | | 518 | | | 10 | 71 | 17 | 83 | 38+3 → 51+2 | | |
| 46 | | 519 | | | 10 | 71 | 18 | 87 | 39+3 → 52+2 | | |
| 47 | | 520 | | | 10 | 71 | 19 | 91 | 40+3 → 53+2 | | |
| 48 | | 521 | | | 10 | 71 | 20 | 95 | 41+3 → 54+2 | | |

File# 534 - mistice

No Log

524 dead

LAND SEISMIC RECORDING LOG

| | | | | | | | |
|--------------------------|--|---|---|--|-----------------------------|--|---|
| | CLIENT: Husky | PROSPECT: NPR-A | AREA: | LINE NO: B-4 | | | |
| | PARTY NO: 1182 | INST. ENG: Windham | | DATE: MO 1 DAY 22 YR 78 | | | |
| INSTRUMENT (9-TRACK) | <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS | <input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 | TYPE <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER | <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK | FORMAT: SEG | <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED | PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 1000 BPI |
| | NO BYTES IN HEADER REC: | NO BYTES IN RECORD ID: | NO BYTES PER SCAN: | RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT | GAIN CONSTANT: 24 db | INPUT IMPEDANCE: _____ ohms | |
| CONFIGURATION (MAG TAPE) | FIELD TRACE NOS: 1-48 | | | AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7) | | | |
| | DATA CHANNEL NOS: 1-48 | | | AUXILIARY CHANNEL NOS: | | | |
| PARAMETER | RECORD LENGTH: 2 sec | SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms | GAIN MODE: <input checked="" type="checkbox"/> TRIP <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL | FILTERS: FREQ OUT LO CUT HZ SLOPE | | FREQ 256 HI CUT HZ SLOPE 72 | NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT |
| DISPLAY | MODE: <input checked="" type="checkbox"/> GGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT | INITIAL GAIN: 18 db | TRIP SENS: 18 db | POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE | | PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY | |
| CFS I | TYPE STACK: | GATE LENGTH: | RECORD REJECTION: | NOISE REDUCTION: | NOISE THRESHOLD: | CORR SCALING: | P.C.U. NORM./ALT SW |
| SOURCE | TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> V. BROSEIS <input type="checkbox"/> OTHER | PATTERN: Single hole | NO. OF POSITIONS: | INLINE SPACING: | LATERAL SPACING: | STAGGER: | LENGTH: WIDTH: LATERAL OFFSET: |
| | | CHG/ HOLE: 10 HOLE DEPTH: 75 | SWEEP POSITION: | SWEEP START: | SWEEP END: | SWEEP LENGTH: SWEEP TAPER: | PHASE COMP: |
| RECEIVER | TYPE: RSC-20 d | PATTERN: IN line | NO. OF ELEMENTS: 3 | INLINE SPACING: 3' | LATERAL SPACING: | LENGTH: WIDTH: LATERAL OFFSET: | |
| | CONNECTION: Parallel | RESISTANCE: _____ ohms | STAGGER: | LENGTH: | WIDTH: LATERAL OFFSET: | | |
| SPREAD | NO. OF GROUPS: 48 | GROUP INTERVAL: 55' | SHOTPOINT INTERVAL: 220' | FOLD: 6 | OFFSET GROUP 1: | DIRECTION OF PROGRESSION: W to E | LEADING GROUP: |

DIAGRAMS/MISC. INFORMATION:

| SHOTPOINT | REEL NO | REC. | REEL NO | REC. | SHOT | | | DIR | CDP SWITCH | LINE GROUPS | | REMARKS | CORR STACK | | |
|-----------|---------|------|---------|------|------|-------|------------|-----|------------|-------------|---------|---------|------------|--|--|
| | | | | | SIZE | DEPTH | NO. OFFSET | | | SET UP | TR 1-24 | | TR 48-96 | | |
| 49 | 7511638 | 522 | | | 10 | 7121 | | | 27 | 4213 | → 5412 | 2. | | | |
| 50 | | 523 | | | 10 | 7122 | | | 31 | 4313 | → 5612 | | | | |
| 51 | | 524 | | | 5 | 7323 | | | 35 | 4413 | → 5712 | | | | |
| 52 | | 525 | | | 10 | 7124 | | | 39 | 4513 | → 5812 | | | | |
| 53 | | 526 | | | 10 | 7125 | | | 43 | 4613 | → 5912 | | | | |
| 54 | | 528 | | | 10 | 7126 | | | 47 | 4713 | → 6012 | | | | |
| 55 | | 529 | | | 10 | 7127 | | | 3 | 4813 | → 6112 | 3 | | | |
| 56 | | 530 | | | 10 | 7128 | | | 7 | 4913 | → 6212 | | | | |
| 57 | | 531 | | | 10 | 7129 | | | 11 | 5013 | → 6312 | | | | |
| 58 | | 532 | | | 10 | 7130 | | | 15 | 5113 | → 6412 | | | | |
| 59 | | 533 | | | 10 | 7131 | | | 19 | 5213 | → 6512 | | | | |
| 60 | | 534 | | | 10 | 7132 | | | 23 | 5313 | → 6612 | | | | |
| 61 | | 535 | | | 10 | 7133 | | | 27 | 5413 | → 6712 | | | | |
| 62 | | 536 | | | 10 | 7134 | | | 31 | 5513 | → 6812 | | | | |
| 63 | | 537 | | | 10 | 7135 | | | 35 | 5613 | → 6912 | | | | |
| 64 | | 538 | | | 10 | 7136 | | | 39 | 5713 | → 7012 | | | | |
| 65 | | 539 | | | 10 | 7137 | | | 43 | 5813 | → 7112 | | | | |
| 66 | | 544 | | | 10 | 7138 | | | 47 | 5913 | → 7212 | | | | |
| 67 | | 545 | | | 10 | 7139 | | | 51 | 6013 | → 7312 | | | | |
| 68 | | 546 | | | 10 | 7140 | | | 61 | 6113 | → 7412 | | | | |

no log

11 11

11 11

11 11

File # 538 → 543 Misfires

wrong CDP



LAND SEISMIC RECORDING LOG

| | | | | | | | | | |
|--------------------------|---|--|---|---|--|--|--|--|-----------------|
| | CLIENT: Husky | PROSPECT: NPR-A | AREA: | LINE NO: B-4 | | | | | |
| | PARTY NO.: | INST. ENG.: | | DATE: MO 1 DAY 22 YR 79 | | | | | |
| INSTRUMENT (9-TRACK) | <input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS | <input checked="" type="checkbox"/> 24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96 | ODDS EVENS | TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV | <input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 2) TRACK | POP/AT: B | <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED | PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI | |
| | NO. BYTES IN HEADER REC. | NO. BYTES IN RECORD ID: | NO. BYTES PER SCAN: | RECORD NUMBERS: DEC OCT | GAIN CONSTANT: 24 db | INPUT IMPEDANCE: ohms | (1) (2) (3) (4) (5) (6) (7) | | |
| CONFIGURATION (MAG TAPE) | FIELD TRACE NOS: 1-48 | | | AUXILIARY DATA: | | | AUXILIARY CHANNEL NOS: | | |
| PARAMETER | RECORD LENGTH: 2 sec. | SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> ms. | GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TRIP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE | FILTERS: FREQ OUT LO CUT HZ SLOPE | | HIGH CUT HZ SLOPE: 72 | NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT | | |
| DISPLAY | MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLAT <input type="checkbox"/> DIRECT | INITIAL GAIN: 18 db | TRIP SENS: 18 db | POLARITY CONVENTION | | PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE | NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK | | |
| CFS I | TYPE STACK: | GATE LENGTH: | RECORD REJECTION: | NOISE REDUCTION: | | NOISE THRESHOLD: | CORR. SCALING: R.C.U. NORM./ALT SW | | |
| SOURCE | TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER | PATTERN: Single hole | NO. OF POSITIONS: | INLINE SPACING: | LATERAL SPACING: | STAGGER: | LENGTH: | WIDTH: | LATERAL OFFSET: |
| | CHG/ HOLE: 10 | HOLES DEPTH: 75 | SWEEP POSITION: | SWEEP START: | SWEEP END: | SWEEP LENGTH: | SWEEP TAPER: | PHASE COMP: | |
| RECEIVER | TYPE: GSC-20d | PATTERN: In line | NO. OF ELEMENTS: 3 | INLINE SPACING: 3' | LATERAL SPACING: | STAGGER: | LENGTH: | WIDTH: | LATERAL OFFSET: |
| | CONNECTION: Parallel | RESISTANCE: ohms | | | | | | | |
| SPREAD | NO. OF GROUPS: 48 | GROUP INTERVAL: 55' | SHOTPOINT INTERVAL: 220' | FOLD: 6 | DIRECTION OF PROGRESSION: W to E | OFFSET GROUP 1: | OFFSET GROUP 48/96: | LEADING GROUP: | |

DIAGRAMS/MISC. INFORMATION:

| SHOTPOINT | TR 1 to 48 | | TR 1 to 48 | | SHOT | | | | | | | | | | | | | CDP SWITCH | CH-1 SPREAD | | CH-48 | REMARKS: | CORR STACK | | | |
|-----------|------------|------|------------|------|------|-------|-----|--------|-----|-------------|--|--|--|--|--|--|--|------------|-------------|---|-------|----------|------------|----------|--|--|
| | REEL NO | REC. | REEL NO. | REC. | SIZE | DEPTH | NO. | OFFSET | DIR | LINE GROUPS | | | | | | | | | | | | | TR 1-48 | TR 48-96 | | |
| 67 | 516 | 567 | | | 10 | 71 | 41 | | | | | | | | | | | 55 | 62+3 | → | 75+2 | 3 | | | | |
| 70 | | 548 | | | 10 | 71 | 42 | | | | | | | | | | | 63 | 63+3 | → | 76+2 | | | | | |
| 71 | | 549 | | | 10 | 71 | 43 | | | | | | | | | | | 67 | 64+3 | → | 77+2 | | | | | |
| 72 | | 550 | | | 10 | 71 | 44 | | | | | | | | | | | 71 | 65+3 | → | 78+2 | | | | | |
| 73 | | 551 | | | 10 | 71 | 45 | | | | | | | | | | | 75 | 66+3 | → | 79+2 | | | | | |
| 74 | | 552 | | | 10 | 71 | 46 | | | | | | | | | | | 79 | 67+3 | → | 80+2 | | | | | |
| 75 | | 553 | | | 10 | 71 | 47 | | | | | | | | | | | 83 | 68+3 | → | 81+2 | | | | | |
| 76 | | 554 | | | 10 | 71 | 48 | | | | | | | | | | | 15 | 69+3 | → | 82+2 | 4 | | | | |
| 77 | | 555 | | | 10 | 71 | 49 | | | | | | | | | | | 19 | 70+3 | → | 83+2 | | | | | |
| 78 | | 556 | | | 10 | 71 | 50 | | | | | | | | | | | 23 | 71+3 | → | 84+2 | | | | | |
| 79 | | 557 | | | 10 | 71 | 51 | | | | | | | | | | | 27 | 72+3 | → | 85+2 | | | | | |
| 80 | | 558 | | | 10 | 71 | 52 | | | | | | | | | | | 31 | 73+3 | → | 86+2 | | | | | |
| 81 | | 559 | | | 10 | 71 | 53 | | | | | | | | | | | 35 | 74+3 | → | 87+2 | | | | | |
| 82 | | 560 | | | 10 | 71 | 54 | | | | | | | | | | | 39 | 75+3 | → | 88+2 | | | | | |
| 83 | | 561 | | | 10 | 71 | 55 | | | | | | | | | | | 43 | 76+3 | → | 89+2 | | | | | |
| 84 | | 562 | | | 10 | 71 | 56 | | | | | | | | | | | 47 | 77+3 | → | 90+2 | | | | | |
| 85 | | 563 | | | 10 | 71 | 57 | | | | | | | | | | | 51 | 78+3 | → | 91+2 | | | | | |
| 86 | | 564 | | | 10 | 71 | 58 | | | | | | | | | | | 55 | 79+3 | → | 92+2 | | | | | |
| 87 | | 565 | | | 10 | 71 | 59 | | | | | | | | | | | 59 | 80+3 | → | 93+2 | | | | | |
| 88 | | 566 | | | 10 | 71 | 60 | | | | | | | | | | | 63 | 81+3 | → | 94+2 | | | | | |

LAND SEISMIC RECORDING LOG



| | | | | | | | | | | | | | | | | | |
|--|---|---|--|--|---|---|--|---|--|--------------------------------------|-----------------------------|-----------------------------|--|--|--|--|--|
|  | CLIENT: Husky | PROSPECT: NPR-A | AREA: | LINE NO: B-4 |  | | | | | | | | | | | | |
| PARTY NO: | | INST. ENG: | | DATE: 1 DAY 22 YR 78 | | | | | | | | | | | | | |
| INSTRUMENT (9-TRACK) | <input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS | <input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96 | ODDS & EVENS <input type="checkbox"/> | TYPE <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input checked="" type="checkbox"/> DFS V <input type="checkbox"/> OTHER | <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK | FORMAT: B SEG | <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED | PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input checked="" type="checkbox"/> 72 BPI <input type="checkbox"/> 1600 BPI | RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> CCY | | GAIN CONSTANT: 24 db | INPUT IMPEDANCE: _____ ohms | | | | | |
| | NO. BYTES IN HEADER REC: _____ | | NO. BYTES IN RECORD ID: _____ | | NO. BYTES PER SCAN: _____ | | | | | | | | | | | | |
| CONFIGURATION (MAG TAPE) | FIELD TRACE NOS: 1-48 | | | AUXILIARY DATA: | | | AUXILIARY CHANNEL NOS: _____ | | | | | | | | | | |
| PARAMETER | RECORD LENGTH: 2 sec | SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> _____ ms | GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE | FILTERS: FREQ Out LO CUT HZ SLOPE _____ HI CUT HZ SLOPE 72 | | NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT | | | | | | | | | | | |
| DISPLAY | MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT | INITIAL GAIN: 18 db | TRIP SENS: 18 db | POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE | | PRESSURE INCREASE ON GEOPHONE: _____ | | NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK | | ON DISPLAY: <input type="checkbox"/> | | | | | | | |
| CFS I | TYPE STACK: _____ | GATE LENGTH: _____ | RECORD REJECTION: _____ | NOISE REDUCTION: _____ | | NOISE THRESHOLD: _____ | | CORR SCALING: _____ | | P.C.U. NORM/ALT SW: _____ | | | | | | | |
| SOURCE | TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER | PATTERN: Single Hole | NO. OF POSITIONS: _____ | INLINE SPACING: _____ | LATERAL SPACING: _____ | STAGGER: _____ | LENGTH: _____ | WIDTH: _____ | LATERAL OFFSET: _____ | | | | | | | | |
| RECEIVER | TYPE: GSC-20d | PATTERN: Inline | NO. OF ELEMENTS: 3 | INLINE SPACING: 3' | LATERAL SPACING: _____ | STAGGER: _____ | LENGTH: _____ | WIDTH: _____ | LATERAL OFFSET: _____ | | | | | | | | |
| SPREAD | CONNECTION: Parallel | RESISTANCE: _____ ohms | GROUP INTERVAL: 55' | SHOTPOINT INTERVAL: 220' | FOLD: 6 | OFFSET GROUP: _____ | OFFSET GROUP 48/96: _____ | DIRECTION OF PROGRESSION: W to E | | | | | | | | | |

DIAGRAMS/MISC. INFORMATION:

| SHOTPOINT | TR _____ to _____ | | TR _____ to _____ | | SHOT | | | | SPREAD | | | REMARKS | CORR. STACK | | | |
|-----------|-------------------|------|-------------------|------|------|-------|-----|--------|--------|------------|---------------|-------------|-------------|-----|----|-----|
| | REEL NO. | REC. | PEEL NO. | REC. | SIZE | DEPTH | NO. | OFFSET | DIR | CDP SWITCH | LINE GROUPS | | HT | REC | HT | REC |
| 89 | 751 | 567 | 17 | | 10 | 71 | 61 | | | 67 | 82+3 → 95+2 | | | | | |
| 90 | | 568 | | | 10 | 71 | 62 | | | 71 | 83+3 → 96+2 | | | | | |
| 91 | | 569 | | | 10 | 71 | 63 | | | 75 | 84+3 → 97+2 | 97+1,2 Dead | | | | |
| 92 | | 570 | | | 10 | 71 | 64 | | | 31 | 85+3 → 98+2 | 5 | | | | |
| 93 | | 571 | | | 10 | 71 | 65 | | | 35 | 86+3 → 99+2 | | | | | |
| 94 | | 572 | | | 10 | 71 | 66 | | | 39 | 87+3 → 100+2 | | | | | |
| 95 | | 573 | | | 10 | 71 | 67 | | | 43 | 88+3 → 101+2 | | | | | |
| 96 | | 574 | | | 10 | 71 | 68 | | | 47 | 89+3 → 102+2 | | | | | |
| 97 | | 575 | | | 10 | 71 | 69 | | | 51 | 90+3 → 103+2 | | | | | |
| 98 | | 576 | | | 10 | 71 | 70 | | | 55 | 91+3 → 104+2 | | | | | |
| 99 | | 577 | | | 10 | 71 | 71 | | | 59 | 92+3 → 105+2 | | | | | |
| 100 | | 578 | | | 10 | 71 | 72 | | | 63 | 93+3 → 106+2 | | | | | |
| 101 | | 579 | | | 10 | 71 | 73 | | | 67 | 94+3 → 107+2 | | | | | |
| 102 | | 580 | | | 10 | 71 | 74 | | | 71 | 95+3 → 108+2 | | | | | |
| 103 | | 581 | | | 10 | 71 | 75 | | | 75 | 96+3 → 109+2 | | | | | |
| 104 | | 582 | | | 10 | 71 | 76 | | | 79 | 97+3 → 110+2 | | | | | |
| 105 | | 583 | | | 10 | 71 | 77 | | | 83 | 98+3 → 111+2 | | | | | |
| 106 | | 584 | | | 10 | 71 | 78 | | | 15 | 99+3 → 112+2 | 6 | | | | |
| 107 | | 585 | | | 10 | 71 | 79 | | | 19 | 100+3 → 113+2 | | | | | |
| 108 | | 587 | | | 10 | 71 | 80 | | | 23 | 101+3 → 114+2 | | | | | |

File # 586 Mistfire

LAND SEISMIC RECORDING LOG

| | | | | | | | | | | | |
|--|---|---|--|-----------------------------------|---|--|---------------------|---|----------------------------------|-----------------------------------|--|
|  | CLIENT: Husky | PROSPECT: NPR-A | AREA: | LINE NO: B-4 |  | | | | | | |
| PARTY NO: | | INST. ENG.: | | DATE: 1 DAY 22 1978 | | | | | | | |
| INSTRUMENT (9-TRACK) | <input checked="" type="checkbox"/> 1 SYSTEM | <input checked="" type="checkbox"/> 1-24 & 25-48 | ODDS | <input type="checkbox"/> 9 TRACK | FORMAT: B | <input type="checkbox"/> GAPPED | PACKING DENSITY: | <input type="checkbox"/> 356 BPI | <input type="checkbox"/> 712 BPI | <input type="checkbox"/> 1000 BPI | |
| | <input type="checkbox"/> 2 SYSTEMS | <input type="checkbox"/> 1-48 & 49-96 | EVEN | <input type="checkbox"/> 21 TRACK | SEG | <input type="checkbox"/> UNGAPPED | | | | | |
| NO. BYTES IN HEADER REC: | | | NO. BYTES IN RECORD ID: | NO. BYTES PER SCAN: | RECORD NUMBERS: | <input type="checkbox"/> DEC. <input type="checkbox"/> OCT | GAIN CONSTANT: | INPUT IMPEDANCE: | | | |
| CONFIGURATION (MAG TAPE) | FIELD TRACE NOS.: 1-48 | | | | AUXILIARY DATA: | | | | | | |
| DATA CHANNEL NOS.: 1-48 | | [ON MAG TAPE] | | | | AUXILIARY CHANNEL NOS.: | | | | | |
| PARAMETER | RECORD LENGTH: 2 sec. | SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. | GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL | FILTERS: OUT | | LO CUT HZ SLOPE: 72 | | NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT | | | |
| DISPLAY | MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT | INITIAL GAIN: _____ db | TRIP SENS: _____ db | POLARITY CONVENTION | | PRESSURE INCREASE ON GEOPHONE: | | NEGATIVE } NUMBERS ON MAG TAPE | | DOWNBREAK } ON DISPLAY | |
| CFS I | TYPE STACK: | GATE LENGTH: | RECORD REJECTION: | NOISE REDUCTION: | | NOISE THRESHOLD: | | CORR. SCALING: | | B.C.U. NORM. ALT SW | |
| SOURCE | TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER | PATTERN: | NO. OF POSITIONS: | INLINE SPACING: | LATERAL SPACING: | STAGGER: | LENGTH: | WIDTH: | LATERAL OFFSET: | | |
| RECEIVER | CONNECTION: | RESISTANCE: | CHG./HOLE: | FOLD DEPTH: | SWEEP POSITION: | SWEEP START: | SWEEP END: | SWEEP LENGTH: | SWEEP TAPER: | PHASE COMP. | |
| SPREAD | NO. OF GROUPS: | GROUP INTERVAL: | SHOTPOINT INTERVAL: | OFFSET GROUP: | OFFSET GROUP: | FOLD: | OFFSET GROUP 48/96: | DIRECTION OF PROGRESSION: | | | |
| DIAGRAMS/MISC. INFORMATION: | | | | | | | | | | | |

| SHOTPOINT | TR 1 to 18 | | TR 19 to 36 | | SHOT | | SPREAD | | REMARKS: | CORR. STACK | | |
|-----------|------------|------|-------------|------|------|-------|--------|--------|---------------|-------------------------|-------------|-------|
| | REEL NO. | REC. | REEL NO. | REC. | SIZE | DEPTH | NO. | OFFSET | | CDP SWITCH | LINE GROUPS | TR 41 |
| 109 | 751658 | 588 | | | 10 | 71 | 31 | 27 | 102+3 → 115+2 | | | |
| 110 | | 589 | | | 10 | 71 | 32 | 31 | 103+3 → 116+2 | | | |
| 111 | | 591 | | | 10 | 71 | 33 | 35 | 104+3 → 117+2 | File # 590 MISFIRE | | |
| 112 | | 592 | | | 10 | 71 | 34 | 39 | 105+3 → 118+2 | No Log | | |
| 113 | | 593 | | | 10 | 71 | 35 | 43 | 106+3 → 119+2 | | | |
| 114 | 751659 | 595 | | | 10 | 71 | 36 | 47 | 107+3 → 120+2 | File # 594 Dummy Record | | |
| 115 | | 596 | | | 10 | 71 | 37 | 51 | 108+3 → 121+2 | | | |
| 116 | | 597 | | | 10 | 71 | 38 | 55 | 109+3 → 122+2 | 110 Log | | |
| 117 | | 598 | | | 10 | 71 | 39 | 59 | 110+3 → 123+2 | | | |
| 118 | | 599 | | | 10 | 71 | 40 | 63 | 111+3 → T2 | | | |
| 119 | | 600 | | | 10 | 71 | 41 | 67 | 112+3 → T6 | No Log | | |
| 120 | | 601 | | | 10 | 71 | 42 | 71 | 113+3 → T10 | " " | | |
| 121 | | 602 | | | 10 | 71 | 43 | 75 | 114+3 → T14 | " " | | |
| 122 | | 603 | | | 10 | 71 | 44 | 79 | 115+3 → T18 | " " | | |
| 123 | | 604 | | | 10 | 71 | 45 | 83 | 116+3 → T22 | | | |
| 124 | | 605 | | | 10 | 71 | 46 | 87 | 117+3 → T26 | No Log | | |

EOW