




# LAND SEISMIC RECORDING LOG


	CLIENT: <u>Nusby</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>North Slope - Alaska</u>	LINE NO: <u>B-5A</u>					
	PARTY NO: <u>1182</u>	INST. ENG: <u>Jerry Windham</u>		DATE: <u>MO 5 DAY 29 YR 78</u>					
INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
CONFIGURATION (MAG TAPE)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <u>134</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>db</u>	INPUT IMPEDANCE: (1) (2) (3) (4) (5) (6) (7)			
PARAMETER	FIELD TRACE NOS.: <u>1-48</u>	DATA CHANNEL NOS.: <u>1-48</u> (ON MAG TAPE)			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:	
DISPLAY	RECORD LENGTH: <u>5</u> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms <input type="checkbox"/> 8 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input checked="" type="checkbox"/> TRF <input type="checkbox"/> FINAL	FILTERS: FREQ: <u>8</u> LO CUT HZ SLOPE: <u>12</u> HI CUT HZ SLOPE: <u>70</u>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE } NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY			
CFS I	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>12</u> db	TRIP SENS: <u>0</u> db	NOISE REDUCTION:	CORR. SCALING:	R.C.U. NORM / ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>In line</u>	NO. OF POSITIONS: <u>1</u>	INLINE SPACING: <u>880'</u>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: <u>GSC-20d</u>	PATTERN: <u>In line</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>18'</u>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: <u>Series-Parallel</u>	RESISTANCE:	OHMS:	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>S to N</u>			
	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220'</u>	OFFSET GROUP 1: <u>5610'</u>	OFFSET GROUP 25: <u>550'</u>	OFFSET GROUP 48: <u>5610'</u>	LEADING GROUP: <u>48</u>			



SHOTPOINT	TR 1 to 48		TR 10		SHOT										DIR.	COP SWITCH	LINE GROUPS	SET	REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	22	23	26	27	29	30	32	35	37	TR 1-24						TR 25-48	TR 49-72	TR 73-96	
301	75118167	27811													19	T-26 → 7+2	8						
2		2782													23	T-22 → 8+2							
3		2783													27	T-18 → 9+2							
4		2784													31	T-14 → 10+2							
5		2785													35	T-10 → 11+2							
6		2786													39	T-6 → 12+2							
7		2787													43	T-2 → 13+2							
8		2789													47	1+3 → 14+2							
9		2790													51	2+3 → 15+2							
10		2791													55	3+3 → 16+2							
10		2792													57	5+3 → 18+2	9	Recover SP-11					
14		2793													25	5+1 → 17+4		Recover SP-13					
16		2794													32	6+4 → 19+3		Recover SP-14					
16		2795													39	8+3 → 21+2							
16		2796													43	9+3 → 22+2							
17		2797													47	10+3 → 23+2							
318		2798													51	11+3 → 24+2							

REMARKS: File # 2779 Dummy Record  
File # 2788 Test

# LAND SEISMIC RECORDING LOG

<b>CLIENT:</b> Husky	<b>PROSPECT:</b> NPR-A	<b>AREA:</b> North Slope - Alaska	<b>LINE NO.:</b> B-5	
<b>PARTY NO.:</b> 1182	<b>INST. ENG.:</b> Jerry Windham		<b>DATE:</b> MO 5 DAY 30 YR 78	

<b>INSTRUMENT</b> (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	DDOS <input checked="" type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1500 BPI
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 134	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: ohms.			


<b>CONFIGURATION (MAG TAPE)</b> FIELD TRACE NOS.: 1-48 DATA CHANNEL NOS.: 1-48 (ON MAG TAPE)	AUXILIARY DATA: AUXILIARY CHANNEL NOS.:
----------------------------------------------------------------------------------------------------	--------------------------------------------

<b>PARAMETER</b>	RECORD LENGTH: 5 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 70	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
<b>DISPLAY</b>	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 1.2 db	TRIP SENS: 0 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON DISPLAY
<b>CFS I</b>	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.

<b>SOURCE</b>	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Inline	NO. OF POSITIONS: 1	INLINE SPACING: 880	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: 70	HOLE DEPTH: 75	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	

<b>RECEIVER</b>	TYPE: ASC-20d	PATTERN: Inline	NO. OF ELEMENTS: 18	INLINE SPACING: 18'	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: Series-Parallel	RESISTANCE: ohms							

<b>SPREAD</b>	NO. OF GROUPS: 48	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 6	DIRECTION OF PROGRESSION: S to N
	OFFSET GROUP 1: 5610'	OFFSET GROUP 24: 550'	OFFSET GROUP 25: 550'	OFFSET GROUP 48: 5610'	LEADING GROUP: 48



SHOTPOINT	TR. 1 to 48		TR. 10 to		SHOT										SPREAD		REMARKS: File # 2800 -> 2812 DR. 14 TATS File # 2814 -> 28 Test TB 2813-Test TB	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		ST	TR 1-48	TR 48-96	REC.				
319	28118	2815			20	67	1				25	12+3	→ 25+2	1						
20		28116			20	67	2				29	13+3	→ 26+2							
21		28117			20	67	3				33	14+3	→ 27+2							
22		28118			20	67	4				37	15+3	→ 28+2							
23		28119			20	67	5				41	16+3	→ 29+2							
24		2820			20	67	6				45	17+3	→ 30+2							
25		2821			20	67	7				49	18+3	→ 31+2							
26		2822			20	67	8				53	19+3	→ 32+2							
27		2823			20	67	9				57	20+3	→ 33+2							
28		2824			20	67	10				61	21+3	→ 34+2							
26		2825			20	67	11				23	22+3	→ 35+2	2						
30		2826			20	67	12				27	23+3	→ 36+2							
31		2827			20	67	13				31	24+3	→ 37+2							
32		2828			20	67	14				35	25+3	→ 38+2							
33		2829			20	67	15				39	26+3	→ 39+2							
34		2830			20	67	16				43	27+3	→ 40+2							
36		2831			20	67	17				47	28+3	→ 41+2							
36		2832			20	67	18				51	29+3	→ 42+2							
37		2833			20	67	19				19	30+3	→ 43+2	3						
338		2834			20	67	20				23	31+3	→ 44+2							

# LAND SEISMIC RECORDING LOG



	CLIENT: <i>Husby</i>	PROSPECT: <i>NPR-A</i>	AREA: <i>North Slope - Alaska</i>	LINE NO: <i>B-5</i>						
	PARTY NO: <i>1182</i>	INST. ENG: <i>Sam Windham</i>		DATE: <i>MO 5 DAY 30 YR 78</i>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-44 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <i>B</i>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <i>134</i>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <i>36</i> db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <i>1-48</i>			AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)						
	DATA CHANNEL NOS.: <i>1-48</i>			AUXILIARY CHANNEL NOS.:						
PARAMETER	RECORD LENGTH: <i>5</i> sec.	SAMPLE RATE: <input type="checkbox"/> 1000 <input type="checkbox"/> 2000 <input type="checkbox"/> 4000	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> IFP	FILTERS: FREQ <i>8</i>	LO CUT HZ SLOPE <i>18</i>	FREQ <i>128</i>	HI CUT HZ SLOPE <i>70</i>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> ACC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT	AMPLIFIER DIRECT	INITIAL GAIN: <i>72</i> db	JRIP SENS: <i>0</i> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <i>In line</i>	NO. OF POSITIONS: <i>1</i>	INLINE SPACING: <i>880</i>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	TYPE: <i>BSC-20d</i>	PATTERN: <i>In line</i>	NO. OF ELEMENTS: <i>18</i>	INLINE SPACING: <i>18'</i>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: <i>48</i>	GROUP INTERVAL: <i>220'</i>	SHOTPOINT INTERVAL: <i>880'</i>	FOLD: <i>6</i>	DIRECTION OF PROGRESSION: <i>S to N</i>	OFFSET GROUP 1: <i>5610'</i>		LEADING GROUP: <i>48</i>		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 48		TR 10 to		SHOT					SPREAD			REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SET UP		TR 1-48	TR 48-96
327	715	1816	2835		20	167	21			27	32+3 → 45+2	3			
NO		2836			20	167	22			31	33+3 → 46+2				
41		2837			20	167	23			35	34+3 → 47+2				
42		2838			20	167	24			39	35+3 → 48+2				
43		2839			20	167	25			43	36+3 → 49+2				
44		2840			20	167	26			47	37+3 → 50+2				
45		2841			20	167	27	440	N	51	38+3 → 51+2		Offset 330' N		
46		2842			20	167	28			47	37+3 → 50+2		SP-48 Recover SP-46		
47		2843			10	50	28	220	N	54	39+2 → 51+1		SP-48 offset 220' N Recover 47		
48		2844			10	50	30	440	N	61	41+1 → 53+4		SP-48 offset 440' N Recover 48		
49		2845			20	167	31			67	42+3 → 55+2				
50		2846			20	167	32			71	43+3 → 56+2				
51		2847			20	167	33			75	44+3 → 57+2				
52		2849			20	167	34			79	45+3 → 58+2		File # 2848 mis fire		
53		2850			20	167	35			83	46+3 → 59+2				
54		2851			20	167	36			87	47+3 → 60+2				
55		2852			20	167	37			25	48+3 → 61+2	4			
56		2853			20	167	38			29	49+3 → 62+2				
57		2854			10	50	39			33	50+3 → 63+2				
367		2855			10	46	40			41	52+3 → 65+2		Recover SP-58		



# LAND SEISMIC RECORDING LOG

	CLIENT: <i>Husky</i>	PROSPECT: <i>NPR-A</i>	AREA: <i>North Slope - Alaska</i>	LINE NO: <i>B-5</i>							
PARTY NO: <i>1182</i>		INST. ENG: <i>Jerry Windham</i>		DATE: <i>MO 5 DAY 30 YR 78</i>							
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM	<input checked="" type="checkbox"/> 1-24 & 25-48	<input checked="" type="checkbox"/> 0005	TYPE: <input type="checkbox"/> DFS III	<input checked="" type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK	FORMAT: <i>B</i>	<input checked="" type="checkbox"/> GAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI	(HI) <input type="checkbox"/> 712 BPI	<input checked="" type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: <i>134</i>		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <i>36</i> db	INPUT IMPEDANCE: _____ ohms.		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <i>1-48</i>		DATA CHANNEL NOS.: <i>1-48</i>		AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____						
	PARAMETER		RECORD LENGTH: <i>5</i> sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 sec. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <i>8</i> LO CUT HZ SLOPE <i>18</i>	FREQ. <i>128</i> HI CUT HZ SLOPE <i>70</i>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	<input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <i>12</i> db	TRIP SENS: <i>0</i> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE		NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK		ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <i>IN line</i>		NO. OF POSITIONS: <i>1</i>	INLINE SPACING: <i>880</i>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: <i>20</i>		HOLE DEPTH: <i>75</i>		SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	
RECEIVER	TYPE: <i>RSC-20d</i>		PATTERN: <i>IN line</i>		NO. OF ELEMENTS: <i>18</i>		INLINE SPACING: <i>18'</i>	LATERAL SPACING:		LATERAL OFFSET:	
	CONNECTION: <i>Series-Parallel</i>		RESISTANCE: _____ ohms		STAGGER:		LENGTH:	WIDTH:	LATERAL OFFSET:		
SPREAD	NO. OF GROUPS: <i>48</i>		GROUP INTERVAL: <i>220'</i>		SHOTPOINT INTERVAL: <i>880'</i>		FOLD: <i>6</i>	DIRECTION OF PROGRESSION: <i>STON</i>		LEADING GROUP: <i>48</i>	
	OFFSET GROUP 1: <i>5610'</i>		OFFSET GROUP 2: <i>550'</i>		OFFSET GROUP 25: <i>550'</i>		OFFSET GROUP 48: <i>5610'</i>				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 48		TR 49 to 96		SHOT										SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SEY	TR 1-48		TR 49-96					
														HT.	REC.	HT.		REC.			
551	751062	2856			20	6741	200	E	48	52+3	→	65+2	4								
60		2857			20	6742			45	53+3	→	66+2									
61		2858			20	6743			49	54+3	→	67+2									
62		2859			20	6744			53	55+3	→	68+2									
63		2860			20	6745			57	56+3	→	69+2									
64		2861			20	6746			25	57+3	→	70+2	5								
65		2862			20	6747			29	58+3	→	71+2									
66		2863			20	6748			33	59+3	→	72+2									
67		2864			20	6749			37	60+3	→	73+2									
68		2865			20	6750			41	61+3	→	74+2									
69		2866			20	6751			45	62+3	→	75+2									
70		2867			20	6752			49	63+3	→	76+2									
71		2868			20	6753			53	64+3	→	77+2									
72		2869			20	6754			57	65+3	→	78+2									
73		2870			20	6755			55	66+3	→	79+2	6								
74		2871			20	6756			59	67+3	→	80+2									
75		2872			20	6757			63	68+3	→	T-2									
76		2873			20	6758			67	69+3	→	T-6									
77		2874			20	6759			71	70+3	→	T-10									
378		2875			20	6760			75	71+3	→	T-14									

