


LAND SEISMIC RECORDING LOG

	CLIENT: Hosky	PROSPECT: NPR-A	AREA:	LINE NO: B-6A	
PARTY NO: 1182		INST. ENG: Jerry Windham		DATE: MO 2 DAY 1 YR 78	
LEAVE CAMP - 0700		ARRIVE FIELD - 0730		LEAVE FIELD 0935	
ARRIVE CAMP 1945					
INSTRUMENT (9-TRACK)		TYPE: <input checked="" type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER		RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		GAIN CONSTANT: (1) (2) (3) (4) (5) (6) (7)	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS: 1-48		AUXILIARY DATA:	
DATA CHANNEL NOS: 1-48				AUXILIARY CHANNEL NOS:	
PARAMETER		RECORD LENGTH: 2 sec		SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: 18 db	
CFS I		TYPE STACK:		GATE LENGTH:	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: Single Hole	
RECEIVER		TYPE: GSC-200		PATTERN: In-line	
SPREAD		NO. OF GROUPS: 24		GROUP INTERVAL: 55'	
DIAGRAMS/MISC. INFORMATION:		OFFSET GROUP 1: 1402.5'		OFFSET GROUP 24: 137.5'	



SHOTPOINT	TR 1 to 18		TR 19 to 36		SHOT		SPREAD		REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-18	TR 19-36	TR 37-54
1	7191	1015	1191	1015	10	71	1	137.5	SW	3	T26 → Sp 7+2				
2		1196			10	71	2			7	T22 → Sp 8+2				1120
3		1197			10	71	3			11	T18 → Sp 9+2				1124
4		1198			10	71	4			15	T14 → Sp 10+2				1130
5		1199			10	71	5			19	T10 → Sp 11+2				1136
6		1200			10	71	6			23	T6 → Sp 12+2				1140
7		1201			10	71	7			27	T2 → Sp 13+2				1146
8		1202			10	71	8			31	T3 → Sp 14+2				1151
9		1203			10	71	9			35	Sp 2+3 → Sp 15+2				1156
10		1205			10	71	10			39	Sp 3+3 → Sp 16+2	File # 1204 Mis Fire			1159
11		1206			10	71	11			43	Sp 4+3 → Sp 17+2				1204
12		1208			10	71	12			47	Sp 5+3 → Sp 18+2				1209
13		1208			10	71	13			51	Sp 6+3 → Sp 19+2				1213
14		1209			10	71	14			7	Sp 7+3 → Sp 20+2	2 Waiting on Drills			1635
15		1210			10	71	15			11	Sp 8+3 → Sp 21+2				1645
16		1211			10	71	16			15	Sp 9+3 → Sp 22+2				1650
17		1212			15	118	17			19	Sp 10+3 → Sp 23+2				1657
18		1213			10	71	18			23	Sp 11+3 → Sp 24+2				1703
19		1214			2 1/2	119	19			27	Sp 12+3 → Sp 25+2				1710
20		1215			10	71	20			31	Sp 13+3 → Sp 26+2				1720

13- Hours Recording time

LAND SEISMIC RECORDING LOG


	CLIENT: Husky	PROSPECT: NPR-A	AREA:	LINE NO: B-6A								
	PARTY NO: 1182	INST. ENG: Lenny Wurdh		DATE: MO 2 DAY 1 YR 78								
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS: 6	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 2 TRACK	FORMAT: B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (M) <input type="checkbox"/> 712 BPI	<input type="checkbox"/> 800 BPI	<input checked="" type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: 24 db	INPUT IMPEDANCE: _____ ohms	(1)	(2)	(3)	(4)	(5)	(6)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: 2 sec	SAMPLE RATE: <input checked="" type="checkbox"/> 1 sec <input type="checkbox"/> 4 ms	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. Out HZ SLOPE	LO CUT HZ SLOPE	FREQ. 756 HZ SLOPE 72	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT					
DISPLAY	MODE: <input checked="" type="checkbox"/> MAG <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 db	TRIP SENS: 18 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY				
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	P.C.U. NORM./ALT SW.					
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Single hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
RECEIVER	TYPE: GSC-200	PATTERN: Inline	NO. OF ELEMENTS: 3	INLINE SPACING: 3'	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: 24	GROUP INTERVAL: 55'	SHOTPOINT INTERVAL: 220'	FOLD: 6	DIRECTION OF PROGRESSION: NE to SW	OFFSET GROUP 1: 1402.5'	OFFSET GROUP 2: 24	OFFSET GROUP 3: 25	OFFSET GROUP 4: 1402.5'	LEADING GROUP: 48		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 48		TR 17 to 24		SHOT				SPREAD			REMARKS	CORR. STACK							
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET	TR 1-48	TR 48-96	TR 1-48	TR 48-96			
21	1218	10	17	22	23	26	27	29	30	32	35	37								
21	1218	10	17	22	23	26	27	29	30	32	35	37	35	Sp14+3 → Sp27+2	File # 1216, 1217 misfire					1728
22	1219	11	17	22	23	26	27	29	30	32	35	37	39	Sp15+3 → Sp28+2						1735
23	1220	12	17	22	23	26	27	29	30	32	35	37	43	Sp16+3 → Sp29+2						1742
24	1221	13	17	22	23	26	27	29	30	32	35	37	47	Sp17+3 → Sp30+2						1753
25	1222	14	17	22	23	26	27	29	30	32	35	37	51	Sp18+3 → Sp31+2						1756
26	1223	15	17	22	23	26	27	29	30	32	35	37	55	Sp19+3 → Sp32+2						1800
27	1224	16	17	22	23	26	27	29	30	32	35	37	11	Sp20+3 → Sp33+2	3	Waiting on Drills				1850
28	1225	17	17	22	23	26	27	29	30	32	35	37	15	Sp21+3 → Sp34+2						1900
29	1227	19	17	22	23	26	27	29	30	32	35	37	19	Sp22+3 → Sp35+2	File # 1226 misfire					1912
30	1228	20	17	22	23	26	27	29	30	32	35	37	23	Sp23+3 → Sp36+2						1917
31	1229	21	17	22	23	26	27	29	30	32	35	37	27	Sp24+3 → Sp37+2						1921
32	1230	22	17	22	23	26	27	29	30	32	35	37	31	Sp25+3 → Sp38+2						1926
33	1231	23	17	22	23	26	27	29	30	32	35	37	35	Sp26+3 → Sp39+2						1930

LAND SEISMIC RECORDING LOG

	CLIENT: Hosky	PROSPECT: NPR-A	AREA:	LINE NO: B-6A					
	PARTY NO: 1182	INST. ENG: Left camp-0700	Arrived field 07:16	DATE: MO 2 DAY 2 YR 78					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 2 TRACK <input type="checkbox"/> 1 TRACK	FORMAT: B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: 1-48	DATA CHANNEL NOS: 1-48	(ON MAG TAPE)			AUXILIARY DATA:	AUXILIARY CHANNEL NOS:		
PARAMETER	RECORD LENGTH: 2 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. Out	LO CUT HZ SLOPE	H1 CUT HZ SLOPE 72	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT	AMPLIFIER DIRECT	INITIAL GAIN: 18 db	JRIP SENS: 18 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE:	NUMBERS ON MAG TAPE	DOWNBREAK UPBREAK ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Single Hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: GSC-200	PATTERN: Inline	NO. OF ELEMENTS: 3	INLINE SPACING: 3'	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS: 24	GROUP INTERVAL: 55'	SHOTPOINT INTERVAL: 220'	FOLD: 6	DIRECTION OF PROGRESSION: NE to SW	OFFSET GROUP 1: 1402.5'	OFFSET GROUP 24: 137.5'	OFFSET GROUP 48: 1402.5ft	LEADING GROUP: 48



SHOTPOINT	TR. 1 to 38		TR. 19 to 38		SHOT		SPREAD		REMARKS: Daily tests File # 1232 → 1245 File # 1246 TTB	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		HI	REC.	HI	REC.
24	7511	1665	1247		10	71	1	15	Sp27+3 → Sp40+2				
35			1248		10	71	2	19	Sp28+3 → Sp41+2				
36			1249		10	71	3	23	Sp29+3 → Sp42+2				
37			1250		10	71	4	27	Sp30+3 → Sp43+2				
38			1251		10	71	5	31	Sp31+3 → Sp44+2				
39			1252		10	71	6	35	Sp32+3 → Sp45+2				
40			1253		10	71	7	39	Sp33+3 → Sp46+2				
41			1254		10	71	8	43	Sp34+3 → Sp47+2				
42			1255		10	71	9	47	Sp35+3 → Sp48+2				
43			1256		10	71	10	51	Sp36+3 → Sp49+2	WOOD to 1100			
44			1257		10	71	11	55	Sp37+3 → Sp50+2				
45			1258		10	71	12	59	Sp38+3 → Sp51+2				
46			1259		10	71	13	63	Sp39+3 → Sp52+2				
47			1260		10	71	14	67	Sp40+3 → Sp53+2				
48			1261		10	71	15	71	Sp41+3 → T2				
49			1262		10	71	16	75	Sp42+3 → T6				
50			1263		10	71	17	79	Sp43+3 → T10				
51			1364		10	71	18	83	Sp44+3 → T14				
52			1265		10	71	19	87	Sp45+3 → T18				
53			1266		10	71	20	91	Sp46+3 → T22				
54			1267		10	71	21	95	Sp47+3 → T26				

FOE