



LAND SEISMIC RECORDING LOG

2

	CLIENT: <u>HUSKY</u>	PROSPECT: <u>SOUTH FOOTHILLS</u>	AREA: <u>NPR-A</u>	LINE NO: <u>R4</u>								
	PARTY NO: <u>1186</u>	INST. ENG: <u>REM</u>		DATE: <u>MO 5 DAY 2 YR 78</u>								
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III	<input type="checkbox"/> DFS IV	<input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK	FORMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI	(HI) <input type="checkbox"/> 712 BPI	<input type="checkbox"/> 1000 BPI
	<input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-48 & 49-96		<input type="checkbox"/> DFS III	<input type="checkbox"/> DFS IV	<input type="checkbox"/> OTHER	<input type="checkbox"/> 21 TRACK		<input type="checkbox"/> UNGAPPED			
CONFIGURATION (MAG TAPE)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC	<input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____			
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____		FREQ. _____	H1 CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	JRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____		NUMBERS ON MAG TAPE: _____	DOWNBREAK UPBREAK: _____	ON DISPLAY			
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM. ALT SW. _____					
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	OFFSET GROUP: _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____				



DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT				SPREAD			REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		OFF	TR 1-48	TR 48-96	REC.	REC.	
56	722523	17	17	22	195	105	10		E	9	73-20	7-8						
57		20			105	105	30		S	17	73-22	8-8						
58		21			105	105				25	73-24	9-8						
59		22			105	105				33	73-16	10-8						
60		23			105	105				41	73-5	11-8						
61		24			105	105				49	1-1	12-8						
62		25			105	105	25		S	9	2-1	13-8	10					
63		26			105	105				17	3-1	14-8						
64		27			105	105				25	4-1	15-8						
65		28			105	105				33	5-1	16-8						
66		29			105	105				41	6-1	17-8						
67		30			105	105				49	7-1	18-8						
68		31			105	105	30		E	9	8-1	19-8	10					
69		32			105	105	50		N	17	9-1	20-8						
					TAPE CHANGE													
70	722524	33			105	105	40											
71		35			105	105				25	10-1	21-8						
72		36			105	105				33	11-1	22-8						
73		37			105	105				41	12-1	23-8						
74		38			105	105				49	13-1	24-8						

DUMMY RECORD
F# 34 MISSFIRE

LAND SEISMIC RECORDING LOG

3

	CLIENT: <u>HUSKY</u>	PROSPECT: <u>SOUTH FOOTHILLS</u>	AREA: <u>NPR-A</u>	LINE NO: <u>R4</u>					
	PARTY NO: <u>1186</u>	INST. ENG: <u>REID</u>		DATE: <u>MO 5 DAY 2 YR 74</u>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> SEG <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: (1) (2) (3) (4) (5) (6) (7)	INPUT IMPEDANCE: ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:					
	DATA CHANNEL NOS.:			AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. _____	LO CUT HZ SLOPE _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: db	TRIP SENS: db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: CHG/HOLE: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	CONNECTION:	PATTERN: RESISTANCE: ohms	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	OFFSET GROUP 1: _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT			SPREAD			REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET DIR	CDP SWITCH	LINE GROUPS	SET UP		TR 1-24 REC.	TR 48-96 REC.	TR 48-96 REC.
20	TR 25-48	39			105	105		9	14-1	25-8	22			
21		40			105	105		17	15-1	26-8				
22		41			105	105	25 S	25	16-1	27-8				
23		42			105	105		33	17-1	28-8				
24		43			105	105		41	18-1	29-8				
25		44			105	105		49	19-1	30-8				
26		45			105	105		9	20-1	31-8	28			
27		46			105	105	75 E	17	21-1	32-8				
28		47			105	105		25	22-1	33-8				
29		48			105	105		33	23-1	34-8				
30		49			105	105	50 N 40 W	41	24-1	35-8				
31		50			105	105	170 S	49	25-1	36-8				
32		51			105	105	700 E	9	26-1	37-8	34			
33		52			105	105	25 E	17	27-1	38-8				
		TR 48-96			C H A N G E									
	TR 25-48	53												
34		54			105	105		25	28-1	39-8				
35		55			105	105	25 N	33	29-1	40-8				
36		56			105	105		41	30-1	41-8				
37		57			105	105		49	31-1	42-8				

DUMMY RECORD

TR# 44 DEAD

LAND SEISMIC RECORDING LOG



4

	CLIENT: <u>Husky</u>	PROSPECT: <u>SOUTH FOOTHILLS</u>	AREA: <u>NPR-A</u>	LINE NO: <u>R4</u>	
	PARTY NO: <u>1186</u>	INST. ENG: <u>Reid</u>		DATE: <u>5 DAY 2 YR 78</u>	
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS <input type="checkbox"/> 9 TRACK <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> EVENS <input type="checkbox"/> 21 TRACK		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER <input type="checkbox"/> DFS IX		FOPMAT: <input type="checkbox"/> GAPPED <input type="checkbox"/> GAPPED SEG <input type="checkbox"/> UNGAPPED
	NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: _____
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____		AUXILIARY DATA: _____		
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)		AUXILIARY CHANNEL NOS.: _____		
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input type="checkbox"/> IFP <input type="checkbox"/> FINAL	FILTERS: LO CUT HI CUT NOTCH <input type="checkbox"/> IN HZ SLOPE HZ SLOPE FILTER: <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/>	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____
	CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____
	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____
	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT			SPREAD			REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 41-44	TR 45-48
38	1513	1518	17	22	23	26	27	29	30	32	35	37		
39	1518	1518				105	105			9	32-1	43-8		
40	1518	1518				105	105			17	33-1	44-9		
41	1518	1518				105	105			25	34-1	45-8		
42	1518	1518				105	105			33	35-1	46-8		
43	1518	1518				105	105			41	36-1	47-1		
44	1518	1518				105	105			49	37-1	48-8		
45	1518	1518				105	105			9	38-1	49-8	46	1-44 SASHED
46	1518	1518				105	105			17	39-1	50-9		
47	1518	1518				105	105			25	40-1	51-8		
48	1518	1518				105	105			33	41-1	52-8		
49	1518	1518				105	105			41	42-1	53-8		
50	1518	1518				105	105			49	43-1	54-8		

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>SOUTH FOOT HILLS</u>	AREA: <u>NPR-A</u>	LINE NO: <u>5</u>	
PARTY NO: <u>1186</u>		INST. ENG: <u>TERRY + REID</u>		DATE: <u>MO 5 DAY 3 YR 78</u>	
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS	<input type="checkbox"/> 9 TRACK	FORMAT: <u>7</u>
	<input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> EVENS	<input type="checkbox"/> 21 TRACK	SEG: <u>7</u>
NO. BYTES IN HEADER REC: <u>128</u>		NO. BYTES IN RECORD ID: <u>254</u>		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>96</u> db
CONFIGURATION (MAG TAPE)			AUXILIARY DATA:		
FIELD TRACE NOS.: <u>1-96</u>			(1) (2) (3) (4) (5) (6) (7)		
DATA CHANNEL NOS.: <u>1-96</u>			AUXILIARY CHANNEL NOS.: <u>975 975 975</u>		
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	FILTERS:	
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER	<input type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	<input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FREQ: <u>8</u>	LO CUT: <u>18</u>
CFS I	TYPE STACK:	INITIAL GAIN: <u>24</u> db	TRIP SENS: <u>18</u> db	FREQ: <u>128</u>	HI CUT: <u>72</u>
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE	PATTERN: <u>SINGULAR HOLE</u>	NO. OF POSITIONS:	POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK
RECEIVER	TYPE: <u>GSC 100</u>	CHG/ HOLE: <u>105</u>	INLINE SPACING:	NOISE REDUCTION:	R.C.U. NORM./ALT SW.
SPREAD	NO. OF GROUPS: <u>96</u>	HOLE DEPTH: <u>105</u>	LATERAL SPACING:	NOISE THRESHOLD:	

DIAGRAMS/MISC. INFORMATION: 1
N x 55 1 55 49 96
5225 55 5225 x 5

SHOTPOINT	TR. 10		TR. 10		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48	REC.	TR 48-96	REC.
50	722526	81			105	105				9	44-1	55-8	52				
51		82			105	105		115	S	17	45-1	56-8					
52		83			105	105				25	46-1	57-8					
53		84			105	105				33	47-1	58-8					
54		85			105	105				41	48-1	59-8					
55		86			105	105				49	49-1	60-8					
56		87			105	105				9	50-1	61-8	58				
57		88			105	105				17	51-1	62-8					
58		89			105	105				25	52-1	63-8					
59		90			105	105		20	S	33	53-1	64-8					
60		91			105	105				41	54-1	65-8					
61		92			105	105				49	55-1	66-8					
62		93			105	105				33	56-1	67-8	61				
63		94			105	105		35	E	41	57-1	68-8					
64		95			105	105		30	N	49	58-1	69-8					
65		96			105	105		40	N	9	59-1	70-8	61				
66		97			105	105		40	S	17	60-1	71-8					
67		98			105	105				25	61-1	72-8					
68		99			105	105				33	62-1	73-8					
69	722537	100			105	105				41	63-1	74-8					

FILE # 100 DUMMY

LAND SEISMIC RECORDING LOG

6

CLIENT: HUSKY	PROSPECT: SOUTH FOOT HILLS	AREA: UPRA ALASKA	LINE NO: R-4
PARTY NO: 1176	INST. ENG: TERRY & REID	DATE: MO 5 DAY 3 YR 78	

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FORMAT SEG: B	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.			

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:	AUXILIARY DATA:
	DATA CHANNEL NOS.:	AUXILIARY CHANNEL NOS.: 525 525 528

PARAMETER	RECORD LENGTH: 7 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 7 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 22	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS.: 18 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: 105	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	

RECEIVER	TYPE: ESL-20D	PATTERN: LINE	NO. OF ELEMENTS: 9	INLINE SPACING: 15	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: 3x3	RESISTANCE: 240 ohms							


SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 110	SHOTPOINT INTERVAL: PTO	FOLD: 6	DIRECTION OF PROGRESSION: SOUTH
	OFFSET GROUP 1: 5225	OFFSET GROUP: 55	OFFSET GROUP: 55	OFFSET GROUP 48/96: 5225	LEADING GROUP: 96



SHOTPOINT	TR 1 to		TR 2 to		SHOT										SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48	TR 49-96	REC.		TR 1-48	TR 49-96	REC.	
70	7125	102	17	22	23	26	27	29	30	32	35	37	1	64-1	74-7	73					
71		103				105	105						9	65-1	75-7						
72						105	105						77	66-1	77-7						

LAND SEISMIC RECORDING LOG



	CLIENT: HUSKY	PROSPECT: SOUTH FOOTHILLS	AREA: UPRA ALASKA	LINE NO: 7						
	PARTY NO: 1176	INST. ENG: FERRY		DATE: MO 5 DAY 7 YR 28						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI	
	NO. BYTES IN HEADER REC: 128	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	DATA CHANNEL NOS.: 1-96	(ON MAG TAPE)	AUXILIARY DATA:	AUXILIARY CHANNEL NOS.: 305	305	305	305	305	
PARAMETER	RECORD LENGTH: 8 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: FREQ Y	LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 22	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS.: 18 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	P.C.U. NORM./ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	TYPE: GSC-200	PATTERN: IN LINE	NO. OF ELEMENTS: 9	INLINE SPACING: 15	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	CONNECTION: 3X3	RESISTANCE: 240 ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
	NO. OF GROUPS: 96	GROUP INTERVAL: 110	SHOTPOINT INTERVAL: 990	FOLD: 6	DIRECTION OF PROGRESSION: SOUTH					
	OFFSET GROUP 1: 5225	OFFSET GROUP: 55	OFFSET GROUP: 55	OFFSET GROUP 48/96: 5225	LEADING GROUP: 96					



SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT				SPREAD			REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS		REV	TR 1-48	TR 49-96	TR 1-48
72	2225	27	108		105	105				17	66-1	92-Y				
73			108		105	105				25	67-1	78-Y				
74			108		105	105				33	68-1	79-Y				
75			108		105	105				41	69-1	80-Y				
76			108		105	105	160	E		49	70-1	81-Y				
77			108		105	105				9	71-1	82-Y				
78			108		105	105	175	N		17	72-1	83-Y				
79			108		100	100				25	73-1	84-Y				
80			108		105	105				33	74-1	85-Y				
81			108		105	105				41	75-1	86-Y				
82			108		105	105				49	76-1	87-Y				
83			108		105	105				9	77-1	88-Y				
84			108		105	105				17	78-1	89-Y				
85	2225	28	108		105	105	100	N		25	79-1	90-Y	FILE # 121 DUMMY			
86			108		105	105	175	S		33	80-1	91-Y	NO. 12P-HOLE ON SIP 96 1/2" FILE # 123			
87			108		105	105	300	E		41	81-1	92-Y	" " " " 97			
88			108		105	105	180	S		49	82-1	93-Y	TR 96 NOISY			
89			108		105	105	900	E		9	83-1	94-Y				
90			108		105	105				17	84-1	95-Y				
91			108		105	105				25	85-1	96-Y				

LAND SEISMIC RECORDING LOG

8



	CLIENT: HUSKY	PROSPECT: SOUTH FOOTHILLS	AREA: NPR-A ALASKA	LINE NO: R-4																				
PARTY NO: 1186		INST. ENG: TERRY		DATE: MO 5 DAY 4 YR 28																				
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI (HI) <input type="checkbox"/> 1600 BPI	NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: _____		RECORD NUMBERS: _____	<input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms						
	CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: _____			AUXILIARY CHANNEL NOS.: _____			NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: _____		RECORD NUMBERS: _____		GAIN CONSTANT: _____ db		INPUT IMPEDANCE: _____ ohms			
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/>	CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM / ALT SW
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____							
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	CONNECTION: _____	RESISTANCE: _____ ohms													
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96: _____															

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT			SPREAD			REMARKS	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS		TR 1-48	TR 48-96	TR 1-48
90	222528	1130			105	105				33	86-1	92-Y				
93		1131			105	105				41	87-1	98-Y				
94		1132			105	105		250 W		49	88-1	99-Y				
96		1133			105	105		140 N		9	89-1	100-Y	12*90			
96		1134			105	105		590 S		17	90-1	101-Y				
97		1135			105	105		1180 W		25	91-1	102-8				
98		1136			105	105				33	92-1	103-8				
99		1137			105	105				41	93-1	104-8				
100		1138			105	105				49	94-1	105-8				
101		1139			105	105				9	95-1	106-8	103			
102		1140			105	105				17	96-1	107-8				
103	222529	1142			105	105				25	97-1	108-8	FILE # 141 DUMMY			
104		1143			105	105		135 S		33	98-1	109-8				
105		1144			105	105				41	99-1	110-8				
106		1145			105	105				49	100-1	111-8				
107		1146			105	105				9	101-1	112-8	109			
108		1147			105	105				17	102-1	113-8				
109		1148			105	105				25	103-1	114-8				
110		1149			105	105				33	104-1	115-8				
111		1150			105	105				41	105-1	116-8				

LAND SEISMIC RECORDING LOG

9

	CLIENT: HUSKY	PROSPECT: SOUTH FOOTHILLS	AREA: UPR-A ALASKA	LINE NO: R-4					
PARTY NO: 1186		INST. ENG: TERRY		DATE: MO 5 DAY 4 YR 78					
INSTRUMENT [9-TRACK]	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION [MAG TAPE]	FIELD TRACE NOS. _____			AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____					
	DATA CHANNEL NOS. _____ [ON MAG TAPE]			AUXILIARY CHANNEL NOS. _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____ HZ HI CUT _____ HZ	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH	LINE GROUPS		SET UP	TR 1-24	TR 48-96	TR 1-24	TR 48-96
1112	7202529	1151			105	105				49	106-1	117-8	10A				
1113		1152			105	105				9	107-1	118-8	15				
1114		1153			105	105				17	108-1	119-8					
1115		1154			105	105				25	109-1	120-8					
1116		1155			105	105				33	110-1	121-8					
1117		1156			105	105				41	111-1	122-8					
1118		1157			105	105				49	112-1	123-8					
1119		1158			105	105				9	113-1	124-8	12A				
1120		1159			105	105				17	114-1	125-8					
1121		1160			105	105				25	115-1	126-8					
1122	7202530	1161			105	105				33	116-1	127-8		FILE # 161 DUMMY			
1123		1162			105	105				41	117-1	128-8					
1124		1163			105	105				49	118-1	129-8					

LAND SEISMIC RECORDING LOG

9



CLIENT: HUSKY		PROSPECT: SOUTH FOOTHILLS		AREA: NPR-A ALASKA		LINE NO: R-4	
PARTY NO: 1186		INST. ENG: TERRY		DATE: MO. 5 DAY 5 YR 77			
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC: 128		TYPE: <input type="checkbox"/> DFS <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER NO. BYTES IN RECORD ID: 254		TRACK: <input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK RECORD NUMBERS: DEC. OCT.		GAIN CONSTANT: 36 db INPUT IMPEDANCE: _____ ohms	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: 1-96 DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)		AUXILIARY DATA: AUXILIARY CHANNEL NOS.: SP³ SP⁵ 518		PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input checked="" type="checkbox"/> 1400 BPI		GAPPED <input type="checkbox"/> UNGAPPED <input type="checkbox"/>	
PARAMETER: RECORD LENGTH: 8 sec		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms INITIAL GAIN: 24 db		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. 8 TO CUT HZ SLOPE 18	
DISPLAY: MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		GATE LENGTH: _____		RECORD REJECTION: _____		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I: TYPE STACK: _____		NOISE REDUCTION: _____		NOISE THRESHOLD: _____		CORR. SCALING: _____	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE HOLE		NO. OF POSITIONS: _____		LATERAL SPACING: _____	
RECEIVER: TYPE: GS1-200		CONNECTION: 3 X 3		RESISTANCE: 240 ohms		STAGGER: _____	
SPREAD: NO. OF GROUPS: 96		GROUP INTERVAL: 110		SHOTPOINT INTERVAL: 180		FOLD: 6	
OFFSET GROUP 1: 5225		OFFSET GROUP: 55		OFFSET GROUP 48/96: 55		DIRECTION OF PROGRESSION: SOUTH	

DIAGRAMS/MISC. INFORMATION: **TR#1 N 5225 85 55 5225 TR#9 S 5.**

SHOTPOINT	TR 1 to		TR 2 to		SHOT			SPREAD			REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	COP SWITCH	LINE GROUPS		TR 1-48	TR 49-96
125	722530	175			120	105			9	119-1 130-8			
126		176			120	105			17	120-1 131-8			
127		177			120	105			25	121-1 132-8			
128		178			100	105			33	122-1 133-8			
129		179			100	105			41	123-1 134-8			
130		180			100	105			49	124-1 135-8			
131		181			100	105			9	125-1 136-8	33	TR 61+62 BAD	
132		182			100	105			17	126-1 137-8			
133		183			100	105			25	127-1 138-8			
134		184			100	105			33	128-1 139-8			
135		185			105	105			41	129-1 140-8			
136		186			105	105			49	130-1 141-8			
137		187			105	105			9	131-1 142-8	39		
138		188			105	105			17	132-1 143-8			
139	722531	190			105	105	110 S		25	133-1 144-8		FILE # 189 DUMMY	
140		191			105	105			33	134-1 145-8			
141		192			105	105			41	135-1 146-8			
142		193			105	105	110 N		49	136-1 147-8			
143		194			105	105	130 S		9	137-1 148-8	45		
144		195			105	105			17	138-1 149-8		TR 5 BAD	

LAND SEISMIC RECORDING LOG

10

	CLIENT: <u>HUSKY</u>	PROSPECT: <u>SOUTH FOOTHILLS</u>	AREA: <u>NPRA ALASKA</u>	LINE NO: <u>R-4</u>	
	PARTY NO: <u>1186</u>	INST. ENG: <u>TERRY</u>		DATE: <u>MO 5 DAY 5 YR 78</u>	
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> 9 TRACK FORMAT: <input type="checkbox"/> GAPPED PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> EVENS <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER <input type="checkbox"/> 21 TRACK SEG <input type="checkbox"/> UNGAPPED (1) (2) (3) (4) (5) (6) (7)		NO. BYTES IN HEADER REC: NO. BYTES IN RECORD ID: NO. BYTES PER SCAN: RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT GAIN CONSTANT: db INPUT IMPEDANCE: ohms.		
	CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: DATA CHANNEL NOS.: (ON MAG TAPE)		AUXILIARY DATA: AUXILIARY CHANNEL NOS.:	
PARAMETER	RECORD LENGTH: sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: LO CUT HZ SLOPE HI CUT HZ SLOPE NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: db	TRIP SENS: db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION: NOISE THRESHOLD: CORR SCALING: R.C.U. NORM./ALT SW.	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: CHG/ HOLE: HOLE DEPTH:	NO. OF POSITIONS: SWEEP POSITION:	INLINE SPACING: SWEEP START:	LATERAL SPACING: SWEEP END:
RECEIVER	TYPE: CONNECTION:	PATTERN: RESISTANCE: ohms	NO. OF ELEMENTS: STAGGER:	INLINE SPACING: LENGTH:	LATERAL SPACING: WIDTH: LATERAL OFFSET:
SPREAD	NO. OF GROUPS: OFFSET GROUP 1:	GROUP INTERVAL: OFFSET GROUP:	SHOTPOINT INTERVAL: OFFSET GROUP:	FOLD: OFFSET GROUP 48/96:	DIRECTION OF PROGRESSION: <u>SOUTH</u> LEADING GROUP: <u>96</u>

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 10		SHOT				SPREAD			REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		101-10	101-10	101-10	101-10
145	722531	196			105	105		30 S.	25	139-1	150-8					
146		197			105	105		30 N	33	140-1	151-8					
147		198			105	105			41	141-1	152-8					
148		199			105	105			49	142-1	153-8					
149		200			105	105			9	143-1	154-8	151				
150		201			105	105			17	144-1	155-8					
151		202			105	105			25	145-1	156-8					
152		203			105	105			33	146-1	157-8					
153		204			105	105			41	147-1	158-8					
154		205			105	105		30 S.	49	148-1	159-8					
155		206			105	105		30 N	9	149-1	160-8	157				
156		207			105	105		8 S.	17	150-1	161-8					
157		208			105	105			25	151-1	162-8					
158	722533	210			105	105		30 N	33	152-1	163-8					
159		211			105	105			41	153-1	164-8					
160		212			105	105			49	154-1	165-8					
161		213			105	105			9	155-1	166-8	163				
162		214			105	105			17	156-1	167-8					
163		215			105	105			25	157-1	168-8					
164		216			105	105			33	158-1	169-8					

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: SOUTH FOOTHILLS	AREA: NPR-A ALASKA	LINE NO: 17 R-4	
	PARTY NO: 1176	INST ENG: REID & TERRY		DATE: MO 5 DAY 2 YR 77	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC: 128	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 21-48 & 49-96 NO. BYTES IN RECORD ID: _____	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 21 TRACK RECORD NUMBERS: <input checked="" type="checkbox"/> SEC <input type="checkbox"/> OCT	FOPMAT: B SEG: _____ GAPPED: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 350 BPI <input type="checkbox"/> 600 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
-------------------------	---------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96 DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)	AUXILIARY DATA: AUXILIARY CHANNEL NOS.: 3P0 5P0 5TB
-----------------------------	-------------------------------------------------------------------------------	---------------------------------------------------------------

PARAMETER	RECORD LENGTH: 5 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: LO CUT _____ HZ H1 CUT _____ HZ SLOPE 1X	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
-----------	------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------	--------------------------------------------------------------------------------------

DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS: 18 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY
---------	-----------------------------------------------------------------------------------------------------------------------------------------------	----------------------------	-------------------------	--------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
--------	-------------------------------------------------------------------------------------------------------------------------	-----------------------------	-------------------------	-----------------------	------------------------	----------------	---------------	--------------	-----------------------



RECEIVER	TYPE: GSC-20D	PATTERN: INLINE	NO. OF ELEMENTS: 9	INLINE SPACING: 15	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
----------	----------------------	------------------------	---------------------------	---------------------------	------------------------	----------------	---------------	--------------	-----------------------

SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 110	SHOTPOINT INTERVAL: 700	FOLD: 6	DIRECTION OF PROGRESSION: SOUTH
--------	--------------------------	----------------------------	--------------------------------	----------------	----------------------------------------

DIAGRAMS/MISC. INFORMATION:	TR#1 N. _____ 5225'	TR#48 N. _____ 55'	TR#49 N. _____ 55'	TR#96S N. _____ 5225'	* NOTE RECORD NUMBER ON TAPE - JUMPED FROM #251 BACK TO #129
-----------------------------	------------------------	-----------------------	-----------------------	--------------------------	---------------------------------------------------------------------

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD				REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SET UP		TR 1-48	TR 48-96	TR 1-48	TR 48-96
1185	120	129	117	22	105	105	40	N	9	179-1	190-8	179					
1186		130			105	105			17	180-1	191-8						
1187		131			105	105			25	181-1	192-8						
1188		132			105	105			33	182-1	193-8						
1189		133			105	105			41	183-1	194-8						
1190		134			105	105	220	N	47	184-1	195-8						
1191		135			105	105			9	185-1	196-8	119					
					TAPE CHANGE												
1192	120	136			105	105			49	190-1	201-8						
1193		137			105	105			25	187-1	194-8						
1194		138			105	105			33	188-1	197-8						
1195		139			105	105			41	189-1	200-8						
1196		140			105	105			49	190-1	201-8						
1197		141			105	105			9	191-1	202-8	119					
1198		142			105	105			17	192-1	203-8						
1199		143			105	105			25	193-1	204-8						
1200		144			105	105			33	194-1	205-8						
1201		145			105	105	156	S	41	194-1	205-8						
1202		146			105	105	410	E	49	196-1	207-8						



LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: SOUTH FOOTHILLS	AREA: NPR-A	LINE NO: 14	
PARTY NO: 1186		INST. ENG: REID & TERRY		DATE: MO 5 DAY 7 YR 77	
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		ODDS & EVENS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		FORMAT: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.:		DATA CHANNEL NOS.:		AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)	
PARAMETER RECORD LENGTH: _____ sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. _____ ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	
DISPLAY MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT		INITIAL GAIN: _____ db		TRIP SENS: _____ db	
CFS I TYPE STACK:		GATE LENGTH:		NOISE REDUCTION:	
SOURCE TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN:		NO. OF POSITIONS:	
RECEIVER TYPE:		PATTERN:		NO. OF ELEMENTS:	
SPREAD NO. OF GROUPS:		GROUP INTERVAL:		SHOTPOINT INTERVAL:	
DIAGRAMS/MISC. INFORMATION:		RESISTANCE: _____ ohms		STAGGER:	
		CHG/ HOLE:		HOLE DEPTH:	
		SWEEP POSITION:		SWEEP START:	
		LATERAL SPACING:		LATERAL SPACING:	
		SWEEP END:		SWEEP LENGTH:	
		LENGTH:		SWEEP TAPER:	
		WIDTH:		PHASE COMP:	
		LATERAL OFFSET:		LATERAL OFFSET:	
		DIRECTION OF PROGRESSION: SOUTH		LEADING GROUP: 96	
		OFFSET GROUP:		OFFSET GROUP 48/96:	


SHOTPOINT	TR. 1 to		TR. 2 to		SHOT				SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR. 1-48
203	2025319	148			105	105	100	N	9	197-1	208-8		
204		149			100	105			17	198-1	209-8		
205		150			100	105	20	N	25	199-1	210-8		
206		151			100	105			33	200-1	211-8		
207		152			105	105	40	E	41	201-1	212-8		
208		153			105	105	40	N	49	202-1	213-8		
209		154			105	105	30	E	9	203-1	214-8		
210		155			105	105	45	E	17	204-1	215-8		
211	222536	157			105	105	35	E	25	205-1	216-8		
212		158			105	105	35	E	33	206-1	217-8		
213		159			105	105	35	E	41	207-1	218-8		
214		160			105	105	45	E	49	208-1	219-8		
215		161			105	105	40	E	9	209-1	220-8		
216		162			105	105	20	N	17	210-1	221-8		
217		163			105	105	30	N	25	211-1	222-8		
218		164			105	105	45	E	33	212-1	223-8		
219		165			105	105	20	E	41	213-1	224-8		
220		166			105	105	25	E	49	214-1	225-8		
221		167			105	105	30	E	9	215-1	226-8		
222		168			105	105	20	N	17	216-1	227-8		

FILE # 156 SUMMARY

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: SOUTH FOOTHILLS	AREA: UPR A ALASKA	LINE NO: 15	
PARTY NO: 1186		INST. ENG: REID & TERRY		DATE: NO 5 DAY 2 YR 74	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:				
	DATA CHANNEL NOS.:			AUXILIARY CHANNEL NOS.:				
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	H1 CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW: _____	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____
	CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____
	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: SOUTH	LEADING GROUP: 96		
	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96: _____				




SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT		SPREAD		REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	SY	TR 48-96	TR 48-96
223	722535	169			105	105				25	217-1	227-8			
224		170			105	105				33	218-1	229-8			
225		171			105	105				41	219-1	230-8			
226		172			105	105				49	220-1	231-8			
227		173			105	105				9	221-1	232-8			
228		174			105	105				17	222-1	236-2			
229		176			105	105				25	223-1	240-2			
230	722536	178			105	105				33	224-1	244-2			
231		179			105	105				41	225-1	248-2			
232		180			105	105		30 N		49	226-1	252-2			

LAND SEISMIC RECORDING LOG

16



	CLIENT: <u>HUSKY</u>	PROSPECT: <u>SOUTH FOOTHILLS</u>	AREA: <u>N.P.R.A.</u>	LINE NO: <u>R4</u>	
	PARTY NO: <u>1186</u>	INST. ENG: <u>TERRAP BEID</u>	EXPERIMENTAL WORK		DATE: <u>MO 5 DAY 8 YR 78</u>
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> 21 TRACK	POPMAT: <u>SEG</u>	<input type="checkbox"/> GAPPED
	<input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> 22 TRACK	SEG	<input checked="" type="checkbox"/> UNGAPPED
	NO. BYTES IN HEADER REC: <u>128</u>	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: <u>254</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>36</u> db
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>			AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____	
	DATA CHANNEL NOS.: <u>1-96</u> (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: <u>SPS SPS STA</u>	
PARAMETER	RECORD LENGTH: <u>8</u> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	FILTERS: FREQ. <u>9</u> LO CUT <u>1K</u> HZ SLOPE <u>12</u> HI CUT _____ HZ SLOPE _____	
DISPLAY	MODE: <input checked="" type="checkbox"/> RGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER	INITIAL GAIN: <u>24</u> db	TRIP SENS: <u>14</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____ NOISE THRESHOLD: _____ CORR. SCALING: _____	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE	PATTERN: <u>SINGLE HOLE</u>	NO. OF POSITIONS: <u>1</u>	INLINE SPACING: _____	LATERAL SPACING: _____
	<input type="checkbox"/> VIBROSEIS	CHG/ HOLE: <u>100</u>	NOLE DEPTH: <u>105</u>	SWEEP POSITION: _____	SWEEP START: _____
RECEIVER	TYPE: <u>G.S.C. 20D</u>	PATTERN: <u>INLINE</u>	NO. OF ELEMENTS: <u>9</u>	INLINE SPACING: <u>15</u>	LATERAL SPACING: _____
	CONNECTION: <u>213</u>	RESISTANCE: <u>240</u> ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____
SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>110</u>	SHOTPOINT INTERVAL: <u>120</u>	FOLD: <u>24</u>	DIRECTION OF PROGRESSION: <u>SOUTH</u>
	OFFSET GROUP: <u>5225</u>	OFFSET GROUP: <u>45 55</u>	OFFSET GROUP: <u>49 55</u>	OFFSET GROUP: <u>5225</u>	LEADING GROUP: <u>96</u>



SHOTPOINT	TR. 1 to		TR. 2 to		SHOT				SPREAD			REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS		HT.	REC.	HT.
233	232537	185			100	105				9	227-1 256-2				8:06
234		186			100	105				11	228-3 257-2				8:08
235		187			100	105				13	229-5 258-2				8:11
236		188			100	105				15	230-7 259-2				8:13
237		189			100	105				17	231-1 260-2				8:15
238		190			100	105				19	232-3 261-2				8:17
239		191			100	105				21	233-5 262-2				8:19
240		192			100	105				23	234-7 263-2				8:20.5
241		193			100	105				25	235-1 264-2				8:22
242		194			100	105				27	236-3 265-2	Hole noise on SP# 238			8:24
243		195			100	105				29	237-5 266-2				8:26
244		196			100	105				31	238-7 267-2				8:28
245		197			100	105				33	239-1 268-2				8:30
246		198			100	105				35	240-3 269-2				8:32
247		199			100	105				37	241-5 270-2				8:34
248		200			100	105				39	242-7 271-2	No Record - Dead Caps			8:36
249		201			100	105				41	243-1 272-2				8:38
250		202			100	105				43	244-3 273-2				8:40
251		203			100	105				45	245-5 274-2				8:42
252	232538	204			100	105				47	246-7 275-2	F# 203 DUMMY			8:44

LAND SEISMIC RECORDING LOG

17

	CLIENT: <u>Husky</u>	PROSPECT: <u>SOUTH FOOTHILLS</u>	AREA: <u>NPR-A</u>	LINE NO: <u>R4</u>	
PARTY NO: <u>1186</u>		INST. ENG: <u>TERRY & REID</u>		DATE: <u>MO 5 DAY 8 YR 88</u>	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> DFS X <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____	AUXILIARY DATA: _____
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)	AUXILIARY CHANNEL NOS.: _____

PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/>	NUMBERS ON MAG TAPE: <input type="checkbox"/>	DOWNBREAK UPBREAK: <input type="checkbox"/>	ON DISPLAY: <input type="checkbox"/>
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.	

SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	

RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INLINE SPACING:	LATERAL SPACING:
	CONNECTION:	RESISTANCE:	STAGGER:	LENGTH:	WIDTH:
					LATERAL OFFSET:



SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:
	OFFSET GROUP 1:	OFFSET GROUP 1:	OFFSET GROUP 1:	OFFSET GROUP 1:	LEADING GROUP:

DIAGRAMS/MISC. INFORMATION: WAIT ON DRILLS 9:00 -> 9:20
WAIT ON DRILLS 10:05 -> 10:43

SHOTPOINT	TR No		TR To		SHOT			SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 41	TR 42	TR 43	TR 44
													HI	REC	HI	REC
253	222538	208			190	105				19	232-1	276-2			8:46	
254		209			190	105				3	233-3	277-2			9:21	
255		210			190	105				5	232-5	278-2			4:24	
256		208			190	105				7	232-7	278-2			9:24	
257		209			190	105				9	233-1	280-2			9:30	
258		210			190	105				11	231-1	281-2			9:32	
259		211			190	105	35	N		13	235-1	282-2			9:35	
260		212			190	105				15	236-1	283-2			9:37	
261		213			190	105				17	237-1	284-2			9:39	
262		214			190	105				19	238-1	285-2			9:41	
263		215			190	105				21	239-1	286-2			9:43	
264		216			190	105				23	240-1	287-2			9:53	
265		217			190	105				25	241-1	288-2			9:55	
266		218			190	105				27	242-1	288-2			9:57	
267		219			190	105				29	243-1	290-2			9:59	
268		220			190	105				31	244-1	291-2			10:01	
269		221			190	105				33	245-1	292-2			10:03	
270		222			190	105				35	246-1	293-2			10:05	
271	222539	224			190	105				37	247-1	294-2			10:47	
272		225			190	105				39	248-1	295-2			10:45	

LAND SEISMIC RECORDING LOG

18



	CLIENT: <u>Husky</u>	PROSPECT: <u>SOUTH FOOTHILLS</u>	AREA: <u>NPR-19</u>	LINE NO: <u>R4</u>					
	PARTY NO: <u>1186</u>	INST. ENG: <u>TERRY REID</u>		DATE: <u>2</u> DAY <u>8</u> YR <u>78</u>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 800 BPI <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) (2) (3) (4) (5) (6) (7)		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> JFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	CONNECTION: _____	PATTERN: _____	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	OFFSET GROUP: _____	OFFSET GROUP #/96: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____	

DIAGRAMS/MISC. INFORMATION: WAIT ON DRIMS 11:24 → 2:37
2:48 → 3:19

SHOTPOINT	TR. 10		TR. 10		SHOT			SPREAD			REMARKS	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-41	TR 42-96	TR 1-41	TR 42-96
270	223539	226			100	105	30	30	N	41	249-1	296-2			10:47	
271		227			100	105	30	30	N	43	250-1	297-2			10:49	
272		228			100	105	30	30	N	45	251-1	298-2			10:51	
273		229			100	105	30	30	N	47	252-1	299-2			10:53	
274		230			100	105	30	30	N	49	253-1	300-2		MOVE UP	10:55	
275		231			100	105	30	30	N	3	254-1	301-2	289		11:14	
276		232			100	105	30	30	N	5	255-1	302-2			11:16	
277		233			100	105	30	30	N	7	256-1	303-2			11:18	
278		234			100	105	30	30	N	9	257-1	304-2			11:20	
279		235			100	105	30	30	N	11	258-1	305-2			11:22	
280		236			100	105	30	30	N	13	259-1	306-2			11:24	
281		237			100	105	30	30	N	15	260-1	307-2			2:37	
282		238			100	105	30	30	N	17	261-1	308-2			2:39	
283		239			100	105	30	30	N	19	262-1	309-2			2:41	
284		240			100	105	30	30	N	21	263-1	310-2			2:43	
285	223540	241			100	105	30	30	N	23	264-1	311-2	F#241	DUMMY RECORD	3:19	
286		242			100	105	30	30	N	25	265-1	312-2			3:21	
287		243			100	105	30	30	N	27	266-1	313-2			3:23	
288		244			100	105	30	30	N	29	267-1	314-2			3:25	
289		245			100	105	30	30	N	31	268-1	315-2			3:27	

LAND SEISMIC RECORDING LOG

19



	CLIENT: <u>HUGHY</u>	PROSPECT: <u>SOUTH FOOTHILLS</u>	AREA: <u>NPR-A</u>	LINE NO: <u>R4</u>					
	PARTY NO: <u>1186</u>	INST. ENG: <u>TERRY REID</u>		DATE: <u>MO 5 DAY 8 YR 78</u>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>SEG</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: [LO] <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI [HI] <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) (2) (3) (4) (5) (6) (7)	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: _____ sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY <input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	CONNECTION:	RESISTANCE: _____ ohms	NO. OF ELEMENTS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	OFFSET GROUP 48/96:	LEADING GROUP:		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT		SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TR 1-48	TR 48-96	
282	225	18	22	23	28	27	29	30	32	35	37			
283	225	18			100	105				33	267-1	316-2	317	
284		248			100	105				35	270-1	317-2		
285		249			100	105				37	271-1	318-2		
286		250			100	105				39	272-1	319-2		
287		251			100	105				41	273-1	320-2		
288		252			100	105				43	274-1	321-2		
289		253			100	105				45	275-1	322-2		
300		254			100	105				47	276-1	323-2		
301		255			100	105				49	277-1	324-2		
302		256			100	105				3	278-1	325-2	313	
303		257			100	105				5	279-1	326-2		
304		258			100	105				7	280-1	327-2		
305		259			100	105	255			9	281-1	328-2		
306		260			100	105				11	282-1	329-2		
307	225	262			100	105	40 N			13	283-1	330-2		F*261 DUMMY RECORD
308		263			100	105				15	284-1	331-2		
309		264			100	105				17	285-1	332-2		
310		265			100	105				19	286-1	333-2		
311		266			100	105				21	287-1	334-2		
312		267			100	105				23	288-1	335-2		

LAND SEISMIC RECORDING LOG

20

	CLIENT: Husky	PROSPECT: SOUTH FOOTHILLS	AREA: NPR-A	LINE NO: R4	
	PARTY NO: 1186	INST. ENG: TERRY & REID		DATE: 5 DAY 8 YR 78	
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS & EVENS <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED <input type="checkbox"/> PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI (M) <input type="checkbox"/> 1000 BPI		
	NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: _____		AUXILIARY DATA: _____		
	DATA CHANNEL NOS: _____ (ON MAG TAPE)		AUXILIARY CHANNEL NOS: _____		
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	JRP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	HI CUT HZ SLOPE: _____
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____
	CHG/HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____
RECEIVER	CONNECTION: _____	PATTERN: _____	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____
				WIDTH: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____
	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____

DIAGRAMS/MISC. INFORMATION:

WAIT ON DRILLS 4:38 → 4:58
5:06 → 5:38
6:00 → 7:10

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH		LINE GROUPS	TR 1-48	TR 49-96	TR 1-48	TR 49-96
313	722541	268			100	105				25	287-1	336-2			4:36	
314		269			100	105		30	S	27	290-1	337-2			4:38	
315		270			100	105		35	S	29	291-1	338-2			4:58	
316		271			100	105		30	S	31	292-1	339-2			5:00	
317		272			100	105				33	293-1	340-2			5:02	
318		273			100	105				35	294-1	341-2			5:04	
319		275			100	105				37	295-1	342-2			5:06	
320		276			100	105				39	296-1	343-2			5:34	
321		277			100	105				41	297-1	344-2			5:40	
322		278			100	105				43	298-1	345-2			5:42	
323		279			100	105				45	299-1	346-2			5:44	
324	722541	280			100	105				47	300-1	347-2			5:45	
325	722542	282			100	105				49	301-1	348-2			5:10	
326	722542	283			100	105				7	302-1	349-2			7:12	
327		284			100	105				5	303-1	350-2			7:14	
328		285			100	105				7	304-1	351-2			7:16	
329		286			100	105				9	305-1	352-2			7:18	
330		287			100	105				11	306-1	353-2			7:20	
331		288			100	105				13	307-1	354-2			7:22	
332		289			100	105				15	308-1	354-2			7:24	

MOVE UP
F# 281 DUMMY RECORD TR#1 DEAD
TR# 7 DEAD
" "
" "
" "
TR#1 DEAD

