

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-4 umiat	AREA: NORTH Slope Alaska	LINE NO: U-1					
	PARTY NO: 1173	INST. ENG: R. Ben. x4 - G. PARKO	Zac Nos 13.0 DRV. 3.0	DATE: MO 03 DAY 19 YR 78					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 2000 ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96				AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)				
PARAMETER	DATA CHANNEL NOS.: _____ (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: _____				
DISPLAY	RECORD LENGTH: 8 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 HZ SLOPE 18	LO CUT HZ SLOPE 70	HI CUT HZ SLOPE 70	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
CFS 1	MODE: <input type="checkbox"/> FLOAT <input checked="" type="checkbox"/> AGC	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 36 db	TRIP SENS: 42 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/>	NUMBERS ON MAG TAPE: <input type="checkbox"/>	DOWNBREAK UPBREAK: <input type="checkbox"/>	ON DISPLAY: <input type="checkbox"/>
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: INLINE	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: D 20-10	PATTERN: INLINE	NO. OF ELEMENTS: _____	RESISTANCE: _____ ohms	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	CONNECTION: SERIES-FAR	RESISTANCE: _____ ohms	SHOTPOINT INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 1200%	OFFSET GROUP 48/96: 10,450	OFFSET GROUP 48/96: 10,450	DIRECTION OF PROGRESSION: NORTH	LEADING GROUP: 1



DIAGRAMS/MISC. INFORMATION: **FILE #1 -> 14 TEST RECORDS**
FILE #10 - LOST

RECORDING CREW WAITING ON DRILL MOST OF DAY - N.B.D.

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT		SPREAD		REMARKS	CORR. STACK							
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		CDP SWITCH	%	LINE GROUPS	#1	RE 21	REC.	RE 22	REC.
1																	
2																	
3																	
4																	
5																	
6																	
7																	
8																	
9																	
10																	
11																	
12																	
13																	
14																	
15																	
16																	
17																	
18																	
19																	
20																	
21																	
22																	
23																	
24																	
25																	
26																	
27																	
28																	
29																	
30																	
31																	
32																	
33																	
34																	
35																	
36																	
37																	
38																	
39																	
40																	
41																	
42																	
43																	
44																	
45																	
46																	
47																	
48																	
49																	
50																	

30 miles

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-4 Unit	AREA: North Slope, Al.	LINE NO: U1	
PARTY NO: 1173		INST. ENG: R. BERTSCH		DATE: MO 3 DAY 20 YR 78	
NO. BYTES IN HEADER REC: 228		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 254	
INSTRUMENT (9-TRACK)		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS: 1-96		AUXILIARY DATA:	
PARAMETER		RECORD LENGTH: 8 sec.		SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db	
CFS I		TYPE STACK:		GATE LENGTH:	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: _____	
RECEIVER		TYPE: D20-10		PATTERN: INLINE	
SPREAD		NO. OF GROUPS: 96		GROUP INTERVAL: 220'	

DIAGRAMS/MISC. INFORMATION:

W.O.D PART OF DAY

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT			SPREAD			REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH	LINE GROUPS #		SET	TR 1-20	TR 21-40	TR 41-60	TR 61-80
1	251148	133	(14000T)	TAPE	110	105			49	7-1	30-4	25				
11		134			110	105			45	8-1	31-4					
12		135			110	105			41	9-1	32-4					
13		136			110	105			37	10-1	33-4					
14		137			110	105			33	11-1	34-4					
15		138			110	105			29	12-1	35-4					
16		139			110	105			25	13-1	36-4					
17		140			110	105			21	14-1	37-4					
18		141			110	105			17	15-1	38-4					
19		157			110	105			13	16-1	39-4					
20		158			110	105			9	17-1	40-4					
21		159			110	105			5	18-1	41-4					
22		160			110	105			49	19-1	42-4	37				
23		161			110	105			45	20-1	43-4					
24		162			110	105			41	21-1	44-4					
25		163			110	105			37	22-1	45-4					
26	251148	165		CHANGE TAPE	110	105			33	23-1	46-4					
27		166			110	105			29	24-1	47-4					
28		167			110	105			25	25-1	48-4					
29		168			110	105			21	26-1	49-4					

LAND SEISMIC RECORDING LOG



CLIENT: Huskey PROSPECT: NPR-4 Umiat AREA: N: Slope AIC. LINE NO: 01

PARTY NO: 1173 INST. ENG: R. BERTSCH DATE: MO 3 DAY 2nd YR 78

INSTRUMENT (9-TRACK) 1 SYSTEM 2 SYSTEMS 1-24 & 25-48 1-48 & 49-96 ODDS & EVENS

TYPE: DFS III DFS IV DFS V OTHER 9 TRACK 21 TRACK

FORMAT: SEG GAPPED UNGAPPED

PACKING DENSITY: (L0) 356 BPI (M1) 712 BPI (H1) 1600 BPI

NO. BYTES IN HEADER REC: _____ NO. BYTES IN RECORD ID: _____ NO. BYTES PER SCAN: _____

RECORD NUMBERS: DEC. OCT. GAIN CONSTANT: _____ db INPUT IMPEDANCE: _____ ohms.

FIELD TRACE NOS: _____ DATA CHANNEL NOS: _____ (ON MAG TAPE)

AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____

AUXILIARY CHANNEL NOS: _____

PARAMETER RECORD LENGTH: _____ sec. SAMPLE RATE: 1 ms. 4 ms. 2 ms. _____ ms.

DISPLAY MODE: AGC FLOAT DEFLOAT AMPLIFIER DIRECT INITIAL GAIN: _____ db

CFS 1 TYPE STACK: _____ GATE LENGTH: _____ RECORD REJECTION: _____

SOURCE TYPE: DYNAMITE VIBROSEIS OTHER PATTERN: _____ NO. OF POSITIONS: _____ INLINE SPACING: _____ LATERAL SPACING: _____ STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____



RECEIVER TYPE: _____ PATTERN: _____ NO. OF ELEMENTS: _____ INLINE SPACING: _____ LATERAL SPACING: _____ CONNECTION: _____ RESISTANCE: _____ ohms STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____

SPREAD NO. OF GROUPS: _____ GROUP INTERVAL: _____ SHOTPOINT INTERVAL: _____ FOLD: _____ DIRECTION OF PROGRESSION: _____ OFFSET GROUP 1: _____ OFFSET GROUP: _____ OFFSET GROUP 48/96: _____ LEADING GROUP: _____

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 20		SHOT							CDP SWITCH	SPREAD			REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	LINE GROUPS	#1		SET UP	TR 1-48	REC.		TR 48-96	REC.				
39	75	14	85	16	17	22	23	26	27	29	30	32	35	37	17	27-1	50-4	37				
40					17										13	28-1	51-4					
41					17										89	25-1	52-4					
42					17										5	30-1	53-4					
43					17										49	31-1	54-4	49				
44					17										45	32-1	55-4					
45					17										41	33-1	56-4					
46					17										37	34-1	57-4					
47					17										33	35-1	58-4					
48					17										29	36-1	59-4					
49					17										25	37-1	60-4					
50					17										21	38-1	61-4					
51					17										17	39-1	62-4					
52					17										13	40-1	63-4					
53					17										9	41-1	64-4					
54					17										5	42-1	65-4					
55					17										49	43-1	66-4	61				
56					17										45	44-1	67-4					
57					17										41	45-1	68-4					No Atw Rec # 87
58					17										37	46-1	69-4					

LAND SEISMIC RECORDING LOG



	CLIENT: <u>Husicy</u>	PROSPECT: <u>NPR-4 UMIAT</u>	AREA: <u>NORTH SUDRA AIC</u>	LINE NO: <u>01</u>						
	PARTY NO: <u>1173</u>	INST. ENG: <u>R. BEUTSCH</u>		DATE: <u>MO 3 DAY 20 YR 78</u>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____				AUXILIARY DATA: _____				AUXILIARY CHANNEL NOS.: _____	
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	FREQ. _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> FLOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	JRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____	DOWNBREAK UPBREAK: <input type="checkbox"/> ON DISPLAY	R.C.U. NORM/ALT SW.	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____				
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
	CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____		
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
	CONNECTION: _____	RESISTANCE: _____ ohms								
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	OFFSET GROUP: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT #	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD				REMARKS:	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS	SET		HT.	REC.	HT.	REC.
69	151	148.5	90		110	110.5				33	49-1	70-4	61				
70		9.6								29	48-1	71-4					
71		9.2								25	49-1	72-4					
72		9.3								21	50-1	73-4					
73		9.4								17	51-1	74-4					
74		9.5								13	52-1	75-4		COP 2000R SE - FOR SP 63			
75		9.6								9	53-1	75-4		" " SP 64			
76		9.7			110	110.5				5	54-1	77-4					

8.0 MILES

LAND SEISMIC RECORDING LOG


	CLIENT: Husky	PROSPECT: NPR-4 JARANT	AREA: NORTH SLOPE, ALASKA	LINE NO: U1									
	PARTY NO: 1173	INST. ENG: R. BERTSCH		DATE: MO 3 DAY 21 YE 78									
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: SEG B	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI				
	NO. BYTES IN HEADER REC: 223	NO. BYTES IN RECORD ID: 2	NO. BYTES PER SCAN: 214	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: ohms	(1)	(2)	(3)	(4)	(5)	(6)	(7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:						
PARAMETER	RECORD LENGTH: 5 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: FREQ. 9	LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 70	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT						
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> DIRECT	INITIAL GAIN: db	TRIP SENS: 45	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY					
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM / ALT SW.						
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
	CHG/ HOLE: 110	HOLE DEPTH: 105'	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:					
RECEIVER	TYPE: 2267D	PATTERN: LINE 1 MAG	NO. OF ELEMENTS: SP75 SP76 SP77	INLINE SPACING: SP75 SP76 SP77	LATERAL SPACING:	STAGGER: 1/2 1/2 1/2	LENGTH: 1 1 1	WIDTH: 1 1 1	LATERAL OFFSET:				
SPREAD	CONNECTION: SER-FAR	RESISTANCE: 220 ohms	STAGGER: 1/2 1/2 1/2	LENGTH: 1 1 1	WIDTH: 1 1 1	LATERAL OFFSET:							
	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880 → 1760	FOLD: 1200% ← → 600%	DIRECTION OF PROGRESSION: NORTH	LEADING GROUP: 1							
OFFSET GROUP 1: 10450'	OFFSET GROUP 48: 110'	OFFSET GROUP 49: 110'	OFFSET GROUP 96: 10450'										

DIAGRAMS/MISC. INFORMATION:

CHANGE TO 6 FOLD ON SP 77, SMARTHANDED BY JUG CREW AGAIN,

SHOTPOINT	TR. 1		TR. 2		SHOT									SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#%	LINE GROUPS #1	SEP	TR 1-21	TR 22-42	TR 43-63		TR 64-84			
167	751/1185	198	199	198	110	105	1				49	55-1	78-7	73	DAILY TESTS F# 168-171 SP 80 to 81. ACROSS LINE and CROSS BOTTOM - PICKING UP HIGH FREQ NOISE BEGIN 600% - 6 FOLD ON SP 77						
168		199	199	199							45	56-1	77-8								
169		1100	1100	1100							41	57-1	78-4								
170		1101	1101	1101							37	58-1	78-8								
171		1102	1102	1102							33	59-1	79-4								
172		1103	1103	1103							29	60-1	79-8								
173		1104	1104	1104							25	61-1	80-4								
174		1105	1105	1105							21	62-1	80-8								
175		1106	1106	1106							17	63-1	81-4								
176	751/1486	1107	CHANGE TAPE 1107 1108								13	64-1	81-8								
177		1122	1122	1122							41	66-1	82-8	79							
178		1123	1123	1123							35	68-1	83-8								
179		1124	1124	1124							25	70-1	84-8								
180		1125	1125	1125							17	72-1	85-8								
181		1126	1126	1126							9	74-1	86-8								
182		1127	1127	1127							49	76-1	87-8								
183		1128	1128	1128							41	77-1	88-8								
184		1129	1129	1129							33	78-1	89-8								
185		1130	1130	1130							25	79-1	90-8								
186		1131	1131	1131	110	105					17	80-1	91-8								



LAND SEISMIC RECORDING LOG

	CLIENT: <u>HUSKY</u>	PROSPECT: <u>NPR-4 UMAT</u>	AREA: <u>NORTH SLOPE ALASKA</u>	LINE NO: <u>01</u>					
	PARTY NO: <u>1113</u>	INST. ENG: <u>R. BERTSON</u>		DATE: <u>MO 3 DAY 21 YE 79</u>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: _____			AUXILIARY DATA: _____			AUXILIARY CHANNEL NOS: _____		
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	H1 CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	DOWNBREAK <input type="checkbox"/> ON DISPLAY <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	CONNECTION: _____	PATTERN: _____	RESISTANCE: _____ ohms	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	OFFSET GROUP: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT #	TR _____ to _____		TR _____ to _____		SHOT				SPREAD				REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#96	LINE GROUPS		#1	SET UP	TR 1-48	TR 48-96
87	70	140	16	132	11	105	1			9	91-1	92-8					
88		133								49	92-1	93-8					
89		134								41	93-1	94-8					
90		135								33	94-1	95-8					
91		136								29	95-1	96-8					
92		137								17	96-1	97-8					
93		138								9	97-1	98-8					
94		139			11	105				1	98-1	99-8					

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>SPR-4 U.A.T</u>	AREA: <u>N. SLOPE ALASKA</u>	LINE NO: <u>01</u>						
PARTY NO: <u>1113</u>		INST ENG: <u>R. BERTSCH</u>		DATE: <u>MO 5 DAY 22 YR 78</u>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	DODS <input checked="" type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 2) TRACK	POP.MAT: <u>SEG</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC: <u>222</u>	NO. BYTES IN RECORD ID: <u>2</u>	NO. BYTES PER SCAN: <u>257</u>	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: <u>8</u> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>8</u> LO CUT HZ SLOPE <u>15</u>	FREQ. <u>128</u> HI CUT HZ SLOPE <u>20</u>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:		R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	CONNECTION: <u>SER. PAR</u>	RESISTANCE: <u>220</u> ohms	NO. OF ELEMENTS: <u>18</u>	STAGGER: _____	LENGTH: <u>220'</u>	WIDTH: _____	LATERAL OFFSET: _____			
SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>1760</u>	FOLD: <u>600%</u>	OFFSET GROUP 48/96: <u>1045'</u>	DIRECTION OF PROGRESSION: <u>NORTH</u>		LEADING GROUP: <u>1</u>		

DIAGRAMS/MISC. INFORMATION:

COMPLETE L-U1, PICK-UP PHONE AND BABLES

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT		SPREAD			REMARKS:	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS #1	#2	TR 1-48	TR 49-96		
95	1511486	140	(COINTEL)	TAPK	110	105				41	89-1	100-8	97				
96		141								33	90-1	101-8					
97		142								25	91-1	102-8					
98		143								27	92-1	103-8					
99		144								9	93-1	104-8					
100		145								37	94-1	105-8	104				
101		146								29	95-1	106-8					
102		147								21	96-1	107-8					
103		148								37	97-1	71-8					
104		149								29	98-1	72-8					
105		150								21	99-1	73-8					
106		151								13	100-1	74-8					
107		152								5	101-1	75-8					

4.0 MILES