

CLIENT: Husky		PROSPECT: NPR-1		AREA: Alaska - N. Slope		LINE NO: U2	
PARTY NO: 1173		INST ENG: Beitsch/Panico		RECORDING: Rec Hrs 16.0		DATE: MO 3 DAY 14 1978	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		ODDS & EVENS: <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER		RECORDING: <input type="checkbox"/> 2-TRACK <input checked="" type="checkbox"/> 21 TRACK	
NO. BYTES IN HEADER REC: 2541		NO. BYTES IN RECORD ID: 2		NO. BYTES PER SCAN: 289		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	
FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: _____		AUXILIARY DATA: _____		AUXILIARY CHANNEL NOS.: _____	
PARAMETER: RECORD LENGTH: _____ SEC.		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> _____ ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: _____	
DISPLAY: MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		TRIP SENS.: _____ db		POLARITY CONVENTION: _____	
CFS I: TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: _____		NO. OF POSITIONS: _____		INLINE SPACING: _____	
CONNECTION: 3ER-PAR		RESISTANCE: 220 ohms		STAGGER: _____		LENGTH: _____	
NO. OF GROUPS: 96		GROUP INTERVAL: 200		SHOTPOINT INTERVAL: 1060		FOLD: 600%	
OFFSET GROUP 1: 20450		OFFSET GROUP 48 : 110'		OFFSET GROUP 49 : 110'		DIRECTION OF PROGRESSION: SOUTH	

DIAGRAMS/MISC. INFORMATION:
LAYOUT LINE U2 : WAITING ON DRILLS BEFORE COMPLETING LAYOUT

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT		SPREAD		REMARKS:	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	*1	LINE GROUPS	H96	561	TR 1-48
1	2514	15			105	105				1	75-8	6-8	4		DAILY TEST FA 1-13 No MONITOR RE FA 14	
2		16			105	105				9	74-8	7-9				
3		17			105	105				17	73-8	8-8				
4		18			105	105				25	72-8	9-8				
5		19			105	105				33	71-8	10-8				
6		20			105	105				41	70-8	11-8				
7		21			105	105				9	1-1	12-8	10			
8		22			105	105				19	2-1	13-8				
9		23			105	105				125	3-1	14-8				
10		24			105	105				2535	4-1	15-8				
11		25			105	105				3344	5-1	16-8				
12		26			105	105				41	6-1	17-8				
13		27			105	105				9	7-1	18-8	16			
14		28			105	105				919	8-1	19-8				
15		29			105	105				17	9-1	20-8				
16		30			105	105				25	10-1	21-8				
17		31			105	105				33	11-1	22-8				
18		32			105	105				41	13-1	23-8				

CLIENT: Husky
 PARTY NO: 1173
 INST ENG: BRETSCH / PARKS
 PROSPECT: MPR-4 Umiat
 AREA: N Slope Alaska
 LINE NO: U2
 DATE: MO 07 DAY 15 YR 78
 REC HRS: 15.0
 DRU: 3.0 HRS


INSTRUMENT: [9-TRACK] 1 SYSTEM [X] 2 SYSTEMS [X]
 NO. BYTES IN HEADER REC: 225
 NO. BYTES IN RECORD ID: 2
 NO. BYTES PER SCAN: 254
 RECPD NUMBERS: [X] DEL [] OCT
 GAIN CONSTANT: (1) (2) (3) (4) (5) (6) (7)
 CONFIGURATION (MAG TAPE): FIELD TRACE NOS: 1-96
 DATA CHANNEL NOS: [] (ON MAG TAPE)
 AUXILIARY CHANNEL NOS: []

PARAMETER: RECORD LENGTH: 8 sec
 SAMPLE RATE: 1 ms [X] 4 ms []
 GAIN MODE: [X] TRIP [] INITIAL [] MANUAL [] OPERATE []
 DISPLAY: MODE: [X] AGC [] FLOAT [] AMPLIFIER [] DIRECT []
 CFS I: TYPE STACK: [] GATE LENGTH: [] RECORD REJECTION: []
 FILTERS: FREQ: 9 LO CUT HZ SLOPE: 18 HI CUT HZ SLOPE: 76
 POLARITY CONVENTION: [X] POSITIVE [] NEGATIVE
 PRESSURE INCREASE ON GEOPHONE: []
 NOISE REDUCTION: [] NOISE THRESHOLD: [] CORR SCALING: []
 P.C.U. NORM: ALT SW

SOURCE: TYPE: [] DYNAMITE [] VIBROSEIS [] OTHER []
 PATTERN: INLINE
 NO. OF POSITIONS: 15
 INLINE SPACING: 12
 LATERAL SPACING: []
 STAGGER: [] LENGTH: [] WIDTH: [] LATERAL OFFSET: []

RECEIVER: TYPE: D2070
 CONNECTION: SERIAL
 RESISTANCE: 220 ohms
 STAGGER: [] LENGTH: 220' 220'
 WIDTH: [] LATERAL OFFSET: []

SPREAD: NO. OF GROUPS: 96
 GROUP INTERVAL: 220'
 OFFSET GROUP 1: 12450'
 SHOTPOINT INTERVAL: SP27 SP28 SP29
 SP27 1760' SP28 1800' SP29 12450'
 OFFSET GROUP 49: 110'
 FOLD: 1200' 1200' SWTH
 DIRECTION OF PROGRESSION: 96
 LEADING GROUP: 5000'



SHOTPOINT	TR		TR		SHOT		SPREAD		REMARKS	CORR STACK							
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET		TR 1-28	TR 29-30	TR 31-32	TR 33-34				
1	751410V	148			105	105	35	37	1 13-1 24-8	22							
2		49			105	105			9 14-1 25-8								
21		50			105	105			19 15-1 26-8								
22		51			105	105			25 16-1 27-8								
23		52			105	105	110	10 E	33 17-1 28-8								
24		53			105	105			41 18-1 29-8								
25		54			105	105			1 19-1 33-4								
26		55			105	105			9 20-1 35-4								
27		56			105	105			17 21-1 37-4								
28		57			105	105			25 22-1 39-4								
29		58			105	105			29 22-5 40-4								
30		59			105	105			33 23-1 43-4								
31		62			105	105			37 23-5 48-4								
32		63			105	105			41 24-1 43-4								
33		64			105	105			45 24-5 44-4								
34		65			105	105			1 25-1 45-4								
35	25114012	167			105	105			5 25-5 46-4								
36		168			105	105			9 26-1 47-4								
37		169			105	105			13 26-5 48-4								
38		170			105	105			17 27-1 49-4								

REMARKS: Tests 33-45
 No Monitors FH 46 & 47
 CHANGE TO 1200% - 12 FOLD ON SP 29
 No MIN FH 60 & 61
 DFS SYSTEM ERROR C-1 ENCOUNTERED - OVER WIDE SEC. FAULT.
 No VP-HOLE SPS
 I.D. REC 66
 No SPS - MAY HAVE PROBLEM IN SCANNING UNIT

LAND SEISMIC RECORDING LOG

		CLIENT: Husky	PROSPECT: NPR-4 umiat	AREA: NORTH Slope Alaska	LINE NO. U-2		
PARTY NO. 1173		INST. ENG. BEDTICH/PANICO		DATE: Zec Has 17.0 Dec 80		MO. 03 DAY 17 YR 79	
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED
	NO BYTES IN HEADER REC: 228	NO BYTES IN RECORD ID: 2	NO BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms	(LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: _____		AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
PARAMETER	RECORD LENGTH: 8 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input checked="" type="checkbox"/> TRF <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ: 8 LO CUT HZ SLOPE: 19 HI CUT HZ SLOPE: 70 NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db		POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE } NUMBERS ON ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____		NOISE REDUCTION: _____ NOISE THRESHOLD: _____ CORR. SCALING: _____ P.C.U. NORM. ALT SW. _____		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: INLINE	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____
RECEIVER	TYPE: 220-10	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 12	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____
SPREAD	CONNECTION: SEA PAD	RESISTANCE: 220 ohms	SHOTPOINT INTERVAL: 220	SHOTPOINT INTERVAL: 880	FOLD: 1200	SWEEP LENGTH: _____ SWEEP TAPER: _____	DIRECTION OF PROGRESSION: SOUTH LEADING GROUP: 96
DIAGRAMS/MISC. INFORMATION:		CHG. HOLE: 105		HOLE DEPTH: 105	SWEEP POSITION: _____ SWEEP START: _____ SWEEP END: _____	OFFSET GROUP 48 : 110' OFFSET GROUP 48/96 : 10'150	

FINISH L-UZ



SHOTPOINT	TR 10		TR 10		SHOT		SPREAD			REMARKS	CORR STACK			
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TR 48	TR 96
147	76V48	191			110	105	35			1	34-1	57-4	52	
148		192			110	105				5	35-1	58-4		
149		193			110	105				9	36-1	59-4		
150		194			110	105				13	37-1	60-4		
151		195			110	105				17	38-1	61-4		
152		196			110	105				21	39-1	62-4		
153		197			110	105				25	40-1	63-4		
154		198			110	105				29	41-1	64-4		
155		199			110	105				33	42-1	65-4		
156		100			110	105				37	43-1	66-4		
157		101			110	105				41	44-1	67-4		
158		102			110	105				45	45-1	68-4		
159		103			110	105				1	46-1	69-4	64	
160		104			110	105				5	47-1	70-4		
161		105			110	105				9	48-1	71-4		
162		106			110	105				13	49-1	72-4		
163		107			110	105				17	50-1	73-4		
164		108			110	105				21	51-1	74-4		
165		109			110	105				25	52-1	75-4		
166		110			110	105				29	53-1	76-4	70	

Holes loaded to 110 lb with 2 primers here after

SKIP SPAC - SIDE OF HILL

NO MAG F# 109

LAND SEISMIC RECORDING LOG

	CLIENT: <u>MUSKY</u>	PROSPECT: <u>NPR-4 Omat</u>	AREA: <u>NORTH SLOPE ALASKA</u>	LINE NO: <u>U2</u>	
PARTY NO: <u>1173</u>		INST. ENG: <u>BRANSH - PANKO PANKO</u>		DATE: <u>MO 3 DAY 17 YR 78</u>	
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		ODDS & EVENS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	
NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: _____	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)		RECORD NUMBERS: _____		GAIN CONSTANT: _____	
PARAMETER RECORD LENGTH: _____ sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	
DISPLAY MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		JRP SENS: _____ db	
CFS I TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____	
SOURCE <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: _____		NO. OF POSITIONS: _____	
RECEIVER TYPE: _____		CONNECTION: _____		RESISTANCE: _____ ohms	
SPREAD NO. OF GROUPS: _____		GROUP INTERVAL: _____		SHOTPOINT INTERVAL: _____	

DIAGRAMS/MISC. INFORMATION: 35
19
26

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT			SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH		#	LINE GROUPS	SET UP	TR 1-24
616		1112			110	105				9	544	77-4	70		
617		1113			110	105				13	554	78-4			
618		1114			110	105				17	564	79-4			
619		1115			110	105				21	574	80-4			
701		1116			110	105				25	584	81-4			
701		1117			110	105				29	594	82-4			
72		1118			110	105				33	604	83-4			
73		1119			110	105				37	614	84-4			
74	751483	1121	CHANGE TAPE		110	105				41	624	85-4			I.D. Rec F# 120
75		1122			110	105				45	634	86-4			
76		1123			110	105				1	644	87-4	82		
77		1124			110	105				5	654	88-4			
78		1125			110	105				9	664	89-4			
79		1126			110	105				13	674	90-4			
80		1127			110	105				17	684	91-4			
81		1128			110	105				21	694	92-4			
82		1129			110	105				25	704	93-4			
83		1130			110	105				29	714	94-4			
84		1131			110	105				33	724	95-4			
85		1132			110	105				37	734	96-4			

LAND SEISMIC RECORDING LOG

	CLIENT:	PROSPECT:	AREA:	LINE NO:	
	PARTY NO:	INST. ENG:		DATE:	

HUSKY

APR-41 UMINT

NORTH SLOPE ALASKA

12

1173

BERTSCH / PAVLO

MO 3 DAY 17 YR 78

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> 2 SENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	POP MAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> JUNGAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
-------------------------	---	--	---	---	---	---	-----------------	---	---------------------	---	--

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS:	AUXILIARY DATA:	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT
	DATA CHANNEL NOS:	AUXILIARY CHANNEL NOS:	GAIN CONSTANT: _____ db

PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS:	LO CUT HZ SLOPE	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
-----------	---------------------------	---	---	----------	--------------------	--------------------	--

DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON ON MAG TAPE	CORR. SCALING:	R.C.U. NORM./ALT SW
---------	--	------------------------	---------------------	---	--	----------------	---------------------

SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
--------	---	----------	-------------------	-----------------	------------------	----------	---------	--------	-----------------

RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
----------	-------	----------	------------------	-----------------	------------------	----------	---------	--------	-----------------

SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:
--------	----------------	-----------------	---------------------	-------	---------------------------

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT							SPREAD			REMARKS:	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	#	LINE GROUPS	#	SET UP		TR 1-48	TR 48-96	REC.	REC.
86	1213	133	17	2223	26	27	29	30	32										
87		134									41	74-1	97-4						
88		135									45	75-1	98-4	92					
89		136									7	76-1	78-4						
90		137									11	77-1	78-4						
91		138									15	78-1	78-4						
92		139									19	79-1	79-4						
93		140									23	80-1	76-4						
94		141									27	81-1	76-4						
95		142									31	82-1	78-4						
96		143									35	83-1	78-4						
97		144									39	84-1	79-4						
98		145									43	85-1	710-4						
											47	86-1	711-4						

END OF L-12

