



# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-4 UMIAT</b>	AREA: <b>NORTH SLOPE, ALASKA</b>	LINE NO: <b>U-7</b>						
	PARTY NO: <b>1173</b>	INST. ENG: <b>LANE</b>		DATE: <b>MO 02 DAY 26 YR 78</b>						
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input checked="" type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI
(9-TRACK)	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>		NO. BYTES PER SCAN: <b>256</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>36</b> db		INPUT IMPEDANCE: <b>2000</b> ohms.		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>				AUXILIARY DATA:					
	DATA CHANNEL NOS.: <b>7-102</b> (ON MAG TAPE)				AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms. ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>8</b>	LO CUT HZ SLOPE <b>18</b>	HI CUT HZ SLOPE <b>70</b>	NOYCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>36</b> db	TRIP SENS: <b>42</b> db		POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> UPBREAK <input type="checkbox"/> DOWNBREAK		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:		NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE Hole - INLINE</b>	NO. OF POSITIONS: <b>1</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
		CHG/ HOLE: <b>100/110</b>	HOLE DEPTH: <b>105</b>	SWEET POSITION:	SWEET START:	SWEET END:	SWEET LENGTH:	SWEET TAPER:	PHASE COMP.	
RECEIVER	TYPE: <b>20-10</b>	PATTERN: <b>Inline</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION: <b>SERIES-PARALLEL</b>	RESISTANCE: <b>220</b> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>1200%</b>	DIRECTION OF PROGRESSION: <b>NORTH</b>	LEADING GROUP: <b>1</b>				
	OFFSET GROUP 1-48: <b>10,450</b>	OFFSET GROUP 48: <b>110'</b>	OFFSET GROUP 49: <b>110</b>	OFFSET GROUP 48/96: <b>10,450</b>						

DIAGRAMS/MISC. INFORMATION: Files 001 → 015 DAILY TESTS

TOTAL TIME: 15.5  
TRAVEL TIME: 2:00

SHOTPOINT	TR. 1 to 96		TR. 10		SHOT					SPREAD			REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIP.	CDP SWITCH	LINE GROUPS	SET		TR. 1-48	TR. 48-96	TR. 1-48	TR. 48-96
1	75146A	000															
2																	
3																	
4		0116			110	105		880	N	37	15-4						
5		0117			110	105				33	16-4						
6		0118			110	105				29	17-4						
7		0119			1110	105		1170	N	25	18-4						
8		020			<del>110</del>	<del>105</del>		<del>880</del>		21	19-4						
9		021			110	105				17	20-4						
10		022			110	105				13	21-4						
11		023			110	105				9	22-4						
12		024			110	105				5	23-4						
13		025			110	105		160	S	49	24-4	1-1	19				
14		026			110	105				45	25-4	2-1					
15		027			110	105				41	26-4	3-1					
16		028			110	105				37	27-4	4-1					
17					110	105				33	28-4	5-1					
18		032			110	105				29	29-4	6-1					
19		033			110	105				25	30-4	7-1					
20		034			110	105				21	31-4	8-1					



Camp Crossing line 45 MINUTES  
90 FEET, 110 LBS

AIRPLANE NOISE

File 029 MISFIRE hole N.G. - shorted  
File 031 MISFIRE

2 1/2 HRS TO ROAD SP 20

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>HUSKY</b>	PROSPECT: <b>NPR-4 UMIAT</b>	AREA: <b>NORTH SLOPE, ALASKA</b>	LINE NO.: <b>U-7</b>						
PARTY NO.: <b>1173</b>		INST. ENG.: <b>LANE-PANKO</b>		DATE: <b>MO 02 DAY 27 YR 78</b>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI (HI) <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____						
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	H1 CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____		
CFS I	TYPE STACK: _____	GATE LENGTH: _____								
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	OFFSET GROUP 1: _____	SHOTPOINT INTERVAL: _____	OFFSET GROUP _____	FOLD: _____	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 96		TR. _____ to _____		SHOT				SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	*1 LINE GROUPS		96	HT	TR 48-96	REC.
57	754	1469	0884		110	105				17	18-4	45-1	55			
58			0885		110	105				15	69-4	46-1				
59			0886		110	105				9	70-4	47-1				
60			0887		110	105				5	71-4	48-1				
61			0888		110	105				49	72-4	49-1	67	WEAK		PLANE ON TAIL END AT SPREAD
62			0889		110	105				45	73-4	50-1	67			
63			0890		110	105				41	74-4	52-1		MULTIPLE ICE CRACKING		
64			0891		110	105				37	75-4	53-1				
65			0892		110	105				33	76-4	54-1		ENERGY RETURNING		
66			0893		110	105				29	77-4	55-1				
67			0894		110	105				25	78-4	56-1				
68			0895		110	105				21	79-4	57-1				
69			0896		110	105				17	80-4	58-1				
70			0897		110	105				13	81-4	59-1				
71			0898		110	105				9	82-4	60-1				
72			0899		110	105				5	83-4	61-1				
73			1000		110	105				49	84-4	62-1	49			
74			1001		110	105				45	85-4	63-1				
75			1002		110	105				41	86-4	64-1				
76			1003		110	105				37	87-4	65-1		MULTIPLE ICE CRACKING		

# LAND SEISMIC RECORDING LOG

Page 1 of 3

	CLIENT: <b>HUSKY</b>	PROSPECT: <b>NPR-4 UMIAT</b>	AREA: <b>NORTH SLOPE</b>	LINE NO.: <b>U-7</b>	
	PARTY NO.: <b>1173</b>	INST. ENG.: <b>LANE - PANKO</b>		DATE: <b>MO 02 DAY 27 YR 78</b>	

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT SEG: <b>B</b>	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input checked="" type="checkbox"/> 1600 BPI
(9-TRACK)	NO. BYTES IN HEADER REC.: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>256</b>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: (1) (2) (3) (4) (5) (7)	INPUT IMPEDANCE: _____ ohms.		

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>	AUXILIARY DATA:
	DATA CHANNEL NOS.: <b>7-102</b> (ON MAG TAPE)	AUXILIARY CHANNEL NOS.:

PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>8</b>	LO CUT HZ SLOPE: <b>18</b>	HI CUT HZ SLOPE: <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>36</b> db	JIP SENS: <b>42</b> db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON <input checked="" type="checkbox"/> OFF
CFS 1	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM / ALT SW.

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE HOLE - INLINE</b>	NO. OF POSITIONS: <b>1</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CHG/ HOLE: <b>110</b>	HOLE DEPTH: <b>105</b>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.

RECEIVER	TYPE: <b>D20-10</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING:	LATERAL SPACING:
	CONNECTION: <b>SERIES - PARALLEL</b>	RESISTANCE: <b>220</b> ohms	STAGGER:	LENGTH:	WIDTH:
				LATERAL OFFSET:	

SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>1200%</b>	DIRECTION OF PROGRESSION: <b>NORTH</b>
	OFFSET GROUP 1-48: <b>10,450</b>	OFFSET GROUP 49-96: <b>110'</b>	OFFSET GROUP 49-96: <b>110'</b>	OFFSET GROUP 48/96: <b>10,450</b>	LEADING GROUP: <b>1</b>



DIAGRAMS/MISC. INFORMATION: **FILE 051 -> 063 DAILY TESTS**

**TOTAL 12.5 TRAVEL 2.0**

SHOTPOINT	TR 1 to 96		TR 10 to 19		TR 20 to 29		TR 30 to 39		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS	SET UP		TR 1-48	TR 48-96	TR 1-48	TR 48-96
37	15	146A	10	64	618	1810	11	11	49	48-4	25-1	43	E29 DEAD				
38		065			110	105			45	49-4	26-1						
39		066			110	105			41	50-4	27-1						
40		067			110	105			37	51-4	28-1						
41		068			110	105			33	52-4	29-1						
42		069			110	105			29	53-4	30-1						
43		070			110	105			25	54-4	31-1						
44		071			110	105			21	55-4	32-1						
45		072			110	105			17	56-4	33-1						
46		073			110	105			13	57-4	34-1						
47		074			110	105			9	58-4	35-1						
48		075			110	105			5	59-4	36-1						
49		076			110	105			49	60-4	37-1						
50		077			110	105			45	61-4	38-1						
51		078			110	105			41	62-4	39-1						
52		079			110	105			37	63-4	40-1						
53		080			110	105			33	64-4	41-1						
54		081			110	105			29	65-4	42-1						
55		082			110	105			25	66-4	43-1						
56		083			110	105			21	67-4	44-1						

# LAND SEISMIC RECORDING LOG

Page 2 of 2

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-4 UMIAT</b>	AREA: <b>North Slope</b>	LINE NO: <b>U-7</b>					
	PARTY NO: <b>1173</b>	INST. ENG: <b>LANE</b>		DATE: <b>MO. 02 DAY 26 YR 78</b>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> SEG <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 354 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) (2) (3) (4) (5) (6) (7)		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	CONNECTION:	PATTERN:	RESISTANCE: _____ ohms	NO. OF ELEMENTS:	INLINE SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	OFFSET GROUP 1:	OFFSET GROUP 48/96:	LEADING GROUP:	



DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 96		TR 17 to 33		SHOT		SPREAD			REMARKS	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS		HY.	REC.	HY.	REC.
21	13	18	17	22	110	105	35	37		17	30-4	9-1	19				
22		10316			100	105				13	33-4	10-1					
23		10317			110	105				9	34-4	10-1					
24		038			110	105				5	35-4	12-1					
25		039			110	105				49	36-4	13-1	31				
26		10410			110	105				45	37-4	14-1					
27		0411			110	105				41	38-4	15-1					
28		042			110	105				37	39-4	16-1					
29		043			110	105				33	40-4	17-1					
30		044			110	105				29	41-4	18-1					
31		045			110	105				25	42-4	19-1					
32		046			110	105				21	43-4	20-1					
33		047			110	105				17	44-4	21-1					
34		048			160	75				13	45-4	22-1					60 lbs
35		049			110	105				9	46-4	23-1					
36		050			160	75				5	47-4	24-1					60 lbs, 75 FEET



# LAND SEISMIC RECORDING LOG

Page 1 of 1

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR 4 UMIAT</b>	AREA: <b>NORTH SLOPE ALASKA</b>	LINE NO: <b>U-7</b>								
PARTY NO: <b>1173</b>		INST. ENG.: <b>LANE - PANKO</b>		DATE: <b>MO 02 DAY 28 YR 78</b>								
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-40 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED	PACKING DENSITY: <b>36</b>	(LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC: <b>228</b>	NO. BYTES IN RECORD ID: <b>2</b>	NO. BYTES PER SCAN: <b>256</b>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: <b>2000</b> ohms.	(1)	(2)	(3)	(4)	(5)	(6)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: <b>9</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ: <b>9</b> HI CUT HZ SLOPE: <b>18</b>	FREQ: <b>128</b> HI CUT HZ SLOPE: <b>10</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT					
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>36</b> db	TRIP SENS: <b>42</b> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY					
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.					
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>INLINE-Single Hole</b>	NO. OF POSITIONS: <b>1</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
RECEIVER	TYPE: <b>D20-10</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	CONNECTION: <b>SERIES-PARALLEL</b>	RESISTANCE: <b>220</b> ohms	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:				
	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>980'</b>	FOLD: <b>1200%</b>	DIRECTION OF PROGRESSION: <b>NORTH</b>			LEADING GROUP: <b>1</b>				
	OFFSET GROUP: <b>10,450'</b>	OFFSET GROUP: <b>49, 110'</b>	OFFSET GROUP: <b>49, 110'</b>	OFFSET GROUP: <b>49, 110'</b>	OFFSET GROUP: <b>49, 110'</b>			OFFSET GROUP: <b>49, 110'</b>				

DIAGRAMS/MISC. INFORMATION: **Daily Tests File # 112-104**

SHOTPOINT	TR 10		TR 10		SHOT			SPREAD			REMARKS:	CORR STACK					
	REEL NO.		REC.		SIZE	DEPTH	NO. OFFSET	DIR.	CDF SWITCH	LINE GROUPS		SET UP	TR 41		TR 41-52		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDF SWITCH	LINE GROUPS		SET UP	REC.	REC.	REC.	REC.	
86		126			110	105			49	96-4	74-1	91					
86		126			110	105			45	97-4	75-1						
87		127			97	105			41	98-4	76-1						
88		128			110	105	75	N	37	99-4	77-1						
89		129			110	105			33	100-4	78-1						
90		130			110	105			29	101-4	79-1						
91		131			110	105			25	102-4	80-1						
92		132			110	105			21	103-4	81-1						
93		133			110	105			17	104-4	82-1						
94		134			110	105	310	S	13	105-4	83-1						
95		135			110	105			9	106-4	84-1						
96		136			110	105			5	107-4	85-1						
97		137			110	105			13	108-4	86-1	94					
98		138			110	105			9	109-4	87-1						
99		139			110	105			5	110-4	88-1						
End of Line U-7																	