




# LAND SEISMIC RECORDING LOG

Page 1

	CLIENT: <b>Huskey</b>	PROSPECT: <b>Southern Hills</b>	AREA: <b>NPRA Alaska</b>	LINE NO: <b>603</b>	
	PARTY NO: <b>1186</b>	INST ENG: <b>Heuch Grawing</b>	Leave camp 7:15 arrive camp 9:00 PM		DATE: <b>MO 1 DAY 9 YR 79</b>
INSTRUMENT	<input type="checkbox"/> LAY SYSTEM	<input type="checkbox"/> 1-24 & 25/48	<input type="checkbox"/> ODDS	<input type="checkbox"/> TYPE	<input type="checkbox"/> 9 TRACK
	<input type="checkbox"/> SYSTEMS	<input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> EVENS	<input type="checkbox"/> DFS	<input type="checkbox"/> 2 TRACK
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS:		AUXILIARY DATA:		
PARAMETER	RECORD LENGTH: <b>8 sec</b>	SAMPLE RATE: <b>21 cps</b>	GAIN MODE: <b>INITIAL</b>	FILTERS: <b>FREQ 8</b>	LO CUT HZ SLOPE
DISPLAY	<input type="checkbox"/> NOBT	<input type="checkbox"/> FLOAT	<input type="checkbox"/> INITIAL	<input type="checkbox"/> POLARITY CONVENTION	<input type="checkbox"/> NOTCH FILTER
CFS I	<input type="checkbox"/> AGC	<input type="checkbox"/> DIRECT	<input type="checkbox"/> FINAL	<input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE	<input type="checkbox"/> DOWNBREAK ON DISPLAY
SOURCE	<input type="checkbox"/> DYNAMITE	<input type="checkbox"/> VIBROSEIS	<input type="checkbox"/> OTHER	<input type="checkbox"/> NOISE REDUCTION	<input type="checkbox"/> CORR. SCALING
RECEIVER	TYPE: <b>HSS</b>	CONNECTION: <b>series parallel</b>	RESISTANCE: <b>18</b>	INLINE SPACING: <b>18</b>	LATERAL SPACING:
SPREAD	NO. OF GROUPS: <b>5225'</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>60070</b>	DIRECTION OF PROGRESSION: <b>south to west</b>



SHOTPOINT	TR. 10		TR. 20		SHOT		SPREAD		REMARKS	CORR. STAGE	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR. 10	TR. 20
114	7225497	42	7225497		110	1015	11	9	File # 29-41 Daily Text		
115		43			110	1015	12	17	Rec @ SP 16		
116		44			110	1015	13	25			
117		45			110	1015	14	33			
118		46			110	1015	15	41			
119		47			110	1015	16	49			
120		48			110	1015	17	9	Rec @ SP 23	48, 49	64 - missing
121		49			110	1015	18	17	Trace # 24 missing		
122		50			110	1015	19	25			
123		51			110	1015	20	9	Rec @ SP 25		
124		52			110	1015	21	17	Trace # 24 missing		
125		53			110	1015	22	25	TR. 16 missing		
126		54			110	1015	23	33	TR. 93 high frequency		
127		55			110	1015	24	41			
128		56			110	1015	25	49			
129		57			110	1015	26	9	Rec @ SP 31	TA # 17 done	
130		58			110	1015	27	17	Last segment on tape	Trace 804 81 missing	
131		59	7225498		110	1015	28	1	Installation on tape	File # 59 AGC Test	Rec @ 34 PARITY
132		60	7225498		110	1015	29	9	Last seg. on tape	not! File 60 SP 31 Parity	32 CROSSFEED
133		61	7225499		110	1015	30	17	New Tape	File # 62 AGC Test	VERY LOW ENERGY

# LAND SEISMIC RECORDING LOG

Page 2

	CLIENT: <i>Husky</i>	PROSPECT: <i>Southern hills</i>	AREA: <i>NPR-A alaska</i>	LINE NO: <i>603</i>			
	PARTY NO: <i>1186</i>	INST. ENG.:		DATE: <i>MO 1 DAY 9 YR 79</i>			
INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC:	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-28 & 29-96 ODDS & EVENS:	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK RECORD NUMBERS:	FORMAT: <input type="checkbox"/> SEG <input type="checkbox"/> DEC <input type="checkbox"/> OCT	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY:	(1) <input type="checkbox"/> 350 BPI <input type="checkbox"/> 800 BPI (11) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. DATA CHANNEL NOS.		AUXILIARY DATA:				
PARAMETER	RECORD LENGTH: _____	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	AUXILIARY CHANNEL NOS.:			
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____	TRIP SENS: _____	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE			
CFS 1	TYPE STACK:	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	
RECEIVER	CONNECTION: _____	RESISTANCE: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____	

DIAGRAMS/MISC. INFORMATION: *same as page 1*

SHOTPOINT	TR 10		TR 10		SHOT				SPREAD		REMARKS	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIP	COP SWITCH		LINE GROUPS	TR 1-4	TR 5-8	TR 9-12	TR 13-16
34	722599	67			110	105	21			25						
35		65			110	105	22			33						
36		66			110	105	23			41						
37		67			110	105	24			177	TR 86, 87	6				
38		68			110	105	25			9	TR 86, 87	6				
39										17		6				

# LAND SEISMIC RECORDING LOG

CLIENT: <b>Husky</b>		PROSPECT: <b>Southernhill</b>		AREA: <b>NPR-A Alaska</b>		LINE NO: <b>603</b>	
PARTY NO: <b>1186</b>		INST. ENG: <b>Donna Camp 7:00</b>		DATE: <b>1 DAY 10 79</b>		TIME: <b>6:00</b>	
INSTRUMENT: <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		ODDS & EVENS: <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER		RECORD NUMBERS: <input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		FORMAL SEG: <b>4413</b>	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS.:		DATA CHANNEL NOS.:		AUXILIARY DATA:	
PARAMETER: RECORD LENGTH: <b>8</b> sec		SAMPLE RATE: <b>8</b> Hz		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: FREQ: <b>8</b> Hz	
DISPLAY: MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>db</b>		TRIG SENS: <b>db</b>		LO CUT: <b>125</b> Hz	
CFS I: TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		HI CUT: <b>2</b> Hz	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>linear</b>		NO. OF POSITIONS:		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
RECEIVER: TYPE: <b>HST 1042</b>		CONNECTION: <b>Series, Parallel</b>		RESISTANCE: <b>ohms</b>		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
SPREAD: NO. OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>5.5'</b>		SHOTPOINT INTERVAL: <b>4.55'</b>		CORR. SCALING: <input type="checkbox"/> COR. NORM. ALT SW	
DIAGRAMS/MISC. INFORMATION: <b>east</b>		5170'		5170'		CORR. SCALING: <input type="checkbox"/> COR. NORM. ALT SW	

SHOTPOINT	TR 1		TR 2		SHOT		SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR	CDP SWITCH
37	82	2549			11	105	1		W	5	
38		83			11	105	1			5	
39		84			12	105	1			13	
40		85			13	105	3			21	
41		86			14	105	3			29	
42		87			14	105	4			29	
43		88			15	105	5			37	
44		89			16	105	6			45	
45		90			17	105	7			5	
46		91			18	105	8			13	
47		93			19	105	9			21	96-52+8
48		94			20	105	10			29	53+8
49		95			21	105	11			37	54+8
50		96			22	105	12			45	55+8
51		97			23	105	13			5	56+8
52		98			24	105	14			13	57+8
53		99			25	105	15			21	58+8
54		100			26	105	16			29	59+8

File 69 → 81 Daily Test

Rec'd 4/14 Time Break

Trace 92 back ✓ REVERSED ON 15' DRK

INST 48-4 & 48-5 TR 84 190 NOISY

END OF TAPE TR 82 NOISY

IFF TEST. \*

TR 74 NOISY

TR 82 NOISY

TR 90 NOISY

INST 53-4 & 53-5 TR 82 NOISY

TR 74 NOISY 1/2 OF GROUP REVERSE



TR 60 NOISY " " "


TR 56 NOISY " " "



# LAND SEISMIC RECORDING LOG

Page 1 of 2

	CLIENT: <b>Husky</b>	PROSPECT: <b>SOUTHERN FOOT HILLS</b>	AREA: <b>N.P.R. - A ALASKA</b>	LINE NO.: <b>603</b>	
PARTY NO.: <b>1186</b>		INST ENG: <b>DERENE - PANKO</b>		DATE: <b>1 DAY 11 79</b>	
LEAVE BASE: <b>7:00 AM</b>		ARRIVE BASE: <b>7:00 PM</b>			
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC:	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96 NO. BYTES IN RECORD ID:	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	BT 9 TRACK <input type="checkbox"/> 21 TRACK RECORD NUMBERS:	TOPMAT: <b>B</b> SEG:
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.:		AUXILIARY DATA:	
PARAMETER		DATA CHANNEL NOS.:		AUXILIARY CHANNEL NOS.:	
DISPLAY		SAMPLE RATE: <input type="checkbox"/> 1ms <input type="checkbox"/> 4ms		FILTERS: FREQ: <b>8</b>	
CFS I		INITIAL GAIN: <b>46</b>		TO CUT, HZ SLOPE: <b>72</b>	
SOURCE		PATTERN: <b>IN LINE</b>		NOISE REDUCTION: <input type="checkbox"/> CORE SCALING: <input type="checkbox"/>	
RECEIVER		TYPE: <b>HST 10 HZ</b>		NOISE THRESHOLD: <input type="checkbox"/>	
SPREAD		CONNECTION: <b>SERIES, PARALLEL</b>		CORR. SCALING: <input type="checkbox"/>	



SHOTPOINT	FA		TA		SHOT			SPREAD		REMARKS	CORR STACK			
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET	LINE GROUPS		YE 1-10	YE 11-20	YE 21-30	
56	122550	117A			110	105	1		37	41.1	46.8			
57		117B			110	105	2		45	50.1	61.8			
58		117C			110	105	3		5	51.1	62.8			
59		117D			110	105	4		13	52.1	63.8			
60		117E			110	105	5		21	53.1	64.8			
61		117F			110	105	6		29	54.1	65.8			
62		117G			110	105	7		37	55.1	66.8			
63	122552	117H			110	105	8		45	56.1	67.8			
64		117I			110	105	9		5	57.1	68.8			
65		117J			110	105	10		13	58.1	69.8			
66		117K			110	105	11		21	59.1	70.8			
67		117L			110	105	12		29	60.1	71.8			
68		117M			110	105	13		37	61.1	72.8			
69		117N			110	105	14		45	62.1	73.8			
70		117O			110	105	15		5	63.1	74.8			
71		117P			110	105	16	25	13	64.1	75.8			
72		117Q			110	105	17		21	65.1	76.8			
73		117R			110	105	18		29	66.1	77.8			

REMARKS:

\*REC 101 TO REC 110 DAILY TESTS

\*REC 111, 112, REC 113 T.B. TESTS

INST 53.4 & 53.5. TR 40 1/2 GRP

INST 59.4 & 59.5 " 34 " "

" 26 " " "

" 18 " " "

" 10 " " "

" 2 " " "

END OF TAPE

5 SEC. ALL ONES

INST 65.4 & 65.5

INST 71.4 & 71.5

\*SKIP REC 132 \*



# LAND SEISMIC RECORDING LOG

Page #1 of 2



	CLIENT: <b>Husky</b>	PROJECT: <b>Southern Foot Hills</b>	AREA: <b>NPR-A ALASKA</b>	LINE NO.: <b>603</b>			
	PARTY NO.: <b>1186</b>	INST. ENG.: <b>KEDE - PANKO</b>	<b>LEAVE BASE - 7:00 AM</b>	<b>ARRIVE BASE - 8:00 PM</b>	DATE: <b>1 DAY 12 79</b>		
INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-28 & 49-96	ODDS TYPE <input type="checkbox"/> ODS III <input type="checkbox"/> ODS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 350 BPI (11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 1000 BPI
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS:	DATA CHANNEL NOS:		AUXILIARY DATA:			
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 7 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL	FILTERS: FREQ: <b>B</b> LO CUT: _____ HI CUT: _____			
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____	TRIP SENS: _____	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE THRESHOLD: _____		CORR. SCALING: _____	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>IN LINE</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____
RECEIVER	TYPE: <b>H.S.T 10 HZ</b>	PATTERN: <b>IN LINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: <b>600 20</b>	DIRECTION OF PROGRESSION: <b>EAST - WEST</b>		

DIAGRAMS/MISC. INFORMATION: **EAST S.P. WEST**  
**\*1 5170' \*48 55' \*55' \*49 5170' \*96**

SHOTPOINT	REEL NO.		REC.		SIZE		DEPTH		NO.	OFFSET	DIP	CDP SWITCH	SPREAD		MARKS	CORR STACK		
	1	2	1	2	1	2	1	2					1	2		3	4	5
81	722553		154		11.0	105	11		W	5	75.1	86.8	1	T.R. TEST.				
82			155		11.0	105	2			13	76.1	87.8		INST 83.4 & 83.5				
83			156		11.0	105	3	30'S		21	77.1	88.8						
84			157		11.0	105	4			29	78.1	89.8						
85			158		11.0	105	5			37	79.1	90.8						
86			159		11.0	105	6			45	80.1	91.8						
87			160		11.0	105	7			5	81.1	92.8	2	INST 89.4 & 89.5				
88			161		11.0	105	8			13	82.1	93.8						
89			162		11.0	105	9			21	83.1	94.8						
90			163		11.0	105	10	0.06'S		29	84.1	95.8						
91			164		11.0	105	11			37	85.1	96.8						
92			165		11.0	105	12			45	86.1	97.8						
93			166		11.0	105	13			5	87.1	98.8	3	INST 95.4 & 95.5				
94			167		11.0	105	14			13	88.1	99.8						
95			168		11.0	105	15			21	89.1	100.8						
96			169		11.0	105	16			29	90.1	101.8						
97			170		11.0	105	17			37	91.1	102.8		END OF TAPE				
98	722554		172		11.0	105	18			45	92.1	103.8		ALL ONES 5 SEC.				

# LAND SEISMIC RECORDING LOG

Page #2 of 2

	CLIENT: <b>Husky</b>	PROSPECT: <b>Southern Foot Hills</b>	AREA: <b>N.P.R.-A ALASKA</b>	LINE NO. <b>603</b>	
PARTY NO. <b>1186</b>		INST. ENG.		DATE: MO <b>1</b> DAY <b>12</b> YR <b>79</b>	
INSTRUMENT (9 TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS NO BYTES IN HEADER REC.		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS NO BYTES IN RECORD 10: NO BYTES PER SCAN:		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER <input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT GAIN CONSTANT: (1) (2) (3) (4) (5) (6) (7)	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS. DATA CHANNEL NOS.		AUXILIARY DATA: AUXILIARY CHANNEL NOS.		<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY: (10) <input type="checkbox"/> 354 BPI <input type="checkbox"/> 300 BPI (11) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
PARAMETER RECORD LENGTH: _____ INCH		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> 8 ms GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: _____ LO CUT _____ HZ SLOPE _____ HI CUT _____ HZ SLOPE _____ NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ dB		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE PRESSURE INCREASE ON GEOFHONE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
CFS I TYPE STACK:		GATE LENGTH: _____		NOISE REDUCTION: _____ CORR. SCALING: _____ <input type="checkbox"/> C.U. NORM./ALT SW	
SOURCE TYPE: <input type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: _____		NO. OF POSITIONS: _____ INLINE SPACING: _____ LATERAL SPACING: _____ STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____	
RECEIVER CONNECTION: _____		RESISTANCE: _____		STAGGER: _____ INLINE SPACING: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____	
SPREAD NO. OF GROUPS: _____		GROUP INTERVAL: _____		SHOTPOINT INTERVAL: _____ FOLD: _____ DIRECTION OF PROGRESSION: _____ LEADING GROUP: _____	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 20		SHOT		SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		LINE GROUPS	TR 1-20
100	72255A	177			110	105	10	10	INST 101.4 & 101.5		
101		178			110	105	20	10	F.S.D.D. FIRE PREMATURE NR. REC* 174 TO REC* 177 T.B. TESTS NO. W/PHONE		
102		180			110	105	22	10			
103		181			110	105	23	10			
104		182			110	105	24	10			
105		183			110	105	25	10			
106		184			110	105	26	10			
107		185			110	105	27	10			
108		186			110	105	28	10			
109		187			110	105	29	10			
110		188			110	105	30	10			
111		189			110	105	31	10			
112		190			110	105	32	10	INST 113.4 & 113.5		
113		191			110	105	33	10			
114		192			110	105	34	10			
115		193			110	105	35	10	WIND NOISE		
116		194			110	105	36	10	" "		



# LAND SEISMIC RECORDING LOG

Page #1 of 2

CLIENT: <b>Husky</b>		PROSPECT: <b>Southern Foothills</b>		AREA: <b>NPR-A ALASKA</b>		LINE NO: <b>603</b>	
PARTY NO: <b>1186</b>		INST. ENG: <b>DEGEDE-PANKO</b>		LEAVE BASE: <b>7:00 AM</b>		DATE: <b>MO 1 DAY 13 YR 79</b>	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		ODDS EVENS: <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS X <input type="checkbox"/> OTHER		TRACKS: <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
NO BYTES IN HEADER REC: <b>128</b>		NO BYTES IN RECORD ID: <b>254</b>		RECORD NUMBERS: <input checked="" type="checkbox"/> DEL. <input type="checkbox"/> OCT		GAIN CONSTANT: <b>36</b>	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS: <b>1-96</b>		DATA CHANNEL NOS: <b>1-96</b>		AUXILIARY DATA:	
PARAMETER: RECORD LENGTH: <b>8</b>		SAMPLE RATE: <input checked="" type="checkbox"/> 1 sec <input type="checkbox"/> 4 sec		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ: <b>8</b> LO CUT: <b>18</b> HI CUT: <b>72</b>	
DISPLAY: <input checked="" type="checkbox"/> MODE <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>40</b>		TRIP SENS: <b>45</b>		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	
CFS I: TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION: <input type="checkbox"/> NOISE THRESHOLD: <input type="checkbox"/> CORR. SCALING: <input type="checkbox"/> C.U. NORM/ALT SW	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>IN LINE</b>		NO. OF POSITIONS: <b>18</b>		INLINE SPACING: <b>7'</b>	
RECEIVER: TYPE: <b>H.S.T 10HZ</b>		PATTERN: <b>IN LINE</b>		NO. OF ELEMENTS: <b>18</b>		INLINE SPACING: <b>7'</b>	
CONNECTION: <b>SERIES PARALLEL</b>		RESISTANCE:		STAGGER:		LENGTH:	
SPREAD: NO. OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>48'</b>		SHOTPOINT INTERVAL: <b>55'</b>		FOLD: <b>5225'</b>	
OFFSET GROUP 1: <b>5225</b>		OFFSET GROUP: <b>48'</b>		OFFSET GROUP: <b>49'</b>		OFFSET GROUP: <b>5225'</b>	

DIAGRAMS/MISC. INFORMATION: **EAST #1 5170' "48 55' F 55' "49 5170' #96 WEST**

SHOTPOINT	TR 10		TR 10		SHOT		SPREAD		CORR STACK	
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO. OFFSET	DIP		
117	722555	205			11.0	105	1	W 5	111.1 122.8	REMARKS: <b>DAILY TESTS REC#196 TO REC#203</b> <b>REC#195 ALL ONES</b> <b>T.S. TEST</b> INST 119.4 d 119.5 TR #30-31 Noisy TR #22-23 Noisy TR #14-15 Noisy INST 125.4 d 125.5 TR #7 Noisy TR #34 Noisy TR #26 Noisy TR #18 Noisy INST 131.4 d 131.5 TR #39 Noisy 5 SEC. ALL ONES *N/A. UNABLE TO DISPLAY A RECORD SUSPECT BAD TAPE TAPE CHANGE
118		206			11.0	105	2	13	112.1 123.8	
119		207			11.0	105	3	21	113.1 124.8	
120		208			11.0	105	4	29	114.1 125.8	
121		209			11.0	105	5	37	115.1 126.8	
122		210			11.0	105	6	45	116.1 127.8	
123		211			11.0	105	7	5	117.1 128.8	
124		212			11.0	105	8	13	118.1 129.8	
125		213			11.0	105	9	21	119.1 130.8	
126		214			11.0	105	10	29	120.1 131.8	
127		215			11.0	105	11	37	121.1 132.8	
128		216			11.0	105	12	45	122.1 133.8	
129		217			11.0	105	13	5	123.1 134.8	
130		218			11.0	105	14	13	124.1 135.8	
131		219			11.0	105	15	21	125.1 136.8	
132		220			11.0	105	16	29	126.1 137.8	
133		221			11.0	105	17	37	127.1 138.8	
134	722556	223			11.0	105	18	45	128.1 139.8	

# LAND SEISMIC RECORDING LOG

Page #2 of 2.

	CLIENT: <b>Husky</b>	PROSPECT: <b># SOUTHERN FOOTHILLS</b>	AREA: <b>NPR-A ALASKA</b>	LINE NO: <b>603</b>							
	PARTY NO: <b>1186</b>	INST ENG:		DATE: <b>1 DAY 13 YE 79</b>							
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVFMS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input type="checkbox"/> DFS I <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: _____	<input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	<input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____	INPUT IMPEDANCE: _____				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: _____ DATA CHANNEL NOS: _____					AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS: _____					
PARAMETER	RECORD LENGTH: _____	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> 8 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____		LO CUT _____	HI CUT _____	NOISE FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____	TRIP SENS: _____	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
CFS I	TYPE: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____		NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM. 1/2 SW			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
RECEIVER	TYPE: _____	CONNECTION: _____	RESISTANCE: _____	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	OFFSET GROUP: _____	FOLD: _____	OFFSET GROUP 1: _____	OFFSET GROUP 2: _____	DIRECTION OF PROGRESSION: _____ LEADING GROUP: _____			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 11		SHOT		SPREAD		REMARKS	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR	COP SWITCH	LINE GROUPS	TR 10	TR 11
135	122556	227			1.10	105	19		W	5	129.1	140.8		
136		228			1.10	105	20			13	130.1	141.8		
137		229			1.10	105	21			21	131.1	142.8		
138		230			1.10	105	22			29	132.1	143.8		
139		231			1.10	105	23			37	133.1	144.8		
140		232			1.10	105	24			45	134.1	145.8		
141		233			1.10	105	25			5	135.1	146.8	5	INST 143.4 & 143.5
142		234			1.10	105	26			13	136.1	147.8		
143		235			1.10	105	27			21	137.1	148.8		#91 DEAD *92-*96 NOISY
144		236			1.10	105	28			29	138.1	149.8		#83 DEAD
145														WALK NO CAP LEADS
146		237			1.10	105	29			45	140.1	151.8		TR #1 NOISY
147		238			1.10	105	30			5	141.1	152.8	6	INST 149.4 & 149.5
148		239			1.10	105	31			13	142.1	153.8		CAT CAMP BETWEEN *153 & 154
149		240			1.10	105	32			21	143.1	154.8		
150		241			1.10	105	33			29	144.1	155.8		
151		242			1.10	105	34			37	145.1	156.8		
152		243			1.10	105	35			45	146.1	157.8		END OF TAPE

# LAND SEISMIC RECORDING LOG


Page #1 of 3.

CLIENT: <b>Husky</b>		PROSPECT: <b>Southern Foothills</b>		AREA: <b>NPR-A ALASKA</b>		LINE NO: <b>603</b>	
PARTY NO: <b>1186</b>		INST ENG: <b>DE REDE - PANKO</b>		LEAVE BASE <b>7:00 AM</b>		ARRIVE BASE <b>8:30</b>	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		ODDS: <input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 49-96		TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		TRACKS: <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
NO BYTES IN HEADER REC: <b>128</b>		NO BYTES IN RECORD ID:		NO BYTES PER SCAN: <b>254</b>		RECORD NUMBERS: <input checked="" type="checkbox"/> REC <input type="checkbox"/> OCT	
FIELD TRACE NOS: <b>1-96</b>		DATA CHANNEL NOS: <b>1-96</b>		AUXILIARY DATA:		AUXILIARY CHANNEL NOS:	
RECORD LENGTH: <b>B</b>		SAMPLE RATE:		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL		FILTERS:	
DISPLAY: <input type="checkbox"/> MODE <input type="checkbox"/> FLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN:		TRIP SENS:		POLARITY CONVENTION:	
CFS 1:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:	
SOURCE:		PATTERN: <b>IN LINE</b>		NO OF POSITIONS:		INLINE SPACING:	
RECEIVER:		TYPE: <b>H.S.T. 10HZ.</b>		CONNECTION: <b>SERIES PARALLEL</b>		RESISTANCE:	
SPREAD:		NO OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>110'</b>		SHOTPOINT INTERVAL: <b>880'</b>	
DIAGRAMS/MISC. INFORMATION:		EAST:		WEST:		DIRECTION OF PROGRESSION: <b>EAST-WEST</b>	

SHOTPOINT	TR		REC		SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	SPREAD		REMARKS	CORR STACK			
	REEL NO	REC.	REEL NO	REC.							LINE GROUPS	LINE GROUPS		1	2	3	4
	722558										*L	*96	REMARKS: <del>Rec #245 to Rec #253</del> DAILY TESTS Rec #244 IFF TEST * T.B. TEST				
153		255			110	105	1		W	5	147.1	158.8	INST 155.4 & 155.5				
154		256			110	105	2			13	148.1	159.8					
155		257			110	105	3			21	149.1	160.8					
156		258			110	105	4			29	150.1	161.8					
157		259			110	105	5			37	151.1	162.8					
158		260			110	105	6			45	152.1	163.8					
159		261			110	105	7			5	153.1	164.8	INST 161.4 & 161.5				
160		262			110	105	8			9	154.1	165.8					
161		263			110	105	9			21	155.1	166.8	SPACE 91 noisy				
162		264			110	105	10			29	156.1	167.8	" 91-96 "				
163		265			110	105	11			37	157.1	168.8					
164		266			110	105	12			45	158.1	169.8	TRACE 97 dead				
165		267			110	105	13			5	159.1	170.8	INST 167.4 & 167.5				
166		268			110	105	14			13	160.1	171.8	#14 DEAD #32 & #68 Noisy				
167		269			110	105	15			21	161.1	172.8	#6 DEAD #60 Noisy				
168		270			110	105	16			29	162.1	173.8					
169		272			110	105	17			37	163.1	174.8	IFF TEST				

# LAND SEISMIC RECORDING LOG

Page #2 of 3



	CLIENT: <b>Husky</b>	PROSPECT: <b>Southern Hills</b>	AREA: <b>NPR-A ALASKA</b>	LINE NO: <b>603</b>									
	PARTY NO: <b>1186</b>	INST ENG:		DATE: <b>NOV 14 1979</b>									
INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> YES <input type="checkbox"/> NO	TYPE <input type="checkbox"/> DFC III <input type="checkbox"/> DFC IV <input type="checkbox"/> OTHER	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: _____	(10) <input type="checkbox"/> 350 BPI <input type="checkbox"/> 800 BPI	(11) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____	DATA CHANNEL NOS.: _____	[ON MAG TAPE]		AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____	AUXILIARY CHANNEL NOS.: _____							
PARAMETER	RECORD LENGTH: _____	SAMPLE RATE: <input type="checkbox"/> 1ms <input type="checkbox"/> 4ms <input type="checkbox"/> 2ms <input type="checkbox"/> _____	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	FREQ: _____	LO CUT HZ SLOPE: _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____	TRIP SENS.: _____	REC. REJECTION: _____	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____	FREQ. <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____			NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR SCALING: _____						
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____				
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____					
SPREAD	CONNECTION: _____	RESISTANCE: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	OFFSET GROUP: _____	OFFSET GROUP 48/96: _____							
DIAGRAMS/MISC. INFORMATION:													

SHOTPOINT	TR 10		TR 20		SHOT		SPREAD		REMARKS	CORR. STAGE			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR	COP SWITCH	#1	LINE GROUPS
170	72255	273			110	105	18	35	W	45	164.1	175.83	
171		274			110	105	19			5	165.1	176.84	
172		275			110	105	20			13	166.1	177.8	INST 173.4 & 173.5
173		276			110	105	21			21	167.1	178.9	
174		277			110	105	22			29	168.1	179.9	
175		278			110	105	23			37	169.1	180.8	
176		279			110	105	24			45	170.1	181.8	
177		280			110	105	25			5	171.1	182.8	5 INST 179.4 & 179.5
178		281			110	105	26			13	172.1	183.8	
179		282			110	105	27			21	173.1	184.8	
180		284			110	105	28			29	174.1	185.8	MISFIRE*
181		285			110	105	29			37	175.1	186.8	S.D.S. 55 MILS.
182		287			110	105	30			45	176.1	187.8	REC 285 T.B. TEST*
183		286			110	105	31			5	177.1	188.8	
184		289			110	105	32			13	178.1	189.8	6 INST 185.4 & 185.5
185		290			110	105	33			21	179.1	190.8	
186		291			110	105	34			29	180.1	191.8	
187		292			110	105	35			37	181.1	192.8	
188		293			110	105	36			45	182.1	193.8	



# LAND SEISMIC RECORDING LOG

Page #3 of 3

	CLIENT: <u>Husky</u>	PROSPECT: <u>Southern Hills</u>	AREA: <u>APR-A ALASKA</u>	LINE NO.: <u>603</u>						
PARTY NO.: <u>1196</u>		INST. ENG.:		DATE: <u>1 DAY 14 79</u>						
INSTRUMENT (9 TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 7-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEC	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(L) <input type="checkbox"/> 350 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			INPUT IMPEDANCE: _____ ohms			
PARAMETER	DATA CHANNEL NOS.:			AUXILIARY CHANNEL NOS.:						
DISPLAY	RECORD LENGTH: _____ sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> _____ ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL	FILTERS: _____	LO CUT HZ SLOPE	H CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
CFS I	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	RECORD REJECTION:	POLARITY CONVENTION: PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY			
SOURCE	TYPE: <input type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	CONNECTION:	RESISTANCE:	CHG/ MOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	OFFSET GROUP 1:	OFFSET GROUP _____:	OFFSET GROUP 48/96:	DIRECTION OF PROGRESSION:		LEADING GROUP:	


DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 20		SHOT			SPREAD		REMARKS	CORR STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR	CDP SWITCH		LINE GROUPS	TR 1-48	TR 49-96
189	1225	294			110	105	37	W	5	183.1	194.8		
190		295			110	105	38		13	184.1	195.8		
191		297			110	105	39		21	185.1	196.8		
192		298			110	106	40		29	186.1	197.8		
193		299			110	106	41		37	187.1	198.8		
194		300			110	105	42		45	188.1	199.8		

Inst. 191.4 + 191.5 TR 1 DEAD  
L222 NOISE  
MISFIRE \*

# LAND SEISMIC RECORDING LOG

PAGE #1 OF 2

	CLIENT: <b>Husky</b>	PROSPECT: <b>SOUTHERN FOOTHILLS</b>	AREA: <b>N.P.P.-A ALASKA</b>	LINE NO. <b>603</b>									
	PARTY NO. <b>1186</b>	INST. ENG. <b>DELENE - PANKO</b>	ARRIVE BASE <b>7:00 AM</b>	DATE: <b>MO 1 DAY 15 YR 79</b>									
INSTRUMENT		NO. BYTES IN HEADER REC: <b>128</b>		NO. BYTES IN RECORD ID: <b>254</b>		NO. BYTES PER SCAN: <b>254</b>		RECORD NUMBERS: <b>DEC</b>		GAIN CONSTANT: <b>36</b> db		INPUT IMPEDANCE: <b>20,000</b> ohms	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: <b>1-96</b>		DATA CHANNEL NOS.: <b>1-96</b>		AUXILIARY CHANNEL NOS.:		FREQ. <b>8</b>		LO CUT HZ SLOPE <b>18</b>		HI CUT HZ SLOPE <b>72</b>	
PARAMETER		RECORD LENGTH: <b>8</b> sec		SAMPLE RATE: <input type="checkbox"/> 1 sec <input type="checkbox"/> 4 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS:		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER		INITIAL GAIN: _____ db		TRIP SENS.: _____ db		NOISE REDUCTION:		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NOISE THRESHOLD: _____		CORR. SCALING: _____	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>IN LINE</b>		NO. OF POSITIONS: _____		INLINE SPACING: _____		LATERAL SPACING: _____		STAGGER: _____	
RECEIVER		TYPE: <b>H.S.T. 10 HZ</b>		PATTERN: <b>IN LINE</b>		NO. OF ELEMENTS: <b>18</b>		SWEEP START: _____		SWEEP END: _____		SWEEP TAPER: _____	
SPREAD		NO. OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>110'</b>		SHOTPOINT INTERVAL: <b>220'</b>		FOLD: <b>600</b>		DIRECTION OF PROGRESSION: <b>EAST-WEST</b>		LEADING GROUP: <b>96</b>	

DIAGRAMS/MISC. INFORMATION: **EAST** **SP.** **WEST**  
**#1 5170' #48 55' F 55' #49 5170' #96**

SHOTPOINT	TR NO		TR NO		SHOT		SPREAD		REMARKS	CORR. STACK			
	REL NO	REC	REL NO	REC	SIZE	DEPTH	NO.	OFFSET		DIR	COP SWITCH	LINE GROUPS	TR 41
195	722558	310			110	105	1		W	5	189.1 200.8		
196		311			110	105	2			13	190.1 201.8		
197		312			110	105	3			21	191.1 202.8		
198		313			110	105	4			29	192.1 203.8		
199		314			110	105	5			37	193.1 204.8		
200		315			110	105	6			45	194.1 205.8		
201		316			110	105	7	35'E		5	195.1 206.8		
202		317			110	105	8			13	196.1 207.8		
203		318			110	105	9			21	197.1 208.8		
204		319			110	105	10			29	198.1 209.8		
205	722559												
206		322			110	105	11	25'E		37	199.1 210.8		
207		323			110	105	12			45	200.1 211.8		
208		324			110	105	13			5	201.1 212.8		
209		325			110	105	14			13	202.1 213.8		
210		326			110	105	15			21	203.1 214.8		
211		327			110	105	16			29	204.1 215.8		
212		328			110	105	17			37	205.1 216.8		
					110	105	18			45	206.1 217.8		

**DAILY TESTS REC 301 TO REC 308**

**T.R. TEST**

**INST 197.4 & 197.5 NO UPHOLE & MISTY**

**NO UPHOLE, PTO OR REP TB. SAME ON 195**

**INST 203.4 & 203.5 NO PTO**

**END OF TAPE NO PTO**

**I.F.P. TEST**

**NO PTO**

**NO PTO**

**INST 209.4 & 209.5 NO PTO**

**MONITOR?**

# LAND SEISMIC RECORDING LOG

Page # 2 of 2

	CLIENT: <b>Husky</b>	PROSPECT: <b>NER - Southern Foothills</b>	AREA: <b>NER-A ALASKA</b>
	PARTY NO.: <b>1186</b>	INST. ENG.:	LINE NO.: <b>603</b>
			DATE: <b>MO 1 DAY 15 YR 79</b>
INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-40 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS
(9-TRACK)	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID	NO. BYTES PER SCAN
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.	DATA CHANNEL NOS.	AUXILIARY DATA
PARAMETER	RECORD LENGTH	SAMPLE RATE	GAIN MODE
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> OTHER	INITIAL GAIN	TRIP SENS.
CFS 1	TYPE STACK	GATE LENGTH	RECORD REJECTION
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN	NO. OF POSITIONS
RECEIVER	TYPE	PATTERN	NO. OF ELEMENTS
SPREAD	NO. OF GROUPS	GROUP INTERVAL	SHOTPOINT INTERVAL

SHOTPOINT	TR		TR		SHOT		SPREAD		REMARKS	CORR STACK						
	PEEL NO.	REC.	PEEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR	CDP SWITCH	LINE GROUPS	NO.	TR 1-20	TR 21-40	TR 41-60
213	222560	329			110	105	19		W	5	207.1	218.0	4			
214		330			110	105	20			13	208.1	219.0				
215		331			110	105	21			21	209.1	220.8				
216		332			110	105	22			29	210.1	221.8				
217		333			110	105	23			37	211.1	222.8				
218		334			110	105	24			45	212.1	223.8				
219		335			110	105	25			5	213.1	224.8	5			
220		336			110	105	26			13	214.1	225.8				
221		337			110	105	27			21	215.1	226.8				
222		338			110	105	28	100' N		29	216.1	227.8				
223		339			110	105	29			37	217.1	228.8				
224		340			110	105	30			45	218.1	229.8				
225		341			110	105	31			5	219.1	230.8	6			
226		342			110	105	32			13	220.1	231.8				
227		343			110	105	33			21	221.1	232.8				
228		344			110	105	34			29	222.1	233.8				
229		345			110	105	35			37	223.1	234.8				
230		346			110	106	36			45	224.1	235.8				

Inst. 215.4 & 215.5 No FTB

NO FIB # 6 BAD

INST 221.4 & 221.5 TR 19 NOISY

TR 86 NOISY REPLANTED BUT

GEOPHONES ARE IN ROCKS

OFFSET 150' WEST 25' SOUTH

INST 227.4 & 227.5

OFFSET 30' W 25' N

\* Slow going TODAY DUE TO Hilly & Rough TERRAIN

# LAND SEISMIC RECORDING LOG Page 1 of 2

	CLIENT: <b>Husky</b>	PROSPECT: <b>SOUTHERN FOOTHILLS</b>	AREA: <b>NPR-A ALASKA</b>	LINE NO: <b>603</b>	
PARTY NO: <b>1186</b>		INST. ENG: <b>DECEDE - PANKO</b>		DATE: <b>1 DAY 16 YR 79</b>	
INSTRUMENT (9-TRACK): <b>128</b>		LEAVE BASE <b>7:00 AM</b>		ARRIVE BASE <b>9:00 PM</b>	
NO. BYTES IN HEADER REC: <b>128</b>		NO. BYTES IN RECORD ID: <b>254</b>		RECORD NUMBERS: <b>DEC</b>	
CONFIGURATION (MAG TAPE): <b>1-96</b>		DATA CHANNEL NOS: <b>1-96</b>		AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)	
PARAMETER: <b>8</b>		SAMPLE RATE: <b>1ms</b>		GAIN MODE: <b>INITIAL</b>	
DISPLAY: <b>MODE</b>		INITIAL GAIN: <b>46</b>		FILTERS: <b>FREQ 8</b>	
CF5 I: <b>TYPE STACK</b>		GATE LENGTH: <b>46</b>		POLARITY CONVENTION: <b>POSITIVE</b>	
SOURCE: <b>DYNAMITE</b>		PATTERN: <b>INLINE</b>		NOISE REDUCTION: <b>NOISE THRESHOLD</b>	
RECEIVER: <b>H.S.T 10 HZ</b>		NO. OF POSITIONS: <b>18</b>		SWEEP LENGTH: <b>7</b>	
SPREAD: <b>96</b>		GROUP INTERVAL: <b>110'</b>		FOLD: <b>600%</b>	
DIAGRAMS/MISC. INFORMATION: <b>EAST</b>		RESISTANCE: <b>IN LINE</b>		DIRECTION OF PROGRESSION: <b>EAST-WEST</b>	
		SP		LEADING GROUP: <b>96</b>	
		WEST			

SHOTPOINT	TR 1-10		TR 11-20		TR 21-30		TR 31-40		TR 41-50		TR 51-60		TR 61-70		TR 71-80		TR 81-90		TR 91-100		REMARKS	CORR STACK	
	REEL NO	REC	REEL NO	REC	SIZE	DEPTH	NO.	OFFSET	ENR	COP SWITCH	SPREAD		LINE GROUPS		CORR		STACK						
231	2256	357			110	105	1		W	5	225.1	236.8	1	96	DAILY TESTS Rec 347-Rec 355								
232		358			110	105	2			13	226.1	237.8	1		TEST T.B. INST. 233A & 235								
233		359			110	105	3			21	227.1	238.8			*34 Noisy								
234		360			110	105	4			29	228.1	239.8											
235		361			110	105	5			37	229.1	240.8											
236		362			110	105	6			45	230.1	241.8											
237		363			110	105	7			5	231.1	242.8	2		TRACE 34 dead								
238		364			110	105	8			13	232.1	243.8			" 26 "								
239		365			110	105	9			21	233.1	244.8			" 18 "								
240		366			110	105	10			29	234.1	245.8			" 10 "								
241		367			110	105	11			37	235.1	246.8			" 2 "								
242		368			110	105	12			45	236.1	247.8											
243	32256	370			110	105	13			5	237.1	248.8	3		CHANGE WIRE Inst. 245.4 + 245.5								
244		371			110	105	14			13	238.1	249.8											
245		372			110	105	15			21	239.1	250.8											
246		373			110	105	16			29	240.1	251.8											
247		374			110	105	17			37	241.1	252.8											
248		375			110	105	18			45	242.1	253.8			r32 noisy								



# LAND SEISMIC RECORDING LOG

Page 2 of 2

	CLIENT: <b>Husky</b>	PROSPECT: <b>Southern Foothills</b>	AREA: <b>NPR-A Alaska</b>	LINE NO: <b>603</b>						
	PARTY NO: <b>1186</b>	INST ENG:		DATE: <b>MO 1 DAY 16 YR 79</b>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(L0) <input type="checkbox"/> 336 BPI <input type="checkbox"/> 800 BPI	(H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO BYTES IN HEADER REC:	NO BYTES IN RECORD ID:	NO BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT:	db	INPUT IMPEDANCE:	ohms	(7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS:			
PARAMETER	RECORD LENGTH:	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> 7 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: FREQ	LD CUT HZ SLOPE	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AGC	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: db	ZIP SENS: db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE:	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBEAR <input type="checkbox"/> UPBEAR	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	CONNECTION:	RESISTANCE: ohms	CHG/ HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	OFFSET GROUP 1:	OFFSET GROUP 2:	SHOTPOINT INTERVAL:	OFFSET GROUP:	FOLD:	DIRECTION OF PROGRESSION:		
DIAGRAMS/MISC. INFORMATION:										

SHOTPOINT	TR 1		TR 2		SHOT				SPREAD		REMARKS	CORR STACK		
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO. OFFSET	DIR	COP SWITCH	LINE GROUPS		TR 1	TR 2	TR 3
249	222.5161	376			110	105.18		W	5	243.1 254.8	4			
250		377			110	105.20			13	244.1 255.8				
251		378			110	105.21			21	245.1 256.8				
252		379			110	105.22			29	246.1 257.8				
253		380			110	105.23			37	247.1 258.8				
254		381			110	105.24			45	248.1 259.8				
255		382			110	105.25			5	249.1 260.8	5			
256		383			110	105.26			13	250.1 261.8				
257		384			110	105.27			21	251.1 262.8				
258		385			110	105.28	200'E		29	252.1 263.8				
259		386			110	105.29	250'E		37	253.1 264.8				
260		387			110	105.30			45	254.1 265.8				
261		388			110	105.31			5	255.1 266.8	6			
262		389			110	105.32			13	256.1 267.8				
263		390			110	105.33			21	257.1 268.8				
264		391			110	105.34			29	258.1 269.8				
265		392			110	105.35			37	259.1 270.8				
266		393			110	105.36	275'E		45	260.1 271.8				

251.4 + 251.5 *Track No 16 noisy*

Inst 257.4 + 257.5

TR #92 noisy  
Inst 263.4 + 263.5

### LAND SEISMIC RECORDING LOG

CLIENT: <b>HUSKY</b>		PROSPECT: <b>SOUTHERN FOOT HILLS</b>		AREA: <b>N.P.P-A ALASKA</b>		LINE NO: <b>603</b>	
PARTY NO: <b>1186</b>		INST ENG: <b>NEREDE - PANKO</b>		LEAVE BASE <b>7:00 AM</b>		ARRIVE BASE <b>9:00 PM</b>	
DATE: <b>MO 1 DAY 17 YR 79</b>							
INSTRUMENT: <b>9-TRACK</b>		NO. BYTES IN HEADER REC: <b>128</b>		NO. BYTES IN RECORD ID: <b>254</b>		RECORD NUMBERS: <b>DEC</b>	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS: <b>1-96</b>		DATA CHANNEL NOS: <b>1-96</b>		AUXILIARY DATA:	
PARAMETER: <b>8</b>		SAMPLE RATE: <b>100</b>		GAIN MODE: <b>INITIAL</b>		FILTERS: <b>FREQ 8</b>	
DISPLAY: <b>AGC</b>		INITIAL GAIN: <b>48</b>		IRIP SENS: <b>48</b>		TO CUT HZ SLOPE: <b>18</b>	
CFS I: <b>TYPE STACK</b>		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:	
SOURCE: <b>DYNAMIC</b>		PATTERN: <b>IN LINE</b>		NO. OF POSITIONS: <b>18</b>		LATERAL SPACING: <b>7'</b>	
RECEIVER: <b>N.S.T 10HZ</b>		CONNECTION: <b>SERIES PARALLEL</b>		RESISTANCE: <b>110LB</b>		HOLE DEPTH: <b>105'</b>	
SPREAD: <b>96</b>		GROUP INTERVAL: <b>110'</b>		SHOTPOINT INTERVAL: <b>880'</b>		FOLD: <b>600</b>	
DIAGRAMS/MISC. INFORMATION: <b>EAST</b>		<b>#1 5170' #48 55' P 55' #49 5170' #96</b>		<b>WEST</b>			

SHOTPOINT	TR 1		TR 2		SHOT		SPREAD		CORR STACK				
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET					
2617	722562	404			110	105	1	W	5	281.1	272.8	1	DAILY TESTS Rec 394 To Rec 403
266		405			110	105	2	282.1	273.8				
269		406			110	105	3	283.1	274.8				
270		407			110	105	4	284.1	275.8				
271		408			110	105	5	285.1	276.8				
272		409			110	105	6	286.1	277.8				
273		410			110	105	7	287.1	278.8	2			Incl. 275.4 + 275.5
274		411			110	105	8	288.1	279.8				
275		412			110	105	9	289.1	280.8				
276		413			110	105	10	290.1	281.8				
277		414			110	105	11	291.1	282.8				
278		415			110	105	12	292.1	283.8				GROUP 96 Noise
279		416			110	105	13	293.1	284.8	3			Incl 291.4 + 291.5
280		417			110	105	14	294.1	285.8				
281	722562	418			110	105	15	295.1	286.8				FILE #418 IFR * TAPE CHANGE
282		420			110	105	16	297.1	287.8				
283		421			110	105	17	297.1	288.8				
284		422			110	105	18	298.1	289.8				
285		423			110	105	19	299.1	290.8	4			TRACE 96 Noise
286		424			110	105	20	299.1	291.8				Incl 287.4 + 287.5

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Huaky</b>	PROSPECT: <b>Southern Foothills</b>	AREA: <b>NPR-A ALASKA</b>	LINE NO.: <b>603</b>							
	PARTY NO.: <b>1186</b>	INST. ENG.:	<b>Page 2 of 2</b>	DATE: <b>NO 1 DAY 17 yr 79.</b>							
INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 7-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input type="checkbox"/> 8 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEC: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 350 BPI (11) <input type="checkbox"/> 772 BPI (12) <input type="checkbox"/> 800 BPI (13) <input type="checkbox"/> 1600 BPI	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____	INPUT IMPEDANCE: _____ ohms
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____ DATA CHANNEL NOS. _____			AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____							
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input type="checkbox"/> 1PP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT: _____ Hz HI SLOPE: _____	HIGH CUT: _____ Hz HI SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY				
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR SCALING: _____	R.C.U. NORM./ALT SW				
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	OFFSET GROUP 1: _____	OFFSET GROUP 2: _____	LEADING GROUP: _____			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT #	TR _____ to _____		TR _____ to _____		SHOT				SPREAD				REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH	LINE GROUPS			REV	TR 24	TR 48-96	TR 24
287	722562	425			110	105	21			21	281.1	292.8	4				
288		426			110	105	22			29	282.1	293.8					
289		427			110	105	23			37	283.1	294.8					
290		428			110	105	24			37	284.1	295.8	5	TRACE 93 dead			
291		429			110	105	25			41	285.1	296.8		289 inch 84 DEAD			
														EARLY DEAD			
														END LINE 603			