

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: Southern Foothills		AREA: NPR A ALASKA		LINE NO: 605			
PARTY NO: 1186		INST. ENG: DEWIDE - BANKO		LEAVE BASE 7:00 AM ARR. FIELD 9:13 AM		DATE: NOV 2 DAY 2 YR 79			
INSTRUMENT (9-TRACK)		<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX		<input type="checkbox"/> 2 TRACK <input type="checkbox"/> 21 TRACK	
NO. BYTES IN HEADER REC: 128		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 254		RECORD NUMBERS:		DEC. <input type="checkbox"/> OCT. <input type="checkbox"/>	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 1-96		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:	
PARAMETER		RECORD LENGTH: 0 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL		FILTERS:	
DISPLAY		MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT		INITIAL GAIN: db		TRIP SENS: db		POLARITY CONVENTION:	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE		PATTERN: Inline		NO. OF POSITIONS:		INLINE SPACING:	
RECEIVER		TYPE: Hst 104		PATTERN: INLINE		NO. OF ELEMENTS: 18		INLINE SPACING:	
SPREAD		NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'		FOLD: 12.5%	

DIAGRAMS/MISC. INFORMATION:

East #1 10,340 48 49 10,340 → 96 West

SHOTPOINT	TR 10		TR 20		SHOT		SPREAD		REMARKS	CORR STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR		CDP SWITCH	LINE GROUPS	TR 1-48
1100	1235	110			116	105	1	W	1	T-48	118.4	
1101		111			116	105	2		5	T-44	117.4	
1102		112			116	105	3		9	T-40	113.4	
1103		113			116	105	11		13	T-36	114.4	
1104		114			116	105	5		17	T-32	115.4	
1105		115			116	105	6		21	T-28	116.4	
1106		116			116	105	7		25	T-24	117.4	
1107		117			116	105	8		29	T-20	118.4	
1108		118			116	105	9		33	T-16	119.4	
1109		119			116	105	10		37	T-12	120.4	
1110		120			116	105	11		41	T-8	121.4	
1111		121			116	105	12		45	T-4	122.4	
1112		122			116	105	13		1	100.1	123.4	
1113		123			116	105	14		5	101.1	124.4	
1114		124			116	105	15		9	102.1	125.4	
1115		125			116	105	16		13	103.1	126.4	
1116		126			116	105	17		17	104.1	127.4	
1117		127			116	105	18		21	105.1	128.4	
1118		128			116	105	19		25	106.1	129.4	
1119		129			116	105	20		29	107.1	130.4	

TR 92 NOISY
 TR 7 BAD TR 17B WEAK
 WIND
 WIND?
 WIND NOISE?

MANY NOISE TRIPLES WIND

FILE # 1-9 DAILY TESTS

FILE # 24 MISFIRE #

LAND SEISMIC RECORDING LOG

Page 1

CLIENT: Husky		PROSPECT: Southern Foothills		AREA: NPR A ALASKA		LINE NO.: 605	
PARTY NO.: 1186		INST. ENG.: PANKO - DERUDE		Leve. BASE: 9:00 a.m.		DATE: MO 3 DAY 3 YR 79	
INSTRUMENT (9-TRACK)		NO. BYTES IN HEADER REC.: 129		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 254	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: 1-26		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:	
PARAMETER		RECORD LENGTH: 9 sec.		SAMPLE RATE: 1 ms. 2 ms. 4 ms.		GAIN MODE: INITIAL MANUAL OPERATE	
DISPLAY		MODE: FLOAT DEFLOAT AMPLIFIER DIRECT		INITIAL GAIN: db		TRIP SENS: db	
CFS 1		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:	
SOURCE		PATTERN: INLINE		NO. OF POSITIONS:		INLINE SPACING:	
RECEIVER		TYPE: H6L 10Ns		PATTERN: INLINE		NO. OF ELEMENTS: 18	
SPREAD		NO. OF GROUPS:		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 890'	

DIAGRAMS/MISC. INFORMATION:
 East #1 10,450 → 48 50 A 49 10,450 → 96 WEST

SHOTPOINT	TR. 10		TR. 10		SHOT		SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR. 10	TR. 10
129	228500	40			NR	108	1	112.1	135.4	1	
129		46			NR	108	2	113.1	136.4		
129		47			NR	108	3	114.1	137.4		
129		48			NR	108	4	115.1	138.4		
129		49			NR	108	5	116.1	139.4		
129		50			NR	108	6	117.1	140.4		
130		51			NR	108	7	118.1	141.4		
131		52			NR	108	8	119.1	142.4		
132		53			NR	108	9	120.1	143.4		
133		54			NR	108	10	121.1	144.4		
134		55			NR	108	11	122.1	145.4		
135		56			NR	108	12	123.1	146.4		
136	228578	58			NR	108	13	124.1	147.4	2	
137		59			NR	108	14	125.1	148.4		
138		60			NR	108	15	126.1	149.4		
139		61			NR	108	16	127.1	150.4		
140		62			NR	108	17	128.1	151.4		
141		63			NR	108	18	129.1	152.4		
142		64			NR	108	19	130.1	153.4		
143		65			NR	108	20	131.1	154.4		

*File #35-44 Daily Tests

*File 141.4-143.1 Tape Change File # 37 1502

LAND SEISMIC RECORDING LOG

Page 2 of

	CLIENT: <u>Husky</u>	PROSPECT: <u>Southern Foothills</u>	AREA: <u>APR-A Alaska</u>	LINE NO: <u>605</u>						
	PARTY NO: <u>1186</u>	INST. ENG:		DATE: <u>MO 2 DAY 03 YR 79</u>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: _____	(L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____	db	INPUT IMPEDANCE: _____	ohms	(7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: _____			AUXILIARY CHANNEL NOS.: _____			
PARAMETER	RECORD LENGTH: _____	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> ITP <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____	HZ SLOPE _____	H1 CUT _____	HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____	TRAP SENS: _____	db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORP SCALING: _____	R.C.U. NORM/ALT SW			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	CONNECTION: _____	RESISTANCE: _____	ohms	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				SPREAD				REMARKS	CORR. STACK			
	REEL NO.	REC.	PEEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			BY	TR	REEL	TR
1444	22R078	161			110	105	21		N	33	132.1	155.4					
1445		161			110	105	22			37	133.1	156.4					
1446		168			110	105	23			41	134.1	157.4					
1447		169			110	105	24			45	135.1	158.4					
1448		170			110	105	25			1	136.1	159.4	3	Inst. 154.1 & 153.4			
1449		171			110	105	26			5	137.1	160.4					
1450		172			110	105	27			9	138.1	161.4					
1451		173			110	105	28			13	139.1	162.4		Trace #29 dead			
1452		174			110	105	29			17	140.1	163.4					
1453		175			110	105	30			21	141.1	164.4					
1454		176			110	105	31			25	142.1	165.4					
1455		177			110	105	32			29	143.1	166.4		Trace #94 dead			
1456		178			110	105	33			33	144.1	167.4					
1457		179			110	105	34	70	W	37	145.1	168.4					
1458		180			110	105	35			41	146.1	169.4					
1459		181			110	105	36			45	147.1	170.4					

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: Southern foothills		AREA: NPR-A ALASKA		LINE NO: 605			
PARTY NO: 1186		INST. ENG: DEKIDE-BANKO		LEAVE BASE 7:00 PM		DATE: JUN 2 DAY 04 TR 79			
		ARR. FIELD 9:00 PM							
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		ODDS EVENS <input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX		<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK		FORMAT: SEG 15	
NO. BYTES IN HEADER REC: 128		NO. BYTES IN RECORD 10: _____		NO. BYTES PER SCAN: 254		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: 76 db	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 1-96		[ON MAG TAPE]		AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____			
PARAMETER RECORD LENGTH: 8 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ: 8 LO CUT HZ SLOPE 18		HI CUT HZ SLOPE 22 NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		TRIP SENS.: _____ db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS DN <input type="checkbox"/> UPBREAK ON DISPLAY	
CFS I TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____		NOISE THRESHOLD: _____	
SOURCE TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: INLINE		NO. OF POSITIONS: _____		INLINE SPACING: _____		LATERAL SPACING: _____	
CONNECTION: SERIES		RESISTANCE: _____ ohms		SWEEP POSITION: _____		SWEEP START: _____		SWEEP END: _____	
RECEIVER TYPE: HSE 1042		PATTERN: INLINE		NO. OF ELEMENTS: 18		INLINE SPACING: _____		LATERAL SPACING: _____	
SPREAD NO. OF GROUPS: _____		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 980'		FOLD: 120%		DIRECTION OF PROGRESSION: WEST	
OFFSET GROUP 1: 16,450		OFFSET GROUP 48, 110'		OFFSET GROUP 49, 110'		OFFSET GROUP 49/96: 16,450		LEADING GROUP: 96	

DIAGRAMS/MISC. INFORMATION:

East #1 10,340 → 48 ⁵⁹ 49 10,390 → 96 * WEST

SHOTPOINT	TR 1-20		TR 21-40		SHOT		SPREAD		REMARKS	CORR STACK				
	REF. NO.	REC.	REF. NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH	LINE GROUPS	TR 1-20	TR 21-40
11601	2225 118	911	2223	26	NR	195	1	11	N	1	149.1	171.4		
11602		912			NR	195	2	11		5	149.1	172.4		
11603		913			NR	195	3	11		9	150.1	173.4		
11604		914			NR	195	4	11		13	151.1	174.4		
11605		915			NR	195	5	11		17	152.1	175.4		
11606		916			NR	195	6	11		21	153.1	176.4		
11607		917			NR	195	7	11		25	154.1	177.4		
11608		918			NR	195	8	11		29	155.1	178.4		
11609		919			NR	195	9	11		33	156.1	179.4		
11610		920			NR	195	10	11		37	157.1	180.4		
11701		101			NR	195	11	11		41	159.1	181.4		
11702		102			NR	195	12	11		45	159.1	182.4		
11703		103			NR	195	13	11		1	160.1	183.4		
11704	2225 118	104			NR	195	14	11		5	161.1	184.4		
11705		105			NR	195	15	11		9	162.1	185.4		
11706		106			NR	195	16	11		13	163.1	186.4		
11707		107			NR	195	17	11		17	164.1	187.4		
11708		108			NR	195	18	11		21	165.1	188.4		
11709		109			NR	195	19	11		25	166.1	189.4		
11710		110			NR	195	20	11		29	167.1	190.4		

F. 16 # 82-90 Daily Tests

1-48 SLASHED - JWC CREW

T 29, 31 NOISY
TR, 8, 9, 26 NOISY AFTER # SEC.

TAPE CHANGE FILE # 104 JFC

1-48 SLASHED @ 2700 JWC CREW

LAND SEISMIC RECORDING LOG

CLIENT: <u>Husky</u>		PROSPECT: <u>Southern Foothills</u>		AREA: <u>NPR-A Alaska</u>		LINE NO.: <u>605</u>			
PARTY NO.: <u>1186</u>		INST. ENG.:		DATE: <u>MO 2 DAY 24 YE 79</u>					
INSTRUMENT		<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS & EVENS <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II		<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK <input type="checkbox"/> 21 TRACK		FORMAT: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED <input type="checkbox"/> PACKING DENSITY: (L) <input type="checkbox"/> 358 BPI (M) <input type="checkbox"/> 712 BPI (H) <input type="checkbox"/> 1424 BPI	
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS:		GAIN CONSTANT: (1) (2) (3) (4) (5) (6) (7)	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.:		DATA CHANNEL NOS.:		AUXILIARY DATA:			
PARAMETER		RECORD LENGTH: _____ sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: LO CUT HI CUT NOTCH FILTER IN OUT	
DISPLAY		MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		TRIP SENS: _____ db		POLARITY CONVENTION: PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION: NOISE THRESHOLD: CORR SCALING: F.C.U. NORM/ALT SW.	
SOURCE		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN:		NO. OF POSITIONS:		LATERAL SPACING:	
RECEIVER		TYPE:		PATTERN:		NO. OF ELEMENTS:		LATERAL SPACING:	
SPREAD		NO. OF GROUPS:		GROUP INTERVAL:		SHOTPOINT INTERVAL:		FOLD:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. to		TR. to		SHOT		SPREAD		REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		CDP SWITCH	LINE GROUPS		TR 48-50
180	1182	118			110	105	31	W	33	168.1	191.4		
181		118			110	105	22		37	169.1	192.4		
182		118			110	105	23		41	170.1	193.4		
183		118			110	105	24		45	171.1	194.4		
184		118			110	105	25		1	172.1	195.4	3	Insl 188.4 + 190.1
185		118			110	105	26		5	173.1	196.4		
186		118			110	105	27		9	174.1	197.4		
187		118			110	105	28		13	175.1	198.4		
188		120			110	105	29		17	176.1	199.4		
189		121			110	105	30		21	177.1	200.4		
190		122			110	105	31		25	178.1	201.4		
191		123			110	105	32		29	179.1	202.4		
192		124			110	105	33		33	180.1	203.4		
193		125			110	105	34		37	181.1	204.4		
194		126			110	105	35		41	182.1	205.4		
195		127			110	105	36		45	183.1	206.4		TR 82 DEAD



LAND SEISMIC RECORDING LOG

CLIENT: <u>Husky</u>		PROSPECT: <u>Southern foothills</u>		AREA: <u>NPR-A Alaska</u>		LINE NO: <u>605</u>													
PARTY NO: <u>1186</u>		INST. ENG.: <u>Bnk. - DEREDE</u>		LEAVE BASE: <u>2:00 P.M.</u>		DATE: <u>MO 4 DAY 05 YR 79</u>		ARR. BASE: <u>3:10 P.M.</u>											
INSTRUMENT (9-TRACK)		<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		ODDS: <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> ODS <input type="checkbox"/> ODS II <input type="checkbox"/> ODS III <input type="checkbox"/> OTHER		<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK		FOP/PAI: <u>SEG 18</u>		<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI (H2) <input type="checkbox"/> 1400 BPI					
NO. BYTES IN HEADER REC: <u>128</u>		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: <u>254</u>		RECORD NUMBERS:		<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: <u>36</u> db		INPUT IMPEDANCE: <u>25,000</u> ohms.		(1) (2) (3) (4) (5) (6) (7)					
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: <u>1-96</u>		DATA CHANNEL NOS.: <u>1-96</u>		(ON MAG TAPE)		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:		(1) (2) (3) (4) (5) (6) (7)		(1) (2) (3) (4) (5) (6) (7)					
PARAMETER		RECORD LENGTH: <u>2</u> sec.		SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. <u>8</u>		LO CUT HZ SLOPE: <u>18</u>		HI CUT HZ SLOPE: <u>12</u>		INCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT					
DISPLAY		<input type="checkbox"/> MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <u>db</u>		TRIP SENS.: <u>db</u>		POLARITY CONVENTION:		PRESSURE INCREASE ON GEOPHONE:		<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE:		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> ON DISPLAY			
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM./ALT. SW.					
SOURCE		<input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>Inline</u>		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:	
RECEIVER		TYPE: <u>Hsc 1014</u>		PATTERN: <u>Inline</u>		NO. OF ELEMENTS: <u>18</u>		INLINE SPACING:		LATERAL SPACING:		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:	
SPREAD		NO. OF GROUPS:		GROUP INTERVAL: <u>200'</u>		SHOTPOINT INTERVAL: <u>880'</u>		FOLD: <u>110%</u>		DIRECTION OF REGRESSION: <u>West</u>		LEADING GROUP:		TRAILING GROUP:		GROUP: <u>96</u>			

DIAGRAMS/MISC. INFORMATION: SP N 49 10.340 → 96

SHOTPOINT	TR. 10		TR. 20		SHOT		SPREAD		REMARKS	CORR. STAGE			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR. 10
1996	722687	148			HLG	105	1	181.1	207.4	1	181.1		
1997		149			HLG	105	2	185.1	208.4				
1998		140			HLG	105	3	186.1	209.4				
1999		141			HLG	105	4	182.1	210.4				
2000		142			HLG	105	5	189.1	211.4				
2001		143			HLG	105	6	182.1	212.4				
2002		144			HLG	105	7	190.1	213.4				
2003		145			HLG	105	8	191.1	214.4				
2004		146			HLG	105	9	192.1	215.4				
2005		147			HLG	105	10	193.1	216.4				
2006		148			HLG	105	11	194.1	217.4				
2007		149			HLG	105	12	195.1	218.4				
2008		150			HLG	105	13	196.1	219.4	2	196.1		
2009		151			HLG	105	14	197.1	220.4				
2010		152			HLG	105	15	198.1	221.4				
2011	722680	153			HLG	105	16	199.1	222.4				
2012		155			HLG	105	17	200.1	223.4				
2013		156			HLG	105	18	201.1	224.4				
2014		157			HLG	105	19	202.1	225.4				
2015		158			HLG	105	20	203.1	226.4				

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>Southern Foothills</u>	AREA: <u>NPR-A ALASKA</u>	LINE NO: <u>605</u>					
	PARTY NO: <u>1186</u>	INST. ENG:		DATE: <u>MO. 2 DAY 05 YR 79</u>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVEN	TYPE: <input type="checkbox"/> DES III <input type="checkbox"/> DES II	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 350 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____			AUXILIARY DATA: _____			AUXILIARY CHANNEL NOS. _____		
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	H1 CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> LAGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____	NUMBERS ON MAG. TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	E.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	OFFSET GROUP 1: _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 10		TR. 20		SHOT		SPREAD		REMARKS	CORR STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS		HT.	TR. 48
216	225180	1657			11.0	165	21		W	33	204.1	227.4			
217		166			11.0	165	22			37	205.1	228.4			
218		161			11.0	165	23	400		41	206.1	229.4			
219		162			11.0	165	24			45	207.1	230.4			
220		163			11.0	165	25	35E		1	208.1	231.4	3	Inst, 225.4+226.1	
221		164			11.0	165	26			5	209.1	232.4			
222		165			11.0	165	27			9	210.1	233.4			
223		166			11.0	165	28			13	211.1	234.4			
224		167			11.0	165	29			17	212.1	235.4			
225		168			11.0	165	30			21	213.1	236.4			
226		169			11.0	165	31			25	214.1	237.4			
227		170			11.0	165	32			29	215.1	238.4			
228		171			11.0	165	33			33	216.1	239.4			
229		172			11.0	165	34			37	217.1	240.4			
230		173			11.0	165	35			41	218.1	241.4			
231		174			11.0	165	36			45	219.1	242.4			

SCANNED 1-45 - NOT 41-45
 Record blank due to scanner passing away
 1-48 SLASHED JUG CREW
 HOLE BASH SLASH AT FIRE

LAND SEISMIC RECORDING LOG



Page #1 of 2

CLIENT: Husky		PROSPECT: SOUTHERN FOOTHILLS		AREA: NPR-A ALASKA		LINE NO.: 605	
PARTY NO.: 1186		INST. ENG.: J. DEBEDE		LEAVE BASE: 7:00		DATE: NO. 2 DAY 6 YR 79	
ARRIVE FIELD: 10:00		ARRIVE BASE: 11:00		LEAVE FIELD: 8:50		ARRIVE FIELD: 8:50	
INSTRUMENT: <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		ODDS: <input type="checkbox"/> 25-45 <input type="checkbox"/> 45-60		EVEN: <input type="checkbox"/> 25-45 <input type="checkbox"/> 45-60		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V	
NO. BYTES IN HEADER REC.: 128		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: 254		RECORD NUMBERS: _____	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 1-96		AUXILIARY DATA: _____	
PARAMETER: RECORD LENGTH: 8 sec.		SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: _____	
DISPLAY: MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		TRIP SENS: _____ db		POLARITY CONVENTION: _____	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: IN LINE		NO. OF POSITIONS: _____		INLINE SPACING: _____	
RECEIVER: TYPE: H.S.T 10HZ.		PATTERN: IN LINE		NO. OF ELEMENTS: 18		INLINE SPACING: 15'	
SPREAD: NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'		FOLD: 1200²	

DIAGRAMS/MISC. INFORMATION: **EAST S.P. WEST**
#1 10340' *48 110' *110' *49 10340' *96

SHOTPOINT #	TR. TO		TR. TO		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR	CDP SWITCH	#1	#2
232	722580	186			110	105	1	110	W	1	220.1	243.4	1
233		187			110	105	2	110		5	221.1	244.4	
234		188			110	105	3	110	W	9	222.1	245.4	
235		189			110	105	4	110	S	13	223.1	246.4	
236		190			110	105	5	110	E	17	224.1	247.4	
237		191			110	105	6	110		21	225.1	248.4	
238		192			110	105	7	110		25	226.1	249.4	
239		193			110	105	8	110	E	29	227.1	250.4	
240		194			110	105	9	110		33	228.1	251.4	*96 NOISY
241		195			110	105	10	110	E	37	229.1	252.4	WAITING ON DRILLS.
242		196			110	105	11	110	E	41	230.1	253.4	120' OFFSET S. (1-32 SLASHED)
243		197			110	105	12	110	S	45	231.1	254.4	
244		198			110	105	13	110	S	1	232.1	255.4	2 TRIST 249.4 & 250.1
245		199			110	105	14	110		5	233.1	256.4	E.S.D.N. 470' M.L.S.
246		200			110	105	15	110		9	234.1	257.4	*REC*200 TO REC*203 TEST T.B.
247		201			110	105	16	110		13	235.1	258.4	
248		202			110	105	17	110		17	236.1	259.4	END OF TAPE

LAND SEISMIC RECORDING LOG Page #2 of 2

	CLIENT: Husky	PROSPECT: SOUTHERN FOOT HILLS	AREA: NPR-A ALASKA	LINE NO: 605						
PARTY NO: 1186		INST. ENG:		DATE: 2 DAY 6 YR 79						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS	TYPE: <input type="checkbox"/> DFS III	<input type="checkbox"/> DFS IV	<input type="checkbox"/> 5 TRACK	FORMAT: <input type="checkbox"/> GAPPED	PACKING DENSITY: (LD) <input type="checkbox"/> 856 BPI	(MI) <input type="checkbox"/> 712 BPI	
	<input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> EVENS	<input type="checkbox"/> DFS IV	<input type="checkbox"/> OTHER	<input type="checkbox"/> 21 TRACK	<input type="checkbox"/> UNGAPPED	<input type="checkbox"/> 800 BPI	<input type="checkbox"/> 1600 BPI	
NO. BYTES IN HEADER REC:			NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC.	<input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	
CONFIGURATION (MAG TAPE)					AUXILIARY DATA:					
FIELD TRACE NOS.:					AUXILIARY CHANNEL NOS.:					
DATA CHANNEL NOS.:					(ON MAG TAPE)					
PARAMETER	RECORD LENGTH: _____ sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	FILTERS:		LO CUT HZ SLOPE	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE:		NUMBERS ON ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE:		HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	
RECEIVER	TYPE:		PATTERN:	NO. OF ELEMENTS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION:		RESISTANCE: _____ ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:					
	OFFSET GROUP 1:	OFFSET GROUP _____:	OFFSET GROUP _____:	OFFSET GROUP 48/96:	LEADING GROUP:					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				SPREAD				REMARKS:	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	* LINE GROUPS	* 9/16 SET		TR 1-48	TR 48-96	TR 96-144	TR 144-192
249	7258	208			1.10	1.05	18		2	21	237.1	260.4					
250		209			1.10	1.05	19		25	238.1	261.4						
251		210			1.10	1.05	20	100'E	29	239.1	262.4						
252		211			1.10	1.05	21	75'W	33	240.1	263.4						
253		212			1.10	1.05	22		37	241.1	264.4						
254		213			1.10	1.05	23		41	242.1	265.4						
255		214			1.10	1.05	24		45	243.1	266.4						

* K.P. loc # 2078
 (From S.P. 255 to S.P. 266 lucky TERRAIN)
 150' S.

LAND SEISMIC RECORDING LOG Page #1 of 2



CLIENT: Husky		PROSPECT: Southern Foot Hills		AREA: NPR-A ALASKA		LINE NO.: 605			
PARTY NO.: 1186		INST. ENG.: J. NERED		LEAVE FIELD: 7:00		ARRIVE FIELD: 9:00		DATE: NO. 2 DAY 7 YR 79	
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		DOGS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II		<input type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	
NO. BYTES IN HEADER REC: 128		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: 254		RECORD NUMBERS: DEC <input type="checkbox"/> OCT <input type="checkbox"/>		GAIN CONSTANT: 3.6 db	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: -96		DATA CHANNEL NOS.: -96		(ON MAG TAPE)		AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____			
PARAMETER RECORDED LENGTH: _____ sec.		SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL		FILTERS: FREQ. B		LO CUT HZ SLOPE 18	
DISPLAY MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		TRIP SENS: _____ db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____		NOISE THRESHOLD: _____	
SOURCE <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE HOLE		NO. OF POSITIONS: _____		INLINE SPACING: _____		LATERAL SPACING: _____	
RECEIVER TYPE: H.S.T 10 HZ		PATTERN: IN LINE		NO. OF ELEMENTS: 18		INLINE SPACING: 15'		LATERAL SPACING: _____	
SPREAD NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'		FOLD: 1200%		DIRECTION OF PROGRESSION: EAST → WEST	

DIAGRAMS/MISC. INFORMATION: **EAST** S.P. WEST.

*1 10340' *48 110' *49 10340' *96

SHOTPOINT #	TR 20		TR 10		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH	#1 LINE GROUPS	
256	2258	2274			110	105	1	110	1	244.1	267.4	INST 261.4 & 262.1	
257		2275			110	105	2	110	W	5	245.1	268.4	*LINE TRUCK BROKE DOWN
258		2276			110	105	3	110		9	246.1	269.4	2 HRS. THIS A.M.
259		2277			110	105	4	35	W	13	247.1	270.4	
260		2278			110	105	5	110		17	248.1	271.4	
261		2279			110	105	6	110		21	249.1	272.4	
262		2280			110	105	7	110		25	250.1	273.4	
263		2281			110	105	8	110		29	251.1	274.4	
264		2282			110	105	9	110		33	252.2	275.4	
265		2283			110	105	10	110		37	253.2	276.4	
266		2284			110	105	11	110		41	254.1	277.4	*96 DEAD
267		2285			110	105	12	110		45	255.1	278.4	From *278.4 - *280.1 Rocky TERRAIN
268		2286			110	105	13	110		1	256.1	279.4	INST 273.4 & 274.1
269		2287			110	105	14	110		5	257.1	280.4	
270		2288			110	105	15	110		9	258.1	281.4	*93 DEAD
271		2289			110	105	16	110		13	259.1	282.4	*89 DEAD
272		2290			110	105	17	110		17	260.1	283.4	*85 DEAD
273		2291			110	105	18	110		21	261.1	284.4	
274		2292			110	105	19	110		25	262.1	285.4	

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: Southern Foothills	AREA: NPR-A ALASKA	LINE NO: 605							
PARTY NO: 1186		INST. ENG:		DATE: M0 2 DAY 7 YR 79							
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> SEG <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI				
	NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			(1) (2) (3) (4) (5) (6) (7)				
PARAMETER	RECORD LENGTH: _____ sec.			SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.			GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> IFF <input type="checkbox"/> OPERATE	FILTERS: LO CUT _____ HZ SLOPE _____ HI CUT _____ HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	<input type="checkbox"/> MODE <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	<input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK:		GATE LENGTH:	RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:	CORR SCALING:	R.C.U. NORM/ALT SW.	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN:		NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	CONNECTION:		RESISTANCE: _____ ohms		STAGGER:		INLINE SPACING:		LATERAL SPACING:		
SPREAD	NO. OF GROUPS:		GROUP INTERVAL:		SHOTPOINT INTERVAL:		FOLD:		DIRECTION OF PROGRESSION:		
OFFSET GROUP 1:		OFFSET GROUP 2:		OFFSET GROUP 3:		OFFSET GROUP 4:		OFFSET GROUP 5:		LEADING GROUP:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT					SPREAD			REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	*1	LINE GROUPS		YR 79	YR 80	YR 81	YR 82
275	722581	243			11.0	1.05	21				29	263.1	286.4				
276	722581	244			11.0	1.05	21		35° E		33	264.1	287.4				
277		245			11.0	1.05	22				37	265.1	288.4				
278		246			11.0	1.05	23				41	266.1	289.4				
279		247			11.0	1.05	24				45	267.1	290.4				

LAND SEISMIC RECORDING LOG

Page 1 of 2

CLIENT: Husky		PROSPECT: Southern Foot Hills		AREA: NPR-A ALASKA		LINE NO: 605			
PARTY NO: 1186		INST. ENG: J. DELENE		LEAVE BASE: 7:00		LEAVE FIELD: 7:30		DATE: NO 2 DAY 8 TH 79	
ARRIVE FIELD: 8:30		ARRIVE BASE: 9:30		TRACK: <input checked="" type="checkbox"/> TRACK 1 <input type="checkbox"/> TRACK 2		FORMAT: B		GAPPED: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	
INSTRUMENT: 19-TRACK		NO. BYTES IN READER REC: 128		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 254		RECORD NUMBERS:	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: -96		DATA CHANNEL NOS.: -96		(ON MAG TAPE)		AUXILIARY DATA:	
PARAMETER		RECORD LENGTH: 8		SAMPLE RATE: <input type="checkbox"/> 1.0 <input type="checkbox"/> 4.0		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL		FILTERS:	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN:		TRIP SENS:		POLARITY CONVENTION:	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE HOLE		NO. OF POSITIONS:		LATERAL SPACING:	
RECEIVER		TYPE: H.S.T. 10HZ.		PATTERN: IN LINE		NO. OF ELEMENTS: 18		INLINE SPACING: 15'	
SPREAD		NO. OF GROUPS: 96		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'		FOLD: 1200%	
DIAGRAMS/MISC. INFORMATION: EAST		S.P.		WEST		#1 10340' *48 110' P 110' *49 10340' *96		LEADING GROUP: 96	

SHOTPOINT	TR 20		TR 10		SHOT		SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	DIR.			
280	2258	257			110	105	1	W	268.1	291.4	DAILY TESTS REC* 248 TO REC* 256 INST 285.4 & 286.1 * ONE LINE TRUCK BRAKE DOWN ALL DAY REC* 262 TEST *
281		258			110	105	2		269.1	292.4	
282		259			110	105	3		270.1	293.4	
283		260			110	105	4		271.1	294.4	
284		261			110	105	5		272.1	295.4	
285	22882	263	22882		110	105	6	W	273.1	296.4	
286		264			110	105	7		274.1	297.4	
287		265			110	105	8		275.1	298.4	
288		266			110	105	9		276.1	299.4	
289		267			110	105	10		277.1	300.4	
290		268			110	105	11	E	278.1	301.4	
291		269			110	105	12	E	279.1	302.4	
292		270			110	105	13	W	280.1	303.4	
293		271			110	105	14		281.1	304.4	
294		272			110	105	15	W	282.1	305.4	
295		273			110	105	16		283.1	306.4	
296		274			110	105	17		284.1	307.4	
297		275			110	105	18	W	285.1	308.4	
298		276			110	105	19		286.1	309.4	
299		277			110	105	20		287.1	310.4	

LAND SEISMIC RECORDING LOG

Page 2 of 2.

	CLIENT: Husky	PROSPECT: Southern Foothills	AREA: NPR-A ALASKA	LINE NO.: 605
	PARTY NO.: 1186	INST. ENG.:		DATE: NO. 2 DAY 8 YR 79
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:		AUXILIARY DATA:	
	DATA CHANNEL NOS.:		AUXILIARY CHANNEL NOS.:	
PARAMETER	RECORD LENGTH:	SAMPLE RATE: <input type="checkbox"/> 1ms. <input type="checkbox"/> 4ms <input type="checkbox"/> 2ms. <input type="checkbox"/> 8ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP	FILTERS: <input type="checkbox"/> LO CUT <input type="checkbox"/> HI CUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT	AMPLIFIER DIRECT	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:
RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INLINE SPACING:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	*1		LINE GROUPS	15	16	17	18
300	225	278			11.0	105	21	1.1		33	288.1	311.4					
301		279			11.0	105	22	1.1		37	289.1	312.4					
302		280			11.0	105	23	1.1		41	290.1	313.4					
303		281			11.0	105	24	1.1		45	291.1	314.4					
304		282			11.0	105	25	1.1		1	292.1	315.4	3	INST 309.4 & 310.1			
305		283			11.0	105	26	1.1		5	293.1	316.4					
306		284			11.0	105	27	1.1		9	294.1	317.4					
307		285			11.0	105	28	1.1		13	295.1	318.4					
308		286			11.0	105	29	1.1		17	296.1	319.4					
309		287			11.0	105	30	1.1		21	297.1	320.4					
310		288			11.0	105	31	1.1		25	298.1	321.4					
311		289			11.0	105	32	1.1		29	299.1	322.4					
312		292			11.0	105	33	1.1		33	300.1	323.4					
313		293			11.0	105	34	1.1		37	301.1	324.4					
314		294			11.0	105	35	1.1		41	302.1	325.4					
315		295			11.0	105	36	30 W		45	303.1	326.4					

LAND SEISMIC RECORDING LOG Page #1 of 3

		CLIENT: Husky	PROSPECT: Southern Foothills	AREA: NPR-A ALASKA	LINE NO: 605				
PARTY NO: 1186		INST. ENG: DeRene	LEAVE BASE: 7:00		LEAVE FIELD: 9:00		DATE: 2 DAY 9 YR 79		
NO. BYTES IN HEADER REC: 128		NO. BYTES IN RECORD ID: 1-96	NO. BYTES PER SCAN: 254	ARRIVE BASE: 8:30	ARRIVE FIELD: 16:00				
INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	<input type="checkbox"/> FOPMAT: SEG <input checked="" type="checkbox"/> B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (1) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI (10) <input type="checkbox"/> 800 BPI (17) <input type="checkbox"/> 1600 BPI	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA:					
PARAMETER	RECORD LENGTH: 8	SAMPLE RATE: <input type="checkbox"/> 1 sec <input checked="" type="checkbox"/> 2 sec	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: FREQ: 8 LO CUT: 18 HI CUT: 128 HZ SLOPE: 72 NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT					
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT	AMPLIFIER: <input type="checkbox"/> DIRECT	TRIP SENS: <input type="checkbox"/> 45	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE? <input type="checkbox"/> NEGATIVE } NUMBERS ON MAG. TAPE <input type="checkbox"/> POSITIVE } DOWNBREAK ON DISPLAY					
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: H.S.T 10HZ	PATTERN: IN LINE	NO. OF ELEMENTS: 18	INLINE SPACING: 15	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SNAPSHOT INTERVAL: 880'	FOLD: 1200%	DIRECTION OF PROGRESSION: EAST → WEST		LEADING GROUP: 96		

DIAGRAMS/MISC. INFORMATION: **EAST** #1 10340' #48 110' S.P. P 110' #49 10340' WEST #96

SHOTPOINT	TR. 10		TR. 10		SHOT		SPREAD		REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR		CDP SWITCH	*L	LINE GROUPS	*96
316	122582	305			110	105	1		1	304.1	327.4	1	
317		306			110	105	2		5	305.1	328.4		
318		307			110	105	3		9	306.1	329.4		
319		308			110	105	4	4530E	13	307.1	330.4		
320		309			110	105	5		17	308.1	331.4		
321		310			110	105	6		21	309.1	332.4		
322		311			110	105	7		25	310.1	333.4		
323	122583	313			110	105	8	180'S	311.1	324.4			
324		314			110	105	9		33	312.1	325.4		
325		315			110	105	10		37	313.1	326.4		
326		316			110	105	11		41	314.1	327.4		
327		317			110	105	12		45	315.1	328.4		
328		318			110	105	13		1	316.1	329.4	2	
329		319			110	105	14		5	317.1	330.4		
330		320			110	105	15		9	318.1	331.4		
331		321			110	105	16		13	319.1	332.4		
332		322			110	105	17		17	320.1	333.4		
333		323			110	105	18		21	321.1	334.4		
334		324			110	105	19		25	322.1	335.4		
335		325			110	105	20		29	323.1	336.4		

DAILY TEST REC 296 TO REC 304

END OF TAPE
REC 312 TEST

ST 346.1 Noisy Due To A Rocky Knoll

LAND SEISMIC RECORDING LOG

Page #2 of 3



CLIENT: Husky		PROSPECT: Southern Foothills		AREA: NPR-A ALASKA		LINE NO.: 605	
PARTY NO.: 1186		INST. ENG.:		DATE: MO 2 DAY 9 YR 79			
INSTRUMENT (9-TRACK)		NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.:		DATA CHANNEL NOS.:		[ON MAG TAPE]	
PARAMETER		RECORD LENGTH:		SAMPLE RATE:		GAIN MODE:	
DISPLAY		MODE:		INITIAL GAIN:		TRIP SENS:	
CFS I		TYPE STACK:		DATE LENGTH:		RECORD REJECTION:	
SOURCE		TYPE:		PATTERN:		NO. OF POSITIONS:	
RECEIVER		TYPE:		PATTERN:		NO. OF ELEMENTS:	
SPREAD		NO. OF GROUPS:		GROUP INTERVAL:		SHOTPOINT INTERVAL:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1-48		TR 49-96		SHOT		SPREAD		REMARKS	CORR STACK	
	TR	REC	TR	REC	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH
336	72758	326			11.0	109	21	336.1	347.4	2	*93 DEAD
337		327			11.0	109	22	325.1	348.4		*89 DEAD
338		328			11.0	109	23	326.1	349.4		*85 DEAD
339		329			11.0	109	24	327.1	350.4		
340		330			11.0	109	25	328.1	351.4	3	INST 344.2 & 344.3
341		331			11.0	109	26	329.1	352.4		
342		332			11.0	109	27	330.1	353.4	4	INST 347.2 & 347.3
343		333			11.0	109	28	331.1	354.4		*BASE CAMP 1/2 MILE OFF LINE BETWEEN S.P 354 & 355
344		334			11.0	109	29	332.1	355.4		
345		335			11.0	109	30	333.1	356.4		
346		336			11.0	109	31	334.1	357.4		
347		337			11.0	109	32	335.1	358.4		
348		338			11.0	109	33	336.1	359.4		*96 DEAD
349		339			11.0	109	34	337.1	360.4		*92 " FIRST PART OF TR 1 TO BE CONTINUED
350		340			11.0	109	35	338.1	361.4		
351		341			11.0	109	36	339.1	362.4		
352		342			11.0	109	37	340.1	363.4	5	INST 357.4 & 358.1
353		343			11.0	109	38	341.1	364.4		
354		344			11.0	109	39	342.1	365.4		
355		345			11.0	109	40	343.1	366.4		

(14) + 6 = 20

LAND SEISMIC RECORDING LOG Page #3 of 3

	CLIENT: <u>Husky</u>	PROSPECT: <u>SOUTHERN FOOTHILLS</u>	AREA: <u>NPR-A ALASKA</u>	LINE NO: <u>605</u>				
PARTY NO: <u>1186</u>		INST. ENG:		DATE: <u>2 9 79</u>				
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 732 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			DATA CHANNEL NOS.:	
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE	FREQ. _____	HI CUT HZ SLOPE
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db		POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE:	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:		NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
RECEIVER	CONNECTION:	RESISTANCE: _____ ohms	CHG/ HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	OFFSET GROUP 1:	OFFSET GROUP _____	LEADING GROUP:

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD				REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS	SEV UP		TR 1-24	TR 25-48	TR 49-96	REC.	
356	72583	346	17	22 23	26 27	28 29	30 31	32 33	34 35	36 37	17	344.1	367.4	732 NOISY				
357		347									21	345.1	368.4					
358		348									25	346.1	369.4					
359		349									29	347.1	370.4					
360		350									33	348.1	371.4					
361		351									37	349.1	372.4					
362		352									41	350.1	373.4					
363		353									45	351.1	374.4					

LAND SEISMIC RECORDING LOG

Page 1 of 2



	CLIENT: Husky	PROSPECT: SOUTHERN ESTIMES	AREA: NPP-A ALASKA	LINE NO: 605				
	PARTY NO: 1186	INST. ENG: NERBE	LEAVE BASE 7:00 ARRIVE FIELD 8:30	LEAVE FIELD 8:30 ARRIVE BASE 10:30	DATE: MO. 2 DAY 12 YR 79			
INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI 800 BPI (M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
CONFIGURATION (MAG TAPE)	NO. BYTES IN HEADER REC: 103	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 254	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 2000 ohms	(1) (2) (3) (4) (5) (6) (7)
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	FREQ. 128	HI CUT HZ SLOPE 12	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: db	TRIP SENS: db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE:	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
RECEIVER	TYPE: HST 1047	PATTERN: IN LINE	NO. OF ELEMENTS: 18	INLINE SPACING: 15'	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 225'	SHOTPOINT INTERVAL: 880'	FOLD: 1200%	DIRECTION OF PROGRESSION: EAST → WEST	OFFSET GROUP 1: 10450'	OFFSET GROUP 96: 10450'	LEADING GROUP: 96

DIAGRAMS/MISC. INFORMATION: EST
 *1 10450' *48 110' *99 10450' *96
 WEST

SHOTPOINT	TR. 10		TR. 10		SHOT		SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH	R.L. LINE GROUPS #96
364	722584	363			110	105	11		1	352.1	375.4	DAILY TESTS REC 354 TO REC 362
365		364			110	105	12		5	353.1	376.4	INST 369.4 & 370.1
366		365			110	105	13		9	354.1	377.4	SHOOTING TRUCK BROKE DOWN THIS A.M.
367		366			110	105	14		13	355.1	378.4	
368		367			110	105	15		17	356.1	379.4	
369		368			110	105	16		21	357.1	380.4	WAITING ON PRE LOADER
370		369			110	105	17		25	358.1	381.4	
371		370			110	105	18		29	359.1	382.4	
372		371			110	105	19		33	360.1	383.4	
373		372			110	105	20		37	361.1	384.4	
374		373			110	105	21		41	362.1	385.4	
375		374			110	105	22		45	363.1	386.4	
376		375			110	105	23		1	364.1	387.4	INST 381.4 & 382.1
377		376			110	105	24	110E	5	365.1	388.4	
378		377			110	105	25		9	366.1	389.4	
379		378			110	105	26		13	367.1	390.4	
380		379			110	105	27		17	368.1	391.4	
381		380			110	105	28		21	369.1	392.4	
382		381			110	105	29		25	370.1	393.4	
383		382			110	105	30		29	371.1	394.4	

LAND SEISMIC RECORDING LOG

PAGE 2 OF 2

	CLIENT: USKY	PROSPECT: SOUTHERN FOOTHILLS	AREA: NPR-A ALASKA	LINE NO: 605		
PARTY NO: 1186		INST. ENG:		DATE: MO 2 DAY 10 YR 79		
INSTRUMENT (P-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODS <input type="checkbox"/> EVENS <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED <input type="checkbox"/> PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (M) <input type="checkbox"/> 712 BPI (H) <input type="checkbox"/> 1600 BPI		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT. GAIN CONSTANT: _____ db INPUT IMPEDANCE: _____ ohms.	
	NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____			NO. BYTES PER SCAN: _____
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____		AUXILIARY DATA: _____		AUXILIARY CHANNEL NOS.: _____	
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____ HZ SLOPE	HI CUT _____ HZ SLOPE
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	CHG/HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD		REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH		LINE GROUPS	TR 1-48	REC.	TR 49-96	REC.
384	722584	383			1.10	1.0521				33	372.1	395A				
385		384			1.10	1.0522				37	373.1	396A				
386		385			1.10	1.0523	200	E		41	374.1	397A				
387		386			1.10	1.0524				45	375.1	398A				
388		387			1.10	1.0525				49	376.1	399A				
LINE TO BE CONTINUED AT A LATER DATE																

Ann's Copy

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: Southern Foothills		AREA: NPR-A ALASKA		LINE NO: 605A	
PARTY NO: 1186		INST. ENG: Hoss - Panke		DATE: MO 02 DAY 20 YR 79			
INSTRUMENT: <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		ODOS: <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER		TRACE: <input type="checkbox"/> 21 TRACK <input type="checkbox"/> 1 SEG	
NO. BYTES IN HEADER REC: 129		NO. BYTES IN RECORD ID: 254		NO. BYTES PER SCAN: 254		RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS: 1-96		DATA CHANNEL NOS: E86		(ON MAG TAPE)		AUXILIARY DATA: _____	
PARAMETER: RECORD LENGTH: 8 sec		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 2 sec		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ: 8 LO CUT HZ SLOPE: 18	
DISPLAY: MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		TRIP SENS: _____ db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I: TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____	
SOURCE: TYPE: <input type="checkbox"/> D-DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: In line (Spike Arr)		NO. OF POSITIONS: _____		INLINE SPACING: _____	
RECEIVER: TYPE: 10 Hz		CONNECTION: SERIES		RESISTANCE: _____ ohms		STAGGER: _____	
SPREAD: NO. OF GROUPS: _____		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'		FOLD: 1200%	
OFFSET GROUP 1: 10,450		OFFSET GROUP 48: 110'		OFFSET GROUP 49: 110'		OFFSET GROUP 48/96: 10,450	

DIAGRAMS/MISC. INFORMATION:
 1 ————— 10,340 —————> 48 ^{SP} 49 ————— 10,340 —————> 96

SHOTPOINT	TR. 10		TR. 10		SHOT		SPREAD		REMARKS	CORE STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS			
389	1122	596			1110	1025	11	11		1	477.1	400.4			
390					1110	1025	12	11		5	378.1	401.4			
391					1110	1025	13	11		9	379.1	402.4			
392					1110	1025	14	11		13	380.1	403.4			
393					1110	1025	15	11		17	381.1	404.4			
394					1110	1025	16	11		21	382.1	405.4			
395					1110	1025	17	11		25	383.1	406.4			
396					1110	1025	18	11		29	384.1	407.4			
397					1110	1025	19	11		33	385.1	408.4			
398					1110	1025	20	11		37	386.1	409.4			
399					1110	1025	21	11		41	387.1	410.4			
400					1110	1025	22	11		45	388.1	411.4			

REMARKS: **File # 1001 - Danny Panke**
~~File # 1001 - Danny Panke~~

LAND SEISMIC RECORDING LOG

CLIENT: <u>Husky</u>		PROSPECT: <u>Southern foothills</u>		AREA: <u>APR-A Alaska</u>		LINE NO: <u>605</u>			
PARTY NO: <u>1196</u>		INST. ENG: <u>Pinke-Loss</u>		DATE: <u>June Field 8:30 PM</u>		MO: <u>02</u> DAY: <u>21</u> YR: <u>79</u>			
INSTRUMENT (9-TRACK): <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS <input checked="" type="checkbox"/> DE <input type="checkbox"/> DFB <input type="checkbox"/> DFB <input type="checkbox"/> OTHER		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT		GAIN CONSTANT: <u>36</u> db		INPUT IMPEDANCE: <u>200</u> ohms	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS. <u>1-96</u>		DATA CHANNEL NOS. <u>1-96</u>		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:			
PARAMETER: RECORD LENGTH: <u>8</u> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. <u>9</u>		LO CUT HZ SLOPE: <u>18</u>	
DISPLAY: MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <u>46</u>		TRIP SENS.: <u>46</u>		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE:	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>Surface/inline</u>		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:	
RECEIVER: TYPE: <u>46 10Hz</u>		PATTERN: <u>Inline</u>		NO. OF ELEMENTS: <u>18</u>		INLINE SPACING:		LATERAL SPACING:	
SPREAD: NO. OF GROUPS: <u>10,450</u>		GROUP INTERVAL: <u>390'</u>		SHOTPOINT INTERVAL: <u>880'</u>		FOLD: <u>120%</u>		DIRECTION OF PROGRESSION: <u>West</u>	

DIAGRAMS/MISC. INFORMATION: 10,340 > 48 49 11,340 > 96

SHOTPOINT	TR 10		TR 20		SHOT			SPREAD		REMARKS	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 10	TR 20	TR 30	TR 40
4101	222986	33			110	105	1		1	389.1	412.4				
4102		34			110	105	2		5	390.1	413.4				
4103		35			110	105	3		9	391.1	414.4				
4104		36			110	105	4		13	392.1	415.4				
4105		37			110	105	5		17	393.1	416.4				
4106		38			110	105	6		21	394.1	417.4				
4107		39			110	105	7		25	395.1	418.4				
4108		30			110	105	8	80W	29	396.1	419.4				
4109		31			110	105	9		33	397.1	420.4				
4110		32			110	105	10		37	398.1	421.4				
4111		33			110	105	11	50S W	41	399.1	422.4				
4112		34			110	105	12		45	400.1	423.4				
4113		35			110	105	13		1	401.1	424.4				
4114		36			110	105	14		5	402.1	425.4				
4115		37			110	105	15		9	403.1	426.4				
4116		38			110	105	16		13	404.1	427.4				
4117		39			110	105	17		17	405.1	428.4				
4118		40			110	105	18		21	406.1	429.4				
4119		41			110	105	19		25	407.1	430.4				
4120		42			110	105	20		29	408.1	431.4				

REMARKS: FILE # 14-22 Railo Tests

REMARKS: NOT ON CABLE & Ocean Groups
CDP ERROR SET FOR SP 4110

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Muskyl</u>	PROSPECT: <u>Southern Foothills</u>	AREA: <u>NPR-A</u>	LINE NO.: <u>605</u>						
	PARTY NO.: <u>1186</u>	INST. ENG.:		DATE: <u>NO 2 DAY 21 YR 79</u>						
INSTRUMENT [9-TRACK]	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 350 BPI (11) <input type="checkbox"/> 800 BPI	(M) <input type="checkbox"/> 712 BPI (N) <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC. _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____			(ON MAG TAPE)						AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____ HZ SLOPE _____	HIGH CUT _____ HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE		<input type="checkbox"/> DOWNBREAK UPBREAK ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM / ALT SW.			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLO: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____	CORR. STAGE			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		YR _____ TO _____		SHOT			SPREAD		REMARKS	CORR. STAGE					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS	STAG.	REC.	DIR.	STAG.
421	222596	443			110	105	21			33	409.1	432.4				
422		444			110	105	22			37	410.1	433.4				
423		445			110	105	23			41	411.1	434.4				
424		446			110	105	24			45	412.1	435.4				
425	222597	447			110	105	25			1	413.1	436.4				
426		448			110	105	26			5	414.1	437.4				
427		449			110	105	27			9	415.1	438.4				
428		450			110	105	28			13	416.1	439.4				
429		451			110	105	29			17	417.1	440.4				
430		452			110	105	30			21	418.1	441.4				
431		453			110	105	31			25	419.1	442.4				
432		454			110	105	32			29	420.1	443.4				
433		455			110	105	33			33	421.1	444.4				
434		456			110	105	34			37	422.1	445.4				
435		457			110	105	35			41	423.1	446.4				
436		458			110	105	36			45	424.1	447.4				
437		459			110	105	37			1	425.1	448.4				
438		460			110	105	38			5	426.1	449.4				
439		461			110	105	39			9	427.1	450.4				
440		462			110	105	40			13	428.1	451.4				

T 94 DEAR
TAPE CHANGE FILE# 47 JFD.

LAND SEISMIC RECORDING LOG

	CLIENT: <i>Hasky</i>	PROSPECT: <i>Southern Foothills</i>	AREA: <i>NPR-A</i>	LINE NO: <i>605</i>						
	PARTY NO: <i>1186</i>	INST. ENG.:		DATE: <i>NO 2 DAY 21 YE 79</i>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.			
PARAMETER	RECORD LENGTH:	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	FILTERS: FREQ. LO CUT HZ SLOPE HI CUT HZ SLOPE			GAIN CONSTANT:		INPUT IMPEDANCE:	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN:	TRIP SENS:	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE			PRESSURE INCREASE ON GEOPHONE:		NUMBERS ON MAG. TAPE	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:			NOISE THRESHOLD:		CORR. SCALING:	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	CONNECTION:	RESISTANCE:	CHG/NOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	GROUP:	SHOTPOINT INTERVAL:	OFFSET GROUP:	FOLD:	OFFSET GROUP #/PB:	DIRECTION OF PROGRESSION:		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. to		TR. to		SHOT						SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIE	CDP SWITCH	LINE GROUPS	TR. 21		TR. 48	TR. 96	TR. 144	
441	7225	98	64	10	11.0	110.5	41	1	17	429.1	452.4						
442		65			11.0	110.5	42	1	21	430.1	453.4						
443		66			11.0	110.5	43	1	25	431.1	454.4						
444		67			11.0	110.5	44	1	29	432.1	455.4						
445		68			11.0	110.5	45	1	33	433.1	456.4						
446		69			11.0	110.5	46	1	37	434.1	457.4						
447		70			11.0	110.5	47	1	41	435.1	458.4						
448		71			11.0	110.5	48	1	45	436.1	459.4						

LAND SEISMIC RECORDING LOG

Page 1 of 4

		CLIENT: Husky	PROSPECT: Southern Foothills	AREA: NPR-A ALASKA	LINE NO.: 605				
PARTY NO. 1186		INST. ENG.: Panko-Loss	LEAVE BASE 7:00 A.M. ARR. FIELD 9:00 A.M.		LEAVE FIELD 0830 ARR. BASE 1000	DATE: MO 02 DAY 22 YR 79			
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	<input type="checkbox"/> TYPE <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input type="checkbox"/> DFS I <input type="checkbox"/> OTHER	<input type="checkbox"/> 1 TRACK <input checked="" type="checkbox"/> 2 TRACK	FORMAT: SEC - B <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 350 BPI (11) <input type="checkbox"/> 500 BPI (12) <input type="checkbox"/> 712 BPI (13) <input type="checkbox"/> 1000 BPI	
NO. BYTES IN HEADER REC. 128		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 254		RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db INPUT IMPEDANCE: 30,000 ohms	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. 1-96			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	DATA CHANNEL NOS. 1-96 (ON MAG TAPE)			RECORD LENGTH: 9 sec.					SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT			INITIAL GAIN: _____ db		JRP SENS: _____ db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I	TYPE STACK:			GATE LENGTH:		NOISE REDUCTION:		NOISE THRESHOLD: _____ CORR. SCALING: _____	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER			PATTERN: SINGLE (INLINE)		NO. OF POSITIONS: _____		INLINE SPACING: _____ LATERAL SPACING: _____	
RECEIVER	TYPE: Hot 10 Hz			PATTERN: INLINE		NO. OF ELEMENTS: 18		INLINE SPACING: _____ LATERAL SPACING: _____	
SPREAD	CONNECTION: SERIES			RESISTANCE: _____ ohms		STAGGER: _____		LATERAL SPACING: _____ WIDTH: _____	
NO. OF GROUPS: _____		GROUP INTERVAL: 90'		SHOTPOINT INTERVAL: 90'		FOLD: 1200%		DIRECTION OF PROGRESSION: West	
OFFSET GROUP 1: 10,450		OFFSET GROUP 48: 110'		OFFSET GROUP 92: 110'		OFFSET GROUP 48/96: 10,450		LEADING GROUP: 96	

DIAGRAMS/MISC. INFORMATION:
 East = 1 ————— 10,340' —————> 48# 110' A 110' 49' ————— 10,340' —————> 96 WEST

SHOTPOINT	TR 10		TR 10		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		COP SWITCH	LINE GROUPS		TR 1-48
4419	722587	178			110	105	12	1	437.1	460.4	1		
4450		179			110	105	12	5	438.1	461.4			
4451		175			110	105	13	9	437.1	462.4			
4452		176			110	105	14	13	440.1	463.4			
4453		177			110	105	15	17	441.1	464.4			
4454		178			110	105	16	21	442.1	465.4			
4455		179			110	105	17	25	443.1	466.4			
4456		180			110	105	18	29	444.1	467.4			
4457		181			110	105	19	33	445.1	468.4			
4458		182			110	105	20	37	446.1	469.4			
4459		183			110	105	21	41	447.1	470.4			
4460		184			110	105	22	45	448.1	471.4			
4461		185			110	105	23	1	449.1	472.4	2		
4462		186			110	105	24	5	450.1	473.4			
4463		187			110	105	25	9	451.1	474.4			
4464		188			110	105	26	13	452.1	475.4			
4465	72251918	190			110	105	27	17	453.1	476.4			
4466		191			110	105	28	21	454.1	477.4			
4467		192			110	105	29	25	455.1	478.4			
4468		193			110	105	30	29	456.1	479.4			


REMARKS: **7657. 78 File # 72**

TR 21 DEAD
 NO
 ↓
 TU

SP. (449-460) Low Cut Filter and

TYPE CHANGE
 File # 89 Dummy Rec

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROJECT: Southern Foothills	AREA: MPR-1A	LINE NO.: 605					
	PARTY NO.: 1186	INST. ENG.:		DATE: MO 2 DAY 22 YR 74					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 26-48 <input type="checkbox"/> 1-48 & 49-96	ORIG. EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEC	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 350 BPI <input type="checkbox"/> 800 BPI	(11) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____ HZ HZ SLOPE _____	FREQ. _____	H1 CUT _____ H2 SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEF/DAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORB. SCALING: _____	B.C.U. NORM./ALT SW		
SOURCE	TYPE: <input type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	CONNECTION: _____	PATTERN: _____	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL SPACING: _____	LATERAL OFFSET: _____	
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____		



DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 20		SHOT		SPREAD		REMARKS	CORR. SPACE					
	TR	NO.	TR	NO.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS		TR 1-48	TR 48-96
	REEL NO.	REC.	REEL NO.	REC.								111	112	113	114
4167	722	1598	194		110	1015	21		33	457.1	4180.4				
420		195			110	1015	22		37	458.1	422.4				
421		196			110	1015	23		41	459.1	427.4				
422		197			110	1015	24		45	460.1	432.4				
423		198			110	1015	25		1	461.1	437.4			3	
424		199			110	1015	26	1515 South	5	462.1	442.4				
425		100			110	1015	27	1615 4007	9	463.1	447.4				
426		101			110	1015	28		13	464.1	452.4				
427		102			110	1015	29		17	465.1	457.4				
428		103			110	1015	30		21	466.1	462.4				
429		104			110	1015	31		25	467.1	467.4				
430		105			110	1015	32		29	468.1	472.4				
431		106			110	1015	33		33	469.1	477.4				
432		107			110	1015	34		37	470.1	482.4				
433		108			110	1015	35		41	471.1	487.4				
434		109			110	1015	36	1705 4007	45	472.1	492.4				
435		110			110	1015	37		1	473.1	497.4			4	
436		111			110	1015	38		5	474.1	502.4				
437		112			110	1015	39		9	475.1	507.4				
438		113			110	1015	40		13	476.1	512.4				

97.2

20

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: Southern Foothills	AREA: NPR-A ALASKA	LINE NO: 605						
	PARTY NO: 1196	INST. ENG:		DATE: MO 02 DAY 22 YR 79						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: _____	<input type="checkbox"/> 350 BPI <input type="checkbox"/> 800 BPI	(M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____ DATA CHANNEL NOS. _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS. _____						
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input type="checkbox"/> IFP	FILTERS: FREQ. _____		LO CUT HZ SLOPE _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONES: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____		NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	LATERAL SPACING: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	OFFSET GROUP: _____	SHOTPOINT INTERVAL: _____	OFFSET GROUP: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____		TR _____		SHOT			SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIP	CDP SWITCH		LINE GROUPS	TR 1-41	TR 42-50	TR 51-59	TR 60-68
488	222	570	1119		110	105	41	W	17	477.1	520.4				
490			1115		110	105	42		21	478.1	501.4				
491			1116		110	105	43		25	479.1	502.4				
492			1117		110	105	44		29	480.1	503.4				
493			1118		110	105	45		33	481.1	504.4				
494			1119		110	105	46		37	482.1	505.4				
495			1120		110	105	47		41	483.1	506.4				
496			1121		110	105	48		45	484.1	507.4				

LAND SEISMIC RECORDING LOG

Page 1 of 2

		CLIENT: Husky	PROSPECT: Southern foothills	AREA: NPR-A Alaska	LINE NO.: 605		
PARTY NO.: 1186		INST. ENG.: BANKO		LEAVE BASE 7:00 AM.		DATE: MO 02 DAY 23 YR 79	
INSTRUMENT		NO. BYTES IN HEADER REC.: 128		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: 254	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 1-96		AUXILIARY DATA: _____	
PARAMETER		RECORD LENGTH: 8 sec		SAMPLE RATE: <input type="checkbox"/> 1 sec <input type="checkbox"/> 4 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	
DISPLAY		MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		TRIP SENS.: _____ db	
CFS I		TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: Single (E-W)		NO. OF POSITIONS: _____	
RECEIVER		TYPE: Net 100g		PATTERN: Inline		NO. OF ELEMENTS: 18	
SPREAD		CONNECTION: SERIES		RESISTANCE: _____ ohms		STAGGER: _____	
DIAGRAMS/MISC. INFORMATION:		NO. OF GROUPS: _____		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'	
OFFSET GROUP 1: 10,450		OFFSET GROUP 48: 110'		OFFSET GROUP 49: 110'		OFFSET GROUP 49/96: 10,450	

DIAGRAMS/MISC. INFORMATION:
 East **1-103340** → 48 **9** 49 → **10,340** → 96 WEST



SHOTPOINT	TR 1		TR 2		SHOT		SPREAD		REMARKS	CORE STACK					
	TR	REC.	TR	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-24	TR 25-48	TR 49-72
497	222598	132			110	105	1	11	W	1	485.1 508.4				
498		133			110	105	2	15	W	5	486.1 509.4				
499		133			110	105	3	20	90°N	9	487.1 510.4				
500		134			110	105	4	25	50°N	13	488.1 511.4				
501		135			110	105	5	30		17	489.1 512.4				
502		136			110	105	6	35		21	490.1 513.4				
503		137			110	105	7	40		25	491.1 514.4				
504	722599	137			110	105	8	45		29	492.1 515.4				
505		140			110	105	9	50		33	493.1 516.4				
506		141			110	105	10	55		37	494.1 517.4				
507		142			110	105	11	60		41	495.1 518.4				
508		143			110	105	12	65		45	496.1 519.4				
509		144			110	105	13	70		45	" "				
510		145			110	105	14	75		45	" "				
511		146			110	105	15	80		45	" "				
512		147			110	105	16	85		45	" "				
513		148			110	105	17	90		45	" "				
514		149			110	105	18	95		45	" "				
515		150			110	105	19	100		45	" "				
516		151			110	105	20	105	20°E	45	" "				

File # 122-130 Daily Test

Tape Change File # 138 during

LAST GP. W. BALANCED SPREAD.

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: Southern Foothills	AREA: NPR-A ALASKA	LINE NO: 605					
	PARTY NO: 1196	INST. ENG.		DATE: MO 02 DAY 23 YR 79					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> DFS XZ <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 354 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____			AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	FREQ. _____	HI CUT HZ SLOPE: _____	INDICH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	JIB SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./AIT SW: _____		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				DIE	COP SWITCH	SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET			LINE GROUPS	ST		TR 1-24	TR 25-48	TR 49-96	REC.
511.0	110	152	110	153	110	105	21	1	W	45	996.1	519.4					
518.0		153			110	105	22			45	"	"					
519.0		152			110	105	23			45	"	"					
520.0		153			110	105	24			45	"	"					
													End of line 605 lay out on line 630.				